PYTHON FOR DATA SCIENCE · LESSON 12 OF 29

Files, Exceptions, JSON and CSV

Read and write text, CSV and JSON files safely with pathlib and with-blocks, handle errors with try/except/else/finally, raise your own exceptions, and log what happened, using a small "load a messy file" project.

Python class 10 | Python 3.13 | Intermediate | 110 min

By the end of this lesson you can

- Open, read and write text files with with-blocks and pathlib
- Read and write CSV with the csv module and JSON with the json module
- Handle errors with try, except, else and finally, and catch specific exceptions
- Raise exceptions and define custom exception classes
- Use logging instead of print for programs that run unattended

Datasets used

`superstore_sales.csv`

Files and paths

Use `pathlib.Path` for paths (works on Windows, macOS and Linux) and a `with` block to open files: the file is closed automatically, even if an error happens.

Python

```
from pathlib import Path
folder = Path("demo_files"); folder.mkdir(exist_ok=True)
notes = folder / "notes.txt"                                  # / joins path parts
with open(notes, "w", encoding="utf-8") as f:                  # "w" overwrites, "a" appends,
"r" reads (default)
    f.write("Line one\n")
    f.writelines(["Line two\n", "Line three\n"])
with open(notes, "a", encoding="utf-8") as f: print("Line four", file=f)
print(notes.read_text(encoding="utf-8"))
print(notes.exists(), notes.name, notes.stem, notes.suffix, notes.stat().st_size, "bytes")
```

OUTPUT

```
Line one
Line two
Line three
Line four

True notes.txt notes .txt 39 bytes
```

Python

```python
with open(notes, encoding="utf-8") as f:
    for i, line in enumerate(f, 1):                    # iterate line by line: constant
memory for huge files
        print(i, line.rstrip("\n"))
with open(notes, encoding="utf-8") as f: lines = f.read().splitlines()
print(lines, sorted(p.name for p in folder.glob("*.txt")))
```

OUTPUT

```
1 Line one
2 Line two
3 Line three
4 Line four
['Line one', 'Line two', 'Line three', 'Line four'] ['notes.txt']
```

Mode	Meaning
`"r"`	Read (error if missing)
`"w"`	Write (creates or **overwrites**)
`"a"`	Append to the end
`"x"`	Create; error if it exists
`"b"` suffix	Binary (`"rb"` , `"wb"`) for images, Excel, Parquet

TIP **Always give the encoding**

`encoding="utf-8"` avoids garbled ₹, é or Hindi text and avoids differences between Windows and Linux defaults.

CSV files

The standard `csv` module handles quoting and commas inside values. (For analysis you will usually use `pandas.read_csv`, Lesson 16.)

Python

```
import csv
rows = [{"id": 1, "city": "Pune", "note": "fast, friendly"}, {"id": 2, "city": "Delhi",
"note": 'said "ok"'}]
with open(folder / "people.csv", "w", newline="", encoding="utf-8") as f:
    w = csv.DictWriter(f, fieldnames=["id", "city", "note"])
    w.writeheader(); w.writerows(rows)
print((folder / "people.csv").read_text(encoding="utf-8"))
with open(folder / "people.csv", newline="", encoding="utf-8") as f:
    for r in csv.DictReader(f): print(r)                # every value is a string
```

OUTPUT

```
id,city,note
1,Pune,"fast, friendly"
2,Delhi,"said ""ok"""

{'id': '1', 'city': 'Pune', 'note': 'fast, friendly'}
{'id': '2', 'city': 'Delhi', 'note': 'said "ok"'}
```

Python

```
# Stream a real 6,000-line CSV without pandas: total sales per region
from collections import defaultdict
totals = defaultdict(float)
with open("superstore_sales.csv", newline="", encoding="utf-8") as f:
    for row in csv.DictReader(f): totals[row["region"]] += float(row["sales"])
print({k: round(v / 1e6, 1) for k, v in sorted(totals.items())})
```

OUTPUT

```
{'East': 46.5, 'North': 49.0, 'South': 54.0, 'West': 52.0}
```

JSON files

JSON maps to Python like this: object ↔ dict, array ↔ list, string ↔ str, number ↔ int/float, true/false ↔ True/False, null ↔ None.

Python

```
import json
config = {"source": "superstore_sales.csv", "regions": ["North", "South"], "min_sales":
1000, "debug": False, "owner": None}
with open(folder / "config.json", "w", encoding="utf-8") as f: json.dump(config, f,
indent=2)
with open(folder / "config.json", encoding="utf-8") as f: loaded = json.load(f)
print(loaded == config, loaded["regions"], json.dumps({"price": 4500.5, "ok": True, "x":
None}))
print(json.dumps({"city": "Pune", "₹": 1}, ensure_ascii=False))
```

OUTPUT

```
True ['North', 'South'] {"price": 4500.5, "ok": true, "x": null}
{"city": "Pune", "₹": 1}
```

`json.dump` / `json.load` work with files; `json.dumps` / `json.loads` work with strings (the "s" is for string). Dates and sets are not JSON types: convert them first (`d.isoformat()` , `list(s)`).

Exceptions

An **exception** is Python's way of reporting an error. Unhandled, it stops the program and prints a traceback. Handled, your program can recover.


Python

```
def safe_ratio(a, b):
    try:
        result = a / b
    except ZeroDivisionError:
        print("  cannot divide by zero")
        return None
    except TypeError as e:
        print("  wrong types:", e)
        return None
    else:                       # runs only when no exception happened
        return round(result, 2)
    finally:                    # always runs: clean-up
        print("  checked", a, b)
print(safe_ratio(10, 4)); print(safe_ratio(1, 0)); print(safe_ratio("10", 2))
```

OUTPUT

```
  checked 10 4
2.5
  cannot divide by zero
  checked 1 0
```

```
None
  wrong types: unsupported operand type(s) for /: 'str' and 'int'
  checked 10 2
None
```



try / except / else / finally: which blocks run.

Common built-in exceptions

Exception	Typical cause
`ValueError`	Right type, wrong value: `int("abc")`
`TypeError`	Wrong type: `"a" + 1`
`KeyError`	Missing dict key
`IndexError`	List index out of range
`FileNotFoundError`	Missing file
`ZeroDivisionError`	Divide by zero
`AttributeError`	Object has no such attribute or method
`ImportError` / `ModuleNotFoundError`	Package not installed

Python

```python
tests = [lambda: int("abc"), lambda: "a" + 1, lambda: {}["x"], lambda: [1][5], lambda:
open("missing.csv"), lambda: None.upper()]
for t in tests:
    try: t()
    except Exception as e: print(f"{type(e).__name__:<18} {e}")
```

OUTPUT

```
ValueError         invalid literal for int() with base 10: 'abc'
TypeError          can only concatenate str (not "int") to str
```

```
KeyError           'x'
IndexError         list index out of range
FileNotFoundError  [Errno 2] No such file or directory: 'missing.csv'
AttributeError     'NoneType' object has no attribute 'upper'
```

WATCH OUT **Do not swallow every error**

`except: pass` or `except Exception: pass` hides bugs. Catch the **specific** exceptions you expect, and let unexpected ones surface (or log them and re-raise).

Raising your own exceptions

Python

```python
class DataQualityError(Exception):
    """Raised when an input file fails validation."""

def validate(df):
    missing = {"order_id", "sales"} - set(df.columns)
    if missing: raise DataQualityError(f"missing columns: {sorted(missing)}")
    if (df["sales"] < 0).any(): raise ValueError("negative sales found")
    return True

import pandas as pd
for d in (pd.DataFrame({"order_id": [1], "sales": [5]}), pd.DataFrame({"order_id": [1]}),
pd.DataFrame({"order_id": [1], "sales": [-2]})):
    try: print("valid:", validate(d))
    except (DataQualityError, ValueError) as e: print(type(e).__name__, "→", e)
```

OUTPUT

```
valid: True
DataQualityError → missing columns: ['sales']
ValueError → negative sales found
```

Use `raise ... from e` to wrap a low-level error in a clearer one while keeping the original cause.

Logging

`print` is for interactive work. Programs that run on a schedule (ETL jobs, APIs) should use `logging`, which adds timestamps and levels and can write to files.

Python

```
import logging, io
stream = io.StringIO()
log = logging.getLogger("etl"); log.handlers.clear(); log.setLevel(logging.INFO)
h = logging.StreamHandler(stream); h.setFormatter(logging.Formatter("%(levelname)s | %
(name)s | %(message)s")); log.addHandler(h)
log.debug("not shown: below INFO"); log.info("loaded 6,323 rows"); log.warning("12 rows had
blank city")
try: 1 / 0
except ZeroDivisionError: log.exception("step failed")       # logs the traceback too
print(stream.getvalue().splitlines()[:3])
```

OUTPUT

```
['INFO | etl | loaded 6,323 rows', 'WARNING | etl | 12 rows had blank city', 'ERROR |
etl | step failed']
```

Levels from low to high: `DEBUG`, `INFO`, `WARNING`, `ERROR`, `CRITICAL`.

Project: load a messy file safely

Python

```
messy = """order_id,amount,city
1,1200,Pune
2,abc,Delhi
3,,Kochi
4,950,
5,-40,Goa
"""
(folder / "messy.csv").write_text(messy, encoding="utf-8")

def load_orders(path):
    good, bad = [], []
    with open(path, newline="", encoding="utf-8") as f:
        for lineno, row in enumerate(csv.DictReader(f), start=2):
            try:
                amount = float(row["amount"])
                if amount < 0: raise ValueError("negative amount")
                if not row["city"]: raise ValueError("blank city")
                good.append({"order_id": int(row["order_id"]), "amount": amount, "city":
row["city"]})
            except ValueError as e:
                bad.append((lineno, str(e)))
    return good, bad

good, bad = load_orders(folder / "messy.csv")
print("good:", good); print("rejected:", bad)
with open(folder / "rejected.json", "w", encoding="utf-8") as f: json.dump(bad, f)
import shutil; shutil.rmtree(folder)                    # tidy up the demo folder
```

OUTPUT

```
good: [{'order_id': 1, 'amount': 1200.0, 'city': 'Pune'}]
rejected: [(3, "could not convert string to float: 'abc'"), (4, "could not convert
string to float: ''"), (5, 'blank city'), (6, 'negative amount')]
```

Real pipelines do exactly this: keep the good rows, quarantine and report the bad ones, never crash on one bad line.

Summary

KEY TAKEAWAYS

- Use `pathlib.Path` and `with open(path, mode, encoding="utf-8")` ; iterate a file line by line for big files.
- `csv.DictReader` / `DictWriter` handle quoting (values are strings); `json.load` / `dump` convert JSON ↔ Python.
- `try` / `except SpecificError` / `else` / `finally` ; never use a bare `except: pass` .
- `raise` your own exceptions (subclass `Exception`) to signal bad data clearly.
- Use `logging` with levels for unattended programs.

Quick quiz

6 questions · tap an answer to check it

1. Why use `with open(...) as f:` ?

A It is faster

B The file is closed automatically, even if an error occurs

C It reads the whole file

D It is required for CSV

Answer: B. The context manager handles clean-up.

2. What does mode `"w"` do to an existing file?

A Appends

B Overwrites it

C Raises an error

D Reads it

Answer: B. Use `"a"` to append and `"x"` to refuse overwriting.

3. When does the `else` block of a `try` statement run?

- **A** Always
- **B** Only if no exception was raised in `try`
- **C** Only after an exception
- **D** Never

Answer: B. `finally` is the block that always runs.

4. What does `json.loads` take?

- **A** A file
- **B** A string
- **C** A dictionary
- **D** A path

Answer: B. `load` takes a file object; `loads` takes a string.

5. What exception does `int("abc")` raise?

- **A** TypeError
- **B** ValueError
- **C** KeyError
- **D** SyntaxError

Answer: B. The type (str) is acceptable, the value is not.

6. Why prefer `logging` over `print` for scheduled jobs?

A It is shorter

B It adds levels and timestamps and can write to files and monitoring tools

C print is deprecated

D logging is faster

Answer: B. You can filter by level and keep a history.

EXERCISE **File and error problems**

(1) Write a function that counts lines, words and characters in a text file. (2) Read `superstore_sales.csv` with `csv.DictReader` and count rows per `category`. (3) Save that result as JSON and load it back. (4) Write `to_int(text, default=0)` that returns the default on `ValueError`. (5) Raise a custom `EmptyFileError` when a file has no data rows.

Show solution (worked answer)

Python

```python
def wc(path):
    text = Path(path).read_text(encoding="utf-8")
    return len(text.splitlines()), len(text.split()), len(text)
from collections import Counter
with open("superstore_sales.csv", newline="", encoding="utf-8") as f:
    counts = Counter(r["category"] for r in csv.DictReader(f))
Path("cat.json").write_text(json.dumps(counts), encoding="utf-8")
print(json.loads(Path("cat.json").read_text(encoding="utf-8")))
def to_int(text, default=0):
    try: return int(text)
    except ValueError: return default
class EmptyFileError(Exception): pass
def check(path):
    with open(path, encoding="utf-8") as f:
        if len(f.read().splitlines()) < 2: raise EmptyFileError(path)
```

INTERVIEW CORNER

Questions you may be asked

Q: How do you read a 10 GB file in Python? Iterate it line by line (`for line in f`), or read in chunks (`pd.read_csv(..., chunksize=...)`), so memory stays constant.

Q: Difference between `except Exception` and a bare `except` ? A bare `except` also catches `KeyboardInterrupt` and `SystemExit` ; catch specific exceptions where possible.

Q: What is `finally` used for? Clean-up that must always happen, such as closing connections or releasing locks.

Q: How do you handle bad rows in an ETL job? Validate each row, keep good rows, write rejects with the reason to a quarantine file or table, log counts, and alert if the reject rate is too high.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.