PYTHON FOR DATA SCIENCE · LESSON 15 OF 29

NumPy: Fast Arrays, Vectorisation and Broadcasting

Learn the array library under pandas, scikit-learn and PyTorch. Create arrays, understand shape and dtype, index and slice in 1-D and 2-D, filter with boolean masks, compute with vectorised operations, aggregations along axes and broadcasting, generate random data and do basic linear algebra.

Python class 11 | NumPy 2.x | Intermediate | 120 min

By the end of this lesson you can

- Create arrays and describe their shape, ndim, dtype and size
- Index, slice and filter 1-D and 2-D arrays with boolean masks and fancy indexing
- Use vectorised arithmetic, universal functions and aggregations along an axis
- Apply broadcasting rules, reshape, stack and split arrays
- Generate reproducible random data and perform matrix operations

Datasets used

`house_prices.csv`

Why NumPy?

A Python list holds pointers to separate objects; a NumPy **array** stores numbers of one type in one contiguous block of memory and runs operations in compiled C. The result: code that is shorter **and** usually many times faster (the gap grows with heavier maths).

Python

```
import numpy as np, time
n = 1_000_000
py = list(range(n)); arr = np.arange(n)
t0 = time.perf_counter(); sq_list = [x * x for x in py]; t1 = time.perf_counter(); sq_arr =
arr * arr; t2 = time.perf_counter()
print(f"list comprehension {1000*(t1-t0):.1f} ms | numpy {1000*(t2-t1):.1f} ms | same
result: {sq_list[-1] == sq_arr[-1]}")
print(np.__version__)
```

OUTPUT

```
list comprehension 44.7 ms | numpy 34.8 ms | same result: True
2.5.3
```


Creating arrays

Python

```
a = np.array([3, 1, 4, 1, 5])
m = np.array([[1, 2, 3], [4, 5, 6]])
print(a, a.dtype, a.shape, a.ndim, a.size)
print(m, m.shape, m.ndim, m.dtype)
print(np.zeros(3), np.ones((2, 2)), np.full(3, 7), np.eye(2))
print(np.arange(0, 10, 2.5), np.linspace(0, 1, 5), np.array([1, 2.5]).dtype, np.array([1,
2], dtype=np.float32).dtype)
```

OUTPUT

```
[3 1 4 1 5] int64 (5,) 1 5
[[1 2 3]
 [4 5 6]] (2, 3) 2 int64
[0. 0. 0.] [[1. 1.]
 [1. 1.]] [7 7 7] [[1. 0.]
 [0. 1.]]
[0.  2.5 5.  7.5] [0.   0.25 0.5  0.75 1.  ] float64 float32
```



Shapes of 1-D, 2-D and 3-D arrays. axis 0 runs down the rows, axis 1 across the columns.

All items share one **dtype** (`int64` , `float64` , `bool` , `<U5` strings…). Mixing ints and floats upcasts to float.

Indexing and slicing

Python

```
a = np.array([10, 20, 30, 40, 50, 60])
print(a[0], a[-1], a[1:4], a[::2], a[::-1])
m = np.arange(1, 13).reshape(3, 4)
print(m)
print(m[0, 2], m[1], m[:, 1], m[1:, 2:], m[-1, -1])          # [row, column]
```

OUTPUT

```
10 60 [20 30 40] [10 30 50] [60 50 40 30 20 10]
[[ 1  2  3  4]
 [ 5  6  7  8]
 [ 9 10 11 12]]
3 [5 6 7 8] [ 2  6 10] [[ 7  8]
 [11 12]] 12
```

WATCH OUT **Slices are views**

`b = a[1:4]` does **not** copy; changing `b` changes `a`. Use `a[1:4].copy()` when you need an independent array. (Python lists behave the other way: slicing copies.)

Boolean masks and fancy indexing

Python

```
sales = np.array([120, 45, 300, 80, 210, 15])
mask = sales > 100
print(mask, sales[mask], sales[(sales > 50) & (sales < 250)], sales[~mask])    # & | ~ with brackets
print(sales[[0, 2, 4]], np.where(sales > 100, "high", "low"), np.where(sales > 100)[0])
sales[sales < 50] = 0                                  # conditional assignment
print(sales, np.count_nonzero(sales), (sales > 100).mean())
```

OUTPUT

```
[ True False  True False  True False] [120 300 210] [120  80 210] [45 80 15]
[120 300 210] ['high' 'low' 'high' 'low' 'high' 'low'] [0 2 4]
[120   0 300  80 210   0] 4 0.5
```

Vectorised maths and aggregations

Python

```
price = np.array([100.0, 250.0, 80.0]); qty = np.array([3, 1, 10])
print(price * qty, (price * qty).sum(), price * 1.18, np.round(np.sqrt(price), 2),
np.log(price).round(2))
m = np.array([[5, 2, 9], [1, 7, 3]])
print(m.sum(), m.sum(axis=0), m.sum(axis=1), m.max(axis=1), m.argmax(axis=1),
m.mean(axis=0))
x = np.array([2, 4, 4, 4, 5, 5, 7, 9])
print(x.mean(), np.median(x), x.std(), x.std(ddof=1).round(3), np.percentile(x, [25, 75]),
np.cumsum(x), np.diff(x))
```


OUTPUT

```
[300. 250. 800.] 1350.0 [118.  295.   94.4] [10.   15.81  8.94] [4.61 5.52 4.38]
27 [ 6  9 12] [16 11] [9 7] [2 1] [3.  4.5 6. ]
5.0 4.5 2.0 2.138 [4.  5.5] [ 2  6 10 14 19 24 31 40] [2 0 0 1 0 2 2]
```

`axis=0` collapses rows (one result per column); `axis=1` collapses columns (one result per row). `ddof=1` gives the **sample** standard deviation that pandas uses by default.

Broadcasting

When shapes differ, NumPy **stretches** the smaller array along dimensions of size 1, without copying data.



Broadcasting: a (3, 3) matrix plus a (3,) row is applied to every row.

Python

```
m = np.arange(1, 10).reshape(3, 3)
print(m + np.array([10, 20, 30]))                    # add to each row
print(m * np.array([[1], [10], [100]]))              # multiply each row by its own
factor (column vector)
scores = np.array([[70, 80, 90], [60, 75, 85], [88, 92, 79]], dtype=float)
z = (scores - scores.mean(axis=0)) / scores.std(axis=0)   # standardise each column in one
line
print(z.round(2))
```

OUTPUT

```
[[11 22 33]
 [14 25 36]
 [17 28 39]]
[[  1   2   3]
 [ 40  50  60]
 [700 800 900]]
[[-0.23 -0.33  1.19]
 [-1.09 -1.03  0.07]
 [ 1.32  1.36 -1.26]]
```

Rule: compare shapes from the right; dimensions are compatible if equal or one of them is 1.

Reshaping, stacking, sorting

Python

```
a = np.arange(12)
print(a.reshape(3, 4).shape, a.reshape(2, -1).shape, a.reshape(3, 4).T.shape, a.reshape(3,
4).ravel()[:5])
x, y = np.array([1, 2]), np.array([3, 4])
print(np.vstack([x, y]), np.hstack([x, y]), np.column_stack([x, y]), np.concatenate([x,
y]))
v = np.array([30, 10, 20, 10])
print(np.sort(v), np.argsort(v), np.unique(v, return_counts=True), v[np.argsort(-v)][:2])
```

OUTPUT

```
(3, 4) (2, 6) (4, 3) [0 1 2 3 4]
[[1 2]
 [3 4]] [1 2 3 4] [[1 3]
 [2 4]] [1 2 3 4]
[10 10 20 30] [1 3 2 0] (array([10, 20, 30]), array([2, 1, 1])) [30 20]
```

Random numbers

Use the modern generator API with a seed so results are reproducible.

Python

```
rng = np.random.default_rng(42)
print(rng.integers(1, 7, size=10))                      # dice
print(rng.normal(loc=50, scale=10, size=5).round(1))    # normal distribution
print(rng.choice(["A", "B"], size=8, p=[0.7, 0.3]), rng.uniform(0, 1, 3).round(3))
sample = rng.normal(50, 10, 100_000)
print(round(sample.mean(), 2), round(sample.std(), 2), round(((sample > 40) & (sample <
60)).mean(), 3))   # about 68% within 1 sd
```

OUTPUT

```
[1 5 4 3 3 6 1 5 2 1]
[37.  51.3 46.8 49.8 41.5]
['A' 'B' 'A' 'B' 'A' 'A' 'A' 'A'] [0.828 0.632 0.758]
49.96 10.04 0.682
```

Linear algebra basics

Machine-learning models are built from these operations.

Python

```
A = np.array([[2, 1], [1, 3]]); b = np.array([5, 10])
print(A @ np.array([1, 2]), A.T, np.linalg.det(A).round(2), np.linalg.inv(A).round(3))
print(np.linalg.solve(A, b))                            # solves 2x + y = 5, x + 3y = 10
w = np.array([0.5, -0.2]); X = np.array([[1.0, 2.0], [3.0, 1.0], [2.0, 2.0]])
print(X @ w)                                             # predictions of a linear model y
= Xw
```

OUTPUT

```
[4 7] [[2 1]
 [1 3]] 5.0 [[ 0.6 -0.2]
 [-0.2  0.4]]
[1. 3.]
[0.1 1.3 0.6]
```

Real data: house prices

Python

```
import pandas as pd
h = pd.read_csv("house_prices.csv")
area, price = h["area_sqft"].to_numpy(), h["price_lakh"].to_numpy()
print("missing values:", np.isnan(area).sum(), "area,", np.isnan(price).sum(), "price")
# real data has gaps
ok = ~np.isnan(area) & ~np.isnan(price)
area, price = area[ok], price[ok]
# keep complete rows
per_sqft = price * 1e5 / area
print(f"{len(price)} houses | median price ₹{np.median(price):.1f} lakh | median ₹
{np.median(per_sqft):,.0f}/sq ft")
print("price percentiles 10/50/90:", np.percentile(price, [10, 50, 90]).round(1))
big = area > 1500
print(f"{big.mean():.0%} are over 1,500 sq ft; their median price is ₹
{np.median(price[big]):.1f} lakh vs ₹{np.median(price[~big]):.1f} lakh")
r = np.corrcoef(area, price)[0, 1]
slope, intercept = np.polyfit(area, price, 1)
print(f"correlation area-price r = {r:.2f}; fitted line: price ≈ {intercept:.1f} +
{slope*100:.2f} lakh per 100 sq ft")
```

OUTPUT

```
missing values: 25 area, 0 price
1175 houses | median price ₹78.7 lakh | median ₹6,258/sq ft
price percentiles 10/50/90: [ 40.3  78.7 119.9]
27% are over 1,500 sq ft; their median price is ₹110.0 lakh vs ₹68.1 lakh
correlation area-price r = 0.79; fitted line: price ≈ -7.5 + 7.05 lakh per 100 sq ft
```

`np.polyfit` fits a straight line by least squares, which is the same idea as linear regression (ML track).

Summary

KEY TAKEAWAYS

- Arrays hold one dtype in contiguous memory; operations are vectorised and much faster than Python loops.
- Know `shape`, `ndim`, `dtype`, `size`; index with `[row, col]`; slices are views (use `.copy()`).
- Boolean masks (`a[a > 0]`, `&`, `|`, `~`) and `np.where` filter and recode.
- Aggregate with `axis=0` (per column) or `axis=1` (per row); `ddof=1` for sample standard deviation.
- Broadcasting stretches size-1 dimensions; reshape with `-1` to infer a dimension.
- Use `np.random.default_rng(seed)` and `@` for matrix multiplication.

Quick quiz

6 questions · tap an answer to check it

1. What is `np.arange(12).reshape(3, -1).shape`?

A (3, 3)

B (3, 4)

C (4, 3)

D Error

Answer: B. -1 lets NumPy infer the missing dimension: 12 / 3 = 4.

2. What does `m.sum(axis=0)` return for a 2 × 3 matrix?

A One number

B Three numbers: the sum of each column

C Two numbers: the sum of each row

D A 2 × 3 matrix

Answer: B. axis=0 collapses the rows.

3. Which expression keeps values between 10 and 20?

A `a[a > 10 and a < 20]`

B `a[(a > 10) & (a < 20)]`

C `a[10:20]`

D `a.between(10, 20)`

Answer: B. Use `&` with brackets for element-wise conditions.

4. After `b = a[0:3]; b[0] = 99`, what happens to `a[0]`?

A Unchanged

B It becomes 99 because a slice is a view

C Error

D It becomes 0

Answer: B. Use `.copy()` to avoid this.

5. Can a (3, 4) array be added to a (4,) array?

A Yes, the (4,) array is broadcast across the rows

B No, shapes must match exactly

C Only with a loop

D Only if both are float

Answer: A. Trailing dimensions match (4 and 4).

6. How do you make random results reproducible?

A Use `np.random.random()`

B Create a generator with a seed: `np.random.default_rng(42)`

C Run the cell twice

D Use floats

Answer: B. The same seed gives the same numbers.

EXERCISE

NumPy practice

(1) Create a 5 × 5 array of 1..25 and select the diagonal and the last column. (2) Replace all negative values in an array with 0. (3) Standardise the `area_sqft` column (z-scores) and count values beyond ±2. (4) Simulate 10,000 rolls of two dice and estimate P(sum = 7). (5) Solve 3x + 2y = 12, x − y = 1.

Show solution (worked answer)

Python

```
g = np.arange(1, 26).reshape(5, 5); print(np.diag(g), g[:, -1])
v = np.array([3, -1, 4, -5]); v[v < 0] = 0; print(v)
z = (area - area.mean()) / area.std(); print((np.abs(z) > 2).sum())
rng = np.random.default_rng(0); rolls = rng.integers(1, 7, (10_000, 2)).sum(axis=1);
print((rolls == 7).mean())   # about 1/6
print(np.linalg.solve([[3, 2], [1, -1]], [12, 1]))   # x = 2.8, y = 1.8
```

INTERVIEW CORNER

Questions you may be asked

Q: Why is NumPy faster than Python lists? Contiguous memory of one dtype, operations implemented in C over the whole array (vectorisation), and no per-element Python overhead.

Q: What is broadcasting? NumPy's rule for operating on arrays of different shapes by virtually repeating dimensions of size 1, aligning shapes from the right.

Q: View vs copy? Basic slices return views that share memory; fancy/boolean indexing and `.copy()` return copies.

Q: Difference between `np.std(x)` and `pandas.Series.std()`? NumPy defaults to population std (`ddof=0`); pandas defaults to sample std (`ddof=1`).

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.