PYTHON FOR DATA SCIENCE · LESSON 23 OF 29

Python and SQL: sqlite3, DuckDB, SQLAlchemy and pandas.read_sql

Connect Python to databases. Create and query SQLite with the standard library, use parameterised queries safely, load DataFrames to tables and back, query CSV and DataFrames directly with DuckDB, connect to MySQL, PostgreSQL and SQL Server with SQLAlchemy, and decide what to do in SQL versus pandas.

Python class 18 · ✦ DuckDB 1.x/2.x · SQLAlchemy 2 · Intermediate · ⏱ 100 min

By the end of this lesson you can


- Create a SQLite database, run DDL/DML from Python and fetch results
- Write parameterised queries and explain SQL injection
- Move data between pandas and databases with to_sql and read_sql
- Query files and DataFrames with DuckDB
- Connect to server databases with SQLAlchemy connection URLs and secrets kept out of code

Datasets used

`superstore_sales.csv` `customers.csv`

Why connect Python to SQL?

Company data lives in databases and warehouses (MySQL, PostgreSQL, SQL Server, Snowflake, BigQuery, Databricks). The usual pattern: **filter and aggregate in SQL** (close to the data), then **analyse, model and chart in Python**.



SQL pulls and summarises; Python analyses, models and presents.

sqlite3: a database in a file

SQLite ships with Python. It is perfect for learning, prototypes and small apps.

Python

```
import sqlite3, pandas as pd
con = sqlite3.connect(":memory:")                    # or "shop.db" for a file
cur = con.cursor()
cur.executescript("""
CREATE TABLE customers (id INTEGER PRIMARY KEY, name TEXT NOT NULL, city TEXT);
CREATE TABLE orders (id INTEGER PRIMARY KEY, customer_id INTEGER REFERENCES customers(id),
amount REAL, order_date TEXT);
""")
cur.executemany("INSERT INTO customers (name, city) VALUES (?, ?)", [("Asha", "Pune"),
("Ravi", "Delhi"), ("Meera", "Kochi")])
cur.executemany("INSERT INTO orders (customer_id, amount, order_date) VALUES (?, ?, ?)",
                [(1, 1200, "2025-01-05"), (1, 450, "2025-02-11"), (2, 3000, "2025-02-14"),
(3, 780, "2025-03-01")])
con.commit()
cur.execute("SELECT c.name, COUNT(*), SUM(o.amount) FROM orders o JOIN customers c ON c.id
= o.customer_id GROUP BY c.name ORDER BY 3 DESC")
print(cur.fetchall())
cur.execute("SELECT * FROM customers WHERE city = ?", ("Pune",)); print(cur.fetchone())
```

OUTPUT

```
[('Ravi', 1, 3000.0), ('Asha', 2, 1650.0), ('Meera', 1, 780.0)]
(1, 'Asha', 'Pune')
```

Method	Use
`con.execute(sql, params)` / `cursor.execute`	Run one statement
`executemany(sql, rows)`	Insert many rows
`fetchone()` , `fetchall()` , `fetchmany(n)`	Read results
`con.commit()` / `con.rollback()`	Save / undo a transaction
`with con:`	Commits on success, rolls back on error

Parameterised queries and SQL injection

Python

```
user_input = "Pune' OR '1'='1"
unsafe = f"SELECT name FROM customers WHERE city = '{user_input}'"       # NEVER build SQL
with f-strings
print("unsafe returns:", con.execute(unsafe).fetchall())
print("safe returns:  ", con.execute("SELECT name FROM customers WHERE city = ?",
(user_input,)).fetchall())
```

OUTPUT

```
unsafe returns: [('Asha',), ('Ravi',), ('Meera',)]
safe returns:   []
```

The unsafe query returned **every** customer because the input changed the SQL. Placeholders (`?` in SQLite, `%s` or `:name` in other drivers) send values separately, so input can never become code.

Transactions

Python

```
try:
    with con:                                                  # one transaction
        con.execute("UPDATE orders SET amount = amount - 500 WHERE id = 1")
        con.execute("INSERT INTO orders (customer_id, amount) VALUES (2, 500)")          #
second change
        raise ValueError("payment gateway down")                    # simulate a failure
mid-way
except ValueError as e:
    print("rolled back:", e)
print(con.execute("SELECT id, amount FROM orders WHERE id = 1").fetchone(),
con.execute("SELECT COUNT(*) FROM orders").fetchone())
```

OUTPUT

```
rolled back: payment gateway down
(1, 1200.0) (4,)
```

Both changes were undone together: that is atomicity (the A in ACID).

pandas ↔ database

Python

```python
s = pd.read_csv("superstore_sales.csv")
s.to_sql("sales", con, index=False, if_exists="replace")              # DataFrame → table
q = """
SELECT region, category, ROUND(SUM(sales) / 1e6, 2) AS sales_m, ROUND(100.0 * SUM(profit) /
SUM(sales), 1) AS margin_pct
FROM sales WHERE discount ⩽ :max_disc GROUP BY region, category ORDER BY sales_m DESC
LIMIT 5
"""
print(pd.read_sql(q, con, params={"max_disc": 0.1}))                  # query → DataFrame
con.close()
```

OUTPUT

```
  region    category  sales_m  margin_pct
0  South  Technology    32.14        15.9
1   West  Technology    30.21        16.1
2  North  Technology    29.93        16.6
3   East  Technology    26.57        17.5
4   West   Furniture     5.36        10.3
```

For large tables, read in pieces with `chunksize=` or push the aggregation into SQL so only the summary travels.

DuckDB: SQL on files and DataFrames

DuckDB is an in-process analytical database: no server, very fast on columnar data, and it can query CSV, Parquet and pandas DataFrames directly.

Python

```
import duckdb
print(duckdb.sql("""
    SELECT category, COUNT(*) AS lines, ROUND(SUM(sales)/1e6, 2) AS sales_m
    FROM 'superstore_sales.csv' GROUP BY category ORDER BY sales_m DESC
""").df())
customers = pd.read_csv("customers.csv")
top = duckdb.sql("""
    SELECT c.state, COUNT(DISTINCT s.customer_id) AS customers, ROUND(SUM(s.sales)/1e6, 2)
AS sales_m,
           RANK() OVER (ORDER BY SUM(s.sales) DESC) AS rnk
    FROM s JOIN customers c USING (customer_id)                    -- s and customers
are pandas DataFrames!
    GROUP BY c.state QUALIFY rnk ⩽ 5 ORDER BY rnk
""").df()
print(top, duckdb.__version__)
```

OUTPUT

```
          category  lines  sales_m
0       Technology   1892   156.44
1        Furniture   1917    34.84
2  Office Supplies   2514    10.13
            state  customers  sales_m  rnk
0     Maharashtra         93    25.67    1
1           Delhi         54    15.66    2
2          Kerala         48    14.71    3
3  Madhya Pradesh         57    14.41    4
4     West Bengal         54    13.89    5 2.0.0
```

DuckDB also writes Parquet (`COPY (SELECT ...) TO 'out.parquet'`), reads from S3, and powers tools such as MotherDuck and the Metabase/MinusX demos in the AI analytics track.

Server databases with SQLAlchemy

`SQLAlchemy` gives one interface to many databases. You need the database's driver package too.

Python

```python
from sqlalchemy import create_engine, text
import os, pandas as pd

# Connection URLs:  dialect+driver://user:password@host:port/database
url = os.environ["DB_URL"]          # e.g.
"postgresql+psycopg://analyst:***@db.company.com:5432/sales"
#   MySQL:       "mysql+pymysql://user:pw@host:3306/db"
#   SQL Server:  "mssql+pyodbc://user:pw@server/db?driver=ODBC+Driver+18+for+SQL+Server"
#   SQLite:      "sqlite:///shop.db"
engine = create_engine(url)

with engine.connect() as conn:
    df = pd.read_sql(text("SELECT * FROM orders WHERE order_date ⩾ :d"), conn, params=
{"d": "2025-01-01"})

df_summary.to_sql("daily_summary", engine, if_exists="append", index=False,
chunksize=10_000)
```

Warehouses have their own connectors (`snowflake-connector-python` , `google-cloud-bigquery` , `databricks-sql-connector`), and most also accept SQLAlchemy URLs.

> **WATCH OUT** **Keep credentials out of code**
>
> Read passwords from environment variables, a `.env` file (with `python-dotenv`) that is in `.gitignore` , or a secrets manager. Use a read-only database user for analysis.

SQL or pandas?

Do it in SQL when…	Do it in pandas when…
The data is large and lives in the database	The data fits in memory
Filtering, joining, aggregating	Complex reshaping, statistics, ML, charts
Many people need the same logic (views)	Exploratory, one-off analysis
You want the database's indexes and compute	You need Python libraries

Summary

KEY TAKEAWAYS

- `sqlite3` creates databases in a file or memory; `execute`, `executemany`, `fetchall`, `commit`; `with con:` wraps a transaction.
- Always use parameter placeholders, never f-strings, to prevent SQL injection.
- `df.to_sql` writes tables; `pd.read_sql(query, con, params=...)` reads results into DataFrames.
- DuckDB runs fast SQL directly on CSV/Parquet files and pandas DataFrames.
- SQLAlchemy connects to MySQL, PostgreSQL, SQL Server and warehouses with a URL; keep credentials in environment variables.

Quick quiz

6 questions · tap an answer to check it

1. How should user input be passed into a SQL query?

A With an f-string

B As parameters with placeholders (`?` , `%s` , `:name`)

C With string concatenation

D In a comment

Answer: B. Placeholders prevent SQL injection.

2. What does `with con:` do in sqlite3?

A Opens a file

B Commits if the block succeeds and rolls back on an exception

C Closes the database

D Creates a table

Answer: B. It makes the block a transaction.

3. Which writes a DataFrame to a database table?

A `pd.read_sql`

B `df.to_sql("table", con)`

C `df.to_csv`

D `con.fetchall`

Answer: B. `if_exists` controls replace/append.

4. What is special about DuckDB?

A It requires a server

B It runs in-process and can query CSV, Parquet and DataFrames directly with SQL

C It only stores text

D It replaces pandas entirely

Answer: B. It is optimised for analytics.

5. Where should a database password be stored?

A In the notebook

B In an environment variable or secrets manager

C In the SQL query

D On GitHub

Answer: B. Never commit credentials.

6. Why aggregate in SQL before loading into pandas?

A SQL is always faster to write

B Only the small summary travels over the network and into memory

C pandas cannot aggregate

D It is required

Answer: B. Push heavy work to the database.

EXERCISE

Practice

(1) Load `customers.csv` and `superstore_sales.csv` into SQLite. (2) In SQL, find the top 5 cities by profit and read the result into pandas. (3) Repeat with DuckDB directly on the CSV files. (4) Write a function `get_sales(con, region)` that uses a parameterised query.

Show solution (worked answer)

Python

```
con = sqlite3.connect(":memory:")
pd.read_csv("customers.csv").to_sql("customers", con, index=False)
pd.read_csv("superstore_sales.csv").to_sql("sales", con, index=False)
print(pd.read_sql("SELECT city, SUM(profit) p FROM sales GROUP BY city ORDER BY p DESC
LIMIT 5", con))
print(duckdb.sql("SELECT city, SUM(profit) p FROM 'superstore_sales.csv' GROUP BY city
ORDER BY p DESC LIMIT 5").df())
def get_sales(con, region):
    return pd.read_sql("SELECT SUM(sales) AS sales FROM sales WHERE region = ?", con,
params=(region,))
print(get_sales(con, "West"))
```

INTERVIEW CORNER

Questions you may be asked

Q: What is SQL injection and how do you prevent it? Malicious input that changes a query's meaning; prevent it with parameterised queries (and least-privilege accounts, input validation, ORMs).

Q: How do you load a 50 GB table for analysis? Aggregate or sample in the database, read in chunks, or use a columnar engine (DuckDB, Spark, the warehouse itself) instead of pulling everything into pandas.

Q: What does ACID mean? Atomicity, Consistency, Isolation, Durability: transactions are all-or-nothing, keep rules valid, do not interfere, and survive crashes.

Practise more online

Free, trusted places to test yourself on this topic. Links open the original site in a new tab.