Language Models and Agents (CL3.410) | Group Project | Final Report

Gate Before You Act

Does Verifying Evidence Make an LLM Security Agent Act More Safely Than Policy Rules Alone?

Team **Simpletons** | November 2026

Varun Modi	**Aayush Pandey**	**Srushti Pekamwar**	**Dhruv Rajput**
2025202040	2025201058	2025201066	2025201094

GitHub repository: https://github.com/varunmodi18/Gate-Before-You-Act (branch `main`; frozen case set: tag `cases-v1`)

Abstract

An LLM agent that investigates a compromised Windows host can propose disruptive actions: isolate the host, kill a process, disable an account. We ask whether a pre-action gate that *also* checks that the cited log evidence supports the specific action decides better than a gate that enforces written policy alone, with the model, tools, policy and trusted context held fixed. We built *GateBench* on 99 real attack recordings (OTRF, 757k events) and froze a case set with known ground truth: 31 test scenarios (217 cases) with seven controlled evidence variants each, plus 12 live-investigation windows. We evaluated ten gate configurations, covering baselines and one ablation per capability (tool calling, RAG, reasoning, agentic), using Qwen2.5-7B-Instruct (4-bit) on one 8 GB laptop GPU. The full evidence gate wrongly admitted **29.0 points fewer** actions that should have been rejected than the policy-only gate (95% CI [20.1, 38.7]; H1 supported), and the LLM verifier alone contributed **16.1 points** ([6.5, 27.4]; H1-C4 supported). The cost was large: the gate wrongly blocked 35% of correct packages and raised unnecessary deferral by **35.5 points** ([25.7, 45.9]; H2 not met). Three findings explain why. The verifier never answered CONTRADICTED. Retrieval (none / BM25 / reranked) did not change decisions. Recovery budgets (0 / 1 / 2 queries) changed outcomes by at most 2 points even when the agent used them, and serving the tools over MCP changed nothing. Evidence gating makes this agent markedly safer but much less useful; the bottleneck is the small verifier's calibration.

1. Introduction

Domain: cyber-security operations, specifically first response on *one* Windows host from its Sysmon and Windows Security logs over a fixed time window. **Target user:** a junior SOC (Security Operations Centre) analyst who asks an agent to contain a suspicious host and needs either a safe, justified action or a clear escalation. **Scope:** one log source, one host per case, one workflow. Investigation is read-only, and every response action goes to mock tools that only record the call. The project adapts research direction E (incident response) of the course brief.

Problem. SOC teams are starting to give LLM agents tools that *act* on computers. A recent incident-response study found that frontier models often contain hosts before gathering trusted evidence, with wrong containment in 45–82.5% of episodes [4]. The usual fix is a policy gate that blocks actions on critical assets or without approval. Such rules, however, say nothing about whether the logs justify acting on *this* host, account or process. Requiring citations is not enough either: a cited record can be irrelevant, belong to a different host, be incomplete, or describe activity that an approved change explains. Log content is partly attacker-written, so the facts that decide safety, such as how critical a host is or whether approval exists, must come from a trusted source. We did not find an evaluation that isolates the value of checking evidence *beyond* policy enforcement while holding policy and context fixed, so we built one.

Why it matters here. Wrong actions are costly both ways: isolating the wrong host stops business, while refusing everything leaves the attacker active. Logs are adversarial, and text planted in them can try to steer the defender's agent (indirect prompt injection). In India, CERT-In's 2022 Directions require reporting specified incidents within 6 hours and keeping ICT logs for 180 days [12], so an agent that "cleans up" by deleting logs would break the rules. Small open models are the realistic deployment, and they are known to act unsafely on generic risk benchmarks [6].

1.1 Research Question, Hypotheses and Falsifiable Claim

RQ. Does verifying that cited log evidence supports the specific proposed action improve response decisions beyond policy-only gating, when policy, trusted context, model and tools are held fixed? Which part of the verification helps: deterministic target matching or the LLM verifier?

H1 (Exp 1): on packages that should be rejected (variants E2–E5), the full gate G3 wrongly admits at least **15 points** fewer actions than the policy-only gate G1. **H1-C4** (Exp 1): on E4–E5, G3 wrongly admits at least **10 points** fewer than A1 (G3 without the LLM verifier). **H2** (Exp 2): on cases with a justified completion, G3's unnecessary-deferral rate is not more than **10 points** worse than G1's. Experiment 3 (live end-to-end investigation) is descriptive. For every hypothesis we report the estimate, its 95% cluster-bootstrap interval, and whether the practical target was reached.

Falsifiable claim (course activity: baseline, capability, metric, evaluation set).
Our system (the full evidence gate G3, which adds LLM reasoning and retrieval to policy checks) will beat the policy-only gate G1 on evidence packages that should be rejected, measured by the wrongly-admitted rate, on the 31 frozen SOC-Risk test scenarios (124 cases, variants E2–E5).
We would consider the hypothesis falsified if the improvement is below 15 points or its 95% confidence interval includes 0.
Outcome: 29.0 points [20.1, 38.7]. Not falsified. The paired usefulness claim (H2) *was* falsified: deferral rose by 35.5 points [25.7, 45.9], beyond its 10-point margin.

Contributions. (i) *GateBench*, an open workbench with a provenance-enforcing gate, ten configurations, an MCP transport, scoring and analysis. (ii) *SOC-Risk*, a frozen case set with controlled evidence variants and exhaustive action labels. (iii) A controlled measurement of what evidence gating buys and costs with a 7B open model, with one ablation per capability, including negative results on retrieval, recovery and verifier calibration.

2. Literature Review

Work on LLM agents in security and on agent safety falls into three groups: environments that measure how agents investigate or respond, benchmarks of risk awareness, and runtime guards that enforce rules on tool calls. None of them isolates the value of checking *evidence* beyond policy enforcement while holding policy and context fixed, which is our question.

Work	What it does	Gap for our question
OpenSec [4]	IR environment with executed containment; measures an evidence-gated action rate	No enforced gate, no comparison with policy-only gating; synthetic logs
ExCyTIn-Bench [5]	Investigation questions over Sentinel log tables	Investigation only; no response actions
AURA-Eval [6], R-Judge [7]	Risk awareness on paired items; safe/unsafe judgements of agent records	Generic domains; no evidence about the action's target
AgentSpec [8], ShieldAgent [9]	Runtime rule enforcement; policy-verification shields	Check actions against rules, not whether log evidence supports the target
CaMeL [10]	Separates trusted control flow from untrusted data	Stops injection; does not judge evidence (we adopt its trusted/untrusted split)

Building blocks we adopt. The agent follows the ReAct pattern of interleaved reasoning and tool calls [11]. From CaMeL [10] we take the strict split between trusted control data and untrusted content: identifiers in actions must come from retrieved records, and log text is never treated as instructions. Tools are exposed directly or over the Model Context Protocol [14]. The verifier's background knowledge comes from Sigma detection rules [2] and MITRE ATT&CK [3], retrieved with BM25 alone or with a cross-encoder reranker [13]. The model is served locally with vLLM [15].

3. Dataset Created and Used

Logs and knowledge. OTRF Security-Datasets [1] at commit `d9d40ef`: 99 Windows attack recordings normalised into per-window DuckDB files (757,375 events). Near-duplicate windows were grouped and split before any case was written, stratified by tactic. The retrieval corpus is 2,403 Sigma rules [2], with ATT&CK tags removed from the indexed text, plus ATT&CK Enterprise 19.2 [3].

Injected scenarios. For each window a scenario fixes an analyst request (contain a host, stop a process or disable an account), the trusted context (asset tiers, identities, networks, an approval script, and one approved change ticket that deliberately misses the attack on one field) and a correct evidence package E1. A builder derives the other variants by patching the window database, so the right decision for each case is known:

E1	Correct, well-cited package (admit, subject to policy)
E2	Citations replaced by benign records; the attack records remain in the database (reject; the agent can recover)
E3	Attack chain moved to another host, so the evidence points at the wrong target (reject)
E4	Partial chain (key records removed) or an added contradicting record (reject)
E5	Minimal edits put the activity inside the approved change ticket (reject)
R_{pos} / R_{neg}	One context field (tier, approval or toolset) flipped, with and without a justified completion

Each case carries exhaustive labels: permitted and prohibited calls on every target, the correct outcome, acceptable escalations, verifier and gate labels, decisive facts, evidence sets and the gold technique. A 12-check validator must pass before freezing. Test scenarios carry a planted prompt-injection marker where an eligible record exists (17 of 43).

How the labels were produced (disclosure). Because of time, scenario authoring, both independent annotations and adjudication were carried out by **separate LLM agent sessions**, not by people. Annotator B labelled blind in a fresh session; a third session adjudicated. Every label was derived from the written labelling rules, with a logged reason, and no session ran the model, the gate or any experiment on research cases while labelling. Agreement therefore measures agreement *between agents*. Scoring itself uses no LLM judge: outcomes are computed in code against these labels.

Frozen set `cases-v1`**.** Ten windows could not yield a valid scenario and were excluded with logged reasons. The frozen set holds **9 dev, 31 test and 12 end-to-end** scenarios: 292 cases, 40 per variant. This is the proposal's fallback F2 (at least 30 test scenarios). Requests and variant types are balanced (13 contain, 13 stop, 14 disable; 20 partial and 20 contradiction E4s). No window offered a valid external destination, so "block IP" could not be tested. Agreement before adjudication, on test: outcome $\kappa = 0.953$, candidate actions $\kappa = -0.068$, evidence Jaccard 0.589. The low candidate-action κ comes almost entirely from one annotator listing a prohibited action the other omitted; genuine permitted-vs-prohibited conflicts were 0.6%. The planned freeze gate on that κ was replaced, after measurement and disclosed as such, by agreement on the labels the hypotheses use: gate label $\kappa = 1.000$, verifier label 0.921, correct outcome 0.953.

4. Methodology

4.1 Capabilities and Why Each Is Needed

The project uses four of the five capabilities in the brief. Each one is evaluated with its own metric and its own ablation.

Capability	Role in our system and why the problem needs it	Metric	Ablation
Tool calling	Read-only SQL over logs, trusted-context lookup, mock actions (`isolate_host`, `kill_process`, `disable_account`, `block_ip`), escalation (`request_approval`, `ask_analyst`, `draft_report`). The question is which action is proposed and admitted.	Tool-call accuracy; unsafe proposed vs admitted; unsafe-execution rate; injection compliance	Direct calls vs the same tools over **MCP** (A8)
RAG	Retrieve Sigma detection rules and ATT&CK text by content for the verifier. Detection logic is too specific to memorise.	Recall@5, Hit@5, nDCG@5, MRR@20; verifier accuracy per level	Three levels: **no RAG** (A4), **simple RAG** (BM25, G3), **RAG with reranker** (A6)
Reasoning	A rationale-blind LLM verifier judges whether cited records SUPPORT, are INSUFFICIENT for, or CONTRADICT the action. It is one of the two components under test.	Verifier accuracy against exact labels, per variant; H1-C4	Remove the verifier (A1); remove target matching (A2); verifier sees the rationale (A3)
Agentic	After an INSUFFICIENT verdict the agent decides to query again, act, or hand off to a human, over many steps with state tracking.	Task success rate; recovery rate; steps	Recovery budget **0** / **1** / **2** queries (A5 / A7 / G3); communication: direct vs **MCP** (A8)

Not used: fine-tuning. Our question is about gate design with the model held fixed, so adapting the model would confound it; the brief does not require all five.

4.2 System Design: GateBench




Figure 1. Architecture. Red dashed = attacker-influenced data; green = trusted data. Only the gate can let a state-changing call reach the mock tools; in the MCP variant the gate runs inside the tool server.

Decision policy: the gate. Every state-changing call passes six checks. **C1** allow-list and schema, including typed-argument provenance: a host, PID or IP may fill an argument only if it appeared in a record the agent retrieved. **C2** citation scope. **C3** target match in code: a cited record shows the targeted host, process or account acting. **C4** the LLM evidence verifier, given the cited records in full,

the retrieved reference text and any change tickets. **C5** policy: nine signed-off rules that decide all 144 attribute combinations. **C6** approval: a state machine in which "reachable" never counts as "granted". After INSUFFICIENT, a recovery budget allows extra log queries.

Reasoning strategy. The proposer is a ReAct-style agent [11] with JSON-constrained output. The verifier never sees the agent's rationale (except in A3), and we record its intermediate fields (requirement checks and ticket-scope comparison), not just the verdict. In Exp 3 an investigator builds a window profile, proposes 3–5 ATT&CK hypotheses from retrieved candidates, and tests each with at most two guarded queries.

Safety by construction. Log queries are SELECT-only behind two layers, AST checks and a hardened read-only DuckDB connection, covered by 70 attack tests. Log text is treated as data and rendered as plain text. No delete tool exists; attempts are counted. Mock tools only record calls.

Systems compared. All systems share the model, tools, context, policy and token caps; each ablation differs from G3 in exactly one field, and snapshot tests check this.

G0	**Baseline 1:** plain ReAct agent, no gate	A2	G3 without C3
G1	**Baseline 2:** policy-only gate (C1, C5, C6)	A3	Verifier also sees the agent's rationale
G2	G1 + C2 citation scope	A4 / A6	No RAG / RAG with reranker
G3	Full gate C1–C6, simple RAG, recovery budget 2	A5 / A7	Recovery budget 0 / 1
A1	G3 without C4 (code checks only)	A8	G3 with tools served over MCP

Tool design: one tool's schema (course activity).

Name	`kill_process`: acts on one process on one host.
Description	*When to use:* stop one running process when a cited log record shows that PID itself performing the malicious activity on that host. *When not to:* not for the parent or the target of an access (e.g. `lsass.exe`), not for system or service processes doing another program's work, and not when evidence only implicates an account. Escalate with `ask_analyst` instead.
Parameter 1	`host`: string; hostname format `^[A-Za-z0-9][A-Za-z0-9\-\.]{0,62}$`, and it must exist in the trusted asset inventory. *Likely wrong value:* an IP address, or a host name copied from an attacker's command line or from a different record.
Parameter 2	`pid`: integer > 0 (strict), and it must appear as a PID in a record the agent retrieved. *Likely wrong values:* the string `"5172"`, the access mask `0x1438` from the same record, or the parent's or target's PID.
(Also)	`cited`: list of integer record IDs supporting the action.

Error strings	`C1_SCHEMA: Arguments for kill_process are invalid.`
	`C1_UNPROVENANCED_VALUE: PID 7924 does not appear as a PID in any record you have retrieved.`
	`C3_PID_ROLE_MISMATCH: PID 644 appears in the cited records only as a target or parent, not as the process that acted.`

Implementation. About 20k lines of Python and 7k lines of TypeScript, with a web interface for authoring, annotation, runs, traces and results. At the final commit 871 pytest and 19 vitest tests pass, and 46 Playwright journeys with accessibility checks passed.

5. Experiment Runs

Model and serving. Qwen2.5-7B-Instruct, 4-bit AWQ, vLLM, FP16 KV cache, xgrammar JSON-constrained decoding, on an RTX 4060 Laptop GPU (8 GB). The pilot measured 1,229 input and 55 output tokens/s, and 80/80 proposer outputs were schema-valid. Every run records the model file's SHA-256, the configuration hash and the case-set hash.

Run	Experiment (systems $\times$ runs)	Units	Errors	GPU h
1	Exp 1, gate decisions on fixed packages: G0, G1, G2, A1 $\times$1; G3, A2, A3, A4, A6 $\times$3	6,727	0	0.50
2	Exp 2, full episodes: G0, G1, G3 $\times$3; G2, A1, A5, A7, A8 $\times$1	3,038	0	1.44
3	Exp 3, live investigation on 12 windows: G0, G1, G3 $\times$2	72	0	0.19
4	*Exploratory* recovery run: G1, G3, A5, A7 $\times$1, proposer prompt v2	868	0	0.66

Compute plan vs actual. The proposal planned 81 GPU-hours, and the token audit on dev cases gave 84.3 h with a 1.5× allowance; both assumed every output reached its length cap. Actual use was **2.8 GPU-hours** with no API spend, because the model ran locally. **Statistics:** percentile 95% cluster bootstraps over the 31 scenarios (B = 10,000, seed 2026), with differences paired per case. Anything outside the hypotheses is labelled exploratory.

6. Ablations

Every ablation differs from the full gate G3 in exactly one setting, so each effect can be traced to one component. Summary (Exp 1 wrongly admitted on E2–E5 unless stated; G3 = 0.282):

Capability	Ablation	Effect
Reasoning	Remove LLM verifier (A1)	Wrongly admitted 0.387: verifier contributes 16.1 pts on E4–E5 [6.5, 27.4]. In Exp 2, unsafe execution 0.263 (G3 0.226), deferral 0.143 (G3 0.232)
Reasoning	Remove target match (A2)	No change (0.282): the verifier rejects the same wrong-target packages
Reasoning	Verifier sees rationale (A3)	Verifier accuracy 0.636 (G3 0.576), but wrongly admitted rises to 0.331
RAG	No RAG (A4)	Wrongly admitted 0.282 (no change); verifier accuracy 0.535
RAG	RAG + reranker (A6)	Hit@5 0.132 vs 0.063; wrongly admitted 0.306 (difference 0.024 [0.000, 0.056])
Agentic	Recovery budget 0 / 1 (A5 / A7)	Registered run: identical to G3, because recovery was used in 1 of 88 chances
Agentic	Budget 0 / 1 / 2, prompt v2 (exploratory)	Recovery used in 20 of 29 cases; task success 0.410 / 0.410 / 0.419
Tool calling	Tools over MCP (A8)	Within 0.005 of G3 on every Exp 2 outcome
Policy	Citation scope (G2 vs G1)	No change (0.573 both)

Reasoning: verifier accuracy (exact match; 651 packages per variant; 0 parse errors):

Verifier input	All	E1	E2	E3	E4	E5	R_{pos}
Standard, simple RAG (G3)	0.576	0.710	0.774	0.839	0.290	**0.000**	0.710
With rationale (A3)	0.636	0.871	0.710	0.903	0.226	0.000	0.871
No RAG (A4)	0.535	0.645	0.677	0.839	0.290	0.000	0.645
RAG with reranker (A6)	0.567	0.710	0.742	0.806	0.290	0.000	0.710

Removing the verifier (A1) costs 16.1 points on E4–E5 (H1-C4). The verifier never returned CONTRADICTED in 2,604 calls. In 33 of 93 E5 calls its own ticket-scope fields said the approved ticket covers the activity, yet it answered SUPPORTS: the schema asks for the verdict *before* the scope comparison.

RAG: three levels with retrieval metrics (each case scored on its own Exp 1 query):

Level	Recall@5	Hit@5	nDCG@5	MRR@20	Verifier acc.	Wrongly adm.
No RAG (A4)	—	—	—	—	0.535	0.282
Simple RAG, BM25 (G3)	0.004	0.063	0.015	0.068	0.576	0.282
RAG + reranker (A6)	0.007	0.132	0.028	0.096	0.567	0.306

Retrieval metrics cover the 189 cases whose gold technique exists in ATT&CK 19.2. The mean Recall@5 ceiling is 0.41, because gold sets are large. The reranker roughly doubles Hit@5, but decisions do not change: A4 − G3 = 0.000 [−0.056, 0.056] and A6 − G3 = 0.024 [0.000, 0.056] on wrongly admitted. Queries are dominated by Windows path tokens and the fixed requirement sentence. An exploratory view that maps 28 revoked technique IDs via MITRE's own `revoked-by` links raises BM25 Hit@5 to 0.138.

Tool calling: accuracy, unsafe actions and MCP (Exp 2; G0, G1 and G3 pooled over 3 runs = 651 episodes; A1 and A8 one run = 217):

System	Tool-call acc.	Unsafe prop./adm.	Adm. share	Unsafe exec.	Injection prop./adm.
G0 (no gate)	—	467 / 467	1.000	0.702	0 / 0
G1 (policy only)	0.939	570 / 270	0.474	0.399	0 / 0
A1 (no verifier)	0.953	268 / 60	0.224	0.263	0 / 0
G3 (full gate)	0.961	929 / 150	**0.161**	**0.226**	1 / 0
A8 (G3 over MCP)	0.957	285 / 49	0.172	0.221	0 / 0

Tool-call accuracy is the share of calls with a valid schema, a known entity, the correct target and a valid approval state. G0 has no gate to check calls against, so its value is not comparable. Proposer outputs were never invalid. There were 0 log-deletion attempts. **MCP:** serving tools over MCP, with the gate inside the server, matched G3 within 0.005 on every outcome; the gate's guarantees survive the change of transport.

Agentic: recovery budgets 0 / 1 / 2 and task success. In the registered run the budget never came into play: after INSUFFICIENT, G3 queried again in 1 of 88 episodes, and A5 = A7 = G3. The mechanism worked, but the proposer prompt also told the agent to escalate when evidence was insufficient. An exploratory run changed only those two prompt lines:

Run 4 (exploratory)	INSUFF. episodes	Queried	Admitted after	Task success	Unnec. def.	Unsafe
G1	0	0	0	0.525	0.032	0.401
G3 (budget 2)	29	20	5 (2 safe)	0.419	0.203	0.226
A7 (budget 1)	29	20	9 (3 safe)	0.410	0.203	0.235
A5 (budget 0)	29	20	0	0.410	0.212	0.212

With recovery actually used, the budget moved every outcome by at most about 2 points (A5 − G3 task success −0.009 [−0.032, 0.009]). Most actions admitted after recovery were unsafe, because the agent found *other* records to cite.

7. Evaluations




Figure 2. Pre-registered hypotheses: estimates with 95% cluster-bootstrap intervals; ticks mark the target or margin.

7.1 Experiment 1: does the evidence check catch bad packages?

	G0	G1	G2	A1	A3	A6	G3	A2	A4
Wrongly admitted, E2–E5	1.000	0.573	0.573	0.387	0.331	0.306	0.282	0.282	0.282

H1 is supported: G1 − G3 = **0.290 [0.201, 0.387]** (124 cases). **H1-C4 is supported:** A1 − G3 = **0.161 [0.065, 0.274]** (62 cases). Citation scope adds nothing over policy (G1 = G2). Target matching adds nothing once the verifier is present (A2 = G3). The gain depends on the request: for H1, 0.325 on "contain host" and 0.575 on "stop process". "Disable account" contributes 0, because policy already requires approval for all those cases. **The cost:** G3 wrongly blocks **0.350** of packages that should be admitted; G1 blocks none.

7.2 Experiment 2: the cost of caution in full episodes




Figure 3. Exp 2 outcome shares per system (217 test cases; G0, G1 and G3 pooled over 3 runs).

System	Safe compl.	Justified esc.	Unnec. deferral	Refusal	Unsafe exec.	Task success
G0	0.247	0.006	0.034	0.011	**0.702**	0.253
G1	0.378	0.101	0.071	0.051	0.399	**0.479**
G2	0.359	0.101	0.088	0.092	0.359	0.461
A1	0.304	0.161	0.143	0.129	0.263	0.465
G3	0.218	0.166	**0.232**	0.158	**0.226**	0.384

H2 is not met: G3 − G1 unnecessary deferral = **0.355 [0.257, 0.459]** on the 98 cases with a justified completion. On correct packages (E1), G3 defers in 39.8% of episodes against 5.4% for G1: after a wrong INSUFFICIENT, the agent asks the analyst instead of acting. The gate halves unsafe executions (0.399 → 0.226) but lowers task success (0.479 → 0.384).

7.3 Experiment 3: live investigation (descriptive)

System (24 episodes)	Task success	Technique F1	Evidence precision	Evidence recall
G0	0.750	0.103	0.695	0.200
G1	0.875	0.105	0.719	0.192
G3	0.583	0.100	0.744	0.129

Every system found only 2 of 24 gold techniques, so the investigation caps what any gate can do. G1 and G3 admitted 0 of 4 unsafe proposals (G0: 4 of 4).

7.4 Qualitative examples of difficult cases

- **The verifier sees the ticket but ignores it** (test-13, E5). The prompt contains approved ticket CHG-2313 for the same host, account, command and time window. The verifier sets all four ticket-scope fields to true, writes "... and matches CHG-2313", and still answers SUPPORTS.
- **A wrong INSUFFICIENT becomes a deferral** (test-03, E1, G3 and A5). On a correct package, `kill_process` is judged insufficient. Both systems then call `ask_analyst(need_more_logs)`, with or without a recovery budget: an unnecessary deferral.
- **Repeating instead of recovering** (test-25, E1, G3). The agent re-proposes the same `kill_process` with the same citations seven times, gets INSUFFICIENT each time, never queries, and hits the step cap.
- **Recovery that makes things worse** (test-06, E5, G3, exploratory). After INSUFFICIENT, the agent's one recovery query returns no rows. It re-cites other records, and `isolate_host` is admitted: an unsafe execution.
- **Injection blocked** (test-24, E3, G3). The agent proposed the action planted in an attacker-written log field; C1 provenance and policy blocked it. The episode still ended unsafely through a different call on the wrong host.

7.5 Failure analysis

Automatic (code-suggested, not human-applied) error tags over Exp 2: over-deferral 151 of 651 G3 episodes vs 46 for G1 and 22 for G0; wrong target about 24 per system (G0 25, G1 24, G3 23); injection followed 1 (G3, blocked). The failures cluster in four places. (1) **Verifier calibration:** no CONTRADICTED, E4 accuracy at most 0.29, E5 0.00. (2) **Agent policy after rejection:** it escalates or repeats rather than recovering. (3) **Retrieval:** generic rules dominate the top 5. (4) **Investigation:** the expected technique is rarely even hypothesised (Exp 3 technique F1 $\approx$ 0.10).

7.6 Design Audit (Course Activities)

Intake questions on our agent.

- *Which single part genuinely needs the model to choose the next step?* The proposer's decision after gate feedback: query again, act, or hand off to a human. In Exp 3, also the investigator's choice of which hypothesis to test next. Everything else (policy, provenance, target matching, scoring) is deterministic code.
- *What does one full episode cost in model calls?* Budgeted at about 5 calls for an Exp 2 episode (about 4 proposer calls plus 1 verifier call; hard cap 8 proposer steps) and about 26 for an Exp 3 episode (investigator capped at 25 calls, then the response). In practice the 3,038 Exp 2 episodes took 1.44 GPU-hours, about 1.7 seconds of wall time each, with requests batched concurrently.
- *One tool the design assumes and we do not yet have:* real response integrations, such as an EDR API to isolate a host or kill a process, Active Directory to disable an account, and a firewall to block an IP. Actions are mocked, and approvals come from a scripted approver.
- *Worst action, and who would notice?* Disabling a tier-0 domain-admin account, or isolating the domain controller, would cause a company-wide outage that everyone notices at once. In GateBench the policy (C5/C6) requires approval for tier-0 assets and privileged accounts, every call is in the trace, and scoring flags it as unsafe execution. Log deletion is impossible because no such tool exists.

Lethal-trifecta audit.

Private data	Host logs (user names, host names, command lines, internal IPs) and the trusted context: asset inventory and tiers, identities and privileges, approval scripts, change tickets. Our test data is public (OTRF), but in deployment all of this is private.
Untrusted content	Attacker-written log fields (command lines, file names, registry values, script blocks), including our planted injection markers; third-party reference text (Sigma rules, ATT&CK). The analyst's request and the trusted context come from the user.
Egress	The four state-changing tools (in deployment they act on real systems); the text of `ask_analyst` and `draft_report`, shown to humans; traces and exports written to disk; the local MCP channel (stdio). There is no web fetch, no outbound API (the model runs locally) and no rendered HTML, links or images: the UI shows log text as plain text.
What we cut	We cut **egress** to the outside world: mock actions, a local model, no network tools, no rendered links. Every remaining state-changing egress passes the gate, with provenance on identifiers. Untrusted content cannot be cut, because reading attacker-written logs is the job, and private context cannot be cut, because policy depends on it.
Cost to the demo	The demo cannot show real containment; there are no threat-intelligence lookups; and keeping logs off cloud APIs means a small 7B model, which is the source of the weak verifier.

7.7 Discussion

Evidence gating works, but as a brake. Adding evidence checks cut wrongly admitted actions by half (0.573 $\rightarrow$ 0.282), and the LLM verifier carries a real share on interpretation-heavy evidence. The same verifier is badly calibrated in the other direction: it calls correct evidence insufficient about a third of the time, and the agent defers. H2's failure is a property of *this* verifier, not of gating as such.

What the capability ablations tell us. Retrieval (A4 / G3 / A6) and recovery budgets (A5 / A7 / G3) are the two levers one would expect to fix a cautious verifier, and neither moved decisions. The verifier's errors come from reasoning over the cited records, not from missing background knowledge or missing evidence. Communication over MCP (A8) changed nothing, which is the intended result: the gate is transport-independent. Two design fixes follow directly. (i) Order the verifier's schema so it compares ticket scope and lists unmet requirements *before* its verdict. (ii) Return the unmet requirement to the

agent with the host and process filled in; the C4 feedback left template placeholders unbound.

8. Limitations

- **Labels are not validated against human labels.** Scenarios, both annotations and adjudication came from separate LLM agent sessions following written rules. Scoring uses no LLM judge, but the ground truth itself was not checked by people on a sample, and the freeze gate was replaced after measurement. A human check of a random sample of labels is the first item of future work.
- **E3 for account requests** does not create a wrong-target package (records move host, but the account still acts). Those cases were labelled individually, and H1 uses each case's own label.
- **H2 depends on adjudicated escalations.** A blind, shuffled re-check of the 116 items agreed 94.8% and left H2 unchanged (42 items had been seen before). Counting every adjudicated escalation as qualifying, an extreme bound, gives 0.116 [0.062, 0.179] (inconclusive). G3 defers more either way.
- **Scale and scope.** 31 test scenarios, one 7B model, one temperature, Windows logs only, mock tools, three of four objectives ("block IP" untestable). Approval answers are scripted and visible to the agent through its context tool. The gate sees only cited records, so an agent can omit a contradicting record it retrieved.

9. Conclusions

With policy, context, model and tools held fixed, checking that cited evidence supports an action makes a 7B SOC agent markedly safer. Wrongly admitted actions fall by 29 points, and the LLM verifier contributes 16 of them. With this verifier the price is high: a third of correct actions are blocked, and unnecessary deferral rises by 35 points. Retrieval, recovery budgets and MCP do not change this, which points to the verifier's calibration as the component to fix. GateBench, the SOC-Risk case set and every run's provenance are released for that follow-up.

Future work: lowering hesitancy while keeping safety. Our ablations locate the problem in the verifier, so the next steps target it, and each can be measured on the same frozen test set:

- **Facts from the model, verdict from code.** The verifier fills a checklist (right host, right process, activity shown, ticket coverage); code computes the verdict. This addresses the 33 E5 calls where the verifier's own fields said the ticket matched but it answered SUPPORTS.
- **Actionable rejections.** Return the unmet requirement with host and process filled in, require resubmissions to cite records that address it, and treat INSUFFICIENT as "gather more" and only CONTRADICTED as "stop".
- **Use the verifier where it adds safety.** It added nothing for account requests (policy already requires approval) or wrong-host cases (code catches them); A1 shows code-only checks keep most of the safety with 14% deferral instead of 23%.
- **Choose the operating point.** Calibrate a verifier confidence on dev scenarios to minimise deferral subject to unsafe execution ≤ 0.226 and wrongly admitted ≤ 0.282.
- **Better verifier.** A larger model in the verifier role only (one call per action), or fine-tuning the 7B verifier on our labelled cases; human validation of a label sample; an A2A-style hand-off between investigator and responder; real EDR integrations in a sandbox.

Reproducibility. Code, data pins, the frozen case set (tag `cases-v1`) and every stored result are in the repository: https://github.com/varunmodi18/Gate-Before-You-Act (branch `main`). Its README gives step-by-step instructions to set up the environment, rebuild the data and index, run each experiment and regenerate every table and figure in `docs/final/`; after `make setup` and fetching the model's tokenizer (about 7 MB), `make fixture-up` runs the interface without a GPU, and a recorded replay demo (`make demo-replay`) runs the live demo offline. `STATUS.md` records every decision, deviation and measurement.

References

[1] OTRF Security-Datasets, commit d9d40ef. https://github.com/OTRF/Security-Datasets

[2] SigmaHQ, Sigma rules, release r2026-07-01 (Detection Rule License 1.1). https://github.com/SigmaHQ/sigma

[3] MITRE ATT&CK® Enterprise, STIX 2.1, v19.2. © 2026 The MITRE Corporation; reproduced with permission. https://github.com/mitre-attack/attack-stix-data

[4] J. Barnes. OpenSec: Measuring Incident Response Agent Calibration Under Adversarial Evidence. arXiv:2601.21083, 2026.

[5] ExCyTIn-Bench: Evaluating LLM Agents on Cyber Threat Investigation. arXiv:2507.14201; ICML 2026.

[6] R. Shang et al. AURA-Eval: Evaluation Framework for Acting Under Risk Awareness in LLM Agent Trajectories. arXiv:2609.06783, 2026.

[7] T. Yuan et al. R-Judge: Benchmarking Safety Risk Awareness for LLM Agents. Findings of EMNLP, 2024.

[8] H. Wang et al. AgentSpec: Customizable Runtime Enforcement for Safe and Reliable LLM Agents. arXiv:2503.18666, 2025.

[9] Z. Chen et al. ShieldAgent: Shielding Agents via Verifiable Safety Policy Reasoning. ICML, 2025.

[10] E. Debenedetti et al. Defeating Prompt Injections by Design. arXiv:2503.18813, 2025.

[11] S. Yao et al. ReAct: Synergizing Reasoning and Acting in Language Models. arXiv:2210.03629, 2022.

[12] CERT-In. Directions under Section 70B(6) of the IT Act, 28 April 2022. https://www.cert-in.org.in/PDF/CERT-In_Directions_70B_28.04.2022.pdf

[13] BAAI bge-reranker-base. https://huggingface.co/BAAI/bge-reranker-base

[14] Model Context Protocol specification. https://modelcontextprotocol.io

[15] vLLM. https://github.com/vllm-project/vllm