

CPG Analytics — Master Index

Maps every step from customer data to deployed experience, with the spec document that governs it.

Refresh this file whenever scope or spec changes.

Last updated: 2026-06-29

Step	Activity	Spec Doc	What We Are Doing
1	Customer provides raw data	<i>(outside spec)</i>	Receive fact tables + dimension tables (sales hierarchy, product, geography, users)
2	Build semantic layer on Cube.js	spec/12 · metric-registry.yaml	Map fact table columns to named measures. Define every metric the business can compute. RBAC wired here.
3	Curate persona cards <i>(vendor IP)</i>	spec/10 · asm.card.yaml · nsm.card.yaml	For each role encode job, hierarchy, grain, primary + secondary KPIs, insight types, questions, actions, cold-start slots.
4	Define preference catalog	spec/11 · catalog.yaml	Every disambiguation slot (sales type, measure unit, comparison period etc.) mapped to metrics/filters. Role defaults pre-filled.
5	Define insight rules	spec/13 · insight-rules.yaml	Deterministic checks on metrics. Risk, Opportunity, Anomaly, Driver. Thresholds, variance, z-score triggers.
6	Define home layout	spec/14 · nsm.home.yaml	Ordered sections for each role's home page. Summary, KPI strip, insight list, actions, questions, chart.
7	Tenant onboarding <i>(customer deploys)</i>	spec/20 §1–3 · Tier 2	Buyer assigns each user to a persona card. Inject their real RBAC scope (region,

Step	Activity	Spec Doc	What We Are Doing
			area, distributor). Override thresholds if needed.
8	Runtime resolution at login	spec/20 §1–4 · Tiers 1, 2, 3	At login: load card (Tier 1) + apply tenant binding (Tier 2) + user choices (Tier 3). Resolve all preference slots.
9	Experience generation <i>(scheduler runs per user)</i>	spec/00 · spec/20 §6–8	Query Cube.js (RBAC-filtered) → run insight rules → score confidence + priority → attach actions + questions → build home via layout → LLM writes the words → store payload.
10	User logs in <i>(render)</i>	spec/14 · spec/20 §8	Fetch stored payload. Render 4 stages: Dashboard → Insights → Actions → Chat.
11	User asks a question <i>(chat / investigation)</i>	spec/20 §4–5 · spec/10 job_description	Scope check (RBAC + job) → curated question fast path OR free-text NLU → Cube.js query → LLM narrates answer.

Governing rule across all steps: Facts are deterministic (Cube.js + SQL). Language is intelligent (LLM narrates only). See [spec/00](#).