

# Learn Python: Modules

## Date and Time in Python

Python provides a module named `datetime` to deal with dates and times.

It allows you to set `date`, `time` or both `date` and `time` using the `date()`, `time()` and `datetime()` functions respectively, after importing the `datetime` module.

```
import datetime
feb_16_2019 = datetime.date(year=2019,
                             month=2, day=16)
feb_16_2019 = datetime.date(2019, 2, 16)
print(feb_16_2019) #2019-02-16

time_13_48min_5sec =
datetime.time(hour=13, minute=48,
              second=5)
time_13_48min_5sec = datetime.time(13, 48,
                                     5)
print(time_13_48min_5sec) #13:48:05

timestamp= datetime.datetime(year=2019,
                              month=2, day=16, hour=13, minute=48,
                              second=5)
timestamp = datetime.datetime(2019, 2, 16,
                              13, 48, 5)
print (timestamp) #2019-01-02 13:48:05
```

## Aliasing with 'as' keyword

In Python, the `as` keyword can be used to give an alternative name as an alias for a Python module or function.

```
# Aliasing matplotlib.pyplot as plt
from matplotlib import pyplot as plt
plt.plot(x, y)

# Aliasing calendar as c
import calendar as c
print(c.month_name[1])
```

## Import Python Modules

The Python **import** statement can be used to import Python modules from other files.

Modules can be imported in three different ways:

```
import module, from module import  
functions, or from module import *.
```

`from module import *` is discouraged, as it can lead to a cluttered local namespace and can make the namespace unclear.

```
# Three different ways to import modules:  
# First way  
import module  
module.function()  
  
# Second way  
from module import function  
function()  
  
# Third way  
from module import *  
function()
```

## random.randint() and random.choice()

In Python, the `random` module offers methods to simulate non-deterministic behavior in selecting a random number from a range and choosing a random item from a list.

The `randint()` method provides a uniform random selection from a range of integers. The `choice()` method provides a uniform selection of a random element from a sequence.

```
# Returns a random integer N in a given  
range, such that start <= N <= end  
# random.randint(start, end)  
r1 = random.randint(0, 10)  
print(r1) # Random integer where 0 <= r1  
<= 10  
  
# Prints a random element from a sequence  
seq = ["a", "b", "c", "d", "e"]  
r2 = random.choice(seq)  
print(r2) # Random element in the sequence
```

## Module importing

In Python, you can import and use the content of another file using `import filename`, provided that it is in the same folder as the current file you are writing.

```
# file1 content  
# def f1_function():  
#     return "Hello World"  
  
# file2  
import file1  
  
# Now we can use f1_function, because we  
imported file1  
f1_function()
```