1. Round

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60),
  student_marks int
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in', 90),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in', 80),
('1RUA25BCA1111', 'Vaibhav', 21, 'hijk@rvu.edu.in', 70);
SELECT * FROM STUDENTS;
SELECT student_name,
student_marks,
ROUND(student_marks*1.05)AS Bonus_Marks
FROM STUDENTS;
```

I/O | AI Agent — 91 ms

STDIN

Input for the program (Optional)

Output:

```
+-------------+--------------+-------------+-----------------+--------------+
| student_usn | student_name | student_age | student_email   | student_marks |
+-------------+--------------+-------------+-----------------+--------------+
| 1RUA25BCA0010 | Varun        |          20 | efgh@rvu.edu.in |           80 |
| 1RUA25BCA0060 | Manu         |          19 | abcd@rvu.edu.in |           90 |
| 1RUA25BCA1111 | Vaibhav      |          21 | hijk@rvu.edu.in |           70 |
+-------------+--------------+-------------+-----------------+--------------+
+--------------+---------------+-------------+
| student_name | student_marks | Bonus_Marks |
+--------------+---------------+-------------+
| Varun        |            80 |          84 |
| Manu         |            90 |          95 |
| Vaibhav      |            70 |          74 |
+--------------+---------------+-------------+
```

2. CEIL

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60),
  student_marks int
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in', 90),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in', 80),
('1RUA25BCA1111', 'Vaibhav', 21, 'hijk@rvu.edu.in', 70);
SELECT * FROM STUDENTS;
SELECT student_name,
student_marks / 10.0 AS Marks_Value,
CEIL(student_marks / 10.0) AS Rounded_Up
FROM STUDENTS;
```

I/O | AI Agent — 118 ms

STDIN

Input for the program (Optional)

Output:

```
+-------------+--------------+-------------+-----------------+--------------+
| student_usn | student_name | student_age | student_email   | student_marks |
+-------------+--------------+-------------+-----------------+--------------+
| 1RUA25BCA0010 | Varun        |          20 | efgh@rvu.edu.in |           80 |
| 1RUA25BCA0060 | Manu         |          19 | abcd@rvu.edu.in |           90 |
| 1RUA25BCA1111 | Vaibhav      |          21 | hijk@rvu.edu.in |           70 |
+-------------+--------------+-------------+-----------------+--------------+
+--------------+-------------+------------+
| student_name | Marks_Value | Rounded_Up |
+--------------+-------------+------------+
| Varun        |      8.0000 |          8 |
| Manu         |      9.0000 |          9 |
| Vaibhav      |      7.0000 |          7 |
+--------------+-------------+------------+
```

3.FLOOR

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60),
  student_marks int
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in', 90),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in', 80),
('1RUA25BCA1111', 'Vaibhav', 21, 'hijk@rvu.edu.in', 70);
SELECT * FROM STUDENTS;
SELECT student_name,
student_marks / 10.0 AS Marks_Value,
FLOOR(student_marks / 10.0) AS Rounded_Down
FROM STUDENTS;
```

I/O | AI Agent — 87 ms

STDIN

Input for the program (Optional)

Output:

```
+-------------+--------------+-------------+-----------------+--------------+
| student_usn | student_name | student_age | student_email   | student_marks |
+-------------+--------------+-------------+-----------------+--------------+
| 1RUA25BCA0010 | Varun        |          20 | efgh@rvu.edu.in |           80 |
| 1RUA25BCA0060 | Manu         |          19 | abcd@rvu.edu.in |           90 |
| 1RUA25BCA1111 | Vaibhav      |          21 | hijk@rvu.edu.in |           70 |
+-------------+--------------+-------------+-----------------+--------------+
+--------------+-------------+--------------+
| student_name | Marks_Value | Rounded_Down |
+--------------+-------------+--------------+
| Varun        |      8.0000 |            8 |
| Manu         |      9.0000 |            9 |
| Vaibhav      |      7.0000 |            7 |
+--------------+-------------+--------------+
```

4. MOD

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60),
  student_marks int
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in', 90),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in', 80),
('1RUA25BCA1111', 'Vaibhav', 21, 'hijk@rvu.edu.in', 70);
SELECT * FROM STUDENTS;
SELECT student_name,
student_marks,
MOD(student_marks, 10) AS Remainder
FROM STUDENTS;
```

I/O | AI Agent — 82 ms

STDIN

Input for the program (Optional)

Output:

```
+--------------+--------------+-------------+-----------------+--------------+
| student_usn  | student_name | student_age | student_email   | student_marks |
+--------------+--------------+-------------+-----------------+--------------+
| 1RUA25BCA0010 | Varun        |          20 | efgh@rvu.edu.in |            80 |
| 1RUA25BCA0060 | Manu         |          19 | abcd@rvu.edu.in |            90 |
| 1RUA25BCA1111 | Vaibhav      |          21 | hijk@rvu.edu.in |            70 |
+--------------+--------------+-------------+-----------------+--------------+
+-------------+--------------+----------+
| student_name | student_marks | Remainder |
+-------------+--------------+----------+
| Varun        |           80 |         0 |
| Manu         |           90 |         0 |
| Vaibhav      |           70 |         0 |
+-------------+--------------+----------+
```

5. ABS

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60),
  student_marks int
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in', 90),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in', 80),
('1RUA25BCA1111', 'Vaibhav', 21, 'hijk@rvu.edu.in', 70);
SELECT * FROM STUDENTS;
SELECT student_name,
student_marks,
ABS(student_marks - 70) AS Difference_From_70
FROM STUDENTS;
```

I/O | AI Agent — 86 ms

STDIN

Input for the program (Optional)

Output:

```
+--------------+--------------+-------------+-----------------+--------------+
| student_usn  | student_name | student_age | student_email   | student_marks |
+--------------+--------------+-------------+-----------------+--------------+
| 1RUA25BCA0010 | Varun        |          20 | efgh@rvu.edu.in |            80 |
| 1RUA25BCA0060 | Manu         |          19 | abcd@rvu.edu.in |            90 |
| 1RUA25BCA1111 | Vaibhav      |          21 | hijk@rvu.edu.in |            70 |
+--------------+--------------+-------------+-----------------+--------------+
+-------------+--------------+-------------------+
| student_name | student_marks | Difference_From_70 |
+-------------+--------------+-------------------+
| Varun        |           80 |                10 |
| Manu         |           90 |                20 |
| Vaibhav      |           70 |                 0 |
+-------------+--------------+-------------------+
```