1.Count using Aggregate Function

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
    student_usn VARCHAR(20) PRIMARY KEY,
    student_name VARCHAR(60),
    date_of_birth DATE,
    student_age INT,
    student_email VARCHAR(60),
    student_marks INT
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', '2007-05-10', 19, 'manurbca25@rvu.edu.in', 90),
('1RUA25BCA0011', 'Varun', '2006-08-15', 20, 'varunbca25@rvu.edu.in', 80),
('1RUA25BCA0066', 'Vaibhav', '2005-12-20', 21, 'vaibhav@rvu.edu.in', 70);
SELECT COUNT(*) AS Total_Students
FROM STUDENTS;
```

I/O | AI Agent | 85 ms

STDIN

Input for the program (Optional)

Output:

```
+---------------+
| Total_Students |
+---------------+
|             3 |
+---------------+
```

2.Sum using Aggregate Function

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  date_of_birth DATE,
  student_age INT,
  student_email VARCHAR(60),
  student_marks INT
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', '2007-02-03', 19, 'manurbca252rvu.edu.in', 90),
('1RUA25BAC0011', 'Varun', '2007-11-11', 20, 'varunbca25@rvu.edu.in', 80),
('1RUA25BCA0117', 'Vabhav', '2007-02-22', 21, 'vaibhavbca25@rvu.edu.in', 70);
SELECT SUM(student_marks) AS Total_Marks
FROM STUDENTS;
```

I/O | AI Agent | 331 ms

STDIN

Input for the program (Optional)

Output:

```
Total_Marks
-----------
        240
```

3.Average using Aggregate Functions

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  date_of_birth DATE,
  student_age INT,
  student_email VARCHAR(60),
  student_marks INT
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', '2007-02-03', 19, 'manurbca252rvu.edu.in', 90),
('1RUA25BAC0011', 'Varun', '2007-11-11', 20, 'varunbca25@rvu.edu.in', 80),
('1RUA25BCA0117', 'Vabhav', '2007-02-22', 21, 'vaibhavbca25@rvu.edu.in', 70);
SELECT AVG(student_marks) AS Average_Marks
FROM STUDENTS;
```

I/O | AI Agent | 329 ms

STDIN

Input for the program (Optional)

Output:

```
Average_Marks
-------------
           80
```

4.Max Marks using Aggregate Functions

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  date_of_birth DATE,
  student_age INT,
  student_email VARCHAR(60),
  student_marks INT
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', '2007-02-03', 19, 'manurbca252rvu.edu.in', 90),
('1RUA25BAC0011', 'Varun', '2007-11-11', 20, 'varunbca25@rvu.edu.in', 80),
('1RUA25BCA0117', 'Vabhav', '2007-02-22', 21, 'vaibhavbca25@rvu.edu.in', 70);
SELECT MAX(student_marks) AS Highest_Marks
FROM STUDENTS;
```

I/O | AI Agent | 333 ms

STDIN

Input for the program (Optional)

Output:

```
Highest_Marks
-------------
           90
```

5.Lowest Marks using Aggregate Functions

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  date_of_birth DATE,
  student_age INT,
  student_email VARCHAR(60),
  student_marks INT
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', '2007-02-03', 19, 'manurbca252rvu.edu.in', 90),
('1RUA25BAC0011', 'Varun', '2007-11-11', 20, 'varunbca25@rvu.edu.in', 80),
('1RUA25BCA0117', 'Vabhav', '2007-02-22', 21, 'vaibhavbca25@rvu.edu.in', 70);
SELECT MIN(student_marks) AS Lowest_Marks
FROM STUDENTS;
```

I/O | AI Agent | 252 ms

STDIN

Input for the program (Optional)

Output:

```
Lowest_Marks
------------
          70
```