1. Upper

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60)
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Abcd', 19, 'abcd@rvu.edu.in'),
('1RUA25BCA0010', 'Efgh', 20, 'efgh@rvu.edu.in'),
('1RUA25BCA1111', 'Hijk', 21, 'hijk@rvu.edu.in');
SELECT * FROM STUDENTS;
SELECT student_name,
UPPER(student_name) AS Uppercase_name
FROM STUDENTS;
```

I/O | AI Agent — 86 ms

STDIN

Input for the program (Optional)

Output:

```
+--------------+--------------+-------------+----------------+
| student_usn  | student_name | student_age | student_email  |
+--------------+--------------+-------------+----------------+
| 1RUA25BCA0010 | Efgh        |          20 | efgh@rvu.edu.in |
| 1RUA25BCA0060 | Abcd        |          19 | abcd@rvu.edu.in |
| 1RUA25BCA1111 | Hijk        |          21 | hijk@rvu.edu.in |
+--------------+--------------+-------------+----------------+
+-------------+---------------+
| student_name | Uppercase_name |
+-------------+---------------+
| Efgh        | EFGH          |
| Abcd        | ABCD          |
| Hijk        | HIJK          |
+-------------+---------------+
```

2. Lower

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60)
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Abcd', 19, 'abcd@rvu.edu.in'),
('1RUA25BCA0010', 'Efgh', 20, 'efgh@rvu.edu.in'),
('1RUA25BCA1111', 'Hijk', 21, 'hijk@rvu.edu.in');
SELECT * FROM STUDENTS;
SELECT student_name,
LOWER(student_name) AS Lowercase_name
FROM STUDENTS;
```

I/O | AI Agent — 91 ms

STDIN

Input for the program (Optional)

Output:

```
+--------------+--------------+-------------+----------------+
| student_usn  | student_name | student_age | student_email  |
+--------------+--------------+-------------+----------------+
| 1RUA25BCA0010 | Efgh        |          20 | efgh@rvu.edu.in |
| 1RUA25BCA0060 | Abcd        |          19 | abcd@rvu.edu.in |
| 1RUA25BCA1111 | Hijk        |          21 | hijk@rvu.edu.in |
+--------------+--------------+-------------+----------------+
+-------------+---------------+
| student_name | Lowercase_name |
+-------------+---------------+
| Efgh        | efgh          |
| Abcd        | abcd          |
| Hijk        | hijk          |
+-------------+---------------+
```

3. Length

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60)
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Abcd', 19, 'abcd@rvu.edu.in'),
('1RUA25BCA0010', 'Efgh', 20, 'efgh@rvu.edu.in'),
('1RUA25BCA1111', 'Hijk', 21, 'hijk@rvu.edu.in');
SELECT * FROM STUDENTS;
SELECT student_name,
LENGTH(student_name) AS Name_length
FROM STUDENTS;
```

I/O | AI Agent — 93 ms

STDIN

Input for the program (Optional)

Output:

```
+--------------+--------------+-------------+----------------+
| student_usn  | student_name | student_age | student_email  |
+--------------+--------------+-------------+----------------+
| 1RUA25BCA0010 | Efgh        |          20 | efgh@rvu.edu.in |
| 1RUA25BCA0060 | Abcd        |          19 | abcd@rvu.edu.in |
| 1RUA25BCA1111 | Hijk        |          21 | hijk@rvu.edu.in |
+--------------+--------------+-------------+----------------+
+-------------+-------------+
| student_name | Name_length |
+-------------+-------------+
| Efgh        |           4 |
| Abcd        |           4 |
| Hijk        |           4 |
+-------------+-------------+
```

4. Concat

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60)
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in'),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in'),
('1RUA25BCA1111', 'Vaibbhav', 21, 'hijk@rvu.edu.in');
SELECT * FROM STUDENTS;
SELECT CONCAT(student_name, '-Age', student_age) AS Student_details
FROM STUDENTS;
```

I/O | AI Agent — 97 ms

STDIN

Input for the program (Optional)

Output:

```
+--------------+--------------+-------------+----------------+
| student_usn  | student_name | student_age | student_email  |
+--------------+--------------+-------------+----------------+
| 1RUA25BCA0010 | Varun       |          20 | efgh@rvu.edu.in |
| 1RUA25BCA0060 | Manu        |          19 | abcd@rvu.edu.in |
| 1RUA25BCA1111 | Vaibbhav    |          21 | hijk@rvu.edu.in |
+--------------+--------------+-------------+----------------+
+-----------------+
| Student_details |
+-----------------+
| Varun-Age20     |
| Manu-Age19      |
| Vaibbhav-Age21  |
+-----------------+
```

5.Substring

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60)
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in'),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in'),
('1RUA25BCA1111', 'Vaibhav', 21, 'hijk@rvu.edu.in');
SELECT * FROM STUDENTS;
SELECT student_name,
SUBSTRING(student_name, 1, 4) AS First_four_characters
FROM STUDENTS;
```

I/O | AI Agent — 85 ms

STDIN

Input for the program (Optional)

Output:

student_usn	student_name	student_age	student_email
1RUA25BCA0010	Varun	20	efgh@rvu.edu.in
1RUA25BCA0060	Manu	19	abcd@rvu.edu.in
1RUA25BCA1111	Vaibhav	21	hijk@rvu.edu.in

student_name	First_four_characters
Varun	Varu
Manu	Manu
Vaibhav	Vaib

6. Trimm

queries.sql

```sql
DROP TABLE IF EXISTS STUDENTS;
CREATE TABLE STUDENTS (
  student_usn VARCHAR(20) PRIMARY KEY,
  student_name VARCHAR(60),
  student_age int,
  student_email VARCHAR(60)
);
INSERT INTO STUDENTS VALUES
('1RUA25BCA0060', 'Manu', 19, 'abcd@rvu.edu.in'),
('1RUA25BCA0010', 'Varun', 20, 'efgh@rvu.edu.in'),
('1RUA25BCA1111', 'Vaibhav', 21, 'hijk@rvu.edu.in');
SELECT * FROM STUDENTS;
SELECT student_name,
TRIM(student_name) AS Trimmed
FROM STUDENTS;
```

I/O | AI Agent — 117 ms

STDIN

Input for the program (Optional)

Output:

student_usn	student_name	student_age	student_email
1RUA25BCA0010	Varun	20	efgh@rvu.edu.in
1RUA25BCA0060	Manu	19	abcd@rvu.edu.in
1RUA25BCA1111	Vaibhav	21	hijk@rvu.edu.in

student_name	Trimmed
Varun	Varun
Manu	Manu
Vaibhav	Vaibhav