Customer Domain API - Design

Overview

The **Customer Service Domain API** provides a set of endpoints that manage core customer-related operations and data. It supports the management of personal details, contact information, addresses, Medicare card details, communication preferences, and other customer-related services and business operations.

Key Entities:

This API handles the following key business functionalities:

- **Customer Information Management**
  - Create, update, and retrieve customer details
  - Advanced people search functionality
- **External Card Management**
  - Add, delete, and retrieve external cards linked to a person
- **Address and Contact Management**
  - Add, update, retrieve, and delete a person's address and contact information
- **Medicare Card Management**
  - Add, update, and delete Medicare card details for a person
- **Communication Preferences**
  - Create and update a person's contact information along with communication preferences
- **Overseas Details Management**
  - Add, update, delete, and retrieve a person's overseas details
- **Student Details Management**
  - Add, update, and delete a person's student details
- **Alerts and Additional Details**
  - Retrieve person alerts and ABD/LHC (Australian-born details / Lifetime Health Cover) information
- **Bupa Contact Management**
  - Create and update a person's Bupa contact details

Technical Product Owner(s): Anbarasan Rajangam

Stakeholders:

The key stakeholders are listed below, for the full list of project stakeholders refer [Project Stakeholders - DotNet Team - Confluence]

Upstream App name	Technical Owner
Apollo	Albert Gouzali / Andre Margono
Cyclops	Anbarasan Rajangam
Batch Jobs	Anbarasan Rajangam
Digital (MyBupa)	Gabriel Lopez, Andy Prince
Facade Services	Anbarasan Rajangam
IVR	Rohit Suvarna
Access Verification	Jonathan Sher

High-Level Integration Diagram



Domain Model

```
{
  "customer": {
    "id": "customer-id",
    "personDetails": {
      "nameTitle": "string",
      "givenName": "string",
      "secondName": "string",
      "familyName": "string",
      "preferredName": "string",
      "nameSuffix": "string",
      "preferredLanguage": "string",
      "birthDate": "DateTime",
      "gender": "string",
      "singleNameOnly": "bool",
      "originCountry": "string",
      "multipleAddresses": "bool",
      "age": "int",
      "personFlags": [
        {
          "id": "long",
          "auditId": "long",
          "flagId": "string",
          "applicableDate": "DateTime",
          "flagValue": "int?",
          "auditTimeStamp": "DateTime?",
          "entityFlagSelectedId": "long?"
        }
      ]
    },
    "communicationDetails": [
      {
        "addresses": [
          {
            "contactId": "long",
            "contactType": "string",
            "contactDetail": "string",
            "addressee": "string",
            "addressLine1": "string",
            "addressLine2": "string",
```

```
            "addressLine3": "string",
            "localityName": "string",
            "state": "string",
            "postCode": "string",
            "addressType": "CommunicationType",
            "inferredCommunicationType": "CommunicationType",
            "countryCode": {
              "code": "string",
              "countryName": "string"
            },
            "customerId": "long?",
            "country": "string",
            "verifiedDate": "DateTime?",
            "latitude": "decimal?",
            "longitude": "decimal?",
            "reliability": "int?",
            "dpid": "string",
            "postalType": "string",
            "addressTypeId": "long?",
            "gnafid": "string",
            "statisticalArea": "long?",
            "hasValidationOverride": "bool",
            "isUnknown": "bool",
            "isValid": "bool",
            "inferredContactId": "long?",
            "inferredCustomerId": "long?"
          }
        ],
        "emails": [
          {
            "email": "string",
            "display": "string",
            "contactId": "long",
            "customerId": "long",
            "locatorTypeId": "long?",
            "verifiedDate": "DateTime?",
            "hasValidationOverride": "bool",
            "isUnknown": "bool",
            "isValid": "bool",
            "auditId": "long",
            "emailType": "CommunicationType",
            "contactType": "ContactType",
            "auditTimestamp": "DateTime?",
            "startDate": "DateTime",
            "endDate": "DateTime?",
            "contactUsageType": "ContactUsageType"
          }
        ],
        "phoneNumbers": [
          {
            "areaCode": "string",
            "nonStandardFunctionality": "string",
            "serviceLineCode": "string",
            "standardFunctionalityCode": "string",
            "number": "string",
            "countryCode": "string",
            "country": "string",
            "contactId": "long",
            "customerId": "long",
            "locatorTypeId": "long?",
            "verifiedDate": "DateTime?",
            "hasValidationOverride": "bool",
            "isUnknown": "bool",
            "isValid": "bool",
            "auditId": "long",
            "phoneNumberType": "CommunicationType",
            "contactType": "ContactType",
            "auditTimestamp": "DateTime?",
            "startDate": "DateTime",
            "endDate": "DateTime?",
            "contactUsageType": "ContactUsageType"
          }
        ],
        "onlineContacts": [
          {
            "isMyBupa": "bool",
            "isOverseas": "bool",
            "isAustralia": "bool",
            "contactDetail": "string",
            "contactId": "long",
            "customerId": "long",
            "locatorTypeId": "long?",
            "verifiedDate": "DateTime?",
            "hasValidationOverride": "bool",
            "isUnknown": "bool",
            "isValid": "bool",
            "auditId": "long",
            "onlineType": "CommunicationType",
```

```
            "contactType": "ContactType",
            "auditTimestamp": "DateTime?",
            "startDate": "DateTime",
            "endDate": "DateTime?",
            "contactUsageType": "ContactUsageType"
          }
        ]
      }
    ],
    "preferences": {
      "communicationPreferences": [
        {
          "contactId": "long",
          "commPrefId": "long",
          "topicId": "int",
          "optOutInd": "bool",
          "locatorTypeId": "long?",
          "timeStamp": "DateTime?",
          "communicationType": "CommunicationType?",
          "startDate": "DateTime",
          "endDate": "DateTime?",
          "locatorTypeName": "string",
          "deliveryMethodId": "int",
          "deliveryMethodDesc": "string",
          "auditTimeStamp": "DateTime",
          "auditId": "long"
        }
      ],
      "cardPreference": {
        "cardType": "HICardPreference"
      },
      "marketingConsent": {
        "marketingConsentType": "MarketingConsentType",
        "startDate": "DateTime?",
        "auditId": "long"
      }
    },
    "visaDetails": {
      "overseasCustomerReferenceId": "long",
      "overseasType": "OverseasPersonType",
      "countryId": "string",
      "visaType": "string",
      "startDate": "DateTime?",
      "endDate": "DateTime?"
    },
    "studentDetails": {
      "studentNumber": "string",
      "institutionId": "string",
      "institutionName": "string",
      "studySummary": {
        "studySummaryId": "long?",
        "endOfStudyYear": "int?",
        "dateLastConfirmed": "DateTime?",
        "lastPeriodConfirmed": "bool"
      },
      "studyPeriods": [
        {
          "studyPeriodId": "long?",
          "systemCreated": "bool?",
          "startDate": "DateTime",
          "endDate": "DateTime?",
          "auditTimestamp": "DateTime?",
          "auditTimestampValue": "long?"
        }
      ]
    },
    "medicareCardDetails": [
      {
        "medicareCardNumber": "long",
        "subNumerateNumber": "int",
        "cardType": "MedicareCardType?",
        "expiryDate": "DateTime?",
        "nameOnCard": "string",
        "medicareCardId": "long?",
        "firstName": "string",
        "surname": "string",
        "initial": "string"
      }
    ],
    "externalCards": [
      {
        "externalCardType": "ExternalCardType",
        "cardNumber": "string",
        "effectiveDate": "DateTime?",
        "expiryDate": "DateTime?",
        "endDate": "DateTime?"
      }
    ],
```

```
216     "alerts": [
217       {
218         "alertId": "long",
219         "alertType": "enumAlertType",
220         "alertCategory": "enumAlertCategory",
221         "isNoteAttached": "bool",
222         "text": "string",
223         "about": "string",
224         "action": "string",
225         "dateCreated": "DateTime",
226         "personId": "long?",
227         "policyId": "long?",
228         "categoryId": "long?",
229         "alertExpiryTrigger": "string"
230       }
231     ],
232     "notes": {
233       "customerInfoId": "long",
234       "severityType": "enumSeverityType",
235       "dateCreated": "DateTime",
236       "personId": "long?",
237       "policyType": "long?",
238       "policyId": "long?",
239       "categoryId": "long?",
240       "groupId": "long?",
241       "sorId": "long?",
242       "textId": "long?",
243       "alertStatus": "int?",
244       "groupDescription": "string",
245       "category": "string",
246       "text": "string",
247       "displayName": "string",
248       "emailEnabled": "bool",
249       "emailTo": "string"
250     },
251     "dataSharingFlags": {
252       "hospitalWaitExemptionFlag": {
253         "hospitalWaitExemption": "bool",
254         "applicableDate": "DateTime?",
255         "managedFlagId": "long?",
256         "operationType": "string",
257         "timeStamp": "DateTime?",
258         "timeStampValue": "string"
259       },
260       "hiClaimsDataSharingFlag": {
261         "hiClaimsDataSharing": "bool",
262         "startDate": "DateTime?",
263         "endDate": "DateTime?",
264         "managedFlagId": "long?",
265         "operationType": "string",
266         "timeStamp": "DateTime?",
267         "timeStampValue": "string"
268       },
269       "hiCardPreferenceFlag": {
270         "cardType": "Enum",
271         "managedFlagId": "long?",
272         "operationType": "string",
273         "timeStamp": "DateTime?",
274         "timeStampValue": "string"
275       },
276       "hiMarketingConsentFlag": {
277         "marketingConsentType": "Enum",
278         "startDate": "DateTime?",
279         "endDate": "DateTime?",
280         "managedFlagId": "long?",
281         "operationType": "string",
282         "timeStamp": "DateTime?",
283         "timeStampValue": "string"
284       }
285     },
286     "digitalIdentity": {
287       "externalIdentityConsent": {
288         "apolloSessionId": "string",
289         "contactId": "string"
290       },
291       "consentForApp": {
292         "personId": "string",
293         "crmContactId": "string",
294         "consentDetails": [
295           {
296             "applicationConsented": "string",
297             "consentValue": "boolean",
298             "consentTemplate": "string",
299             "externalPolicyGuid": "string",
300             "startDate": "string (date-time)",
301             "endDate": "string (date-time)"
302           }
303         ]
```

```
      }
    },
    "paymentDetails": [
      {
        "entityName": "string",
        "accountUse": "string",
        "person": "string",
        "name": "string",
        "id": "string",
        "bankType": "string",
        "accountName": "string",
        "bsbNumber": "string",
        "accountNumber": "string",
        "bankName": "string",
        "branchName": "string",
        "validationDate": "string",
        "tokenisation": "string",
        "tokenReferenceId": "string",
        "tokenCardHolderName": "string",
        "tokenExpiryDate": "string",
        "cardHolderName": "string",
        "maskedCardNumber": "string",
        "cardType": "string",
        "cardExpiryDate": "DateTime",
        "tokenRefID": "string"
      }
    ],
    "products": {
      "description": "string",
      "endDate": "DateTime",
      "identifier": "string",
      "longName": "string",
      "name": "string",
      "productCategoryName": "enum (Hospital | Medical | Extras | Pharmacy | Ambulance | AddOn)",
      "productTypeName": "enum (HealthInsurance)",
      "shortName": "string",
      "startDate": "DateTime",
      "state": {
        "code": "string",
        "stateName": "string",
        "hiMembership": "HIMembership",
        "address": "Address",
        "countryCode": "CountryCode"
      },
      "status": "string",
      "statusReason": "string",
      "package": [
        {
          "code": "string",
          "description": "string",
          "endDate": "DateTime",
          "identifier": "string",
          "longName": "string",
          "shortName": "string",
          "startDate": "DateTime",
          "state": {
            "code": "string",
            "stateName": "string",
            "hiMembership": "HIMembership",
            "address": "Address",
            "countryCode": "CountryCode"
          },
          "status": "string",
          "statusReason": "string",
          "contractPackageAssoc": [
            "ContractPackageAssoc"
          ],
          "familyType": "MembershipCategoryType (enum)"
        }
      ],
      "service": [
        {
          "code": "string",
          "endDate": "DateTime",
          "identifier": "string",
          "name": "string",
          "order": "string",
          "serviceType": "ProductGroupCategory (enum)",
          "claimGroup": [
            {
              "code": "string",
              "identifier": "string"
            }
          ],
          "limit": [
            "Limit"
          ],
```

```
          "memberUsage": [
            "MemberUsage"
          ],
          "claimItem": [
            "ClaimItem"
          ],
          "contractServiceSelection": [
            "ContractServiceSelection"
          ],
          "inclusionType": "InclusionType",
          "hasMemberFirstOptions": "bool",
          "isMemberFirst": "bool"
        }
      ],
      "contractProductAssoc": [
        {
          "prdContractAssocDesc": "string",
          "prdContractAssocEndDate": "DateTime",
          "prdContractAssocEnrolDate": "DateTime",
          "prdContractAssocReason": "string",
          "prdContractAssocReasonCode": "string",
          "prdContractAssocStartDate": "DateTime",
          "prdContractAssocStatus": "string",
          "prdContractAssocStatusCode": "string",
          "contract": "Contract"
        }
      ]
    },
    "authorities": [
      {
        "selfGranted": "bool",
        "onBehalfof": "string",
        "authorisedBy": "string",
        "authorityHolder": "string",
        "relationshipToAuthoriser": "string",
        "type": "string",
        "subType": "string",
        "startDate": "DateTime",
        "endDate": "DateTime",
        "owner": "string",
        "policyId": "string",
        "source": "string",
        "statusReason": "string"
      }
    ]
  }
}
```

Upstream and Downstream Systems

- **Upstream systems:** The following systems shall access Customer Domain API
  - Cyclops
  - Apollo
  - Batch Jobs
  - Facade Services
  - Digital (MyBupa)
  - IVR
  - Access Verification
- **Downstream systems:** The following systems shall be accessed by Customer Domain API
  - Boss
  - Address Validation Service
  - Apollo

Caching

Caching Component Details

Caching Component - Redis

Integration Approach

How to integrate HI.Library.Cache component with domain API

Authentication

Authentication for the Customer Domain API is implemented using **Bearer Token Authentication** (OAuth 2.0 + JWT).

- **Client Applications** obtain an access token from **Microsoft Entra** using either:
  - **User Credentials** (Public Clients), or
  - **Managed Identity** (Confidential Clients).
- The access token **must** include the required permissions as **scopes** or **roles**.
- For every request to the Customer Domain API, the client application must send the access token as a **Bearer token** in the `Authorization` header:

```
Authorization: Bearer <access_token>
```

- The Bearer token is validated, and access to the requested endpoint is granted accordingly.

Authentication Packages

- **Public Client Applications** can use the `BUPA.HI.Authentication` package to:
  - Authenticate users
  - Obtain an access token.
- For **Confidential Clients**, the same package supports:
  - Obtaining tokens using Managed Identity.

Additional References

- **Thick Client to Domain API (Cyclops to Domain API)**
  Thick Client to Domain API (Cyclops to Domain API)- Authentication and Authorization Flow
- **API to API Flow (BFF to Domain API)**
  Authentication and Authorization Flow – DotNet Team - Confluence

Token Validation Logic

The JWT is validated at the **API Management (APIM)** level for every request. Validation checks include:

- Valid Issuer
- Valid Audience
- Token Signature
- Token Lifetime

If any validation fails, the request is rejected with a **401 Unauthorized** response.

> Note: Similar token validation functionality exists within the `BUPA.HI.Authorization` package and can be enabled or disabled via configuration. Currently, this package's token validation is bypassed because tokens are validated at the APIM level.

Client Certificate Handling

- Client applications **must use an SSL certificate** when making requests to the Customer Domain API.
- Certificate validation is performed at the APIM level.
- For details on the client certificate and usage instructions, please refer to the designated **Confluence page**.

  Client Certificate details for Domain API Access

Authorisation

Authorisation Overview

Authorisation is performed based on the **scopes** or **role claims** present in the JWT bearer token of each request. The `BUPA.HI.Authorization` package is utilized by the Customer Domain API to implement the authorisation logic.

How is Authorisation Implemented?

- All applicable permissions such as `CustomerDomainAPI.Create`, `CustomerDomainAPI.Read`, etc., will be initialized for authorisation purposes.
- Endpoints requiring authorisation will be annotated with the `[AuthorizePermission]` custom attribute, specifying the required permission as an argument.
  Example:
  ```
  [AuthorizePermission("CustomerDomainAPI.Read")]
  ```
  This would typically be used on an HTTP GET method.
  Please refer to the complete list of permissions in the Customer Domain API - Design | Per Endpoint Access Rules section.
- When a request is made to an endpoint, the authorisation handlers validate that the required permissions (specified in the `[AuthorizePermission]` attribute) exist within the `scope` or `roles` claim of the JWT.
- If the required claims are present and valid, access to the endpoint is granted. Otherwise, the request is rejected with a **401 Unauthorized** response.

Mapping of Users/Groups to Roles

> **Note:** This section applies to **Public Client Applications** only.

- For **Cyclops**, users will be added to the Azure Entra group:
  `RES-CLD-Cyclops-Hugo-dev-access`
  This group is associated with the App Registration during User Onboarding.
- Similarly, other public client applications (involving user interaction) can have their own groups, which can be assigned to their respective App Registrations.

Per-Endpoint Access Rules

- Each endpoint **must** use the `[AuthorizePermission]` custom attribute provided by the `BUPA.HI.Authorization` package.
- The following permissions apply to the Customer API Endpoints (list to be provided in the detailed API design documentation).

Permission	Applicable HTTP Verb
`CustomerDomainAPI.Read`	`GET`
`CustomerDomainAPI.Create`	`POST`
`CustomerDomainAPI.Update`	`PUT`

`CustomerDomainAPI.Delete`	`DELETE`

Logging

The **Logging component** provides a centralized logging solution for Hugo Domain APIs. It is implemented as a separate class library, enabling seamless integration across microservices as a reusable NuGet package.

- **Package Name:** `Bupa.HI.Logging.Package`
- **Logging Design Documentation:**
  [Logging - Design]

Architecture & Implementation

- Logs are sent to **Azure Application Insights** for centralized monitoring and analysis.
- Uses the `ILogger` interface from **Microsoft.Extensions.Logging** to capture logs across Domain APIs.
- **OpenTelemetry** is leveraged to collect and export logs to Azure Application Insights via the `Azure.Monitor.OpenTelemetry.AspNetCore` package.

Key Logged Fields

Field Name	Description	Field Type
Timestamp	Date and time when the log entry was created.	Telemetry
Message	Main content of the log describing the event or issue.	Telemetry
Severity Level	Severity of the log (Info(1), Warning(2), Error(3), Critical(4)).	Telemetry
Operation ID	Unique identifier for the API request to correlate logs across services.	Telemetry
Operation Parent Id	ID of the parent operation to correlate nested operations (e.g., request & dependencies).	Telemetry
Cloud Role Name	Role name of the cloud service where telemetry data originated.	Telemetry
Method	HTTP method used in the request (GET, POST, PUT, DELETE).	Telemetry / Custom
Path	URL path of the request indicating the accessed endpoint.	Telemetry / Custom
Trace Id	Unique identifier for a single trace.	Telemetry
Item Type	Type of telemetry item (request, exception, trace).	Telemetry
Session ID	Identifier for a user session tracking user actions over a timeframe.	Custom

Customer ID	Unique identifier for a customer.	Custom
CorrelationID	Custom correlation ID to trace and correlate requests/responses across distributed services.	Custom

Log Levels and Retention

Log Level	Description
Information	Informational messages about normal application operation.
Warning	Potential issues or unexpected behaviors that do not disrupt application flow.
Error	Application errors or exceptions preventing specific operations from succeeding.
Critical	Severe errors causing application or critical component failures.

Retention Policy

- Application Insights retains log data for a configurable retention period (90 days).

Exception and Error Handling

Global Exception Handling Pattern

Exceptions are handled using the **Global Exception Handling Middleware** provided by the `BUPA.HI.ExceptionHandling` package.

Mapping Exception Types to HTTP Status Codes

Exception Type	HTTP Status Code	Description
Bad Request	400 Bad Request	The server could not understand the request due to invalid syntax.
Unauthorized	401 Unauthorized	Authentication is required and has failed or has not yet been provided.
Forbidden	403 Forbidden	The client does not have access rights to the content.
NotFound	404 Not Found	The server can't find the requested resource.
RequestTimeout	408 Request Timeout	The server timed out waiting for the request.
Conflict	409 Conflict	The request conflicts with the current state of the server.

PreconditionFailed	412 Precondition Failed	The server does not meet one of the preconditions in the request headers.
Unprocessable Request	422 Unprocessable Entity	The request was well-formed but unable to be followed due to semantic errors.
InternalServerError	500 Internal Server Error	The server has encountered a situation it doesn't know how to handle.
NotImplemented	501 Not Implemented	The request method is not supported by the server and cannot be handled.
BadGateway	502 Bad Gateway	The server received an invalid response from the upstream server.
ServiceUnavailable	503 Service Unavailable	The server is not ready to handle the request, often due to maintenance.
GatewayTimeout	504 Gateway Timeout	The server did not receive a timely response from an upstream server.

Custom Error Schema

Error responses conform to the following JSON schema:

```
{
  "data": {},
  "errors": [
    {
      "code": "string",
      "message": "string",
      "severity": "enum (Possible values: \"NotSet\", \"Information\", \"Warning\", \"Error\")",
      "classification": "enum (Possible values: \"Business\", \"System\")"
    }
  ]
}
```

Request Payload Storage in Application Insights

- When an exception occurs, the **request payload** is **encrypted** and stored in **Application Insights** as a property within the custom dimensions.
- Sensitive values are securely stored in **Azure Key Vault**.

Handling Custom Correlation Id (`X-Correlation-Request`)

- If a custom correlation ID is **not present** in the HTTP request header, the exception handling middleware **generates one** and assigns it to the header.
- If a correlation ID **already exists**, the middleware logs the exception in Application Insights using the **existing correlation ID**.

API Performance and Capacity Metrics

Metric Type	Metric	Value

Functional Load	Error rate [Failed requests per minute]	6/hour or .1/minute
	Availability [System uptime percentage]	100%
Latency	Average response time	500 ms
	90th percentile	1 sec
	Worst case	1.5 sec
Throughput	Average requests per minute	2000 calls/min
	Peak requests per minute	5000 calls/min
	Each endpoint requests per minute	100 calls/min
Rate limiting and throttling	Rate limited on the API Level	1000 requests per IP/min
Expected Resource Use	Limits: Memory	1Gi
	Requests: CPU	400m
	Requests: Memory	750Mi
	HPA Configuration: Min Replicas	6
	HPA Configuration: Max Replicas	10

Infrastructure and Deployment Design

At the API level, define

- AKS namespace and container info:
  - Namespace: **hicbocoreservices-{env}-ns**
  - Container: **hi-api-customer**
- Ingress/APIM setup
  - APIM API Name - **hicustomerdomain/{env}**
- ConfigMap and Secret usage
  - Library Variable Group: **hicbocoreservices-customer-api-{env}-vars**
- Infrastructure CI/CD pipeline details:
  - **<To be Provided later>**
- Environment strategy (Dev, T27, Prod, etc.)
  - DEV: **d24**, SIT: **d34**, PERF: **t33**, UAT:**euat**, PROD: **Prod**

Observability

AppDynamics/App Insights Integration Setup

- AppDynamics Tier/node mapping: NA
- AppDynamics Custom business transactions and metrics: NA
- App Insights: **hicbocoreservices-{env}-ai01**

AppDynamics/AppInsights Alerts

- CPU/memory/error rate thresholds: Api Alerts
- Notification channels: ServiceNow Ticket and Email Alert to dotnet support team.

Repository and Pipelines

Details	Link
Git repository	Bupa.HI.Customer.Api - Repos
Branching strategy	Branching Strategy for .NET based projects - DotNet Team - Confluence
Build and release pipelines	Pipelines - Runs for Bupa.HI.Customer.Api
Security scans, tests, validations	https://anz.ast.checkmarx.net/projects/1ef1c72d-061a-4991-825d-fca8c0eeafa7/scans?id=8aedd9e5-0dad-428b-90b4-353a6d4ba618&branch=comm-pref-create-update-changes https://sonarqube-ent.internal.bupa.com.au/dashboard?id=HI-CBO-Apps_Bupa.HI.Customer.Api_Bupa.HI.Customer.Api&branch=comm-pref-create-update-changes

---

Non-Functional Requirements

- Scalability: HPA should be enabled.
- Resilience and failover strategy (DR): API will be Active - Active running in both AKS clusters **productionaks** and **productiondraks.** For infrastructure DR refer the document:
  - Hugo Core Services and Batch Jobs Technical Recovery Procedure - Disaster Recovery
- Security and compliance standards (e.g., OWASP): SCR_008 API Security & Management

---

Secrets Management

- Use of Key Vault or secret manager: Key Vaut will be used **banz-hi-cust-{env}-kv01**
- Rotation and access control:
  - Manual yearly rotation of key vault entries has to be done for the following **<More details will be filled after the initial release>**

Key Vault Value	Description
ApimKeyValue	Subscription key for authenticating with Azure API Management (APIM).

ClientCertificateBase64	Base64-encoded client certificate for mutual TLS authentication.
CacheBlueKeyCPHSalt	Salt used in encryption of BlueKey CPH cache data.
CacheUnsubscribeCommPreferenceSalt	Salt used for unsubscribe communication preference cache encryption.
CacheBlueKeyCERTSalt	Salt used for encrypting BlueKey certificate cache entries.
CacheBluekeyRefDataSalt	Salt used for encrypting BlueKey reference data cache.
MembershipDomainSettings--ClientOptions--ClientCertificateBase64	Client certificate for secure Membership API access.
MembershipDomainSettings--ClientOptions--DefaultRequestHeaders--Ocp-Apim-Subscription-Key	APIM subscription key for Membership service calls.
InteractionDomainSettings--ClientOptions--ClientCertificateBase64	Client certificate for secure Interaction API access.
CrmApiSettings--ServiceUsers[1]--ClientOptions--JwtTokenOptions--Password	Client password for CRM API user 1.
CrmApiSettings--ServiceUsers[2]--ClientOptions--JwtTokenOptions--Password	Client password for CRM API user 2.
CrmApiSettingsPNP--ClientOptions--JwtTokenOptions--Password	Password for PNP CRM integration.
AzureMonitor--EncryptionKey	Encryption key for logs sent to Azure Monitor.
AzureMonitor--EncryptionIV	Initialization Vector for Azure Monitor encryption.
DatabaseConnectionStrings--OracleHugoConnectionString	Connection string to Oracle Hugo database.

ServiceBus--EncryptionKey	Key used to encrypt messages on the Service Bus.
ServiceBus--EncryptionIV	Initialization Vector used with Service Bus encryption.
ProductCatalogueAPI--SubscriptionKey	Subscription key for accessing Product Catalogue API.
ProductCatalogueAPI--ClientSecret	Client secret for authenticating Product Catalogue client.
TokenSettings--clientSecret	OAuth client secret used with client ID.

- Access Control:

Resource	Role
RES-CLD-AzureRM-DotNetAppSupport-Prod [For support group members]	Key Vault Administrator
hicbocore-services-prod-msi [For AKS managed identity]	Key Vault Administrator

---

API Specification

- Customer Details
- Communcation Details
- Preferences
- Student Details
- Student Details
- Visa Details
- External Card
- Medicare Details
- Notes
- Digital Identity
- Alerts
- OHA
- Fulfilment
- Health Check Customer Domain
- Customer Domain API - Non-Restful Endpoints