Status	Finished
Started	Tuesday, 25 August 2026, 9:17 AM
Completed	Thursday, 27 August 2026, 2:38 PM
Duration	2 days 5 hours
Grade	**6.00** out of 10.00 (**60**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Justin is a carpenter who works on an hourly basis. He works in a company where he is paid Rs 50 for an hour on weekdays and Rs 80 for an hour on weekends. He works 10 hrs more on weekdays than weekends. If the salary paid for him is given, write a program to find the number of hours he has worked on weekdays and weekends.

Hint:

If the final result(hrs) are in -ve convert that to +ve using abs() function

The `abs()` function returns the absolute value of the given number.

```
number = -20
absolute_number = abs(number)
print(absolute_number)
# Output: 20
```

Sample Input:

450

Sample Output:

weekdays 10.38

weekend 0.38

For example:

Input	Result
450	weekdays 10.38 weekend 0.38

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
def calculate_hours(salary):
    # Let w be weekend hours.
    # Weekday hours = w + 10
    # Total Salary = (Weekday hours * 50) + (Weekend hours * 80)
    # salary = (w + 10) * 50 + w * 80
    # salary = 50w + 500 + 80w
    # salary = 130w + 500
    # 130w = salary - 500
    # w = (salary - 500) / 130

    weekend_hours = (salary - 500) / 130
    weekend_hours = abs(weekend_hours)

    weekday_hours = weekend_hours + 10

    print(f"weekdays {weekday_hours:.2f}")
    print(f"weekend {weekend_hours:.2f}")
```

	Input	Expected	Got	
✓	450	weekdays 10.38 weekend 0.38	weekdays 10.38 weekend 0.38	✓
✓	500	weekdays 10.00 weekend 0.00	weekdays 10.00 weekend 0.00	✓
✓	10000	weekdays 83.08 weekend 73.08	weekdays 83.08 weekend 73.08	✓

	Input	Expected	Got	
✓	6789	weekdays 58.38 weekend 48.38	weekdays 58.38 weekend 48.38	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Incorrect

Mark 0.00 out of 1.00

Ramesh's basic salary is input through the keyboard. His dearness allowance is 40% of his basic salary, and his house rent allowance is 20% of his basic salary. Write a program to calculate his gross salary.

Sample Input:

10000

Sample Output:

16000

For example:

Input	Result
10000	16000

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
#include <stdio.h>

int main() {

    float basic_salary, da, hra, gross_salary;

    // Ask user to input basic salary
    printf("Enter basic salary: ");
    scanf("%f", &basic_salary);

    // Calculate DA (40%) and HRA (20%)
    da = basic_salary * 0.40;
    hra = basic_salary * 0.20;

    // Calculate Gross Salary
    gross_salary = basic_salary + da + hra;

    // Print the final result
```

Syntax Error(s)

```
  File "__tester__.python3", line 3
    int main() {
        ^^^^
SyntaxError: invalid syntax
```

Incorrect

Marks for this submission: 0.00/1.00.

Question **3**

Incorrect

Mark 0.00 out of 1.00

You went on a tour to Ooty with your friends. As a part of the tour, you went boating with them. For the boat to remain stable, the number of people on one boat is restricted based on the weight of the people. You find that the boatman who is sailing your boat is so much greedy of money. For earning more, he takes too many people to travel in the boat at a time. So you want to check how many people can travel in the boat at a time so that the boat will not drown. Calculate the weight by considering the number of adults and number of children. Assume that an adult weighs 75 kg and children weigh 30 kg each. If the weight is normal, display Boat is stable, else display Boat will drown.

INPUT & OUTPUT FORMAT:

Input consists of 3 integers.

First input corresponds to the weight that the boat can handle.

Second input corresponds to the number of adults.

Third input corresponds to the number of children.

For example:

Input	Result
340 2 3	Boat is stable
600 7 4	Boat will drow

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
#include <stdio.h>

int main()
  { int capacity, adults, children;
    int weight;

    scanf("%d", &capacity);
    scanf("%d", &adults);
    scanf("%d", &children);

    weight = (adults * 75) + (children * 30);

    if (weight <= capacity)
        printf("Boat is stable");
    else
        printf("Boat will drow");

    return 0;}
```

Syntax Error(s)

```
  File "__tester__.python3", line 3
    int main()
        ^^^^
SyntaxError: invalid syntax
```

Incorrect

Marks for this submission: 0.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

In department 54% are boys and 46% are girls and 8% are hostel (boys/girls). write a python code to print total no of boys, girls and hostel students in the specific format using modulo operator.

input: 1500

output: Total Students : 1500, Boys : 810, Girls : 690, Hostel : 120

For example:

Input	Result
1500	Total Students : 1500, Boys : 810, Girls : 690, Hostel : 120
1200	Total Students : 1200, Boys : 648, Girls : 552, Hostel : 96

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
# Read the total number of students from input
total_students = int(input())

# Calculate the number of boys, girls, and hostel students as integers
boys = int(total_students * 0.54)
girls = int(total_students * 0.46)
hostel = int(total_students * 0.08)

# Print the results in the exact requested format using the modulo (%) string
formatting operator
print("Total Students : %d, Boys : %d, Girls : %d, Hostel : %d" %
(total_students, boys, girls, hostel))
```

	Input	Expected	Got	
✓	1500	Total Students : 1500, Boys : 810, Girls : 690, Hostel : 120	Total Students : 1500, Boys : 810, Girls : 690, Hostel : 120	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

In a Logistic the Parcels to be delivered in 4 locations (1st locaion 20%, 2nd location 40%, 3rd location 30% and 4th location 10%). write a python code to find the total no. of parcels after the delivery in 2 locations . use a format() to print the no of parcels delivered in in each location

Input:

250

output:

Total Parcels is 250

1st Location 50 parcels

2nd Location 100 parcels

3rd Location 75 parcels

4th Location 25 parcels

For example:

Input	Result
250	Total Parcels is 250 1st Location 50 parcels 2nd Location 100 parcels 3rd Location 75 parcels 4th Location 25 parcels
400	Total Parcels is 400 1st Location 80 parcels 2nd Location 160 parcels 3rd Location 120 parcels 4th Location 40 parcels

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
# Read the total number of parcels from user input
total_parcels = int(input())

# Calculate the number of parcels for each location based on percentages
loc1 = int(total_parcels * 0.20)
loc2 = int(total_parcels * 0.40)
loc3 = int(total_parcels * 0.30)
loc4 = int(total_parcels * 0.10)

# Print the output exactly as requested using format()
print("Total Parcels is {}".format(total_parcels))
print("1st Location {} parcels".format(loc1))
print("2nd Location {} parcels".format(loc2))
print("3rd Location {} parcels".format(loc3))
print("4th Location {} parcels".format(loc4))
```

	Input	Expected	Got	
✓	250	Total Parcels is 250 1st Location 50 parcels 2nd Location 100 parcels 3rd Location 75 parcels 4th Location 25 parcels	Total Parcels is 250 1st Location 50 parcels 2nd Location 100 parcels 3rd Location 75 parcels 4th Location 25 parcels	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

In a Lab 36% are Dell and 34% Lennovo and 28% are Acer and 2% are Samsung. write a python code to print total systems and brand wise count in the specific format using sep operator.

input: 150

output: Total System:150

Dell:54

Lennovo:51

Acer:42

Samsung:3

For example:

Input	Result
150	Total System:150 Dell:54 Lennovo:51 Acer:42 Samsung:3
250	Total System:250 Dell:90 Lennovo:85 Acer:70 Samsung:5

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
# Read total systems from user input
total_systems = int(input())

# Calculate brand-wise counts using integer conversion to get exact whole
numbers
dell = int(total_systems * 0.36)
lenovo = int(total_systems * 0.34)
acer = int(total_systems * 0.28)
samsung = int(total_systems * 0.02)

# Print using the sep operator to match the exact output format
print("Total System:", total_systems, sep="")
print("Dell:", dell, sep="")
print("Lennovo:", lenovo, sep="")
print("Acer:", acer, sep="")
print("Samsung:", samsung, sep="")
```

	Input	Expected	Got	
✓	150	Total System:150 Dell:54 Lennovo:51 Acer:42 Samsung:3	Total System:150 Dell:54 Lennovo:51 Acer:42 Samsung:3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

Alfred buys an old scooter for Rs. X and spends Rs. Y on its repairs. If he sells the scooter for Rs. Z (Z>X+Y). Write a program to help Alfred to find his gain percent. Get all the above-mentioned values through the keyboard and find the gain percent.

Input Format:

The first line contains the Rs X

The second line contains Rs Y

The third line contains Rs Z

Sample Input:

10000

250

15000

Sample Output:

46.34 is the gain percent.

For example:

Input	Result
45500 500 60000	30.43 is the gain percent.

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
# Read input values from the keyboard
X = float(input())
Y = float(input())
Z = float(input())

# Calculate total cost price (CP)
cost_price = X + Y

# Calculate gain
gain = Z - cost_price

# Calculate gain percent
gain_percent = (gain / cost_price) * 100

# Print the result formatted to 2 decimal places
print(f"{gain_percent:.2f} is the gain percent.")
```

	Input	Expected	Got	
✓	10000 250 15000	46.34 is the gain percent.	46.34 is the gain percent.	✓
✓	45500 500 60000	30.43 is the gain percent.	30.43 is the gain percent.	✓
✓	5000 0 7000	40.00 is the gain percent.	40.00 is the gain percent.	✓

	Input	Expected	Got	
✓	12500 5000 18000	2.86 is the gain percent.	2.86 is the gain percent.	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Incorrect

Mark 0.00 out of 1.00

Write a program that returns the second last digit of the given number. Second last digit is being referred 10the digit in the tens place in the given number.

For example, if the given number is 197, the second last digit is 9.

Note1 - The second last digit should be returned as a positive number. i.e. if the given number is -197, the second last digit is 9.

Note2 - If the given number is a single digit number, then the second last digit does not exist. In such cases, the program should return -1. i.e. if the given number is 5, the second last digit should be returned as -1

For example:

Input	Result
197	9
-197	9
5	-1

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
    def get_second_last_digit(number):
    # Convert to a positive number
    num = abs(number)

    # Check if the number is a single digit
    if num < 10:
        return -1

    # Remove the last digit, then get the new last digit
    return (num // 10) % 10

# Test cases
print(get_second_last_digit(197))    # Output: 9
print(get_second_last_digit(-197))   # Output: 9
print(get_second_last_digit(5))      # Output: -1
```

Syntax Error(s)

```
Sorry: IndentationError: unexpected indent (__tester__.python3, line 1)
```

Incorrect

Marks for this submission: 0.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

In many jurisdictions, a small deposit is added to drink containers to encourage people to recycle them. In one particular jurisdiction, drink containers holding one liter or less have a $0.10 deposit and drink containers holding more than one liter have a $0.25 deposit. Write a program that reads the number of containers of each size(less and more) from the user. Your program should continue by computing and displaying the refund that will be received for returning those containers. Format the output so that it includes a dollar sign and always displays exactly two decimal places.

Sample Input

10

20

Sample Output

Your total refund will be $6.00.

For example:

Input	Result
20 20	Your total refund will be $7.00.

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
# Read the number of containers holding one liter or less
less_containers = int(input())

# Read the number of containers holding more than one liter
more_containers = int(input())

# Compute the total refund
total_refund = (less_containers * 0.10) + (more_containers * 0.25)

# Display the result formatted with a dollar sign and two decimal places
print(f"Your total refund will be ${total_refund:.2f}.")
```

	Input	Expected	Got	
✓	20 20	Your total refund will be $7.00.	Your total refund will be $7.00.	✓
✓	11 22	Your total refund will be $6.60.	Your total refund will be $6.60.	✓
✓	123 200	Your total refund will be $62.30.	Your total refund will be $62.30.	✓
✓	76 38	Your total refund will be $17.10.	Your total refund will be $17.10.	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Incorrect

Mark 0.00 out of 1.00

Write a program to convert strings to an integer and float and display its type.

Sample Input:

10

10.9

Sample Output:

10,<class 'int'>

10.9,<class 'float'>

For example:

Input	Result
10 10.9	10,<class 'int'> 10.9,<class 'float'>

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?
Falling back to raw text area.

```
# Read input string and split into two values
val1, val2 = input("Enter values: ").split()

# Convert to integer and float
int_val = int(val1)
float_val = float(val2)

# Display result and type
print(f"{int_val},{type(int_val)}")
print(f"{float_val},{type(float_val)}")
```

	Input	Expected	Got	
✗	10 10.9	10,<class 'int'> 10.9,<class 'float'>	Enter values: ***Run error*** Traceback (most recent call last): File "__tester__.python3", line 2, in <module> val1, val2 = input("Enter values: ").split() ^^^^^^^^^^ ValueError: not enough values to unpack (expected 2, got 1)	✗

Testing was aborted due to error.

Your code must pass all tests to earn any marks. Try again.

Show differences

Incorrect

Marks for this submission: 0.00/1.00.