

# VSAR-DSL: A Specification Language for Multi-Mode VSA Reasoning Programs

This document defines **VSAR-DSL**, a small, compositional specification language for writing VSAR reasoning programs that leverage:

- the **FHRR encoding substrate** (roles, tags, typed symbols)
- the **unification kernel** (unbind  $\rightarrow$  typed cleanup)
- the **multi-mode inference engine** (deduction, DL, defaults, paraconsistency, probability, argumentation, epistemic, abduction, induction, analogy, CBR)

VSAR-DSL is designed to be:

- **declarative**: state knowledge and policies; let the engine run
- **multi-semantics**: select which controllers apply and how they interact
- **explainable**: every conclusion carries a proof/argument trace
- **VSA-native**: explicit about types, cleanup domains, and similarity thresholds

---

## 1) Core ideas

### 1.1 A VSAR program is four blocks

1) **SIGNATURE**: symbols and types (typed codebooks) 2) **KB**: facts, rules, DL axioms, cases, arguments 3) **SEMANTICS**: which reasoning modes are active and how conflicts are handled 4) **QUERIES**: what to ask (deductive entailment, DL entailment, abduction, analogy, CBR, epistemic, etc.)

### 1.2 Everything is an item with metadata

Facts/rules/axioms/edges/cases are inserted as items with:

- weight (probability / confidence)
- priority (for defaults/defeasible)
- agent (for epistemic)
- provenance (source/time)

VSAR-DSL makes this explicit.

---

## 2) Syntax overview (EBNF-ish)

```
program      := signature semantics? kb queries?
```

```

signature      := "SIGNATURE" "{" decl* "}"

decl           := type_decl | pred_decl | func_decl | role_decl | agent_decl

type_decl      := "type" IDENT ("<:" IDENT)? ";"

pred_decl      := "pred" IDENT ":" "(" type_list ")" pred_attrs? ";"
func_decl      := "func" IDENT ":" "(" type_list ")" "->" IDENT ";"
role_decl      := "role" IDENT ";"           // argument/structural roles if user
wants custom
agent_decl     := "agent" IDENT ";"

type_list      := IDENT ("," IDENT)*

pred_attrs     := "[" attr ("," attr)* "]"
attr           := "dl" | "closed" | "open" | "symmetric" | "transitive" |
"functional"

semantics      := "SEMANTICS" "{" setting* "}"
setting        := IDENT ":" value ";"
value          := NUMBER | STRING | IDENT | list
list           := "[" value ("," value)* "]"

kb             := "KB" "{" stmt* "}"

stmt           := fact | rule | default_rule | dl_axiom | arg_edge | case_stmt |
map_stmt

fact           := lit meta? "."

lit            := atom | "~" atom | "not" atom
atom           := IDENT "(" term_list? ")"
term_list      := term ("," term)*
term           := IDENT | STRING | NUMBER | IDENT "(" term_list? ")" // constant
or function term

rule           := "rule" IDENT? ":" atom "<-" body meta? "."
body           := lit ("," lit)*

default_rule   := "default" IDENT? ":" atom "<-" body ("unless" body)? meta? "."

dl_axiom       := "tbox" concept "<:" concept meta? "." |
"tbox" concept "==" concept meta? "." |
"abox" concept "(" IDENT ")" meta? "." |
"abox" role_atom meta? "."

concept        := IDENT |
"(" concept "and" concept ")" |

```

```

        "(" concept "or" concept ")" |
        "(" "not" concept ")" |
        "(" "exists" IDENT "." concept ")" |
        "(" "forall" IDENT "." concept ")"

role_atom      := IDENT "(" IDENT "," IDENT ")"

arg_edge       := "support" "(" lit "," lit ")" meta? "." |
                 "attack"  "(" lit "," lit ")" meta? "."

case_stmt      := "case" IDENT ":" "{" case_field+ "}" meta? "."
case_field     := ("problem" ":" term) | ("solution" ":" term) | ("context" ":"
term) | ("outcome" ":" term)

map_stmt       := "map" IDENT? ":" term "->" term meta? "."

meta           := "{" meta_kv ("," meta_kv)* "}"
meta_kv        := IDENT ":" value

queries        := "QUERIES" "{" query* "}"
query          := "ask" ask_expr meta? "."
ask_expr       := lit |
                 "entails" "(" lit ")" |
                 "dl_entails" "(" concept "(" IDENT ")" ")" |
                 "explain" "(" lit ")" |
                 "analogize" "(" term "," term ")" |
                 "retrieve_case" "(" term ")" |
                 "epistemic" "(" term ")"

```

### 3) Semantics block (selecting reasoning modes)

The **SEMANTICS** block chooses controllers and conflict policies.

Example:

```

SEMANTICS {
  logic: horn;                // horn | datalog | backward | mixed
  dl: alc;                    // off | alc
  paraconsistent: belnap;     // off | belnap
  defaults: enabled;         // enabled | off
  defeat: [priority, weight, specificity];
  uncertainty: probabilistic; // off | probabilistic | intervals
  t_norm: product;            // product | min | lukasiewicz
  t_conorm: noisy_or;         // noisy_or | max | logsumexp

```

```

argumentation: gradual;          // off | dung | gradual
epistemic: enabled;              // enabled | off
cwa: [closed(pred1), open(pred2)];
cleanup_threshold: 0.25;         // abstain if below
retrieval_k: 25;                // for exploratory similarity
proof_trace: full;              // none | brief | full
}

```

Notes:

- `cleanup_threshold` controls symbol commitment; below threshold the engine returns `UNKNOWN`.
- `retrieval_k` controls exploratory similarity search for analogy/CBR.

## 4) Knowledge block: facts, rules, defaults, DL axioms, arguments

### 4.1 Facts and literals

```

KB {
  parent(alice, bob) {w: 0.9}.
  ~parent(alice, bob) {w: 0.4}.      // classical negation
  not sick(bob) {w: 0.6}.           // default/NAF literal
}

```

Interpretation:

- `~A` encodes **classical negation** using the `NEG ⊗ TAG_LIT` wrapper.
- `not A` is a **meta-literal**; its meaning is controlled by the defaults/CWA semantics.

### 4.2 Horn rules

```

KB {
  rule r1: grandparent(x,z) <- parent(x,y), parent(y,z) {w: 0.95}.
}

```

### 4.3 Default (defeasible) rules

```

KB {
  default d1: flies(x) <- bird(x) unless penguin(x) {prio: 10, w: 0.8}.
  rule r2: ~flies(x) <- penguin(x) {w: 0.9}.
}

```

This exercises:

- defaults
- exceptions
- paraconsistency (if both `flies` and `~flies` derived)
- argumentation/defeat resolution

#### 4.4 Description Logic axioms

```
SIGNATURE {  
  type Individual;  
  type Concept;  
  pred hasChild: (Individual, Individual) [dl];  
  pred Person: (Individual) [dl];  
  pred Doctor: (Individual) [dl];  
}  
  
KB {  
  tbox Doctor <: Person.  
  abox Doctor(alice).  
  abox hasChild(alice, bob).  
  abox Person(bob).  
}
```

DL concept expressions:

```
KB {  
  tbox (exists hasChild . Doctor) <: Person.  
}
```

#### 4.5 Argumentation edges

```
KB {  
  support( bird(tweety), flies(tweety) ) {w: 0.7}.  
  attack( penguin(tweety), flies(tweety) ) {w: 0.9}.  
}
```

The argumentation controller will compute acceptability and warranted conclusions.

#### 4.6 Epistemic statements

Epistemic operators are written with `K(agent,  $\varphi$ )` and `B(agent,  $\varphi$ )`.

```
SIGNATURE { agent alice; agent bob; }
KB {
  B(alice, parent(alice,bob)) {w: 0.9}.
  K(bob, ~parent(alice,bob)) {w: 0.8}.
}
```

Agents have separate KB partitions; trust/communication are set via SEMANTICS.

## 4.7 Cases and mappings (CBR + analogy)

```
KB {
  case c1: {
    problem: diagnose(symptoms(fever,cough));
    context: patient(age(8));
    solution: treat(viral_support);
    outcome: success;
  } {w: 0.8}.

  map m1: doctor -> mechanic {w: 0.6}.
}
```

# 5) Query block

## 5.1 Deductive queries

```
QUERIES {
  ask entails(grandparent(alice, z)).
}
```

## 5.2 Paraconsistent query

```
QUERIES {
  ask flies(tweety) {return: [support_pos, support_neg]}.
}
```

## 5.3 Abductive query

```
QUERIES {
  ask explain(sick(bob)) {k: 5}.
}
```

## 5.4 DL entailment query

```
QUERIES {  
  ask dl_entails(Person(alice)).  
}
```

## 5.5 Analogy and cases

```
QUERIES {  
  ask analogize(domainA, domainB) {k: 10}.  
  ask retrieve_case(diagnose(symptoms(fever,cough))) {k: 3}.  
}
```

## 5.6 Epistemic query

```
QUERIES {  
  ask entails(B(alice, parent(alice,bob))).  
  ask entails(K(bob, ~parent(alice,bob))).  
}
```

---

# 6) Compilation to VSAR operations (operational semantics)

VSAR-DSL compiles each construct into:

1) **Encodings** (FHRR role-filler binding + tags) 2) **Indexes** (predicate/concept/role indexes for crisp narrowing) 3) **Controller selection** (semantics portfolio)

## 6.1 How an atom compiles

`p(t1, t2)` compiles to the FHRR encoding:

$$enc(p(t_1, t_2)) = (P_p \otimes TAG_{ATOM}) \otimes ((ARG_1 \otimes enc(t_1)) \oplus (ARG_2 \otimes enc(t_2)))$$

## 6.2 How crisp matching works

To answer `p(a, ?)`:

- use predicate index for `p`
- decode `ARG1` and verify equals `a` via typed cleanup
- decode `ARG2` and return cleanup result(s)

This avoids whole-vector fuzziness.

## 6.3 Cleanup and similarity roles

- **cleanup**: typed nearest-neighbor symbol commitment
- **retrieval**: exploratory similarity over stored items (facts/rules/cases)

The DSL exposes both via `cleanup_threshold`, `retrieval_k`, and query-level overrides.

---

## 7) Safety and clarity features

### 7.1 Explicit abstention

If cleanup confidence is below threshold, the engine returns `UNKNOWN` and can optionally trigger:

- abductive expansion
- argumentation resolution
- case retrieval

### 7.2 Proof and argument traces

Every derived conclusion can return:

- proof tree (Horn/DL)
  - argument graph slice (argumentation)
  - explanation set (abduction)
  - mapping witness (analogy)
- 

## 8) Minimal viable DSL subset (MVP)

Start with:

- SIGNATURE (types, predicates)
- KB facts
- Horn rules
- QUERIES entails()
- SEMANTICS cleanup\_threshold + retrieval\_k

Then add modules:

- defaults + defeat
- paraconsistent belief state
- argumentation
- DL axioms
- epistemic operators
- abduction
- analogy + cases

---

## 9) Example: a single program exercising many modes

```
SIGNATURE {
  type Individual;
  pred parent: (Individual, Individual);
  pred bird: (Individual);
  pred penguin: (Individual);
  pred flies: (Individual);
  agent alice;
}

SEMANTICS {
  logic: horn;
  paraconsistent: belnap;
  defaults: enabled;
  argumentation: gradual;
  uncertainty: probabilistic;
  t_norm: product;
  t_conorm: noisy_or;
  cleanup_threshold: 0.25;
  retrieval_k: 25;
  proof_trace: full;
}

KB {
  parent(alice, bob) {w: 0.9}.

  rule r1: grandparent(x,z) <- parent(x,y), parent(y,z) {w: 0.95}.

  default d1: flies(x) <- bird(x) unless penguin(x) {prio: 10, w: 0.8}.
  rule r2: ~flies(x) <- penguin(x) {w: 0.9}.

  bird(tweety) {w: 0.7}.
  penguin(tweety) {w: 0.9}.

  B(alice, parent(alice,bob)) {w: 0.9}.
}

QUERIES {
  ask entails(grandparent(alice, z)).
  ask flies(tweety) {return: [support_pos, support_neg]}.
  ask explain(flies(tweety)) {k: 3}.
}
```

## 10) Implementation notes

- Prefer a **parser + AST** that compiles into engine API calls.
  - Keep DSL surface syntax stable while internal engine evolves.
  - Provide an interactive REPL where users can:
    - add facts incrementally
    - run queries
    - inspect traces and decoded slots
- 

## 11) Final view

VSAR-DSL makes VSAR usable as a **programmable reasoning system**:

- users write structured knowledge
- users select semantics portfolios
- VSAR compiles into FHRR encodings and invokes the inference engine

This gives a practical path from the math of VSAX/FHRR to usable reasoning programs.