

## **ASSIGNMENT-2**

**DATE: 07-06-2024**

### **1.Container with more water**

```
def maxArea(A, Len) :  
    area = 0  
    for i in range(Len) :  
        for j in range(i + 1, Len) :  
            area = max(area, min(A[j], A[i]) * (j - i))  
    return area  
a = [ 1, 5, 4, 3 ]  
b = [ 3, 1, 2, 4, 5 ]  
len1 = len(a)  
print(maxArea(a, len1))  
len2 = len(b)  
print(maxArea(b, len2))
```

### **2.Roman to Numeral**

```
def value(r):  
    if (r == 'I'):  
        return 1  
    if (r == 'V'):  
        return 5  
    if (r == 'X'):  
        return 10  
    if (r == 'L'):  
        return 50  
    if (r == 'C'):
```

```

        return 100
    if (r == 'D'):
        return 500
    if (r == 'M'):
        return 1000
    return -1
def romanToDecimal(str):
    res = 0
    i = 0
    while (i < len(str)):
        s1 = value(str[i])
        if (i + 1 < len(str)):
            s2 = value(str[i + 1])
            if (s1 >= s2):
                res = res + s1
                i = i + 1
            else:
                res = res + s2 - s1
                i = i + 2
        else:
            res = res + s1
            i = i + 1
    return res
print("Integer form of Roman Numeral is")
print(romanToDecimal("MCMIV"))

```

### 3.Roman to Integer

```
def romanToInt(s):  
    roman = {'I': 1, 'V': 5, 'X': 10, 'L': 50, 'C': 100, 'D': 500, 'M': 1000}  
    total = 0  
    prev_value = 0  
  
    for char in s:  
        value = roman[char]  
        if value > prev_value:  
            total += value - 2 * prev_value  
        else:  
            total += value  
        prev_value = value  
  
    return total  
s = "MCMXCIV"  
print(romanToInt(s))
```

### 4.Longest common prefix

```
def longestCommonPrefix(strs):  
    if not strs:  
        return ""  
  
    shortest = min(strs, key=len)  
  
    for i, char in enumerate(shortest):  
        for other in strs:
```

## 5. 3sum

```
        right -= 1
    return res

nums = [-1,0,1,2,-1,-4]
print(threeSum(nums))
```

## 6. 3sum closest

```
def three_sum_closest(nums, target):
    nums.sort()
    closest_sum = float('inf')

    for i in range(len(nums) - 2):
        left, right = i + 1, len(nums) - 1

        while left < right:
            total = nums[i] + nums[left] + nums[right]
            if abs(target - total) < abs(target - closest_sum):
                closest_sum = total

            if total < target:
                left += 1
            elif total > target:
                right -= 1
            else:
                return total

    return closest_sum
```

## 7. Letter combinations of a phone number

```
def threeSumClosest(nums, target):
    nums.sort()
    closest_sum = float('inf')

    for i in range(len(nums) - 2):
        left, right = i + 1, len(nums) - 1
        while left < right:
            current_sum = nums[i] + nums[left] + nums[right]
            if abs(current_sum - target) < abs(closest_sum - target):
                closest_sum = current_sum
            if current_sum < target:
                left += 1
            elif current_sum > target:
                right -= 1
            else:
                return current_sum
        return closest_sum

nums = [-1, 2, 1, -4]
target = 1
print(threeSumClosest(nums, target))
```

## 8. 4sum

```
def letterCombinations(digits):
    if not digits:
        return []
```

```

phone = {
    '2': 'abc', '3': 'def', '4': 'ghi', '5': 'jkl',
    '6': 'mno', '7': 'pqrs', '8': 'tuv', '9': 'wxyz'
}

```

```

def backtrack(index, path):
    if len(path) == len(digits):
        combinations.append("".join(path))
        return
    for letter in phone[digits[index]]:
        path.append(letter)
        backtrack(index + 1, path)
        path.pop()

```

```

combinations = []
backtrack(0, [])
return combinations

digits = "23"
print(letterCombinations(digits))

class ListNode:
    def __init__(self, val=0, next=None):
        self.val = val
        self.next = next

```

## 9. Remove nth node from end of list

```

class ListNode:
    def __init__(self, val=0, next=None):

```

```
self.val = val
self.next = next
```

```
def removeNthFromEnd(head, n):
    dummy = ListNode(0)
    dummy.next = head
    first = dummy
    second = dummy
    for _ in range(n + 1):
        first = first.next
    while first is not None:
        first = first.next
        second = second.next
    second.next = second.next.next
    return dummy.next
```

```
def create_linked_list(arr):
    head = ListNode(arr[0])
    current = head
    for val in arr[1:]:
        current.next = ListNode(val)
        current = current.next
    return head

head = create_linked_list([1, 2, 3, 4, 5])
n = 2
new_head = removeNthFromEnd(head, n)
```



```

def linked_list_to_list(node):
    result = []
    while node:
        result.append(node.val)
        node = node.next
    return result

print(linked_list_to_list(new_head))

```

## 10. Valid parentheses

```

def isValid(s):
    stack = []
    mapping = {")": "(", "}": "{", "]": "["}

    for char in s:
        if char in mapping:
            top_element = stack.pop() if stack else '#'
            if mapping[char] != top_element:
                return False
        else:
            stack.append(char)

    return not stack

s = "()[]{}"
print(isValid(s))

```