# • UNIT -2 Part 1 Forms

## **TEXT BOOK**

- Internet Technology and Web Design
  - Publisher: Tata McGraw Hills
  - Author : ISRD Group

- HTML, Java Script, DHTML and PHP
  - Publisher: BPB Publication
  - Author: Ivan Byross

## **Tables and Forms**

#### **Forms**

- Creating form & all its attribute
- Adding controls to an HTML form
- <input> tag
- <text area>
- Adding a selection control
- Grouping the control of html forms

## Form in HTML5

- •Forms are used to build interctive HTML webpages.
- •<input> tag is used to add elements in Forms

# **Elements of Form**

- <input type="button">
- <input type="checkbox">
- <input type="color">
- <input type="date">
- <input type="email">
- <input type="file">
- <input type="number">
- <input type="url">

- <input type="password">
- <input type="radio">
- <input type="range">
- <input type="reset">
- <input type="search">
- <input type="submit">
- <input type="tel">
- <input type="text">
- <input type="time">

# **Elements of Form**

input type="text"> : defines a one-line text input field.

Eg: First Name: <input type="text" name="fname">

<input type="password"> : A free-form text field for sensitive
information.

Eg: <input type="password" name="password">

<input type="submit"> : It defines a button for submitting form data to a form handler.

Eg: <input type="submit" value="Submit">

<input type="reset"> : It defines a reset button that will reset all
form values to their default values.

Eg: <input type="reset">

### <input type="checkbox">:

Checkboxes let a user select ZERO or MORE options of a limited number of choices.

```
<input type="checkbox" name="ahbd" value="ahbd" > Ahmedabad <input type="checkbox" name="surat" value="surat" > Surat <input type="checkbox" name="baroda" value="baroda" > Baroda
```

### <input type="radio">:

Radio buttons let a user select ONLY ONE of a limited number of choices

### Eg:

```
<input type="radio" name="gender" value="male" checked>
Male<br/>br>
```

```
<input type="radio" name="gender" value="female">
Female<br/>br>
```

# <input type="button"> defines a button. Some of the attributes of button are:

autofocus	Specifies that a button should automatically get focus when the page loads
disabled	Specifies that a button should be disabled
name	Specifies a name for the button
type	Specifies the type of button as Button, Submit, Reset
value	Specifies an initial value for the button

```
<input type="date">: inserts date control in webpage
```

```
Eg:<input type="date" id="start" name="dob" value="2018-07-2">
```

<input type="time">: inserts time control in
webpage

Eg:<input type="time" name="dot">

<input type="color">: inserts colorpicker control
in webpage

Eg:<input type="color" name="favcolor">

```
<input type="email">: is used for input fields
that should contain an e-mail address.
Eg:<input type="email" name="mailid">
```

<input type="file">: defines a file-select field
and a "Browse" button for file uploads.
Eg:<input type="file" name="fselect">

<input type="tel">: is used for input fields that
should contain a telephone number.
Eg:<input type="tel" name="contact no">

<input type=""number">: defines a numeric input field.

Eg:<input type="number" name="num">
Some of the attributes are:

min	Specifies the minimum value for an input field
max	Specifies the maximum value for an input field
disabled	Specifies that a button should be disabled
name	Specifies a name for the button
step	Specifies the increments for numeric values
value	Specifies an initial value for the button

<input type="range">: enter range control
Eg:<input type="range" name="price range">

Some of the attributes are:

min	Specifies the minimum value for an input field
max	Specifies the maximum value for an input field
name	Specifies a name for the button

c<input type="url">: Enter URL:
Eg:<input type="url" name="webname">

## <textarea>

<textarea>: enables to add control that allows the user to input text over multiple rows.

Eg: <textarea>

</textarea>