

Identity-Share-Discovery “Real-NAS Recon Results (2026-06-26)

Revision: 1 **Last modified:** 2026-06-26T11:05:00Z **Authority:** Identity-share-discovery epic; Â§11.4.6 (no-guessing), Â§11.4.10 (no secret values here “ identities referenced by env-var only), Â§11.4.27 (real-system test), Â§11.4.74. **Anti-bluff:** every row below is a captured FACT from a live SMB probe of the real LAN, not a guess.

“ i, No credential value appears in this document. Identities are referenced by env-var index only (CATALOGIZER_IDENTITY_1/2, user milosvasic).

Method

A recon probe (go-smb2, password read from env, never argv/log) dialed each SMB host on 192.168.0.0/24, tried **anonymous first**, then each stored identity in order, and on success enumerated the **real** shares via SRVSVC ListShareNames().

Hosts + working (host, identity, real-shares) bindings “ FACT

Host	MAC OUI	Anonymous	Working identity	Real shares (SRVSVC)
192.168.0.108	90:09:d0 = Synology	rejected (guest required)	#1	Data
192.168.0.109	Synology	rejected	#1	DATA18
192.168.0.110	Synology	rejected	#1	DATA12
192.168.0.111	Synology	rejected	#1	DATA20, music, WORK20
192.168.0.105	“	rejected	#1	Public, TimeMachineBackup
192.168.0.213	“	rejected	#2 (#1 fails)	Public, Music, Projects

Findings that drive implementation

- Â§11.4.6 anti-bluff fix landed (this PWU): smb_discovery.go enumerateShares previously **guessed** from a hardcoded common-name list (shared/public/media/music/videos/data/...) “ it MISSED every real Synology share (Data, DATA18, DATA12, DATA20, WORK20, Projects). Replaced

- with real `ListShareNames()` SRVSVC enumeration (IPC\$ filtered). Proven by `TestDiscoverShares_RealShares_NoGuessing` (§11.4.27 real-system, §11.4.3 SKIP-gated, §11.4.115 RED-on-guessing + GREEN-on-fix).
2. **Anonymous-first needs GUEST, not true-anonymous:** go-smb2 rejects a true-anonymous bind (‘Anonymous account is not supported yet. Use guest account instead’). The epic’s anon-first step MUST attempt a **guest** session, then fall through to identities.
 3. **Multi-identity fallback is real + required:** host .213 rejects identity #1 and authenticates only with identity #2 – exactly the ‘try each identity until one passes, remember the working binding’ mechanic the operator specified. The remembered binding key is (host, share, identity-index, protocol=smb).
 4. **Catalog ingest targets:** the Synology media lives under `DATA*/WORK20/music` shares on .108 – .111 – these become `storage_roots` (one per working (host, share, identity)), scanned by `UniversalScanner` to populate the catalog (then dedup + group per epic pillars 4–5).

Next PWUs (per DESIGN.md)

- Identity store (multi-scheme: credentials/api_token/ssh_key) + secure storage (no plaintext in `storage_roots` – §11.4.10 debt).
- Guest/anon-first + multi-identity probe service + remembered-binding table.
- Auto-register working bindings as `storage_roots` + scan + dedup + group.
- UI: identity-manager + discovered-shares + grouped browse (OpenDesign §11.4.162), per app.
- Full §11.4.169 test matrix.