

Herald



Herald — Continuation

Field	Value
Revision	7
Created	2026-05-20
Last modified	2026-05-22
Status	active
Status summary	Wave 6 code-doc closure landed (this commit). pherald inbound runtime + Claude Code headless bridge complete. Tag v0.4.0 DEFERRED to T13b (operator-supplied live evidence). HRD-100 closed atomically with 12 Wave-6 commit SHAs T1=ad87d7f..T12=96c7c6b. 8 new e2e invariants E63-E70 land in this commit but currently SKIP with documented reasons — convert to PASS at T10b when the operator runs the live closed-loop end-to-end and commits docs/qa/HRD-100-<run-id>/. Workspace at 16 modules (Wave 5 added qaherald; Wave 6 added NO new module — inbound is pherald/internal/inbound/). Spec V3 at r12. Pre-existing e2e FAILs on the Postgres-:24100 dependent invariants (E7-E12 + E14-E16 + E37-E42 — SASL handshake) are NOT Wave 6 regressions; documented in this commit as carry-over. Anti-bluff gates green: inheritance gate 15/15 PASS; audit_antibluff 18/0/1; codegraph_validate 7/0/2. Prior r6 covered Wave 3a + Wave 2 + Foundation M1/M2/M3.
Issues	HRD-008, HRD-015, HRD-018 (in progress), HRD-019..HRD-027, HRD-029..HRD-056, HRD-081, HRD-085..HRD-090
Issues summary	see Issues.md — 47 open items
Fixed	HRD-001..HRD-007, HRD-009, HRD-009b, HRD-010, HRD-011, HRD-012, HRD-013, HRD-014, HRD-016, HRD-017, HRD-028, HRD-080, HRD-092..HRD-100 (HRD-018 partial — M1 + M2 components landed)
Fixed summary	see Fixed.md
Continuation	T10b next (live closed-loop evidence) — operator exports HERALD_TGRAM_BOT_TOKEN + HERALD_TGRAM_CHAT_ID + HERALD_CLAUDE_BIN, then runs bash tests/test_wave6_live_loop.sh --qa-out-dir docs/qa/HRD-100-<run-id>/. The script types a synthetic message into the chat, observes the original message_id, starts pherald listen in the background with --qa-out-dir pointing at the new directory, waits up to 45s for a reply with

Field	Value
	<code>reply_to_message_id == original</code> , and exits 0 on PASS. The resulting <code>docs/qa/HRD-100-<run-id>/</code> directory carries <code>transcript.jsonl</code> (bidirectional events) + <code>pherald-listen.log</code> + <code>claude-stdout.log</code> + <code>claude-stderr.log</code> + <code>attachments/<sha256>.<ext></code> (any exchanged) + an operator-authored <code>README.md</code> narrative. After T10b PASS, T13b tags <code>v0.4.0</code> and pushes to all 4 mirrors. After Wave 6: §43 command-catalogue rollout (HRD-029..056), <code>iherald /v1/webhooks/page</code> live (HRD-024), <code>sherald destructive-guard</code> body (HRD-033 — unlocks E48), HRD-091 codegraph submodule-traversal gap, comprehensive docs audit per task #147. Multi-mirror push after each milestone. Update on every non-trivial commit (per Universal §12.10).

Table of contents

- [§0. How to use this document](#)
- [§1. Snapshot](#)
- [§2. Last commit landed](#)
- [§3. Active work](#)
- [§4. Next concrete steps](#)
- [§5. Long-form pointers](#)

§0. How to use this document

Paste the following block into any CLI agent (Claude Code / OpenCode / Cursor / Aider / Gemini CLI) to resume Herald work exactly where it was left:

```
You are working on the Herald project at ~/Projects/Herald (also reachable as
the Herald/ submodule of a consuming project). The Helix Universal Constitution
lives at <ancestor>/constitution/ (parent-walk discovery). Read in this
order: CLAUDE.md, AGENTS.md, README.md, docs/guides/
HERALD_CONSTITUTION.md, docs/guides/
CONSTITUTION_INHERITANCE.md, docs/specs/mvp/
specification.V3.md. Then read docs/CONTINUATION.md (this file) for
live state, docs/Issues.md for open work, docs/Status.md for current
phase, docs/Fixed.md for closed history. Go workspace builds via go
test ./commons/... ./commons_prefix/... ./
commons_messaging/... ./commons_storage/.... Inheritance gate
tests/test_constitution_inheritance.sh MUST exit 0 before any
commit. Multi-mirror fan-out push to four hosts (GitHub + GitLab + GitFlic +
GitVerse) is mandatory per Constitution §103.
```

§1. Snapshot

- **Active spec:** `docs/specs/mvp/specification.V3.md` Revision 4 (~4300 lines).
- **Archived specs:** V1 + V2 in `docs/specs/mvp/archive/` (frozen).
- **Go modules:** `commons`, `commons_prefix`, `commons_messaging`, `commons_storage`, `pherald` (all compile + unit tests pass).
- **Container scaffold:** `quickstart/{docker-compose.quickstart.yml, Dockerfile.pherald, otel-config.yaml, .env.example}` for §26.5 quickstart.

- **CLI:** `pherald version --json` returns canonical build info; `serve/send/doctor/migrate/subscriber/deadletter` stubbed with HRD-NNN pointers.
- **Inheritance gate:** 12 PASS / 0 FAIL. Meta-test ✓.
- **Phase:** implementation r1.

§2. Last commit landed

This commit (V3 r4 + Go scaffold + tracking-doc refresh) closes HRD-009/HRD-009b/HRD-013/HRD-014 (with a Universal §11.4.19 atomic Issues.md → Fixed.md migration) and lands spec V3 §37–§41 (tracker events, workable-item announcement contract, message presentation + Herald Canonical Template, docs/tests completeness, REST API surface). Builds + tests:

```
$ go test ./commons/... ./commons_prefix/... ./commons_messaging/... ./commons_storage/...
ok      github.com/vasic-digital/herald/commons 1.135s
ok      github.com/vasic-digital/herald/commons_prefix 0.639s
ok      github.com/vasic-digital/herald/commons_messaging/channels/null 0.001s
ok      github.com/vasic-digital/herald/commons_messaging/dispatch/claude 0.001s
ok      github.com/vasic-digital/herald/commons_storage 1.630s
```

§3. Active work

ID	Status	What
HRD-008	in_progress	Operator-side Quickstart compose validation (Postgres + Redis + OTel + pherald container) — scaffold shipped this commit; live end-to-end run pending operator.
HRD-010	open	commons_storage live (pgx pool + golang-migrate driver + River queue + Redis ACL).
HRD-011	open	Telegram adapter live (telebot SDK + getUpdates long-poll + webhook secret_token).
HRD-012	open	Claude Code dispatcher live (<code>claude --resume + parse <<<HERALD-REPLY>>></code>).
HRD-015	open	Inheritance gate I8 invariants for Go scaffold (<code>go.work</code> + <code>commons/types.go</code> + null adapter test passes).
HRD-016	open	REST API surface via Gin Gonic per spec §41.
HRD-017	open	Propagate Universal §11.4.6X spec-versioning + submodule-catalogue-first mandates into the parent constitution.

§4. Next concrete steps

1. **HRD-018 Catalogue-Check survey + commons_constitution scaffold** — first action of the §42 implementation rollout. **MUST start** with a `vasic-digital + HelixDevelopment` catalogue survey per the brand-new Universal §11.4.74. Record Catalogue-Check: `reuse|extend|no-match` on HRD-018 before any Go code lands. Then scaffold the `Evaluator` interface, 12 event-class emit helpers, `constitution_state + constitution_bindings` migrations, `bundle-hash` captureer, `mode-ladder` runtime config.
2. **HRD-008 quickstart validation** — On a fresh laptop with Podman or Docker:

```
git clone <Herald repo>
git submodule update --init
cd quickstart
podman build -t herald/pherald:dev -f Dockerfile.pherald ../../
cp .env.example ../../.env && $EDITOR ../../.env
podman-compose -f docker-compose.quickstart.yml up -d
curl --retry 30 --retry-delay 2 http://localhost:24090/readyz
```

The current pherald serve returns "not implemented" — HRD-010/HRD-011/HRD-012 must land first to make the live curl POST /v1/events succeed end-to-end. Validation reveals which of the spec's assumptions (port ranges, Compose syntax, OTEL collector config, Postgres healthcheck) hold against real infrastructure.

3. **HRD-010** — wire commons_storage/storage.go's MigrationDriver to golang-migrate; bring pgx + River + Redis client up; add integration tests under // go:build integration.
4. **HRD-011** — replace commons_messaging/channels/tgram/tgram.go stub with a live implementation against gopkg.in/telebot.v3 or github.com/mymmrac/telego; recorded HTTP fixtures under testdata/.
5. **HRD-012** — replace commons_messaging/dispatch/claude_code/claude_code.go's Dispatch stub with a real claude --resume invocation; capture session UUID; parse <<<HERALD-REPLY>>>.
6. **HRD-016** — scaffold pherald/internal/http/ with Gin routes per V3 §41; wire pherald serve to mount the Gin router on http_port.
7. **HRD-017** — propagate Universal §11.4.6X new mandates (spec-versioning + submodule-catalogue-first) into the constitution submodule.

§4a. Wave 6 live-test handoff (T10b — gating tag v0.4.0)

Operator-supplied credentials required — Wave 6's e2e invariants E63-E70 land as honest SKIPs until the live closed-loop runs against real Telegram + real Claude Code with real chat messages exchanged.

Step-by-step.

1. Export credentials in the shell that will drive the test:

```
export HERALD_TGRAM_BOT_TOKEN="<your-bot-token-from-  
BotFather>"
export HERALD_TGRAM_CHAT_ID="<numeric-chat-id-where-bot-is-  
admin>"
export HERALD_CLAUDE_BIN="$(command -v claude)"      # path to
the claude CLI binary
export HERALD_PROJECT_NAME="Herald"                  # or any
operator-chosen session name
```

2. Pick a <run-id> (timestamp + 4-char nonce):

```
RUN_ID="$(date -u +%Y-%m-%dT%H-%M-%S)-$(uuidgen | cut -c1-4)"
QA_DIR="docs/qa/HRD-100-#{RUN_ID}"
mkdir -p "${QA_DIR}/attachments"
```

3. Type ONE message in the configured Telegram chat (script reads it via getUpdates within 60s).
4. Run the live closed-loop test:

```
bash tests/test_wave6_live_loop.sh
```

The script builds pherald, observes the original message_id, starts pherald listen --bot-token "\$HERALD_TGRAM_BOT_TOKEN" --chat-id "\$HERALD_TGRAM_CHAT_ID" --qa-out-dir "\$QA_DIR" in the background, waits up to 45s for a reply with reply_to_message_id == original, and exits 0 on PASS.

5. Capture supplementary logs:

```
cp /tmp/pherald-w6.log "${QA_DIR}/pherald-listen.log"
# claude stdout/stderr — paths depend on the journaling
# setup. Copy whatever
# the test produced into ${QA_DIR}/claude-stdout.log +
# claude-stderr.log.
```

6. Author a brief \${QA_DIR}/README.md (5 lines minimum) narrating: who ran it, when, what message was sent, what reply came back, any anomalies. This is NOT auto-generated — operator-written narrative is the §107.x evidence anchor.
7. git add \${QA_DIR}/ && git commit -m "Wave 6 step 10b: docs/qa/HRD-100-#{RUN_ID}/ live closed-loop evidence" then proceed to T13b (v0.4.0 tag + 4-mirror push).

If the script SKIPS (any env var unset): the test prints SKIP: <reason> and exits 0. That is honest §11.4.3 hardware-absent SKIP-with-reason, not a PASS. Tag v0.4.0 MUST NOT be created until at least one PASS run is committed to docs/qa/HRD-100-<run-id>/.

§5. Long-form pointers

- docs/specs/mvp/specification.V3.md — full active spec (Revision 4).
- docs/specs/mvp/specification.V3.md#30-v2-self-review-log — every review pass.
- docs/guides/HERALD_CONSTITUTION.md — §101..§106 extending Universal.
- docs/guides/CONSTITUTION_INHERITANCE.md — parent-discovery + gate.
- tests/test_constitution_inheritance.sh — the gate.
- quickstart/ — HRD-008 scaffold.
- commons/types.go — the §11.0 type contract reference.