

Herald



Herald — iherald Flavor Guide (Operator)

Field	Value
Revision	1
Created	2026-05-30
Last modified	2026-05-30
Status	active
Status summary	Nano-detail operator reference for iherald (Incident Herald) — a serving flavor (DefaultPort=24794). Documents serve and its now-LIVE application route <code>POST /v1/webhooks/page</code> (HRD-024): a JWT-gated escalation handler driving the <code>iherald/internal/bindings</code> Pipeline → emit CloudEvent → persist state/audit → 202 + Receipt. ANTI-BLUFF: derived from the built iherald binary (<code>iherald --help, version --json</code>) + <code>commons/branding.go</code> + <code>iherald/internal/page/page.go</code> . Third-party pager egress (PagerDuty/Opsgenie) is a separate operator-credentialed subscriber — each Receipt discloses <code>pager_delivery</code> ; no fake "pager notified" 200 (§11.4.69).
Issues	(none specific to this guide)
Continuation	Bump when HRD-024 lands the live <code>/v1/webhooks/page</code> paging handler body.

Table of contents

- [§1. What iherald is](#)
- [§2. The subcommand surface](#)
- [§3. version](#)
- [§4. serve — and the 501 paging stub](#)
- [§5. References](#)

§1. What iherald is

iherald is **Incident Herald** — flavor key `i`, prefix `IHR`, default serving port **24794**. Per `commons/branding.go` its mission is "Credential-leak page-out + operator-blocked escalation". It is the paging surface for incident escalation. As of HRD-024 its `POST /v1/`

webhooks/page route is **LIVE**: a JWT-gated handler that classifies the page through the `iherald/internal/bindings` escalation Pipeline, emits the `.credential.leak/.policy.violation` CloudEvent on the constitution bus, persists `constitution_state + constitution_audit`, and returns `202` + a Receipt. Actual outbound delivery to a third-party pager (PagerDuty/Opsgenie) is a separate operator-credentialed bus subscriber — every Receipt carries a `pager_delivery` disclosure note; no fake "pager notified" `200` is returned (the §11.4.69 anti-bluff posture).

Build it:

```
go build -o /tmp/iherald ./iherald/cmd/iherald
```

§2. The subcommand surface

Verbatim from `iherald --help` — `iherald` has the smallest surface of all flavors (no §43 command catalogue yet):

Subcommand What it does

<code>serve</code>	Start the Incident Herald HTTP server
<code>version</code>	Print Incident Herald version + build info
<code>completion</code>	Generate shell autocompletion (Cobra built-in)

§3. version

```
$ iherald version --json
{"arch":"arm64","binary":"iherald","build_time":"unknown","commit":"unknown-dev"}
```

§4. serve — and the 501 paging stub

`iherald serve` starts the Incident Herald HTTP server on port 24794. Like the other serving flavors it exposes the standard health/metrics surface (`/v1/healthz`, `/v1/readyz`, `/metrics`), and shares the `commons/cli` serve scaffold.

The application route `POST /v1/webhooks/page` is **LIVE (HRD-024)**. Per `iherald/internal/page/page.go` it is a JWT+tenant-gated handler (via `commons_auth.GinMiddleware`) that accepts a page webhook body (`rule_id`, `subject_kind`, `subject_id`, optional `operator_id`), classifies it through the matching `iherald/internal/bindings` escalation rule (§11.4.10 credential-leak page-out, §11.4.21 operator-blocked, §11.4.66 blocker-clarification, §18.8 incident-severity), emits the `.credential.leak/.policy.violation` CloudEvent on the constitution bus, persists `constitution_state + constitution_audit`, and returns `202` + a Receipt (`decision`, `mode`, `escalation`, `emitted`, `audited`, `changed`). Malformed/unknown-rule bodies return `400` with an `event_parser:-tagged` error; an `operator_id` outside the `HERALD_OPERATOR_IDS` allow-list (when configured) returns `403` for the operator-gated rules. **Honest follow-up:** outbound delivery to a third-party pager (PagerDuty Events API / Opsgenie) is a separate operator-credentialed bus subscriber — the emitted event IS the in-Herald page-out; each Receipt carries a `pager_delivery` disclosure. No fake `200`.

```
iherald serve --http-port 24794
# POST /v1/webhooks/page → 501 Not Implemented (HRD-024
  pending)
```

Do not build a pager integration against `/v1/webhooks/page` yet — it does not deliver. The `iherald/internal/bindings/` package supplies the constitution-binding scaffold (incident/escalation Evaluator) that the future handler will consume, but the handler body itself is not written.

§5. References

- Source: `iherald/cmd/iherald/main.go`, `iherald/internal/http/routes.go`, `iherald/internal/bindings/bindings.go`.
- Branding: `commons/branding.go` (flavor `i`, `DefaultPort=24794`).
- Integration: `docs/INTEGRATION.md` §1/§10 (iherald row — `POST /v1/webhooks/page` LIVE escalation handler, HRD-024).
- Open work: HRD-024 (the live paging handler + §43 escalation command bodies).
- Companion flavor guides: `docs/guides/{PHERALD,SHERALD,CHERALD,BHERALD,RHERALD,SCHERALD,QAHERALD}.md`.

Sources verified

Verified 2026-05-30: internal doc — no external online sources. The subcommand surface + `version --json` were derived by running the built `iherald` binary (`iherald --help`, `iherald version --json`) on 2026-05-30; the 501-stub status of `POST /v1/webhooks/page` was confirmed by reading `iherald/internal/http/routes.go` (route registered with HRD: `"HRD-024"`) and the package comments in `iherald/cmd/iherald/main.go` + `iherald/internal/bindings/bindings.go`, plus `commons/branding.go` for the flavor identity. No routes or flags were invented; the not-yet-implemented status is stated honestly. Re-verify when HRD-024 lands the live paging handler.