

Herald



{width=96px height=96px}

Constitution inheritance — operator & agent guide

Field	Value
Revision	1
Created	2026-05-15
Last modified	2026-05-19
Status	active
Status summary	—
Issues	none
Issues summary	—
Fixed	none
Fixed summary	—
Continuation	—

Table of contents

- [Summary](#)
- [Why no embedded submodule?](#)
- [Discovery contract](#)
 - [Standalone development](#)
- [The inheritance gate](#)
 - [Common failure: FAIL I1 constitution NOT found ...](#)
 - [Common failure: FAIL I6 No constitution submodule embedded in Herald](#)
- [The paired mutation meta-test \(§1.1\)](#)
- [When to run the gates](#)
- [Promoting Herald rules into the constitution](#)
- [Glossary](#)

This guide explains how Herald inherits from the Helix Universal Constitution, why Herald does **not** keep its own copy, how the runtime discovery contract works, and how the inheritance gate enforces both.

If you only need the rule, read [§Summary](#) and stop. If you're operating Herald, building tooling around it, or debugging a FAIL I1 from the gate, read on.

Summary

- Herald **does not** carry a `constitution/` submodule.
- Herald is consumed as a submodule of a parent project that **already provides** `<parent>/constitution/`.
- For standalone Herald work, clone the constitution **alongside** Herald (`$(dirname "$PWD")/constitution`), never inside.
- The inheritance contract is enforced by `tests/test_constitution_inheritance.sh` (gate) and `tests/test_constitution_inheritance_meta.sh` (paired §1.1 mutation proof).
- Discovery uses parent-walk: walk up directories until you find `<ancestor>/constitution/Constitution.md`.

Why no embedded submodule?

Herald is a building block. It will be used as a submodule by several parent projects. Each parent already includes the Helix Constitution at `<parent>/constitution/`. If Herald also carried its own `constitution/`:

1. **Two pins, one source of truth.** The parent and Herald could pin to different constitution SHAs, silently disagreeing on which clauses apply. Constitution §3 requires submodule commits propagate first — duplicate copies make the propagation order undefined.
2. **Doubled storage** for a 250 KB content set that should be shared.
3. **Confusion about authority.** Two `constitution/CLAUDE.md` files (one at `<parent>/constitution/`, one at `<parent>/Herald/constitution/`) is exactly the kind of "which file wins?" ambiguity the anti-bluff covenant exists to prevent.

Herald therefore inherits from the parent's constitution and provides only a discovery mechanism to locate it.

Discovery contract

Discovery uses the same algorithm as the canonical `find_constitution.sh` (Phase 1):

1. Start at Herald's repo root.
2. Walk up parent directories.
3. At each step, check whether `<dir>/constitution/Constitution.md` exists.
4. First match wins; print its absolute path and exit 0.
5. If no ancestor matches, exit non-zero with an error.

This works at any nesting depth:

```
SomeBigProject/                                ← parent project, ships constitution
├── constitution/                               ← provided by the parent
│   ├── Constitution.md
│   ├── CLAUDE.md
│   ├── AGENTS.md
│   └── find_constitution.sh
└── third-party/
    ├── notification/
    │   └── Herald/                            ← Herald lives here; walks up 3 levels
    │       └── tests/test_constitution_inheritance.sh
```

From Herald's gate, the parent-walk visits Herald/ → notification/ → third-party/ → SomeBigProject/ and matches at the last step.

Standalone development

If you cloned just Herald (no parent project), put a clone of the constitution **alongside** Herald — exactly mirroring the Projects/ layout used during Herald's bootstrap:

```
git clone git@github.com:HelixDevelopment/HelixConstitution.git \
    $(dirname "$PWD")/constitution
```

This gives you Projects/Herald/ (your work) and Projects/constitution/ (the sibling). Parent-walk from Herald visits Herald/ → Projects/ and matches.

Do not clone the constitution inside Herald. The gate's invariant I6 will FAIL if <repo-root>/constitution/ or .gitmodules reappears.

The inheritance gate

tests/test_constitution_inheritance.sh is read-only and idempotent. It asserts:

Invariant What it checks

- I1** A constitution/Constitution.md is reachable via parent-walk from Herald's repo root. Prints the discovered path.
- I2** The discovered Constitution.md contains the exact line `### §11.4 End-user quality guarantee – forensic anchor (User mandate, 2026-04-28)`. This is the line the §1.1 mutation removes; the gate's I2 and the mutation's removal are paired by design.
- I3** The discovered CLAUDE.md contains `MANDATORY ANTI-BLUFF COVENANT`.
- I4** The discovered AGENTS.md contains `Anti-bluff covenant`.
- I5a** Herald's CLAUDE.md declares `INHERITED FROM Helix Constitution` and references `find_constitution.sh`.
- I5b** Herald's AGENTS.md references `find_constitution.sh`.
- I5c** `docs/guides/HERALD_CONSTITUTION.md` extends the Helix Universal Constitution.
- I5d** `README.md` documents the Helix Constitution inheritance contract.
- I6** No constitution/ directory or .gitmodules file exists at Herald's root (§104).

Run:

```
bash tests/test_constitution_inheritance.sh
```

Expected output on a healthy tree:

```
PASS I1 constitution discovered at /Users/<you>/Projects/constitution
PASS I2 Constitution.md contains §11.4 forensic anchor
PASS I3 constitution/CLAUDE.md contains anti-bluff covenant anchor
PASS I4 constitution/AGENTS.md contains anti-bluff covenant anchor
PASS I5a CLAUDE.md declares Helix Constitution inheritance (parent-discov
PASS I5b AGENTS.md references the parent-provided constitution + find_con
```

```
PASS I5c HERALD_CONSTITUTION.md extends the Helix Universal Constitution
PASS I5d README.md documents the constitution-inheritance contract
PASS I6 No constitution submodule embedded in Herald
----
Result: 9 PASS / 0 FAIL
```

Non-zero exit means at least one invariant FAILED; fix the offending invariant at root cause per Universal §11.4.4 (test-interrupt-on-discovery).

Common failure: FAIL I1 constitution NOT found ...

Means there's no `<ancestor>/constitution/Constitution.md` reachable above Herald. Either:

- **You're working standalone** — clone the constitution as a sibling (see [Standalone development](#)).
- **You're inside a parent project that lacks the constitution submodule** — fix the parent. Herald is not the right place to fix this.

Common failure: FAIL I6 No constitution submodule embedded in Herald

Means somebody re-added `constitution/` inside Herald (a §104 violation). Remove it cleanly:

```
git submodule deinit -f constitution
git rm -f constitution
rm -rf .git/modules/constitution
# If .gitmodules becomes empty, delete it too:
[ ! -s .gitmodules ] && git rm -f .gitmodules
```

The paired mutation meta-test (§1.1)

`tests/test_constitution_inheritance_meta.sh` is the proof that the gate is not itself a bluff. Per Universal §1.1, every gate must have a paired mutation demonstrating it catches the regression it claims to catch.

The meta-test:

1. Discovers the constitution (same algorithm as the gate).
2. Delegates to `<discovered>/meta_test_inheritance.sh`, passing Herald's gate as the command-under-test.
3. The constitution's meta-runner snapshots `Constitution.md`, strips the §11.4 anchor, runs Herald's gate, asserts the gate exits non-zero, then restores the file.
4. If the gate exited zero with the anchor removed, the meta-test fails with `META-TEST FAIL: gate returned 0 even though the §11.4 anchor was removed`.

Run:

```
bash tests/test_constitution_inheritance_meta.sh
```

Expected output on a healthy tree:

Mutation applied: §11.4 anchor removed from Constitution.md
Running consuming-project gate: bash '/.../tests/test_constitution_inheritance'
✓ META-TEST PASS: gate correctly FAILED (rc=1) on mutated Constitution

The restore happens via trap inside the constitution-side runner; if you ever see a .bak file alongside Constitution.md after a meta-test run, the restore was interrupted — restore manually from the .bak.

When to run the gates

- **Before any commit that touches root docs** (CLAUDE.md, AGENTS.md, README.md), docs/guides/, or tests/test_constitution_inheritance*.
- **After cloning** Herald standalone, immediately after cloning the constitution sibling.
- **In CI** as a precondition to any other test (catches drift early).
- **When integrating Herald into a new parent project** to confirm discovery works at the new nesting depth.

Promoting Herald rules into the constitution

If Herald grows a rule that genuinely deserves universal status (applies to ≥ 3 unrelated projects, references no Herald-specific tech, encodes a policy not a configuration value), promote it via the HelixConstitution repo, not by editing the parent's constitution/ from Herald. Universal §11.4 + §11.4.10 require this audit; the default is to keep rules in docs/guides/HERALD_CONSTITUTION.md until the audit clears.

Glossary

- **Parent project** — the larger project that includes Herald as a submodule and provides <parent>/constitution/.
- **Discovered constitution** — the result of parent-walk; the absolute path printed by bash <ancestor>/constitution/find_constitution.sh or by I1 of Herald's gate.
- **Forensic anchor** — the exact line ### §11.4 End-user quality guarantee — forensic anchor (User mandate, 2026-04-28). The gate checks for it; the meta-test removes it.
- **Bluff gate** — a gate that returns PASS without actually checking the thing it claims to check. Universal §1.1 forbids them; paired mutations are the mechanism that catches them.