

# Herald



{width=96px height=96px}

## Herald — Aider Dispatcher Setup Guide

| Field                  | Value                                                                                                      |
|------------------------|------------------------------------------------------------------------------------------------------------|
| Status                 | <b>PLANNED</b> — HRD-NNN (planned)                                                                         |
| Spec ref               | V3 §33 (pluggable Dispatcher)                                                                              |
| Env vars<br>(reserved) | HERALD_AIDER_BIN, HERALD_AIDER_MODEL (e.g. <code>claude-3-5-sonnet-20241022</code> ), HERALD_AIDER_API_KEY |
| Code                   | (not yet implemented)                                                                                      |

Aider is a popular open-source pair-programming CLI agent. Different envelope+reply format than Claude Code — the adapter will translate.

This guide is a **placeholder**. When the Aider dispatcher lands as an HRD, this file will expand to the same step-by-step structure as [CLAUDE\\_CODE.md](#): install the CLI/SDK → set env vars → verify session resolution → verify Dispatch round-trip → troubleshooting.

### What you can do now

- Reserve the env-var names in your `.env` per [../OPERATOR\\_CREDENTIALS.md](#).
- The Dispatcher interface in `commons_messaging/dispatch/` is the seam every new dispatcher implements — see the Claude Code implementation as the reference shape.

### Related

- [OPERATOR\\_CREDENTIALS.md](#) §"Alternate LLM dispatchers"
- [CLAUDE\\_CODE.md](#) — canonical live-dispatcher guide shape
- Spec: V3 §33 (pluggable Dispatcher)