

Herald



{width=96px height=96px}

Herald — Cursor Dispatcher Setup Guide

Field	Value
Status	PLANNED — HRD-NNN (planned)
Spec ref	V3 §33 (pluggable Dispatcher)
Env vars (reserved)	HERALD_CURSOR_BIN, HERALD_CURSOR_PROJECT_NAME
Code	(not yet implemented)

Cursor is the AI-first IDE. Its CLI surface is evolving; integration will follow when Cursor exposes a stable headless API or CLI.

This guide is a **placeholder**. When the Cursor dispatcher lands as an HRD, this file will expand to the same step-by-step structure as [CLAUDE_CODE.md](#): install the CLI/SDK → set env vars → verify session resolution → verify Dispatch round-trip → troubleshooting.

What you can do now

- Reserve the env-var names in your `.env` per [../OPERATOR_CREDENTIALS.md](#).
- The Dispatcher interface in `commons_messaging/dispatch/` is the seam every new dispatcher implements — see the Claude Code implementation as the reference shape.

Related

- [OPERATOR_CREDENTIALS.md](#) §"Alternate LLM dispatchers"
- [CLAUDE_CODE.md](#) — canonical live-dispatcher guide shape
- Spec: V3 §33 (pluggable Dispatcher)