

Herald



{width=96px height=96px}

Herald — Email (SMTP + Resend) Channel Setup Guide

Field	Value
Status	PLANNED — HRD-NNN (planned V2)
Spec ref	V3 §11.4 + §11.9
Env vars (reserved)	HERALD_SMTP_HOST, HERALD_SMTP_PORT, HERALD_SMTP_USERNAME, HERALD_SMTP_PASSWORD, HERALD_SMTP_FROM OR HERALD_RESEND_API_KEY, HERALD_RESEND_FROM
Code	(not yet implemented)

Email is planned for V2. Two backends will be supported: raw SMTP (any provider — Postmark, SES, etc.) and Resend (transactional email API). Choose ONE based on your infra. The `mailto://` adapter URL form encodes the destination address.

This guide is a **placeholder**. When the Email (SMTP + Resend) adapter lands as an HRD, this file will expand to the same step-by-step structure as [TELEGRAM.md](#): obtain credentials → set env vars → verify HealthCheck → verify Send → optional Subscribe → troubleshooting.

What you can do now

- Reserve the env-var names in your `.env` (commented out, per [../OPERATOR_CREDENTIALS.md](#)).
- Watch the HRD for status updates — it will move from `open` to `code complete`; awaiting live evidence to `Fixed` over its implementation lifecycle.
- If you have an urgent need for the Email (SMTP + Resend) channel, open an issue against the HRD asking for priority — operator-driven escalation is honored per the constitution.

Related

- [OPERATOR_CREDENTIALS.md](#) — the umbrella credentials guide with reserved env-var blocks for every planned channel
- [TELEGRAM.md](#) — the canonical live-channel guide shape (this file will mirror that structure when Email (SMTP + Resend) lands)
- Spec: V3 §11.4 + §11.9