

Herald



{width=96px height=96px}

Herald — Slack Channel Setup Guide

Field	Value
Status	PLANNED — HRD-NNN (planned V2)
Spec ref	V3 §11.2 + §11.9
Env vars (reserved)	HERALD_SLACK_BOT_TOKEN, HERALD_SLACK_SIGNING_SECRET, HERALD_SLACK_APP_TOKEN, HERALD_SLACK_DEFAULT_CHANNEL
Code	(not yet implemented)

Slack is planned for V2. The adapter will support both Events API (HTTPS webhooks) and Socket Mode (WebSocket — useful for hosts without inbound HTTPS). Channels are addressed by ID (not name) since Slack channels are renamable while IDs are stable.

This guide is a **placeholder**. When the Slack adapter lands as an HRD, this file will expand to the same step-by-step structure as [TELEGRAM.md](#): obtain credentials → set env vars → verify HealthCheck → verify Send → optional Subscribe → troubleshooting.

What you can do now

- Reserve the env-var names in your `.env` (commented out, per [../OPERATOR_CREDENTIALS.md](#)).
- Watch the HRD for status updates — it will move from `open` to `code complete`; `awaiting live evidence` to `Fixed` over its implementation lifecycle.
- If you have an urgent need for the Slack channel, open an issue against the HRD asking for priority — operator-driven escalation is honored per the constitution.

Related

- [OPERATOR_CREDENTIALS.md](#) — the umbrella credentials guide with reserved env-var blocks for every planned channel
- [TELEGRAM.md](#) — the canonical live-channel guide shape (this file will mirror that structure when Slack lands)
- Spec: V3 §11.2 + §11.9