

Herald — CURSOR

Herald — Cursor Dispatcher Setup Guide
What you can do now
Related

Herald — Cursor Dispatcher Setup Guide

Field	Value
Status	PLANNED — HRD-NNN (planned)
Spec ref	V3 §33 (pluggable Dispatcher)
Env vars (reserved)	HERALD_CURSOR_BIN, HERALD_CURSOR_PROJECT_NAME
Code	(not yet implemented)

Cursor is the AI-first IDE. Its CLI surface is evolving; integration will follow when Cursor exposes a stable headless API or CLI.

This guide is a **placeholder**. When the Cursor dispatcher lands as an HRD, this file will expand to the same step-by-step structure as CLAUDE_CODE.md: install the CLI/SDK → set env vars → verify session resolution → verify Dispatch round-trip → troubleshooting.

What you can do now

- Reserve the env-var names in your .env per ./OPERATOR_CREDENTIALS.md.
- The Dispatcher interface in commons_messaging/dispatch/ is the seam every new dispatcher implements — see the Claude Code implementation as the reference shape.

Related

- OPERATOR_CREDENTIALS.md §“Alternate LLM dispatchers”
- CLAUDE_CODE.md — canonical live-dispatcher guide shape
- Spec: V3 §33 (pluggable Dispatcher)