

Herald — MAX

Herald — Max Channel Setup Guide

What you can do now

Related

Herald — Max Channel Setup Guide

Field	Value
Status	PLANNED — HRD-NNN (planned V2)
Spec ref	V3 §11.3
Env vars (reserved)	HERALD_MAX_BOT_TOKEN, HERALD_MAX_CHAT_ID
Code	(not yet implemented)

Max is the Russian-market messenger; Bot API similar in shape to Telegram's. Planned for V2 alongside Telegram + Slack. Detailed bot-creation steps (analogous to Telegram's @BotFather flow) will land when the HRD opens.

This guide is a **placeholder**. When the Max adapter lands as an HRD, this file will expand to the same step-by-step structure as [TELEGRAM.md](#): obtain credentials → set env vars → verify HealthCheck → verify Send → optional Subscribe → troubleshooting.

What you can do now

- Reserve the env-var names in your `.env` (commented out, per [../OPERATOR_CREDENTIALS.md](#)).
- Watch the HRD for status updates — it will move from open to code complete; awaiting live evidence to Fixed over its implementation lifecycle.
- If you have an urgent need for the Max channel, open an issue against the HRD asking for priority — operator-driven escalation is honored per the constitution.

Related

- [OPERATOR_CREDENTIALS.md](#) — the umbrella credentials guide with reserved env-var blocks for every planned channel

- TELEGRAM.md — the canonical live-channel guide shape (this file will mirror that structure when Max lands)
- Spec: V3 §11.3