

HRD-011 + HRD-012 Implementation Plan

HRD-011 (Telegram) + HRD-012 (Claude Code) Live Wiring Implementation Plan

File Structure

Files to CREATE

Files to MODIFY

Files NOT touched (deferred to later HRDs)

Task 1: Vendor telebot.v3 as a Helix-style submodule

Task 2: Telegram HealthCheck against live Bot API

Task 3: Telegram Send (sendMessage + sendDocument)

Task 4: Telegram Subscribe (getUpdates long-poll)

Task 5: Telegram persistence (outbound_delivery_evidence)

Task 6: Claude Code Dispatch (live claude --resume invocation)

Task 7: Claude Code session persistence

Task 8: Vertical-slice integration test (E19)

Task 9: Add E17/E18/E19 to e2e_bluff_hunt.sh

Task 10: .env.example + atomic Issues→Fixed for HRD-011 + HRD-012

Task 11: Anti-bluff battery + multi-mirror push

Self-Review

Execution Handoff

HRD-011 (Telegram) + HRD-012 (Claude Code) Live Wiring Implementation Plan

For agentic workers: REQUIRED SUB-SKILL: Use superpowers:subagent-driven-development (recommended) or superpowers:executing-plans to implement this plan task-by-task. Steps use checkbox (– []) syntax for tracking.

Goal: Land Herald's first true end-user-visible vertical slice: a real Telegram message arrives → Herald dispatches it to Claude Code via claude --resume <session> → the <<<HERALD-REPLY>>> is parsed → reply gets sent back through Telegram. Closes HRD-011 + HRD-012; adds §107 E17 (Telegram round-trip) + E18 (Claude Code round-trip) + E19 (full slice round-trip) invariants to scripts/e2e_bluff_hunt.sh.

Architecture: Two thin live integrations on top of Plan 1's storage stack. `commons_messaging/channels/tgram/` swaps its stub `Send/Subscribe/HealthCheck` for real `telebot.v3` calls (vendored as `submodules/telebot/`) and persists `outbound_delivery_evidence` rows via the live `commons_storage` pool. `commons_messaging/dispatch/claude_code/` swaps its stub `Dispatch` for a real `claude --resume <UUID> --print "<envelope>"` invocation with structured stdout parsing. The full slice ties them: an inbound Telegram message routed through the `Subscriber` model (§7) → `claude_code.Dispatch` → `parsed <<<HERALD-REPLY>>>` → `tgram.Send`. All three new e2e invariants SKIP-with-reason per §11.4.3 if operator credentials absent.

Tech Stack: Go 1.25+; `gopkg.in/telebot.v3` (vendored as `submodules/telebot/`); `claude` CLI (external binary, operator-supplied); `pgx` + `commons_storage` for persistence; `commons_infra` for the live pool. Operator-supplied env vars: `HERALD_TGRAM_BOT_TOKEN`, `HERALD_TGRAM_CHAT_ID`, `HERALD_CLAUDE_BIN` (defaults to `claude` on `$PATH`), `HERALD_CLAUDE_PROJECT_NAME`.

Spec refs: HRD-011, HRD-012 in `docs/Issues.md`; spec V3 §11.1 (Telegram), §32 (subscriber-reply loops), §33 (LLM/agent dispatch), §33.2 (session-resolution algorithm); master roadmap §“Wave 1 — Storage + first user-visible feature”.

Catalogue-Check (Universal §11.4.74): - no-match → vendor `gopkg.in/telebot.v3` as `submodules/telebot/` (no equivalent in `vasic-digital/HelixDevelopment` per §11.4.74 mandate) - extend `digital.vasic.database@<pinned>` (`pgx` + `commons_storage` live pool from Plan 1) - no-match → `claude` CLI is an external binary, not a library - extend `digital.vasic.background.TaskQueue` if queueing outbound retries (deferred to a future HRD; this plan uses synchronous `Send`)

The HRD-011 row's References cell MUST be updated with the resolved Catalogue-Check value before HRD-011 closes in Task 11.

File Structure

Files to CREATE

Path	Responsibility
<code>submodules/telebot/</code>	NEW git submodule pointing at https://github.com/tucnak/telebot.git (the <code>gopkg.in/telebot.v3</code> repo)
<code>commons_messaging/channels/tgram/send.go</code>	Live <code>sendMessage</code> + <code>sendDocument</code> against Bot API via <code>telebot.Client</code>
<code>commons_messaging/channels/tgram/subscribe.go</code>	<code>getUpdates</code> long-poll (25s) + 30s safety-net timer per §32.2
<code>commons_messaging/channels/tgram/healthcheck.go</code>	<code>getMe</code> API call to verify bot token
<code>commons_messaging/channels/tgram/persist.go</code>	Persist <code>outbound_delivery_evidence</code>

Path	Responsibility
	rows via injected commons_storage.Database
commons_messaging/channels/tgram/tgram_integration_test.go	//go:build integration — Telegram round-trip live test (E17)
commons_messaging/dispatch/claude_code/dispatch.go	Live claude --resume <UUID> --print "<envelope>" invocation + stdout parse
commons_messaging/dispatch/claude_code/dispatch_integration_test.go	//go:build integration — Claude Code round-trip live test (E18)
commons_messaging/dispatch/claude_code/persist.go	Persist session_state rows (session UUID + last_dispatch_at) via injected DB
commons_messaging/vertical_slice_integration_test.go	//go:build integration — full Telegram→Claude→Telegram slice (E19)
docs/Fixed.md HRD-011 + HRD-012 entries	Atomic Issues→Fixed at end

Files to MODIFY

Path	Change
commons_messaging/channels/tgram/tgram.go	Inject the live *telebot.Bot client into Adapter; remove “not implemented” stubs and delegate to send.go / subscribe.go / healthcheck.go
commons_messaging/channels/tgram/go.mod	Add require gopkg.in/telebot.v3 v3.x.x + replace gopkg.in/telebot.v3 => ../../../../submodules/telebot
commons_messaging/dispatch/claude_code/claude_code.go	Inject os/exec-backed runner into Dispatcher; remove stub return; delegate to dispatch.go
commons_storage/migrations/000010_outbound_delivery_evidence.up.sql + .down.sql	NEW migration if not already present in 000001..000005 — verify first via grep -l outbound_delivery commons_storage/migrations/*.sql
commons_storage/migrations/000011_session_state.up.sql + .down.sql	NEW migration for Claude Code session tracking — verify §33 says what columns are needed
commons_storage/migrations_test.go	

Path	Change
	Bump expected migration count if migrations 000010/000011 are added
pherald/cmd/pherald/serve.go (or equivalent)	Wire the live Telegram subscriber + Claude Code dispatcher loop into pherald serve (if pherald owns the slice runner — verify; otherwise this lives in a separate run target)
scripts/e2e_bluff_hunt.sh	Add E17 (Telegram round-trip), E18 (Claude Code round-trip), E19 (full slice) invariants; bump count 18 → 21
quickstart/.env.example	Document HERALD_TGRAM_BOT_TOKEN, HERALD_TGRAM_CHAT_ID, HERALD_CLAUDE_BIN, HERALD_CLAUDE_PROJECT_NAME
docs/Issues.md	Atomic migrate HRD-011 + HRD-012 rows → Fixed.md (per §11.4.19) at the end of Task 11
docs/Status.md	r7 → r8: commons_messaging Telegram + Claude Code now 
docs/{Issues,Fixed,Status}. {html,docx,pdf}	Regenerate after edits

Files NOT touched (deferred to later HRDs)

- commons_messaging/channels/{slack,email,markdown,...} — out of Wave 1 scope
- commons_messaging/dispatch/{openai,aider,...} — §33 lists these as later iterations
- §42 constitution bindings (Wave 3) — not touched by Plan 2

Task 1: Vendor telebot.v3 as a Helix-style submodule

Why first: Per §11.4.74 + CLAUDE.md’s “Vendored SDKs” rule, the Telegram SDK MUST be a git submodule (not go get’d into go.mod). Vendor it first so all subsequent tasks can use the real type.

Files: - New submodule: submodules/telebot/ - Modify: .gitmodules - Modify: commons_messaging/channels/tgram/go.mod (require + replace)



Step 1: Verify telebot.v3’s upstream repo is accessible

Run:

```
cd /Users/milosvasic/Projects/Herald
git ls-remote https://github.com/tucnak/telebot.git 2>&1 | head -3
```

Expected: lists remote heads (proves the repo exists and is reachable). If access fails, fall back to checking the v3 tag exists via `git ls-remote https://github.com/tucnak/telebot.git v3.*`.



Step 2: Add the submodule

Run:

```
git submodule add https://github.com/tucnak/telebot.git
submodules/telebot
cd submodules/telebot
git checkout v3.3.8
# or whatever the latest v3.* stable tag is – verify with
`git tag | grep '^v3' | sort -V | tail -5` first
cd ../../
git submodule update --init --recursive
```

NOTE: Use a tagged version, NOT main. Tagged versions are reproducible. If v3.3.8 doesn't exist, pick the highest v3.*.* tag.



Step 3: Add require + replace in commons_messaging/channels/tgram/go.mod

Wait — `commons_messaging/channels/tgram/` is not its own module today. Verify:

```
ls commons_messaging/channels/tgram/
ls commons_messaging/
find commons_messaging -name 'go.mod'
```

If `commons_messaging/` has a single `go.mod` at its root, modify THAT file. Add:

```
require gopkg.in/telebot.v3 v3.3.8 // adjust to the actual tag
you pinned
```

```
replace gopkg.in/telebot.v3 => ../submodules/telebot
```

If `commons_messaging/channels/tgram/` is its own submodule with its own `go.mod`, modify that one and adjust the relative path accordingly.

Run `go mod tidy` from the appropriate module root.



Step 4: Verify the import resolves

Run:

```
cd /Users/milosvasic/Projects/Herald
go build ./commons_messaging/channels/tgram/...
```

Expected: clean build. (No imports of telebot yet, but the require+replace must not error.)



Step 5: Confirm inheritance gate still green

Run:

```
bash tests/test_constitution_inheritance.sh 2>&1 | tail -5
```

Expected: 15 PASS / 0 FAIL. The new submodule must NOT trip I6 (which forbids only the constitution/ path) per HRD-080 refinement.



Step 6: Commit

```
git add .gitmodules submodules/telebot commons_messaging/go.mod
      commons_messaging/go.sum # adjust paths
git commit -m "HRD-011 step 1: vendor telebot.v3 as submodules/
      telebot"
```

Per Universal §11.4.74 + Herald CLAUDE.md \"Vendored SDKs\" rule,
the
Telegram Bot API client lives as a git submodule, not go get'd.
Pinned
to v3.3.8 (or whatever stable tag was selected) for
reproducibility.

Catalogue-Check: no-match (no Telegram SDK exists in
vasic-digital/HelixDevelopment); vendor as Herald submodule.

Inheritance gate 15/15 PASS unchanged (HRD-080 I6 refinement
permits
non-constitution submodules).

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

DO NOT push.

Task 2: Telegram HealthCheck against live Bot API

Why second: HealthCheck is the smallest live integration — proves token works before Send/Subscribe touch the wire.

Files: - Create: commons_messaging/channels/tgram/healthcheck.go -
Modify: commons_messaging/channels/tgram/tgram.go (inject telebot.Bot;
rewire HealthCheck)



Step 1: Write failing integration test

Create commons_messaging/channels/tgram/
healthcheck_integration_test.go:

```
//go:build integration
```

```
package tgram
```

```
import (  
    "context"  
    "os"  
    "testing"  
    "time"  
)
```

```
func TestHealthCheck_LiveBotAPI(t *testing.T) {  
    token := os.Getenv("HERALD_TGRAM_BOT_TOKEN")  
    if token == "" {  
        t.Skipf("skip: hardware_not_present -  
        HERALD_TGRAM_BOT_TOKEN absent per §11.4.3 explicit SKIP-  
        with-reason")  
    }  
    chatID := os.Getenv("HERALD_TGRAM_CHAT_ID")  
    if chatID == "" {  
        t.Skipf("skip: hardware_not_present - HERALD_TGRAM_CHAT_ID  
        absent")  
    }  
  
    a, err := New("tgram://" + token + "/" + chatID)  
    if err != nil {  
        t.Fatalf("New: %v", err)  
    }  
    ctx, cancel := context.WithTimeout(context.Background(),  
        30*time.Second)  
    defer cancel()  
    if err := a.HealthCheck(ctx); err != nil {  
        t.Fatalf("HealthCheck against live Bot API: %v", err)  
    }  
}
```



Step 2: Run, expect FAIL (“not implemented”)

Run:

```
cd /Users/milosvasic/Projects/Herald  
HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN  
HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID \  
go test ./commons_messaging/channels/tgram/ -tags=integration  
-run TestHealthCheck_LiveBotAPI -count=1 -timeout=60s
```

If no operator-supplied credentials: SKIP cleanly per the build-tag dance. If credentials present: expect FAIL with “not implemented”.



Step 3: Inject telebot.Bot into Adapter

Modify commons_messaging/channels/tgram/tgram.go:

Update the Adapter struct:

```
type Adapter struct {
    botToken string
    chatID   string
    bot      *telebot.Bot // nil until first connection
}
```

Add the telebot import:

```
import (
    // ... existing ...
    telebot "gopkg.in/telebot.v3"
)
```



Step 4: Create commons_messaging/channels/tgram/healthcheck.go

```
package tgram
```

```
import (
    "context"
    "fmt"

    telebot "gopkg.in/telebot.v3"
)

// HealthCheck verifies the bot token by issuing a getMe call
// against the
// live Bot API. Returns nil only if the API responds with a non-
// empty
// bot username – proves the token is valid AND the bot is
// enabled.
//
// Per §107: HealthCheck is the cheapest live evidence the adapter
// works.
// A PASS without observing a real getMe response would be a §107
// bluff.
func (a *Adapter) HealthCheck(ctx context.Context) error {
    if a.bot == nil {
        bot, err := telebot.NewBot(telebot.Settings{
            Token:  a.botToken,
            Client: nil, // use default http.Client
        })
        if err != nil {
```



```

        return fmt.Errorf("tgram: connect to Bot API: %w",
            err)
    }
    a.bot = bot
}
me, err := a.bot.Raw("getMe", nil)
if err != nil {
    return fmt.Errorf("tgram: getMe: %w", err)
}
// telebot.Bot.Raw returns the JSON response body bytes;
// assert non-empty.
if len(me) == 0 {
    return fmt.Errorf("tgram: getMe returned empty body (§107
        bluff guard)")
}
return nil
}

```

NOTE: telebot.v3's API: confirm Bot.Raw(method, params interface{}) ([]byte, error) exists. If the API surface differs (e.g., Bot.Me() returns a *User directly), use that and assert me.Username != "". Adjust based on what go doc gopkg.in/telebot.v3.Bot returns.



Step 5: Remove the stub HealthCheck from tgram.go

Delete the old func (a *Adapter) HealthCheck(ctx context.Context) error that returns errors.New("not implemented") from tgram.go. The new one in healthcheck.go replaces it.



Step 6: Run unit + integration tests

```

go test -race -count=1 ./commons_messaging/channels/tgram/
    # unit only
HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN
HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID \
go test ./commons_messaging/channels/tgram/ -tags=integration
    -run TestHealthCheck_LiveBotAPI -count=1 -timeout=60s

```

Expected: - Unit tests: still PASS (HealthCheck has no unit test currently — and we're NOT adding one for the live wire since unit-testing real network calls is meaningless mocking) - Integration test (with creds): PASS — getMe succeeds, non-empty body - Integration test (without creds): SKIP-with-reason



Step 7: Commit

```

git add commons_messaging/channels/tgram/tgram.go
    commons_messaging/channels/tgram/healthcheck.go
    commons_messaging/channels/tgram/
        healthcheck_integration_test.go
git commit -m "HRD-011 step 2: Telegram HealthCheck against live
    Bot API

```

Replaces the stub HealthCheck with a real getMe call via telebot.v3.
Integration test (//go:build integration) SKIPS cleanly if HERALD_TGRAM_BOT_TOKEN absent (§11.4.3); PASSES only if Bot API responds with non-empty body.

§107 evidence: cheapest live wire – proves token valid + bot enabled

before later tasks touch sendMessage / getUpdates.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 3: Telegram Send (sendMessage + sendDocument)

Files: - Create: commons_messaging/channels/tgram/send.go - Modify: commons_messaging/channels/tgram/tgram.go (rewire Send)



Step 1: Write failing integration test

Append to commons_messaging/channels/tgram/healthcheck_integration_test.go (or create send_integration_test.go):

//go:build integration

package tgram

```
import (  
    "context"  
    "os"  
    "testing"  
    "time"  
  
    "github.com/vasic-digital/herald/commons"  
)
```

```
func TestSend_LiveBotAPI(t *testing.T) {  
    token := os.Getenv("HERALD_TGRAM_BOT_TOKEN")  
    chatID := os.Getenv("HERALD_TGRAM_CHAT_ID")  
    if token == "" || chatID == "" {  
        t.Skipf("skip: hardware_not_present –  
            HERALD_TGRAM_BOT_TOKEN or _CHAT_ID absent")  
    }  
  
    a, err := New("tgram://" + token + "/" + chatID)  
    if err != nil {  
        t.Fatalf("New: %v", err)  
    }  
    ctx, cancel := context.WithTimeout(context.Background(),  
        30*time.Second)
```

```

defer cancel()

msg := commons.OutboundMessage{
    Body: commons.Body{
        Text: "Herald E17 integration test " +
            time.Now().Format(time.RFC3339Nano),
    },
    Recipient: commons.Recipient{
        ChannelID: commons.ChannelID("tgram://" + token + "/"
            + chatID),
    },
}
receipt, err := a.Send(ctx, msg)
if err != nil {
    t.Fatalf("Send: %v", err)
}
if receipt.MessageID == "" {
    t.Fatalf("Send returned empty MessageID – §107 bluff guard
        (proves Telegram actually received the message and
        returned a chat-side ID)")
}
}

```



Step 2: Run, expect FAIL (“not implemented”)

```

HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN
HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID \
go test ./commons_messaging/channels/tgram/ -tags=integration
    -run TestSend_LiveBotAPI -count=1 -timeout=60s

```

Expected: FAIL with “not implemented” or SKIP without creds.



Step 3: Create commons_messaging/channels/tgram/send.go

```

package tgram

import (
    "context"
    "fmt"
    "strconv"

    telebot "gopkg.in/telebot.v3"

    "github.com/vasic-digital/herald/commons"
)

// Send dispatches a single OutboundMessage to the bot's
// configured chat.
// Uses telebot.v3's Bot.Send with parseMode=MarkdownV2 per spec
// §11.1.
// On success, returns a Receipt with the Telegram-side message ID
// for

```

```

// idempotency tracking.
//
// Anti-bluff (§107): the returned Receipt.MessageID MUST be the
// chat-side
// integer assigned by Telegram, not a Herald-generated UUID. A
// PASS that
// returns a fake ID is a §107 bluff.
func (a *Adapter) Send(ctx context.Context, msg
    commons.OutboundMessage) (commons.Receipt, error) {
    if a.bot == nil {
        // Lazy connect on first Send.
        bot, err := telebot.NewBot(telebot.Settings{Token:
            a.botToken})
        if err != nil {
            return commons.Receipt{}, fmt.Errorf("tgram.Send:
                connect: %w", err)
        }
        a.bot = bot
    }

    chatIDInt, err := strconv.ParseInt(a.chatID, 10, 64)
    if err != nil {
        return commons.Receipt{}, fmt.Errorf("tgram.Send: chatID
            %q not numeric: %w", a.chatID, err)
    }
    chat := &telebot.Chat{ID: chatIDInt}

    opts := &telebot.SendOptions{
        ParseMode: telebot.ModeMarkdownV2,
    }
    sent, err := a.bot.Send(chat, msg.Body.Text, opts)
    if err != nil {
        return commons.Receipt{}, fmt.Errorf("tgram.Send:
            sendMessage: %w", err)
    }
    if sent == nil || sent.ID == 0 {
        return commons.Receipt{}, fmt.Errorf("tgram.Send: empty
            sent message - §107 bluff guard")
    }

    return commons.Receipt{
        MessageID: strconv.Itoa(sent.ID),
        Evidence: commons.DeliveryEvidence(1), // delivered
    }, nil
}

```

NOTE: Confirm `telebot.Bot.Send(to telebot.Recipient, what interface{}, opts ...interface{}) (*telebot.Message, error)` exists with this signature. Look at `submodules/telebot/bot.go` to verify. If the signature differs, adjust.

NOTE: `commons.DeliveryEvidence` is an int enum. Use the proper constant from `commons/types.go` instead of 1 — look up the value for “delivered” (likely `commons.DeliveryDelivered` or similar). DO NOT hardcode the integer.



Step 4: Remove stub Send from `tgram.go`

Delete the old stub

```
Send(ctx, msg) (Receipt, error) { return Receipt{},
errors.New("not implemented") }.
```



Step 5: Run integration test (with creds)

```
HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN
HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID \
go test ./commons_messaging/channels/tgram/ -tags=integration
-run TestSend_LiveBotAPI -count=1 -timeout=60s
```

Expected: PASS. The test bot’s chat receives the test message; the receipt’s `MessageID` is a non-empty Telegram-side integer string.



Step 6: Commit

```
git add commons_messaging/channels/tgram/tgram.go
commons_messaging/channels/tgram/send.go
commons_messaging/channels/tgram/
healthcheck_integration_test.go
git commit -m "HRD-011 step 3: Telegram Send (sendMessage
MarkdownV2)
```

Replaces stub `Send` with real `telebot.v3 Bot.Send` call. Returns `Receipt` with chat-side `MessageID` (the integer Telegram assigns) — not a Herald-generated UUID. §107 bluff guard: asserts non-empty `MessageID` in the integration test, proving the message actually landed in the chat.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 4: Telegram Subscribe (`getUpdates` long-poll)

Files: - Create: `commons_messaging/channels/tgram/subscribe.go` - Modify: `commons_messaging/channels/tgram/tgram.go` (rewire `Subscribe`)

Spec ref: §32.2 — 25s long-poll timeout, 30s safety-net timer for stalled polls.



Step 1: Write integration test

Create commons_messaging/channels/tgram/
subscribe_integration_test.go:

```
//go:build integration
```

```
package tgram
```

```
import (
```

```
    "context"
```

```
    "os"
```

```
    "sync/atomic"
```

```
    "testing"
```

```
    "time"
```

```
    "github.com/vasic-digital/herald/commons"
```

```
)
```

```
// TestSubscribe_LiveBotAPI exercises the long-poll loop. The  
    operator
```

```
// MUST send a message to the configured bot within the 60s test  
    window
```

```
// for the test to PASS; otherwise it SKIPS after the timeout.
```

```
//
```

```
// $!07: an empty-poll PASS is a bluff – the assertion that ≥1  
    message
```

```
// was actually received from the operator's hand-sent message is  
    the
```

```
// load-bearing check.
```

```
func TestSubscribe_LiveBotAPI(t *testing.T) {
```

```
    token := os.Getenv("HERALD_TGRAM_BOT_TOKEN")
```

```
    chatID := os.Getenv("HERALD_TGRAM_CHAT_ID")
```

```
    if token == "" || chatID == "" {
```

```
        t.Skipf("skip: hardware_not_present –  
            HERALD_TGRAM_BOT_TOKEN or _CHAT_ID absent")
```

```
    }
```

```
    if os.Getenv("HERALD_TGRAM_LIVE_INBOUND") != "1" {
```

```
        t.Skipf("skip: hardware_not_present – set  
            HERALD_TGRAM_LIVE_INBOUND=1 AND send a message to the bot  
            within 60s to exercise this test")
```

```
    }
```

```
    a, err := New("tgram://" + token + "/" + chatID)
```

```
    if err != nil {
```

```
        t.Fatalf("New: %v", err)
```

```
    }
```

```
    ctx, cancel := context.WithTimeout(context.Background(),  
        60*time.Second)
```

```
    defer cancel()
```

```
    var got atomic.Int64
```

```
    handler := commons.InboundHandlerFunc(func(ctx
```

```
        context.Context, ev commons.InboundEvent) error {
```

```
        got.Add(1)
```

```
        return nil
```

```

    })
    if err := a.Subscribe(ctx, handler); err != nil && err !=
        context.DeadlineExceeded {
        t.Fatalf("Subscribe: %v", err)
    }
    if got.Load() == 0 {
        t.Fatal("Subscribe received 0 messages from operator's
            hand-sent input – §107 bluff guard (proves getUpdates
            actually pulled real updates)")
    }
}

```

NOTE: `commons.InboundHandlerFunc` may not exist —
`commons.InboundHandler` is an interface. Either: (a) `commons` exposes a
`HandlerFunc` adapter — check `commons/types.go` (b) Define a small local adapter
in the test file (c) Use a struct that implements `InboundHandler`

Use whichever is cleanest. The test must actually invoke the handler when an
inbound message arrives.



Step 2: Run, expect FAIL

```

HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN
HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID
HERALD_TGRAM_LIVE_INBOUND=1 \
go test ./commons_messaging/channels/tgram/ -tags=integration
    -run TestSubscribe_LiveBotAPI -count=1 -timeout=90s

```

Expected: FAIL with “not implemented” (without the inbound flag: SKIP).



Step 3: Create `commons_messaging/channels/tgram/subscribe.go`

```
package tgram
```

```

import (
    "context"
    "fmt"
    "time"

    telebot "gopkg.in/telebot.v3"

    "github.com/vasic-digital/herald/commons"
)

// Subscribe runs the long-poll getUpdates loop until ctx is
// cancelled.
// Per spec §32.2: 25s long-poll timeout, 30s safety-net timer.
//
// Implementation note: telebot.v3 ships its own poller
// (telebot.LongPoller)
// – we wire that with timeout=25s and start the bot. The 30s
// safety-net

```

```

// fires only if the poll thread misses two consecutive 25s
// windows, which
// indicates a real stall. We log + continue rather than die.
func (a *Adapter) Subscribe(ctx context.Context, h
commons.InboundHandler) error {
    if a.bot == nil {
        bot, err := telebot.NewBot(telebot.Settings{
            Token: a.botToken,
            Poller: &telebot.LongPoller{Timeout: 25 *
time.Second},
        })
        if err != nil {
            return fmt.Errorf("tgram.Subscribe: connect: %w", err)
        }
        a.bot = bot
    }

    // telebot dispatches via handler registrations.
    a.bot.Handle(telebot.OnText, func(c telebot.Context) error {
        ev := commons.InboundEvent{
            ChannelID: commons.ChannelID("tgram://" + a.botToken
+ "/" + a.chatID),
            Body: commons.Body{
                Text: c.Message().Text,
            },
            // Source: telebot.v3 Message → commons.InboundEvent
            // mapping
            // - add ConversationRef from c.Message().Chat.ID +
            // MessageID.
        }
        return h.Handle(ctx, ev)
    })

    // Safety-net timer per §32.2.
    stallTicker := time.NewTicker(30 * time.Second)
    defer stallTicker.Stop()
    stallDetect := make(chan struct{}, 1)
    go func() {
        for {
            select {
            case <-ctx.Done():
                return
            case <-stallTicker.C:
                select {
                case stallDetect <- struct{}{}:
                default:
                }
            }
        }
    }()

    // Block until ctx cancelled. telebot.Start runs in this
    // goroutine.
    go a.bot.Start()

```



```

    defer a.bot.Stop()
    <-ctx.Done()
    return ctx.Err()
}

```

NOTE: The above mixes goroutines + telebot's Start. Verify telebot.Start's semantics — is it blocking or non-blocking? Adjust the goroutine wiring to match. If Start is blocking, run it in a goroutine and wait on ctx.

NOTE: commons.InboundHandler.Handle(ctx, ev) error is the interface method — verify the exact method name via
 grep -A 3 'type InboundHandler' commons/types.go. If it's OnInbound or Receive, use that name.



Step 4: Remove stub Subscribe from tgram.go



Step 5: Run integration test with the hand-sent inbound flag

```

# Step a: in another terminal, manually send a Telegram message to
the bot.
# Step b: in this terminal, run:
HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN
HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID
HERALD_TGRAM_LIVE_INBOUND=1 \
go test ./commons_messaging/channels/tgram/ -tags=integration
-run TestSubscribe_LiveBotAPI -count=1 -timeout=90s

```

Expected: PASS within 60s — the handler ran at least once, atomic counter > 0.



Step 6: Commit

```

git add commons_messaging/channels/tgram/tgram.go
commons_messaging/channels/tgram/subscribe.go
commons_messaging/channels/tgram/
subscribe_integration_test.go
git commit -m "HRD-011 step 4: Telegram Subscribe (getUpdates
long-poll)

```

Live long-poll loop with 25s telebot.LongPoller timeout + 30s
 safety-net
 timer per spec §32.2. Real handler invocation on OnText events.

§107: integration test asserts ≥1 handler invocation from an
 operator-
 hand-sent message – proves the loop actually pulled real updates,
 not
 just "no error from polling".

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 5: Telegram persistence (outbound_delivery_evidence)

Files: - Create: commons_messaging/channels/tgram/persist.go - Modify: commons_messaging/channels/tgram/send.go (call Persist after successful Send) - Verify migration exists: commons_storage/migrations/ for outbound_delivery_evidence table



Step 1: Verify the outbound_delivery_evidence schema

```
cd /Users/milosvasic/Projects/Herald
grep -rln 'outbound_delivery' commons_storage/migrations/
```

If a migration already declares the table (likely from Plan 1's M2 work), inspect its columns. If NOT present, create a new migration
000010_outbound_delivery_evidence.up.sql.

Required columns at minimum: - id UUID PK - tenant_id UUID NOT NULL - channel_id TEXT NOT NULL - channel_message_id TEXT NOT NULL (the Telegram-side ID returned by sendMessage) - evidence INT NOT NULL (commons.DeliveryEvidence enum) - sent_at TIMESTAMPTZ DEFAULT now()

If you create the migration, bump commons_storage/migrations_test.go's expected count by 1.



Step 2: Write failing integration test

Create commons_messaging/channels/tgram/persist_integration_test.go:

```
//go:build integration
```

```
package tgram
```

```
import (
    "context"
    "os"
    "testing"
    "time"

    "github.com/google/uuid"
    "github.com/vasic-digital/herald/commons"
    infra "github.com/vasic-digital/herald/commons_infra"
    storage "github.com/vasic-digital/herald/commons_storage"
)
```

```
func TestSend_PersistsDeliveryEvidence(t *testing.T) {
    token := os.Getenv("HERALD_TGRAM_BOT_TOKEN")
    chatID := os.Getenv("HERALD_TGRAM_CHAT_ID")
    if token == "" || chatID == "" {
```

```

        t.Skipf("skip: hardware_not_present – Telegram credentials
absent")
    }
    if _, err := exec.LookPath("podman"); err != nil {
        if _, err := exec.LookPath("docker"); err != nil {
            t.Skipf("skip: hardware_not_present – no container
runtime")
        }
    }
}

ctx, cancel := context.WithTimeout(context.Background(),
    120*time.Second)
defer cancel()
boot, err := infra.NewQuickstartBoot(infra.Config{Services:
    []string{"postgres"}})
if err != nil {
    t.Fatalf("NewQuickstartBoot: %v", err)
}
if err := boot.Up(ctx); err != nil {
    t.Fatalf("Up: %v", err)
}
t.Cleanup(func() { _ = boot.Down(context.Background()) })

pool, err := boot.Pool()
if err != nil {
    t.Fatalf("Pool: %v", err)
}

a, err := NewWithStorage("tgram://" + token + "/" + chatID,
    pool) // NEW constructor – see Step 3
if err != nil {
    t.Fatalf("NewWithStorage: %v", err)
}

tenant := uuid.New()
msgText := "Herald E17 persist test " +
    time.Now().Format(time.RFC3339Nano)
receipt, err := a.SendForTenant(ctx, tenant,
    commons.OutboundMessage{
        Body: commons.Body{Text: msgText},
        Recipient: commons.Recipient{ChannelID:
            commons.ChannelID("tgram://" + token + "/" + chatID)},
    })
if err != nil {
    t.Fatalf("SendForTenant: %v", err)
}

// Read back the persisted row via WithTenantContext.
var persistedChannelMsgID string
err = storage.WithTenantContext(ctx, pool, tenant, func(tx
    db.Tx) error {
    return tx.QueryRow(ctx,

```

```

        `SELECT channel_message_id FROM
        outbound_delivery_evidence WHERE tenant_id = $1 ORDER BY
        sent_at DESC LIMIT 1`,
        tenant,
    ).Scan(&persistedChannelMsgID)
})
if err != nil {
    t.Fatalf("read-back: %v", err)
}
if persistedChannelMsgID != receipt.MessageID {
    t.Fatalf("persisted channel_message_id mismatch: got %q
    want %q ($107 bluff guard)", persistedChannelMsgID,
    receipt.MessageID)
}
}
}

```

NOTE: `NewWithStorage` and `SendForTenant` are new APIs you'll define in Step 3. The existing `Send` doesn't know about tenants or pools — we need a tenant-scoped variant for persistence.

NOTE: Import paths: `exec "os/exec", db "digital.vasic.database/pkg/database"`.



Step 3: Create `commons_messaging/channels/tgram/persist.go` + extend Adapter

```

package tgram

import (
    "context"
    "fmt"

    "github.com/google/uuid"
    db "digital.vasic.database/pkg/database"

    "github.com/vasic-digital/herald/commons"
    storage "github.com/vasic-digital/herald/commons_storage"
)

// NewWithStorage constructs an Adapter that persists delivery
// evidence
// to the given live pool. Persistence happens AFTER a successful
// sendMessage – a Send-then-persist failure leaves the message
// delivered
// without a persistence row, which is a known limitation ($107
// honest:
// we prefer dropping a persistence row over double-sending the
// message).
func NewWithStorage(rawURL string, pool db.Database) (*Adapter,
    error) {
    a, err := New(rawURL)
    if err != nil {
        return nil, err
    }
}

```

```

    }
    a.pool = pool
    return a, nil
}

// SendForTenant calls Send and persists the delivery evidence row
// under
// the given tenant's RLS context. Returns the same Receipt as
// Send,
// plus an error if EITHER the network send OR the persistence
// write
// fails.
func (a *Adapter) SendForTenant(ctx context.Context, tenantID
    uuid.UUID, msg commons.OutboundMessage) (commons.Receipt,
    error) {
    receipt, err := a.Send(ctx, msg)
    if err != nil {
        return receipt, err
    }
    if a.pool == nil {
        // Persistence not configured – return receipt unchanged.
        return receipt, nil
    }
    err = storage.WithTenantContext(ctx, a.pool, tenantID,
        func(tx db.Tx) error {
            _, execErr := tx.Exec(ctx,
                `INSERT INTO outbound_delivery_evidence (id,
                tenant_id, channel_id, channel_message_id, evidence)
                VALUES ($1, $2, $3, $4, $5)`,
                uuid.New(), tenantID,
                string(msg.Recipient.ChannelID), receipt.MessageID,
                int(receipt.Evidence),
            )
            return execErr
        })
    if err != nil {
        return receipt, fmt.Errorf("tgram.SendForTenant: persist:
        %w", err)
    }
    return receipt, nil
}

```

Add pool db.Database to the Adapter struct in tgram.go:

```

type Adapter struct {
    botToken string
    chatID   string
    bot      *telebot.Bot
    pool     db.Database // optional; nil = persistence disabled
}

```



Step 4: Run integration test

```
HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN
HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID \
go test ./commons_messaging/channels/tgram/ -tags=integration
-run TestSend_PersistsDeliveryEvidence -count=1
-timeout=180s
```

Expected: PASS — Telegram delivers the message; a row in outbound_delivery_evidence matches the chat-side MessageID exactly.



Step 5: Commit

```
git add commons_messaging/channels/tgram/*.go commons_messaging/
channels/tgram/go.mod commons_storage/migrations/
000010_*.sql commons_storage/migrations_test.go
git commit -m "HRD-011 step 5: Telegram delivery-evidence
persistence"
```

NewWithStorage constructs an Adapter that persists outbound_delivery_evidence rows to the live pool. SendForTenant calls Send then persists the row under the tenant's RLS context.

\$107 evidence: integration test asserts the persisted channel_message_id matches the receipt's MessageID exactly – not 'a row exists'.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 6: Claude Code Dispatch (live claude --resume invocation)

Files: - Create: commons_messaging/dispatch/claude_code/dispatch.go - Modify: commons_messaging/dispatch/claude_code/claude_code.go (rewire Dispatch)



Step 1: Write integration test

Create commons_messaging/dispatch/claude_code/dispatch_integration_test.go:

```
//go:build integration
```

```
package claude_code
```

```
import (
    "context"
    "os"
    "os/exec"
    "testing"
```

```

    "time"
)

func TestDispatch_LiveClaudeInvocation(t *testing.T) {
    binary := os.Getenv("HERALD_CLAUDE_BIN")
    if binary == "" {
        binary = "claude"
    }
    if _, err := exec.LookPath(binary); err != nil {
        t.Skipf("skip: hardware_not_present - %s not on PATH",
            binary)
    }
    projectName := os.Getenv("HERALD_CLAUDE_PROJECT_NAME")
    if projectName == "" {
        t.Skipf("skip: hardware_not_present -
            HERALD_CLAUDE_PROJECT_NAME absent")
    }

    d, err := New(binary, ".", projectName)
    if err != nil {
        t.Fatalf("New: %v", err)
    }
    ctx, cancel := context.WithTimeout(context.Background(),
        180*time.Second)
    defer cancel()

    req := DispatchRequest{
        InboundText: "Herald E18 integration test: please reply
            with outcome=acknowledged and summary=ack",
        ProjectName: projectName,
        // other DispatchRequest fields - read DispatchRequest
        struct
    }
    resp, err := d.Dispatch(ctx, req)
    if err != nil {
        t.Fatalf("Dispatch: %v", err)
    }
    if resp.Outcome == "" {
        t.Fatal("Dispatch returned empty Outcome - §107 bluff
            guard (proves Claude actually emitted the structured
            reply, not a hand-rolled default)")
    }
    if resp.Summary == "" {
        t.Fatal("Dispatch returned empty Summary - §107 bluff
            guard")
    }
}

```



Step 2: Run, expect FAIL (“not implemented”)

```

HERALD_CLAUDE_PROJECT_NAME=Herald HERALD_CLAUDE_BIN=claude \
go test ./commons_messaging/dispatch/claude_code/
    -tags=integration -run TestDispatch_LiveClaudeInvocation
    -count=1 -timeout=300s

```

Expected: FAIL with “not implemented” if claude available; SKIP otherwise.



Step 3: Create commons_messaging/dispatch/claude_code/dispatch.go

```

package claude_code

import (
    "bufio"
    "context"
    "encoding/json"
    "fmt"
    "os/exec"
    "strings"
)

// Dispatch invokes `claude --resume <UUID> --print "<envelope>"`
// and parses
// the structured reply line prefixed with <<<HERALD-REPLY>>>.
//
// §107: a PASS requires (a) Claude exits 0, AND (b) stdout
// contains a
// well-formed JSON reply with non-empty Outcome + Summary. A
// reply
// where Claude refused, errored, or never produced the marker is
// a FAIL.
func (d *Dispatcher) Dispatch(ctx context.Context, req
    DispatchRequest) (DispatchResponse, error) {
    sessionUUID, anchor, err := d.ResolveSession()
    if err != nil {
        return DispatchResponse{}, fmt.Errorf("dispatch: resolve
            session: %w", err)
    }

    envelope := d.FormatEnvelope(req)
    cmd := exec.CommandContext(ctx, d.binaryPath,
        "--resume", sessionUUID.String(),
        "--print", envelope,
    )
    cmd.Dir = d.workingDir
    out, err := cmd.Output()
    if err != nil {
        if ee, ok := err.(*exec.ExitError); ok {
            return DispatchResponse{}, fmt.Errorf("dispatch:
                claude --resume %s: exit %d: %s",
                    sessionUUID, ee.ExitCode(),
                    strings.TrimSpace(string(ee.Stderr)))
        }
    }
}

```



```

        return DispatchResponse{}, fmt.Errorf("dispatch: exec:
        %w", err)
    }

    resp, err := parseReply(out)
    if err != nil {
        return DispatchResponse{}, fmt.Errorf("dispatch: parse
        reply: %w", err)
    }
    resp.SessionUUID = sessionUUID
    resp.AnchorPath = anchor
    return resp, nil
}

// parseReply scans Claude Code's stdout for the <<<HERALD-
//      REPLY>>> marker
// and decodes the following JSON object into DispatchResponse.
//      Returns
// an error if no marker is found or the JSON is malformed -
//      explicit
// reject preserves $107 anti-bluff.
func parseReply(stdout []byte) (DispatchResponse, error) {
    scanner := bufio.NewScanner(strings.NewReader(string(stdout)))
    scanner.Buffer(make([]byte, 0, 64*1024), 1024*1024) // allow
    long reply lines
    for scanner.Scan() {
        line := scanner.Text()
        const marker = "<<<HERALD-REPLY>>>"
        if idx := strings.Index(line, marker); idx >= 0 {
            payload := strings.TrimSpace(line[idx+len(marker):])
            var resp DispatchResponse
            if err := json.Unmarshal([]byte(payload), &resp);
            err != nil {
                return DispatchResponse{}, fmt.Errorf("unmarshal:
                %w (raw: %q)", err, payload)
            }
            return resp, nil
        }
    }
    if err := scanner.Err(); err != nil {
        return DispatchResponse{}, fmt.Errorf("scan stdout: %w",
        err)
    }
    return DispatchResponse{}, fmt.Errorf("no <<<HERALD-REPLY>>>
    marker found in claude stdout ($107 bluff guard)")
}

```



Step 4: Inspect DispatchResponse struct fields

Confirm the `DispatchResponse` struct in `claude_code.go` has the fields the test asserts on (Outcome, Summary, SessionUUID, AnchorPath). If SessionUUID + AnchorPath are NOT present, add them as new exported fields. Update the `replyJSONSchema` const if needed to reflect the schema.



Step 5: Remove stub Dispatch from `claude_code.go`

Delete the old Dispatch that returns "not implemented".



Step 6: Run integration test (with operator-supplied claude)

```
HERALD_CLAUDE_PROJECT_NAME=Herald HERALD_CLAUDE_BIN=claude \  
go test ./commons_messaging/dispatch/claude_code/  
-tags=integration -run TestDispatch_LiveClaudeInvocation  
-count=1 -timeout=300s
```

Expected: PASS — the real claude CLI receives the envelope, replies with a <<<HERALD-REPLY>>> line, the JSON decodes, Outcome + Summary are non-empty.

NOTE: This requires Claude Code being correctly configured for the test machine. If the test FAILs with “no marker found”, the issue is likely that the operator-side claude session doesn’t honour the envelope schema yet — that’s a real bug worth investigating (NOT a §107 PASS-bluff to paper over).



Step 7: Commit

```
git add commons_messaging/dispatch/claude_code/*.go  
git commit -m "HRD-012 step 6: Claude Code Dispatch live  
invocation"
```

Replaces stub Dispatch with real `exec.Command(claude --resume <UUID> --print <envelope>)`. Parses stdout for <<<HERALD-REPLY>>> JSON line per spec §33. §107 bluff guards: rejects if no marker found OR Outcome/Summary empty.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 7: Claude Code session persistence

Files: - Create: `commons_messaging/dispatch/claude_code/persist.go` - Modify: `commons_messaging/dispatch/claude_code/dispatch.go` (persist session_state after each Dispatch) - Possibly create: `commons_storage/migrations/000011_session_state.up.sql` (verify if not already present)



Step 1: Verify or create the session_state migration

```
grep -rln 'session_state\|claude_session' commons_storage/
migrations/
```

If not present, create migration 000011_session_state.up.sql:

```
CREATE TABLE IF NOT EXISTS claude_code_sessions (
  project_name TEXT PRIMARY KEY,
  session_uuid UUID NOT NULL,
  anchor_path TEXT NOT NULL,
  last_dispatch_at TIMESTAMPTZ DEFAULT now(),
  last_response JSONB
);
```

Plus down migration. Bump commons_storage/migrations_test.go expected count.



Step 2: Write failing integration test

Append to dispatch_integration_test.go:

```
func TestDispatch_PersistsSessionState(t *testing.T) {
  // Same env-var guards as TestDispatch_LiveClaudeInvocation.
  // PLUS boot commons_infra QuickstartBoot for the live pool.

  // Call Dispatch, then SELECT from claude_code_sessions and
  // assert
  // project_name + session_uuid + last_dispatch_at populated.
  // Assert last_response JSONB contains Outcome + Summary.
}
```

(Full test body follows the pattern from Task 5 — boot Postgres, do Dispatch, read-back.)



Step 3: Create commons_messaging/dispatch/claude_code/persist.go

```
package claude_code
```

```
import (
  "context"
  "encoding/json"
  "fmt"

  db "digital.vasic.database/pkg/database"

  storage "github.com/vasic-digital/herald/commons_storage"
)
```

```
// PersistSessionState upserts the session row for this project
// after a
```

```

// successful Dispatch. Persistence is best-effort – a PG-down
// state
// returns an error to the caller but does NOT roll back the
// dispatch
// itself (the claude reply has already been received).
//
// The function is RLS-scoped to a Herald-internal "system" tenant
// UUID
// since session-state is operator-shared, not tenant-scoped. The
// HERALD_SYSTEM_TENANT_UUID const is the canonical anchor.
func (d *Dispatcher) PersistSessionState(ctx
    context.Context, pool db.Database, resp DispatchResponse)
    error {
    payload, err := json.Marshal(resp)
    if err != nil {
        return fmt.Errorf("marshal response: %w", err)
    }
    return storage.WithTenantContext(ctx, pool,
        HeraldSystemTenant, func(tx db.Tx) error {
        _, execErr := tx.Exec(ctx,
            `INSERT INTO claude_code_sessions (project_name,
            session_uuid, anchor_path, last_dispatch_at,
            last_response)
            VALUES ($1, $2, $3, NOW(), $4)
            ON CONFLICT (project_name) DO UPDATE SET
            session_uuid = EXCLUDED.session_uuid,
            anchor_path = EXCLUDED.anchor_path,
            last_dispatch_at = NOW(),
            last_response = EXCLUDED.last_response`,
            d.projectName, resp.SessionUUID, resp.AnchorPath,
            string(payload),
        )
        return execErr
    })
}

```

NOTE: HeraldSystemTenant is a new exported constant — declare it as a fixed UUID at the top of `claude_code.go`:

```

// HeraldSystemTenant is a fixed UUID that scopes Herald's
// internal
// (non-tenant-scoped) data. Sessions, configs, etc. live under
// this.
// Per §16, this is NOT a real tenant – it's the operator-shared
// bucket.
var HeraldSystemTenant =
    uuid.MustParse("00000000-0000-0000-0000-000000000001")

```



Step 4: Wire PersistSessionState into Dispatch

If a pool is provided to the Dispatcher (extend Dispatcher with an optional `pool` field, similar to `tgram.Adapter`), call `PersistSessionState` after a successful Dispatch.



Step 5: Run, expect PASS

```
HERALD_CLAUDE_PROJECT_NAME=Herald HERALD_CLAUDE_BIN=claude \
go test ./commons_messaging/dispatch/claude_code/
    -tags=integration -count=1 -timeout=300s
```



Step 6: Commit

```
git add commons_messaging/dispatch/claude_code/*.go
    commons_storage/migrations/000011_session_state.up.sql
    commons_storage/migrations/000011_session_state.down.sql
    commons_storage/migrations_test.go
git commit -m "HRD-012 step 7: Claude Code session state
    persistence"
```

Upserts `claude_code_sessions` row after each `Dispatch` – tracks
`session_uuid` + `anchor_path` + `last_dispatch_at` + `last_response`
JSONB.

Scoped to `HeraldSystemTenant` (fixed UUID, NOT a real tenant) per
§16.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 8: Vertical-slice integration test (E19)

Files: - Create: `commons_messaging/vertical_slice_integration_test.go`

The slice: operator hand-sends a Telegram message → `tgram.Subscribe` receives it
→ handler calls `claude_code.Dispatch` → response parsed → handler calls
`tgram.SendForTenant` → operator sees the reply in Telegram.



Step 1: Write the integration test

```
//go:build integration
```

```
package messaging_test
```

```
import (
    "context"
    "os"
    "os/exec"
    "sync/atomic"
    "testing"
    "time"

    "github.com/google/uuid"
    "github.com/vasic-digital/herald/commons"
    "github.com/vasic-digital/herald/commons_messaging/channels/
        tgram"
```

```

        "github.com/vasic-digital/herald/commons_messaging/dispatch/
        claude_code"
    infra "github.com/vasic-digital/herald/commons_infra"
)

// TestVerticalSlice exercises the full E19 round-trip:
// operator-sent Telegram inbound → claude_code.Dispatch →
// telegram outbound.
//
// REQUIRES: operator has booted the quickstart compose; has a
// Telegram bot
// token; has `claude` on PATH; HAS just sent ANY message to the
// bot before
// the 90s test window expires.
//
// $107: PASSES only when (a) inbound observed, (b) Claude
// responded with
// non-empty Outcome, (c) outbound MessageID is non-empty.
func TestVerticalSlice_TelegramClaudeRoundTrip(t *testing.T) {
    // env-var guards: HERALD_TGRAM_BOT_TOKEN,
    // HERALD_TGRAM_CHAT_ID,
    // HERALD_TGRAM_LIVE_INBOUND=1, HERALD_CLAUDE_PROJECT_NAME,
    // HERALD_CLAUDE_BIN.
    // SKIP if any absent.

    // Boot Postgres.
    // Construct tgram.Adapter with NewWithStorage(token, pool).
    // Construct claude_code.Dispatcher.
    // Subscribe with a handler that:
    // 1. Dispatch to Claude.
    // 2. SendForTenant(reply.Summary) back.
    // 3. Atomic flag set.
    // Wait up to 90s for handler completion.
    // Assert: handler ran, dispatch returned non-empty Outcome,
    // outbound MessageID non-empty.
}

```

Fill in the body following the per-task patterns from Tasks 4/5/6/7.



Step 2: Run end-to-end

```

# Send a Telegram message to the bot. Then:
HERALD_TGRAM_BOT_TOKEN=$HERALD_TGRAM_BOT_TOKEN
    HERALD_TGRAM_CHAT_ID=$HERALD_TGRAM_CHAT_ID \
HERALD_TGRAM_LIVE_INBOUND=1 \
HERALD_CLAUDE_BIN=claude HERALD_CLAUDE_PROJECT_NAME=Herald \
go test ./commons_messaging/ -tags=integration -run
    TestVerticalSlice_TelegramClaudeRoundTrip -count=1
    -timeout=300s -v

```

Expected: PASS — the operator's Telegram chat receives a reply derived from Claude's <<<HERALD-REPLY>>> Summary.



Step 3: Commit

```
git add commons_messaging/vertical_slice_integration_test.go
git commit -m "HRD-011 + HRD-012 step 8: vertical-slice E19
integration test"
```

Full Telegram → Claude Code → Telegram round-trip. Requires operator to hand-send a Telegram message and have claude on PATH. §107: asserts the operator's chat receives a non-empty derived reply.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 9: Add E17/E18/E19 to e2e_bluff_hunt.sh

Files: - Modify: scripts/e2e_bluff_hunt.sh



Step 1: Add the three invariants

After the E14-E16 block, add:

```
echo ""
echo "== E17-E19: HRD-011 + HRD-012 live channel + dispatcher =="
if [ -n "${HERALD_TGRAM_BOT_TOKEN:-}" ] && [ -n "${HERALD_TGRAM_CHAT_ID:-}" ]; then
    check "E17 Telegram Send delivers + persists evidence (live Bot API + live PG)" \
        "go test ./commons_messaging/channels/tgram/
-tags=integration -run TestSend_PersistsDeliveryEvidence
-count=1 -timeout=180s"
else
    echo "SKIP E17 (no HERALD_TGRAM_BOT_TOKEN - §11.4.3 explicit SKIP-with-reason)"
fi

if command -v "${HERALD_CLAUDE_BIN:-claude}" >/dev/null 2>&1 && [
    -n "${HERALD_CLAUDE_PROJECT_NAME:-}" ]; then
    check "E18 Claude Code Dispatch round-trip + session persist (live CLI + live PG)" \
        "go test ./commons_messaging/dispatch/claude_code/
-tags=integration -count=1 -timeout=300s"
else
    echo "SKIP E18 (no claude CLI or HERALD_CLAUDE_PROJECT_NAME - §11.4.3 explicit SKIP-with-reason)"
fi

if [ -n "${HERALD_TGRAM_BOT_TOKEN:-}" ] && [ -n "${HERALD_TGRAM_LIVE_INBOUND:-}" ] && command -v "${HERALD_CLAUDE_BIN:-claude}" >/dev/null 2>&1; then
```

```

    check "E19 full vertical slice – Telegram → Claude Code →
    Telegram (operator hand-sent inbound)" \
    "go test ./commons_messaging/ -tags=integration -run
    TestVerticalSlice_TelegramClaudeRoundTrip -count=1
    -timeout=300s"
else
    echo "SKIP E19 (HERALD_TGRAM_LIVE_INBOUND=1 + Telegram creds
    + claude CLI required – §11.4.3)"
fi

```



Step 2: Update the header comment “Eighteen invariants” → “Twenty-one invariants” and add E17/E18/E19 to the list.



Step 3: Run the script

```
bash scripts/e2e_bluff_hunt.sh 2>&1 | tail -30
```

Expected outcomes: - All creds + claude available: 21 PASS / 0 FAIL - No creds: 18 PASS / 0 FAIL + 3 SKIP (still considered a PASS overall)



Step 4: Commit

```

git add scripts/e2e_bluff_hunt.sh
git commit -m "HRD-011 + HRD-012 step 9: e2e_bluff_hunt E17/E18/
E19 – Wave 1 vertical slice

```

E17: Telegram Send + outbound_delivery_evidence persistence (live Bot API + PG).

E18: Claude Code Dispatch round-trip + session_state persistence (live CLI + PG).

E19: Full slice – operator's Telegram inbound → Claude → Telegram outbound.

Without operator creds, each SKIPS with explicit §11.4.3 reason.

Total e2e_bluff_hunt: 18 PASS → 21 PASS.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 10: .env.example + atomic Issues→Fixed for HRD-011 + HRD-012

Files: - Modify: quickstart/.env.example - Modify: docs/Issues.md, docs/Fixed.md, docs/Status.md - Regenerate: all 9 sibling formats



Step 1: Add new env vars to .env.example


```
# HRD-011 Telegram (landed 2026-05-XX)
# Get a bot token from @BotFather on Telegram; chatID is a numeric
  chat ID.
HERALD_TGRAM_BOT_TOKEN=
HERALD_TGRAM_CHAT_ID=
# Set to 1 to enable the live-inbound TestSubscribe test (operator
  must
# hand-send a message during the test window).
HERALD_TGRAM_LIVE_INBOUND=

# HRD-012 Claude Code dispatcher (landed 2026-05-XX)
# Path to the `claude` binary; defaults to "claude" on $PATH.
HERALD_CLAUDE_BIN=claude
# Project name used to resolve the session anchor file.
HERALD_CLAUDE_PROJECT_NAME=Herald
```



Step 2: Atomic Issues→Fixed migration for HRD-011 AND HRD-012

Per §11.4.19 atomic — both rows move in the same commit.

1. Open docs/Issues.md. Cut the HRD-011 row AND the HRD-012 row.
2. Open docs/Fixed.md. Insert both rows at the TOP of the “Recently fixed” table.
3. Update headers of both files.

HRD-011 row template for Fixed.md (adjust commit refs):

```
| HRD-011 | task | middle | Telegram channel live integration –
sendMessage MarkdownV2 + getUpdates long-poll (25s/30s safety-net
per §32.2) + outbound_delivery_evidence persistence; 3 new §107
e2e invariants (E17 send+persist) | 2026-05-XX | (this commit) |
spec V3 §11.1 + §32; Catalogue-Check: no-match (no vasic-digital
Telegram SDK); vendored gopkg.in/telebot.v3 as submodules/telebot
|
```

HRD-012 row template:

```
| HRD-012 | task | middle | Claude Code dispatcher live
integration – `claude --resume <UUID> --print <envelope>` exec +
<<<HERALD-REPLY>>> JSON parse + claude_code_sessions persistence
per §33; E18 round-trip + E19 vertical slice (combined with
HRD-011) | 2026-05-XX | (this commit) | spec V3 §33 + §33.2;
Catalogue-Check: no-match (claude is an external binary, not a
library) |
```



Step 3: Update Status.md r7→r8

- e2e_bluff_hunt: 21 PASS / 0 FAIL (was 18)
- Submodules: 13 vendored (was 12 — added telebot)
- Implementation table: commons_messaging now  landed (was partial)

- Continuation: Wave 1 complete; HRD-008 operator-side e2e validation next



Step 4: Regenerate siblings

```
for f in docs/Issues.md docs/Fixed.md docs/Status.md; do
  base="${f%.md}"
  pandoc "$f" -o "${base}.html" --standalone --toc --metadata
    title="$(basename $base)"
  pandoc "$f" -o "${base}.docx" --toc --metadata title="$
    (basename $base)"
  pandoc "$f" -o "${base}.pdf" --pdf-engine=weasyprint --toc --
    metadata title="$(basename $base)"
done
```



Step 5: Atomic-migration grep

```
grep -c "^| HRD-011 |" docs/Fixed.md # expect 1
grep -c "^| HRD-011 |" docs/Issues.md # expect 0
grep -c "^| HRD-012 |" docs/Fixed.md # expect 1
grep -c "^| HRD-012 |" docs/Issues.md # expect 0
```



Step 6: Commit

```
git add quickstart/.env.example docs/Issues.md docs/Issues.html
  docs/Issues.docx docs/Issues.pdf docs/Fixed.md docs/
  Fixed.html docs/Fixed.docx docs/Fixed.pdf docs/Status.md
  docs/Status.html docs/Status.docx docs/Status.pdf
git commit -m "HRD-011 + HRD-012 step 10: atomic Issues→Fixed +
  Status r8 + .env.example"
```

Both HRD-011 (Telegram live) and HRD-012 (Claude Code dispatcher live)
closed atomically per §11.4.19. Status r7→r8: commons_messaging
now
✅ landed; e2e_bluff_hunt 18→21 PASS; submodules count 12→13
(added
telebot).

.env.example documents the 4 new env vars operators need: bot
token,
chat ID, live-inbound flag, claude binary path, claude project
name.

Co-Authored-By: Claude Opus 4.7 <noreply@anthropic.com>

Task 11: Anti-bluff battery + multi-mirror push

Files: none modified — validates and ships.



Step 1: Run full anti-bluff battery

```
cd /Users/milosvasic/Projects/Herald
bash tests/test_constitution_inheritance.sh           # expect 15
    PASS
bash tests/test_constitution_inheritance_meta.sh      # expect
    META-TEST PASS
bash tests/test_i6_refinement_meta.sh                # expect 3
    PASS
bash tests/test_i8_usability_meta.sh                 # expect 5
    PASS
bash scripts/audit_antibluff.sh                      # expect 16
    PASS (or more after Models/Concurrency added)
bash scripts/codegraph_validate.sh                   # expect 7+
    PASS
bash scripts/e2e_bluff_hunt.sh                       # expect 21
    PASS (with creds) or 18 PASS + 3 SKIP
```

All MUST be green. Any FAIL blocks the push.



Step 2: Re-index CodeGraph

```
bash scripts/codegraph_setup.sh
bash scripts/codegraph_validate.sh
```



Step 3: Multi-mirror fan-out push

```
git push origin main
```

Expected: 4 lines (GitHub + GitLab + GitFlic + GitVerse) each showing the new commits.



Step 4: Final verification

```
git log -15 --oneline
```

Should show this plan's commits on top of HEAD. Confirm Issues.md no longer contains HRD-011 or HRD-012 in the open table.

Self-Review

1. Spec coverage check.

Spec requirement	Task
§11.1 Telegram sendMessage MarkdownV2	Task 3
§11.1 sendDocument for attachments	Task 3 (deferred — only sendMessage in v1; attachments are a follow-up)
§11.1 getUpdates long-poll	Task 4
§32.2 30s safety-net timer	Task 4
§11.1 webhook ingress with secret_token	Deferred — long-poll-only in v1; webhook is HRD-NNN follow-up
Telegram delivery evidence persistence	Task 5
§33 claude –resume invocation	Task 6
§33 <<>> JSON parse	Task 6
§33.2 session-resolution algorithm	Already done in existing scaffold (ResolveSession + PersistSession exist) — Task 6 just calls them
Session state persistence	Task 7
E17 send+persist	Task 5 (test) + Task 9 (e2e invariant)
E18 dispatch+persist	Task 7 (test) + Task 9 (e2e invariant)
E19 full vertical slice	Task 8 (test) + Task 9 (e2e invariant)
.env.example documentation	Task 10
HRD-011 + HRD-012 Issues→Fixed	Task 10
Status.md r8	Task 10
Anti-bluff battery + push	Task 11

Spec gaps: §11.1 sendDocument (attachments) + webhook ingress are deferred to a follow-up HRD. Both are spec-mandated for the FULL §11.1 capability, but the long-poll + sendMessage path covers the canonical E17 evidence. Note this in the HRD-011 Fixed.md row's title.

2. Placeholder scan: - 2026-05-XX — parametric close-date for the engineer to fill at Task 10. Legitimate. - (this commit) — Fixed.md convention. Legitimate. - <UUID> — protocol literal in <<<HERALD-REPLY>>> discussion. Legitimate.

No genuine TBDs.

3. Type consistency: - NewWithStorage (Task 5) + SendForTenant (Task 5) — same naming used consistently. - HeraldSystemTenant (Task 7) — declared once, referenced in persist.go. - DispatchResponse Outcome + Summary + SessionUUID + AnchorPath — added consistently in Tasks 6 + 7. - parseReply (Task 6) — internal helper, single definition.

4. Anti-bluff trap coverage:

Trap	Mitigation
Mock-driven PASS	Every integration test uses live Bot API + live claude CLI; no mocks
Compile-only PASS	

Trap	Mitigation
	Integration tests assert specific runtime evidence (MessageID, Outcome, persisted row matching receipt)
Empty-field PASS	Each probe asserts non-empty MessageID / Outcome / Summary
Skipped-silently PASS	SKIP-with-explicit-reason if creds absent — never PASS-by-default
Parsed-junk PASS	parseReply returns explicit error if marker absent or JSON malformed
Sandbox-leakage PASS	All tests run inside <code>t.Cleanup(boot.Down)</code> and use fresh tenant UUIDs

Execution Handoff

Plan complete and saved to `docs/superpowers/plans/2026-05-20-hrd-011-012-telegram-and-claude-code-live.md`.

Two execution options:

1. **Subagent-Driven (recommended)** — fresh subagent per task, two-stage review (spec + code), continuous execution.
2. **Inline Execution** — `superpowers:executing-plans`, batch with checkpoints.

Which approach?