

Herald



Herald — Continuation

Field	Value
Revision	8
Created	2026-05-20
Last modified	2026-05-23
Status	active
Status summary	2026-05-23 session-end checkpoint — safe to shut down. Wave 6.5 lifecycle layer landed (12/12 implementation tasks + premature v0.5.0 tag from a parallel Haiku session). One root-cause bug discovered live + fixed: envelope ACTION FORMAT GUIDANCE (commit 53a7ad3) — before the fix, every Bug:/Task: defaulted to action: "reply" and never wrote Issues.md (§107 PASS-bluff at the prompt layer). qaherald-auto Go framework T1+T2+T3+T4+T5 of 8 landed (full 15-scenario lifecycle test framework using a 2nd Telegram bot @pherald_qa_bot as automated subscriber). T6+T7+T8 remaining: pre-flight validator + httptest-driven unit tests + tests/test_wave6.5_lifecycle.sh adapter. After T8 + live run + v0.5.1 tag: ready to start Wave 7 (genericize messenger framework Slack/Email per operator mandate) / close 47 remaining HRDs. v0.4.0 (Wave 6 closed-loop) + v0.5.0 (Wave 6.5 implementations) both tagged + pushed to all 4 mirrors. Live evidence so far under docs/qa/HRD-100-2026-05-22T18-27-30-w6live/ (4-event closed loop) + docs/qa/HRD-101-lifecycle-2026-05-22T20-04-04-w6.5live/ (partial — only S1+S2 evidence; superseded by qaherald-auto). Workspace at 16 modules. Spec V3 at r12 + §32.7 + §32.9 + §33.6 + §33.7 captured. Constitutional propagation of §107.x docs/qa-evidence + §107.y working-tree-quiescence covenant complete across 13 submodules + parent constitution + Herald root (QA1 commit bff18db + per-submodule a8c1cb4..b464136). Anti-bluff gates green: inheritance 15/15 PASS, audit_antibluff 18/0/1, Wave 6 mutation gate 4/4 PASS, Wave 6.5 mutation gate 6/6 PASS. Pre-existing carry-over: Postgres-SASL-dependent e2e invariants (E7-E12, E14-E16, E37-E42 — 15 FAILs against the running PG container, root cause is local-PG SASL handshake; unrelated to Wave 6/6.5). HRD-008, HRD-015, HRD-018 (in_progress), HRD-019..HRD-027, HRD-029..HRD-056, HRD-081, HRD-085..HRD-090, HRD-101 (in_progress — qaherald-auto + full lifecycle evidence)
Issues summary	see Issues.md — 48 open items (HRD-101 in flight)

Field	Value
Fixed	HRD-001..HRD-007, HRD-009, HRD-009b, HRD-010, HRD-011, HRD-012, HRD-013, HRD-014, HRD-016, HRD-017, HRD-028, HRD-080, HRD-092..HRD-100 (HRD-018 partial — M1 + M2 components landed)
Fixed summary	see <code>Fixed.md</code>
Continuation	Resume tomorrow at qaherald-auto T6+T7+T8 (<code>docs/superpowers/plans/2026-05-23-qaherald-auto.md</code> commit 52ce679). T1-T5 landed: qaherald lifecycle Cobra subcommand + MessengerClient interface (Telegram impl) + 15 scenarios (S1..S15) + orchestrator + Markdown report — 12 hermetic unit tests PASS under <code>-race -count=1</code>. T6: 10-gate pre-flight validator (pherald-bot getMe, qa-bot privacy disabled, group membership, OPERATOR_IDS contains qa-bot, etc.). T7: full unit-test pass against <code>httptest</code> impersonating Bot API + canned pherald transcripts. T8: rewrite <code>tests/test_wave6.5_lifecycle.sh</code> to delegate to qaherald lifecycle (keep <code>--manual</code> for old interactive UX). After T8: live e2e run with operator-supplied creds (see §4a below), commit <code>docs/qa/HRD-101-lifecycle-<run-id>/ + tag v0.5.1 + 4-mirror</code> push. Subsequent: Wave 7 (genericize messenger framework — Slack/Email next per operator 2026-05-22), then close-out of HRDs 018..027 + 029..056 + 081 + 085..090 for v1.0.0 production-ready, then the docs-audit task #147 (operator manuals + PDF/HTML/DOCX exports for every wave). Operator restated 2026-05-22/23: NO BLUFF, NO FALSE POSITIVES, fix root causes immediately. The 53a7ad3 envelope fix is the canonical example of that rule operating live. Push to all 4 mirrors + every submodule's own origin on every non-trivial commit per Universal §12.10.

Table of contents

- [§0. How to use this document](#)
- [§1. Snapshot](#)
- [§2. Last commit landed](#)
- [§3. Active work](#)
- [§4. Next concrete steps](#)
- [§5. Long-form pointers](#)

§0. How to use this document

Paste the following block into any CLI agent (Claude Code / OpenCode / Cursor / Aider / Gemini CLI) to resume Herald work exactly where it was left:

```
You are working on the Herald project at ~/Projects/Herald (also reachable as
the Herald/ submodule of a consuming project). The Helix Universal Constitution
lives at <ancestor>/constitution/ (parent-walk discovery). Read in this
order: CLAUDE.md, AGENTS.md, README.md, docs/guides/
HERALD_CONSTITUTION.md, docs/guides/
CONSTITUTION_INHERITANCE.md, docs/specs/mvp/
specification.V3.md. Then read docs/CONTINUATION.md (this file) for
live state, docs/Issues.md for open work, docs/Status.md for current
phase, docs/Fixed.md for closed history. Go workspace builds via go
test ./commons/... ./commons_prefix/... ./
commons_messaging/... ./commons_storage/.... Inheritance gate
tests/test_constitution_inheritance.sh MUST exit 0 before any
```

commit. Multi-mirror fan-out push to four hosts (GitHub + GitLab + GitFlic + GitVerse) is mandatory per Constitution §103.

§1. Snapshot

- **Active spec:** docs/specs/mvp/specification.V3.md Revision 4 (~4300 lines).
- **Archived specs:** V1 + V2 in docs/specs/mvp/archive/ (frozen).
- **Go modules:** commons, commons_prefix, commons_messaging, commons_storage, pherald (all compile + unit tests pass).
- **Container scaffold:** quickstart/{docker-compose.quickstart.yml, Dockerfile.pherald, otel-config.yaml, .env.example} for §26.5 quickstart.
- **CLI:** pherald version --json returns canonical build info; serve/send/doctor/migrate/subscriber/deadletter stubbed with HRD-NNN pointers.
- **Inheritance gate:** 12 PASS / 0 FAIL. Meta-test ✓.
- **Phase:** implementation r1.

§2. Last commit landed

This commit (V3 r4 + Go scaffold + tracking-doc refresh) closes HRD-009/HRD-009b/HRD-013/HRD-014 (with a Universal §11.4.19 atomic Issues.md → Fixed.md migration) and lands spec V3 §37–§41 (tracker events, workable-item announcement contract, message presentation + Herald Canonical Template, docs/tests completeness, REST API surface). Builds + tests:

```
$ go test ./commons/... ./commons_prefix/... ./commons_messaging/... ./commons_storage/...
ok      github.com/vasic-digital/herald/commons 1.135s
ok      github.com/vasic-digital/herald/commons_prefix 0.639s
ok      github.com/vasic-digital/herald/commons_messaging/channels/null 0.001s
ok      github.com/vasic-digital/herald/commons_messaging/dispatch/claude 0.001s
ok      github.com/vasic-digital/herald/commons_storage 1.630s
```

§3. Active work

ID	Status	What
HRD-008	in_progress	Operator-side Quickstart compose validation (Postgres + Redis + OTel + pherald container) — scaffold shipped this commit; live end-to-end run pending operator.
HRD-010	open	commons_storage live (pgx pool + golang-migrate driver + River queue + Redis ACL).
HRD-011	open	Telegram adapter live (telebot SDK + getUpdates long-poll + webhook secret_token).
HRD-012	open	Claude Code dispatcher live (claude --resume + parse <<<HERALD-REPLY>>>).
HRD-015	open	Inheritance gate I8 invariants for Go scaffold (go.work + commons/types.go + null adapter test passes).
HRD-016	open	REST API surface via Gin Gonic per spec §41.
HRD-017	open	Propagate Universal §11.4.6X spec-versioning + submodule-catalogue-first mandates into the parent constitution.

§4. Next concrete steps

1. **HRD-018 Catalogue-Check survey + commons_constitution scaffold** — first action of the §42 implementation rollout. **MUST start** with a vasic-digital + HelixDevelopment catalogue survey per the brand-new Universal §11.4.74. Record Catalogue-Check: reuse|extend|no-match on HRD-018 before any Go code lands. Then scaffold the Evaluator interface, 12 event-class emit helpers, constitution_state + constitution_bindings migrations, bundle-hash captureer, mode-ladder runtime config.
2. **HRD-008 quickstart validation** — On a fresh laptop with Podman or Docker:

```
git clone <Herald repo>
git submodule update --init
cd quickstart
podman build -t herald/pherald:dev -f Dockerfile.pherald ../..
cp .env.example ../../.env && $EDITOR ../../.env
podman-compose -f docker-compose.quickstart.yml up -d
curl --retry 30 --retry-delay 2 http://localhost:24090/readyz
```

The current pherald serve returns "not implemented" — HRD-010/HRD-011/HRD-012 must land first to make the live curl POST /v1/events succeed end-to-end. Validation reveals which of the spec's assumptions (port ranges, Compose syntax, OTel collector config, Postgres healthcheck) hold against real infrastructure.

3. **HRD-010** — wire commons_storage/storage.go's MigrationDriver to golang-migrate; bring pgx + River + Redis client up; add integration tests under // go:build integration.
4. **HRD-011** — replace commons_messaging/channels/tgram/tgram.go stub with a live implementation against gopkg.in/telebot.v3 or github.com/mymmrac/telego; recorded HTTP fixtures under testdata/.
5. **HRD-012** — replace commons_messaging/dispatch/claude_code/claude_code.go's Dispatch stub with a real claude --resume invocation; capture session UUID; parse <<<HERALD-REPLY>>>.
6. **HRD-016** — scaffold pherald/internal/http/ with Gin routes per V3 §41; wire pherald serve to mount the Gin router on http_port.
7. **HRD-017** — propagate Universal §11.4.6X new mandates (spec-versioning + submodule-catalogue-first) into the constitution submodule.

§4a. Wave 6 live-test handoff (T10b — gating tag v0.4.0)

Operator-supplied credentials required — Wave 6's e2e invariants E63-E70 land as honest SKIPs until the live closed-loop runs against real Telegram + real Claude Code with real chat messages exchanged.

Step-by-step.

1. Export credentials in the shell that will drive the test:

```
export HERALD_TGRAM_BOT_TOKEN="<your-bot-token-from-  
BotFather>"  
export HERALD_TGRAM_CHAT_ID="<numeric-chat-id-where-bot-is-  
admin>"  
export HERALD_CLAUDE_BIN="$(command -v claude)" # path to  
the claude CLI binary  
export HERALD_PROJECT_NAME="Herald" # or any  
operator-chosen session name
```

2. Pick a `<run-id>` (timestamp + 4-char nonce):

```
RUN_ID="$(date -u +%Y-%m-%dT%H-%M-%S)-$(uuidgen | cut -c1-4)"  
QA_DIR="docs/qa/HRD-100-${RUN_ID}"  
mkdir -p "${QA_DIR}/attachments"
```

3. Type ONE message in the configured Telegram chat (script reads it via `getUpdates` within 60s).
4. Run the live closed-loop test:

```
bash tests/test_wave6_live_loop.sh
```

The script builds `pherald`, observes the original `message_id`, starts `pherald listen --bot-token "$HERALD_TGRAM_BOT_TOKEN" --chat-id "$HERALD_TGRAM_CHAT_ID" --qa-out-dir "$QA_DIR"` in the background, waits up to 45s for a reply with `reply_to_message_id == original`, and exits 0 on PASS.

5. Capture supplementary logs:

```
cp /tmp/pherald-w6.log "${QA_DIR}/pherald-listen.log"  
# claude stdout/stderr — paths depend on the journaling  
setup. Copy whatever  
# the test produced into ${QA_DIR}/claude-stdout.log +  
claude-stderr.log.
```

6. Author a brief `${QA_DIR}/README.md` (5 lines minimum) narrating: who ran it, when, what message was sent, what reply came back, any anomalies. This is NOT auto-generated — operator-written narrative is the §107.x evidence anchor.
7. `git add ${QA_DIR}/` && `git commit -m "Wave 6 step 10b: docs/qa/HRD-100-${RUN_ID}/ live closed-loop evidence"` then proceed to T13b (`v0.4.0` tag + 4-mirror push).

If the script SKIPS (any env var unset): the test prints `SKIP: <reason>` and exits 0. That is honest §11.4.3 hardware-absent SKIP-with-reason, not a PASS. Tag `v0.4.0` MUST NOT be created until at least one PASS run is committed to `docs/qa/HRD-100-<run-id>/`.

§4b. qaherald-auto resume runbook (next session — gating tag v0.5.1)

Status as of 2026-05-23 session end:

- HEAD `8ad4cb9` on main; all 4 mirrors in sync (`github.com:vasic-digital/Herald.git`, `gitlab.com:vasic-digital/herald.git`,

gitflic.ru:vasic-digital/herald.git, gitverse.ru:vasic-digital/Herald.git).

- Tag v0.4.0 shipped (Wave 6 closed-loop). Tag v0.5.0 shipped (Wave 6.5 lifecycle implementations — premature: only S1+S2 live evidence + carries the pre-53a7ad3 envelope-action-guidance bug). Tag v0.5.1 is the target after qaherald-auto T6-T8 land + full 15-scenario evidence committed.
- Plan: docs/superpowers/plans/2026-05-23-qaherald-auto.md (commit 52ce679).
- Done: T1 skeleton + T2 messenger + T3 scenarios + T4 orchestrator + T5 report (combined commit 8ad4cb9 for T3-T5).
- TODO: **T6 pre-flight** + **T7 hermetic tests** + **T8 shell-adapter** then live run + tag.

Resume prerequisites

The following are **already provisioned** in ~/.zshrc (export-on-shell-start):

```
HERALD_TGRAM_BOT_TOKEN
    # @atmosphere_worker_bot — pherald-bot (Telegram bot
    # 8823384001)
HERALD_TGRAM_CHAT_ID      # -4946584787 (ATMOSphere Development
    group)
HERALD_OPERATOR_IDS      # 2057253161 (the operator's user-id)
HERALD_QA_BOT_TOKEN      # @pherald_qa_bot — 2nd bot
    (8971749017, privacy DISABLED, member of the group)
```

The qa-bot token is plaintext in ~/.zshrc — operator should /revoke via @BotFather after Wave 6.5 close-out and regenerate (the token leaked into one prior session's bash output earlier today, was never committed to git but lives in /private/tmp/claude-501/... operator-local files).

The containers herald-postgres (port 24100) and herald-redis (port 24200) are LIVE — both have been Up since the start of this session; data persists across podman restarts. Schema is at migration v12 (all 12 applied).

Resume sequence (suggested next-session order)

1. Pull state + verify:

```
cd ~/Projects/Herald && git pull origin main && git log --
    oneline -10
git status --short # expect clean
git stash list     # 2 stashes preserved: T8 Wave-5 salvage
    + premature S3-S5 transcript WIP
```

2. **Spawn T6 (pre-flight)** via a fresh subagent — read docs/superpowers/plans/2026-05-23-qaherald-auto.md Task 6 in full. Implementation lands at qaherald/internal/lifecycle/preflight.go + preflight_test.go. 10 gates: pherald-bot reachable via getMe, qa-bot reachable, qa-bot privacy disabled, qa-bot is group member, OPERATOR_IDS contains qa-bot, etc. Each gate has distinct exit code for diagnostics.

3. **Spawn T7 (full hermetic tests)** — extends T3-T5's 12 tests with httptest-based scenario simulation. Coverage targets: every scenario PASS path + every FAIL diagnostic + S9 SKIP path + S14 outbound-attachment sha256 round-trip + S11/S12/S13 inbound-attachment download + Issues.md/Fixed.md fs-mutation assertion.
4. **Spawn T8 (shell-script adapter)** — rewrites `tests/test_wave6.5_lifecycle.sh` to delegate to `qaherald lifecycle` for automated runs. Keeps the original `--manual` flag for the operator-typing interactive UX as a fallback.
5. **Run the live e2e (the §107 watershed):**

```
cd ~/Projects/Herald
# Add qa-bot user-id to OPERATOR_IDS so S5/S6/S8/S10 succeed
export HERALD_OPERATOR_IDS="$
    {HERALD_OPERATOR_IDS},8971749017"
# Re-export from .zshrc (or just open a new shell)
source ~/.zshrc

# Build pherald + qaherald
go build -o /tmp/pherald ./pherald/cmd/pherald
go build -o /tmp/qaherald ./qaherald/cmd/qaherald

# Start pherald listen in background with QA journaling
RUN_ID="$(date -u +%Y-%m-%dT%H-%M-%S)-w6.5live"
PHERALD_QA_DIR="docs/qa/HRD-101-lifecycle-`${RUN_ID}`-pherald"
QAUTO_QA_DIR="docs/qa/HRD-101-lifecycle-`${RUN_ID}`"
mkdir -p "${PHERALD_QA_DIR}/attachments" "${QAUTO_QA_DIR}/
    attachments"
/tmp/pherald listen --qa-out-dir "${PHERALD_QA_DIR}" --docs-
    dir docs &
PHERALD_PID=$!
trap 'kill -TERM $PHERALD_PID 2>/dev/null' EXIT
sleep 5

# Run qaherald lifecycle (T6-T8 must be done first)
/tmp/qaherald lifecycle \
    --pherald-bot-username=atmosphere_worker_bot \
    --pherald-qa-out-dir="${PHERALD_QA_DIR}" \
    --out="${QAUTO_QA_DIR}" \
    --run-id="${RUN_ID}"
# Exit 0 on all-PASS or all-PASS-with-S9-SKIP. Non-zero on
    any FAIL.
```

6. Capture evidence:

- `${PHERALD_QA_DIR}/transcript.jsonl` — pherald's view (classifications, dispatch, replies)
- `${QAUTO_QA_DIR}/transcript.jsonl` — qaherald-auto's view (sends, assertions)
- `${QAUTO_QA_DIR}/report.md` — Markdown summary

- `${QAUTO_QA_DIR}/attachments/<sha256>.<ext>` — content-addressed inbound + outbound attachments
- `docs/Issues.md` + `docs/Fixed.md` — mutated by S5/S6/S8/S10 (and reverted by S10 + S15 cleanups; both files end in valid state)

7. Author operator README + commit:

```
cat > "${QAUTO_QA_DIR}/README.md" <<EOF
# HRD-101 Wave 6.5 lifecycle evidence — <run-id>

<5+ lines narrating: who ran it, when, which scenarios
    PASSed/FAILed/SKIPped,
bot reply quality observations, any anomalies. Operator-
    written, NOT auto-generated.>
EOF
git add docs/qa/HRD-101-lifecycle-${RUN_ID}*
git commit -m "Wave 6.5 step 13: HRD-101 live 15-scenario
    lifecycle evidence (qaherald-auto)"
```

8. Tag v0.5.1 + 4-mirror push:

```
git tag -a v0.5.1 -m "Wave 6.5 close: full lifecycle live
    evidence + envelope action-guidance fix"
git push origin main
git push origin v0.5.1
# Verify all 4 mirrors converged on the same SHA + tag
for mirror in github.com:vasic-digital/Herald.git
    gitlab.com:vasic-digital/herald.git
    gitflic.ru:vasic-digital/herald.git
    gitverse.ru:vasic-digital/Herald.git; do
    git ls-remote "git@${mirror}" v0.5.1
done
```

Open / known constraints for tomorrow

- **S9 (non-operator Done: rejection):** requires `HERALD_QA_BOT_TOKEN_NON_OPERATOR` env (a THIRD bot account whose user-id is NOT in `OPERATOR_IDS`). Without it, S9 emits a SKIP-with-reason. Operator may register a third bot OR accept the SKIP (S9's logic is already unit-tested hermetically in T5's mutation gate).
- **First-scenario CC bootstrap:** ~30s on first inbound message because the Claude Code session must spawn. Subsequent scenarios use the cached session (~5-15s typical).
- **Issues.md mutation race:** if you run `qaherald lifecycle` while ANOTHER pherald listen is also processing in the same checkout, `Issues.md` may receive double-writes. Single-pherald-listen invocation is the safe default.
- **Pre-existing carry-over:** 15 `e2e_bluff_hunt` FAILs on Postgres-SASL invariants (E7-E12 + E14-E16 + E37-E42). Root cause is local-PG container's SASL handshake; not related to Wave 6/6.5; can be addressed in a separate HRD post-v1.0.0.

Safe-shutdown checklist (NOW — end of 2026-05-23 session)

Check	State
All committed work pushed to 4 mirrors	YES — HEAD 8ad4cb9 confirmed on github+gitlab+gitflic+gitverse
Local working tree clean	YES — <code>git status --short</code> empty
Stashes preserved	2 stashes: T8 Wave-5 salvage (older) + premature mid-test S3-S5 transcript WIP (newer, will be regenerated cleanly by qaherald-auto in next session)
Background pherald/qaherald processes	NONE running (<code>ps aux grep pherald</code> empty)
Container state	<code>herald-postgres + herald-redis</code> Up 17 hours — persist data across <code>podman stop && podman start</code> ; can be left running OR stopped (<code>podman stop herald-postgres herald-redis</code>); next session restart is <code>podman start herald-postgres herald-redis</code>
<code>/tmp/*.log</code> files	one operator-token leak shred-deleted earlier today; remaining transient logs contain no credentials (verified)
<code>.zshrc</code>	contains 4 <code>HERALD_*</code> exports including <code>HERALD_QA_BOT_TOKEN</code> plaintext — operator should <code>/revoke</code> + regenerate via <code>@BotFather</code> post-Wave-6.5 closure
Memory entries	All session findings persisted under <code>/Users/milosvasic/.claude/projects/-Users-milosvasic-Projects-Herald/memory/</code> — survive across sessions

Machine is safe to shut down. Resume tomorrow by `cd ~/Projects/Herald && git pull origin main` and start with `qaherald-auto T6`.

§5. Long-form pointers

- `docs/specs/mvp/specification.V3.md` — full active spec (Revision 4).
- `docs/specs/mvp/specification.V3.md#30-v2-self-review-log` — every review pass.
- `docs/guides/HERALD_CONSTITUTION.md` — §101..§106 extending Universal.
- `docs/guides/CONSTITUTION_INHERITANCE.md` — parent-discovery + gate.
- `tests/test_constitution_inheritance.sh` — the gate.
- `quickstart/` — HRD-008 scaffold.
- `commons/types.go` — the §11.0 type contract reference.