

Herald



Herald — Aider Dispatcher Setup Guide

Field	Value
Status	PLANNED — HRD-NNN (planned)
Spec ref	V3 §33 (pluggable Dispatcher)
Env vars (reserved)	HERALD_AIDER_BIN, HERALD_AIDER_MODEL (e.g. <code>claude-3-5-sonnet-20241022</code>), HERALD_AIDER_API_KEY
Code	(not yet implemented)

Aider is a popular open-source pair-programming CLI agent. Different envelope+reply format than Claude Code — the adapter will translate.

This guide is a **placeholder**. When the Aider dispatcher lands as an HRD, this file will expand to the same step-by-step structure as [CLAUDE_CODE.md](#): install the CLI/SDK → set env vars → verify session resolution → verify Dispatch round-trip → troubleshooting.

What you can do now

- Reserve the env-var names in your `.env` per [../OPERATOR_CREDENTIALS.md](#).
- The Dispatcher interface in `commons_messaging/dispatch/` is the seam every new dispatcher implements — see the Claude Code implementation as the reference shape.

Related

- [OPERATOR_CREDENTIALS.md](#) §"Alternate LLM dispatchers"
- [CLAUDE_CODE.md](#) — canonical live-dispatcher guide shape
- Spec: V3 §33 (pluggable Dispatcher)