

Herald



Herald — Lark Channel Setup Guide

Field	Value
Status	PLANNED — HRD-NNN (later iteration)
Spec ref	V3 §11 (later iteration)
Env vars (reserved)	HERALD_LARK_APP_ID, HERALD_LARK_APP_SECRET, HERALD_LARK_CHAT_ID
Code	(not yet implemented)

Lark (Feishu in China) is reserved for a later iteration. Uses an OAuth-style app-id + app-secret flow rather than a single bot token.

This guide is a **placeholder**. When the Lark adapter lands as an HRD, this file will expand to the same step-by-step structure as [TELEGRAM.md](#): obtain credentials → set env vars → verify HealthCheck → verify Send → optional Subscribe → troubleshooting.

What you can do now

- Reserve the env-var names in your `.env` (commented out, per [../OPERATOR_CREDENTIALS.md](#)).
- Watch the HRD for status updates — it will move from `open` to `code complete`; `awaiting live evidence` to `Fixed` over its implementation lifecycle.
- If you have an urgent need for the Lark channel, open an issue against the HRD asking for priority — operator-driven escalation is honored per the constitution.

Related

- [OPERATOR_CREDENTIALS.md](#) — the umbrella credentials guide with reserved env-var blocks for every planned channel
- [TELEGRAM.md](#) — the canonical live-channel guide shape (this file will mirror that structure when Lark lands)
- Spec: V3 §11 (later iteration)