

Herald

Herald

Field	Value
Revision	2
Created	2026-05-15
Last modified	2026-05-20
Status	active
Status summary	Updated spec links to V3 (active) + archive/ for V1/V2; repo-layout block reflects current docs/specs/mvp/ tree.
Issues	none
Issues summary	—
Fixed	spec-path references updated to specification.V3.md path
Fixed summary	aligned README with the V1→V2→V3 supersession chain
Continuation	—

Table of contents

- [Status](#)
- [Mission](#)
- [Deployment model](#)
- [Governance — Helix Constitution inheritance](#)
- [Repository layout](#)
- [Quickstart for developers and agents](#)
 - [1. Place a copy of the Helix Constitution alongside Herald](#)
 - [2. Verify the inheritance contract](#)
 - [3. Read the inherited rules](#)
- [Mirror & push convention](#)
- [License](#)
- [Contact / contribution](#)

Ingesting system events and reliably fanning them out to multiple notification channels so every alert reaches the right destination without confusion.

Status

Herald is **pre-implementation** (2026-05-15). The repository currently contains:

- This README.
- The current specification at [docs/specs/mvp/specification.V3.md](#) — comprehensive (~3900 lines): project-integration contract, inbound processing pipeline, LLM/agent dispatch with Claude Code, tri-stage reply protocol, versioned reports, multi-format outbound attachments, nine refined flavors. V1 and V2 preserved in [docs/specs/mvp/archive/](#) for traceability.
- Project-specific Constitution + operator/agent guides under [docs/guides/](#).
- Mirror declarations at [upstreams/](#) — one shell script per host that exports UPSTREAMABLE_REPOSITORY.
- The inheritance gate + paired mutation meta-test at [tests/](#).
- .gitignore tuned for Go (*.test, go.work*, coverage.*) and .DS_Store.

There is no go.mod, no Go source code, and no build tooling yet. Intended language is Go; standard cmd/ + internal/ layout will be used when scaffolding starts.

Mission

Herald sits between systems that **emit events** and humans/services that **want to be told about them**. It guarantees:

- Every event is delivered to every configured channel for its category.
- Duplicate suppression and routing are explicit, not accidental.
- Delivery failures on one channel never block delivery to other channels.

Deployment model

Herald is designed to be consumed as a **git submodule** of a larger project (the "consuming project"). The consuming project provides:

- The **Helix Constitution** submodule at its own <consuming-project>/constitution/.
- Its own CI / build orchestration that drives Herald.
- Any project-wide configuration (credentials, deployment targets, channel registries).

Herald therefore **does not carry its own copy** of the constitution. See [docs/guides/CONSTITUTION_INHERITANCE.md](#) for the full rationale and the discovery contract that lets Herald locate the constitution at runtime from any nested depth.

Governance — Helix Constitution inheritance

Herald inherits unconditionally from the [Helix Universal Constitution](#). Inheritance is enforced by a paired gate + mutation meta-test under tests/ (see below). Herald-specific extensions live in [docs/guides/HERALD_CONSTITUTION.md](#); there are currently no overrides of any universal clause.

Key invariants Herald inherits from the constitution:

- **No bluffing** — every PASS carries positive evidence (§11.4).
- **Mutation-paired gates** — every new gate has a paired mutation proving it catches regressions (§1.1).
- **No guessing language** — likely, probably, maybe, seems, appears are forbidden when reporting causes (§11.4.6).
- **Credentials never tracked** — .env git-ignored, runtime-load only (§11.4.10).
- **Multi-upstream push** — every commit fans out to GitHub + GitLab + GitFlic + GitVerse (§2.1).
- **Hardlinked backup before destructive ops** (§9).

The constitution lives at <https://github.com/HelixDevelopment/HelixConstitution> and is mirrored to GitLab, GitFlic, and GitVerse.

Repository layout

```
Herald/
├── README.md                # this file
├── CLAUDE.md                # guidance for
Claude Code agents
├── AGENTS.md                # guidance for
generic CLI agents
├── LICENSE
├── .gitignore
├── docs/
│   ├── guides/
│   │   └── HERALD_CONSTITUTION.md    # Herald's project
constitution (extends Helix)
│   └── CONSTITUTION_INHERITANCE.md  # operator/agent
guide for the inheritance contract
│   └── specs/
│       └── mvp/
│           ├── specification.V3.md    # active spec
(operator-product)
│           └── archive/
│               ├── specification.V1.md # historical,
superseded
│               └── specification.V2.md # historical,
superseded
├── upstreams/                # Herald's mirror
declarations
│   ├── GitHub.sh
│   ├── GitLab.sh
│   ├── GitFlic.sh
│   └── GitVerse.sh
└── tests/
    ├── test_constitution_inheritance.sh    # inheritance gate
    └── test_constitution_inheritance_meta.sh # paired mutation
meta-test (§1.1)
```

Quickstart for developers and agents

1. Place a copy of the Helix Constitution alongside Herald

If you cloned Herald standalone (not as a submodule of a larger project), put a clone of the constitution **next to** Herald (not inside it — see §104 of the [Herald Constitution](#)):

```
git clone git@github.com:HelixDevelopment/HelixConstitution.git \
    $(dirname "$PWD")/constitution
```

This is only needed for standalone work. When Herald is consumed as a submodule of a larger project, that project already provides <parent>/constitution/.

2. Verify the inheritance contract

```
bash tests/test_constitution_inheritance.sh          # gate (7
              invariants)
bash tests/test_constitution_inheritance_meta.sh     # paired $1.1
              mutation proof
```

Both MUST exit 0. The gate prints PASS ... / FAIL ... per invariant and a summary line. The meta-test prints ✓ META-TEST PASS when the gate correctly fails on a mutated constitution.

If I1 fails (constitution not found), follow the message — clone the constitution alongside Herald.

3. Read the inherited rules

In this order, read fully before submitting any change:

1. <discovered-constitution>/CLAUDE.md + Constitution.md — universal Helix rules.
2. <discovered-constitution>/AGENTS.md — anti-bluff, no-guessing, paired mutations.
3. This README — Herald overview.
4. [CLAUDE.md](#) / [AGENTS.md](#) — Herald-specific guidance.
5. [docs/guides/HERALD_CONSTITUTION.md](#) — Herald's articles §101–§106.
6. [docs/guides/CONSTITUTION_INHERITANCE.md](#) — the discovery contract and gate semantics.
7. [docs/specs/mvp/specification.V3.md](#) — current spec (active). Historical V1/V2 in [docs/specs/mvp/archive/](#).

Mirror & push convention

Herald is mirrored to four hosts. The origin remote is **fan-out**: one fetch URL + four push URLs. A single `git push origin main` propagates to every mirror in one operation.

Remote name	URL
github	git@github.com:vasic-digital/Herald.git
gitlab	git@gitlab.com:vasic-digital/herald.git
gitflic	git@gitflic.ru:vasic-digital/herald.git
gitverse	git@gitverse.ru:vasic-digital/Herald.git
origin	(fetch from github; push fans out to all four)

Each entry under `upstreams/` is a shell script that exports a single `UPSTREAMABLE_REPOSITORY=...` URL and is meant to be **sourced**, not executed for its output. Capitalization matches each host's brand (GitFlic, GitVerse); do not normalize to lowercase or collapse into one file — external mirror-push tooling keys on the per-file split.

If you ever need to rebuild the fan-out configuration, the constitution submodule ships `install_upstreams.sh` that consumes `Upstreams/*.sh` declarations and configures git remotes accordingly; the same pattern can be adapted for Herald.

License

LICENSE — see file for terms.

Contact / contribution

Substantive contributions land via PRs on GitHub; mirrors are read-only for external consumers. Inheritance rules and the gate apply to every PR.