

Herald



Herald

Field	Value
Revision	3
Created	2026-05-15
Last modified	2026-05-20
Status	active
Status summary	Updated spec links to V3 (active) + archive/ for V1/V2; repo-layout block reflects current docs/specs/mvp/ tree.
Issues	none
Issues summary	—
Fixed	spec-path references updated to specification.V3.md path
Fixed summary	aligned README with the V1→V2→V3 supersession chain
Continuation	—

Table of contents

- [Status](#)
- [Mission](#)
- [Deployment model](#)
- [Governance — Helix Constitution inheritance](#)
- [Repository layout](#)
- [Quickstart for developers and agents](#)
 - [1. Place a copy of the Helix Constitution alongside Herald](#)
 - [2. Verify the inheritance contract](#)
 - [3. Read the inherited rules](#)
- [Operator setup guides](#)
 - [Messengers](#)
 - [LLM / agent dispatchers](#)
 - [Per-flavor operator guides](#)
 - [Credentials master guide](#)
- [Mirror & push convention](#)
- [License](#)
- [Contact / contribution](#)

Ingesting system events and reliably fanning them out to multiple notification channels so every alert reaches the right destination without confusion.

Status

Herald is **pre-implementation** (2026-05-15). The repository currently contains:

- This README.
- The current specification at [docs/specs/mvp/specification.V3.md](#) — comprehensive (~3900 lines): project-integration contract, inbound processing pipeline, LLM/agent dispatch with Claude Code, tri-stage reply protocol, versioned reports, multi-format outbound attachments, nine refined flavors. V1 and V2 preserved in [docs/specs/mvp/archive/](#) for traceability.
- Project-specific Constitution + operator/agent guides under [docs/guides/](#).
- Mirror declarations at [upstreams/](#) — one shell script per host that exports `UPSTREAMABLE_REPOSITORY`.
- The inheritance gate + paired mutation meta-test at [tests/](#).
- `.gitignore` tuned for Go (`*.test`, `go.work*`, `coverage.*`) and `.DS_Store`.

There is no `go.mod`, no Go source code, and no build tooling yet. Intended language is Go; standard `cmd/` + `internal/` layout will be used when scaffolding starts.

Mission

Herald sits between systems that **emit events** and humans/services that **want to be told about them**. It guarantees:

- Every event is delivered to every configured channel for its category.
- Duplicate suppression and routing are explicit, not accidental.
- Delivery failures on one channel never block delivery to other channels.

Deployment model

Herald is designed to be consumed as a **git submodule** of a larger project (the "consuming project"). The consuming project provides:

- The **Helix Constitution** submodule at its own `<consuming-project>/constitution/`.
- Its own CI / build orchestration that drives Herald.
- Any project-wide configuration (credentials, deployment targets, channel registries).

Herald therefore **does not carry its own copy** of the constitution. See [docs/guides/CONSTITUTION_INHERITANCE.md](#) for the full rationale and the discovery contract that lets Herald locate the constitution at runtime from any nested depth.

Governance — Helix Constitution inheritance

Herald inherits unconditionally from the [Helix Universal Constitution](#). Inheritance is enforced by a paired gate + mutation meta-test under `tests/` (see below). Herald-specific extensions live in [docs/guides/HERALD_CONSTITUTION.md](#); there are currently no overrides of any universal clause.

Key invariants Herald inherits from the constitution:

- **No bluffing** — every PASS carries positive evidence (§11.4).
- **Mutation-paired gates** — every new gate has a paired mutation proving it catches regressions (§1.1).
- **No guessing language** — likely, probably, maybe, seems, appears are forbidden when reporting causes (§11.4.6).
- **Credentials never tracked** — .env git-ignored, runtime-load only (§11.4.10).
- **Multi-upstream push** — every commit fans out to GitHub + GitLab + GitFlic + GitVerse (§2.1).
- **Hardlinked backup before destructive ops** (§9).

The constitution lives at <https://github.com/HelixDevelopment/HelixConstitution> and is mirrored to GitLab, GitFlic, and GitVerse.

Repository layout

```
Herald/
├── README.md                # this file
├── CLAUDE.md                # guidance for Claude Code
├── AGENTS.md                # guidance for generic CLI
├── LICENSE
├── .gitignore
├── docs/
│   ├── guides/
│   │   ├── HERALD_CONSTITUTION.md        # Herald's project constitution
│   │   └── CONSTITUTION_INHERITANCE.md    # operator/agent guide for inheritance
│   └── specs/
│       ├── mvp/
│       │   ├── specification.V3.md        # active spec (operator-product)
│       │   └── archive/
│       │       ├── specification.V1.md     # historical, superseded
│       │       └── specification.V2.md     # historical, superseded
├── upstreams/
│   ├── GitHub.sh
│   ├── GitLab.sh
│   ├── GitFlic.sh
│   └── GitVerse.sh
├── tests/
│   ├── test_constitution_inheritance.sh    # inheritance gate
│   └── test_constitution_inheritance_meta.sh # paired mutation meta-test
```

Quickstart for developers and agents

1. Place a copy of the Helix Constitution alongside Herald

If you cloned Herald standalone (not as a submodule of a larger project), put a clone of the constitution **next to** Herald (not inside it — see [§104 of the Herald Constitution](#)):

```
git clone git@github.com:HelixDevelopment/HelixConstitution.git \
    $(dirname "$PWD")/constitution
```

This is only needed for standalone work. When Herald is consumed as a submodule of a larger project, that project already provides `<parent>/constitution/`.

2. Verify the inheritance contract

```
bash tests/test_constitution_inheritance.sh          # gate (7
              invariants)
bash tests/test_constitution_inheritance_meta.sh     # paired §1.1
              mutation proof
```

Both MUST exit 0. The gate prints `PASS ... / FAIL ...` per invariant and a summary line. The meta-test prints `✓ META-TEST PASS` when the gate correctly fails on a mutated constitution.

If I1 fails (constitution not found), follow the message — clone the constitution alongside Herald.

3. Read the inherited rules

In this order, read fully before submitting any change:

1. `<discovered-constitution>/CLAUDE.md + Constitution.md` — universal Helix rules.
2. `<discovered-constitution>/AGENTS.md` — anti-bluff, no-guessing, paired mutations.
3. This README — Herald overview.
4. [CLAUDE.md](#) / [AGENTS.md](#) — Herald-specific guidance.
5. [docs/guides/HERALD_CONSTITUTION.md](#) — Herald's articles §101–§106.
6. [docs/guides/CONSTITUTION_INHERITANCE.md](#) — the discovery contract and gate semantics.
7. [docs/specs/mvp/specification.V3.md](#) — current spec (active). Historical V1/V2 in [docs/specs/mvp/archive/](#).

Operator setup guides

Every supported messenger and every supported LLM / agent dispatcher has its own step-by-step setup guide under [docs/guides/](#). **Live** ones are detailed end-to-end (obtain credentials → set env vars → verify integration tests → troubleshooting). **Planned** ones are placeholder stubs that reserve the env-var names so your `.env` stays stable as features land.

Messengers

Channel	Status	Guide
Telegram	LIVE (HRD-011 code complete; awaiting live evidence)	docs/guides/messengers/TELEGRAM.md
Slack	Planned (V2)	docs/guides/messengers/SLACK.md
Email (SMTP + Resend)	Planned (V2)	docs/guides/messengers/EMAIL.md
Max	Planned (V2)	docs/guides/messengers/MAX.md
Microsoft Teams	Planned (V3)	

Channel	Status	Guide
		docs/guides/messengers/TEAMS.md
Lark / Feishu	Planned (later)	docs/guides/messengers/LARK.md
Discord	Planned (later)	docs/guides/messengers/DISCORD.md
WhatsApp Business	Planned (later)	docs/guides/messengers/WHATSAPP.md
Viber	Planned (later)	docs/guides/messengers/VIBER.md

LLM / agent dispatchers

Dispatcher	Status	Guide
Claude Code	LIVE (HRD-012 Fixed — live E18 evidence captured)	docs/guides/dispatchers/CLAUDE_CODE.md
OpenCode	Planned	docs/guides/dispatchers/OPENCODE.md
Aider	Planned	docs/guides/dispatchers/AIDER.md
Gemini	Planned	docs/guides/dispatchers/GEMINI.md
Cursor	Planned	docs/guides/dispatchers/CURSОР.md
Anthropic Managed Agent	Planned	docs/guides/dispatchers/ANTHROPIC.md

Per-flavor operator guides

Each Herald flavor binary ships with a nano-detail operator reference under [docs/guides/](#), documenting every subcommand the built binary surfaces (`<flavor> --help`), the env/credentials each needs, real example invocations, and which subcommands are live vs not-yet-implemented (all anti-bluff — derived from running the actual binary, nothing invented).

Flavor	Role	Guide
pherald	Project Herald — the richest flavor: <code>serve/listen/watch/migrate/wizard/commit-push</code> + the §43 GitOps commands	docs/guides/PHERALD.md
sherald	System Herald — <code>serve (/v1/safety_state)</code> + the host-safety guard commands (<code>destructive-guard</code> , <code>force-push-gate</code> , <code>mem-budget-watch</code> , <code>backup-snapshot</code> , <code>sysctl</code>)	docs/guides/SHERALD.md
cherald	Constitution Herald — <code>serve (/v1/compliance)</code> + the §11.4 compliance-check catalogue (<code>creds-scan</code> , <code>docs-sync</code> , <code>composite-gate</code> , <code>readme-sync</code> , ...)	docs/guides/CHERALD.md
bherald	Build Herald — CLI-only CI/test gates: <code>evidence-capture</code> (§11.4.2) + <code>test-tier-verify</code> (§40.2 8-tier matrix); <code>gate-retest</code> not-yet-implemented (HRD-045)	docs/guides/BHERALD.md

Flavor	Role	Guide
rherald	Release Herald — CLI-only release path: <code>change log-generate</code> (§5), <code>tag-mirror</code> (§4 cross-mirror parity), <code>gate-retest</code> (§11.4.40 pre-tag retest)	docs/guides/RHERALD.md
iherald	Incident Herald — <code>serve</code> ; <code>/v1/webhooks/page</code> is an honest 501 stub pending HRD-024	docs/guides/IHERALD.md
scherald	Status-Check Herald — CLI-only <code>status-digest</code> (§11.4.45 rollup)	docs/guides/SCHERALD.md
qaherald	QA Herald — Herald's autonomous QA bot: <code>run</code> (scenario harness → docs/qa evidence), <code>mtproto</code> session lifecycle (<code>login/whoami/logout</code>), <code>lifecycle</code> (15-scenario driver, SKELETON)	docs/guides/QAHERALD.md

Credentials master guide

[docs/guides/OPERATOR_CREDENTIALS.md](https://docs.guide.com/OPERATOR_CREDENTIALS.md) is the umbrella reference covering:

- The 12-factor resolution order (CLI flag > shell exports > `.env` > defaults)
- How to set credentials via `~/ .bashrc` / `~/ .zshrc` (shell-export path) AND `.env` (project-local path) — both supported per spec V3 §3.3
- Pre-commit secrets audit checklist (`.env` not tracked; no obvious-format secrets; `.env.example` only has placeholders)
- Quickstart-compose vs native pherald operating modes
- Troubleshooting (SQLSTATE 28P01, "DSN not set", SKIP-with-reason logic per §11.4.3, ...)

Per Universal Constitution §11.4.10: `.env` **files MUST NEVER be committed**. The repo's `.gitignore` already covers `.env`. The committed `quickstart/.env.example` is the only credentials-file that lives in git, and it contains only placeholder values.

Active blockers — operator action required

[docs/requirements/blockers/missing_env_variables.md](https://docs.requirements/blockers/missing_env_variables.md) — the step-by-step MTPROTO credential setup the operator must complete to unblock Wave 8 Track B (the full-automation rewrite of `TestSubscribe_LiveBotAPI`, `tests/test_wave6_live_loop.sh`, and Wave 6.5 lifecycle scenarios per HelixConstitution §11.4.98 + Herald §108.m). Available in Markdown / HTML / PDF / DOCX. **Required for §11.4.98 compliance — release-gate item.**

[docs/audits/full-automation-114-98-audit-2026-05-28.md](https://docs.audits/full-automation-114-98-audit-2026-05-28.md) — the canonical classification of every Herald test against §11.4.98 (794 tests audited: 758 COMPLIANT-hermetic, 32 COMPLIANT-with-creds-bootstrap, 4 NON-COMPLIANT-manual-dep, 1 STRUCTURALLY-BROKEN). NON-COMPLIANT items have until 2026-06-27 (T+30 days) to be rewritten before graduating to §11.4.90 Obsolete.

Mirror & push convention

Herald is mirrored to four hosts. The `origin` remote is **fan-out**: one fetch URL + four push URLs. A single `git push origin main` propagates to every mirror in one operation.

Remote name URL

github	git@github.com:vasic-digital/Herald.git
gitlab	git@gitlab.com:vasic-digital/herald.git
gitflic	git@gitflic.ru:vasic-digital/herald.git
gitverse	git@gitverse.ru:vasic-digital/Herald.git
origin	(fetch from github; push fans out to all four)

Each entry under `upstreams/` is a shell script that exports a single `UPSTREAMABLE_REPOSITORY=...` URL and is meant to be **sourced**, not executed for its output. Capitalization matches each host's brand (GitFlic, GitVerse); do not normalize to lowercase or collapse into one file — external mirror-push tooling keys on the per-file split.

If you ever need to rebuild the fan-out configuration, the constitution submodule ships `install_upstreams.sh` that consumes `Upstreams/*.sh` declarations and configures git remotes accordingly; the same pattern can be adapted for Herald.

License

[LICENSE](#) — see file for terms.

Contact / contribution

Substantive contributions land via PRs on GitHub; mirrors are read-only for external consumers. Inheritance rules and the gate apply to every PR.

Sources verified

Per HelixConstitution §11.4.99 + Herald §108.n (Latest-Source Documentation Cross-Reference Mandate). This README is a gateway document — the substantive operator-facing instructions live in the per-channel / per-dispatcher guides linked above. Each linked guide carries its own `## Sources verified` footer covering the external services it documents. The cross-references below cover the external claims this README makes directly.

Last verified: 2026-05-28

Source	URL / path	Authored / verified
HelixConstitution	https://github.com/HelixDevelopment/HelixConstitution	§"Governance" (constitution authority + canonical URL); §"Quickstart" step 1 (clone-alongside command); §"Inherited invariants" list (§11.4 anti-bluff, §1.1 paired mutations, §11.4.6 no-guessing language, §11.4.10 credentials-never-tracked, §2.1 multi-upstream push, §9 hardlinked-backup).
Telegram official Bot API documentation	https://core.telegram.org/bots/api	§"Messengers" table — Telegram channel status (LIVE — HRD-011 + HRD-100). The substantive setup steps are in docs/guides/messengers/TELEGRAM.md +

Source	URL / path	Authored / verified
Anthropic — Claude Code documentation	https://docs.anthropic.com/claude-code	docs/guides/TELEGRAM.md which carry their own §11.4.99 footers. §"LLM / agent dispatchers" table — Claude Code status (LIVE — HRD-012 Fixed). The substantive setup steps are in docs/guides/ dispatchers/CLAUDE_CODE.md which carries its own §11.4.99 footer. §"Active blockers" link target — that document carries the canonical Telegram-userbot safety walkthrough (the <code>recover@telegram.org</code> pre- login email; no VoIP / Google Voice / Twilio / TextNow numbers; one phone = one <code>api_id</code> forever; Short-name STRICTLY alphanumeric — underscores REJECTED; <code>ratelimit + floodwait</code> middlewares) with its own §11.4.99 footer. §"Status" claims about Herald implementation maturity; §"Mission" canonical statement; §"Repository layout"; the V1→V2→V3 supersession chain. The spec itself carries its own §11.4.99 footer covering the external service contracts its design decisions depend on.
Herald active blockers — MTProto credential setup	docs/requirements/ blockers/ missing_env_variables.md	
Herald spec V3 (source of truth)	docs/specs/mvp/ specification.V3.md	

Re-verification cadence (per §11.4.99 (C)): This README does not contain operator-actionable external-service instructions directly — those are in the linked guides, each with its own cadence. README-level re-verification is **on Herald structural changes** (repo-layout changes, new flavors, new mirror hosts, new linked guides) — no time-bound staleness. Linked guides **MUST** be kept current per their own footers.