

Herald



Herald — iherald Flavor Guide (Operator)

Field	Value
Revision	1
Created	2026-05-30
Last modified	2026-05-30
Status	active
Status summary	Nano-detail operator reference for iherald (Incident Herald) — a serving flavor (DefaultPort=24794). Documents serve and, honestly, that its only application route POST /v1/webhooks/page is currently a 501 stub (HRD-024 pending). ANTI-BLUFF: derived from the built iherald binary (iherald --help, version --json) + commons/branding.go + iherald/internal/http/routes.go. Per the §11.4.69 anti-bluff posture, iherald serves an honest 501 + HRD pointer rather than a fake 200 stub — this guide states that plainly.
Issues	(none specific to this guide)
Continuation	Bump when HRD-024 lands the live /v1/webhooks/page paging handler body.

Table of contents

- [§1. What iherald is](#)
- [§2. The subcommand surface](#)
- [§3. version](#)
- [§4. serve — and the 501 paging stub](#)
- [§5. References](#)

§1. What iherald is

iherald is **Incident Herald** — flavor key i, prefix IHR, default serving port **24794**. Per commons/branding.go its mission is "Credential-leak page-out + operator-blocked escalation". It is intended to be the paging surface for incident escalation. As of this revision its HTTP plane is wired but the paging route itself is a **501 stub** awaiting HRD-024 — iherald is

the most honest demonstration of Herald's anti-bluff posture: it returns a real 501 Not Implemented + an HRD pointer rather than a fake 200.

Build it:

```
go build -o /tmp/iherald ./iherald/cmd/iherald
```

§2. The subcommand surface

Verbatim from `iherald --help` — `iherald` has the smallest surface of all flavors (no §43 command catalogue yet):

Subcommand What it does

<code>serve</code>	Start the Incident Herald HTTP server
<code>version</code>	Print Incident Herald version + build info
<code>completion</code>	Generate shell autocompletion (Cobra built-in)

§3. version

```
$ iherald version --json
{"arch":"arm64","binary":"iherald","build_time":"unknown","commit":"unknown-dev"}
```

§4. serve — and the 501 paging stub

`iherald serve` starts the Incident Herald HTTP server on port 24794. Like the other serving flavors it exposes the standard health/metrics surface (`/v1/healthz`, `/v1/readyz`, `/metrics`), and shares the `commons/cli` serve scaffold.

The one application route, `POST /v1/webhooks/page`, is a 501 stub. Per `iherald/internal/http/routes.go` the route is registered with HRD: `"HRD-024"` and returns an honest 501 Not Implemented + an HRD pointer. The package comment states the rationale directly: an honest 501 + HRD pointer beats a 200 stub under the §11.4.69 anti-bluff posture. The live paging integration (the `/v1/webhooks/page` handler body + the §43 escalation command bodies) is scope-locked to the HRD-024 follow-ups.

```
iherald serve --http-port 24794
# POST /v1/webhooks/page → 501 Not Implemented (HRD-024 pending)
```

Do not build a pager integration against `/v1/webhooks/page` yet — it does not deliver. The `iherald/internal/bindings/` package supplies the constitution-binding scaffold (incident/escalation Evaluator) that the future handler will consume, but the handler body itself is not written.

§5. References

- Source: `iherald/cmd/iherald/main.go`, `iherald/internal/http/routes.go`, `iherald/internal/bindings/bindings.go`.
- Branding: `commons/branding.go` (flavor `i`, `DefaultPort=24794`).

- Integration: docs/INTEGRATION.md §1/§10 (iherald row — POST /v1/webhooks/page 501 stub, HRD-024 pending).
- Open work: HRD-024 (the live paging handler + §43 escalation command bodies).
- Companion flavor guides: docs/guides/{PHERALD, SHERALD, CHERALD, BHERALD, RHERALD, SCHERALD, QAHERALD}.md.

Sources verified

Verified 2026-05-30: internal doc — no external online sources. The subcommand surface + version --json were derived by running the built iherald binary (iherald --help, iherald version --json) on 2026-05-30; the 501-stub status of POST /v1/webhooks/page was confirmed by reading iherald/internal/http/routes.go (route registered with HRD: "HRD-024") and the package comments in iherald/cmd/iherald/main.go + iherald/internal/bindings/bindings.go, plus commons/branding.go for the flavor identity. No routes or flags were invented; the not-yet-implemented status is stated honestly. Re-verify when HRD-024 lands the live paging handler.