

Herald



Herald — scherald Flavor Guide (Operator)

Field	Value
Revision	1
Created	2026-05-30
Last modified	2026-05-30
Status	active
Status summary	Nano-detail operator reference for scherald (Scheduled-audit Herald) — a CLI-only flavor (DefaultPort=0) for the periodic status sweep. Documents status-digest (§11.4.45 status-sweep + compliance digest) and version. ANTI-BLUFF: derived from the built scherald binary (scherald --help, scherald status-digest --help, version --json)+commons/branding.go. status-digest is DETECT/REPORT-only by default and exits non-zero when docs/Status.md is missing or stale; --apply is the only mutating mode.
Issues	(none specific to this guide)
Continuation	Bump as the scheduled-audit catalogue gains commands.

Table of contents

- [§1. What scherald is](#)
- [§2. The subcommand surface](#)
- [§3. version](#)
- [§4. status-digest](#)
- [§5. References](#)

§1. What scherald is

scherald is **Scheduled-audit Herald** — flavor key `sc`, prefix `SCR`, **CLI-only** (DefaultPort=0, no serve mode). Per `commons/branding.go` its mission is "Periodic Status.md sweep + compliance digest". It is designed to be invoked from cron (or any scheduler) to sweep the work-

item trackers and report on their state, exiting non-zero when docs/Status.md is missing or stale so the schedule surfaces drift.

Build it:

```
go build -o /tmp/scherald ./scherald/cmd/scherald
```

§2. The subcommand surface

Verbatim from scherald --help:

Subcommand	What it does
status-digest	Sweep docs/Status.md + digest work-item state, classify §11.4.45 (-- apply regenerates the summary)
version	Print Scheduled-audit Herald version + build info
completion	Generate shell autocompletion (Cobra built-in)

§3. version

```
$ scherald version --json
{"arch":"arm64","binary":"scherald","build_time":"unknown","commit":"unknown","dev"}
```

§4. status-digest

SCHEDULED-AUDIT SWEEP: reads docs/Status.md (plus docs/Issues.md / docs/Fixed.md for evidence) under --repo, prints a concise digest of the work-item state — a tally of open vs fixed HRD-ids plus any items still flagged open in BOTH trackers as the stale-item count — builds the §11.4.45 status-sweep Subject, classifies it through the HRD-025 binding, and **exits non-zero when docs/Status.md is missing or stale** (a §11.4.45 violation). Default is DETECT/REPORT-only (hermetic, no mutation).

Flag	Meaning
--apply	(Re)generate docs/Status_Summary.md from Status.md (mutation; default: detect-only)
--repo string	Repo dir to scope the sweep/regeneration to (default: discovered from CWD)
--emit	Also drive the §11.4.45 verdict as a real constitution event

```
# Cron-friendly detect-only sweep (exit non-zero on stale/missing Status.md):
```

```
scherald status-digest --repo /path/to/herald
```

```
# Regenerate the derived summary as part of the sweep:
```

```
scherald status-digest --apply
```

§5. References

- Source: `scherald/cmd/scherald/main.go + digest_cmds.go`.
- Branding: `commons/branding.go` (flavor `sc`, `DefaultPort=0`).
- Trackers swept: `docs/Status.md`, `docs/Issues.md`, `docs/Fixed.md`; derived: `docs/Status_Summary.md`.
- Constitution binding: HRD-025 §11.4.45 (status-sweep).
- Companion flavor guides: `docs/guides/{PHERALD, SHERALD, CHERALD, BHERALD, RHERALD, IHERALD, QAHERALD}.md`.

Sources verified

Verified 2026-05-30: internal doc — no external online sources. Every subcommand, flag, default, and behaviour claim above was derived by running the built `scherald` binary (`scherald --help`; `scherald status-digest --help`; `scherald version --json`) and reading `commons/branding.go` on 2026-05-30. No flags were invented. Re-verify whenever the `scherald` Cobra surface changes.