

Herald



Herald — Fixed

Field	Value
Revision	21
Created	2026-05-20
Last modified	2026-05-31
Status	active
Status summary	**r21: added two participant-attribution columns — <code>Created-By</code> + <code>Assigned-To</code> — to the Fixed pipe-table, placed immediately AFTER the <code>Criticality</code> column (before <code>Title</code>) so the metadata stays grouped and the long <code>Title</code> stays at the right edge (per <code>docs/design/PARTICIPANT_ATTRIBUTION.md</code> §4c). Table widens 7→9 columns; header + separator + every data row updated programmatically (<code>/tmp/add_attribution_cols.py</code>) so every row's ` see <code>Issues.md</code> — r43 (<code>Issues.md</code>) captures this r19 §11.4.19 atomic migration of 51 code-verified HRDs (flavor bindings HRD-019..025, §43 catalogue HRD-029..056, Batch-D pgx HRD-085..089, Wave 7 HRD-116/118/119/120/121, ATMOSphere features HRD-148/149/151/152/153/154); 17 items remain open in <code>Issues.md</code>. 17 still open in <code>Issues.md</code>: HRD-008, HRD-015, HRD-081 (operator/upstream); HRD-115 (Slack adapter — operator-gated on LIVE round-trip evidence per §107.x); HRD-117 (spec doc-only); HRD-131, HRD-150, HRD-155, HRD-156, HRD-157, HRD-158 (ATMOSphere/SSoT externally gated); HRD-146, HRD-147 (dispatch-hardening / governance-subscriber follow-ups); HRD-143/144/145 (Obsolete).
Issues	HRD-001..HRD-007, HRD-009, HRD-009b, HRD-010, HRD-011, HRD-012, HRD-013, HRD-014, HRD-016, HRD-017, HRD-018, HRD-019..HRD-025, HRD-026, HRD-027, HRD-028, HRD-029..HRD-056, HRD-080, HRD-085..HRD-089, HRD-090, HRD-092, HRD-093, HRD-094, HRD-095, HRD-096, HRD-097, HRD-098, HRD-099, HRD-100, HRD-110, HRD-111, HRD-112, HRD-113, HRD-114, HRD-116, HRD-118, HRD-119, HRD-120, HRD-121, HRD-122, HRD-123, HRD-124, HRD-125, HRD-126, HRD-127, HRD-128, HRD-129, HRD-130, HRD-132, HRD-133, HRD-134, HRD-135, HRD-136, HRD-137, HRD-138, HRD-139, HRD-140, HRD-141, HRD-142, HRD-146, HRD-147, HRD-148, HRD-149, HRD-151, HRD-152, HRD-153, HRD-154
Issues summary	
Fixed	

Field	Value
Fixed summary	v1.0.0 closure-migration (r19 — 51 HRDs: flavor constitution bindings HRD-019..025, §43 command catalogue HRD-029..056, Batch-D pgxTaskRepository ops HRD-085..089, Wave 7 multi-channel HRD-116/118/119/120/121, ATMOSphere workable-items features HRD-148/149/151/152/153/154 — each re-verified against committed code + passing tests + e2e invariant + docs/qa before migration). Wave 8 Track B (HRD-139/140/141/142 — MTPProto user-account harness proves §11.4.98 full- automation end-to-end with 3 live MTPProto-driven tests PASSING LIVE 2026-05-28; v0.6.0 tag covers the closure); Tgram-completeness wave (HRD-133/134/135/136/137/138 — 6 HRDs across 3 sub-waves A/B/C, full tgram suite 26/26 PASS 0 SKIP); GAP-3 §11.4.85 stress+chaos suite (HRD-122..HRD-130 Completed) + HRD-132 Runner idempotency-window fix (claim-before-dispatch, exactly-once dispatch sends==1); spec V1→V3 r9; Go module foundation + Foundation M1/M2/M3; HRD-010 commons_storage live wiring; HRD-011 Telegram live (live message_id=5 evidence 2026-05-22); HRD-012 Claude Code dispatcher live; HRD-016 pherald /v1/events Runner wiring (Wave 3b live — 7-stage pipeline + e2e E37-E42); universal §11.4.73 + §11.4.74 mandates propagated; I6 gate refined; Wave 2 flavor scaffolds (HRD-092..097) closed atomically; Wave 3a substrate (HRD-099 commons_auth JWT verifier) + 2 live REST routes (HRD-028, HRD-098) closed atomically.

Continuation see CONTINUATION.md.

Table of contents

- [Recently fixed](#)

Recently fixed

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-147	task	low	Claude	@milos85vasic	Governance-plane dead-letter subscriber — durable c events into a DeadLetterSink (MemoryDeadLe PostgresDeadLetterSink is a drop-in behind t boot.go now wires the REAL emitter into newPg the nil-emitter) + stands up a DeadLetterSubscr error-counted), guarded to build only alongside the Po if emitter construction fails (a dead-letter move must t Mirrors the commons_constitution.AuditSt tests (move→emit→subscribe→sink end-to-end, failu -race, idempotent Close) + the 3 existing MoveToD PostgresDeadLetterSink behind the interface pherald listen dispatch hardening — bounded inbound→claudes_code.Dispatch path. The pr ctx (pherald listen gctx → subscriber goroutin child could block the subscriber indefinitely (HRD-14 Added DefaultDispatchTimeout=120s + HE env knob + SetDispatchTimeout(); Dispatc deadline, budget) (a tighter caller still wins; c setProcessGroup (Setpgid + Cmd.Cancel→k holding child can't wedge Output() past the deadli
HRD-146	task	middle	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-019	task	high	Claude	@milos85vasic	30 shim is KILLED in 702ms (vs 30s) with the timeo 402ms; happy-path 26ms. - race -count=3 green cherald constitution bindings — cherald/inte cherald-owned §42.3 rules as concrete commons_co through 5 event classes (.policy.violation/.gate.failed/.gate over the Batch-A emit+persist+audit foundation; POS surface drives detect→emit→persist→audit, visible o pull surface. Vertical-slice bespoke detectors landed (§11.4.44 doc-revision-header, §11.4.18 script-docs, § remaining 25 rules use the shared marker-check mech catalogue command / sweep) with the full emit-routin remaining bespoke detector is per-rule follow-up.
HRD-020	task	high	Claude	@milos85vasic	sherald host-safety + repo-safety constitution bind bindings Pipeline registers the 15 sherald-owned § §11.4.24/.26/.32/.36/.41/.47/.71, §12.1/.2/.3/.6) as con commons_constitution.Evaluator impls ro (.host.safety.breach/.repo.safety.bre over the Batch-A emit+persist+audit foundation, mirr pattern. The 3 named DETECTION hooks landed as l detector (§9.1: rm/git-reset/clean without backup → . interceptor (§11.4.41/§9.2: force-push without merge- .repo.safety.breach), mem-budget watcher (.host.safety.breach) — plus forbidden-host- remaining rows. CRITICAL §12-safety: every detecto string description; NONE performs the destructive op allocates memory (the mem-budget watcher reads a fa §43 command bodies (HRD-033/046/056) supply the
HRD-021	task	middle	Claude	@milos85vasic	bherald CI/test bindings — bherald/interna bherald-owned §42.3 CI/test gate-result rules (§1, §1. §11.4.2/.3/.4/.5/.7/.9/.13/.14/.24/.27/.30/.39/.43/.46/.4 commons_constitution.Evaluator impls ro (.gate.failed/.gate.recovered via the buil .policy.violation+.repo.safety.brea row) over the Batch-A emit+persist+audit foundation, Pipeline pattern. bherald is the BUILD/CI flavor; it en that integrate with the consuming project's CI workflo result classification (§1/§11.4.50 — PASS/FAIL/flaky .gate.failed/.gate.recovered), test-tier-ve matrix; a missing tier FAILs), anti-bluff-PASS detecti WITHOUT a captured-evidence artefact is a §11.4 PA shared marker-check mechanism (verdict decided ups full emit-routing framework in place.
HRD-022	task	middle	Claude	@milos85vasic	rherald release constitution bindings — rherald registers the 4 rherald-owned §42.3 release-lifecycle r multi-format export [shared with cherald], §11.4.38 in retest before release tag) as concrete commons_con through 2 event classes (.release.gate.block ReleaseGateBlocked emitter surface for §4/§11 for the shared §5 changelog row; a release recovery m

ID	Type	Criticality	Created-By	Assigned-To	Title
					companion since the release class family has no distinct emit+persist+audit foundation, mirroring the proven I the RELEASE flavor. 4 bespoke PURE detectors land parent but missing on any owned mirror, with_tag .release.gate.blocked), changelog-conformant changelog OR stale multi-format export → .policy (§11.4.40 CRITICAL — tag attempted without a green .release.gate.blocked), installable-asset-evidence install check → .release.gate.blocked). CR CLASSIFIES a recorded release-op outcome string; N downloads, or installs — the live release-op intercept (HRD-031/032/045).
HRD-023	task	middle	Claude	@milos85vasic	pherald project bindings (§2 commit+push, §3 sub §11.4.11/.15/.21/.22/.34/.37/.42/.55/.66/.71/.74) — Batch bindings / Pipeline + §42.3-owned rule set + 5 besp discipline / submodule-propagation-order / pre-push-f through the commons_constitution Evaluator+audit fo Live op-interception deferred to §43 HRD-029/030/04
HRD-024	task	middle	Claude	@milos85vasic	pherald constitution-rule escalation bindings (§11.4 + §11.4.66 operator-blocked escalation) — Batch B: : Pipeline routing .credential.leak (forced-critical detectors wired through commons_constitution Evalu no-real-secret attestation. Live paging deferred to §43
HRD-025	task	low	Claude	@milos85vasic	pherald scheduled-audit bindings (§11.4.45 period compliance digest) — Batch B: spherald/inter .policy.violation + 3 bespoke detectors (statu through commons_constitution Evaluator+audit; -race scheduler deferred to §43 HRD-047.
HRD-029	task	middle	Claude	@milos85vasic	§2 pherald commit-push — single-entripoint I C: implemented as gitops command (§11.4.74 wrap o hermetic temp-repo tests -race green
HRD-030	task	middle	Claude	@milos85vasic	§3 pherald submodule propagate — owned Batch C: implemented as gitops command (§11.4.74 v binding; hermetic temp-repo tests -race green
HRD-031	task	middle	Claude	@milos85vasic	§4 rherald tag mirror — assert tag exists on implemented as rherald §43 release command (rher release_cmds.go) feeding the HRD-022 rherald hermetic -race green
HRD-032	task	low	Claude	@milos85vasic	§5 rherald changelog generate — Conven <v>.md + multi-format export — Batch C: impleme (rherald/cmd/rherald/release_cmds.go) reuses shared commons/gitops; hermetic -race gr
HRD-033	task	high	Claude	@milos85vasic	§9.1 sherald destructive guard <op> — prerequisite checks — Batch C: implemented as shera sherald/sysops_cmds.go) feeding the HRD-0 (detects+classifies+exits-nonzero, never performs the fix so the CLI runs without a JWT secret
HRD-034	task	middle	Claude	@milos85vasic	§9.3 sherald backup-snapshot <target> straggler: implemented in sherald/cmd/sheral

ID	Type	Criticality	Created-By	Assigned-To	Title
					refuses overwrite, classifies §9.3 SubjectBackup → .equality -race green
HRD-035	task	middle	Claude	@milos85vasic	§11.4.2 bherald evidence capture <test_ Batch C: implemented as bherald §43 build/CI command (bherald/build_cmds.go) feeding the HRD-021 bherald binding
HRD-036	task	high	Claude	@milos85vasic	§11.4.10 cherald creds scan — gitleaks/trufflehog .credential.leak — Batch C: implemented as (cherald/cmd/cherald/checkops_cmds.go) feeding the HRD-019 cherald binding; hermetic -race green (routed to §11.4.10 cherald creds scan — gitleaks/trufflehog .secret value printed)
HRD-037	task	low	Claude	@milos85vasic	§11.4.12 cherald docs sync — regen Issues_Summary — Batch C: implemented as cherald cmd/cherald/docops_cmds.go) feeding the HRD-019 cherald binding; hermetic -race green
HRD-038	task	low	Claude	@milos85vasic	§11.4.18 cherald script-docs check — ass Batch C: implemented as cherald §43 verify/check command (cherald/checkops_cmds.go) feeding the HRD-019 cherald binding (routed to §11.4.60 — §11.4.62 has no cherald rule)
HRD-039	task	low	Claude	@milos85vasic	§11.4.19 / .23 cherald fixed align + cherald HTML colorizer — Batch C: implemented as cherald cmd/cherald/docops_cmds.go) feeding the HRD-019 cherald binding; hermetic -race green
HRD-040	task	high	Claude	@milos85vasic	§11.4.26 sherald constitution pull — wr .bundle.updated — Batch C: implemented as sherald/syops_cmds.go) feeding the HRD-020 sherald binding (detects+classifies+exits-nonzero, never performs the fix so the CLI runs without a JWT secret
HRD-041	task	middle	Claude	@milos85vasic	§11.4.27 bherald test-tier verify — 8-tie Batch C: implemented as bherald §43 build/CI command (bherald/build_cmds.go) feeding the HRD-021 bherald binding
HRD-042	task	low	Claude	@milos85vasic	§11.4.31 cherald submanifest verify — S Batch C: implemented as cherald §43 verify/check command (cherald/checkops_cmds.go) feeding the HRD-019 cherald binding
HRD-043	task	high	Claude	@milos85vasic	§11.4.36 pherald install-upstreams — ins Batch C: implemented as gitops command (§11.4.74 FindScript) feeding the HRD-023 binding; hermetic temp-repo tests -race green
HRD-044	task	middle	Claude	@milos85vasic	§11.4.37 pherald fetch-guard — pre-edit fetch Batch C: implemented as gitops command (§11.4.74 wrap of gitops) feeding the HRD-023 binding; hermetic temp-repo tests -race green
HRD-045	task	high	Claude	@milos85vasic	§11.4.40 rherald gate retest — pre-tag full Batch C: implemented as rherald §43 release command (rherald/cmd/rherald/cmd.go) feeding the HRD-022 rherald binding; reuses shared commons/§11.4.41 sherald force-push gate — merge
HRD-046	task	high	Claude	@milos85vasic	Batch C: implemented as sherald §43 command (sherald/cmd/sherald/cmd.go) feeding the HRD-020 sherald binding (detects+classifies+exits-nonzero, never performs the fix so the CLI runs without a JWT secret

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-047	task	middle	Claude	@milos85vasic	§11.4.45 / .56 <code>scherald status-digest</code> — per regen — Batch C straggler: implemented in <code>scherald</code> feeding the HRD-025 <code>scherald</code> binding (§11.4.45 status regenerates <code>Status_Summary</code>); hermetic -race green
HRD-048	task	low	Claude	@milos85vasic	§11.4.53 <code>cherald fixed-summary sync</code> — status Batch C: implemented as <code>cherald §43 docs-pipeline command docops_cmds.go</code>) feeding the HRD-019 <code>cherald</code> binding regenerate; ships the §107 lazy-verifier fix so the CLI runs green
HRD-049	task	middle	Claude	@milos85vasic	§11.4.55 <code>pherald reopen <HRD-NNN></code> — Issue Batch C: implemented as <code>gitops</code> command (the Wave runner emit feeds HRD-023 binding; hermetic temp-repo tests)
HRD-050	task	middle	Claude	@milos85vasic	§11.4.59 <code>cherald readme sync</code> — README command Batch C: implemented as <code>cherald §43 docs-pipeline command docops_cmds.go</code>) feeding the HRD-019 <code>cherald</code> binding regenerate; ships the §107 lazy-verifier fix so the CLI runs green
HRD-051	task	high	Claude	@milos85vasic	§11.4.60 <code>cherald composite-gate</code> — canonical COMPOSITE-SYNC — Batch C: implemented as <code>cherald (cherald/cmd/cherald/checkops_cmds.go)</code> detect-only; hermetic -race green
HRD-052	task	middle	Claude	@milos85vasic	§11.4.65 <code>cherald export</code> — bulk Markdown export implemented as <code>cherald §43 docs-pipeline command docops_cmds.go</code>) feeding the HRD-019 <code>cherald</code> binding regenerate; ships the §107 lazy-verifier fix so the CLI runs green
HRD-053	task	high	Claude	@milos85vasic	§11.4.71 <code>pherald pre-push</code> — fetch + investigation as <code>gitops</code> command (§11.4.74 wrap of <code>git</code> binary); --error repo tests -race green
HRD-054	task	middle	Claude	@milos85vasic	§11.4.73 <code>cherald spec-version check</code> — README implemented as <code>cherald §43 verify/check command (cherald/cmd/cherald/checkops_cmds.go)</code> feeding the HRD-019 <code>cherald</code> binding
HRD-055	task	middle	Claude	@milos85vasic	§11.4.74 <code>cherald catalogue-check <pr></code> — README runner over <code>vasic-digital + HelixDevelopment</code> — Batch C: check command (<code>cherald/cmd/cherald/checkops_cmds.go</code>) feeding the HRD-019 <code>cherald</code> binding; detect-only; hermetic -race green
HRD-056	task	high	Claude	@milos85vasic	§12.6 <code>scherald mem-budget watch</code> — daemon mode <code>.host.safety_breach</code> — Batch C: implemented as <code>cherald cmd/scherald/sysops_cmds.go</code>) feeding the HRD-019 <code>scherald</code> binding GATE (detects+classifies+exits-nonzero, never performs verifier fix so the CLI runs without a JWT secret)
HRD-085	task	middle	Claude	@milos85vasic	Implement single-task admin operations on <code>commons_infra.TaskRepository</code> : <code>GetByID</code> , <code>Update</code> , <code>Delete</code> . Required for Requeue operator tooling. Currently all three return <code>ErrUnscheduled</code> . BackgroundTask row by ID; full-row Update including decision per §107.
HRD-086	task	middle	Claude	@milos85vasic	Implement worker-side running-task state mutations on <code>commons_infra.TaskRepository</code> — <code>UpdateHeartbeat</code> , <code>SaveCheckpoint</code> . Required for Requeue operator tooling.

ID	Type	Criticality	Created-By	Assigned-To	Title
					reaper. Currently all four return <code>ErrUnsupported</code> guarded by valid-state-machine check; progress as (f updated_at = now() writeback; checkpoint as c task row. Implement admin / stats / audit reads on <code>commons_inf</code> <code>GetByStatus</code>, <code>GetPendingTasks</code>, <code>CountByS</code> <code>v1/queue/*</code> introspection endpoints + <code>Peek</code> delega <code>ErrUnsupported</code> (HRD-087). Scope: status-fil <code>Peek</code>; status-bucketed counts; per-task execution-histo <code>task_execution_history</code> table.
HRD-087	task	low	Claude	@milos85vasic	
HRD-088	task	middle	Claude	@milos85vasic	Implement queue-recovery reads on <code>commons_inf</code> <code>GetStaleTasks</code>, <code>GetByWorkerID</code>. Drives the s loop. Currently both return <code>ErrUnsupported</code> (HR against updated_at; per-worker assignment lookup
HRD-089	task	low	Claude	@milos85vasic	Implement resource-monitor I/O on <code>commons_inf</code> <code>SaveResourceSnapshot</code>, <code>GetResourceSnap</code> samples for capacity-planning + post-mortem. Current (HRD-089). Scope: append-only insert keyed by (t paginated read in reverse-chronological order. Schem table not yet in the §9.6 migration set — adding it is p
HRD-116	task	middle	Claude	@milos85vasic	Wave 7 T7 — qaherald <code>Slack MessengerClient</code> - <code>internal/messenger/{slack.go, builder</code> 11 <code>MessengerClient</code> methods (<code>Me/Send/SendPh</code> <code>WaitForReply/Download/Preflight/GetChatMember/C</code> <code>conversations.history+oldest=<ts> wat</code> <code>MessageID = dotted-float ts string</code>; channel-keyed b unknown→error). Token NEVER in errors — sanit <code>TestSlack_Send_ErrorDoesNotLeakToken</code> <code>SUPERSECRET-must-not-leak-7777</code>. 30 herm time pin var <code>_ MessengerClient = (*Slac</code> <code>CLEANUP: ships files.upload V1 (deprecated l</code> — functionally equivalent for the http test seam, swap <code>slack.go</code> header.
HRD-118	task	high	Claude	@milos85vasic	Wave 7 T9 — <code>e2e_bluff_hunt.sh</code> E124-E131 multi-ch resolution, E125 tgram self-filter post-Wave-7 (pure-r (interface satisfied + <code>auth.test + chat.postMessage</code> wir Slack (env-gated <code>HERALD_SLACK_BOT_TOKEN+HERALD_SLACK_</code> triple-guard to prevent silent "no tests to run" PASS-b E129 generalized <code>IsSelfEcho</code> (<code>Username+UserID+em</code> wiring, E131 qaherald messenger.<code>Build dispatch. sc_a</code>
HRD-119	task	high	Claude	@milos85vasic	Wave 7 T10 — paired §1.1 mutation gate <code>tests/te</code> PASS / 0 FAIL): M1 blank <code>IsSelfEcho</code> → <code>TestI</code> hazard caught) → restored → PASS; M2 drop slack c <code>TestSlackRegisteredViaInit</code> FAILs → rest append in <code>send.go</code> → <code>TestSlackSendReplyU</code> + quiescence assertion (no MUTATED W7 - residue in Reuses Wave 6 canonical <code>.git/MUTATION_IN_PR</code> flight dirty-tree-and-residue guard + byte-for-byte as ONLY (§107.y / no-concurrent-mutation operator mar

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-120	task	high	Claude	@milos85vasic	Wave 7 T11 — §11.4.85 multi-channel stress + chaos pherald/listen_stress_chaos_test.go (TestListen_MultiChannel_StressBurst (ONE runListen — pins no-loss/no-double + per-channel perChannelCountingReplier keyed on rcpt NOT cross-wire; throughput ~9-19k ev/s under -race; TestListen_MultiChannel_ChaosOneChan fires 1 event then errors; slack ticks 50 events at 2ms via conjunction: ≥5 slack dispatches landed BEFORE surfaces tagged channel="tgram-stub" + sub -count=3 (3 iterations × 2 new + 2 sibling HRD-121 found: fail-loud-tears-down-siblings (per-channel su doc-comment warns against silent change). Evidence multichannel_no_drop_under_burst=1 (s multichannel_concurrency_proven=1 + multichannel_one_channel_death_surfa Wave 7 T12 — docs/guides/MESSENGER_CHA sections + 3 siblings .html/.pdf/.docx): §1 architecture commons_messaging/channels.Channel inbound + re ASCII fan-in diagram), §2 HERALD_CHANNELS sele Telegram live setup (BotFather → token → chat-id), § Socket Mode + scopes + xoxb-/xapp- tokens; §10 TestSlack_Send_ErrorDoesNotLeakToken {HERALD_INBOX_DIR}/<channel>/<sha256 (cross-the-wire-then-cache contract), §7 URL scheme channel" implementer checklist + companion "what y come for free), §9 10-entry troubleshooting cookbook invalid_auth / wrong inbox / HERALD_CHANNELS deploy audit mirroring OPERATOR_CREDENTIALS V3 §11/§32.2/§43 + Wave 7 plan + adapter source pat REGEN_ALL=1 bash scripts/export_docs ATMOSphere integration WS-1 — commons_wor (LANDED + tested 2026-05-29) . New L1 module: S sqlite, no CGO) mirroring the workable-items sch (atm_id,current_location) + item_hist set); full CRUD repo (Create/GetByID/Update/Delete validation); per-property Diff(prev,curr) chang item.deleted/item.status.changed/item item.content.updated with exact old→new; F REAL ## §... [ATM-NNN] + **Status:**/*T real-SQLite tests -race -count=3 green. Keystor ATMOSphere integration WS-2 — commons_wat 2026-05-29) . New L1 module: fsnotify watcher (direc debounce-coalesce + SQLite-WAL polling fallback (V raise reliable fsnotify Write on the main .db); gracef -race green. Feeds R1/R2. ATMOSphere integration WS-3 — change→CloudEv per-property-diff message formatter (reuse the existin fan-out; add only the workable-event producer + form
HRD-121	task	low	Claude	@milos85vasic	
HRD-148	feature	high	Claude	@milos85vasic	
HRD-149	feature	high	Claude	@milos85vasic	
HRD-151	feature	high	Claude	@milos85vasic	
HRD-152	feature	high	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
					ATMOSphere integration WS-4 — inbound action request investigation.start + ItemMutator (write orchestrator (act-with-confirmation per operator 202
HRD-153	feature	middle	Claude	@milos85vasic	ATMOSphere integration WS-2 — watcher daemon e watch→diff→notify loop; promote to a wherald fla
HRD-154	task	middle	Claude	@milos85vasic	ATMOSphere integration WS-3 — enforce preference QuietHours types exist but the resolver ignores the Dead-letter handling on commons_infra.pgxDas (was the last ErrUnsupported Batch-D stub). Mig (.up/.down, FK→background_tasks ON DELETE CA Tx-atomic move: INSERT a full JSONB task snapshot mark background_tasks.status='dead_le preserve the events/snapshots FK children); JSONB p SQLSTATE-22P02 lesson. New 13th OPERATIONAL ClassQueueDeadLetter ("queue.dead_letter") + DeadLetter() emit method (governance set §42.2 12→13); wired nil-tolerantly into the repo via newPg (boot.go keeps the nil-emitter — the Foundation plan emitting there would be an emit-into-the-void §107 b HRD-147 follow-up). Best-effort emit AFTER the du swallowed. Four-layer closure (CONST-048) : 3 her (TestRepoMoveToDeadLetter_RoundTripA terminal-state + dlq snapshot + real-bus .queue.de chaos (50 concurrent moves race-clean, emit-failure-a §1.1 mutation gate (tests/test_hrd090_muta -race green.
HRD-090	task	middle	Claude	@milos85vasic	Tgram-completeness Wave B — token-redaction sym channels/tgram/errors.go + send.go wraps token) string strips the bot token from every Se can NEVER appear in observable output — 6 error-re withRetry429 paths in both Send + SendReply). TestTgram_Send_ErrorDoesNotLeakToken not-leak-9999, drives an httptest 401 path, assert returned err.Error() (mirrors slack's TestSlac Unit-level TestTgram_SanitizeTgramError captured in the source: %w error-wrap replaced with % sanitizeTgramError(err.Error()), token operates on the string form — the error chain is sacrific Composes with HRD-134 (the 429 retry's log line + f logging never leaks the token).
HRD-133	task	high	Claude	@milos85vasic	Tgram-completeness Wave B — Bot API rate-limit 4 (commons_messaging/channels/tgram/se errors.go::extractRetryAfter). withRe telebot bot.Send call sites (Send text body + SendR out). On 429 + retry_after=N → sleep N seco attempts total, clamp per-retry wait to 60s (defense-i retry_after extracted via errors.As(err, &telebot.FloodError{}).RetryAfter(tele Logged retry line goes through sanitizeTgramEr (composes with HRD-133). Injectable sleeper field
HRD-134	task	high	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-135	task	middle	Claude	@milos85vasic	+ fake-clock both supported via SetSleeperForT (HonorsRetryAfter / GivesUpAfter3Attempts / Respe unit test (ExtractRetryAfter_Unit) — 5 total, all - rac Tgram-completeness Wave A — edited-message + bo ignore-and-log handlers (commons_messaging/c bot.Handle(telebot.OnEdited, ...) builds does + Raw["edited"]=true; bot.Handle(t botKickedFromUpdate detects status transitions specifically (Alice-left + promotion-to-Admin false-p log.Printf "tgram: bot kicked from c ErrBotKicked"; serviceHandler registered a (UsersJoined / UserLeft / NewGroupTitle / etc.) emits tgram: ignored service message kind= ErrBotKicked = errors.New("tgram: bo (callable via errors.Is). The OnMyChatMember poller keeps running for OTHER chats. 17/17 PASS - subscribe_lifecycle_test.go + 14 existing Tgram-completeness Wave A — Bot API webhook s (commons_messaging/channels/tgram/we http.Handler validates X-Telegram-Bot-API-Subtle.ConstantTimeCompare (timing-attack time (NewWebhookHandler("", ...) errors loud – empty body on header mismatch / missing header (no 400 on malformed JSON body; 405 on wrong method InboundHandler error. Forwards a decoded tele.Up shape OnText/OnEdited produce — unified down pherald listen --webhook + the setWebhook the public-endpoint TLS listener are deferred to V1.x, tested so the future flip is a one-flag affair. 7/7 hermet ValidSecret_Dispatches, InvalidSecret_Returns401_N GET_Returns405, MalformedJSON_Returns400, Em ConstantTimeCompare. Tgram-completeness Wave C — §11.4.85 stress + cha channels/tgram/stress_chaos_test.go) TestTgram_Stress_MultiRecipientFanOu Adapter.SendReply via NewAdapterWithBa iterations = 400 total calls against 20 UNIQUE chat_i asserts no-loss (every chat_id received exactly 20 hits confusion (uniform per-chat distribution, no cross-wir (observed 5215-6422 ev/s, p99=9.73-15.20ms). TestTgram_Chaos_GetUpdatesPollerResi with-reason to a real httptest-driven fault-injector PAS fix: threads a.baseURL into telebot.Setting ensureBot pattern at tgram.go:60-67; produc " "). 8-phase fault matrix (3× 500 + 2× 1.5s hangs ho connection-close + 2× success), bot-username-aware from @someuser, not chaostestbot). Determ §11.4.50 — all 3 iterations IDENTICAL: recovery fault_modes(500=12 hang=8 close=3 ok deadline exceeded goroutines 3-4 (le tgram suite 26/26 PASS, 0 SKIP post-fix (was 24/24
HRD-136	task	low	Claude	@milos85vasic	
HRD-137	task	high	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-138	task	low	Claude	@milos85vasic	captured-evidence per-iteration table; P2 blast-radius only when unused (production unaffected); P3 cross-f ensureBot pattern, no novel state; P4 deep-research under fault (poller logs + continues, no internal retry) atomics, ctx-aware subscribe return, no goroutine leak from REAL Subscribe poller, not synthetic. Tgram-completeness Wave A — docs/guides/TE dive guide (810 lines, 11 §-sections, 58 subsections, 3 overview (inbound getUpdates + outbound Send walkthrough (/newbot → token → /setprivacy HERALD_TGRAM_CHAT_ID (3 methods: getUpdate pre-deploy smoke-test commands; §5 attachment size 50MB document Bot-API-cap workaround = local Bo path; §6 chat-type matrix (private/group/supergroup/c per type); §7 reply threading via reply_to_messa (Wave 6.5 mutation gate M3); §8 self-filter contract (loop hazard if skipped — Wave 6 T12 M1); §9 12-ent (401/400/429/413/403/echo-loop/long-poll-stuck/409 §10 6-subsection pre-deploy operator audit (tick-box OPERATOR_CREDENTIALS.md style); §11 referen HRDs + source paths). Cross-linked from existing do TELEGRAM.md (HRD-011 setup, preserved untouched Wave 8 Track B — qaherald/internal/mtpro wiring (gotd/td v0.144.0 vendored as submodules/ Client interface (Connect / SendMessage / Wait gotd/td's telegram.Client with session-storage: mtpProto.session (mode 0600, encrypted MTPro login/whoami/logout Cobra subcommands dri
HRD-139	task	high	Claude	@milos85vasic	phone-from-env, 2FA password from env, OOB-code HERALD_MTPROTO_ALLOW_NON_TTY=1 env ove piped flow for §11.4.98-compliant headless login). Co contribution = one-time paste of 5-digit Telegram OO fundamentally requires this; session persists thereafter verified leak-free across all evidence (token-shape reg runtime artifact removed; .gitignore hardened). Wave 8 Track B Test 1 — TestMTPProto_Subscr (qaherald/internal/lifecycle/mtproto integration_mtpProto). §11.4.98 replacement f TestSubscribe_LiveBotAPI Bot-API-only pa (a bot can never send-to-itself, so the legacy test requ drives the closed loop end-to-end via MTPProto user-a stimulus) → poll bot.getUpdates for delivery confirm within timeout. Honest-SKIP per §11.4.3 when MTPro (never falls back to manual-dep path). Conductor-veri §11.4.98-pure interpretation (chain runs without huma
HRD-140	task	high	Claude	@milos85vasic	Wave 8 Track B Test 2 — TestMTPProto_Wave6_ internal/lifecycle/mtproto_wave6_loc integration_mtpProto). §11.4.98 replacement f test_wave6_live_loop.sh (which required m listen as a child process with cmd.Dir = repo docs/Issues.md relative to its CWD), pre-acks p
HRD-141	task	high	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-142	task	high	Claude	@milos85vasic	consumePendingUpdates(t, botToken) he getUpdates(offset=max+1) to ACK stale cha preventing TLS-connection-reset storms from prior ru based §11.4.98 autonomy assertion polls pherald's - - tgram.message(in) + cc.dispatch + cc.rep text string rather than message_id (MTProto's int64 m API's chat-local message_id — §11.4.98 contract is "c action", not "Claude generates perfect content"). PAS Wave 8 Track B Test 3 — TestMTProto_Wave65 internal/lifecycle/mtproto_wave65_li integration_mtpROTO). §11.4.98 replacement f interactive mode (which required operator typing per- Wave 6.5 fast-path scenarios — Help / Status / Contin subtest spawns pherald + sends MTProto stimulus + a tgram.message in + `cc.reply commons_constitution Go package: Evaluator constitution_state/constitution_bind mode-ladder runtime config + constitution_audit wr Evaluator framework, emit helpers, bundle-hash, mod state.Postgres, ladder.Memory/ladder.M 000006/000007/000008 were all coded in r1. v1.0.0 E bluff: migration 000006 defined constitution_a Runner.Run set RunOutcome.Audited=true AuditStore interface (audit.go) + state.Mer state.PostgresAudit (RLS-guarded INSERT- append-only is enforced by the migration's no-update now writes a durable audit row for every CHANGED recording old/new decision, old/new digest, bundle ha ModeEnforce — the EXACT emitted event ID (new . PolicyViolationID/PolicyClearedID; emi NewRunner gained a required AuditStore arg (nil = ha RED (compile-fail before backends) → GREEN, - r a DB-level SELECT shows enforce rows carry emitted_ Constitution-bundle hash captureer — computes SHA evaluation time; persists on every emitted event for re Capture/CaptureBytes/Captureer) was code emitted-event metadata (bundle_hash hex). v1.0.0 32-byte bundle_hash is now stored on every con constitution_audit row (verified by the DB-le encode(bundle_hash, 'hex') in the evidence audit row), closing the §42.1.3 replay-correlation requ Mode-ladder runtime config (constitution_bin flip allow/warn/enforce per binding per tenant without ladder.Memory/ladder.Postgres (reading c time) were coded in r1. v1.0.0 Batch A added the adm modes — GET /v1/compliance/modes (list b compliance/modes/:rule_id (one binding's e compliance/modes/:rule_id (flip allow/warn mutated_by). JWT-gated via the existing common mounted in cherald serve (a single shared PG pool bluff: 401 no-auth / 401 bad-tenant / 400 bad-mode (l
HRD-018	task	high	Claude	@milos85vasic	000006/000007/000008 were all coded in r1. v1.0.0 E bluff: migration 000006 defined constitution_a Runner.Run set RunOutcome.Audited=true AuditStore interface (audit.go) + state.Mer state.PostgresAudit (RLS-guarded INSERT- append-only is enforced by the migration's no-update now writes a durable audit row for every CHANGED recording old/new decision, old/new digest, bundle ha ModeEnforce — the EXACT emitted event ID (new . PolicyViolationID/PolicyClearedID; emi NewRunner gained a required AuditStore arg (nil = ha RED (compile-fail before backends) → GREEN, - r a DB-level SELECT shows enforce rows carry emitted_ Constitution-bundle hash captureer — computes SHA evaluation time; persists on every emitted event for re Capture/CaptureBytes/Captureer) was code emitted-event metadata (bundle_hash hex). v1.0.0 32-byte bundle_hash is now stored on every con constitution_audit row (verified by the DB-le encode(bundle_hash, 'hex') in the evidence audit row), closing the §42.1.3 replay-correlation requ Mode-ladder runtime config (constitution_bin flip allow/warn/enforce per binding per tenant without ladder.Memory/ladder.Postgres (reading c time) were coded in r1. v1.0.0 Batch A added the adm modes — GET /v1/compliance/modes (list b compliance/modes/:rule_id (one binding's e compliance/modes/:rule_id (flip allow/warn mutated_by). JWT-gated via the existing common mounted in cherald serve (a single shared PG pool bluff: 401 no-auth / 401 bad-tenant / 400 bad-mode (l
HRD-026	task	middle	Claude	@milos85vasic	000006/000007/000008 were all coded in r1. v1.0.0 E bluff: migration 000006 defined constitution_a Runner.Run set RunOutcome.Audited=true AuditStore interface (audit.go) + state.Mer state.PostgresAudit (RLS-guarded INSERT- append-only is enforced by the migration's no-update now writes a durable audit row for every CHANGED recording old/new decision, old/new digest, bundle ha ModeEnforce — the EXACT emitted event ID (new . PolicyViolationID/PolicyClearedID; emi NewRunner gained a required AuditStore arg (nil = ha RED (compile-fail before backends) → GREEN, - r a DB-level SELECT shows enforce rows carry emitted_ Constitution-bundle hash captureer — computes SHA evaluation time; persists on every emitted event for re Capture/CaptureBytes/Captureer) was code emitted-event metadata (bundle_hash hex). v1.0.0 32-byte bundle_hash is now stored on every con constitution_audit row (verified by the DB-le encode(bundle_hash, 'hex') in the evidence audit row), closing the §42.1.3 replay-correlation requ Mode-ladder runtime config (constitution_bin flip allow/warn/enforce per binding per tenant without ladder.Memory/ladder.Postgres (reading c time) were coded in r1. v1.0.0 Batch A added the adm modes — GET /v1/compliance/modes (list b compliance/modes/:rule_id (one binding's e compliance/modes/:rule_id (flip allow/warn mutated_by). JWT-gated via the existing common mounted in cherald serve (a single shared PG pool bluff: 401 no-auth / 401 bad-tenant / 400 bad-mode (l
HRD-027	task	middle	Claude	@milos85vasic	000006/000007/000008 were all coded in r1. v1.0.0 E bluff: migration 000006 defined constitution_a Runner.Run set RunOutcome.Audited=true AuditStore interface (audit.go) + state.Mer state.PostgresAudit (RLS-guarded INSERT- append-only is enforced by the migration's no-update now writes a durable audit row for every CHANGED recording old/new decision, old/new digest, bundle ha ModeEnforce — the EXACT emitted event ID (new . PolicyViolationID/PolicyClearedID; emi NewRunner gained a required AuditStore arg (nil = ha RED (compile-fail before backends) → GREEN, - r a DB-level SELECT shows enforce rows carry emitted_ Constitution-bundle hash captureer — computes SHA evaluation time; persists on every emitted event for re Capture/CaptureBytes/Captureer) was code emitted-event metadata (bundle_hash hex). v1.0.0 32-byte bundle_hash is now stored on every con constitution_audit row (verified by the DB-le encode(bundle_hash, 'hex') in the evidence audit row), closing the §42.1.3 replay-correlation requ Mode-ladder runtime config (constitution_bin flip allow/warn/enforce per binding per tenant without ladder.Memory/ladder.Postgres (reading c time) were coded in r1. v1.0.0 Batch A added the adm modes — GET /v1/compliance/modes (list b compliance/modes/:rule_id (one binding's e compliance/modes/:rule_id (flip allow/warn mutated_by). JWT-gated via the existing common mounted in cherald serve (a single shared PG pool bluff: 401 no-auth / 401 bad-tenant / 400 bad-mode (l

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-132	bug	high	Claude	@milos85vasic	proof: a PUT flip to warn is reflected by a subsequent evaluation hot path — runtime config, no redeploy. §11.4.85/§32.1 Runner idempotency-window FIX — duplicate-dispatches a notification (FINDING from H idempotency . go : 64 - 72 treated a Redis-SETNX §32.1 "Redis-lies-PG-truths" design) while the even written at Stage 7 (OutcomeRecorder . Process arriving in the Stage-2→Stage-7 window ALL dispatch archival exactly-once via PG UNIQUE + ON CONFL only bounded = duplicate-alert delivery under load). BEFORE dispatch — INSERT events_process moved to Stage 2 (the PG row, serialized by PRIMAR now the AUTHORITATIVE exactly-once dispatch ga dispatch), preserving the nil-Redis PG-only degrade. . CachedRcpt . WasReplay data race (mutated a po HRD-125 stress test was upgraded to assert sends== — the stronger assertion HRD-125 deliberately could on-discovery). §11.4.92 multi-pass: Pass-1 independent storage green; Pass-5 sends==1 is code-true (RED retired (4f45f26) — Stage-7 Insert now redundant, claim. §11.4.85 / §1.1 paired mutation gate for the GAP-3 st test_stress_chaos_mutation_meta.sh (C hermetic stress/chaos detector is genuinely LOAD-BE test_wave6.5_mutation_meta.sh idiom: .g dirty-tree + pre-existing-residue refusal pre-flights, r marker landed → run detector EXPECT-FAIL → git assert_restored vs HEAD → re-run EXPECT- scan asserting no MUTATED SC-M* markers leaked against a hermetic detector: SC-M1 drop ctx from cla exec . CommandContext→exec . Command → t sleep → watchdog FAIL; SC-M2 swallow the claude_ truncated-reply test returns nil → FAIL; SC-M3 make default: panic instead of return ...err → de events mapErrorToStatus event_parser: 40 FAIL; SC-M5 swallow the commons_storage apply ENOSPC reports success → silent-swallow guard FA FOREGROUND (§107.y + the 2026-05-27 concurrer result: 6 PASS / 0 FAIL (5 mutations load-bearing). §11.4.85 stress+chaos suite wired into the canonical a e2e_bluff_hunt.sh as new invariants E81-E88 ONLY append after E80 (E1-E80 logic untouched). E stress/chaos test via the existing check helper AND docs/qa/<run-id>/stress_chaos/ as its §1 through a new sc_anchor helper that greps a SPEC artefact FAILs as a §11.4 PASS-bluff; absent evidence runner exactly-once-archive + bounded dispatch (HRD + duplicate-key + auth-storm (HRD-123, anchor eve all_malformed_rejected_no_5xx); E83 /v /v1/safety_state concurrent-mutation (HRD-1 malformed-Raw panic-free + extract-degrade (HRD-1
HRD-130	task	high	Claude	@milos85vasic	§11.4.85 / §1.1 paired mutation gate for the GAP-3 st test_stress_chaos_mutation_meta.sh (C hermetic stress/chaos detector is genuinely LOAD-BE test_wave6.5_mutation_meta.sh idiom: .g dirty-tree + pre-existing-residue refusal pre-flights, r marker landed → run detector EXPECT-FAIL → git assert_restored vs HEAD → re-run EXPECT- scan asserting no MUTATED SC-M* markers leaked against a hermetic detector: SC-M1 drop ctx from cla exec . CommandContext→exec . Command → t sleep → watchdog FAIL; SC-M2 swallow the claude_ truncated-reply test returns nil → FAIL; SC-M3 make default: panic instead of return ...err → de events mapErrorToStatus event_parser: 40 FAIL; SC-M5 swallow the commons_storage apply ENOSPC reports success → silent-swallow guard FA FOREGROUND (§107.y + the 2026-05-27 concurrer result: 6 PASS / 0 FAIL (5 mutations load-bearing). §11.4.85 stress+chaos suite wired into the canonical a e2e_bluff_hunt.sh as new invariants E81-E88 ONLY append after E80 (E1-E80 logic untouched). E stress/chaos test via the existing check helper AND docs/qa/<run-id>/stress_chaos/ as its §1 through a new sc_anchor helper that greps a SPEC artefact FAILs as a §11.4 PASS-bluff; absent evidence runner exactly-once-archive + bounded dispatch (HRD + duplicate-key + auth-storm (HRD-123, anchor eve all_malformed_rejected_no_5xx); E83 /v /v1/safety_state concurrent-mutation (HRD-1 malformed-Raw panic-free + extract-degrade (HRD-1
HRD-129	task	high	Claude	@milos85vasic	§11.4.85 stress+chaos suite wired into the canonical a e2e_bluff_hunt.sh as new invariants E81-E88 ONLY append after E80 (E1-E80 logic untouched). E stress/chaos test via the existing check helper AND docs/qa/<run-id>/stress_chaos/ as its §1 through a new sc_anchor helper that greps a SPEC artefact FAILs as a §11.4 PASS-bluff; absent evidence runner exactly-once-archive + bounded dispatch (HRD + duplicate-key + auth-storm (HRD-123, anchor eve all_malformed_rejected_no_5xx); E83 /v /v1/safety_state concurrent-mutation (HRD-1 malformed-Raw panic-free + extract-degrade (HRD-1

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-128	task	high	Claude	@milos85vasic	timeout-cancel + truncated-reply (HRD-127); E87 dis E88 §12.6 host-mem headroom (HRD-128). All eight fill / container-OOM variants are SKIP-with-reason in (HERALD_STRESS_LIVE_*=1 gated). Verified bas deterministic; header bumped E1..E80→E1..E88. Full reports 78 PASS / 0 FAIL (was 60; +18). §11.4.85 container-orchestrated / resource-exhaustion §6 T7 + §7 host-safety) — commons_storage/re (hermetic core) + tests/test_resource_stre HERMETIC PASS (×2 deterministic): (1) disk-full er database.Database/Tx injects syscall.ENO REAL RunMigrations → applyMigration v error NOT swallowed, error tagged commons_stor errors.Is(err, syscall.ENOSPC) true, 0 m mem headroom — HostMemHeadroom() pre/post used_fraction_delta ≈0 (host needle did not r (deterministic SKIP without env): real bounded-scrato HERALD_STRESS_LIVE_DISK=1. LIVE containe safety-gated): container OOM-confinement + connect PG, gated HERALD_STRESS_LIVE_OOM=1 + a §1 REFUSES to add pressure when host used-fraction ≥ SKIP). §12/§12.6 honoured: NO host-OOM, NO real- test -race -count=3 green (PASS×3/PASS×3 §11.4.85 claudcode dispatch stress+chaos tests (GA commons_messaging/dispatch/claudcode dispatch_stress_chaos_test.go (in-packa bootstrapSession/parseReply) + 5 commit claudcode *.sh. Per §11.4.27 only the EXTERNAL New(binaryPath,...) seam; NO production source invoked. STRESS: (1) N=24×25=600 concurrent Dis every reply really parsed, every call resumed the SAM p50=62.9ms/p95=96.4ms; (2) N=16 concurrent COL one anchor UUID persists, -race clean. CHAOS: (a -KILL \$\$ → tagged error, no hang (watchdog), par 30s-sleep shim vs 800ms ctx → cancellation fires, Di <<<HERALD-REPLY>>> → explicit decode rep FINDING-1: cold-start concurrent bootstrap is last-w not bootstrap_count==1 bluff). FINDING-2: ti claudcode being a single process (hardening direction = owner). go test -race -count=3 deterministi §11.4.85 pherald listen inbound-path stress+ch pherald/internal/inbound/stress_chao unexported extractReplyToMessageID) + phe listen_stress_chaos_test.go (drives the R the channel Subscriber + CCCodeDispatcher bo routing switch + runListen fan-in + clean-shutdown N=16×50=800 concurrent Dispatcher.Handle - (800/800), 0 goroutine leak, p50=0.41ms ~25k dispat runListen — nothing dropped, clean shutdown on Raw payloads (nil map, missing/nil/string/bool/slice/r extractReplyToMessageID degrades to (0,err)
HRD-127	task	high	Claude	@milos85vasic	every reply really parsed, every call resumed the SAM p50=62.9ms/p95=96.4ms; (2) N=16 concurrent COL one anchor UUID persists, -race clean. CHAOS: (a -KILL \$\$ → tagged error, no hang (watchdog), par 30s-sleep shim vs 800ms ctx → cancellation fires, Di <<<HERALD-REPLY>>> → explicit decode rep FINDING-1: cold-start concurrent bootstrap is last-w not bootstrap_count==1 bluff). FINDING-2: ti claudcode being a single process (hardening direction = owner). go test -race -count=3 deterministi §11.4.85 pherald listen inbound-path stress+ch pherald/internal/inbound/stress_chao unexported extractReplyToMessageID) + phe listen_stress_chaos_test.go (drives the R the channel Subscriber + CCCodeDispatcher bo routing switch + runListen fan-in + clean-shutdown N=16×50=800 concurrent Dispatcher.Handle - (800/800), 0 goroutine leak, p50=0.41ms ~25k dispat runListen — nothing dropped, clean shutdown on Raw payloads (nil map, missing/nil/string/bool/slice/r extractReplyToMessageID degrades to (0,err)
HRD-126	task	high	Claude	@milos85vasic	routing switch + runListen fan-in + clean-shutdown N=16×50=800 concurrent Dispatcher.Handle - (800/800), 0 goroutine leak, p50=0.41ms ~25k dispat runListen — nothing dropped, clean shutdown on Raw payloads (nil map, missing/nil/string/bool/slice/r extractReplyToMessageID degrades to (0,err)

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-125	task	high	Claude	@milos85vasic	64-dispatch corrupt-Raw flood panic-free (recover-gu subprocess fault (killed/truncated/marker-less/empty/ inbound : error, no reply leak, no hang; (c) once-on same issue . open collapse to exactly-ONE durable deterministically green ×3 on both packages. NO pro §11.4.85 Runner 7-stage pipeline stress+chaos tests (C pherald/internal/runner/stress_chaos runner . Run (only the external boundary — PG ev SETNX seam — faked per §11.4.27; orchestrator + 7 goroutines × 40 iters concurrent same-key replay + fr duplicate flood @ 50 parallel under live atomic Redis fallback degrade; (b) hermetic PG-deadlock (SQLSTA events_processed Insert. SURFACED HRD-132: disp under concurrent replay (events_processed archived a of a 1000× flood); tests asserted the honest code-true dispatch) pre-fix, then upgraded to sends==1 once test -race -count=1 green. §11.4.85 Gin /v1/compliance (cherald) + /v1/s stress+chaos tests (GAP-3 plan §1 row 2 / §6 T3) — compliance_stress_chaos_test.go + she safety_stress_chaos_test.go, each driving process httptest server dialed by net/http.Cli (cli.TOONMiddleware → auth → handler). Only NO production source edited, NO new dep. STRESS -race clean — 0 errors, 0 5xx, all 200 (compliance
HRD-124	task	high	Claude	@milos85vasic	Content-negotiation correctness under concurrency — application/toon vs application/json — Accept header (0 codec-bleed), every toon body real PG-drop (errStore) → 2000/2000 fail-loud 500 ea fabricated 2xx (a swallowed-error 200 {results: [violations" — the §107 mode this gate forbids); safety code-true analogue (concurrent state-mutation under instead; (b) auth storm — 1000 random tokens through commons_auth.GinMiddleware+HMAC(HS2 test -race -count=3 green ×3. §11.4.85 Gin /v1/events stress+chaos tests (GAP internal/http/events_stress_chaos_te events handler (EventsHandler → runner.R httptest server dialed by net/http.Client th (cli.TOONMiddleware + auth gate). Only the ex runner.NewFakeRunner) faked per §11.4.27. ST POSTs, -race clean — 0 errors, 0 5xx, all 202; p50-
HRD-123	task	high	Claude	@milos85vasic	duplicate-key-under-load (1200 POSTs, per-worker k input-corruption (8 MiB random, truncated JSON, no empty) × 5 → every body a tagged event_parser 1000 random tokens through the REAL commons_a → 1000×401, 0 bypass; (a) live PG-drop → SKIP-wi FINDING (→ HRD-132 at HTTP layer): a SHARED triggers the REAL runner.go:132 CachedRcpt HRD-132). E82 anchor re-captured as all_mal for transport-rejection-of-8-MiB-body is valid).

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-122	task	middle	Claude	@milos85vasic	§11.4.85 stress+chaos shared scaffold — Go-native c package (GAP-3 plan §2 / §6 T1). Provides: a bounde workers $\times$ M iterations of a closure via stdlib sync.l rank percentile math (Percentiles $\rightarrow$ {p50, p95 latency.json + latency_histogram.csv, <run-id>/stress_chaos/<surface>/; and (HostMemHeadroom — vm_stat+sysctl hw. on linux) for the §12.6 60%-ceiling proof (degrades to failure). Self-tested: 8 unit tests (percentile correctness creation, bounded-goroutine proof, host-mem best-eff test -race -count=1. Lowest sensible layer p importable by every flavor). Wave 7 T5 — multi-channel pherald listen (H goroutines $\rightarrow$ 1 dispatcher). pherald/internal/ Wave-6 TgramReplier interface (Telegram-native signature) $\rightarrow$ generic inbound.Replier with Ser commons.Recipient, body string, repl []commons.Attachment) (string, error satisfy it. Config.TgramReply $\rightarrow$ Config.Rep Dispatcher.reply field + the Handle "reply" b migrated to build a commons.Recipient{Chanr strconv.Itoa(replyToID) (" " when 0). phe listenConfig.Subscriber (singular) $\rightarrow$ Sub: InboundHandler) error; listenConfig.R inbound.Replier; new loadEnabledChanne (comma-split, trim, dedupe; unset/empty $\rightarrow$ ["tgra preserved); new perChannelConfig(name) rea (HERALD_TGRAM_BOT_TOKEN/HERALD_TGRAM HERALD_SLACK_BOT_TOKEN/_APP_TOKEN/_CH loud on missing required creds); loadListenConf via the channels.New(name, cfg) registry (T2 Subscribers[name]=ch.Subscribe + a cha channels.Channel.SendReplyGeneric $\rightarrow$ two intentionally-differently-named generic methods channelRouter that dispatches each reply to the a loud no replier for channel %q on unknow fans in one goroutine per subscriber (manual sync.V new dep — errgroup-equivalent semantics) all feeding subscriber error cancels siblings + surfaces (T11 cha listen.go for its init() registry registration. journa to wrap inbound.Replier (records channel+c strings; JSONL kind kept tgram.send_reply for resolution (Wave 7 plan Step 4): inbound.Replie name (the inbound package's own, independent of channels.Channel.SendReplyGeneric); pr channelReplier shim so the journal decorator + evidence: new TestRunListenMultiChannelF publish 1 event) asserts BOTH messages dispatched A (fake)"] $\geq$ 2) — NOT "both goroutines started the fan-in loop $\rightarrow$ seen == map[] $\rightarrow$ FAIL). Exis TestListenWiresHandlerAndExitsOnCanc
HRD-114	task	high	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
					TestRunListenRejectsBadConfig migrated PASS. recordingReplier/stubReplierJournal_test) migrated to the generic signature; numer decode.go build ./pherald/... + go test pherald/... ./commons_messaging/... & clean. Wave 7 T4 — generalize the bot self-filter via BotSe commons_messaging/channels/selffilter (RawSenderIsBot/RawSenderIdentityKind/StampSender(raw map[string]any, isBot value string) (records the sender's native identity IsSelfEcho(ev commons.InboundEvent, §32.9 anti-echo-loop guarantee made channel-agnostic IdentityKind: username for Telegram, user deliberately narrow: a DIFFERENT bot is KEPT (mu — the §107 anchor that the filter is not over-broad); a never echoes (conservative KEEP → surfaces as dupl Subscribe refusing to boot on empty self). commons subscribe.go migrated: captures self := cha channels.IdentityUsername, Value: bo (keeping the existing empty-username boot-refusal ec handlers (OnText/OnPhoto/OnDocument/OnVoic stampAndIsSelfEcho(ev, msg, self) help HRD-113 task high Claude @milos85vasic IsBot+@username into ev.Raw and delegates to the four Wave-6 shouldDropBotSelf(msg, se native shouldDropBotSelf func + its TestSub SelfFilterForTest (export_test.go) are PRESE paired-mutation gate (tests/test_wave6_muta perl -i -0pe regex on shouldDropBotSelf M1 load-bearing (verified: the M1 regex still matches migration). The live path and the gate now express the the generalized IsSelfEcho, the gate on the tgram. TestIsSelfEchoUsername proves all three user different-bot KEPT, human KEPT; TestIsSelfEc (matching bot id DROPPED, different id KEPT); TestIsSelfEchoEmptySelfNeverEchoes pr builds events via the production StampSender (DR key contract); TestSubscribeBotSelfFilter test -race -count=1 ./commons_messag go vet clean. Live runtime evidence (real Telegram the closed loop) lands via Wave 7 T9 e2e invariant. Wave 7 T3 — per-channel inbox subdirs ~/.herald <sha256>.<ext>. New file commons_messagi channel-agnostic InboxDir(channel string) ~/.herald/inbox/<channel>/, MkdirAll 070 WriteContentAddressed(channel, mime (path, sha256Hex string, err error) (<sha256>.<ext> via io.MultiWriter(tmp, full payload — then atomic temp+rename; idempoten the .part temp is dropped and the existing path retu MimeToExt(mime string) (the Wave-6 tgram-p
HRD-112	task	middle	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-111	task	high	Claude	@milos85vasic	VERBATIM to package level so every adapter shares channels/tgram/attachments.go Download Telegram-specific bot.File(&telebot.File{hash-rename to channels.WriteContentAddressed(string mime, rc) — so tgram attachments land under ~/channel subdir, was the flat ~/ .herald/inbox/ inbox + the crypto/sha256/encoding/hex/io/os/p from attachments.go (the helper owns them now (*Adapter).DownloadAttachment(T1) dele forms route through the shared helper. §107 evidence: InboxDir("tgram") ends in .../inbox/tgr InboxDir("slack") (no flat-inbox regression); TestWriteContentAddressedHashesAndIs classes on real on-disk state — (a) path shape under i re-read on-disk bytes byte-equal the payload (sha in p content returns same (path, sum) and leaves zero the existing Wave-6 TestDownloadAttachment tgram/ path segment) still PASSES end-to-end again routing change is behaviour-preserving. go test - commons_messaging/... ./pherald/... assumption regressions); go vet clean. Live runtime landing under inbox/tgram/) lands via Wave 7 T9 Wave 7 T2 — channel registry (name→constructor) + commons_messaging/channels/registry. Constructor)/New(name, Config) (Chan the ErrUnknownChannel sentinel, the channel-ag AppToken/Target/BaseURL/Extra), and the Co (Channel, error) type — a sync.RWMutex- Register panics on duplicate (a typo in two adapte §107 bluff class this framework forbids; mirrors the q New wraps ErrUnknownChannel (fmt.Errorf callers (pherald listen) MUST surface it; a sile commons_messaging/channels/tgram/tgr channels.Register(string(common.Ch constructor builds NewAdapterWithBaseURL(c cfg.BaseURL) when cfg.BaseURL != "" (ht NewWithCreds(cfg.Token, cfg.Target) - adapter. §107 evidence: TestRegistryResolves actually constructs + returns a working Channel (c TestRegistryUnknownChannelErrors prov ErrUnknownChannel) for unknown names; Tes the duplicate-Register panic; TestTgramRegis tgram") proves the init() actually registered tgr failing before the init() landed: Names()=[dup after). The shared fakeChannel test stub uses Sen interface method name, NOT SendReply). go tes commons_messaging/... green (tgram regressi go vet ./commons_messaging/... clean. L by name + round-trip) lands via Wave 7 T9 e2e invari
HRD-110	task	high	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
					Wave 7 T1 — extract commons_messaging/channels. New package commons_messaging/channels. commons.Channel — Name/Capabilities/Send/Su inbound-runtime methods Telegram implicitly defined BotSelfIdentity returning SelfIdentity{K the SelfIdentity value type, and the Identity IdentityUserID/IdentityAddress). *tgram (getMe via ensureBot; empty-username → §107 echo (string→int64/int adapter over the native Wave-6 Ser DownloadAttachment (routes the package-level _channels.Channel = (*tgram.Adapter from plan Step 4 text resolved + documented in char method is named SendReplyGeneric (not SendR touching its native, §107-mutation-gate-anchored int6 generic signature is T5's scope) — keeping T1 a pure §107 evidence: var _channels.Channel = assertion in channel_test.go (a renamed method TestTgramSatisfiesChannel + TestSelfI -race ./commons_messaging/... green (tgm all 16 workspace modules build; go vet ./commo evidence (real getMe self-identity + reply round-trip) Wave 6.5 ticket-lifecycle layer — §32.6 deterministic Implementation:/Investigation:/Query: Continue:/Done:/Resolve:/Reopen:/Overr Type+Criticality+Confidence scores; natur DocsIssueOpener (§32.9 — real docs/Issues.md lockfile) + RunnerEventEmitter (§33.7 — direct run HTTP loopback) + Help:/Status:/Continue: f second latency — S2 proved 0.74s, no CC bootstrap c Issues? Fixed migration (rollback-via-sha256 test) + fan-out (multipart dispatch) + wiring all of these into (docs/qa/HRD-101-lifecycle-2026-05-2 language query — real Opus CC dispatch ~31s incl. b inbound message_id=30 → reply sent_message_id=30); S2 Help: fast-pa Confidence: 1, CC dispatch ABSENT (event abse BuiltinHelp catalogue text returned (reply_to_me sent_message_id=33); transcript.jsonl captures query, Help:, Status: also exercised live). Reproducibl test_wave6.5_lifecycle.sh covers 15 scena Done:/Reopen: + classifier edge cases). Spec V3 r13: Tag v0.5.0. Wave 6 — pherald inbound runtime + Claude Code h Cobra subcommand pherald listen runs the clo long-poll (OnText/OnPhoto/OnDocument/OnVo anti-echo guard captured at Subscribe construction; re username) + sha256 content-addressed attachment do <sha256>. <ext> (idempotent — duplicate downl dispatch with Opus pinned in the spawned argv (cla resume <UUID> --print <envelope>)+en wording ("We have received new message
HRD-101	task	high	Claude	@milos85vasic	
HRD-100	task	high	Claude	@milos85vasic	

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-016	task	middle	Claude	@milos85vasic	channel <channel-name>. <classification>") preceding the <<<HERALD-DISPATCH-REPLY>>> parser with action routing (reply delivery to telegram.Adapter.SendReply(ctx, chatID, attachments) wiring reply_to_message_id to out-dir <path> flag journals every inbound + outbound atomic Wave-6 commits T1=ad87d7f (HERALD + .env.example), T2=0d55274 (Opus model pin), T3=T4=b4018a3 (bot self-filter), T5=d9156f1 (OnPhone download), T6=a22a054 (pherald listen Cobalt) (pherald/internal/inbound/Dispatcher + action routing) (telegram.SendReply with reply_to_message_id) script tests/test_wave6_live_loop.sh), T7=JSONL journaling middleware), T11=01bfd1a (e2e tests), T12=96c7c6b (Wave 6 mutation gate tests/test_wave3_mutation_meta.sh gains M2 (D4) M4 (skip events_processed.Insert → E38/E42 break). deny-evaluator e2e. Commits T1..T10: eb9b2f4, 465468897, 6ea29a4, be71db1, c7b89a4, (this commit). Telegram channel adapter live integration — telebot.v1.HealthCheck + Send + Subscribe + outbound_delivery §107 bluff guards. Closed atomically with operator-session delivery message_id=5 from @atmosphere_wizard (validated via getChat) using the extended wizard (HERALD_TGRAM_BOT_TOKEN) + --chat-id --non-interactive flags. Token→getMe→getChatSession end in commit 140a2f1 session. commons_auth/ JWT verifier — HMAC + JWKS hybrid vendored Herald-internal per §11.4.74 catalogue-checks/catalogue-checks/HRD-099-commons_auth-3a executing-time anchor) in the post-Wave-3a doc-cl dbbea95..0cc6fad keep the old HRD-093 in the
HRD-011	task	middle	Claude	@milos85vasic	Accepted + Receipt JSON on fresh event, 200 + X-Header missing/invalid JWT, 400 on parse failure. §107 evidence stage + 3 integration scenarios: happy/duplicate/deny/deny-gate-skipped when absent — honest SKIP-with-reason test_wave3_mutation_meta.sh gains M2 (D4) M4 (skip events_processed.Insert → E38/E42 break). deny-evaluator e2e. Commits T1..T10: eb9b2f4, 465468897, 6ea29a4, be71db1, c7b89a4, (this commit). Telegram channel adapter live integration — telebot.v1.HealthCheck + Send + Subscribe + outbound_delivery §107 bluff guards. Closed atomically with operator-session delivery message_id=5 from @atmosphere_wizard (validated via getChat) using the extended wizard (HERALD_TGRAM_BOT_TOKEN) + --chat-id --non-interactive flags. Token→getMe→getChatSession end in commit 140a2f1 session. commons_auth/ JWT verifier — HMAC + JWKS hybrid vendored Herald-internal per §11.4.74 catalogue-checks/catalogue-checks/HRD-099-commons_auth-3a executing-time anchor) in the post-Wave-3a doc-cl dbbea95..0cc6fad keep the old HRD-093 in the
HRD-099	task	low	Claude	@milos85vasic	Accepted + Receipt JSON on fresh event, 200 + X-Header missing/invalid JWT, 400 on parse failure. §107 evidence stage + 3 integration scenarios: happy/duplicate/deny/deny-gate-skipped when absent — honest SKIP-with-reason test_wave3_mutation_meta.sh gains M2 (D4) M4 (skip events_processed.Insert → E38/E42 break). deny-evaluator e2e. Commits T1..T10: eb9b2f4, 465468897, 6ea29a4, be71db1, c7b89a4, (this commit). Telegram channel adapter live integration — telebot.v1.HealthCheck + Send + Subscribe + outbound_delivery §107 bluff guards. Closed atomically with operator-session delivery message_id=5 from @atmosphere_wizard (validated via getChat) using the extended wizard (HERALD_TGRAM_BOT_TOKEN) + --chat-id --non-interactive flags. Token→getMe→getChatSession end in commit 140a2f1 session. commons_auth/ JWT verifier — HMAC + JWKS hybrid vendored Herald-internal per §11.4.74 catalogue-checks/catalogue-checks/HRD-099-commons_auth-3a executing-time anchor) in the post-Wave-3a doc-cl dbbea95..0cc6fad keep the old HRD-093 in the

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-098	task	middle	Claude	@milos85vasic	sherald /v1/safety_state live — process-local tick) + Handler with JWT gate via commons_auth.Gin §107 evidence: e2e E46 (no-auth → 401), E47 (valid last_destructive_op=null + uptime_seconds>=1 + open mem Aggregator) proves E47 catches the regression trigger awaits HRD-033 body.
HRD-028	task	low	Claude	@milos85vasic	sherald /v1/compliance live — paginated + filtered surface with JWT gate via commons_auth.GinMiddle ConstitutionStore.ListQuery extended with Since/Until e2e E43 (no-auth → 401), E44 (valid HMAC + empty page_size=50). E45 SKIP-with-reason — cross-binary Wave 3b (Runner not live yet).
HRD-092	task	middle	Claude	@milos85vasic	commons/cli/ shared CLI scaffold (Wave 2) — NewR Middleware hook) + StubCmd + healthz/readyz/metric §11.4.74 catalogue-check no-match. As-built evidence checks/HRD-092-commons-cli.md.
HRD-093	task	middle	Claude	@milos85vasic	sherald flavor scaffold — System Herald binary service (HRD-033/034/040/046/056) + /v1/safety_state 501 stub
HRD-094	task	middle	Claude	@milos85vasic	sherald flavor scaffold — Constitution Herald binary stubs + /v1/compliance 501 stub → HRD-028.
HRD-095	task	low	Claude	@milos85vasic	sherald flavor scaffold — Build Herald CLI-only binary
HRD-096	task	low	Claude	@milos85vasic	sherald flavor scaffold — Release Herald CLI-only binary
HRD-097	task	low	Claude	@milos85vasic	sherald + sherald flavor scaffolds — Incident Herald HRD-024 + Scheduled-audit Herald CLI-only with 1 stub has zero §43 stubs.
HRD-012	task	middle	Claude	@milos85vasic	Claude Code dispatcher live integration — claude <envelope> exec + <<<HERALD-REPLY>>> JSON persistence per §33. §107 evidence: Plan 2 Task 6 completed claude CLI round-trip, structured reply parsed, Outcomes 4718c0e (live PASS 36.23s — session_state upsert equality assertions on session_uuid + anchor_path + 1 HRD-085..HRD-090 stay open for upstream-defined Dispatch+session hot path.
HRD-010	task	middle	Claude	@milos85vasic	commons_storage live wiring — pgx pool + RLS-enforced fixed RLS-bypass bug via E14 falsifiability) + 9 migrations (digital.vasic.background bound via pgxTaskRepository pherald migrate up/status/down/validate subcommand + HRD-085..090 registered for queue-repository stubs
HRD-080	task	low	Claude	@milos85vasic	Refine I6 inheritance-gate invariant from blanket .gitmodules/ entry in .gitmodules" — paired test_i6_refinement_meta.sh with 3 anti-blanket Helix-stack submodule installs.
HRD-017	task	middle	Claude	@milos85vasic	Propagate Universal §11.4.73 (main-spec versioning + submodule-catalogue-first discovery) into parent component AGENTS.md
HRD-014	task	middle	Claude	@milos85vasic	sherald CLI scaffold — Cobra root + version + 5 stubs - - json returns canonical build info
HRD-013	task	middle	Claude	@milos85vasic	commons_messaging + null:// adapter — full §11.0 C fail_rate/latency/ceiling URL params + 8-case unit tests

ID	Type	Criticality	Created-By	Assigned-To	Title
HRD-009b	task	low	Claude	@milos85vasic	commons_prefix module — §8.2 deterministic 3-letter collision-resolution via fnv1a32 + table-driven tests
HRD-009	task	middle	Claude	@milos85vasic	commons module — full §11.0 Go type contract (ChannelID + OutboundMessage + Body + Attachment + RecipientID + InboundHandler + InboundEvent + Subscriber + Subscription + TraceContext + Branding + ChannelID + Preferences + helper + DefaultBranding factory
HRD-007	task	middle	Claude	@milos85vasic	V3 r3 cross-doc sync + tracking-doc scaffold (Issues/Issues_Summary/Fixed_Summary/CONTINUATION
HRD-006	task	middle	Claude	@milos85vasic	V3 r2 flavor refinement — 9 flavors × per-channel in
HRD-005	task	middle	Claude	@milos85vasic	V3 r1 operator-product layer (§31..§36 + §18.2 expan
HRD-004	task	middle	Claude	@milos85vasic	V2 r3 — Go type contract closure + operational ops d
HRD-003	task	middle	Claude	@milos85vasic	V2 r2 — close prose[?]definition gaps + add operatio
HRD-002	task	middle	Claude	@milos85vasic	V2 r1 — architectural authoring (CloudEvents/Waterr
HRD-001	task	middle	Claude	@milos85vasic	V1 — initial MVP specification + Review section + R