

API_REFERENCE

API Reference

Package agent

Interfaces

Agent

Core interface for all CLI agents.

Method	Signature	Description
ID	() string	Unique instance identifier
Name	() string	Agent type name
Start	(ctx context.Context) error	Launch agent process
Stop	(ctx context.Context) error	Graceful shutdown
IsRunning	() bool	Process active status
Health	(ctx context.Context) HealthStatus	Health check
Send	(ctx context.Context, prompt string) (Response, error)	Send prompt, get response
SendStream	(ctx context.Context, prompt string) (<-chan StreamChunk, error)	Streaming response
SendWithAttachments	(ctx context.Context, prompt string, attachments	Send with files

Method	Signature	Description
	<code>[]Attachment) (Response, error)</code>	
<code>OutputDir</code>	<code>() string</code>	Artifact output directory
<code>Capabilities</code>	<code>() AgentCapabilities</code>	Agent capabilities
<code>SupportsVision</code>	<code>() bool</code>	Vision support
<code>ModelInfo</code>	<code>() ModelInfo</code>	Model information

AgentPool

Thread-safe pool with capability matching.

Method	Signature	Description
<code>Register</code>	<code>(agent Agent) error</code>	Add agent to pool
<code>Acquire</code>	<code>(ctx context.Context, requirements AgentRequirements) (Agent, error)</code>	Get matching agent (blocks)
<code>Release</code>	<code>(agent Agent)</code>	Return agent to pool
<code>Available</code>	<code>() []Agent</code>	List available agents
<code>HealthCheck</code>	<code>(ctx context.Context) []HealthStatus</code>	Check all agents
<code>Shutdown</code>	<code>(ctx context.Context) error</code>	Stop all agents

Types

- `Response` - Parsed result from `Send()`
- `StreamChunk` - Individual streaming chunk
- `Attachment` - File attachment
- `AgentCapabilities` - Agent feature flags
- `AgentRequirements` - Caller requirements
- `HealthStatus` - Health check result
- `Action` - Structured action (click, type, scroll, etc.)
- `ParsedResponse` - Fully parsed response
- `Issue` - Detected problem
- `ModelInfo` - LLM model information

Functions

- `NewPool()` `AgentPool` - Create thread-safe agent pool
- `NewCircuitBreaker()` `*CircuitBreaker` - Create circuit breaker (default config)
- `NewCircuitBreakerWithConfig(threshold int, timeout time.Duration)` `*CircuitBreaker` - Custom config
- `NewHealthMonitor()` `*HealthMonitor` - Create health monitor

Package adapter

Constructors

Function	Description
<code>NewOpenCodeAgent(id string, config AdapterConfig)</code> <code>*OpenCodeAgent</code>	OpenCode adapter
<code>NewClaudeCodeAgent(id string, config AdapterConfig)</code> <code>*ClaudeCodeAgent</code>	Claude Code adapter
<code>NewGeminiAgent(id string, config AdapterConfig)</code> <code>*GeminiAgent</code>	Gemini adapter
<code>NewJunieAgent(id string, config AdapterConfig)</code> <code>*JunieAgent</code>	Junie adapter
<code>NewQwenCodeAgent(id string, config AdapterConfig)</code> <code>*QwenCodeAgent</code>	Qwen Code adapter
<code>NewBaseAdapter(id, name string, config AdapterConfig, caps AgentCapabilities, modelInfo ModelInfo)</code> <code>*BaseAdapter</code>	Base adapter

AdapterConfig

```
type AdapterConfig struct {  
    BinaryPath string  
    Args       []string  
    Env        []string  
    WorkDir    string  
    OutputDir  string  
    Timeout    time.Duration  
    MaxRetries int  
}
```

Package protocol

PipeTransport

Method	Description
NewPipeTransport(reader io.Reader, writer io.Writer) *PipeTransport	Create transport
Send(ctx, msg PipeMessage) error	Write JSON-line
Receive(ctx) (PipeMessage, error)	Read JSON-line
SendPrompt(ctx, requestID, content, imagePath string) error	Convenience prompt
SendShutdown(ctx) error	Send shutdown signal
Close() error	Mark closed

FileTransport

Method	Description
NewFileTransport(sessionDir string) (*FileTransport, error)	Create with inbox/outbox/shared
WriteToInbox(msg FileMessage) error	Write to inbox
WriteToOutbox(msg FileMessage) error	Write to outbox
ReadFromInbox() ([]FileMessage, error)	Read inbox messages
ReadFromOutbox() ([]FileMessage, error)	Read outbox messages
WriteSharedFile(name string, data []byte) error	Write shared artifact
ReadSharedFile(name string) ([]byte, error)	Read shared artifact
Cleanup() error	Remove session directory

Package parser

ResponseParser Interface

Method	Description
Parse(raw string) (ParsedResponse, error)	Full parse

Method	Description
ExtractJSON(raw string) (map[string]any, error)	Extract JSON
ExtractActions(raw string) ([]Action, error)	Extract actions
ExtractIssues(raw string) ([]Issue, error)	Extract issues

Functions

- NewParser() ResponseParser - Create default parser

Package config

Functions

Function	Description
DefaultConfig() *Config	Sane defaults
LoadFromEnv(path string) (*Config, error)	Load from .env file
LoadFromEnvironment() *Config	Load from OS env
MaskAPIKey(key string) string	Mask key for logging

Config Methods

Method	Description
AgentBinaryPath(name string) (string, error)	Resolve binary path
IsAgentEnabled(name string) bool	Check if enabled
SessionDir(sessionID string) string	Get session directory
Validate() error	Validate configuration