

architecture

LLMOrchestrator Architecture

Module: `digital.vasic.llmorchestrator`

LLMOrchestrator manages headless CLI agents (OpenCode, Claude Code, Gemini, Junie, Qwen Code) with a hybrid pipe+file communication protocol. It provides a unified Agent interface, a thread-safe pool, per-agent circuit breakers, and a structured response parser.

Package Overview

Package	Role
pkg/agent	Agent interface, AgentPool, CircuitBreaker, Health-Monitor
pkg/adapter	BaseAdapter + 5 CLI-specific adapters
pkg/protocol	PipeTransport (JSON-lines) and FileTransport (inbox/outbox)
pkg/parser	ResponseParser: action, issue, and JSON extraction
pkg/config	.env loading, binary path resolution, validation

Agent Pool

flowchart TD
A[Caller: Acquire ctx, requirements] --> B[AgentPool]
B --> C{Available agent\nmatches requirements?}
C -- yes --> D[Return Agent handle]
C -- no --> E[sync.Cond.Wait]
E --> C
D --> F[Caller uses Agent]

```
F --> G[Release back to pool]
G --> H[sync.Cond.Broadcast]
H --> E
```

AgentPool is protected by sync.Mutex + sync.Cond. Acquire blocks until a matching agent is available or ctx is cancelled, preventing busy-wait. Capability matching checks agent type, health status, and workload flags declared in requirements.

Adapter Pattern

Agent interface

```
└─ BaseAdapter (shared process management)
    ├── OpenCodeAdapter (parses opencode JSON-lines output)
    ├── ClaudeCodeAdapter (parses claude-code streaming JSON)
    ├── GeminiAdapter (parses gemini JSON output)
    ├── JunieAdapter (parses junie output format)
    └─ QwenCodeAdapter (parses qwen-code output format)
```

BaseAdapter owns process lifecycle: Start (exec + pipe setup), Stop (SIGTERM with timeout, SIGKILL fallback), Restart, and IsAlive. Each concrete adapter only implements ParseResponse(raw string) (*Response, error) and declares its binary name and default flags, keeping per-agent code minimal.

Hybrid Communication Protocol

Pipe Transport (real-time)

protocol.PipeTransport attaches to the agent's stdin/stdout as a JSON-lines stream:

```
stdin  → {"type":"prompt","content":"...", "id":"req-1"}\n
stdout ← {"type":"response","content":"...", "id":"req-1"}\n
```

Each message is a single newline-terminated JSON object. The transport enforces a configurable response length limit and a read deadline per request.

File Transport (artifact exchange)

protocol.FileTransport manages three directories per agent session:

Directory	Purpose
inbox/	Files written by the caller for the agent to read

Directory	Purpose
outbox/	Files written by the agent for the caller to consume
shared/	Bidirectional scratch space for large artifacts

File transport is used for code files, diffs, and other payloads too large or ill-suited for inline JSON.

Circuit Breaker

Each agent has an independent `CircuitBreaker`:

- **Closed** (healthy) — requests pass through normally.
- **Open** (unhealthy) — after 3 consecutive failures, requests are rejected immediately for a 60-second cool-down period.
- **Half-Open** — after the cool-down, one probe request is allowed; success returns to Closed, failure resets the 60-second timer.

`HealthMonitor` runs a background goroutine that periodically calls `Agent.Ping` and feeds results into the circuit breaker, allowing recovery without requiring an incoming request.

Response Parser

`parser.ResponseParser` operates on raw string output and extracts:

Extraction	Pattern
JSON blocks	First valid JSON object or array in the output
Actions	Lines matching ACTION: <verb> <target> convention
Issues	Lines matching ISSUE: or ERROR: prefixes

The parser is intentionally stateless and side-effect-free, making it safe to call concurrently from multiple goroutines without locking.

Security Constraints

- **Path traversal protection** — `FileTransport` rejects any path containing `..` or absolute segments outside the session directory.

- **Response length limit** — PipeTransport returns an error if a single response exceeds the configured byte ceiling (default 1 MB).
- **API key masking** — Config loader redacts *_API_KEY values in log output.
- **Command injection prevention** — Agent binary paths are validated against an allowlist; no shell interpolation is used when spawning processes.