

oom-watch — Deployment Guide

One-shot install + verify for the OOM-Protect monitoring daemon

OOM-Protect maintainers

2026-04-30

oom-watch — Deployment Guide

- 1. The one command
- 2. Prerequisites
- 3. What the script does, step by step
 - 3.0 Optional `--pull`
 - 3.1 Pre-flight
 - 3.2 Build + install
 - 3.2a Post-install path checks
 - 3.2b Validate `/etc/oom-watch/config.json`
 - 3.3 daemon-reload + enable + restart
 - 3.4 Wait for `active` state (timeout 30 s)
 - 3.5 Journal sanity check
 - 3.6 Wait for first report (timeout 60 s)
 - 3.7 Summary
- 4. Flags
- 5. Exit codes
- 6. Idempotency and re-running
- 7. Failure modes
- 8. Reverse and uninstall
- 9. After deploy: live operations
- 10. Constitution alignment (Article I)
- See also

oom-watch — Deployment Guide

This guide is the canonical, end-to-end procedure for getting `oom-watch` running on a host. It documents the deployer script (`oom-watch/scripts/install-and-verify.sh`) and the `make oom-watch-deploy` target that wraps it.

If you are debugging a failed deployment, jump straight to **§7 Failure modes** — every documented symptom maps to a specific assertion the script makes, and the EXIT trap dumps the corresponding diagnostic automatically.

1. The one command

On a target host with the OOM-Protect repo checked out, atop installed, and Go $\geq$ 1.22 available:

```
sudo make oomwatch-deploy
```

...or, when already root (e.g. logged in via `su -`):

```
make oomwatch-deploy
```

That is the entirety of a fresh deploy. The Makefile target invokes `oom-watch/scripts/install-and-verify.sh`, which performs every step described below in order, asserts each one, and aborts with a full diagnostic dump if any check fails.

If your repo is checked out somewhere other than the working directory, run the script directly:

```
sudo bash /path/to/OOM-Protect/oom-watch/scripts/install-and-verify.sh
```

2. Prerequisites

The script will refuse to proceed unless every prerequisite is satisfied. There are no silent skips.

Prerequisite	Why	Install hint (ALT Linux)
Root or sudo	Writes to <code>/usr/local/sbin</code> , <code>/etc/oom-watch</code> , <code>/etc/systemd/system</code> , <code>/var/log/oom-watch</code> , <code>/var/lib/oom-watch</code>	<code>su -</code> or configure sudoers
<code>atop</code> on PATH	The daemon's only data source. Without atop the daemon refuses to start.	<code>apt-get install atop</code>
<code>systemctl</code>	The unit is managed by systemd.	included with systemd
Go $\geq$ 1.22	Only required if the <code>oom-watch/oomwatch</code> binary has not already been built.	<code>apt-get install golang</code>
<code>make</code>	Drives the install target.	usually pre-installed

The script does **not** install atop or Go for you. Fixing prerequisites is intentionally a separate step from deployment so you can review what you're installing.

3. What the script does, step by step

The script is `oom-watch/scripts/install-and-verify.sh`. Each numbered step here corresponds to a header section in the script's stderr output.

3.0 Optional `--pull`

If invoked with `--pull`, runs `git pull --ff-only` in the repo so that the binary you build, the example config you install, and the unit file all come from current `main`. **Off by default** because pulling on a dirty tree may conflict; turn it on for fully-automated update-and-redeploy.

3.1 Pre-flight

- Re-execs under sudo when not root (or fails loudly if sudo is missing on a non-root host).
- Verifies `atop` is on PATH and prints its version.
- Verifies `systemctl` is reachable.

3.2 Build + install

- Builds `oom-watch/oomwatch` if missing (or always, with `--rebuild`). Skipped entirely with `--no-install`.

- Runs `make oomwatch-install`, which is itself idempotent:
 - copies the binary to `/usr/local/sbin/oomwatch`
 - creates `/etc/oom-watch/`, `/var/log/oom-watch/`, `/var/lib/oom-watch/`
 - copies `oom-watch/config/oom-watch.example.json` to `/etc/oom-watch/config.json` **only if the file does not already exist** (preserves customised configs)
 - copies `oom-watch/systemd/oom-watch.service` to `/etc/systemd/system/`

3.2a Post-install path checks

Asserts every artefact landed where expected: binary executable, config file present, unit file present. Catches a regression in `make oomwatch-install` before any service ever tries to start.

3.2b Validate `/etc/oom-watch/config.json`

Runs `oomwatch -dry-run` against the **installed** config. This is the anti-bluff guard against a class of bug where the daemon enters the systemd start path, fails configuration parsing, and dies at exit code 2 with no human-readable diagnostic.

If validation fails, the script auto-remediates:

1. The broken file is moved aside to `/etc/oom-watch/config.json.broken.<timestamp>`.
2. The shipped example is copied in as the new config.
3. The new config is re-validated.

If even the fresh example fails validation, the repository itself is broken and the script exits fatal. The backup path is printed; if you had custom thresholds, you can re-apply them by diffing the backup against the current file.

3.3 daemon-reload + enable + restart

Reload the systemd manager configuration, enable the unit if not already enabled, and restart the unit. Restart (vs. start) gives the verifier a known starting state.

3.4 Wait for `active` state (timeout 30 s)

Polls `systemctl is-active oom-watch.service` once per second:

- `active` → proceed.
- `failed` → exit 1 immediately (no point in waiting).
- anything else → keep polling.

Times out at 30 s. The systemd unit is `Type=simple`, so it should reach `active` within milliseconds; staying in `activating` for 30 s indicates the binary is crashing on startup. The EXIT trap will then dump `systemctl status` and the journal so you can see why.

3.5 Journal sanity check

Asserts `journalctl -u oom-watch.service --since "2 minutes ago"` contains the line `atop located`. The daemon prints this once it has resolved `atop` on its restricted (sandboxed) PATH. A daemon that bounced because the systemd hardening blocked something would otherwise show `active` but not have run; this check rules that out.

3.6 Wait for first report (timeout 60 s)

Polls `/var/log/oom-watch/reports/` for any `.md` file. A genuinely calm host may not produce ANY automatic report — quiet IS the goal — so if the wait expires, the script forces a `-one-shot` diagnostic so we have proof on disk that the *report-writing* path also works.

3.7 Summary

Prints unit state, binary mode and ownership, paths, and the latest report file name and size, plus the live-tail command so you know how to follow the daemon going forward.

4. Flags

```
sudo bash oom-watch/scripts/install-and-verify.sh [FLAGS]
```

Flag	Effect
<code>--pull</code>	<code>git pull --ff-only</code> the repo before building. Off by default.
<code>--no-install</code>	Skip step 3.2 entirely. Use to verify a running unit after a manual restart.
<code>--rebuild</code>	Force a fresh <code>go build</code> even if the binary already exists.
<code>--quiet</code>	Suppress per-step OK / informational prints. Failure diagnostics are always printed.
<code>--help</code> , <code>-h</code>	Print the script's header documentation and exit.

5. Exit codes

Code	Meaning
0	Success. The daemon is installed, active, and producing reports.
1	Any pre-flight, install, validation, or runtime check failed. The EXIT trap will have dumped <code>systemctl status</code> , the last 50 journal lines, the config file, the unit file, and a listing of the report directory.
64	Usage error (unknown flag).

6. Idempotency and re-running

The script is **idempotent by design**. Re-running on a host where `oom-watch` is already deployed is safe; it will:

- Skip the binary build if `oom-watch/oomwatch` is current (override with `--rebuild`).
- Skip `enable` if the unit is already enabled.
- **Always** restart the unit (gives a clean starting state for verification).
- **Always** re-validate the installed config and auto-remediate if broken.

Re-running is also the recommended remediation when something has drifted on the host — it converges the host to the deployed state.

7. Failure modes

Every failure surfaces a specific error from the script (above the EXIT-trap diagnostic dump). The diagnostic dump always includes `systemctl status`, journal tail, config, unit file, and report directory listing.

Symptom	Most likely cause	What to do
<code>atop</code> is not installed	<code>atop</code> binary not on PATH	Install <code>atop</code> , retry.
<code>systemctl</code> not found	Host is not <code>systemd</code>	This script is <code>systemd</code> -only; for non- <code>systemd</code> hosts run <code>oomwatch -one-shot</code> from <code>cron</code> or your supervisor of choice.
Go toolchain required to build <code>oomwatch</code>	No prebuilt binary AND no Go on host	Either install Go and retry, or copy a prebuilt <code>oom-watch/oomwatch</code> from another host.
INSTALLED CONFIG IS INVALID	<code>/etc/oom-watch/config.json</code> fails <code>-dry-run</code>	The script auto-remediates: backs up to <code>config.json.broken.<ts></code> , replaces with shipped example. If the validator output mentions an unknown field, the repo's example may also be broken — file an issue.
unit went to 'failed' state	The daemon process exits non-zero before the verifier polls	The EXIT-trap dump shows the precise cause: usually a sandbox path the daemon needs is blocked, or the binary is built for a different architecture.
unit did not reach 'active' within 30 s	<code>Type=simple</code> daemon stuck activating	Same as above — read the dumped journal. Common cause: <code>Restart=on-failure</code> is bouncing because the binary is crashing immediately.
journal does not contain 'atop located'	Daemon got past unit start but never reached the sample loop	<code>atop</code> probably failed to spawn. Look at the dumped journal for <code>atop</code> -related errors.
even <code>-one-shot</code> did not produce a report	<code>atop</code> emits zero samples or <code>report-dir</code> is unwritable	Check the report dir's mode and the daemon's <code>User=</code> in the unit file (default <code>root</code>).

8. Reverse and uninstall

There is no first-class uninstall yet (TODO). To manually uninstall:

```

sudo systemctl disable --now oom-watch.service
sudo rm /etc/systemd/system/oom-watch.service
sudo systemctl daemon-reload
sudo rm /usr/local/sbin/oomwatch
sudo rm -rf /etc/oom-watch /var/log/oom-watch /var/lib/oom-watch

```

Note: removing `/var/log/oom-watch` deletes any past forensic reports. If you want to keep them, move the directory aside first.

9. After deploy: live operations

```

# Tail the daemon log:
journalctl -fu oom-watch.service

# List recent reports:
ls -lt /var/log/oom-watch/reports/ | head -20

# Open the most recent report (any severity):
ls -t /var/log/oom-watch/reports/*.md | head -1 | xargs less

# Open the most recent CRITICAL:
ls -t /var/log/oom-watch/reports/*-critical.md 2>/dev/null | head -1 | xargs less

# Show effective config (defaults overlaid with the file):
sudo /usr/local/sbin/oomwatch -config /etc/oom-watch/config.json -print-config

# Force a diagnostic report right now:
sudo /usr/local/sbin/oomwatch -config /etc/oom-watch/config.json -one-shot

# Clean up old reports (cron candidate):
sudo find /var/log/oom-watch/reports -name '*.md' -mtime +30 -delete

```

10. Constitution alignment (Article I)

This deployer is itself an anti-bluff artefact. Each numbered step asserts an observable outcome — file on disk, exit code, systemd unit state, journal substring, report file size — and exits non-zero on the first failed assertion. There are no `|| true`s, no `t.Skip`-equivalents, and no silent successes. The EXIT-trap diagnostic dump means a failure always surfaces enough context for the operator to act without re-running anything.

The corresponding regression Challenge is `challenges/challenge-config-validation.sh`, which asserts the shipped `oom-watch.example.json` itself passes `-dry-run`. A future commit that re-introduces an unknown field in the example config would fail that Challenge, not your fresh install.

See also

- `manuals/oom-watch-manual.md` — full daemon documentation (config keys, severity ladder, threshold tuning, report anatomy).
- `reports/oom-watch-architecture.md` — design decisions, including why the deployer validates with `-dry-run` before enabling.
- `Constitution.md` — the project charter and Article I (anti-bluff testing).