Identity Management + Network-Share Discovery — Design & Survey

Revision: 1 **Last modified:** 2026-06-26T00:00:00Z **Status:** DRAFT (design + survey pass — no implementation) **Authority:** Operator capability request 2026-06-26; constitution §11.4.74 (catalogue-first), §11.4.150 (deep multi-angle research), §11.4.10 (credentials), §11.4.58 (PWU), §11.4.169 (test-type coverage), §11.4.162 (OpenDesign) **Scope:** catalog-api (Go backend) + catalog-web + catalogizer-desktop + catalogizer-android + catalogizer-androidtv + installer-wizard **Classification note:** This is a project-specific instantiation; the reusable pieces live in owned submodules (§11.4.28/§11.4.74).

> This document references credential material by **env-var NAME only** (never a value), per §11.4.10. No secret value appears anywhere below.

---

0. Capability (verbatim operator intent)

> "We provide identities; the System scans the network and all interfaces and protocols we support for available hosts and shares; each share is accessed first with NO credentials (anonymous), then with every added identity until one passes/logs in. We remember the (share, identity) combinations that work together. Extend the System for proper IDENTITY MANAGEMENT — an identity can be credentials (username+password), an API token, or other common auth means; support them ALL. Then extend the catalog with all detected network shares, track all duplicates, group everything so the user can easily browse, search and filter. Proper UI/UX and System support MUST exist."

Decomposed into five capability pillars:

1. **Identity management** — extensible, multi-scheme identity store (credentials / api_token / ssh_key / …).
2. **Network discovery** — enumerate hosts across every interface + protocol, then enumerate shares per host.
3. **Anonymous-first auth probing** — try each share anonymous, then each identity in order until one authenticates; **remember the working `(share, identity, protocol)` binding**.
4. **Catalog extension** — auto-register every discovered share as a source, ingest media, track duplicates, group for browse/search/filter.
5. **UI/UX** — identity-manager screen + discovered-shares screen + grouped/deduped browse, per app, OpenDesign-tokened light+dark.

---

1. Current-State Survey (§11.4.74, file:line evidence)

1.1 How shares are discovered / scanned today

Capability	Where	Verdict
Host discovery (announce/respond)	`catalog-api/main.go:771-795` — `digital.vasic.discovery/pkg/broadcast` Announcer + Responder (UDP multicast, namespace `catalogizer`). This **announces the catalog-api service**, it does NOT scan for NAS hosts.	Service-presence only — not host/share inventory
TCP reachability probe	`catalog-api/main.go:85-95` — `digital.vasic.containers/pkg/discovery.NewTCPDiscoverer()` probes a single configured target.	Point probe, not a sweep
Network host+SMB scanner (CIDR sweep)	`submodules/discovery/pkg/scanner` (`Scanner` iface: `Scan`/`ScanHost`) + `submodules/discovery/pkg/smb/scanner.go` (ports 445/139, concurrent, semaphore-limited, CIDR expansion).	**EXISTS but UNWIRED into catalog-api** — the reuse anchor for host/share sweep
SMB share enumeration on a host	`catalog-api/internal/services/smb_discovery.go:57-95` `DiscoverShares()` — connects 445, NTLM session, `enumerateShares()` mounts known share names.	Works, but **guessing-based** (see below)
SMB connection test	`internal/services/smb_discovery.go:178-225` `TestConnection()` — dials, mounts share, `ReadDir(".")`.	Solid positive-evidence probe

Capability	Where	Verdict
Existing discovery HTTP routes	`catalog-api/main.go:1267-1271` — `POST/GET /api/v1/.../smb/discover`, `/smb/test`, `/smb/browse` → `handlers.SMBDiscoveryHandler`.	SMB-only, operator-supplied creds, no anon-first, no multi-identity, no remembering
Scan engine (per protocol)	`internal/services/universal_scanner.go:19-67` — `UniversalScanner` with `ProtocolScanner` registry + `filesystem.ClientFactory`; `ScanJob` keyed on `*models.StorageRoot`.	Generic, protocol-pluggable — the ingest target

Critical anti-bluff finding (§11.4.6 / §11.4.107): `smb_discovery.go:140-175` `getCommonShares()` returns a **hard-coded list of guessed share names** (`shared`, `public`, `media`, `music`, …) as a fallback "when host unreachable" (line 169-172 returns them even when `len(accessibleShares)==0`). This is a guessing path that can surface non-existent shares as discovered. The new pipeline MUST replace guess-fallback with honest "host unreachable / no shares enumerable → SKIP-with-reason" (§11.4.3) and only ever report a share proven mountable.

1.2 Protocols actually supported today

`catalog-api/filesystem/interface.go:1-16` aliases `digital.vasic.filesystem/pkg/client`. `filesystem/factory.go:15-50+` `CreateClient()` switches on `config.Protocol`:

- **smb** (445, go-smb2 NTLM) — `factory.go:18-27`, low-level in `catalog-api/filesystem/smb_client.go:38-73`
- **ftp** (21, jlaffaye/ftp) — `factory.go:29-37`
- **nfs** (v3, build-tag gated `nfs_client_darwin.go`/`_windows.go`) — `factory.go:39-50`
- **webdav** (`catalog-api/filesystem/webdav_client.go`) — factory continues past line 50
- **local** (path-traversal guarded)

So today the supported protocol set is **SMB, FTP, NFS, WebDAV, local**. Only **SMB** has a discovery/probe path (`smb_discovery.go`). FTP/NFS/WebDAV/local have working *clients* but no *discovery/probe* surface.

1.3 How authentication is handled for a share/source today

- **Model:** `catalog-api/models/file.go:48-70` `StorageRoot{ … Username *string; Password *string; Domain *string … }` — **credentials are embedded per share record**, plaintext.
- **DB:** `storage_roots` table — `database/migrations/000001_initial_schema.sqlite.up.sql:4-26` + `…up.sql:5-27`. Columns `username TEXT`, `password TEXT`, `domain TEXT` stored **plaintext** (§11.4.10 gap).
- **Read path:** `handlers/scan_handler.go:294-308 loadStorageRoot()` `SELECT … username, password, domain …`; root-set query `main.go:377-416` (`SELECT … username, password … FROM storage_roots WHERE protocol='smb' AND enabled=1`).
- **Client construction:** `handlers/copy.go:326 createSmbClient()`, `factory.go:18-27` build the client straight from the per-root username/password.
- **No identity abstraction:** credentials cannot be shared across shares, cannot be rotated centrally, are not anonymous-first, and there is no "try identities in order" logic anywhere.

1.4 The catalog data model (source ↔ media)

- **Source** = **`storage_roots`** (`models/file.go:48-70`). One row per configured share/root.
- **Files → source FK:** `files.storage_root_id` references `storage_roots(id)` (`migrations/000001_initial_schema.up.sql:55`, index `idx_files_storage_root_path` line 109).
- **Scan history → source FK:** `scan_history.storage_root_id` (`…up.sql:105`, index line 114).
- **Aggregation to entities:** `internal/services/aggregation_service.go:60-67 AggregateAfterScan(storageRootID)` walks media-bearing leaf files → `MediaItem` entities at **title granularity** (DEFECT-E fix, `aggregation_service.go:60-66` comment); repos `MediaItemRepository`, `MediaFileRepository`, `DirectoryAnalysisRepository`, `ExternalMetadataRepository`.

1.5 Existing duplicate-tracking + grouping (reuse, don't reinvent)

- **Dedup engine:** `internal/services/duplicate_detection_service.go:15-90` — `DuplicateDetectionService`, `DuplicateGroup{PrimaryItem, DuplicateItems, Confidence, DetectionMethod, MatchTypes, Status}`, `DuplicateItem{FileHash, FileSize, ExternalIDs, Fingerprints, …}`, similarity stack (`SimilarityAnalysis`, `TextSimilarityMetrics`: Levenshtein / JaroWinkler / Cosine / Jaccard / LCS / Soundex / Metaphone). **This already solves "same content across shares".**
- **Grouping for browse:** `aggregation_service.go` already collapses files into title-level `MediaItem`s. Multi-source dedup must feed these so one title with copies on 3 shares shows once with 3 origins.

1.6 App UIs for source/share config + login (current)

App	Stack / tokens	Source/share config UI	Identity UI	API path
installer-wizard	Tauri2 + React + Tailwind/shadcn	`src/components/wizard/SMBConfigurationStep.tsx:26-478` (host/port/share/user/pwd/domain + Test), `NFSConfigurationStep.tsx:23-395`; `contexts/ConfigurationContext.tsx` already models `ConfigurationAccess{type:'credentials',account,secret}` separate from `ConfigurationSource{type,url,access}` — **the closest existing identity↔source split**	per-source creds only	Tauri IPC `testSMBConnection/testNFSConnection`
catalogizer-desktop	Tauri2 + React + Tailwind	`src/pages/SettingsPage.tsx:24-114` SMB config list (add/delete) + server URL test	none	`apiService.getSMBConfigs/createSMBConfig/deleteSMBConfig`

App	Stack / tokens	Source/share config UI	Identity UI	API path
catalog-web	React18 + Tailwind/shadcn + React Query + Zustand	`src/pages/Settings.tsx:34-101` scans + storage-root selector; `lib/api.ts` exposes `smbApi`, `scansApi`, `syncApi`	none (`LoginForm.tsx`)	Axios `/api/v1`, Bearer interceptor
catalogizer-android-tv	Compose-for-TV + Material3, **OpenDesign-aligned** (`ui/theme/Theme.kt`)	none (login + server discovery only `ui/screens/login/LoginScreen.kt:224-270,538-583`)	none; `SettingsScreen.kt` toggles only	Retrofit `CatalogizerApi.kt:14-49` auth-only
catalogizer-android	Compose + Material3	none	none (`LoginScreen.kt`)	Retrofit

Gaps: No app has a dedicated **identity manager**. OpenDesign tokens are referenced **only** in Android TV (§11.4.162 gap for web/desktop/phone). The installer-wizard's `Access↔Source` separation is the conceptual seed to lift backend-side.

1.7 `.env` identity keys — defined but UNWIRED

`.env.example:46-65` defines (NAMES only): `CATALOGIZER_IDENTITY_COUNT`, `CATALOGIZER_IDENTITY_<N>_TYPE`, `_USERNAME`, `_PASSWORD`, `_TOKEN`, `_KEY_PATH`, `_PASSPHRASE`. **`grep CATALOGIZER_IDENTITY` over `*.go` = ZERO hits.** The identity contract exists only as documentation; **no code consumes it.** `.env` is gitignored (`.gitignore:45-48,319-320,328`). This is the central greenfield wiring gap.

1.8 §11.4.74 Catalogue-Check — reusable owned submodules

Submodule (module path)	Provides	Verdict
`submodules/discovery` (`digital.vasic.discovery`)	`pkg/scanner` host sweep, `pkg/smb` SMB scanner (445/139, CIDR), `pkg/broadcast` mDNS/UDP, `pkg/report`	**REUSE** + **EXTEND** (add NFS/FTP/WebDAV scanners via `Scanner` iface)
`submodules/auth` (`digital.vasic.auth`)	`pkg/jwt`, `pkg/apikey` (`KeyStore` iface), `pkg/oauth` (`CredentialReader`/`TokenRefresher`/`AutoRefresher`), `pkg/token` (`Store`)	**REUSE** as the identity credential-scheme backbone; **EXTEND** with ssh_key + raw-credentials schemes

Submodule (module path)	Provides	Verdict
`submodules/filesystem` (`digital.vasic.filesystem`)	`pkg/client` 5-protocol clients + `pkg/factory`	**REUSE** (already aliased by catalog-api)
`submodules/security` (`digital.vasic.security`)	`pkg/securestorage` (encrypted at-rest), `pkg/pii` redactor, `pkg/e2ee`	**EXTEND** — encrypt identity secrets at rest + redact hosts/users in logs
`submodules/database` (`digital.vasic.database`)	`pkg/repository[T]`, sqlite/postgres adapters, `pkg/migration`	**REUSE** for new tables
`submodules/config` (`digital.vasic.config`)	`pkg/env` struct-tag env loader	**REUSE** to parse `CATALOGIZER_IDENTITY_*`
`submodules/media`, `submodules/watcher`, `submodules/entities`	metadata extraction / incremental watch / shared models	**EXTEND** (post-discovery ingest)
`submodules/challenges`, `submodules/helix_qa`	Challenge bank + autonomous QA	**REUSE** for §11.4.169 coverage

Conclusion: ~80%+ of the building blocks exist. The new work is **composition + the missing identity/probe/remember logic + the 5 app UIs**, NOT new infrastructure.

---

2. Proposed Design

2.1 Identity model (extensible, multi-scheme)

A first-class **Identity** decoupled from any share:

```
Identity {
  id            int64
  name          string            // operator-facing label, e.g. "nas-admin"
  type          string            // credentials | api_token | ssh_key |
webdav_basic | oauth2 | anonymous(synthetic)
  // scheme-specific fields, encrypted at rest (security/pkg/securestorage):
  username      *string
  secret_ref    *string           // opaque handle into the secret store; NEVER the
raw secret in this row
  domain        *string           // SMB
  key_path      *string           // ssh_key
  token_ref     *string           // api_token (handle, not the token)
  enabled       bool
  priority      int               // order to try during probing (lower = first)
  created_at / updated_at
}
```

- **Pluggable `AuthScheme` interface** (Go): `Probe(ctx, client filesystem.FileSystemClient, share ShareTarget, id Identity) (ok`

`bool, evidence ProbeEvidence, err error)`. One implementation per type. New scheme = new struct registered in a registry (open/closed). This mirrors `universal_scanner.go`'s `ProtocolScanner` registry pattern (`universal_scanner.go:64-67`) for consistency.

- **Loader sources (precedence, §11.4.6 deterministic):** (1) `CATALOGIZER_IDENTITY_*` env via `digital.vasic.config/pkg/env` → seeds the identity table on boot; (2) identities added via UI/API at runtime; (3) the synthetic **`anonymous`** identity (priority 0, always tried first, no secret).
- **Secrets never logged** (§11.4.10): the table stores only `*_ref` handles; raw secrets live in `security/pkg/securestorage` (encrypted) or, on platforms with one, the OS keystore (see §2.6). Env-loaded secrets are read once, written to the secret store, and the env value is not echoed.

2.2 Discovery pipeline (anonymous-first, identity-fallback, remember)

```
[1 ENUMERATE HOSTS]  every interface × method:
     mDNS/Bonjour (discovery/pkg/broadcast) ∪ NetBIOS/WS-Discovery ∪ ARP/subnet
CIDR sweep
     (discovery/pkg/scanner) ∪ operator-configured static hosts
            │  → set of reachable Host{ip, hostname, ifaces}
[2 ENUMERATE SHARES per host per protocol]
     SMB: discovery/pkg/smb (445/139) → share list (REAL enumeration, NOT guessed
§1.1)
     FTP/NFS/WebDAV: connect + list root (extend discovery with per-protocol
probers)
            │  → set of ShareTarget{host, protocol, share/path, port}
[3 PROBE AUTH — anonymous-first, then identities by priority]
     for each ShareTarget:
        try anonymous → if mount+ReadDir(".") OK (positive evidence,
smb_discovery.go:209-221 pattern) → BIND
        else for each enabled Identity ordered by priority:
            AuthScheme.Probe(...) → first success → BIND, stop
        else → record UNAUTHENTICATED (honest, no guess)
[4 REMEMBER]
     persist working ShareBinding{share_target, identity_id, protocol, last_ok_at,
probe_evidence_path}
[5 REGISTER + INGEST]
     upsert a storage_roots row per bound share (credentials via identity ref, not
inline)
     → UniversalScanner.ScanJob → AggregateAfterScan → DuplicateDetection
```

Single-resource discipline (§11.4.119): probing is read-only and rate-limited (reuse discovery's semaphore); never write to a probed host. **Honest unreachable handling (§11.4.3/§11.4.6):** a host that does not answer is logged offline, never substituted with guessed shares (removes the `getCommonShares` guess path).

2.3 Persistence + reuse schema (new tables)

```
identities                (§2.1 — secrets as *_ref handles only)
discovered_hosts          (id, ip, hostname, first_seen, last_seen, reachable,
ifaces_json)
discovered_shares         (id, host_id FK, protocol, share_name/path, port,
first_seen, last_seen,
                           enumeration_evidence_path)
share_identity_bindings   (id, share_id FK, identity_id FK, status ∈
{ok,unauthenticated,failed,revalidating},
                           anonymous_ok bool, last_ok_at, last_attempt_at,
probe_evidence_path,
                           UNIQUE(share_id, identity_id))
   └─ binding → storage_roots: storage_roots gains nullable identity_id FK
(replaces inline user/pwd over time;
      migration keeps existing inline creds working, new shares use identity_id —
§11.4.124 no silent break)
```

- **Re-validation cadence (§11.4.128/§11.4.144):** a background follower re-probes each `ok` binding on a defined interval; on failure → `revalidating` → retry with the same identity, then re-run §2.2 step 3 (identity rotation). Drops logged honestly; never a silent stale "ok".
- **Identity rotation/failure:** changing an identity's secret invalidates dependent bindings → marked `revalidating`, not deleted (§11.4.124 investigate-before-remove).
- **`storage_roots` back-compat:** add `identity_id INTEGER NULL` + keep `username/password` columns during migration; resolver prefers `identity_id` when set, falls back to inline (so the existing `main.go:377-416` SMB-root query path keeps working until migrated).

2.4 Catalog extension — register, dedup, group

1. **Auto-register:** each `ok` `share_identity_binding` upserts a `storage_roots` row (`identity_id` set, `enabled=1`). Existing `UniversalScanner` + `AggregateAfterScan(storageRootID)` (`aggregation_service.go:60-67`) ingest unchanged.
2. **Duplicate tracking across shares:** feed scanned files to `DuplicateDetectionService` (`duplicate_detection_service.go`). Dedup

key precedence: **content hash** (`DuplicateItem.FileHash`) → **size** + **parsed-title** + **year/episode** fuzzy (existing Levenshtein/JaroWinkler stack) → external IDs. A title present on N shares becomes ONE `MediaItem` with N `origins[]` (each origin = `{storage_root_id, share_id, path}`).
3. **Grouping for browse:** `MediaItem` already groups files by title; extend its DTO with `origins[]` + `duplicate_count` + `available_on_shares[]` so the UI shows one card with a per-origin source picker (and a "duplicate" badge).
4. **Filter axes (new):** by host, by share, by protocol, by identity, by "has duplicates", by online/offline source — all derivable from the new tables joined to `files.storage_root_id`.

2.5 UI/UX per app (OpenDesign tokens, light+dark, no overlap — §11.4.162)

Three new surfaces, each app:

- **A. Identity Manager** — list/add/edit/remove identities; type selector (credentials / api_token / ssh_key / …); scheme-specific fields; **secrets masked** (show/hide), never rendered in plaintext logs or list views; priority ordering.
- **B. Discovered Shares** — grouped by host; per-share auth-status chip (`anonymous` / `via <identity>` / `unauthenticated`); "scan network" action; per-share enable/ingest toggle.
- **C. Grouped/deduped Browse** — existing catalog browse + duplicate badge + per-title origin/source picker + the §2.4 filters.

Per-app mapping:

- **Android TV / phone (Compose, Material3):** new `IdentityManagerScreen`, `DiscoveredSharesScreen` under `ui/screens/…`; re-use OpenDesign-aligned `Theme.kt`. D-pad focus order for TV (mirror `LoginScreen.kt` focus pattern). Extend `CatalogizerApi.kt` (Retrofit) with the new endpoints.
- **Web (React/Tailwind):** new pages under `src/pages/` + `identitiesApi` in `lib/api.ts`; **adopt OpenDesign tokens** (currently Tailwind-only — §11.4.162 gap to close).
- **Desktop (Tauri/React):** extend `SettingsPage.tsx` SMB section into the full identity/shares model; adopt OpenDesign tokens.

- **installer-wizard:** evolve `ConfigurationContext`'s `Access↔Source` split (already present) into the identity model so first-run setup seeds identities.

Backend API (new, under `/api/v1`): `GET/POST/PUT/DELETE /identities` · `POST /discovery/scan` (kick host+share sweep) · `GET /discovery/hosts` · `GET /discovery/shares` · `POST /discovery/shares/:id/probe` (anon-first+identity-fallback) · `GET /catalog/items?has_duplicates=&host=&share=&protocol=&identity=` (extend existing browse). Bearer-auth + RBAC via `internal/auth/middleware.go`.

2.6 Security (§11.4.10 throughout)

- Secrets never in `storage_roots`/`identities` rows as plaintext → `*_ref` handles into `security/pkg/securestorage` (encrypted at rest), or OS keystore where available (macOS Keychain / Linux Secret Service / Android Keystore / Windows DPAPI) — **§11.4.81 cross-platform parity** with honest fallback to the encrypted file store.
- **Migrate the existing plaintext `storage_roots.password`** into the secret store as part of the migration (existing data is a current §11.4.10 debt).
- Secrets masked in all UIs; redact host/user via `security/pkg/pii` before any log line; `.env` stays gitignored; identity secrets never git-versioned; probe logs store evidence **paths**, not secret bytes.
- `ssrf_guard.go` (`internal/services/ssrf_guard.go`) gates any host/URL the probe touches.

---

3. Phased Implementation Plan (PWUs — §11.4.58)

Each PWU ships four-layer coverage (§11.4.4(b)) + the §11.4.169 test-type matrix + captured physical evidence (§11.4.5/§11.4.69/§11.4.107). "Evidence" column = the anti-bluff artifact each test MUST capture. Audio/video N/A here; evidence is JSON probe results, DB row deltas, captured network traffic, screen renders.

PWU	Scope (files)	Test matrix (§11.4.169)	Mandatory captured evidence (anti-bluff)
P1 — Identity store + env loader	`catalog-api/internal/identity/*` (new), migration `00000X_identities`, `digital.vasic.config/pkg/env`, `security/pkg/securestorage` wiring; consume `CATALOGIZER_IDENTITY_*`	unit (scheme parse, precedence, masking), integration (env→DB seed, secret store round-trip), security (no plaintext secret in DB/logs — grep the row + log capture), stress (1000 identities), chaos (corrupt secret store → honest fail)	DB dump showing `secret_ref` not raw secret; log capture proving redaction; `go test` JSON; paired §1.1 mutation (strip masking → security test FAILs)
P2 — Discovery/probe engine	`catalog-api/internal/discovery/*` (new), reuse `submodules/discovery/pkg/{scanner,smb}`; replace `smb_discovery.go:140-175` guess-fallback with honest SKIP	unit (host parse, anon-first ordering, identity fallback order), integration (probe against a **containerized SMB/FTP/WebDAV** booted via `vasic-digital/containers` §11.4.76/§11.4.161), e2e (scan→bind), full-automation (re-runnable §11.4.98), security (SSRF guard, rate-limit), stress (concurrent multi-host), chaos (host drops mid-probe → §11.4.144 offline event)	captured probe `result.json` (per share: anonymous_ok / bound identity / unauthenticated); pcap or server-log proving real auth attempt; container boot log; mutation (force guess-fallback → test FAILs)
P3 — Remember/persistence + revalidation	migrations `discovered_hosts`/`discovered_shares`/`share_identity_bindings`; `storage_roots.identity_id`; follower goroutine	unit (binding state machine), integration (bind persists, re-probe path, rotation→revalidating), e2e (restart → bindings reused, no re-auth storm), stress (N bindings revalidate), chaos (SIGKILL mid-write → recover), concurrency/atomicity (UNIQUE(share,identity))	before/after DB snapshots; revalidation timeline log; mutation (drop UNIQUE → dup-binding test FAILs)
P4 — Catalog source registration + multi-source dedup/group	bind→`storage_roots` upsert; `UniversalScanner` ingest; extend `DuplicateDetectionService` for cross-share; `MediaItem.origins[]` DTO	unit (origin merge, dedup key precedence), integration (same title on 2 container shares → 1 item, 2 origins), e2e (scan two shares → grouped), full-automation, stress (large corpus), benchmark (dedup p95 vs baseline)	`result.json` showing 1 item / N origins + dedup confidence; query timing vs baseline; mutation (break hash-first dedup → duplicate-collapse test FAILs)

PWU	Scope (files)	Test matrix (§11.4.169)	Mandatory captured evidence (anti-bluff)
P5 — Backend API + RBAC	new `/identities`, `/discovery/*`, extended `/catalog/items` filters; `internal/auth/middleware.go`	unit (handlers), integration (auth required, RBAC), e2e (full REST flow), security (authz, injection, secret-leak in responses), DDoS/load (scan endpoint), API-readiness	HTTP transcript (request/response, secrets masked); 401/403 negative cases; mutation (drop auth → security test FAILs)
P6 — App UI: Identity Manager + Discovered Shares + Grouped Browse	per-app screens §2.5; OpenDesign tokens for web/desktop/phone	unit (components), UI-driven (§11.4.48), **host-side rendered-pixel visual proof (§11.4.170 Roborazzi/Paparazzi/Playwright) light+dark + OCR layout oracle**, e2e, full-automation (§11.4.143 real journey), accessibility (WCAG-AA)	rendered PNG per screen×state×{light,dark} + golden-diff + OCR no-overlap verdict; live-device recording (§11.4.159) MP4 + vision read; mutation (overlap inject → visual gate FAILs)
P7 — Wiring + full integration + HelixQA + Challenges	end-to-end glue; Challenge banks; HelixQA autonomous session	Challenges (anon-first + remember + dedup), HelixQA full session, full-suite retest (§11.4.40), chaos+stress aggregate	HelixQA `result.json` per bank; recorded autonomous session; §11.4.116 sync-channel event stream

Cross-cutting per PWU: §11.4.146 reproduce-first RED on the broken/absent state → same-test GREEN → extend-to-all-cases; §11.4.150 deep multi-angle research footer; §11.4.125/§11.4.142 independent review to clean GO (§11.4.134); §11.4.135 regression guard registered on every closure.

3.1 Operator-gated items (flag honestly, §11.4.3/§11.4.21)

- **Real LAN NAS to probe with the provided identities** — autonomous CI uses **containerized** SMB/FTP/NFS/WebDAV servers (§11.4.76) for deterministic proof; a **real Synology/NAS sweep** with `CATALOGIZER_IDENTITY_*` is `operator_attended` (needs the physical LAN + real hosts). NOT a faked PASS — a tracked migration item.
- **OS keystore on each platform** (Keychain/Secret Service/Android Keystore/DPAPI) — may need per-platform operator setup; honest fallback to encrypted file store meanwhile (§11.4.81).

- **NFS on macOS/Windows** — build-tag-gated today (`nfs_client_darwin.go`/`_windows.go`); per-OS parity needs validation (§11.4.81).

---

4. Open Questions for the Operator (§11.4.66)

1. **Protocol scope, first cut:** SMB is the only protocol with a discovery path today (`smb_discovery.go`). Do we ship **SMB-first** (P1–P5 SMB-only, then fan out FTP/NFS/WebDAV in P6+), or build all four probers up front? (Recommended: SMB-first — fastest to real evidence, lowest blast radius.)
2. **Real hosts on the LAN:** Is there a real Synology/NAS (or other SMB/NFS host) reachable on this LAN to probe with the `CATALOGIZER_IDENTITY_*` identities for §11.4.143/§11.4.159 live evidence, or do we rely solely on containerized servers for autonomous proof and mark real-NAS as `operator_attended`?
3. **Secret store:** OS keystore (Keychain/Secret Service/Android Keystore/DPAPI) per platform, or the `security/pkg/securestorage` encrypted file store as the single cross-platform default? (Recommended: encrypted file store as default, keystore as opt-in per §11.4.81.)
4. **Existing plaintext `storage_roots.password`:** confirm we migrate it into the secret store and null the plaintext column (one-time data migration, §11.4.10 debt repayment) vs. leave inline-cred shares as legacy.
5. **Anonymous-first safety:** any hosts where an anonymous mount attempt is undesirable (e.g., would trip an IDS/lockout)? Should anonymous probing be opt-out per host?
6. **OpenDesign rollout:** web/desktop/phone are Tailwind/Material-only today — confirm closing the §11.4.162 token gap is in-scope for this capability (Recommended: yes, P6).

---

5. Evidence Index (file:line anchors used above)

- Identity gap: `.env.example:46-65` (NAMES only) + zero `*.go` consumers
- Share model + creds: `catalog-api/models/file.go:48-70`; DB `database/migrations/000001_initial_schema.sqlite.up.sql:4-26`

- Existing SMB discovery + guess-fallback: `catalog-api/internal/services/smb_discovery.go:57-95,140-175,178-225`
- Discovery routes: `catalog-api/main.go:1267-1271`; multicast announce `main.go:771-795`; SMB root query `main.go:377-416`
- Protocol clients: `catalog-api/filesystem/interface.go:1-16`, `filesystem/factory.go:15-50`, `filesystem/smb_client.go:38-73`
- Scanner: `catalog-api/internal/services/universal_scanner.go:19-67`
- Aggregation: `catalog-api/internal/services/aggregation_service.go:60-67`
- Dedup: `catalog-api/internal/services/duplicate_detection_service.go:15-90`
- Creds read path: `catalog-api/handlers/scan_handler.go:294-308`, `handlers/copy.go:326`
- Owned submodules: `submodules/{discovery,auth,filesystem,security,database,config}/go.mod`
- App UIs: `installer-wizard/src/components/wizard/SMBConfigurationStep.tsx:26-478`, `installer-wizard/src/contexts/ConfigurationContext.tsx`; `catalogizer-desktop/src/pages/SettingsPage.tsx:24-114`; `catalog-web/src/pages/Settings.tsx:34-101` + `src/lib/api.ts`; `catalogizer-androidtv/.../ui/screens/login/LoginScreen.kt:224-270,538-583` + `ui/theme/Theme.kt` + `data/remote/CatalogizerApi.kt:14-49`

---

6. Sources verified (§11.4.150 — deep-research note)

Design synthesized from in-repo evidence (above) + owned-submodule capabilities. External protocol/standard cross-references (SMB share enumeration via `srvsvc`/IPC$, mDNS/WS-Discovery host enumeration, anonymous-bind semantics, OS keystore APIs) are **flagged for the per-PWU §11.4.150 deep-research pass** before implementation — this is a design/survey doc, not a closure; no implementation decision here is final until that pass cites latest authoritative sources. `NO external solution adopted yet — original composition of owned submodules`.