

README

digital.vasic.challenges

A generic, reusable Go module for defining, registering, executing, and reporting on challenges (structured test scenarios). Features a plugin-based architecture with built-in assertion evaluation, multi-format reporting, and live monitoring.

Installation

```
go get digital.vasic.challenges
```

Quick Start

```
package main

import (
    "context"
    "fmt"
    "log"

    "digital.vasic.challenges/pkg/assertion"
    "digital.vasic.challenges/pkg/challenge"
    "digital.vasic.challenges/pkg/registry"
    "digital.vasic.challenges/pkg/runner"
)

// Define a custom challenge
type HealthChallenge struct {
    challenge.BaseChallenge
}

func NewHealthChallenge() *HealthChallenge {
    return &HealthChallenge{
        BaseChallenge: *challenge.NewBaseChallenge(
            "health_check", "Health Check",
            "Verify all services are healthy", "core",
            nil,
```

```

    ),
}
}

func (c *HealthChallenge) Execute(ctx context.Context)
    (*challenge.Result, error) {
    result := c.CreateResult()
    result.Status = challenge.StatusPassed
    result.Assertions = []challenge.AssertionResult{
        {Type: "not_empty", Target: "response", Passed: true,
        Message: "Service responded"},
    }
    return result, nil
}

func main() {
    ctx := context.Background()

    // Register challenge
    reg := registry.NewRegistry()
    reg.Register(NewHealthChallenge())

    // Run all challenges
    r := runner.NewRunner(
        runner.WithRegistry(reg),
        runner.WithTimeout(5 * time.Minute),
    )

    results, err := r.RunAll(ctx, &challenge.Config{
        Verbose: true,
    })
    if err != nil {
        log.Fatal(err)
    }

    for _, res := range results {
        fmt.Printf("%s: %s (%v)\n",
            res.ChallengeName, res.Status, res.Duration)
    }
}

```

Features

- **Challenge framework:** Define, register, and execute structured test scenarios
- **Dependency ordering:** Automatic topological sort (Kahn's algorithm)
- **Assertion engine:** 16 built-in evaluators + custom evaluator support
- **Multi-format reports:** Markdown, JSON, HTML

- **Shell adapter:** Wrap existing bash scripts as challenges
- **Plugin system:** Extend with custom challenge types and assertions
- **Live monitoring:** WebSocket-based real-time dashboard
- **Prometheus metrics:** Built-in challenge metrics
- **Environment management:** Secure env var handling with redaction
- **Challenge banks:** Load definitions from JSON/YAML files
- **Parallel execution:** Run independent challenges concurrently
- **Infrastructure bridge:** Integrates with `digital.vasic.containers`
- **User flow automation:** Multi-platform testing across browser, mobile, API, gRPC, and WebSocket

User Flow Automation (pkg/userflow)

Multi-platform user flow automation framework with adapter-per-platform pattern.

Adapters (8 interfaces, 21 implementations)

Interface	Adapters	Technology
BrowserAdapter	PlaywrightCLI, PlaywrightHTTP, Selenium, Cypress, Puppeteer	CDP, W3C WebDriver, CLI
MobileAdapter	ADB, Appium, Maestro, Espresso	ADB, Appium 2.0, YAML flows, Gradle
DesktopAdapter	TauriCLI	Tauri WebDriver
APIAdapter	HTTPAPIAdapter	REST via pkg/httpclient
GRPCAdapter	GRPCCLIAdapter	grpcurl (unary + streaming)
WebSocketFlowAdapter	GorillaWebSocket	gorilla/websocket (thread-safe)
BuildAdapter	Gradle, Cargo, NPM, Robolectric	Build tool integration
RecorderAdapter	PanopticRecorder, ADBRecorder	CDP screencast, ADB

Challenge Templates (19 types)

APIFlowChallenge, BrowserFlowChallenge, MobileFlowChallenge, DesktopFlowChallenge, GRPCFlowChallenge, WebSocketFlowChallenge, BuildChallenge, TestRunnerChallenge, LintChallenge, MultiPlatformChallenge, plus Recorded variants with video verification.

Evaluators (12 userflow-specific)

http_status_ok, http_status_created, http_status_unauthorized, http_json_valid, browser_element_visible, browser_url_matches, mobile_activity_visible, mobile_element_exists, build_success, test_pass_rate, and more.

See docs/userflow/ for full adapter documentation and framework comparison.

Architecture

```
runner.Runner
├─ registry.Registry      (Challenge registration +
ordering)
├─ assertion.Engine      (16 built-in evaluators)
├─ report.Reporter       (Markdown/JSON/HTML)
├─ logging.Logger        (Structured logging)
├─ monitor.EventCollector (Live monitoring)
└─ plugin.PluginRegistry (Extensibility)

challenge.Challenge (interface)
├─ challenge.BaseChallenge (Template method base)
├─ challenge.ShellChallenge (Bash script wrapper)
├─ userflow.APIFlowChallenge (HTTP API flow testing)
├─ userflow.GRPCFlowChallenge (gRPC service testing)
├─ userflow.WebSocketFlowChallenge (WebSocket flow testing)
└─ [your custom challenges]

infra.InfraProvider
└─ ContainersAdapter      (Bridge to
digital.vasic.containers)
```

Built-in Assertion Evaluators

Evaluator	Description
not_empty	Value is non-nil and non-empty
not_mock	Response is not mocked/placeholder
contains	String contains substring (case-insensitive)

Evaluator	Description
contains_any	String contains any of the given values
min_length	String length meets minimum
quality_score	Numeric score meets threshold
reasoning_present	Response contains reasoning indicators
code_valid	Response contains valid code patterns
min_count	Count meets minimum
exact_count	Count matches exactly
max_latency	Response time within limit
all_valid	All array items are valid
no_duplicates	No duplicate items in array
all_pass	All sub-assertions pass
no_mock_responses	No mocked responses in array
min_score	Numeric minimum score

License

MIT