

# Changelog

All notable changes to the Claude multi-account toolkit.

## **v1.7.11 — 2026-06-28 — Round-4: coverage-gap regression tests, toon recursion guard, arg validation**

Fourth audit round: found the codebase is converging (export-docs, test harness, add/list/remove/rollback all verified clean); shipped 10 targeted coverage tests closing the same shallow-coverage class that let the v1.7.10 enable-plugins bug ship; plus 2 LOW code findings.

### **Fixed**

- **toon\_encode.py fallback\_encode**: unbounded recursion on deeply nested JSON. A crafted input with >1000 levels would blow Python's default stack and exit with an unhandled traceback instead of encoding. Added a `_depth` guard; beyond 64 levels emits compact JSON as a safe fallback.
- **toon.mjs encode-file / decode-file**: running `toon.mjs encode-file` with no argument produced a confusing `TypeError` from Node's `fs.readFileSync`. Now prints `Error: encode-file requires a filename argument + exit 1`.

### **Added — coverage-gap regression tests (the same class that let enable-plugins**

ship)

- **B9 (HIGH) — cma\_ensure\_alias\_file migration path** (`test_coverage.sh`): builds a realistic old `cma_run_provider()` body lacking `claude-sync-state`, calls `cma_ensure_alias_file`, asserts the body is migrated, the following `alias claude1=` survives, and `cma_run_provider()` appears exactly once.
- **B3 (HIGH) — \_cma\_q bash quoting in cma\_provider\_write\_env** (`test_coverage.sh`): sources a `.env` with a model name containing a literal single quote and asserts it round-trips intact; also asserts an injection payload does NOT execute on `source` (mirrors the already-tested Python `q()`).

- **B1 (HIGH) — absorb\_default\_plugins** (test\_unify.sh): creates a real plugin file under \$HOME/.claude/plugins/cache/ before unify; asserts it lands in \$SHARED\_DIR/plugins/cache/.
- **B2 (HIGH) — link\_default\_plugin\_subdirs** (test\_unify.sh): asserts \$DEFAULT\_DIR/plugins/cache becomes a symlink into \$SHARED\_DIR/plugins/cache after unify, and that re-running unify doesn't create a second backup.
- **B4 (MEDIUM-HIGH) — sync\_claude\_md seed branches** (test\_unify.sh): branch (b) seeds \$DEFAULT\_DIR/CLAUDE.md and asserts it wins; branch (c) removes it and gives an account a CLAUDE.md, asserts that one wins.

## Verified

- run-all.sh **10/10 ALL GREEN** (coverage now 39+10=49 assertions; unify now 43+7=50); **shellcheck 0**; all .py compile under python3 -W error; node --check toon.mjs clean; toon\_encode 500-level-nest no longer crashes; toon.mjs missing-arg gives clean error + exit 1.

## v1.7.10 — 2026-06-28 — Round-3 audit: enable-plugins bug fix, path-traversal guards, proxy robustness

Third audit round (deep dive on the less-covered surface: opencode\_sync, claude-unify merge, the poe proxy, bootstrap). Fixes verified centrally.

## Fixed

- **cma\_enable\_plugins silently enabled NO plugins when given 3 or more** (lib.sh). The jq --arg index was derived as \$ {#args[@]}/2, but each iteration appends **three** elements — so for the default 4 always-on plugins it produced arg names p0,p1,p3,p4 while the jq program referenced \$p0..\$p3; \$p2 was undefined, jq failed, 2>/dev/null swallowed the error, and enabledPlugins was left empty. Replaced the derived index with a dedicated counter. Proven live: cma\_enable\_plugins a b c d now yields all four true (was empty); a ≥3-plugin regression test was added.

## Security (defense-in-depth)

- **Path traversal via unvalidated provider id** in claude-providers.sh cmd\_show / cmd\_remove: \$id was interpolated into <dir>/\$id.env and then cat/rm -f'd without validation. Now

rejected unless it matches [A-Za-z0-9.\_-] (blocks ../),  
matching `cma_provider_write_alias`.

- **`opcode_sync.py`** `${CLAUDE_PLUGIN_ROOT}` **path traversal**: a malicious installed plugin could set an arg like `${CLAUDE_PLUGIN_ROOT}/../../../../tmp/evil.js` and `--enable-all-local` would have OpenCode exec the traversed path. Expansion now lexically contains the result to the plugin dir; an escaping value is left unexpanded (fails safe).
- **`cma_write_alias` now rejects whitespace in the config dir** (`lib.sh`): an unquoted space silently word-split the alias into a bogus command — now a clear error instead of a broken alias.

## Robustness

- **`poe_proxy.py`**: `resolve_refs` gained a recursion-depth guard (a circular `$ref` previously crashed the request handler with `RecursionError`); the success-path `gzip.decompress` is now guarded like the error path, so a corrupt gzip body no longer propagates.

## Verified

- `run-all.sh` **10/10 ALL GREEN** (coverage now 32 assertions incl. the enable-plugins + injection regressions); **shellcheck 0**; all `.py` compile under `python3 -W error`.
- `cma_enable_plugins` fix proven live (4 plugins → all true); `opcode` containment + id validation proven with PoCs. The model-verification / alias- write path is unchanged from v1.7.9's live-proven 137 models / 32 aliases.

## Audit (round 3) — verified clean

`cma_merge_claude_json` private-key isolation, eval-token provenance, `cma_validate_alias`, proxy bind (localhost only) + no key logging, `_cma_q` escaping, `merge_settings_json` atomic write, history dedup, rollback NUL-safe traversal, bootstrap `--dir-of` injection filter. (`opcode_sync --enable-all` intentionally bypasses the needs-secret guard — operator opt-in, documented.)

## v1.7.9 — 2026-06-28 — Hardening round 2: injection-safe alias writes, broadened secret redaction, docs accuracy, shellcheck 0

A second multi-agent audit + hardening pass on top of v1.7.8 (adversarial security audit + doc-accuracy audit + lint sweep, fixes verified centrally).

### Security

- **Provider id / config dir can no longer inject shell via the alias file** (`lib.sh cma_provider_write_alias / cma_write_alias`). Both interpolate values into `alias name="..."` lines that the shell **re-parses on invocation**, and `jq @tsv` does not escape `"`. They now reject shell metacharacters (provider id restricted to `[A-Za-z0-9._-]`; config dir rejects `" $ \ \ ; & | < > ( )` and newline). Proven: `afoo"; touch ...`` payload is rejected, no command runs, the hostile alias is never written.
- **Keys-file read no longer breakable by a quote in the path** (`claude-providers.sh cmd_sync_multi`). The old bash `-c "set -a; source '$keysf'; ..."` let a single quote in the keys-file path break out of the string. Replaced with an isolated subshell `( set +e; set -a +u; . "$keysf"; set +a; eval ... )` — the same safe pattern `cmd_sync` already used. Proven with a `do n't/ path`.
- **.env value quoting** (`providers_generate.py`): `q()` now POSIX single-quote-escapes embedded quotes (mirrors `lib.sh _cma_q`), so a catalog value containing a quote can't inject when `cma_run_provider` sources the `.env`. Proven: an injection payload is neutralized to a literal.
- **xtrace secret leak** (`lib.sh cma_run_provider`): the indirect key read is now wrapped in `set +x/restore` so an active `set -x` in the user's shell can't echo the key to the terminal or a redirected log.
- **Broadened secret redaction + guard**: `cma_redact_secrets()` (`verify_opencode_live.sh`) and the committed-proof scan guard (`test_lib.sh`) now also catch `sk-ant-`, `hf_`, `AIza`, `xoxb-/xoxp-/xoxs-`, `pc-`, `re_`, `secret_`, and JWTs — regardless of JSON field name — closing the gap where arbitrary MCP env-var names (e.g. `NOTION_API_KEY`) slipped through the original six-name allowlist.

### Fixed

- **install.sh used readlink -f** (absent on BSD/macOS) for its symlink up-to-date check — missed by the v1.7.7 sweep. Now uses `cma_realpath`; the `test_lib.sh` guard scans `install.sh` too.

- **verify\_aliases\_live.sh hardcoded one developer's account dirs**, producing false FAILs on every other host. Now discovers accounts dynamically and skips dirs that don't exist.
- Dead code / cruft: providers\_generate.py (unused import, dead vars, lambda→def, a no-op provider\_id + ('' if ... else '')); model\_verify.py (unused import hashlib); model\_verify.py docstring --key → CMA\_PROBE\_KEY.

## Docs

- Long-form doc + READMEs + CLAUDE.md corrected against the code: macOS rc-file caveat (~/.zshrc only), the test table now lists all 10 suites, the full installed-command list (+claude-providers/claude-sync-state/ claude-bootstrap), repo-relative paths (was ~/Documents/scripts/), a new claude-bootstrap section, the CMA\_PROBE\_KEY security model in §11, and a refreshed date stamp.

## Quality

- **shellcheck: 93 → 0** across all scripts. Added .shellcheckrc (external-sources=true) which resolves the sourced-file warnings properly; fixed the \$?-after-condition (SC2319) test idioms, SC2015/SC1090/SC1003; the one remaining reserved no-op flag carries a justified inline disable.

## Verified

- scripts/tests/run-all.sh **10/10 ALL GREEN; shellcheck 0**; every .py compiles under python3 -W error.
- Injection PoCs (provider id, config dir, .env value, keys-file path) all proven neutralized; broadened redaction proven against AIza/hf\_/JWT/etc.
- Live sync --multi: **137 models verified, 32 aliases** across 8 providers (opencode 4, poe 33, chutes 7, huggingface 6, nvidia 30, openrouter 14, siliconflow 38, xiaomi 5), zero CMA\_PROBE\_KEY/unbound errors — identical to the v1.7.8 baseline, so the new key-read path is non-regressive end-to-end.
- 4-host byte-parity + 10/10 suite re-verified after deploy.

## v1.7.8 — 2026-06-28 — Secret hygiene (argv + committed-proof leaks), dead-code fix, coverage tests

Security + robustness follow-up found by a parallel multi-agent audit of v1.7.7. Four independent subagents fixed disjoint file sets; integration + the full suite + live multi-model verification were run centrally.

### Security

- **API key no longer passed on argv** (model\_verify.py + claude-providers.sh). cmd\_sync\_multi invoked model\_verify.py --key "\$token", placing the secret verbatim in /proc/<pid>/cmdline and ps aux output — readable by any user on a multi-user host. The key now flows via the CMA\_PROBE\_KEY environment variable (set per-command, not exported); model\_verify.py reads it from the environment and errors clearly if unset. The --key flag is removed entirely.
- **API key no longer passed to curl on argv** (verify\_aliases\_live.sh). Six live-probe calls used -H "Authorization: Bearer \$key". The header is now written to a mktemp'd, chmod 600 config file consumed via curl --config (portable on GNU + BSD curl) and removed via an EXIT/INT/TERM trap.
- **Leaked secrets purged from committed proof artifacts** (committed in 24bc379, rolled into this release): the OpenCode live verifier wrote resolved opencode debug config / mcp list output — which contained a real provider key and a DB connection-string password — verbatim into the committed proof dir. The three artifacts are redacted; the generator (verify\_opencode\_live.sh) now redacts via cma\_redact\_secrets() before writing (raw dump → .raw temp → redacted file → .raw removed). **Operator follow-up still required:** rotate the leaked key and decide on a git-history scrub — the values remain in history on all four remotes.

### Fixed

- **Unreachable code** in verify\_aliases\_live.sh: exit \$failed sat *before* the Claude-alias test function and its caller, making them dead (shellcheck SC2317). exit \$failed moved to the final statement.
- **Fragile \$? capture** in test\_list.sh: grep ...; [[ \$? -ne 0 ]] then assert\_eq 0 \$? read \$? from the wrong command. Now captures rc=\$? immediately.
- **Unquoted glob** in claude-sync-state.sh:67: "\$HOME"/\${ACCOUNT\_PREFIX}prov-\* / → "\$HOME/\${ACCOUNT\_PREFIX}"prov-\* / so only the intended \* globs.

- **SyntaxWarning: invalid escape sequence '\ ' in** providers\_resolve.py: the usage docstring's \ line-continuations are now a raw string (r""").

## Added

- **test\_coverage.sh** — 11 new hermetic tests (19 assertions) covering previously-untested lib.sh behavior: cma\_ensure\_alias\_file (fresh / idempotent / old-format migration preserving unrelated lines), cma\_can\_prompt (CMA\_NONINTERACTIVE=1 and no-tty both non-interactive), cma\_enable\_plugins (JSON shape + additive + the jq // falsy-vs-null upgrade), cma\_link\_shared\_items (every CMA\_SHARED\_ITEMS entry becomes a symlink into \$SHARED\_DIR, idempotent), and stats-cache.json newest-by-mtime selection.
- **Proof regression guard** (test\_lib.sh): scans scripts/tests/proof for provider-key prefixes and URL user:password@ creds, counting suspect lines so a failure never re-echoes a secret.

## Verified

- scripts/tests/run-all.sh — **10/10 ALL GREEN** locally (was 9; +test\_coverage.sh).
- Live multi-model verification (claude-providers.sh sync --multi, real HTTP probes with the host's real keys): **137 models verified, 32 aliases generated** across 8 providers (opencode 4, poe 33, chutes 7, huggingface 6, nvidia 30, openrouter 14, siliconflow 38, xiaomi 5). Zero CMA\_PROBE\_KEY-unset and zero unbound variable errors — the env-var key path works end-to-end. (Providers with 0 verified are external: dead/paid keys, HTTP 401/402/403, WAF blocks — not toolkit regressions.)
- The new proof secret-scan guard immediately earned its keep: on first cross-host run it flagged a **stale, pre-redaction proof dir on all three remote hosts** (3 files with literal secrets), which were then re-synced with the redacted artifacts.
- model\_verify.py / providers\_resolve.py compile clean under python3 -W error.

## v1.7.7 — 2026-06-28 — Portable realpath (BSD portability hardening), set -u edge fix, regression tests

Follow-up hardening release found by a parallel multi-agent audit of v1.7.6.

## Fixed

- **readlink -f** → **portable cma\_realpath** at three sites: `claude-unify.sh` (already\_linked\_to\_shared and merge\_settings\_json) and `claude-list-accounts.sh` (the link check). `readlink -f` is absent on older macOS and on other BSDs (FreeBSD/NetBSD); there the checks silently fail — making `claude-unify` re-link every shared item on each re-run (accumulating stale `.preunify.*` backups) and `claude-list-accounts` report linked accounts as "not linked". **Honest scope:** modern macOS (Sequoia) and GNU coreutils DO support `readlink -f`, so on the current fleet this was a *latent* bug with no active symptom — but it broke the toolkit's stated BSD portability. Replaced with a new pure-bash `cma_realpath` (single-arg `readlink symlink-walk + pwd -P`), verified to produce output identical to `readlink -f` on macOS.
- **set -u empty-array edge in cma\_enable\_plugins** — `jq "$ {args[@]}"` with an empty `args` is an "unbound variable" error on bash 3.2 (reachable via `CMA_ALWAYS_ON_PLUGINS=""` from the non-re-exec'd `claude-providers.sh`). Guarded with `${args[@]+"${args[@]}"}`.

## Added

- **cma\_realpath** portable canonicalizer in `lib.sh`.
- **Regression tests** (`test_lib.sh`): `cma_realpath` resolves a symlink chain and is identity on a real path; plus a guard asserting NO runtime script *invokes* `readlink -f`.

## Verified

- `scripts/tests/run-all.sh` — **9/9 ALL GREEN on all four hosts:** nezha, thinker, amber (Linux), mistborn (macOS, re-exec to bash 5.3, BSD userland).
- `cma_realpath` output confirmed byte-identical to `readlink -f` on macOS.

## Audit findings (v1.7.6 — no code change required)

- Disabled providers are EXTERNAL, not toolkit bugs (toolkit correctly disabled them on failed verify): `github-models` → HTTP 401 (dead GitHub PAT), `upstage` → HTTP 403 from AWS WAF (egress-IP block).
- `api_keys.sh` across all 4 hosts: **0 dangling refs, 0 duplicates, 0 malformed**; key parity confirmed (mistborn's 2 host-local Kimi-Platform keys preserved).
- Cross-host integrity: all 11 toolkit scripts byte-identical to the released tag on every host.
- Known/deferred: published tags `v1.2.0` (gitlab) and `v1.5.0` (gitlab/gitverse/gitflic) point to older commits than local —



reconciling needs a force tag push; left for a maintainer decision.

## **v1.7.6 — 2026-06-28 — Always-non-interactive execution, alias-file integrity, macOS/bash-3.2 portability, 4-host rollout**

### **Fixed**

- **Alias-file corruption from a mis-firing migration** — `cma_ensure_alias_file`'s "outdated `cma_run_provider`" migration grepped for `claude-sync-state` pull, but the emitted on-disk text is `.../claude-sync-state` pull (a quote precedes the space), so the guard **never matched** and the migration fired on *every* alias write. Its `awk` then chopped everything from `cma_run_provider()` to EOF — destroying previously-written provider aliases and any `claudeN` aliases that follow the function block. This silently corrupted the alias file on multi-provider / multi-account hosts. Detection is now scoped to the function body and matches the bare command name (quote/space agnostic), and the migration removes **only** the function block, preserving alias lines. This was the single root cause of the failures across `test_providers.sh`, `test_claude.sh`, and `test_add_remove.sh`.
- **set -u abort while sourcing the keys file** — provider sync sourced `~/api_keys.sh` inside a `set -euo pipefail` subshell. A dangling reference in the user's keys file (e.g. `export SARVAM_API_KEY=$ApiKey_Sarvam_AI_India`) aborted the source **mid-file** under `nounset`, leaving every key defined *after* it unexported — so those providers silently failed verification ("unverified") and `stderr` was spammed with "unbound variable". Keys are now sourced with `nounset` disabled (subshell-local in sync; save/restore around the alias-file `cma_run_provider`). Installed alias files are auto-migrated to the `nounset-safe` wrapper on next sync.
- **macOS / bash-3.2 portability of the test harness** — `tests/run-all.sh` used `mapfile` (bash 4+), so the **entire suite failed to run on stock macOS**. Replaced with a portable read loop and guarded empty-array expansion under `set -u`. Same fix applied to `test_lib.sh` and `tests/lib/sandbox.sh` (empty `${arr[@]}` expansions are unbound on bash 3.2). The suite now runs green on macOS bash 3.2.

### **Added**

- **CMA\_NONINTERACTIVE + automatic TTY detection** — a new `cma_can_prompt` helper makes every prompt (`claude-add-account`,

claude-remove-account, claude-bootstrap) fall back to its non-interactive default whenever no terminal is available (CI, SSH without a PTY, the test sandbox) or when CMA\_NONINTERACTIVE=1 is exported. Toolkit execution is now **always non-interactive off a terminal**. Destructive account removal still refuses (rather than guessing) without --yes when it cannot confirm.

- **Regression tests** for non-interactive claude-add-account and for alias-line survival across repeated account adds.
- **test\_export.sh graceful SKIP** when its prerequisites (pandoc + a PDF engine) are absent — matching the existing SKIP convention for optional-dependency features.

## Multi-host rollout (nezha · mistborn.local · thinker.local · amber.local)

- Distributed ~/api\_keys.sh to every host via a **no-loss merge** (host-local keys preserved — e.g. mistborn kept its 2 Kimi-Platform keys; amber created fresh) and wired **both** .bashrc and .zshrc to source it on every host.
- Installed/updated the toolkit on all four hosts and configured claude1/claude2/claude3 on each; installed Claude Code on amber.
- Ran live provider/model detection on every host — **17-20 active providers each**, models verified via HTTP probes, **0 unbound errors**.

## Verified

- scripts/tests/run-all.sh — **9/9 files, ALL GREEN on all four hosts**: nezha (Linux), thinker (Linux), amber (Linux), mistborn (macOS / bash 3.2).
- Cross-host: both rc files source api\_keys.sh; claude1/2/3 + poe/deepseek/xiaomi aliases present on every host.

## v1.7.5 — 2026-06-28 — Cross-provider / resume session visibility fix

### Fixed

- **Cross-provider /resume session loss** — when switching between provider aliases (e.g., deepseek → opencode → kimi-for-coding), /resume would sometimes show empty session history. Root cause: the cma\_run\_provider function in the alias file was **missing sync-state pull/push calls** that were present in lib.sh. The alias file is what actually runs when a user invokes an alias, so the sync never happened.
- **Migration for outdated alias files** — added automatic detection and regeneration of outdated cma\_run\_provider

functions in `lib.sh`. If the function exists but lacks `claude-sync-state pull`, it's removed and rewritten with the correct implementation.

- **Router transport transformer config** — added `transformer: {use:["cleancache","streamoptions"]}` to the alias file's router transport section (was only in `lib.sh`), ensuring `cache_control` stripping works for all router-transport providers.

## Root Cause Analysis

The `cma_run_provider` function in `lib.sh` (lines 225-333) correctly includes `sync-state pull/push` calls, but the alias file's copy of the function was outdated and explicitly stated "cross-account `claude-sync-state` is intentionally NOT run." This meant:

1. Sessions created under provider A had their `lastSessionId` written only to A's `.claude.json`
2. When switching to provider B, B's `.claude.json` still had its own (different) `lastSessionId`
3. `/resume` read B's `lastSessionId` and couldn't find A's session

After fix: all providers/accounts share the same merged `lastSessionId` via `sync-state`.

## Verified

- **Local host:** all providers show identical `lastSessionId` after `sync` (confirmed)
- **mistborn.local:** 76 projects merged across all accounts/providers (confirmed)
- **Migration:** `install.sh` correctly detects and fixes outdated alias files on both hosts

## Tests

- Cross-alias session visibility (Section 5): **ALL PASS**
- Existing test suite: session-related tests pass

## v1.7.4 — 2026-06-26 — Kimi provider fix + AWS IaC MCP disabled by default

### Fixed

- **Kimi Code provider base URL** in `scripts/providers/overrides.json` — changed from `/coding/v1` to `/coding/` so native transport works correctly.
- **AWS IaC MCP timeout** — removed `aws-dev-toolkit/awsiac` from the default OpenCode MCP allowlist in `scripts/claude-`

opencode-sync.sh. The server consistently timed out on connection and is now configured but disabled by default.

## Changed

- Regenerated Claude\_Multi\_Account\_Fine\_Tuning.{html,pdf,docx} from current markdown.
- Refreshed proof artifacts in scripts/tests/proof/.

## Tests

- Local: **9/9 ALL GREEN**
- Live OpenCode verification: **9 passed, 0 failed**, 27/27 enabled MCPs connected
- Provider alias verification: **5 passed, 0 failed**

# v1.6.6 — 2026-06-21 — TOON integration for token-efficient prompts

## Added

- **TOON (Token-Oriented Object Notation)** integration — saves ~40% tokens vs JSON for structured data in LLM prompts by declaring fields once in arrays.
- **scripts/toon.mjs** — Node.js TOON utility (encode/decode/demo)
- **scripts/toon\_encode.py** — Python wrapper for TOON encoding
- **docs/TOON\_Integration.md** — comprehensive guide on using TOON with Claude Code
- **package.json** — @toon-format/toon v2.3.0 dependency

## Token Savings

- File listings: ~39% fewer tokens
- Tool definitions: ~40% fewer tokens
- User records: ~42% fewer tokens
- Accuracy: 76.4% (vs JSON's 75.0%)

## Note

TOON formats message CONTENT for token savings. API transport remains JSON (providers require it). HTTP/3 and compression require provider-side support.

## Tests

- 8/8 ALL GREEN

## v1.6.5 — 2026-06-21 — Poe proxy fix (alias file + install)

### Fixed

- **Poe proxy not starting from alias** — proxy logic was only in `lib.sh`, not in the alias file's `cma_run_provider` function. The alias file is what actually runs when a user invokes an alias. Added proxy detection + auto-start to the alias file.
- **install.sh: SHARE\_DIR → SHARED\_DIR** — wrong variable name caused unbound variable error on nezha (Linux, set -u).
- **install.sh: auto-copy proxy scripts** to `~/.local/share/.../proxy/` during install.

### Verified

- All 3 Poe aliases work: poe , poe2 , poe3 
- Deployed to both local host and nezha.local

## Tests

- 8/8 ALL GREEN

## v1.6.4 — 2026-06-21 — Poe proxy fix for tool compatibility

### Fixed

- **Poe tool format error** — Poe requires parameters in every tool function definition. Claude Code sometimes omits it (valid in Anthropic format, invalid for Poe). Added `poe_proxy.py` that auto-fixes tools before forwarding to Poe API.
- **Proxy auto-start** — `cma_run_provider` now auto-starts compatibility proxies for providers that need them (detected by `scripts/proxy/<provider>_proxy.py`).

### Verified

- All 3 Poe aliases work through proxy: poe , poe2 , poe3 

## Tests

- 8/8 ALL GREEN

## v1.6.3 — 2026-06-21 — Poe provider (382 models, 3 aliases)

### Added

- **Poe provider** — universal AI platform with 382 models from all major providers. OpenAI-compatible API at <https://api.poe.com/v1>. Chat, code, image gen, video gen, TTS, STT, and more.
- **3 aliases**: poe (claude-sonnet-4.6 + gpt-5.4-mini), poe2 (gpt-5.5 + deepseek-v4-pro-e), poe3 (grok-4 + gemini-3.1-pro)
- **key-aliases**: POE\_API\_KEY + ApiKey\_Poe → poe
- **Tool calling verified** on claude-sonnet-4.6, gpt-5.4-mini, deepseek-v4-pro-e, grok-4
- **382 models categorized**: 130 chat/reasoning, 16 code, 40 image gen, 17 video gen, 12 TTS, 1 STT, 166 other
- **Documentation**: full Poe section in Provider\_Aliases\_User\_Guide.md

### Verified

- API endpoint responds correctly
- Authentication works
- Tool calling confirmed
- All 3 aliases tested through ccr with "Do you see our codebase?" — all YES

## v1.6.2 — 2026-06-21 — Chutes provider documentation + model update

### Changed

- **Chutes provider models updated** — catalog was stale. Chutes now offers 13 TEE (Trusted Execution Environment) models. Updated strong=zai-org/GLM-5.2-TEE, fast=Qwen/Qwen3.6-27B-TEE.
- **Chutes documentation** added to Provider\_Aliases\_User\_Guide.md with full model table, TEE explanation, pay-per-use note, and setup instructions.

## Verified

- Chutes API endpoint responds correctly
- All 13 TEE models accessible (require funded account for actual inference)
- OpenAI-compatible format confirmed at <https://llm.chutes.ai/v1>

## v1.6.1 — 2026-06-21 — cache\_control fix + E2E tests

### Fixed

- **cache\_control parameter error** — Claude Code sends `cache_control` (Anthropic-specific) in its API requests. ccr forwarded this to OpenAI-compatible endpoints which reject it with HTTP 422. Fixed by adding ccr's built-in `clean_cache` transformer to every provider config, which strips `cache_control` before forwarding to the provider.

### Added

- **alias\_e2e\_test.py** — end-to-end alias verification script that tests each alias by sending requests through ccr and verifying responses work without errors.

## Verified working (all aliases tested with "Do you see our codebase?")

- `opcode` (north-mini-code-free):  YES
- `opcode2` (big-pickle):  YES
- `opcode3` (nemotron-3-ultra-free):  YES
- `deepseek` (native transport):  YES
- `deepseek2` (router transport):  YES
- `xiaomi` (native transport):  YES
- `zai-coding-plan` (router transport):  YES

## v1.6.0 — 2026-06-21 — Multi-alias provider system

### Added

- **Multi-alias provider system** — every provider can now have multiple aliases (`provider`, `provider2`, `provider3`...) exposing ALL

working models, not just the top 2. Verified via live HTTP probes with anti-bluff detection.

- **model\_verify.py** — comprehensive model verification & scoring engine. Tests every model for a provider via HTTP probes, scores on 7 dimensions (existence 25pts, tool\_call 20pts, reasoning 15pts, context\_window 15pts, streaming 10pts, latency 10pts, free\_tier 5pts). Anti-bluff detection prevents false positives (HTTP 200 with error body, empty responses, boilerplate errors). 24h verification cache to avoid re-testing.
- **providers\_generate.py** — multi-alias generation from verified models. Pairs models into alias groups of 2 (strong + fast), handles odd count (last model reused for both positions), single model (used for both positions). Generates env files, shell aliases, and overrides.json entries.
- **claude-providers.sh --multi** — new flag for sync that triggers the full verification + multi-alias generation pipeline. Additional flags: --max-aliases (default 5), --min-score (default 25), --verify-concurrency (default 5).
- **Endpoint normalization** — /anthropic endpoints auto-converted to /v1 for OpenAI-compatible probing during verification.
- **Submodules updated** to helix\_translate-2.3.1: LLMsVerifier (ModelVerifier, Seed, xiaomi provider), challenges (anti-bluff §11.4, chaos/stress tests), containers (deploy-stack).

## Changed

- Probe max\_tokens increased from 32 to 128 — reasoning models need more tokens for chain-of-thought + response (was causing false anti-bluff rejections).
- User-Agent header added to HTTP probes (some APIs require it).

## Full test suite

- 8/8 test files passed (ALL GREEN), 0 failures.

## Usage

```
# Standard sync (2 models per provider, as before)
claude-providers sync
```

```
# Multi-alias sync (verify ALL models, create multiple aliases)
claude-providers sync --multi
```

```
# With options
claude-providers sync --multi --max-aliases 10 --min-score 20
```



## v1.5.1 — 2026-06-20 — Linux stat fix + nezha deployment

### Fixed

- **stat -f %m on Linux** — the mtime cache check in `claude-providers.sh` used `stat -f %m || stat -c %Y` as an `||` chain. On Linux, `stat -f` succeeds (returning filesystem info, not mtime), so both outputs merged into garbage ("File: ...1781634386"), causing File: unbound variable under `set -u`. Fixed with case "\$(`uname -s`)" to pick the correct flag per platform.

### Deployment

- **nezha.local** (Linux x86\_64) deployed and verified: 19 providers activated, 100/100 provider tests pass, 5/5 live verifier pass, cross-alias sync confirmed. Evidence in `scripts/tests/proof/90-nezha-deployment.txt`.

### Full test suite

- macOS: 8/8 ALL GREEN
- Linux (nezha): 7/8 pass (export fails: pandoc not installed — pre-existing)

## v1.5.0 — 2026-06-20 — Cross-alias session visibility

### Added

- **Cross-alias session visibility** — sessions created under ANY alias (claudeN, deepseek, opencode, xiaomi, etc.) are now visible from every other alias via `/resume`. Memory, project settings, and session data are fully shared across all accounts and providers.
- **claude-sync-state.sh extended** — now discovers provider dirs (`~/.claude-prov-*`) alongside account dirs for its `.claude.json` merge. Provider sessions participate in the same lightweight `jq` merge that keeps account sessions in sync.
- **cma\_run\_provider sync-state hooks** — the provider wrapper now calls `claude-sync-state pull` before launch and `claude-sync-state push` after exit, matching the `cma_run` pattern. Previously provider sessions were intentionally excluded from sync; now they participate fully.
- **Sandbox test coverage**: 10 new assertions proving cross-alias merge (sessions from account→provider,

provider→account, account→account all visible after sync).

Providers test 90 → 100 assertions.

- **Live verification:** lastSessionId for a real project confirmed identical across all dirs (3 accounts + 1 provider). 61 projects merged in every .claude.json. Evidence in scripts/tests/proof/80-cross-alias-sessions.txt.

## Changed

- scripts/claude-sync-state.sh — provider dirs included in merge targets
- scripts/lib.sh — cma\_run\_provider wrapper updated with sync-state pull/push
- Alias file aliases.sh — updated cma\_run\_provider function (re-installed)

## Full test suite

- 8/8 test files passed (ALL GREEN), 0 failures. Providers test includes 10 new assertions for cross-alias session visibility.

## How it works

1. claude-sync-state pull merges every account's + provider's .claude.json into the launching dir before Claude Code starts (including lastSessionId, allowedTools, MCP config, etc.).
2. Claude Code launches with the merged state — /resume sees all sessions.
3. claude-sync-state push merges the post-session .claude.json back out after exit, so the next alias to launch picks up the new session.
4. The sessions/ directory was already shared via symlink — this release ensures .claude.json project settings are also merged.

## Performance

- Adds ~1-2 seconds overhead per provider launch (jq merge of .claude.json across all dirs). Same overhead that claudeN aliases already have.

# v1.4.0 — 2026-06-20 — OpenCode Zen provider alias

## Added

- **opencode provider alias** — OpenCode Zen curated AI gateway with **21 free models** (all \$0 cost, all support tool calling +

reasoning) and 49 paid models. The alias uses **router transport** (ccr) targeting the OpenAI-compatible endpoint <https://opencode.ai/zen/v1/chat/completions>.

- **Model overrides:** strong = big-pickle (free stealth model, 200K context, reasoning + tool\_call), fast = deepseek-v4-flash-free (free, 200K context, reasoning + tool\_call). Pinning is deliberate — auto-selection would pick nemotron-3-ultra-free (1M ctx) as strong and trinity-large-preview-free (131K, no reasoning) as fast, both suboptimal for coding workloads.
- **key-aliases.json mappings:** ZEN\_API\_KEY → opencode and ApiKey\_Opencode\_Zen → opencode (both key vars present in the user's keys file).
- **overrides.json pin:** strong\_model=big-pickle, fast\_model=deepseek-v4-flash-free (no transport/base\_url override needed — catalog values are correct).
- **Sandbox test coverage:** resolver tests (key-alias mapping for both key vars, router transport from @ai-sdk/openai-compatible npm, zen/v1 base\_url from catalog, model override beats auto-selection, stale-model-never-selected guards) + sync e2e tests (env file, alias, config-dir + plugins symlink, account-detection exclusion, idempotency, no-secret-leak). Providers test 69 → 90 assertions.
- **Live endpoint verification:** GET /v1/models HTTP 200; POST /v1/chat/completions round trip HTTP 200 with correct text for big-pickle (stealth, cost=\$0, reasoning\_content present) and deepseek-v4-flash-free (cost=\$0); additional free models (mimo-v2.5-free, nemotron-3-ultra-free, north-mini-code-free) all HTTP 200 with cost=\$0. Evidence in scripts/tests/proof/70-zen-live.txt (secret-free).
- **Docs:** dedicated opencode section in docs/ Provider\_Aliases\_User\_Guide.md (full free models table, setup, usage, live-verified notes, stealth model explanation).

## Changed

- scripts/providers/key-aliases.json and scripts/providers/overrides.json extended with the opencode entries (config-only; no code changes — same dynamic pattern as Xiaomi v1.3.0 / Z.AI v1.2.0 / DeepSeek).

## Full test suite

- 8/8 test files passed (ALL GREEN), 0 failures. Providers test includes 21 new assertions for opencode.

## Honest notes

- The alias uses router transport (ccr) because Zen's free models use OpenAI-compatible format (/v1/chat/completions), not

Anthropic native format. This adds a ccr dependency that native-transport aliases (deepseek, xiaomi) don't have.

- Big Pickle is a stealth model — the actual model served may vary (observed as deepseek-v4-flash). This is by design per OpenCode's documentation.
- The same pre-existing `~/api_keys.sh set -u` issue affects the in-process verifier for all providers; authoritative proof is the direct HTTP round trip.
- The 2 pre-existing, environmental `opencode-skill-discovery` failures in `run-proof.sh` remain unchanged (unrelated to this work).

## v1.3.0 — 2026-06-19 — Xiaomi MiMo provider alias

### Added

- **xiaomi provider alias** — Xiaomi MiMo via the **Anthropic-native endpoint** `https://api.xiaomimimo.com/anthropic` (POST `/anthropic/v1/messages`). Unlike most providers in this toolkit, MiMo exposes a genuine native Anthropic endpoint that accepts `Authorization: Bearer`, so the alias uses **native transport** with no `claude-code-router (ccr)` dependency — the same direct-launch model as deepseek.
- **Model overrides**: `strong` = `mimo-v2.5-pro` (flagship, 1M context, reasoning, tool-call), `fast` = `mimo-v2-flash` (256K, cheapest tier). Pinning is deliberate — `models.dev` lists a `mimo-v2.5-pro-ultraspeed` id the **live API does not serve**, so the override guarantees only live-served ids are used.
- **key-aliases.json mapping**: `XIAOMI_MIMO_API_KEY` → `xiaomi` (the user's key-var name does not match the `models.dev` provider's documented `XIAOMI_API_KEY` env).
- **overrides.json pin**: `native transport`, `/anthropic base_url`, `mimo-v2.5-pro / mimo-v2-flash`.
- **Sandbox test coverage**: resolver tests (key-alias mapping, override forces native transport, `/anthropic base_url` beats `catalog /v1`, model pinning beats the stale `ultraspeed` entry, `stale-id-never-selected` guard) + sync e2e tests (env file, alias, config-dir + plugins symlink, account-detection exclusion, idempotency, no-secret-leak). Providers test 60 → 69 assertions.
- **Live endpoint verification**: GET `/v1/models` HTTP 200 (10 models); native `/anthropic/v1/messages` round trip HTTP 200 with correct text for both `mimo-v2.5-pro` and `mimo-v2-flash`; tool calling proven (`finish_reason: tool_calls`
  - `reasoning_content`); streaming confirmed. Evidence in `scripts/tests/proof/60-xiaomi-live.txt` (secret-free).

- **Docs:** dedicated xiaomi section in docs/ Provider\_Aliases\_User\_Guide.md (model table, setup, usage, live-verified notes).

## Changed

- scripts/providers/key-aliases.json and scripts/providers/overrides.json extended with the xiaomi entries (config-only; no code changes — same dynamic pattern as Z.AI v1.2.0 / DeepSeek).

## Full test suite

- 8/8 test files passed (ALL GREEN), 0 failures. Providers test includes 9 new assertions for xiaomi. Live provider verifier 5/5 PASS.

## Honest notes

- The only failures in the repo's run-proof.sh are 2 **pre-existing, environmental** opencode-skill-discovery checks, unrelated to Xiaomi (zero opencode files changed by this release; they fail identically when run standalone).
- The in-process LLMsVerifier step reports (unverified) for every provider because ~/api\_keys.sh has a pre-existing unrelated unbound variable on a different provider's key under set -u; authoritative proof is the direct native-endpoint round trip (HTTP 200), recorded in the evidence file.

# v1.2.0 — 2026-06-19 — Z.AI Coding Plan provider alias

## Added

- **zai-coding-plan provider alias** — OpenAI-compatible router transport via https://api.z.ai/api/coding/paas/v4 (Coding Max-Yearly Plan endpoint).
- **Model overrides:** strong = glm-5.2 (flagship 1M context reasoning model, free on plan), fast = glm-4.7 (204k context, tool\_call, 0 cost).
- **key-aliases.json mapping:** ZAI\_API\_KEY → zai-coding-plan (targets the coding plan API endpoint instead of the general z.ai paas endpoint).
- **overrides.json pin:** overrides auto-selected strong/fast models for the coding plan.

- **Sandbox test coverage:** resolver tests (env-key matching, coding endpoint, router transport, glm-5.2/glm-4.7 model selection) + sync e2e tests (env file, alias, model overrides).
- **Live endpoint verification:** HTTP 200 at /models (8 models discovered), curl test of glm-4.7 chat completion confirmed operational.
- **ccr integration:** provider auto-registered in ~/.claude-code-router/config.json as the active default route.

## Changed

- overrides.json extended with zai-coding-plan section for model pinning.

## Full test suite

- 8/8 test files passed (ALL GREEN), 0 failures. Provider tests include 5 new assertions for zai-coding-plan.

# v1.1.0 — 2026-06-16 — Distributed infrastructure + provider verification

Headline: stand up the full LLMsVerifier System on a remote host for heavy testing against **real production LLM services**, plus end-to-end provider aliases proven on two hosts and two transports.

## Added

- **containers + challenges submodules** (submodules/) — the distributed-boot orchestrator and its sibling. helix-deps.yaml confirms containers has zero own-org submodule deps.
- **Remote host registration** — config/containers/nezha.env registers nezha.local as a remote boot/test host (SSH key, podman runtime).
- **LLMsVerifier deployment overlays** (config/containers/llmsverifier/):
  - docker-compose.app.yml — the llm-verifier API (cgo image, config mount, /api/health healthcheck, loopback, fail-fast secrets).
  - docker-compose.infra.yml — observability tier: prometheus + grafana (auto-provisioned datasource + dashboard) + node-exporter. **No DBs** (the app uses SQLite; postgres/redis were unused and removed).
  - Dockerfile.nezha / Dockerfile.mv — cgo nested-module builds for the server + the model-verification tool.
  - patches/0001..0005 — upstream LLMsVerifier fixes (see PR #2 below).

- **Deployment guide** config/containers/llmsverifier/README.md and the **Provider Aliases User Guide** docs/Provider\_Aliases\_User\_Guide.md (HTML/PDF/DOCX exports included).
- **QA evidence** docs/qa/20260616-infra/ — verification proofs, endpoint coverage, security posture, observability, per-provider sweeps, dual-host end-to-end alias proofs.

## Changed

- **Provider session accent color: orange → purple** across spec, guide, and the long-form doc. (Claude Code 2.1.178 cannot persist a default /color, so this is the documented default + a manual /color purple — a platform limit.)
- `claude-add-account` consolidated onto the shared `cma_link_shared_items` helper (single `CMA_SHARED_ITEMS` source).
- `claude-export-docs` now also emits **DOCX** (HTML/PDF/DOCX).

## Fixed (LLMsVerifier — shipped as PR #2, applied to deployed builds)

- **Auth header missing** — verification requests sent no Authorization header → HTTP 401 for every provider. Now Bearer <key>.
- **cohere 405** — switched to the OpenAI-compatible endpoint (`api.cohere.ai/compatibility/v1`). Verifies at score 1.00.
- **gemini / huggingface** — corrected to OpenAI-compatible / router endpoints (huggingface verifies; gemini code-ready pending a valid key).
- **model-id strictness** — verifies a requested id directly when not in the discovered list (no premature `model_not_found`).
- **no /metrics** — added GET `/api/metrics` + `/metrics` (stdlib Prometheus).
- **provider-session sync-state noise** — `cma_run_provider` no longer runs cross-account sync-state on isolated provider dirs.

## Verified live (real "Do you see my code?" against production APIs)

- **9 providers verified:** DeepSeek, Groq, Mistral, Cerebras, Novita, NVIDIA, Cohere, Codestral, HuggingFace.
- **Both transports, both hosts:** native (DeepSeek) + router (Novita via ccr) on macOS and on nezha.
- Account-side failures (402/401/429/403) and non-OpenAI providers documented honestly; excluded under "valid users only" but kept fully supported.

## Safety

- Provider dirs (~/.claude-prov-\*) excluded from account detection — existing claudeN accounts and claude-add-account untouched.
- Secrets only in the keys file + on-host mode-600 .env; never in the repo. All published ports bound to loopback.

## v1.0.0 — 2026-06-16 — Dynamic provider-alias generator

First tagged release. claude-providers creates per-provider Claude Code aliases (DeepSeek, Groq, GLM, ...) from your keys file pointed at each provider's strongest model — fully dynamic via models.dev + the LLMsVerifier submodule, hybrid native/claude-code-router transport, full lifecycle + tests + docs. See docs/Provider\_Aliases\_User\_Guide.md.

## v1.6.7 — 2026-06-21 — Poe proxy fix for all aliases

### Fixed

- **Poe proxy not starting for poe2/poe3** — proxy detection used exact provider ID (poe2\_proxy.py) which doesn't exist. Fixed to check base name too (poe\_proxy.py for poe2, poe3 aliases).
- **lib.sh**: base proxy detection with \${CMA\_PROVIDER\_ID%%[0-9]\*}
- **alias file**: same fix applied

### Verified

- All 3 Poe aliases work: poe , poe2 , poe3 
- Deployed to both local host and nezha.local

### Tests

- Local: 8/8 ALL GREEN
- nezha.local: 7/8 (pandoc missing — pre-existing)



## v1.6.8 — 2026-06-21 — Poe proxy gzip fix

### Fixed

- **Poe proxy gzip decompression** — Poe API returns gzip-compressed responses but the proxy tried to read them as UTF-8 without decompressing, causing UnicodeDecodeError. Added gzip decompression for both success and error responses.

### Verified

- poe (claude-sonnet-4.6):  YES
- poe2 (gpt-5.5):  YES
- poe3 (grok-4):  Different error (Grok-4 schema validation, not tools format)

### Tests

- Local: 8/8 ALL GREEN
- nezha.local: 8/8 ALL GREEN

## v1.6.9 — 2026-06-21 — Poe proxy \$ref fix for Grok-4

### Fixed

- **Poe proxy \$ref resolution** — Claude Code sends tool schemas with \$ref references to \$defs. Grok-4 and some providers don't support \$ref in tool schemas. Added resolve\_refs() function that extracts \$defs, resolves all \$ref references to inline definitions, and removes \$defs.

### Verified

- poe (claude-sonnet-4.6):  YES
- poe2 (gpt-5.5):  YES
- poe3 (grok-4):  YES (was failing, now works)

### Tests

- Local: 8/8 ALL GREEN
- nezha.local: 8/8 ALL GREEN

## v1.7.0 — 2026-06-22 — Poe proxy complete fix (all aliases verified)

### Fixed

- **Poe proxy shared directory** — the proxy at ~/.local/share/.../proxy/poe\_proxy.py was the OLD version without gzip and \$ref fixes. install.sh copies from scripts/ but the shared dir still had the old version. Fixed by ensuring updated proxy is copied to shared directory.
- **install.sh** now copies proxy scripts during installation (already in place)

### Verified (all three aliases through full Claude Code flow)

- poe (claude-sonnet-4.6):  YES
- poe2 (gpt-5.5):  YES
- poe3 (grok-4):  YES

### Root Cause Analysis

The proxy had three issues:

1. **gzip** — Poe returns gzip-compressed responses, proxy didn't decompress
2. **\$ref** — Claude Code sends tool schemas with \$ref, Grok-4 doesn't support them
3. **shared dir** — Updated proxy wasn't copied to shared directory

All three fixed and verified.

### Tests

- Local: 8/8 ALL GREEN
- nezha.local: 8/8 ALL GREEN

## v1.7.1 — 2026-06-22 — Full validation + release

### Fixed

- **Port-ready check** for proxy startup — replaced sleep 1 with polling loop (lsof -i) ensuring proxy is listening before ccr config is written

- **Claude alias regression test** — 11 assertions proving claudeN aliases use cma\_run (no proxy/transformer code), providers use cma\_run\_provider
- **Command injection fix** in verify\_aliases\_live.sh — replaced `bash -c` subshell with safe indirect expansion

## Tests

- Local: **9/9 ALL GREEN** (new: test\_claude.sh — 11 assertions)
- nezha.local: 8/9 (export fails — pandoc missing)

## Release

- v1.7.1 — pushed to github, gitlab, gitflic, gitverse

# v1.7.2 — 2026-06-22 — Claude alias verification, full release

## Added

- **Claude alias verification** in verify\_aliases\_live.sh — tests claude1/2/3 alongside provider aliases
- **TOON tested** on all aliases — verified working

## Tests

- Local: **9/9 ALL GREEN**
- nezha.local: 8/9 (pandoc missing)
- All claude1/2/3:  OK
- All provider aliases: verified