Claude Multi-Account Fine Tuning

Running multiple Claude Code accounts on one host with shared history, memory, and settings

milos85vasic

2026-07-27

Claude Multi-Account Fine Tuning

1. Motivation
2. How Claude Code stores state
3. Architecture after fine-tuning
4. Reproducing this on any host
   - 4.0 Clean-slate host: `claude-bootstrap`
   - 4.1 Prerequisites
   - 4.2 Lay down the scripts directory
   - 4.3 Run the installer
   - 4.4 Add a third (or fourth, ...) account
   - 4.5 Verify the result
   - 4.6 Rollback if needed
5. Operational notes
   - 5.1 Concurrent use of two accounts
   - 5.2 Plugin path rewriting
   - 5.3 Adding a new account from scratch (no existing dir)
   - 5.4 Removing an account
   - 5.5 Backups created during install
6. Cross-platform reproduction
   - Linux
   - macOS
   - WSL / Windows Subsystem for Linux
7. Tests
   - 7.1 Running the suite
   - 7.2 What each test covers
   - 7.3 How the test harness works
   - 7.4 Adding a new test
8. The complete script source
   - 8.1 `lib.sh`
   - 8.2 `claude-unify.sh`
   - 8.3 `claude-add-account.sh`
   - 8.4 `claude-remove-account.sh`

8.5 `claude-list-accounts.sh`
8.6 `claude-rollback.sh`
8.7 `claude-export-docs.sh`
8.8 `install.sh`
8.9 `tests/lib/assert.sh`
8.10 `tests/lib/sandbox.sh`
8.11 `tests/run-all.sh`
8.12 `tests/test_lib.sh`
8.13 `tests/test_unify.sh`
8.14 `tests/test_add_remove.sh`
8.15 `tests/test_list.sh`
8.16 `tests/test_export.sh`
11. Provider aliases — running other LLMs through Claude Code
Data flow (nothing hardcoded)
Model tier — strongest paid if funded, strongest free if not
Transports
Router selector semantics — the `/` that killed 16 of 24 aliases
Token-limit guards — the arithmetic, and which direction is dangerous
HelixAgent: a local GPU backend, and why auto-start is opt-in
Safety
Commands
Session color — auto-applied (v1.10.0)
12. Per-project auto-session & per-alias color
13. TOON utility
14. Authoring rule: the generated alias file is self-contained
15. Dependencies and their pins
16. Kimi Code: accounts and the family model
16.1 The namespace contract
16.2 Kimi accounts
16.3 `kimi-<id>` provider aliases
16.4 Legacy rename (`kimi-*` → `kc-*`)

Claude Multi-Account Fine Tuning

Corresponds to toolkit release `claude_toolkit-1.26.7`.

This document captures, in reproducible detail, how a single host can run multiple Claude Code accounts (e.g. `claude1`, `claude2`, …, `claudeN`) while sharing conversation history, project memory, todos, plans, plugins, and settings between them. Only account identity (`.credentials.json`, `.claude.json`, MCP auth cache) is kept private per account.

Companion artifacts:

- `scripts/` in this repository — the automation scripts, and the source of truth for the procedure described here. (Earlier revisions of this document pointed at `~/Documents/scripts/`; that was the author's pre-repo location and is no longer correct.)
- `Claude_Multi_Account_Fine_Tuning.html` — same content as this file, rendered as a standalone HTML page.
- `Claude_Multi_Account_Fine_Tuning.pdf` — same content, paginated PDF.
- `Claude_Multi_Account_Fine_Tuning.docx` — same content, Word format.

All three siblings are regenerated by `claude-export-docs.sh`, so editing the markdown is the only place changes need to be made:

```
MD_FILE="$PWD/Claude_Multi_Account_Fine_Tuning.md" bash scripts/
        claude-export-docs.sh
```

The `MD_FILE` override matters: the script's default is `$DOC_DIR/Claude_Multi_Account_Fine_Tuning.md` with `DOC_DIR` defaulting to `~/Documents`, so a bare invocation inside the repo renders the wrong copy.

---

1. Motivation

The Claude Code CLI is invoked as `claude`. By default it writes all of its state — credentials, conversation transcripts, project memory, todos, plans, plugin installs, settings — under a single config directory (`~/.claude` on Linux/macOS).

When you want to use **multiple Anthropic accounts** (for example, one personal Max subscription and one team/work account), you typically run two separate config dirs and switch between them with an environment variable:

```
# ~/.bashrc (before this setup)
export CLAUDE_BIN="$HOME/.local/bin/claude"
alias claude1="CLAUDE_CONFIG_DIR=$HOME/.claude-milos85vasic
        $CLAUDE_BIN"
alias claude2="CLAUDE_CONFIG_DIR=$HOME/.claude-milos85vasic2nd
        $CLAUDE_BIN"
```

That works for isolation, but the two accounts now have **completely separate** project memory, history, todos, and plugin sets. Switching accounts means losing the working context you built up under the other.

Goal: keep the two-alias UX (cheap account switch) while ensuring both accounts read and write the same project memory, conversation transcripts, todos, plans, plugins, and settings.

---

2. How Claude Code stores state

Every key piece of state lives under the directory pointed at by `CLAUDE_CONFIG_DIR` (with `~/.claude` as the default). Items fall into three categories:

Category	Path under `CLAUDE_CONFIG_DIR`	What it is
Identity (private)	`.credentials.json`	OAuth tokens for the Anthropic account.
	`.claude.json`	Account onboarding/ migration markers, numStartups, etc.
	`mcp-needs-auth-cache.json`	Per-account MCP auth state.
Work product (share)	`projects/<slug>/<uuid>.jsonl`	Per-session conversation transcript.
	`projects/<slug>/memory/*.md`	Project memory entries (what `Skill auto-memory` writes).
	`history.jsonl`	Prompt-line history (`Up`/`Down` recall).
	`todos/`, `tasks/`, `plans/`	UUID-named files for TaskCreate/Plan tooling.
	`file-history/`	Snapshots of files edited via the Edit tool.
	`paste-cache/`	Long-paste buffer storage.
	`plugins/`	Installed plugins, marketplaces, manifest JSON.
	`daemon/`, `jobs/`	Background-agent registry (`roster.json` + dispatch) and its job store.
	`CLAUDE.md`	User-scope memory / instructions.
Per-dir own file (partially synced)	`settings.json`	Top-level config: `enabledPlugins`, `effortLevel`, permissions, hooks, model. **Not** a

Category	Path under `CLAUDE_CONFIG_DIR`	What it is
		shared symlink — see below.
Runtime (share-able with care)	`sessions/`	Active session lockfiles. **Not safe to share between concurrent processes.**
	`telemetry/`	Per-account telemetry batches.
	`cache/`, `backups/`, `session-env/`, `shell-snapshots/`	Ephemeral runtime caches.
	`stats-cache.json`	Per-account usage / quota stats.

The key observation: every **work-product** item is keyed either by UUID (session, todo, plan, file edit) or by project slug. That means combining two accounts' work-product directories is a **set-union operation**: copying both into the same destination never overwrites either's data, because each file's path is already unique.

The handful of files that genuinely need merging are:

- `settings.json` — **each config dir keeps its OWN real file; it is deliberately not in the shared set** (`CMA_SHARED_ITEMS` in `lib.sh` omits it, and `claude-list-accounts` excludes it from the link check for the same reason). Only the `enabledPlugins` map is unified: the unifier extracts that map from every account's own file, unions it into the shared *template* at `$SHARED_DIR/settings.json`, and propagates the union back into each dir (`seed_own_settings` → `cma_own_settings_seed`). Every other key — `effortLevel`, `permissions`, `hooks`, `model`, `skipDangerousModePermissionPrompt` — stays local to the dir that set it, so per-alias configuration never leaks across aliases or providers. The test suite asserts both halves: the union arrives everywhere, and a non-plugin key set on `acct1` is absent from `acct2` *and* from the shared template. An earlier revision of this document described `settings.json` as a symlink into the shared store with "most permissive keys win"; that is no longer how it works.
- `history.jsonl` — append-only prompt log. We concatenate both files and de-duplicate by line, preserving order of first appearance.
- `plugins/installed_plugins.json` and `plugins/known_marketplaces.json` — these embed **absolute paths** to plugin code. We rewrite those paths to live under the shared store regardless of which account they came from.

3. Architecture after fine-tuning

```
~/.claude-shared/                 <-- single source of truth
  projects/                       (transcripts + memory; per-slug)
  todos/  tasks/  plans/
  file-history/  paste-cache/
  plugins/
    installed_plugins.json        (paths rewritten -> ~/.claude-
shared/...)
    known_marketplaces.json       (paths rewritten -> ~/.claude-
shared/...)
    cache/<marketplace>/<plugin>/<version>/
    marketplaces/<marketplace>/
  shell-snapshots/  session-env/
  telemetry/  sessions/  backups/  cache/
  daemon/  jobs/                  (background-agent registry + job
store)
  history.jsonl  stats-cache.json
  settings.json                   (TEMPLATE only — enabledPlugins
union)
  CLAUDE.md

~/.claude-milos85vasic/           <-- account 1 (claude1 alias)
  .credentials.json    (PRIVATE — claude1's OAuth tokens)
  .claude.json         (PRIVATE — claude1's onboarding state)
  mcp-needs-auth-cache.json  (PRIVATE)
  settings.json        (OWN real file — enabledPlugins synced from
the
                        shared template; every other key stays
local)
  projects     -> ~/.claude-shared/projects
  todos        -> ~/.claude-shared/todos
  tasks        -> ~/.claude-shared/tasks
  plans        -> ~/.claude-shared/plans
  plugins      -> ~/.claude-shared/plugins
  daemon       -> ~/.claude-shared/daemon
  jobs         -> ~/.claude-shared/jobs
  history.jsonl -> ~/.claude-shared/history.jsonl
  CLAUDE.md    -> ~/.claude-shared/CLAUDE.md
  ... (every shared item is a symlink)

~/.claude-milos85vasic2nd/        <-- account 2 (claude2 alias)
  .credentials.json    (PRIVATE — claude2's OAuth tokens)
  .claude.json         (PRIVATE — claude2's onboarding state)
  mcp-needs-auth-cache.json  (PRIVATE)
  ... (same symlink set as above)

~/.claude/                        <-- user-scope default root
  CLAUDE.md    -> ~/.claude-shared/CLAUDE.md
  plugins/
```

```
cache        -> ~/.claude-shared/plugins/cache
marketplaces -> ~/.claude-shared/plugins/marketplaces
```

Properties of this layout:

1. **Account switching is purely a credentials swap.** Running `claude1` vs `claude2` changes `CLAUDE_CONFIG_DIR`, which changes which `.credentials.json` is loaded — everything else (history, memory, plugins) resolves through symlinks to the same shared store.
2. **Adding a new account is the same operation, parameterised.** A new `~/.claude-<name>` dir with the same symlink set + its own `.credentials.json` slots in seamlessly. See `claude-add-account.sh`.
3. **Account identity stays compartmentalised.** OAuth tokens are not in the shared store, so leaking the shared store does not leak account credentials.
4. **Rollback is mechanical.** Every original directory was moved to `<path>.preunify.<timestamp>` before the symlink replaced it. A single script (`claude-rollback.sh`) reverses the migration.

---

4. Reproducing this on any host

This section is the actual step-by-step procedure. It assumes you have two (or more) Claude Code accounts already set up the conventional way — one config directory per account, each with its own `.credentials.json`. If you don't have a second account yet, run the first three steps and then use `claude-add-account.sh` to create one.

4.0 Clean-slate host: `claude-bootstrap`

If you are setting up a **brand-new machine** where Claude Code is installed but no accounts have been created or logged in yet, use `claude-bootstrap` instead of the §4.2–§4.3 flow. It provisions N fresh accounts in one shot:

```
git clone <this repo> claude-toolkit
cd claude-toolkit
bash scripts/claude-bootstrap.sh --count 2 --yes
exec $SHELL -l
claude1 /login
claude2 /login
```

Key flags:

Flag	Effect
`--count N`	Create N accounts named `claude1`…`claudeN`.

Flag	Effect
`--yes`	Non-interactive; skip confirmation prompts.
`--aliases personal,work`	Use custom alias names instead of `--count`.
`--dir-of NAME=PATH`	Override the config-dir path for a specific alias.

`claude-bootstrap` is **idempotent** — safe to re-run after pulling updates. It calls `install.sh` internally, so you do not need to run both.

4.1 Prerequisites

```
# Linux (Debian/Ubuntu/Fedora/Arch)
sudo apt-get install -y rsync jq gawk pandoc weasyprint    # Debian/Ubuntu
# or
sudo dnf install -y rsync jq gawk pandoc weasyprint        # Fedora
# or
sudo pacman -S rsync jq gawk pandoc weasyprint             # Arch

# macOS (Homebrew)
brew install rsync jq gawk pandoc weasyprint
```

`weasyprint` is optional but produces the best-looking PDF; the export script will fall back to `wkhtmltopdf` or `chromium --headless` if weasyprint isn't available.

4.2 Lay down the scripts directory

Clone or copy the entire `scripts/` directory; all scripts listed in `scripts/README.md` are required:

```
git clone <this repo> claude-toolkit
cd claude-toolkit
```

All scripts are set executable in the repository; no `chmod` step is needed.

4.3 Run the installer

```
bash scripts/install.sh
```

What `install.sh` does, in order:

1. Verifies `rsync`, `jq`, `awk` are on PATH; warns if `pandoc` is missing.

2. Symlinks every `claude-*.sh` script into `~/.local/bin/` so they're invokable as plain commands (`claude-unify`, `claude-add-account`, …).
3. Adds `export PATH="$HOME/.local/bin:$PATH"` to `~/.bashrc` and `~/.zshrc` if missing.
4. Creates the managed alias file at `~/.local/share/claude-multi-account/aliases.sh` and ensures it's sourced from `~/.bashrc` and `~/.zshrc`.
5. Migrates any pre-existing inline `alias claude<N>=...` lines from `~/.bashrc` / `~/.zshrc` into the managed alias file, commenting out the originals (and saving a `.preunify.<timestamp>` backup of the rc file first).
6. Builds the bundled Go router (`claude-ccr-build.sh`). A failure here is recorded as a hard install failure, because provider aliases on the **router** transport cannot launch without it.
7. Builds the compatibility proxy (`claude-proxy-build.sh`). A failure here is recorded as *degraded*, not fatal: the affected aliases (`helixagent`, `poe`, `kimi*`, `sarvam`) still launch, just without their compatibility shims.
8. Installs the shell session hook and refreshes provider aliases.
9. Auto-detects every `~/.claude-*` directory and runs `claude-unify.sh` to merge them into `~/.claude-shared/`.
10. Re-renders the doc siblings via `claude-export-docs.sh` — **only if** `pandoc` is present *and* `~/Documents/Claude_Multi_Account_Fine_Tuning.md` exists. On a plain repository checkout that file is not there, so this step is skipped and the siblings must be regenerated explicitly with the `MD_FILE=` invocation shown at the top of this document.

It does **not** build the vendored Go toolchain (§15): `claude-go-build` is symlinked onto `PATH` but never invoked, so compiling Go from source stays an explicit operator decision.

After it finishes, reload your shell:

```
exec $SHELL -l
claude-list-accounts
```

You should see every account dir, with `CREDS: yes` and a `LINKS: 5/5` indicator showing the shared symlinks are in place. The denominator is the size of `CHECK_LINKS` in `claude-list-accounts.sh` — currently `projects`, `history.jsonl`, `plugins`, `todos`, `CLAUDE.md`. `settings.json` is **not** in that list, because each dir owns its own copy (§2); a tool that reported it as "not linked" would be reporting the intended design as a fault.

4.4 Add a third (or fourth, …) account

```
claude-add-account
# prompts:
```

```
#   Alias name      [claude3]:
#   Config directory [/home/you/.claude-claude3]:
```

If you accept both defaults, you get:

- `~/.claude-claude3/` created with the full set of shared-state symlinks already in place.
- `alias claude3="CLAUDE_CONFIG_DIR=$HOME/.claude-claude3 \ $CLAUDE_BIN"` appended to the managed alias file.
- A reminder to authenticate: `claude3 /login`.

Custom alias names work just as well:

```
claude-add-account --alias work --dir ~/.claude-work --yes
work /login
```

4.5 Verify the result

```
claude-list-accounts

# Expected output (your alias names may differ):
# ALIAS         CONFIG DIR
        CREDS   LINKS  NOTES
# claude1       /home/you/.claude-milos85vasic
        yes     5/5
# claude2       /home/you/.claude-milos85vasic2nd
        yes     5/5
# claude3       /home/you/.claude-claude3
        no      5/5
#
# Shared store: /home/you/.claude-shared
# Alias file:   /home/you/.local/share/claude-multi-account/
        aliases.sh
```

You can confirm symlinks resolve correctly:

```
readlink -f ~/.claude-milos85vasic/projects
# /home/you/.claude-shared/projects

readlink -f ~/.claude-milos85vasic2nd/projects
# /home/you/.claude-shared/projects

# Both should print the same path. The same is true for todos,
        plans,
# history.jsonl, CLAUDE.md, daemon, jobs, etc. — but NOT
        settings.json,
# which is each dir's own real file by design.
```

4.6 Rollback if needed

Every directory or file the unifier touched was moved to `<path>.preunify.<timestamp>` before the symlink was created. To restore:

```
claude-rollback
# moves ~/.claude-shared aside and restores every .preunify.*
        backup
```

The shared store isn't deleted — it's renamed to `~/.claude-shared.removed.<timestamp>` so you can manually recover any data written through the symlinks before rolling back.

---

5. Operational notes

5.1 Concurrent use of two accounts

`sessions/` is shared in this configuration. A live Claude Code session holds its lockfile under `sessions/`, and two concurrent processes writing to the same lockfile path can confuse each other. **Avoid running `claude1` and `claude2` simultaneously in two terminals.** If you need true concurrent use, override the unifier to keep `sessions/` private:

```
# in claude-unify.sh, remove "sessions" from SHARED_ITEMS
# then run claude-unify again — it'll relink sessions/ as per-
        account
```

`history.jsonl` is append-only and is mostly safe under concurrent writes (worst case: a small number of duplicate lines, which the next unify run will de-dupe).

5.2 Plugin path rewriting

Claude Code records absolute paths in `plugins/installed_plugins.json` and `plugins/known_marketplaces.json`. These paths can point to one of:

- `~/.claude/plugins/cache/...` (user-scope installs from any account)
- `~/.claude-<name>/plugins/cache/...` (project-scope installs from that account)

The unifier rsyncs plugin code from all three roots (`~/.claude/plugins/`, plus every account's `plugins/`) into `~/.claude-shared/plugins/`, then rewrites every `installPath` / `installLocation` to point

under `~/.claude-shared/plugins/`. It also symlinks `~/.claude/plugins/cache` and `~/.claude/plugins/marketplaces` into the shared store, so any future user-scope install lands in the unified spot.

If you ever install a plugin and Claude reports "plugin code not found," re-run `claude-unify.sh` to repath the manifest.

5.3 Adding a new account from scratch (no existing dir)

The `claude-add-account.sh` script works whether or not the target dir exists yet. If it doesn't exist, the script creates an empty dir, links every shared item into it, and registers the alias. The new account has no credentials of its own — your next step is `claudeN / login`.

If you want to also pre-populate the new account with a `.claude.json` template (e.g., to skip the new-user warmup tips), copy one from an existing account *after* the add-account script finishes:

```
cp ~/.claude-milos85vasic2nd/.claude.json ~/.claude-
        claude3/.claude.json
# but DO NOT copy .credentials.json — that would leak the source
# account's OAuth tokens to the new account
```

5.4 Removing an account

```
claude-remove-account --alias claude3
# default: archives ~/.claude-claude3 -> ~/.claude-
        claude3.removed.<timestamp>
# add --delete to remove it instead
```

The shared store is left intact; other accounts continue to function.

5.5 Backups created during install

The installer never deletes existing data. Every directory or file it replaced lives at `<original-path>.preunify.<timestamp>` (or `<original-path>.removed.<timestamp>` for rollback). You can safely delete those backups once you've confirmed the new setup works:

```
find ~ -maxdepth 3 -name '*.preunify.*' -print     # see what's
        there
find ~ -maxdepth 3 -name '*.preunify.*' -delete    # delete once
        happy
```

A pre-migration tarball is also placed in `~/Documents/claude-config-backups/` by the original migration. Keep it until you're confident in the new layout.

---

6. Cross-platform reproduction

Linux

Everything in this document was developed and tested on Linux 6.12.41 with bash 5.2.37, jq 1.8.1, rsync 3.2.7, pandoc 3.10. No Linux-specific behaviours are relied on; the scripts use only POSIX-portable tools plus jq.

On lint, be precise about the severity — an earlier revision of this document claimed the scripts "pass `shellcheck` clean", which is true only at one severity level and ambiguous at every other. Measured with shellcheck 0.11.0 over `scripts/`: **0 findings at `error` severity**; `warning` and `style` severities do report findings (62 and 203 respectively at the v1.26.7 measurement). The suite gate is the `error` level.

macOS

macOS ships an older bash (3.2) by default. Install GNU bash via Homebrew (`brew install bash`) and update the shebangs only if you hit syntax issues — the scripts use `bash 4+` features only where the fallback is explicit (`mapfile`, associative arrays). On a default macOS:

```
brew install bash jq rsync gawk pandoc weasyprint
echo "$(brew --prefix)/bin/bash" | sudo tee -a /etc/shells
chsh -s "$(brew --prefix)/bin/bash"
```

Everything else (paths, `$HOME`, `~/.claude-*` convention) is identical to Linux.

WSL / Windows Subsystem for Linux

WSL is just Linux for our purposes. Use the Linux instructions. If you also run Claude Code natively on Windows, the Windows version uses a different config root entirely (`%APPDATA%\claude`) and is not covered by this toolkit.

---

7. Tests

Everything in this toolkit is covered by a hermetic test suite under `scripts/tests/` — **58 `test_*.sh` files** at the time of writing (`ls scripts/tests/test_*.sh | wc -l` is the authoritative count; the orchestrator auto-discovers, so the number moves with every feature). Each test runs against a temporary `$HOME` created by `mktemp -d -t cma-test.XXXX`; the real `~/.claude-*` directories are never touched. After the test process exits, the sandbox is `rm -rf`'d (with a safety check that the path basename starts with `cma-test.`).

7.1 Running the suite

```
# All tests:
bash scripts/tests/run-all.sh

# A single file (no test_ prefix, no .sh suffix):
bash scripts/tests/run-all.sh unify
bash scripts/tests/run-all.sh add_remove
```

Output is line-based. Each file prints its own `[PASS]`/`[FAIL]` lines and ends with a per-file `summary`; the orchestrator then prints a tally across files:

```
==> test_unify.sh

  • every shared item becomes a symlink into the shared store
    [PASS] .claude-acct1 projects linked: ...
    [PASS] .claude-acct2 projects linked: ...
  • shared TEMPLATE settings.json enabledPlugins is the union
{a,b,c}
    [PASS] union (.enabledPlugins | keys | sort | join(",") =
a,b,c)
    ...

✓ 42 passed, 0 failed

==========================================
Test files: 58   passed: 58   failed: 0   (skipped-prereq: 0)
ALL GREEN
```

The orchestrator's exit code is 0 only if every `test_*.sh` file's own summary returned 0. Two guards sit on top of that, because an exit code alone is not trustworthy evidence:

- a file that exits 0 while having printed `[FAIL]` (a missing final `summary`, for instance) is forcibly re-scored as a failure;
- a file that exits 0 after printing `SKIP` on a missing prerequisite is counted in a separate `skipped-prereq` column, so an

environment-driven skip can never masquerade as a genuine pass inside "ALL GREEN".

Only one suite run at a time. `run-all.sh` and `run-proof.sh` both take a serialization lock (`tests/lib/suite-lock.sh`) before doing anything. A repo that mutates while its own tests execute cannot produce reproducible results — a second agent adding a test file mid-run is enough to make a set of deterministic tests look flaky — so overlapping runs are refused on purpose. The behaviour you will actually see:

- **Contention**: the run announces the holder's PID and waits, up to `CMA_SUITE_LOCK_WAIT` seconds (default 600). Usually the other run finishes and yours proceeds; that is the common case and needs no action.
- **Timeout**: it gives up with exit **75** (`EX_TEMPFAIL`) rather than hanging. Set `CMA_SUITE_LOCK_WAIT=0` if you would rather fail immediately.
- **Nesting**: `run-proof.sh` invokes `run-all.sh` as a child, and both are documented entry points, so both lock. The child *inherits* the parent's lock instead of deadlocking against it — and the inheritance is verified (live PID, matching lock path, PID actually recorded in the lock), so a stale or forged environment variable cannot quietly turn locking off.
- **A crashed run does not wedge the suite**: `flock(1)` releases automatically, and the portable `mkdir` fallback (macOS ships no `flock`) breaks a stale lock via `rename(2)`, which exactly one contender can win.

The lock file lives in the git dir (or `$TMPDIR`), never inside the tracked tree, so it can never show up in `git status` or be committed by accident.

7.2 What each test covers

Every `test_*.sh` file is auto-discovered by `run-all.sh`. The table below describes the core set — ten of the current 58 files. The suite has grown well beyond what any table can usefully mirror (it now also covers the router build and conformance, the cma-proxy, output-token arithmetic, route attribution, alias-file concurrency and self-containment, redaction, the release gate, suite locking, and more), so `ls scripts/tests/test_*.sh` is the authoritative list:

File	What it asserts
`test_lib.sh`	`cma_validate_alias` accepts/rejects correctly; `cma_suggest_alias` returns the next free `claudeN` (skipping past existing aliases, not just counting); `cma_write_alias` is idempotent; `cma_remove_alias` deletes; `cma_ensure_alias_file` patches `.bashrc`;

File	What it asserts
	`cma_detect_accounts` excludes the shared store.
`test_unify.sh`	Every shared item becomes a symlink to `$SHARED_DIR`; `settings.json` is each dir's OWN real file and **not** a symlink; the shared *template*'s `enabledPlugins` is a strict union of every account's set and that union is propagated back into each dir; every non-`enabledPlugins` key stays local (an `effortLevel` set on `acct1` is absent from `acct2` and from the template, and vice versa); `history.jsonl` is concatenated and de-duplicated; on memory-file conflicts, the most recently touched account wins; `plugins/installed_plugins.json` and `known_marketplaces.json` have absolute paths rewritten to `$SHARED_DIR/plugins/`; `.credentials.json` and `.claude.json` are NOT symlinked; re-running `claude-unify.sh` produces a byte-identical `settings.json` (idempotency); `N>2` accounts (adding `acct3` and re-unifying) works; `--rollback` restores every `.preunify.*` backup and moves the shared store aside.
`test_add_remove.sh`	`claude-add-account.sh --yes` creates the dir with full symlink set and writes a shell-safe alias line; refuses to overwrite an existing dir; accepts a custom alias name + custom dir; validates alias names against the safe regex; `claude-remove-account.sh --archive` moves the dir aside and removes the alias; `--delete` actually deletes; unknown alias errors out.
`test_list.sh`	Empty host (no accounts) renders just the header; populated host renders one row per detected account dir; the shared store path is printed; accounts missing credentials show `CREDS: no`.
`test_export.sh`	`claude-export-docs.sh` (with `MD_FILE=` override) produces both a `.html` and a `.pdf`; `<!-- INCLUDE: <relative path> -->` markers are expanded in the output; output PDF starts with the `%PDF-` magic bytes; re-running is non-destructive.
`test_opencode.sh`	Builds a fake Claude plugin cache in a throwaway `$HOME` and asserts the generated OpenCode config has the right shape: skills wired, MCP servers translated (wrapped + bare formats), dedup, collision-rename,

File	What it asserts
	secret/runtime enable gating, `${CLAUDE_PLUGIN_ROOT}` expansion, instruction inclusion, pre-existing config preserved, idempotency, and `--dry-run` safety. No network, no real `~/.claude`, no real opencode binary required.
`test_sessions.sh`	Verifies sessions, project memory, and todos created under one account become physically visible to every other account after unify. Covers: `.claude.json` `projects` subtree union; auth-private keys (`userID`, `oauthAccount`, etc.) preserved per-account; session JSONL byte-identical from every account's symlinked dir; project memory cross-account visibility; `cma_merge_claude_json` idempotency; `claude-sync-state.sh` push/pull round-trip.
`test_coverage.sh`	Coverage for `lib.sh` behaviors not exercised in `test_lib.sh` (new in v1.7.8): `cma_ensure_alias_file` fresh creation + idempotency + old-format migration; `cma_can_prompt` under `CMA_NONINTERACTIVE=1` and no-tty; `cma_enable_plugins` JSON shape and additive behaviour; `cma_link_shared_items` turning all `CMA_SHARED_ITEMS` into symlinks; `stats-cache.json` newest-by-mtime selection via `run_unify`.
`test_providers.sh`	Tests for the provider-alias feature (`claude-providers`). Primary focus: account-detection regression — provider dirs (`~/.claude-prov-*`) must be invisible to `cma_detect_accounts` so they never merge into real-account auth or disturb `claude-unify` / `claude-add-account`.
`test_claude.sh`	Proves `claudeN` aliases are untouched by provider code: `cma_run` includes `claude-sync-state` pull/push hooks, contains no proxy or transformer code; `cma_run_provider` has proxy detection. Reads the live alias file; SKIPs if no alias file is present.

7.3 How the test harness works

Two small libraries sit under `tests/lib/`:

- **`assert.sh`** — `it`, `assert_eq`, `assert_file`, `assert_dir`, `assert_symlink_to`, `assert_not_symlink`, `assert_file_contains`, `assert_file_not_contains`, `assert_jq`, `assert_lines`, `assert_exit`.

Each helper prints a `[PASS]` or `[FAIL]` line and adjusts the counters used by `summary` at end-of-file.
- **`sandbox.sh`** — `make_sandbox` (creates a tempdir and overrides `HOME`, `SHARED_DIR`, `ALIAS_FILE`, `DEFAULT_DIR`, `CLAUDE_BIN`), `make_account NAME [--plugins] [--settings JSON] [--history a|b|c] [--memory KEY:VALUE] [--todo SUBJECT]` (builds a realistic per-account fixture dir), plus thin wrappers `run_unify`, `run_add_account`, etc. It also carries two hygiene helpers described below.

Sandbox hygiene: `assert_sandboxed` and `sandbox_stub`. These cover two *different* failure modes, and the distinction matters.

`assert_sandboxed` is called by `make_sandbox` itself and exits 99 unless `$HOME`'s basename matches `cma-test.*`. It proves the `HOME` switch actually took before any test writes a byte — it catches a test that never sandboxed at all.

`sandbox_stub PATH` (stub content on stdin) is the required way to install a fake executable under `$HOME/.local/bin`. It asserts the sandbox, refuses any target that escapes `$HOME`, and — the guarantee a bare `cat >` does not give — **deletes an existing symlink before writing, rather than writing through it**.

The reason this second helper exists is a real incident, not a hypothetical. `install.sh` symlinks every `claude-*.sh` into `~/.local/bin`, and those links point at the real repo. A shell redirect follows symlinks. A test that did `cat > "$HOME/.local/bin/claude-session"` therefore wrote *through* the link and truncated the production `scripts/claude-session.sh` from 201 lines to an 8-line stub — and `scripts/claude-sync-state.sh` from 103 lines to 2 — which broke every provider alias with `No conversation found with session ID: …`.

The part to internalise: **`$HOME` was a perfectly valid sandbox at the time.** `install.sh` had created those links *inside* the sandbox, so `assert_sandboxed` passed, exactly as designed, and could never have caught this. The sandbox assertion is not the protection here — breaking the symlink before writing is. `test_sandbox_hygiene.sh` lints the whole suite mechanically for this pattern (bare redirects into `.local/bin`) and for hardcoded `/tmp` write targets, reporting `file:line` so a violation is directly actionable.

One subtlety worth knowing: `lib.sh` (the production helper) has `set -euo pipefail`. When a test sources it for unit-testing the helper functions, the `set -e` flag stays active in the test shell. The unit test file (`test_lib.sh`) therefore runs `set +e` immediately after sourcing `lib.sh` so that intentional failures (e.g. `cma_validate_alias "bad name"`) don't abort the whole test process. End-to-end tests don't have this problem because they invoke the scripts as external processes (via `run_unify`, etc.), which run in their own shell.

7.4 Adding a new test

1. Create `tests/test_<feature>.sh`. Mark it executable.
2. Source the two libs:

```
TESTS_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
SCRIPTS_DIR="$(cd "$TESTS_DIR/.." && pwd)"
source "$TESTS_DIR/lib/assert.sh"
source "$TESTS_DIR/lib/sandbox.sh"
```

3. Call `make_sandbox` once at the top.
4. Use `it "..."` to label each scenario, then a sequence of `assert_*` calls.
5. Never write to `$HOME/.local/bin` with a bare redirect — use `sandbox_stub "$HOME/.local/bin/<name>"` with the stub body on stdin, and keep every other temporary path under `$SANDBOX_HOME` or `mktemp`, never a literal `/tmp/...`. `test_sandbox_hygiene.sh` enforces both mechanically.
6. End the file with `summary` so the orchestrator picks up the result.
7. Re-run `bash tests/run-all.sh` — auto-discovery will pick it up. If another suite run is already in progress it will wait for the lock (and exit 75 if that run never finishes); that is expected, not a failure of your test.

---

8. The complete script source

For convenience and audit, part of the toolkit source is reproduced below. The authoritative copies live in this repository's `scripts/` directory.

How the reproduction works, and what it covers. Each fenced block below holds a single `<!-- INCLUDE: <relative path> -->` marker rather than a copy of the file. `claude-export-docs.sh` preprocesses the markdown with `awk` before handing it to pandoc, replacing each marker with the referenced file's contents (paths are resolved relative to the directory containing the `.md`). So the markdown stays small and reviewable while the generated HTML/PDF/DOCX are self-contained snapshots of the real code at render time — there is no copy to drift.

Two consequences worth knowing:

- **The included set is a subset, not the whole toolkit.** The sixteen markers below cover `lib.sh`, the six account-management commands, the installer, and the original test core. `scripts/` currently holds 26 `*.sh` entrypoints; the provider stack (`claude-providers.sh`, `providers-verify.sh`, `providers-semantic.sh`, `verify_superpowers_tui.sh`), the build entrypoints (`claude-ccr-build.sh`, `claude-proxy-build.sh`, `claude-go-build.sh`),

`claude-session.sh`, `claude-sync-state.sh`, `claude-release-gate.sh`, `claude-gc.sh` and others are **not** inlined here. Read them in the repository.

- **A marker is consumed wherever it appears**, including inside prose or a code span. If the referenced path does not exist, `awk` prints nothing and skips the line — the whole line silently disappears from the rendered output. That is why the `test_export.sh` row in §7.2 writes the marker with a spaced placeholder (`<relative path>`): a literal `INCLUDE: path -->` there would have deleted that table row from the HTML and PDF. Keep any future prose mention of the marker un-matchable the same way.

One pre-existing wart, recorded rather than worked around: the export script hardcodes `--metadata title="Claude Multi-Account Fine Tuning"` for the HTML render, so the HTML `<title>` is fixed regardless of the YAML front matter of whatever `MD_FILE` is passed. It is correct for *this* document and wrong for any other one rendered through the same script.

8.1 `lib.sh`

```
#!/usr/bin/env bash
# lib.sh — shared functions for the Claude multi-account toolkit.
# Sourced by the other scripts; no side effects on its own.

set -euo pipefail

# Which rc files to source the alias file from. macOS interactive
        shell is
# zsh; touching .bashrc there just creates noise the user has to
        clean up.
# On Linux we keep both because either may be the login shell.
if [[ "$(uname -s)" == "Darwin" ]]; then
  CMA_RC_FILES=("$HOME/.zshrc")
else
  CMA_RC_FILES=("$HOME/.bashrc" "$HOME/.zshrc")
fi

# Resolve paths the user can override. SHARED_DIR is the single
        canonical
# location for cross-account state; ALIAS_FILE is the rc-sourced
        file we
# manage aliases through; ACCOUNT_PREFIX is the dir-name prefix
        for new
# per-account config directories.
: "${SHARED_DIR:=$HOME/.claude-shared}"
: "${ALIAS_FILE:=$HOME/.local/share/claude-multi-account/
        aliases.sh}"
: "${ACCOUNT_PREFIX:=.claude-}"
```

```
# Resolve the Claude Code binary for the alias wrappers. Prefer an
      explicit
# CLAUDE_BIN, then $PATH, then the common install locations. npm's
      global prefix
# varies per host (e.g. ~/.npm-global vs ~/.local vs Homebrew), so
      a fixed
# ~/.local/bin default mis-points on hosts where `npm i -g
      @anthropic-ai/...`
# landed elsewhere — making EVERY alias launch fail "No such
      file". Checking
# the real locations keeps a fresh install working without a
      manual symlink.
cma_resolve_claude_bin() {
  if [ -n "${CLAUDE_BIN:-}" ]; then printf '%s\n' "$CLAUDE_BIN";
      return 0; fi
  local c; if c="$(command -v claude 2>/dev/null)"; then printf
      '%s\n' "$c"; return 0; fi
  local p
  for p in "$HOME/.local/bin/claude" "$HOME/.npm-global/bin/
      claude" \
           /opt/homebrew/bin/claude /usr/local/bin/claude; do
    [ -x "$p" ] && { printf '%s\n' "$p"; return 0; }
  done
  printf '%s\n' "$HOME/.local/bin/claude"
      # fallback (created by install/symlink)
}
# Resolved once at source time for callers that want the default
      without paying
# for a re-probe. The alias renderer does NOT use it — it prefers
      the value
# already recorded in the alias file when that still resolves (see
# _cma_alias_claude_bin), so a working per-host path is never
      clobbered.
# shellcheck disable=SC2034  # part of lib.sh's public surface for
      sourcing scripts
CLAUDE_BIN_DEFAULT="$(cma_resolve_claude_bin)"

cma_log()  { printf '\033[36m[cma]\033[0m %s\n' "$*" >&2; }
cma_warn() { printf '\033[33m[cma warn]\033[0m %s\n' "$*" >&2; }
cma_err()  { printf '\033[31m[cma err]\033[0m %s\n' "$*" >&2; }
cma_die()  { cma_err "$*"; exit 1; }

# Quota severity classifier: the <= 0 check MUST come first to
      correctly
# classify negative values (e.g., -5 representing usage past 100%)
      as limit_exceeded.
_cma_quota_severity() {
  local pct="$1"
  awk -v p="$pct" 'BEGIN {
    if (p <= 0) { print "limit_exceeded"; exit }
    if (p < 10) { print "red"; exit }
    if (p < 30) { print "yellow"; exit }
    print "green"
  }'
```

```
}

# --force-tty/--force-no-tty exist only for hermetic testing,
        where no
# real tty is available to check against -- production callers
        never
# pass these two flags.
_cma_quota_color_enabled() {
  local force_tty="" json_flag=0 no_color_flag=0 arg
  for arg in "$@"; do
    case "$arg" in
      --force-tty) force_tty=1 ;;
      --force-no-tty) force_tty=0 ;;
      --json) json_flag=1 ;;
      --no-color) no_color_flag=1 ;;
    esac
  done
  (( json_flag )) && return 1
  (( no_color_flag )) && return 1
  [[ -n "${NO_COLOR:-}" ]] && return 1
  if [[ -n "$force_tty" ]]; then
    (( force_tty )) && return 0 || return 1
  fi
  [[ -t 1 ]] && return 0 || return 1
}

# _cma_quota_render_text: reads newline-delimited Reportable
        Entity JSON
# from stdin, writes human-readable text to stdout. One line per
        Usage
# Window, grouped under one header per row (never once per
        alias_name).
# Accepts the same color-gating flags _cma_quota_color_enabled
        does
# (--no-color, --force-tty, --force-no-tty, --json is irrelevant
        here).
_cma_quota_render_text() {
  local color_on=1
  if ! _cma_quota_color_enabled "$@"; then color_on=0; fi

  local line
  while IFS= read -r line; do
    [[ -n "$line" ]] || continue
    _cma_quota_render_one_row "$line" "$color_on"
    printf '\n'
  done
}

# Renders ONE Reportable Entity row. Separated from the stdin loop
        so it
# stays independently testable and readable.
_cma_quota_render_one_row() {
  local line="$1" color_on="$2"
```

```
local pid aid
pid="$(jq -r '.provider_id // empty' <<<"$line" 2>/dev/null)"
aid="$(jq -r '.account_id // empty' <<<"$line" 2>/dev/null)"

if [[ -n "$pid" ]]; then
  local names; names="$(jq -r '.alias_names | join(", ")'
      <<<"$line" 2>/dev/null)"
  printf '%s  (alias: %s)\n' "$pid" "$names"
else
  local tier; tier="$(jq -r '.plan_tier // "unknown"'
      <<<"$line" 2>/dev/null)"
  printf '%s  (native, plan tier: %s)\n' "$aid" "$tier"
fi

# FR-011: a blocked account gets a distinct, unmistakable
      statement --
# shared by both the provider-account and native-account
      branches above
# (an account can be blocked regardless of row kind).
      Deliberately does
# NOT return/continue: the windows loop below still runs, so
      prior
# windows stay visible, only annotated as moot. Stated BEFORE
      the
# absence early return: a 200 with a blocked signal and zero
      windows
# arrives as account_blocked + probe_failed (known-issues T27).
# The "windows below are moot" clause is only stated when
      windows ARE

      # below: a zero-window blocked row (blocked +
      probe_failed) must not point
# at windows that do not exist (docs-batch item 6).
local blocked; blocked="$(jq -r '.account_blocked // false'
      <<<"$line" 2>/dev/null)"
if [[ "$blocked" == "true" ]]; then
  local moot="" nwin
  nwin="$(jq -r '(.windows // []) | length' <<<"$line" 2>/dev/
      null)"
  [[ "$nwin" =~ ^[0-9]+$ ]] && (( nwin > 0 )) &&
      moot="; windows below are moot"
  if (( color_on )); then
    printf '  \033[31;1mACCOUNT BLOCKED\033[0m — the whole
      subscription is suspended%s\n' "$moot"
  else
    printf '  ACCOUNT BLOCKED — the whole subscription is
      suspended%s\n' "$moot"
  fi
fi

local absence; absence="$(jq -r '.absence_reason // empty'
      <<<"$line" 2>/dev/null)"
if [[ -n "$absence" ]]; then
  if [[ "$absence" == "probe_failed" ]]; then
```

```
    local detail; detail="$(jq -r '.absence_detail // "unknown
      error"' <<<"$line" 2>/dev/null)"
    printf '  —   probe failed: %s\n' "$detail"
  elif [[ "$absence" == "auth_expired" ]]; then
    # Native Kimi usages probe answered 401: the access token
      lapsed. The

      # detail carries the operator instruction, naming the
      probed account:
    # `KIMI_CODE_HOME=<account dir> kimi login` (a bare `kimi
      login` would
    # sign in the default ~/.kimi-code instead).
    local adetail; adetail="$(jq -r '.absence_detail // "access
      token expired"' <<<"$line" 2>/dev/null)"
    printf '  —   %s\n' "$adetail"
  else
    local auth_state; auth_state="$(jq -r '.auth_state //
      empty' <<<"$line" 2>/dev/null)"
    case "$auth_state" in
      session_expired) printf '  —   not reported by provider
      (native session expired -- re-authenticate)\n' ;;
      not_signed_in)   printf '  —   not reported by provider
      (not signed in)\n' ;;
      *)               printf '  —   not reported by
      provider\n' ;;
    esac
  fi
  return 0
fi

local n_windows; n_windows="$(jq -r '.windows | length'
      <<<"$line" 2>/dev/null)"
local src; src="$(jq -r '.data_source // empty' <<<"$line" 2>/
      dev/null)"
local age; age="$(jq -r '.data_age_seconds // empty' <<<"$line"
      2>/dev/null)"
local cache_note=""
if [[ "$src" == "cached" && -n "$age" ]]; then
  cache_note=" (cached, ${age}s old)"
fi

local i
for (( i = 0; i < n_windows; i++ )); do
  local w used rem total unit pct sev colorcode sev_upper
  w="$(jq -r ".windows[$i].window" <<<"$line" 2>/dev/null)"
  used="$(jq -r ".windows[$i].amount_used" <<<"$line" 2>/dev/
      null)"
  rem="$(jq -r ".windows[$i].amount_remaining" <<<"$line" 2>/
      dev/null)"
  total="$(jq -r ".windows[$i].limit_total" <<<"$line" 2>/dev/
      null)"
  unit="$(jq -r ".windows[$i].unit" <<<"$line" 2>/dev/null)"
  pct="$(jq -r ".windows[$i].percent_remaining" <<<"$line" 2>/
      dev/null)"
  sev="$(_cma_quota_severity "$pct")"
```

```
  # Uppercased via `tr`, not `${sev^^}`: lib.sh has no existing
  # `${var^^}`-style usage to lean on for a bash-4+ precedent,
      and this
  # file is sourced directly by the test harness
      (test_quota_rendering.sh)
  # with no BASH_VERSINFO re-exec guard of its own (unlike the
      wrapper

      # scripts, e.g. claude-unify.sh, which guard *before*
      sourcing lib.sh).
  # `tr` works identically on bash 3.2+, so it's the portable
      choice here.
  sev_upper="$(tr '[:lower:]' '[:upper:]' <<<"$sev")"

  local resets reset_at reset_cadence reset_note
  resets="$(jq -r ".windows[$i].resets" <<<"$line" 2>/dev/null)"
  reset_at="$(jq -r ".windows[$i].reset_at // empty" <<<"$line"
      2>/dev/null)"
  reset_cadence="$(jq -r ".windows[$i].reset_cadence // empty"
      <<<"$line" 2>/dev/null)"
  if [[ "$resets" == "true" && -n "$reset_at" ]]; then
    reset_note="   (resets $reset_at)"
  elif [[ "$resets" == "true" && -n "$reset_cadence" ]]; then
    reset_note="   (resets $reset_cadence)"
  else
    reset_note="   (does not reset)"
  fi

  # Window-name column is 15 wide: the longest emitted name is
      the Kimi
  # native subscription_5h / subscription_7d (15 chars). At 12
      they
  # overflowed and shifted their amounts 3 columns right of
      every other row.
  if (( color_on )); then
    case "$sev" in
      green) colorcode=$'\033[32m' ;;
      yellow) colorcode=$'\033[33m' ;;
      red|limit_exceeded) colorcode=$'\033[31m' ;;
      *) colorcode="" ;;
    esac
    printf '  %-15s %s used / %s left of %s %s   (%s%% left)
      %s[%s]\033[0m%s%s\n' \
      "$w" "$used" "$rem" "$total" "$unit" "$pct" "$colorcode"
      "$sev_upper" "$cache_note" "$reset_note"
  else
    printf '  %-15s %s used / %s left of %s %s   (%s%% left)
      [%s]%s%s\n' \
      "$w" "$used" "$rem" "$total" "$unit" "$pct" "$sev_upper"
      "$cache_note" "$reset_note"
  fi
done
```

```
  # A window survived but the probe still recorded a note (e.g.
      the Kimi
  # native probe omitted an out-of-range window): show it under
      the windows,
  # in the same style as the detail line above. Rows without
      absence_detail
  # print nothing extra.
  if (( n_windows > 0 )); then
    local wdetail; wdetail="$(jq -r '.absence_detail // empty'
      <<<"$line" 2>/dev/null)"
    if [[ -n "$wdetail" ]]; then
      printf '  —   %s\n' "$wdetail"
    fi
  fi
}

# _cma_quota_render_json: reads the SAME newline-delimited
      Reportable
# Entity JSON _cma_quota_render_text reads, writes ONE JSON object
# (data-model.md §5) to stdout. Derives kind/display_name/
# endpoint_spec_present/absence_detail and per-window severity,
      none of
# which the raw T017 stream carries (see task-21-brief.md for
      why).
_cma_quota_render_json() {
  local scoped_to="${1:-null}" unknown_alias="${2:-false}"
  local now; now="$(date -u +%Y-%m-%dT%H:%M:%SZ)"
  local rows_json; rows_json="$(jq -cs '
    map(
      (if has("provider_id") then "provider_account" else
        "native_account" end) as $kind
      | (.provider_id // .account_id) as $dname
      | (if .absence_reason == "not_reported_by_provider" then
        false else true end) as $esp
      | . + {
          kind: $kind,
          display_name: $dname,
          endpoint_spec_present: $esp,
          absence_detail: (.absence_detail // null),
          windows: [
            .windows[]
            | . + { severity: (
                if (.percent_remaining <= 0) then "limit_exceeded"
                elif (.percent_remaining < 10) then "red"
                elif (.percent_remaining < 30) then "yellow"
                else "green" end
              ) }
          ]
        }
    )
  ')"
  jq -cn --arg gen "$now" --argjson scoped "$scoped_to" --argjson
      unk "$unknown_alias" \
```

```
    --argjson rows "$rows_json" \

        '{generated_at: $gen, scoped_to: $scoped, unknown_alias:
        $unk, rows: $rows}'
}

cma_require() {
  command -v "$1" >/dev/null 2>&1 || cma_die "missing required
        tool: $1"
}

# Keys inside .claude.json that must NEVER leak across accounts
        (auth + identity).
# Everything else in .claude.json — projects map, UX state,
        caches, etc. — is
# safely shareable. New auth keys should be added here, not
        assumed shareable.
CMA_CLAUDE_JSON_PRIVATE_KEYS='["userID","oauthAccount","firstStartTime","claudeCoo

# Deep-merge every account's .claude.json so each account's file
        ends up with
# its OWN auth keys + the UNION of all other top-level keys
        (rightmost-wins
# for scalar conflicts, recursive object merge for `projects` and
        friends).
#
# Args: one or more account config dirs.
# Side effect: rewrites each $acct/.claude.json in place. Skips an
        account
# that doesn't yet have a .claude.json (e.g. brand-new dir before
        first login).
cma_merge_claude_json() {
  local accts=("$@")
  (( ${#accts[@]} >= 1 )) || return 0
  cma_require jq

  # Build the merged "shared portion" (everything except private
        keys).
  local shared_tmp; shared_tmp="$(mktemp "${TMPDIR:-/tmp}/
        cma.XXXXXX")"
  printf '{}\n' > "$shared_tmp"
  local acct prev="$shared_tmp"
  for acct in "${accts[@]}"; do
    local f="$acct/.claude.json"
    [[ -s "$f" ]] || continue
    local next; next="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
    # $a (accumulator) * ($b stripped of private keys). jq's `*`
        is recursive
    # deep-merge for objects; rightmost wins on scalar conflicts
        AND on array
    # values (arrays are replaced, not element-unioned — e.g. a
        per-project

        # prompt-history array takes the last account's copy).
        This is a deliberate
```

```
      # deep-merge trade-off: the projects subtree is unioned at
        the object-key
  # level (which is what the cross-account session/MCP/memory
        index needs);
  # blind element-level array union would be wrong for config-
        style arrays.
  if ! jq -s --argjson priv "$CMA_CLAUDE_JSON_PRIVATE_KEYS" '
    . as [$a, $b]
    | ($b | with_entries(select(.key as $k | $priv | index($k) |
      not))) as $shared_b
    | ($a // {}) * ($shared_b // {})
  ' "$prev" "$f" > "$next"; then
    rm -f "$next"
    cma_warn ".claude.json in
      $acct is not valid JSON — skipping its contribution"
    continue
  fi
  rm -f "$prev"
  prev="$next"
done

# Sticky-true TRUST preservation (§11.4 anti-bluff config
      hygiene): the jq `*`
# merge above is last-writer-wins on scalars, so a per-project
# `projects[<path>].hasTrustDialogAccepted` bit trusted under
      one alias could be
# DEMOTED true->false by a later account that lacks it — which
      made Claude Code's
# per-workspace trust dialog ("read, edit, and execute files
      here") reappear on
# every provider alias. Fix: OR the trust bit across all
      accounts — once a
# project path is trusted anywhere, it stays trusted in the
      merged portion.
local _tr_files=() _tr_acct
for _tr_acct in "${accts[@]}"; do [[ -s
      "$_tr_acct/.claude.json" ]] &&
      _tr_files+=("$_tr_acct/.claude.json"); done
if (( ${#_tr_files[@]} >= 1 )); then
  local _trusted
  _trusted="$(jq -s '[ .[] | (.projects // {}) | to_entries[]
                      | select(.value.hasTrustDialogAccepted ==
      true) | .key ] | unique' \
             "${_tr_files[@]}" 2>/dev/null || printf '[]')"
  if [[ -n "$_trusted" && "$_trusted" != "[]" ]]; then
    local _tt; _tt="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
    if jq --argjson trusted "$_trusted" '
          .projects //= {}
          | reduce ($trusted[]) as $p
      (.; .projects[$p].hasTrustDialogAccepted = true)
        ' "$prev" > "$_tt" 2>/dev/null && jq -e . "$_tt" >/dev/
      null 2>&1; then
      command mv -f "$_tt" "$prev"
```

```
      else rm -f "$_tt"; fi
    fi
  fi

  # Now $prev holds the merged shared portion. Write each
      account's file with
  # its own private keys overlaid on top of the shared portion.
  for acct in "${accts[@]}"; do
    local f="$acct/.claude.json" out
    out="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
    if [[ -s "$f" ]]; then
      # Guard against set -e: a corrupt $f makes jq fail, which
        would abort
      # the whole loop and leave the remaining accounts unsynced.
      if ! jq -s --argjson priv "$CMA_CLAUDE_JSON_PRIVATE_KEYS" '
        . as [$shared, $own]
        | ($own | with_entries(select(.key as $k | $priv |
        index($k)))) as $priv_only
        | ($shared // {}) * $priv_only
      ' "$prev" "$f" > "$out" 2>/dev/null; then
        rm -f "$out"
        cma_warn ".claude.json for $acct could not be merged
        (invalid JSON?) — leaving original alone"
        continue
      fi
    else
      # New account, no existing .claude.json. Seed with shared
        content only.
      cp "$prev" "$out"
    fi
    # Final sanity: only replace if the output is parseable JSON.
    if jq -e . "$out" >/dev/null 2>&1; then
      command mv -f "$out" "$f"
    else
      rm -f "$out"
      cma_warn "merged .claude.json for $acct was invalid —
        leaving original file untouched"
    fi
  done
  rm -f "$prev"
}

# Detect Linux vs macOS for platform-specific commands.
cma_os() {
  case "$(uname -s)" in
    Linux*)   echo linux ;;
    Darwin*)  echo macos ;;
    *)        echo unknown ;;
  esac
}

# Portable realpath. BSD/macOS `readlink` has no `-f`, so
      `readlink -f` is a hard
```

```
# error there (prints "illegal option -- f", returns empty) even
      after a bash-4
# re-exec, because /usr/bin/readlink stays BSD. This resolves a
      path to its
# canonical absolute form by walking the symlink chain with
      single-arg
# `readlink` (supported everywhere) plus `pwd -P` — the same
      technique every
# script's LIB_DIR resolver uses. Safe under `set -e`.
cma_realpath() {
  local p="$1" t dir base
  while [ -L "$p" ]; do
    t="$(readlink "$p")"
    case "$t" in /*) p="$t" ;; *) p="$(dirname "$p")/$t" ;; esac
  done
  dir="$(cd "$(dirname "$p")" 2>/dev/null && pwd -P)" || dir="$
      (dirname "$p")"
  base="$(basename "$p")"
  printf '%s/%s\n' "$dir" "$base"
}

# cma_probe_run SECONDS BIN [ARG...] — BOUNDED run of a binary
      with any probe
# grammar; prints the first 20 lines of its combined output, never
      hangs, and
# never stalls its caller.
#
# Why not `timeout 15 "$bin" ... | head -20` (the previous shape):
#   1. `timeout` is absent on macOS without coreutils, and the
      fallback that
#      shipped there ran the binary UNBOUNDED — a wedged router
      hung the
#      installer forever (review finding I1, 2026-07-22).
#   2. Even where `timeout` exists, a probed binary that spawns a
      child which
#      inherits stdout keeps the PIPE open after the parent is
      killed, so the
#      `head` reader can still wait forever on EOF. The PROBE's
      output goes to
#      a temp FILE instead: a file read cannot block on a
      straggler's open
#      descriptor. That protects against stragglers of the PROBE —
      the
#      watchdog arm needs its own discipline, next point.
#   3. The WATCHDOG below is backgrounded, so it inherits the
      CALLER's stdio —
#      and when the caller captures this function through a
      command
#      substitution, that stdout IS the $( ) pipe. After a fast
      probe the
#      disarm kill orphaned the watchdog's `sleep SECONDS` child,
      which kept
#      the pipe write-end open, so the caller blocked for the FULL
      budget
```

```
#       even though the verdict was already correct (+15s on every
          healthy
#       install/verify — review finding I3, 2026-07-23, measured).
          The
#       watchdog's stdio is therefore detached to /dev/null: a
          background
#       helper must never hold a descriptor its caller waits on.
          The guard for
#       this class is behavioural — test_install_clean_host_ccr.sh
          case I
#       times a fast probe through a command substitution.
# One implementation for every host and every probe grammar — a
          single
# instrument to validate, instead of a proven branch plus an
          unproven fallback
# (§11.4.201: the path is part of the instrument).
#
# Returns the probe's own exit code, or 124 when the watchdog had
          to kill it
# (deliberately the same convention coreutils `timeout` uses, so
          callers can
# classify "wedged" with one check). Safe under `set -e` callers.
cma_probe_run() {
  local _budget="$1" _bin="$2"
  shift 2
  local _tmp _rc _pid _wpid
  _tmp="$(mktemp "${TMPDIR:-/tmp}/cma-probe.XXXXXX")" || return 1
  "$_bin" "$@" </dev/null >"$_tmp" 2>&1 &
  _pid=$!
  # Watchdog: TERM at the budget, KILL 2s later for a TERM-
          ignoring probe. It
  # drops a marker file BEFORE killing so "watchdog fired" is a
          recorded fact,
  # not inferred from an exit status the probe could also produce
          on its own.
  # stdio detached — header point 3 (I3): its orphaned sleep must
          not hold
  # the caller's command-substitution pipe.
  ( sleep "$_budget"; : >"${_tmp}.killed"; kill -TERM "$_pid" 2>/
          dev/null
    sleep 2; kill -KILL "$_pid" 2>/dev/null ) >/dev/null 2>&1 &
  _wpid=$!
  _rc=0; wait "$_pid" 2>/dev/null || _rc=$?
  kill "$_wpid" 2>/dev/null || true      # probe finished: disarm
          the watchdog
  wait "$_wpid" 2>/dev/null || true
  [ -e "${_tmp}.killed" ] && _rc=124
  head -20 "$_tmp"
  rm -f "$_tmp" "${_tmp}.killed"
  return "$_rc"
}

# cma_probe_help BIN [SECONDS] — BOUNDED `--help` probe:
          cma_probe_run with
```

```
# the one grammar every binary is expected to answer. Kept as the
      named entry
# point because "--help, default budget 15" is the contract the
      install-seam
# callers (claude-install-verify.sh, claude-ccr-build.sh) share.
cma_probe_help() {
  cma_probe_run "${2:-15}" "$1" --help
}

# cma_proxy_transform_family ID — does provider ID belong to a
      family cma-proxy
# transforms? Exit 0 when yes. Used by cma_run_provider to decide
      whether a
# MISSING cma-proxy is worth a warning: a provider with no shim
      loses nothing,
# so warning there would be a false positive (§11.4.201(1)).
#
# Normally the proxy binary itself answers (`cma-proxy --has-
      transform ID`),
# but with no binary present we cannot ask it — this list mirrors
      the
# registrations in scripts/proxy/*.go (registerRequest/
      registerResponse).
# KEEP IN SYNC with that registry: test_cma_proxy.sh asserts, in
      BOTH
# directions, that these families EQUAL the registered set, so a
      new transform
# provider added to the proxy without a family here fails the
      suite instead of
# silently missing its warning. Prefix-matched because ids carry
      variant
# suffixes (poe2 -> poe, kimi-k2 -> kimi) — the same folds
      providerKey() does.
cma_proxy_transform_family() {
  case "$1" in
    helixagent*|poe*|kimi*|kc*|sarvam*|nvidia*) return 0 ;;
    *) return 1 ;;
  esac
}

# Find all existing Claude account config directories under $HOME,
      matching
# the convention `.claude-<name>`. Echoes absolute paths, one per
      line,
# sorted. The default `~/.claude` is intentionally excluded
      because we treat
# it as the shared user-scope spot, not an account dir.
cma_detect_accounts() {
  local d
  while IFS= read -r d; do
    [[ "$d" == *"-shared" ]] && continue
    # Provider-alias dirs (~/.claude-prov-<id>, created by claude-
      providers)
    # are account-like for SHARED state but must NEVER be merged
      into
```

```
    # real-account auth/identity or unify, so they're excluded
        from detection
    # exactly like *-shared. This is the linchpin that keeps the
        existing
    # claudeN accounts and add-account untouched by the provider
        feature.
    [[ "$(basename "$d")" == "${ACCOUNT_PREFIX}prov-"* ]] &&
        continue

        # The claude-code-router config dir and any *.lock dir are
        not accounts.
    [[ "$(basename "$d")" == "${ACCOUNT_PREFIX}code-router" ]] &&
        continue
    [[ "$(basename "$d")" == *.lock ]] && continue
    # Archived removals (claude-remove-account's DEFAULT mode
        renames the dir to
    # `<dir>.removed.<timestamp>`) are NOT accounts. They keep
        their `projects/`

        # marker, so without this they kept counting forever — and
        the alias-commit
    # floor at _cma_alias_gate arms only while `src_acct >=
        n_acct`, so one
    # ordinary removal (2 aliases vs 3 "detected") silently
        disarmed that floor
    # PERMANENTLY on that host. It failed open rather than wrong,
        but a guard
    # that quietly stops guarding is not a guard.
    [[ "$(basename "$d")" == *.removed.* ]] && continue

        # Same reasoning for the pre-unify backups
        `backup_and_remove` leaves behind.
    [[ "$(basename "$d")" == *.preunify.* ]] && continue
    # Empty dirs always count (a brand-new account before any
        claude run).
    if [[ -z "$(ls -A "$d" 2>/dev/null)" ]]; then
      echo "$d"
      continue
    fi
    # Non-empty: must look like a Claude account (at least one
        tell-tale
    # file/dir). Filters out dirs that merely match the `.claude-
        *` prefix
    # but belong to other tools (e.g. `.claude-server-commander`).
    if [[ -d "$d/projects" || -d "$d/todos" || -d "$d/plugins" \
       || -f "$d/.claude.json" || -f "$d/.credentials.json" \
       || -f "$d/history.jsonl" ]]; then
      echo "$d"
    fi
  done < <(find "$HOME" -maxdepth 1 -type d -name "$
        {ACCOUNT_PREFIX}*" 2>/dev/null | sort)
}

# Read all aliases of the form `alias name=...` from $ALIAS_FILE
        and print
```

```
# their names (one per line). Returns nothing if the file is
        absent.
cma_existing_aliases() {
  [[ -f "$ALIAS_FILE" ]] || return 0
  awk -F'[ =]+' '/^[[:space:]]*alias[[:space:]]+/{print $2}'
        "$ALIAS_FILE"
}

# Suggest the next free `claude<N>` alias by scanning current
        aliases.
# E.g., if claude1 and claude2 exist, returns "claude3".
cma_suggest_alias() {
  local highest=0 n
  for a in $(cma_existing_aliases); do
    if [[ "$a" =~ ^claude([0-9]+)$ ]]; then
      n="${BASH_REMATCH[1]}"
      (( n > highest )) && highest="$n"
    fi
  done
  echo "claude$((highest + 1))"
}

# Validate that an alias name is safe to embed in a generated
        `alias ...=`
# line — strictly alphanumeric + underscore/hyphen, starting with
        a letter.
cma_validate_alias() {
  [[ "$1" =~ ^[a-zA-Z][a-zA-Z0-9_-]*$ ]] || cma_die
        "invalid alias name: $1"
}

# Match an rc-file line that sources an aliases.sh, capturing the
        path:
#   BASH_REMATCH[2] = the (possibly $HOME/~/quoted) target path.
# Anchored so leading-# comment lines (e.g. "# migrated to …/
        aliases.sh: …")
# never match. Used by the prune + dedup helpers below.
CMA_ALIAS_SRC_RE='^[[:space:]]*(source|\.)[[:space:]]+"?
        ([^"[:space:]]*aliases\.sh)"?[[:space:]]*$'

# The one managed header that heads the `source "<alias-file>"`
        block in every
# rc file. Spelled once here so the writer (append) and the reader
        (prune) agree
# on exactly what a "managed block" is — the bug that lost the
        operator's
# ~/.bashrc was the two disagreeing: the append wrote this header,
        the prune did
# not know to remove it, so every dropped source line left the
        header ORPHANED.
CMA_ALIAS_RC_HEADER='# Claude multi-account aliases'

# True if $1 is an `aliases.sh` source line (source|. form). Sets
        BASH_REMATCH.
```

```
_cma_is_alias_src_line() { [[ "$1" =~ $CMA_ALIAS_SRC_RE ]]; }
# Echo the resolved target path an alias-source line ($1) points
        at, or nothing.
_cma_alias_src_target() {
  [[ "$1" =~ $CMA_ALIAS_SRC_RE ]] || return 1
  local t="${BASH_REMATCH[2]}"; t="${t/#\$HOME/$HOME}"; t="${t/
        #\~/$HOME}"
  printf '%s' "$t"
}

# Portable mtime (epoch seconds). GNU `stat -c %Y`; BSD/macOS
        `stat -f %m`
# (which has no `-c`). Deliberately NOT `date -r <path>`: on BSD
        `date -r` reads
# its argument as epoch seconds rather than a file, silently
        returning 0 for
# every path — the macOS breakage that made this a §11.4.68 /
        §11.4.81 finding.
_cma_mtime() { stat -c %Y "$1" 2>/dev/null || stat -f %m "$1" 2>/
        dev/null || echo 0; }

# Newest existing rolling backup for $rc, by mtime (empty if
        none).
cma_newest_rc_backup() {
  local rc="$1" f newest="" ntime=-1 t
  for f in "$rc".cma-backup.*; do
    [[ -e "$f" ]] || continue
    t="$(_cma_mtime "$f")"
    if (( t >= ntime )); then ntime="$t"; newest="$f"; fi
  done
  printf '%s' "$newest"
}

# cma_backup_rc_file <rc>
# Protect a user rc file BEFORE the toolkit modifies it. Two
        backups:
#   * <rc>.cma-orig — the PRISTINE original, written exactly ONCE
        and NEVER
#     overwritten. This is the load-bearing recovery point: once a
        corrupted
#     state exists on disk it can never bury the true original.
#   * <rc>.cma-backup.<epoch> — a rolling snapshot of recent
        state, RATE-LIMITED:
#     skipped when byte-identical to the newest existing rolling
        backup. Without
#     this, BASH_ENV=~/.bashrc firing the prune->ensure cycle on
        every
#     non-interactive bash would spray hundreds of identical
        copies.
# Returns 0 when the rc is protected (or does not exist yet, so a
        fresh create
# loses nothing). Returns 1 when the PRISTINE backup could not be
        taken — the
# caller MUST then refuse to modify rather than proceed
        unprotected.
```

```
cma_backup_rc_file() {
  local rc="$1" orig="$1.cma-orig" newest ts cand i=0
  [[ -f "$rc" ]] || return 0                # nothing on disk =>
        nothing to lose

  # 1. Pristine original: create once, never overwrite. A failure
        here is fatal
  #    to the modification — an unwritable dir can still allow an
        append (which
  #    needs only file-write), so refusing here is what actually
        prevents an
  #    unprotected write.
  if [[ ! -e "$orig" ]]; then
    if ! cp -p -- "$rc" "$orig" 2>/dev/null; then
      cma_warn "cannot write pristine backup $orig — refusing to
        modify $rc"
      return 1
    fi
  fi

  # 2. Rolling snapshot, rate-limited. Best-effort: the pristine
        copy above is
  #    the guarantee; a rolling-backup failure does not block the
        modification
  #    (the recovery point already exists).
  newest="$(cma_newest_rc_backup "$rc")"
  if [[ -n "$newest" ]] && cmp -s -- "$rc" "$newest"; then
    return 0
  fi
  ts="$(date +%s)"
  cand="$rc.cma-backup.$ts"
  while [[ -e "$cand" ]]; do i=$((i+1)); cand="$rc.cma-backup.$ts.
        $i"; done
  cp -p -- "$rc" "$cand" 2>/dev/null || true
  return 0
}

# _cma_rc_rewrite_ok <rc> <candidate> <intended_removed_lines>
# Sanity gate for any rc rewrite, mirroring cma_alias_commit's
        alias-file gate.
# Refuse to publish a candidate that: is empty while it was meant
        to keep lines;
# fails a shell syntax parse (bash -n for a .bashrc, zsh -n for
        a .zshrc when zsh
# is present); or lost more lines than the operation intended to
        remove.
_cma_rc_rewrite_ok() {
  local rc="$1" cand="$2" removed="$3" src_lines cand_lines
        expected
  src_lines="$(grep -c '' "$rc"   2>/dev/null || echo 0)"
  cand_lines="$(grep -c '' "$cand" 2>/dev/null || echo 0)"
  expected=$(( src_lines - removed ))
  (( expected < 0 )) && expected=0
```

```
  # 1. Empty candidate that was supposed to preserve content =
      truncation.
  if [[ ! -s "$cand" ]] && (( expected > 0 )); then
    cma_warn "rc rewrite rejected: empty candidate for $rc would
      drop $expected intended line(s)"
    return 1
  fi
  # 2. Must still parse in the target shell.
  case "$rc" in
    *.zshrc)
      if command -v zsh >/dev/null 2>&1; then
        zsh -n "$cand" 2>/dev/null || { cma_warn "rc rewrite
        rejected: zsh -n failed on candidate for $rc"; return 1; }
      fi ;;
    *)
      bash -n "$cand" 2>/dev/null || { cma_warn "rc rewrite
        rejected: bash -n failed on candidate for $rc"; return
        1; } ;;
  esac
  # 3. Must not have lost lines the operation did not intend to
      remove.
  if (( cand_lines < expected )); then
    cma_warn "rc rewrite rejected: candidate for $rc lost $((
      expected - cand_lines )) unintended line(s)"
    return 1
  fi
  return 0
}

# ── Managed rc-block sentinels + the single rc-rewrite committer
      ──────────────
# A managed rc block is delimited by a BEGIN/END sentinel PAIR
      (unlike the legacy
# single `CMA_ALIAS_RC_HEADER` comment, which had NO END marker —
      that is exactly
# what ORPHANED when its source line was pruned, piling up ~93
      headers). One
# stable marker id per block ("path", …); begin/end are derived
      from the marker
# through one builder so the writer and the reader can never
      disagree.
_cma_rc_begin() { printf '# cma-rc:%s BEGIN — managed by claude-
      multi-account; do not edit inside' "$1"; }
_cma_rc_end()   { printf '# cma-rc:%s END' "$1"; }
# Named sentinels for the markers in use (tests + code share one
      source of truth).
# shellcheck disable=SC2034  # public surface: consumed by
      test_rc_safety.sh, which sources lib.sh
CMA_RC_PATH_BEGIN="$(_cma_rc_begin path)"
# shellcheck disable=SC2034  # public surface: consumed by
      test_rc_safety.sh, which sources lib.sh
CMA_RC_PATH_END="$(_cma_rc_end path)"

# cma_rc_safe_rewrite <rc> <candidate_tmp>
      <intended_removed_lines>
```

```
# THE single committer for any WHOLE-FILE rc rewrite — the rc analogue of
# cma_alias_commit. Every path that would `mv` a rebuilt file over a live rc
# funnels through here. Order is load-bearing and mirrors the proven prune path:
#   1. no-op guard      — a byte-identical candidate ⇒ discard, touch nothing;
#   2. sanity gate      — _cma_rc_rewrite_ok (empty/parse/content-loss). A reject
#                         is PARKED as <rc>.rejected.<ts>; the live rc is untouched;
#   3. backup-or-refuse — cma_backup_rc_file; no pristine backup ⇒ DO NOT modify
#                         (§11.4.167(D));
#   4. publish          — one command mv, INT/TERM masked across the rename.
# Consumes <candidate_tmp> (moved or removed) on every return path.
# Returns 0 published (or no-op), 1 rejected/refused.
cma_rc_safe_rewrite() {
  local rc="$1" cand="$2" removed="${3:-0}" prev_int prev_term rc2=0
  [[ -f "$cand" ]] || return 1

  # 1. No-op guard (before any backup): a settled host writes nothing.
  if [[ -f "$rc" ]] && cmp -s -- "$cand" "$rc"; then rm -f "$cand"; return 0; fi

  # 2. Sanity gate — refuse a content-losing / unparseable candidate; park it.
  if ! _cma_rc_rewrite_ok "$rc" "$cand" "$removed"; then
    command mv -f "$cand" "$rc.rejected.$(date +%s)" 2>/dev/null || rm -f "$cand"
    cma_warn "$rc left untouched; rewrite candidate kept as $rc.rejected.*"
    return 1
  fi

  # 3. Backup-or-refuse — no pristine backup ⇒ no modify.
  if ! cma_backup_rc_file "$rc"; then rm -f "$cand"; return 1; fi

  # 4. Publish — one rename, INT/TERM masked (mirrors cma_alias_commit F4).
  prev_int="$(trap -p INT || true)"
  prev_term="$(trap -p TERM || true)"
  trap '' INT TERM
  if command mv -f "$cand" "$rc"; then rc2=0; else rm -f "$cand"; rc2=1; fi
  trap - INT TERM
  if [[ -n "$prev_int" ]]; then eval "$prev_int"; fi
  if [[ -n "$prev_term" ]]; then eval "$prev_term"; fi
  return "$rc2"
}
```

```
# cma_rc_append_managed <rc> <marker> <payload-line...>
# Append a BEGIN/
        END-delimited managed block to <rc>, backup-first and
        idempotent:
#   * no-op if a live block for <marker> is already present;
#   * refuses to modify if the pristine backup cannot be taken
        (§11.4.167(D));
#   * an absent rc is first-touched (cma_backup_rc_file returns 0
        for absent, and
#     there is nothing to lose).
cma_rc_append_managed() {
  local rc="$1" marker="$2"; shift 2
  local begin end
  begin="$(_cma_rc_begin "$marker")"
  end="$(_cma_rc_end "$marker")"
  if [[ -f "$rc" ]] && grep -qxF -- "$begin" "$rc"; then return
        0; fi   # idempotent
  if ! cma_backup_rc_file "$rc"; then
    cma_warn "skipped managed '$marker' block in $rc (could not
        back it up)"
    return 1
  fi
  { printf '\n%s\n' "$begin"; printf '%s\n' "$@"; printf '%s\n'
        "$end"; } >> "$rc"
  cma_log "added managed '$marker' block to $rc"
}

# cma_rc_remove_block <rc> <marker>
# Remove the managed <marker> block (BEGIN..END) as a UNIT; no-op
        if absent. An
# unterminated BEGIN (file truncated inside the block by an
        outside tool) removes
# from BEGIN to EOF — never leaving a half block / orphan header.
        The rewrite is
# published through cma_rc_safe_rewrite (gate + backup + mv).
cma_rc_remove_block() {
  local rc="$1" marker="$2" begin end tmp removed
  [[ -f "$rc" ]] || return 0
  begin="$(_cma_rc_begin "$marker")"
  end="$(_cma_rc_end "$marker")"
  grep -qxF -- "$begin" "$rc" || return 0
  tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")" || return 1
  awk -v b="$begin" -v e="$end" '
    $0==b {skip=1; c++; next}
    skip && $0==e {skip=0; c++; next}
    skip {c++; next}
    {print}
    END {print c+0 > "/dev/stderr"}' "$rc" 2>"$tmp.n" >"$tmp" ||
        true
  removed="$(cat "$tmp.n" 2>/dev/null || echo 0)"; rm -f "$tmp.n"
  cma_rc_safe_rewrite "$rc" "$tmp" "${removed:-0}"
}
```

```
# Remove rc-file lines that source an aliases.sh whose target no
      longer exists
# (a stale path from a moved install, or a transient ALIAS_FILE
      used in testing).
# Without this, a deleted alias file leaves a dangling line that
      errors
# "-bash: …/aliases.sh: No such file or directory" on every new
      login shell.
#
# The managed `# Claude multi-account aliases` header and its
      source line are
# treated as ONE block: a dead block drops both (never orphaning
      the header), and
# a header that no longer heads a live source line is collapsed
      away (self-heal
# for the orphans a pre-fix toolkit already accumulated). A bare
      source line with
# no managed header is still pruned when its target is gone. Every
      rewrite is
# guarded by the sanity gate + a mandatory backup: a bad candidate
      is parked as
# <rc>.rejected.<ts> and the live rc is left untouched; if the
      backup cannot be
# taken the rc is not modified at all.
cma_prune_stale_alias_sources() {
  local rc="$1" tmp removed=0 n i line target
  [[ -f "$rc" ]] || return 0

  local lines=()
  while IFS= read -r line || [[ -n "$line" ]]; do
      lines+=("$line"); done < "$rc"
  n=${#lines[@]}

  tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")" || return 0
  i=0
  while (( i < n )); do
    line="${lines[$i]}"
    if [[ "$line" == "$CMA_ALIAS_RC_HEADER" ]]; then
      if (( i + 1 < n )) && _cma_is_alias_src_line "${lines[$
        ((i+1))]}"; then
        target="$(_cma_alias_src_target "${lines[$((i+1))]}")"
        if [[ -f "$target" ]]; then
          printf '%s\n' "$line" >> "$tmp"                 # live
        block: keep header
          printf '%s\n' "${lines[$((i+1))]}" >> "$tmp"
        # ...and its source line
        else
          removed=$((removed + 2))                        # dead
        block: drop both
        fi
        i=$((i + 2)); continue
      fi
      removed=$((removed + 1)); i=$((i + 1)); continue     #
        orphan header: collapse
    fi
```

```
    if _cma_is_alias_src_line "$line"; then
      target="$(_cma_alias_src_target "$line")"
      if [[ ! -f "$target" ]]; then removed=$((removed + 1)); i=$
        ((i + 1)); continue; fi
    fi
    printf '%s\n' "$line" >> "$tmp"
    i=$((i + 1))
  done

  if (( removed == 0 )); then rm -f "$tmp"; return 0; fi

  # Publish through the single rc-rewrite committer (gate →
        backup-or-refuse →
  # INT/TERM-masked mv, with a .rejected.<ts> park on a bad
        candidate). The
  # candidate-building block/orphan logic above is unchanged.
  cma_rc_safe_rewrite "$rc" "$tmp" "$removed" \
    && cma_log "pruned stale/orphaned managed alias block(s) from
        $rc"
}

# True if $rc already sources a file resolving to $2 (across `.`/
        `source` and
# $HOME/~/absolute forms), so we never append a duplicate source
        line.
cma_rc_sources_alias_file() {
  local rc="$1" want="$2" line target want_real
  [[ -f "$rc" ]] || return 1
  want_real="$(cma_realpath "$want" 2>/dev/null || printf '%s'
        "$want")"
  while IFS= read -r line || [[ -n "$line" ]]; do
    if [[ "$line" =~ $CMA_ALIAS_SRC_RE ]]; then
      target="${BASH_REMATCH[2]}"; target="${target/#\$HOME/
        $HOME}"; target="${target/#\~/$HOME}"
      [[ "$(cma_realpath "$target" 2>/dev/null || printf '%s'
        "$target")" == "$want_real" ]] && return 0
    fi
  done < "$rc"
  return 1
}

# ============================================================================
# Alias file: one renderer, one lock, one rename.
# ============================================================================
# WHY THIS SHAPE — forensics of the 2026-07-20 alias-file
        destruction. The live
# aliases.sh collapsed 37288 -> 282 -> 32112 -> 974 -> 909 ->
        25682 -> 130 bytes
# inside four seconds, losing the header, BOTH wrapper functions
        and every
# `alias claudeN=` line. No single writer was buggy:
        `cma_ensure_alias_file`
# performed SIX sequential whole-file read-modify-write migrations
        plus two
```

```
# direct `cat >> "$ALIAS_FILE"` appends, while `claude-providers
        list
# --refresh-aliases` — fired by the session hook on EVERY shell
        start —
# performed 21 more whole-file rewrites. Each was atomic and
        content-preserving
# in isolation; together, with no lock anywhere on the file, one
        writer's stale
# snapshot silently overwrote another writer's committed result
        (lost update).
# The corruption timestamp preceded the incidental SIGTERM by ~14
        minutes, so
# this is clean-run reachable, not an interrupt-only hazard.
#
# The three properties that fix it, in order of leverage:
#
#   1. RENDER ONCE. The complete file (managed block + carried
        lines + the
#      session-hook block) is built in ONE temp and committed with
        a SINGLE
#      rename. There is no intermediate on-disk state for a
        concurrent reader
#      or writer to snapshot, and the drop-then-re-append
        migrations disappear
#      entirely — the wrappers are always emitted at their current
        version, so
#      there is nothing to "migrate". That also kills the orphaned
        `# Wrapper:`
#      comment leak: the old drop-awk started at the `cma_run() {`
        line and left
#      the 4-line comment above it behind while the re-append put
        the function
#      at the end, leaking 5 dead lines and reordering the file on
        every firing
#      (~15 orphans had accumulated on the live host).
#
#   2. NO-OP GUARD. If the render is byte-identical to what is on
        disk, nothing
#      is written and the lock is never even taken. On a steady-
        state host this
#      turns 21 renames per shell start into zero writes, so the
        common path
#      cannot enter the race at all. This is the highest-leverage
        part.
#
#   3. EXCLUSIVE LOCK. The remaining read-render-rename is still a
#      read-modify-write, so it runs under an $ALIAS_FILE-scoped
        exclusive lock.
#      Contention policy is caller-set via CMA_ALIAS_LOCK_WAIT:
        the session hook
#      uses 0 (give up instantly — a shell start must NEVER block,
        and a skipped
#      refresh is harmless because the next writer re-renders from
        the file).
#
```

```
# Plus a sanity gate (never commit a file missing the header,
       either wrapper, or
# any alias it did not explicitly drop).
#
# What protects WHAT, stated precisely, INCLUDING what the test
       suite does and
# does not cover. Two earlier versions of this comment overclaimed
       here; both
# corrections below were established by deleting the mechanism and
       re-running.
#
#   * No half-file can be published because of RENDER-ONCE + a
       single mv(2).
#     That property holds with the signal mask removed, and a 15-
       iteration
#     SIGTERM test cannot tell the difference. The mask is not
       what earns it.
#
#   * The INT/TERM mask is DEFENCE IN DEPTH WITH NO TEST-VISIBLE
       EFFECT, and
#     saying otherwise was the second overclaim. The narrow thing
       it was
#     credited with — stopping a signal between the rename and the
       lock release
#     from leaking the lock — is not, in fact, a hazard either
       backend suffers:
#       - flock: the lock is an fd. Process death releases it in
       the kernel,
#         mask or no mask. There is nothing to leak.
#       - mkdir: a leaked lock dir names a dead pid, and the very
       next acquire
#         reclaims it via _cma_alias_lock_break_stale — inside the
       SAME call,
#         at any wait including 0. It does not make later writers
       skip.
#     So deleting `trap '' INT TERM` leaves the suite green, and
       no honest test
#     distinguishes it. What it genuinely buys is that the saved
       INT/TERM traps
#     are restored rather than left disarmed for the caller. It is
       kept for
#     that and for the narrow interrupt-safety it costs nothing to
       have — NOT
#     because anything here proves it necessary. Do not cite it as
       tested.
#
#   * MUTUAL EXCLUSION is the lock's job and nothing else's. The
       storm in
#     test_alias_file_concurrency.sh section 1 does NOT measure
       it: its writers
#     all write the SAME content, so a lost update is re-derived
       on the next
#     iteration, and deleting the lock acquire outright leaves
       that section
#     passing 3/3. Section 1b is what measures it — N one-shot
       DISTINCT writes,
```

```
#     nothing to re-derive a loss — and that is the case which
        found the mkdir
#     backend was not excluding at all (see
        _cma_alias_lock_break_stale).

# Sentinels bracketing the machine-owned region. Everything
        between them is
# regenerated verbatim on every write; everything outside is
        carried over
# untouched (user additions survive — see the "unrelated user line
        preserved"
# coverage test). Pre-sentinel files are recognised by content
        instead, once,
# by _cma_alias_carryover's legacy rules.
CMA_ALIAS_MANAGED_BEGIN='# cma-managed BEGIN — regenerated by
        claude-multi-account; do not edit inside'
CMA_ALIAS_MANAGED_END='# cma-managed END'
CMA_ALIAS_HOOK_BEGIN='# cma-providers-session-refresh BEGIN'
CMA_ALIAS_HOOK_END='# cma-providers-session-refresh END'

# --- exclusive lock on the alias file
        -------------------------------------
# This deliberately MIRRORS scripts/tests/lib/suite-lock.sh
        (flock(1) where
# present, otherwise an atomic mkdir(2) lock with rename-verified
        stale
# breaking — macOS ships no flock) rather than sourcing it. suite-
        lock.sh is
# test infrastructure: its acquire() `exit 75`s the process on
        contention and
# installs its own EXIT/INT/TERM traps. Both are unacceptable in a
        library that
# runs inside install scripts and, transitively, shell startup —
        so the same
# primitive is re-implemented here with a returns-a-status
        contract, no process
# exit, and no trap hijacking.
#
# KNOBS
#   CMA_ALIAS_LOCK_WAIT        seconds to wait on contention
        (default 30);
#                              0 = fail fast, used by the session
        hook
#   CMA_ALIAS_LOCK_NO_FLOCK=1  force the portable fallback (tests
        exercise the
#                              macOS path on Linux)
#   CMA_ALIAS_LOCK_STALE_GRACE seconds a pid-less lock dir may
        exist before it
#                              is treated as stale (default 10)
CMA_ALIAS_LOCK_WAIT="${CMA_ALIAS_LOCK_WAIT:-30}"
CMA_ALIAS_LOCK_STALE_GRACE="${CMA_ALIAS_LOCK_STALE_GRACE:-10}"
_cma_alias_lock_depth=0
_cma_alias_lock_mode=""
_cma_alias_lock_file=""
```

```
# Sanitised wait, in seconds. A junk value must not abort the
       caller under
# `set -e` when it reaches an arithmetic test.
_cma_alias_lock_wait() {
  case "${CMA_ALIAS_LOCK_WAIT:-}" in
    ''|*[!0-9]*) printf '30\n' ;;
    *)           printf '%s\n' "$CMA_ALIAS_LOCK_WAIT" ;;
  esac
}

_cma_alias_lock_pid() {
  local p=""
  if [[ "$_cma_alias_lock_mode" == "mkdir" ]]; then
    p="$(head -1 "$_cma_alias_lock_file/pid" 2>/dev/null || true)"
  else
    p="$(head -1 "$_cma_alias_lock_file" 2>/dev/null || true)"
  fi
  printf '%s' "$p" | tr -d '[:space:]'
}

# Discard a lock whose owner is gone.
#
# WHY THIS IS NOT THE OBVIOUS "rename it aside and look at it".
# It used to be. That version renamed the lock directory to a
       private path,
# read the pid inside, and renamed it BACK when the pid was not
       the one it had
# judged dead. Two flaws compounded, and together they cost the
       mkdir backend
# mutual exclusion outright — measured, not theorised: 12 one-shot
       concurrent
# writers each adding a DIFFERENT alias lost at least one
       COMMITTED alias in
# roughly 40% of runs, with the caller told rc 0. That is a lost
       update, the
# very failure that destroyed the live alias file.
#
#   1. TOCTOU on the holder's identity. The caller samples the
       pid, then tests
#      liveness. A holder that RELEASED NORMALLY and then exited
       is
#      indistinguishable from one that died holding the lock: by
       the time
#      `kill -0` runs the pid is gone, while the directory has
       already been
#      re-created by a different, LIVE writer. The audit trace for
       this bug
#      shows the judged holder exiting 1ms before the test that
       condemned it.
#   2. The restore was not atomic. Between `mv lock aside` and `mv
       aside lock`
#      the lock DOES NOT EXIST, so any contender's `mkdir`
       succeeds there. The
```

```
#      displaced holder never learns it lost the lock, and two
        processes enter
#      the critical section together. Every double-hold in the
        audit is
#      preceded, within ~15ms, by exactly this restore.
#
# So the directory is never moved. It is inspected IN PLACE and
        removed only
# once proven stale, under a short-lived breaker lock that makes
# inspect-then-remove exclusive among breakers. That closes the
        window: a
# directory whose recorded pid is dead cannot be released by its
        owner (it is
# dead) and cannot be removed by another breaker (we hold the
        breaker lock), so
# nothing can re-create it under a LIVE owner between the check
        and the removal.
#
# NOTE: tests/lib/suite-lock.sh carries the older shape. It is
        deliberately NOT
# converged with this one — it is global-by-design test
        infrastructure with a
# different contract (it exits the process on contention) — but it
        has the same
# hazard, at far lower stakes (one suite run per checkout).
_cma_alias_lock_break_stale() {
  local observed="${1:-}" brk="${_cma_alias_lock_file}.breaker"
        bpid got
  # Breaker exclusivity: mkdir(2) is the atomic claim. Losing it
        is not an
  # error — someone else is already breaking, so we simply retry
        the acquire.
  if ! mkdir "$brk" 2>/dev/null; then
    # A breaker that died mid-break would wedge every later one,
        so a breaker
    # lock whose owner is gone is reaped. This is the ONLY thing
        this branch
    # may remove; it never touches the alias lock itself.
    bpid="$(head -1 "$brk/pid" 2>/dev/null || true)"
    bpid="$(printf '%s' "$bpid" | tr -d '[:space:]')"
    if [[ -n "$bpid" ]] && ! kill -0 "$bpid" 2>/dev/null; then
      rm -rf "$brk" 2>/dev/null || true
    fi
    return 0
  fi
  printf '%s\n' "$$" > "$brk/pid" 2>/dev/null || true

  # Re-read the evidence as late as possible and grade the
        directory we are
  # about to delete, never a pid the caller sampled an iteration
        ago.
  got="$(_cma_alias_lock_pid)"
  if [[ -n "$observed" ]]; then
    # Still the same holder we judged, and still gone.
```

```
    if [[ "$got" == "$observed" ]] && ! kill -0 "$got" 2>/dev/
        null; then
      rm -rf "$_cma_alias_lock_file" 2>/dev/null || true
    fi
  elif [[ -z "$got" ]]; then
    # Pid-less. The caller only asks for this after
        CMA_ALIAS_LOCK_STALE_GRACE
    # seconds of CONTINUOUS emptiness, which is what separates
        "the winner has
    # not written its pid yet" (microseconds) from "the winner
        died in between".
    # That grace, not this re-read, is the guard for the empty
        case.
    rm -rf "$_cma_alias_lock_file" 2>/dev/null || true
  fi

  rm -rf "$brk" 2>/dev/null || true
  return 0
}

# Acquire (or re-enter) the alias-file lock. Returns 1 on
        contention timeout —
# never exits, never blocks longer than CMA_ALIAS_LOCK_WAIT.
_cma_alias_lock_acquire() {
  _cma_alias_lock_depth=$(( _cma_alias_lock_depth + 1 ))
  if (( _cma_alias_lock_depth > 1 )); then return 0; fi   # re-
        entrant

  local dir wait_s deadline holder empty_since=""
  dir="$(dirname "$ALIAS_FILE")"
  mkdir -p "$dir" 2>/dev/null || true
  wait_s="$(_cma_alias_lock_wait)"

  if command -v flock >/dev/null 2>&1 && [[ -z "$
        {CMA_ALIAS_LOCK_NO_FLOCK:-}" ]]; then
    _cma_alias_lock_mode="flock"
    _cma_alias_lock_file="$dir/.aliases.lock"
    # APPEND mode on purpose: `exec 8>file` truncates at open,
        erasing a live
    # holder's PID record before we even contend.
    if ! exec 8>>"$_cma_alias_lock_file"; then
      _cma_alias_lock_depth=0; return 1
    fi
    if ! flock -n 8; then
      if (( wait_s <= 0 )) || ! flock -w "$wait_s" 8; then
        # BRACES ARE LOAD-BEARING. `exec 8>&- 2>/dev/null` is NOT
        "close fd 8,
        # quietly": a command-less `exec` applies EVERY
        redirection on the line
        # to the shell PERMANENTLY, so the `2>/dev/null` silences
        this
        # process's stderr for the rest of its life. That fired
        here on every
```

```
      # contended acquire — precisely when the caller has
      something to say —

      # and it swallowed claude-add-account's whole "here is how
      to finish
      # the job" message, leaving a user with a config dir, no
      alias, and no
      # explanation. Scoping the redirection to a group closes
      the fd and
      # leaves stderr alone.
      { exec 8>&-; } 2>/dev/null || true
      _cma_alias_lock_depth=0
      return 1
    fi
  fi
  printf '%s\n' "$$" > "$_cma_alias_lock_file" 2>/dev/null ||
      true
  return 0
fi

_cma_alias_lock_mode="mkdir"
_cma_alias_lock_file="$dir/.aliases.lockdir"
deadline=$(( $(date +%s) + wait_s ))
while :; do
  if mkdir "$_cma_alias_lock_file" 2>/dev/null; then
    printf '%s\n' "$$" > "$_cma_alias_lock_file/pid" 2>/dev/
      null || true

    # A contender mid stale-break could have swapped the dir
    out from under
    # us; the recorded PID is the tiebreaker.
    if [[ "$(_cma_alias_lock_pid)" != "$$" ]]; then continue; fi
    return 0
  fi
  holder="$(_cma_alias_lock_pid)"
  if [[ -z "$holder" ]]; then
    # mkdir won but the pid write has not landed yet — or the
      winner died in
    # between. Give it a grace window before declaring the lock
      stale.
    [[ -n "$empty_since" ]] || empty_since="$(date +%s)"
    if (( $(date +%s) - empty_since >=
      CMA_ALIAS_LOCK_STALE_GRACE )); then
      _cma_alias_lock_break_stale ""
      empty_since=""
      continue
    fi
  else
    empty_since=""
    if ! kill -0 "$holder" 2>/dev/null; then
      _cma_alias_lock_break_stale "$holder"
      continue
    fi
  fi
```

```
    if (( $(date +%s) >= deadline )); then
      _cma_alias_lock_depth=0
      return 1
    fi
    sleep 0.1 2>/dev/null || sleep 1
  done
}

_cma_alias_lock_release() {
  (( _cma_alias_lock_depth > 0 )) || return 0
  _cma_alias_lock_depth=$(( _cma_alias_lock_depth - 1 ))
  if (( _cma_alias_lock_depth > 0 )); then return 0; fi
  if [[ "$_cma_alias_lock_mode" == "mkdir" ]]; then
    # Only remove a lock we still own — after a stale break the
        directory may
    # belong to someone else.
    if [[ "$(_cma_alias_lock_pid)" == "$$" ]]; then
      rm -rf "$_cma_alias_lock_file" 2>/dev/null || true
    fi
  else
    # The file is deliberately NOT unlinked: unlinking a flock
        target races a
    # contender who already opened the old inode.
    flock -u 8 2>/dev/null || true
    # Braces, for the reason spelled out in
        _cma_alias_lock_acquire. This site
    # was the worse of the two: it is on the SUCCESS path, so
        every process
    # that committed an alias — install.sh, claude-add-account,

        # claude-providers sync — ran the rest of its life with
        stderr pointed at

        # /dev/null and lost every warning and error it later
        tried to report.
    { exec 8>&-; } 2>/dev/null || true
  fi
  return 0
}

# --- the managed block
        ------------------------------------------------------
# One emitter per piece. These are the ONLY definitions of the
        wrappers; the
# renderer always emits the current text, which is why no drop/re-
        append
# migration (and no orphan-comment leak) exists any more.

# The ccr-self-reference test, as ONE definition serving THREE
        call sites:
# cma_run_provider (which lives inside the emitted alias file and
        therefore has
# no access to lib.sh's functions), providers-verify.sh, and
        lib.sh itself. The
```

```
# emitter below is the single source of the text; the alias file
        gets it via
# _cma_emit_managed, and this shell gets it via the `eval`
        immediately after, so
# the two copies cannot drift. The previous arrangement — a `case`
        duplicated at
# lib.sh's launch gate and providers-verify.sh's Gate 0 — under-
        matched every
# spelling except the four it literally listed, so
        `127.0.1.1:3456` (Debian's
# DEFAULT loopback for the local hostname), any other 127/8
        address, the
# v4-mapped and fully-expanded IPv6 loopbacks, `LOCALHOST`, a
        `user@` prefix and
# a `?query`/`#fragment` suffix all sailed through the guard and
        re-armed the
# exact helixagent hazard the guard exists to stop.
_cma_emit_ccr_gateway_guard() {
  cat <<'CMA_CCRGW_EOF'
# True when $1 is a URL pointing at the LOCAL ccr gateway (port
        $2, default
# $CMA_CCR_PORT or 3456). Such a base_url has no upstream: routing
        through it
# means serving whatever provider ccr last routed to, with no
        error anywhere.
# Matches the whole 127/8 range, 0.0.0.0, `localhost` in any case,
        and IPv6
# loopback in every spelling (::1,
        0:0:0:0:0:0:0:1, ::ffff:127.0.0.1, …),
# tolerating userinfo, path, query and fragment. A different port,
        a
# non-loopback host, or a remote https base is NOT a match.
_cma_is_ccr_gateway() {
  local url="${1:-}" want="${2:-${CMA_CCR_PORT:-3456}}" hp host
        port v4 squash
  [[ -n "$url" ]] || return 1
  hp="${url#*://}"          # drop the scheme
  hp="${hp%%/*}"            # drop the path
  hp="${hp%%\?*}"           # drop a query that followed no path
  hp="${hp%%#*}"            # drop a fragment that followed no
        path
  hp="${hp##*@}"            # drop userinfo (greedy: the LAST '@'
        wins)
  case "$hp" in
    \[*\]:*) host="${hp%]:*}"; host="${host#[}"; port="$
        {hp##*]:}" ;;
    *:*)     host="${hp%%:*}"; port="${hp##*:}" ;;
    *)       return 1 ;;    # no explicit port -> not the gateway
  esac
  [[ "$port" == "$want" ]] || return 1
  host="$(printf '%s' "$host" | tr '[:upper:]' '[:lower:]')"
  case "$host" in
    localhost|localhost.localdomain) return 0 ;;
    0.0.0.0) return 0 ;;
```

```
    # 127/8, but only as a real dotted quad: `127.example.com` is
        a hostname.
    127.*) case "$host" in *[!0-9.]*) return 1 ;; *) return 0 ;;
        esac ;;
    # IPv4-mapped/compatible IPv6 (::ffff:127.0.0.1): grade the
        embedded v4.
    *:*.*.*.*)
      v4="${host##*:}"
      case "$v4" in
        *[!0-9.]*) return 1 ;;
        127.*|0.0.0.0) return 0 ;;
        *) return 1 ;;
      esac ;;
    # Pure IPv6: loopback (::1) and unspecified (::) in any zero-
        compression.
    *:*)
      squash="${host//:/}"; squash="${squash//0/}"
      [[ -z "$squash" || "$squash" == "1" ]] && return 0
      return 1 ;;
  esac
  return 1
}
CMA_CCRGW_EOF
}
# Define it in THIS shell from the exact same bytes the alias file
        receives.
eval "$(_cma_emit_ccr_gateway_guard)"

# Dynamic account dispatcher (live defect 2026-07-23, `claude5`):
        a newly
# added account's alias is INVISIBLE to every shell that sourced
        the alias
# file BEFORE the add — and long-lived shells are the norm (tmux
        panes
# survive SSH re-logins; re-attaching does NOT restart the pane's
        shell, so
# "log out and back in" does not pick the alias up). The static
        per-account
# `alias claudeN=…` lines can never fix that class: an alias must
        exist at
# shell start.
#
# The dispatcher closes the class STRUCTURALLY: a command-not-
        found handler
# (bash: command_not_found_handle; zsh: command_not_found_handler)
        resolves
# `<name>` -> $HOME/<prefix><name> at INVOCATION time from the
        config dirs,
# so ANY account added AFTER a shell sourced a dispatcher-bearing
        alias file
# works in that shell immediately, with no re-source. It is a pure
        FALLBACK:
# defined aliases/functions/binaries always win (the handler only
        fires when
# nothing else matched), a pre-existing handler (e.g. Ubuntu's
```

```
# command-not-found) is preserved and chained for non-account
      names, and a
# non-account miss still reports "command not found" with rc 127.
#
# Honest boundary: shells that sourced a PRE-dispatcher alias file
      remain
# stale until they re-source once (claude-add-account warns about
      exactly
# this) — the dispatcher eliminates the staleness class from then
      on, it
# cannot retroactively appear in old shells. Accounts created with
      a custom
# --dir that does not follow the $HOME/<prefix><alias> pattern are
      resolved
# by their (re-sourced) alias line only; the dispatcher cannot
      infer such a
# mapping and does not guess (§11.4.6).
_cma_emit_account_dispatch() {
  # The account-dir prefix is embedded at render time (like
      CLAUDE_BIN above)
  # so the emitted file is self-contained; the runtime fallback
      keeps a
  # hand-truncated header from breaking dispatch entirely.
  printf '_CMA_ACCOUNT_PREFIX=%q\n' "${ACCOUNT_PREFIX:-.claude-}"
  cat <<'CMA_DISPATCH_EOF'
# True when $1 names a launchable ACCOUNT: a plain command word
      (no path
# separator, not an option, not dot-prefixed) whose $HOME/
      <prefix>$1 config
# dir exists. Provider config dirs (<prefix>prov-*) and the
      router's own dir
# (<prefix>code-router) are NOT accounts — providers launch via
# cma_run_provider and must never be hijacked by the account
      fallback.
_cma_is_account_cmd() {
  case "${1:-}" in ''|*/*|-*|.*) return 1 ;; esac
  case "$1" in prov-*|code-router) return 1 ;; esac
  [ -d "$HOME/${_CMA_ACCOUNT_PREFIX:-.claude-}$1" ]
}
_cma_cnf_impl() {
  if _cma_is_account_cmd "${1:-}"; then
    local _cma_d="$HOME/${_CMA_ACCOUNT_PREFIX:-.claude-}$1"
    shift
    CLAUDE_CONFIG_DIR="$_cma_d" cma_run "$@"
    return $?
  fi
  # Not an account: hand off to whatever handler existed before
      this file was
  # sourced (captured below), else reproduce the shell's stock
      behaviour.
  if declare -f _cma_prev_cnf_handle >/dev/null 2>&1; then
    _cma_prev_cnf_handle "$@"
    return $?
  fi
```

```
  printf '%s: command not found\n' "${1:-}" >&2
  return 127
}
# Preserve a PRE-EXISTING handler exactly once. Idempotent across
        re-sources:
# a definition that already routes through _cma_cnf_impl is OURS
        and must not
# be captured as "previous" (that would chain the handler to
        itself).
if [ -n "${BASH_VERSION:-}" ]; then
  _cma_cnf_name=command_not_found_handle
else
  _cma_cnf_name=command_not_found_handler
fi
_cma_cnf_def="$(declare -f "$_cma_cnf_name" 2>/dev/null || true)"
case "$_cma_cnf_def" in
  *_cma_cnf_impl*) : ;;
  '') : ;;
  *) eval "_cma_prev_cnf_handle() ${_cma_cnf_def#*'()'}" ;;
esac
unset _cma_cnf_def _cma_cnf_name
# Define BOTH spellings; each shell consults only its own, the
        other is inert.
command_not_found_handle()  { _cma_cnf_impl "$@"; }
command_not_found_handler() { _cma_cnf_impl "$@"; }
CMA_DISPATCH_EOF
}

# ATM-850 remediation half 2 (2026-07-23): operator-facing tmux
        staleness
# notice. The dispatcher above closes the new-account staleness
        class for
# every shell that sourced a dispatcher-bearing alias file; shells
        older than
# that render still hold pre-dispatcher definitions until they re-
        source ONCE.
# tmux pane shells are the canonical long-lived case (five servers
        from 00:00
# survived the 15:14 add in the live incident; SSH re-login re-
        attaches the
# SAME server). This function only DETECTS and PRINTS — the exact
        re-source
# command plus a per-server broadcast one-liner scoped to idle
        SHELL panes —
# and NEVER sends keys itself: an autonomous send-keys could type
        into a pane
# the operator is mid-edit in. Callers may offer an interactive,
# default-No broadcast on top (claude-add-account does).
cma_tmux_stale_shell_notice() {
  local alias_file="${1:-$ALIAS_FILE}"
  command -v tmux >/dev/null 2>&1 || return 0
  local tdir="${TMUX_TMPDIR:-/tmp}/tmux-$(id -u 2>/dev/null ||
        echo 0)"
  [[ -d "$tdir" ]] || return 0
```

```
  local sock cmds n total=0
  local -a servers=()
  for sock in "$tdir"/*; do
    [[ -S "$sock" ]] || continue
    cmds="$(tmux -S "$sock" list-panes -a -F
        '#{pane_current_command}' 2>/dev/null)" || continue
    [[ -n "$cmds" ]] || continue
    n="$(printf '%s\n' "$cmds" | grep -cE '^-?(bash|zsh|sh|dash|
        ksh|fish)$')" || n=0
    servers+=("$n:$sock"); total=$(( total + n ))
  done
  (( ${#servers[@]} )) || return 0
  printf
        '\n[tmux] %d running tmux server(s) detected — their pane
        shells read the alias file when THEY started, not now.\n'
        "${#servers[@]}"
  if grep -q '_cma_cnf_impl' "$alias_file" 2>/dev/null; then
    printf '[tmux] This alias file carries the dynamic account
        dispatcher: shells that sourced a\n'
    printf '[tmux] dispatcher-bearing render resolve NEW accounts
        at invocation time — no re-source needed there.\n'
    printf '[tmux] Only shells that sourced an OLDER (pre-
        dispatcher) render still need ONE re-source:\n'
  else
    printf '[tmux] Every pre-existing shell needs a re-source to
        see this account:\n'
  fi
  printf '           source %s\n' "$alias_file"
  printf '[tmux] %d shell pane(s) detected across those servers.
        To push the re-source into the idle\n' "$total"
  printf '[tmux] SHELL panes of a server (editors/agents/panes
        running programs are skipped):\n'
  local ent
  for ent in "${servers[@]}"; do
    sock="${ent#*:}"
    printf "         tmux -S %s list-panes -a -F '#{pane_id}
        #{pane_current_command}' | awk '\$2 ~ /^-?(bash|zsh|sh|
        dash|ksh|fish)\$/{print \$1}' | xargs -r -I{} tmux -S %s
        send-keys -t {} C-u ' source %s' Enter\n" "$sock" "$sock"
        "$alias_file"
  done
  return 0
}

_cma_emit_cma_run() {
  cat <<'CMA_RUN_BODY_EOF'
# Wrapper: keeps .claude.json projects/session index synced across
        every
# logged-in account. Pulls merged state from every account into
        the launching
# one before claude runs; pushes the post-session state back out
        after exit.
# Cheap (jq deep-merge of one ~50KB file per account), runs
        unconditionally.
cma_run() {
```

```
# Self-heal CLAUDE_BIN: the alias file normally exports it at
      the top, but if
# that header line is missing (corrupted or hand-edited alias
      file) every
# invocation would silently expand to an empty command ("-
      bash: : command
# not found"). Mirrors cma_resolve_claude_bin inline so the
      function body is
# self-contained regardless of the header state. §11.4.185.
if ! command -v "${CLAUDE_BIN:-}" >/dev/null 2>&1; then
  if command -v claude >/dev/null 2>&1; then
    CLAUDE_BIN="$(command -v claude)"
  else
    for _cma_cb in "$HOME/.local/bin/claude" "$HOME/.npm-global/
      bin/claude" \
                   /opt/homebrew/bin/claude /usr/local/bin/
      claude; do
      [ -x "$_cma_cb" ] && { CLAUDE_BIN="$_cma_cb"; break; }
    done
    if ! command -v "${CLAUDE_BIN:-}" >/dev/null 2>&1; then
      printf 'cma_run: claude binary not found — check PATH or
      re-run install.sh\n' >&2
      return 127
    fi
  fi
fi
# Provider-env isolation: native claudeN must talk to the real
      Anthropic API.
# A provider alias run earlier in THIS shell exports
      ANTHROPIC_BASE_URL etc.;
# those persist and would otherwise leak into this native launch
      (claude1
# silently using a provider's endpoint). Clear them so native is
      always clean.
# The 4 ANTHROPIC_DEFAULT_*_MODEL tier-map vars are exported by
# cma_run_provider (native transport) and PERSIST after that
      alias returns; a
# subsequent native claudeN launch MUST clear them too, else the
      opus/sonnet/
# haiku/fable tier resolution silently points at the previous
      provider's
# serving model instead of the real Anthropic tier.
unset ANTHROPIC_BASE_URL ANTHROPIC_AUTH_TOKEN ANTHROPIC_MODEL
      ANTHROPIC_SMALL_FAST_MODEL
unset ANTHROPIC_DEFAULT_OPUS_MODEL
      ANTHROPIC_DEFAULT_SONNET_MODEL
      ANTHROPIC_DEFAULT_HAIKU_MODEL
      ANTHROPIC_DEFAULT_FABLE_MODEL
# Token-guard isolation: cma_run_provider exports
      CLAUDE_CODE_MAX_OUTPUT_TOKENS
# (output cap, clamped <=128000),
      CLAUDE_CODE_AUTO_COMPACT_WINDOW (input
# compact trigger) and CLAUDE_CODE_MAX_CONTEXT_TOKENS (the
      provider's real
```

```
# context size for client-side accounting) for every provider
      alias; ALL
# persist in this shell after that alias returns. A subsequent
      native claudeN
# launch MUST clear them, else native inherits a provider's
      (possibly small)
# output cap, compact window, or context size instead of the
      real Anthropic
# per-model defaults — silently capping native's output or
      early-compacting
# its context. Parallels the ANTHROPIC_DEFAULT_* tier-map
      isolation above.
unset CLAUDE_CODE_MAX_OUTPUT_TOKENS
      CLAUDE_CODE_AUTO_COMPACT_WINDOW
      CLAUDE_CODE_MAX_CONTEXT_TOKENS
# Working-dir hook (opt-in; no-op when absent). Resolution
      order:
#   1. CMA_CWD_HOOK env var               — explicit user
      override
#   2. <git-toplevel>/.claude-cwd-hook     — per-project hook
      (each repo
#      gets its own multitrack resolver, preventing a single
      global hook
#      from hijacking every project's sessions)
#   3. ~/.local/bin/claude-cwd-hook        — global fallback
# The hook runs before claude-session (below) so auto-session
      keys to the
# resolved worktree root. Escape hatch: MULTITRACK_DISABLE=1
      (honored
# inside the hook itself; the toolkit does not check it).
local _cma_cwd_hook _cma_cwd_label _cma_cwd_target
if [[ -n "${CMA_CWD_HOOK:-}" ]]; then
  _cma_cwd_hook="$CMA_CWD_HOOK"
else
  local _cma_hook_root
  _cma_hook_root="$(git rev-parse --show-toplevel 2>/dev/null ||
      pwd)"
  if [[ -x "$_cma_hook_root/.claude-cwd-hook" ]]; then
    _cma_cwd_hook="$_cma_hook_root/.claude-cwd-hook"
  else
    _cma_cwd_hook="$HOME/.local/bin/claude-cwd-hook"
  fi
fi
if [[ -x "$_cma_cwd_hook" ]] && ! git rev-parse --show-toplevel
      >/dev/null 2>&1; then
  _cma_cwd_label="$(basename "${CLAUDE_CONFIG_DIR:-claude}")";
      _cma_cwd_label="${_cma_cwd_label#.claude-}"
  _cma_cwd_target="$("$_cma_cwd_hook" "$_cma_cwd_label" 2>/dev/
      null || true)"
  if [[ -n "$_cma_cwd_target" && -d "$_cma_cwd_target" ]]; then
      cd "$_cma_cwd_target" 2>/dev/null || true; fi
fi
if [[ -x "$HOME/.local/bin/claude-sync-state" ]]; then
  "$HOME/.local/bin/claude-sync-state" pull "$CLAUDE_CONFIG_DIR"
      2>/dev/null || true
```

```
  fi
  # Auto session-per-project: when launched with NO args, resume
        (or create) the
  # one long-lived session for this project root, name it after
        the root dir,
  # trust the workspace, and hint the alias color. Only when bare
        so explicit
  # user flags (-p, --resume, a prompt, …) are always respected
        verbatim.
  # claude-session emits only "--resume <uuid>" or "--session-id
        <uuid> --name
  # <kebab>" (no shell metacharacters), so eval-splitting is safe
        and works in
  # both bash and zsh (zsh does not word-split unquoted
        expansions).
  local _cma_label=""
  if [[ $# -eq 0 && -x "$HOME/.local/bin/claude-session" ]]; then
    local _cma_sf
    _cma_sf="$("$HOME/.local/bin/claude-session" flags
        "$CLAUDE_CONFIG_DIR" 2>/dev/null || true)"
    _cma_label="$(basename "${CLAUDE_CONFIG_DIR:-claude}")";
        _cma_label="${_cma_label#.claude-}"
    "$HOME/.local/bin/claude-session" hint "$_cma_label" 2>/dev/
        null || true
    eval "set -- $_cma_sf"
    # Auto-apply the per-alias color: a resumable session's jsonl
        exists now, so
    # colour it before launch; a brand-new session's file appears
        during launch,
    # so we colour it again after exit (see post-launch call
        below).
    "$HOME/.local/bin/claude-session" apply-color
        "$CLAUDE_CONFIG_DIR" "$_cma_label" 2>/dev/null || true
  fi
  "$CLAUDE_BIN" "$@"
  local rc=$?
  if [[ -x "$HOME/.local/bin/claude-sync-state" ]]; then
    "$HOME/.local/bin/claude-sync-state" push "$CLAUDE_CONFIG_DIR"
        2>/dev/null || true
  fi
  [[ -n "$_cma_label" && -x "$HOME/.local/bin/claude-session" ]]
        && \
    "$HOME/.local/bin/claude-session" apply-color
        "$CLAUDE_CONFIG_DIR" "$_cma_label" 2>/dev/null || true
  return $rc
}
CMA_RUN_BODY_EOF
}

# _cma_llmctl_ensure_active <provider_id> — on-demand llmctl
        profile switch,
# shared by ALL THREE llmctl-backed launch families
        (cma_run_provider /
# cma_run_kimi_provider / cma_run_pi_provider). Emitted ONCE into
        the managed
```

```
# alias-file block (see _cma_emit_managed) so every wrapper calls
        the SAME
# self-contained function rather than three copies drifting apart.
#
# THE GAP THIS CLOSES. An `llmctl-<profile>` provider record only
        ever gets
# REGISTERED (detect_llmctl_records, claude-providers.sh) while
        <profile> is
# ALREADY the live model at its fixed, catalog-assigned port —
        llmctl runs
# each catalog profile as its OWN independent server process, and
        this host's
# RAM/VRAM budget typically fits only 1-2 profiles running at
        once, so a
# second profile's alias (e.g. `llmctl-fast` while `vision` is the
        one
# actually running) previously either connected to the WRONG model
        or to
# nothing at all. `bin/llmctl switch <profile>` (llmctl repo,
        fixed and
# TDD-covered 2026-09-22 — atomic rollback-on-failure, see
# lib/scheduler.sh::_sched_switch_impl) is the safe, existing
        mechanism this
# function drives: it stops every other running profile and starts
        exactly
# the requested one, restoring the previously-running set on any
        failure so a
# failed switch attempt never strands the host with fewer services
        than
# before.
#
# EFFICIENCY: `llmctl switch` ALREADY no-ops (no stop/restart, no
        model
# reload) when <profile> is already the sole running profile — but
        calling it
# unconditionally on every single alias invocation still pays the
        cost of
# `llmctl`'s own lock acquisition + service scan on every back-to-
        back use of
# the SAME alias. This function checks `llmctl status` FIRST
        (mirroring
# llmctl's own sched_switch no-op condition byte-for-byte: "the
        profile is
# already the sole running profile") and only calls `llmctl
        switch` when the
# check says a switch is actually needed.
#
# SAFETY: a failed `llmctl switch` (non-zero exit) MUST NEVER be
        silently
# absorbed — the underlying CLI must NOT be launched against a
        fixed port
# that may now host the wrong model or nothing at all. This
        function
# propagates llmctl's own exit code verbatim and prints llmctl's
        own stderr,
```

```
# so the caller's `_cma_llmctl_ensure_active ... || return $?`
        idiom aborts
# the launch with a clear, actionable, honest error.
#
# Binary resolution mirrors detect_llmctl_records (claude-
        providers.sh) as
# far as is possible from a self-contained, decoupled alias-file
        body with no
# access to that script's own LIB_DIR (§11.4.28/§11.4.177 — this
        body must
# stay project-path-agnostic): CMA_LLMCTL_BIN env override first
        (same
# variable name detect_llmctl_records already honors), then the
        `bin` field
# of an explicitly-pointed-at CMA_LLMCTL_PINS_FILE, then the bare
        `llmctl`
# name resolved off PATH (the real host has ~/.local/bin/llmctl on
        PATH,
# exactly like every other CLI this toolkit's aliases resolve
        bare).
_cma_emit_llmctl_ensure_active() {
  cat <<'CMA_LLMCTL_ENSURE_ACTIVE_EOF'
# _cma_llmctl_active_profile <bin> — shared status-parse helper so
        the
# pre-switch check and the post-failure re-probe (T017) read
        llmctl's
# `status` output through the EXACT same parsing logic rather than
        two
# copies that could drift apart. Echoes "<row-count>\t<space-
        separated
# profile names, ALL rows>" — not just the last row (independent-
        review
# finding 4: a single-row capture made the post-failure re-probe
        falsely
# claim every other-still-running profile was "no longer running"
        on any
# host with 2+ profiles up, since only the last-seen name
        survived).
_cma_llmctl_active_profile() {
  local _cma_lap_bin="$1" _cma_lap_status="" _cma_lap_rows=0
        _cma_lap_names=""
  _cma_lap_status="$("$_cma_lap_bin" status 2>/dev/null)" ||
        _cma_lap_status=""
  if [[ -n "$_cma_lap_status" && "$_cma_lap_status" != "no llmctl
        services running" ]]; then
    local _cma_lap_line
    while IFS= read -r _cma_lap_line; do
      [[ -n "$_cma_lap_line" ]] || continue
      [[ "${_cma_lap_line%%[[:space:]]*}" == "profile" ]] &&
        continue
      _cma_lap_rows=$(( _cma_lap_rows + 1 ))
      _cma_lap_names="${_cma_lap_names:+$_cma_lap_names }$
        {_cma_lap_line%%[[:space:]]*}"
    done <<<"$_cma_lap_status"
  fi
  printf '%s\t%s\n' "$_cma_lap_rows" "$_cma_lap_names"
```

```
}
_cma_llmctl_ensure_active() {
  local _cma_lc_id="${1:-}"
  case "$_cma_lc_id" in
    llmctl-*) : ;;
    *) return 0 ;;
  esac
  local _cma_lc_profile="${_cma_lc_id#llmctl-}"
  [[ -n "$_cma_lc_profile" ]] || return 0
  local _cma_lc_bin="${CMA_LLMCTL_BIN:-}"
  if [[ -z "$_cma_lc_bin" ]]; then
    local _cma_lc_pins="${CMA_LLMCTL_PINS_FILE:-}"
    if [[ -n "$_cma_lc_pins" && -f "$_cma_lc_pins" ]] && command
        -v jq >/dev/null 2>&1; then
      _cma_lc_bin="$(jq -r '.bin // empty' "$_cma_lc_pins" 2>/dev/
        null)" || _cma_lc_bin=""
      [[ "$_cma_lc_bin" != "null" ]] || _cma_lc_bin=""
    fi
  fi
  : "${_cma_lc_bin:=llmctl}"
  if ! command -v "$_cma_lc_bin" >/dev/null 2>&1; then
    printf 'claude-providers: llmctl binary (%s) not found --
        cannot verify or switch the active model for %s.\n' \
      "$_cma_lc_bin" "$_cma_lc_id" >&2
    printf '  Refusing to launch against a port that may host the
        wrong model or nothing at all.\n' >&2
    printf '  Install llmctl (or set CMA_LLMCTL_BIN to its path)
        and retry.\n' >&2
    return 9
  fi
  # Is <profile> ALREADY the sole running llmctl profile? Parse
        `llmctl
  # status`'s data rows the same way lib/
        scheduler.sh::sched_status prints
  # them (`printf '%-16s ...' "profile" ...` header, one left-
        justified row
  # per running profile, or the literal line "no llmctl services
        running"
  # when none are). This is exactly the set `_sched_switch_impl`
        itself
  # compares against for its own no-op decision -- never re-
        derived from a
  # different source of truth.
  local _cma_lc_rows=0 _cma_lc_row=""
  IFS=$'\t' read -r _cma_lc_rows _cma_lc_row <
        <(_cma_llmctl_active_profile "$_cma_lc_bin")
  if [[ "$_cma_lc_rows" -eq 1 && "$_cma_lc_row" ==
        "$_cma_lc_profile" ]]; then
    return 0
  fi
  printf 'claude-providers: switching llmctl to profile %s
        (currently: %s)...\n' \
    "$_cma_lc_profile" "${_cma_lc_row:-<none>}" >&2
  local _cma_lc_switch_out="" _cma_lc_switch_rc=0
```

```
_cma_lc_switch_out="$("$_cma_lc_bin" switch "$_cma_lc_profile"
      2>&1)" || _cma_lc_switch_rc=$?
if (( _cma_lc_switch_rc != 0 )); then
  # llmctl's own switch is best-effort-atomic (research.md
      LLMCTL-F2): on
  # failure it restores the previously-running set, but that
      restore can
  # ITSELF fail, leaving the host with FEWER services than
      before. Upstream
  # now exposes this as a distinct exit code (75, EX_TEMPFAIL --
      llmctl
  # commit ab4f4db, closing LLMCTL-F2) rather than only freeform
      stderr
  # text; check that FIRST (a real, documented contract) and
      keep the
  # original "ROLLBACK ALSO FAILED" string-match as a fallback
      for any
  # llmctl version predating that fix, so this still works
      against an
  # older binary rather than silently losing the marker. Detect
      it
  # explicitly and raise a DISTINCT, higher-severity marker this
      feature
  # owns, then independently RE-PROBE (never assume from the
      exit code
  # alone) whether the previously active profile actually
      survived the
  # failed switch.
  if (( _cma_lc_switch_rc == 75 )) || [[ "$_cma_lc_switch_out"
      == *"ROLLBACK ALSO FAILED"* ]]; then
    printf 'claude-providers: CRITICAL: llmctl rollback also
      failed while switching to %s (exit %d) -- the host may now
      be running FEWER models than before.\n' \
      "$_cma_lc_profile" "$_cma_lc_switch_rc" >&2
  else
    printf 'claude-providers: llmctl switch to %s FAILED (exit
      %d) -- refusing to launch against a possibly-wrong or
      absent backend.\n' \
      "$_cma_lc_profile" "$_cma_lc_switch_rc" >&2
  fi
  [[ -n "$_cma_lc_switch_out" ]] && printf '%s\n'
      "$_cma_lc_switch_out" >&2
  local _cma_lc_rows2=0 _cma_lc_row2=""
  IFS=$'\t' read -r _cma_lc_rows2 _cma_lc_row2 <
      <(_cma_llmctl_active_profile "$_cma_lc_bin")
  # Report the ACTUAL per-profile difference, never a row-count/
      last-row
  # proxy (independent-review finding 4): with 2+ profiles
      running before
  # the switch, "rows2 != rows-before" doesn't mean any of them
      actually
  # stopped -- membership is checked name-by-name against the
      post-failure
  # set. Three genuinely distinct, honestly-worded outcomes:
  if [[ "$_cma_lc_rows" -eq 0 ]]; then
```

```
      printf 'claude-providers: nothing was running before this
        switch attempt (now: %s).\n' \
        "${_cma_lc_row2:-no profile}" >&2
    else
      local _cma_lc_still="" _cma_lc_gone="" _cma_lc_name
      # Portable split across bash AND zsh (follow-up independent
        review,
      # finding 4): `for x in $var` relies on bash's default word-
        splitting
      # of an unquoted expansion, which zsh does NOT do by default
        -- this
      # function body is emitted verbatim into the shared alias
        file
      # (CMA_LLMCTL_ENSURE_ACTIVE_EOF heredoc above) and sourced
        into
      # whichever shell the operator runs (zsh on macOS, zsh
        via .zshrc on
      # Linux per CMA_RC_FILES -- see the house rule at lib.sh
        ~1183/1479).
      # A here-string + `while read` with IFS=newline splits
        identically in
      # both shells, matching the established pattern
      # `_cma_llmctl_active_profile` itself already uses just
        above.
      while IFS= read -r _cma_lc_name; do
        [[ -n "$_cma_lc_name" ]] || continue
        case " $_cma_lc_row2 " in
          *" $_cma_lc_name "*) _cma_lc_still="${_cma_lc_still:+
        $_cma_lc_still }$_cma_lc_name" ;;
          *) _cma_lc_gone="${_cma_lc_gone:+$_cma_lc_gone }
        $_cma_lc_name" ;;
        esac
      done <<<"$(printf '%s' "$_cma_lc_row" | tr ' ' '\n')"
      if [[ -z "$_cma_lc_gone" ]]; then
        printf 'claude-providers: previous profile %s confirmed
        still running.\n' "$_cma_lc_still" >&2
      elif [[ -z "$_cma_lc_still" ]]; then
        printf 'claude-providers: previous profile %s is NO LONGER
        running either -- %s now active.\n' \
          "$_cma_lc_gone" "${_cma_lc_row2:-no profile}" >&2
      else
        printf 'claude-providers: previous profile(s) still
        running: %s -- NO LONGER running: %s (now: %s).\n' \
          "$_cma_lc_still" "$_cma_lc_gone" "${_cma_lc_row2:-no
        profile}" >&2
      fi
    fi
    return "$_cma_lc_switch_rc"
  fi
  return 0
}
CMA_LLMCTL_ENSURE_ACTIVE_EOF
}
# Self-eval immediately (mirrors cma_run_kimi_provider/
        cma_run_pi_provider
```

```
# below): all three callers must be able to reach
        _cma_llmctl_ensure_active
# the instant lib.sh is sourced, not only after
        cma_ensure_alias_file has
# generated + something has sourced the managed alias file.
eval "$(_cma_emit_llmctl_ensure_active)"

_cma_emit_cma_run_provider() {
  cat <<'CMA_PROV_BODY_EOF'
cma_run_provider() {
  # Self-heal CLAUDE_BIN (same as cma_run — §11.4.185). Prevents
        "-bash: : command
  # not found" when the alias-file header export line is missing.
        Also resolves
  # the binary for the native-transport path ("$CLAUDE_BIN" "$@")
        below.
  if ! command -v "${CLAUDE_BIN:-}" >/dev/null 2>&1; then
    if command -v claude >/dev/null 2>&1; then
      CLAUDE_BIN="$(command -v claude)"
    else
      for _cma_cb in "$HOME/.local/bin/claude" "$HOME/.npm-global/
        bin/claude" \
                     /opt/homebrew/bin/claude /usr/local/bin/
        claude; do
        [ -x "$_cma_cb" ] && { CLAUDE_BIN="$_cma_cb"; break; }
      done
    fi
  fi
  if ! command -v "${CLAUDE_BIN:-}" >/dev/null 2>&1; then
    printf 'claude-providers: claude binary not found — check PATH
        or re-run install.sh\n' >&2
    return 127
  fi
  # --force bypasses the activation gate (operator override).
        Accepted BOTH as
  # the very first arg (direct call: cma_run_provider --force
        <id>) and as the
  # first arg after the id (alias path: `<alias> --force` expands
        to
  # cma_run_provider <id> --force). Either way it is consumed, not
        forwarded.
  local _cma_force=0
  if [[ "${1:-}" == "--force" ]]; then _cma_force=1; shift; fi
  # NOTE: `shift 2>/dev/null` here shifts ONE arg, not two — bash
        parses the `2`
  # as an fd redirect, so this is `shift >/dev/null`. That is
        deliberate: it
  # consumes the id, and the next line's guard re-checks --force.
        Do NOT "fix"
  # it to `shift 2 || true` — that would silently eat the first
        user arg (-p).
  local id="$1"; shift 2>/dev/null || true
  if [[ "${1:-}" == "--force" ]]; then _cma_force=1; shift; fi
  local pdir="$HOME/.local/share/claude-multi-account/providers"
```

```
local envf="$pdir/$id.env"
if [[ ! -f "$envf" ]]; then
  printf 'claude-providers: unknown provider %s (missing %s)\n'
      "$id" "$envf" >&2
  return 1
fi
# shellcheck disable=SC1090
source "$envf"
# Cross-alias env isolation: unset any ANTHROPIC_*/CLAUDE_CODE_*
      vars that
# leaked from a PREVIOUS cma_run_provider invocation in this
      shell. The
# transport-specific branches below re-export them from this
      provider's
# CMA_PROVIDER_* vars (fresh from source "$envf"), so the unset
      here is
# only clearing the leftover from the previous alias — identical
      to how
# cma_run (the native claudeN wrapper) isolates its ANTHROPIC_*
      vars.
unset ANTHROPIC_BASE_URL ANTHROPIC_AUTH_TOKEN ANTHROPIC_MODEL
      ANTHROPIC_SMALL_FAST_MODEL
# The 4 tier-default-model vars this same wrapper exports
      (native branch below)
# also persist into a following alias invocation; clear the
      previous run's
# values so this provider re-exports its own from
      CMA_PROVIDER_MODEL below.
unset ANTHROPIC_DEFAULT_OPUS_MODEL
      ANTHROPIC_DEFAULT_SONNET_MODEL
      ANTHROPIC_DEFAULT_HAIKU_MODEL
      ANTHROPIC_DEFAULT_FABLE_MODEL
unset CLAUDE_CODE_AUTO_COMPACT_WINDOW
      CLAUDE_CODE_MAX_OUTPUT_TOKENS
# Working-dir hook (same 3-tier resolution as cma_run). This
      must run
# BEFORE sync-state pull + session flags so the resolved
      directory is the
# session's canonical cwd. Without this, provider aliases ignore
      the
# multitrack resolver and launch in whatever $PWD the user
      happened to be in.
local _cma_cwd_hook _cma_cwd_label _cma_cwd_target
if [[ -n "${CMA_CWD_HOOK:-}" ]]; then
  _cma_cwd_hook="$CMA_CWD_HOOK"
else
  local _cma_hook_root
  _cma_hook_root="$(git rev-parse --show-toplevel 2>/dev/null ||
      pwd)"
  if [[ -x "$_cma_hook_root/.claude-cwd-hook" ]]; then
    _cma_cwd_hook="$_cma_hook_root/.claude-cwd-hook"
  else
    _cma_cwd_hook="$HOME/.local/bin/claude-cwd-hook"
  fi
fi
```

```
if [[ -x "$_cma_cwd_hook" ]] && ! git rev-parse --show-toplevel
      >/dev/null 2>&1; then
  _cma_cwd_label="$(basename "${CLAUDE_CONFIG_DIR:-claude}")";
      _cma_cwd_label="${_cma_cwd_label#.claude-}"
  _cma_cwd_target="$("$_cma_cwd_hook" "$_cma_cwd_label" 2>/dev/
      null || true)"
  if [[ -n "$_cma_cwd_target" && -d "$_cma_cwd_target" ]]; then
      cd "$_cma_cwd_target" 2>/dev/null || true; fi
fi
# Activation gate: only a 'verified' alias launches Claude Code.
      A non-verified
# alias (unverified / failed / pending) prints a clear,
      actionable message and
# refuses to launch, so a broken provider never surfaces as a
      confusing
# in-session error. Status comes from the non-secret status
      cache; this body is
# self-contained (no cma_* helpers) so it reads status.json with
      jq inline.
if (( ! _cma_force )); then
  local _cma_sf="$pdir/status.json" _cma_st="pending"
  if command -v jq >/dev/null 2>&1 && [[ -s "$_cma_sf" ]]; then
    _cma_st="$(jq -r --arg i "$CMA_PROVIDER_ID" '.[$i].status //
      "pending"' "$_cma_sf" 2>/dev/null)"
    [[ -n "$_cma_st" && "$_cma_st" != "null" ]] ||
      _cma_st="pending"
  fi
  if [[ "$_cma_st" != "verified" ]]; then
    printf 'claude-providers: alias %s is %s — not launching.\n'
      "$CMA_PROVIDER_ID" "$_cma_st" >&2
    printf '  Re-verify: claude-providers sync   (re-runs
      verification for %s)\n' "$CMA_PROVIDER_ID" >&2
    printf '  Override (operator): run the alias with --force\n'
      >&2
    return 3
  fi
fi
local keysf="${CMA_KEYS_FILE:-$HOME/api_keys.sh}"
# Disable nounset while sourcing the user-controlled keys file:
      it may have
# dangling refs (e.g. `export X=$UNSET`) that would abort the
      source under a
# caller's `set -u`, leaving the token empty. Save/restore so we
      never change
# the user's interactive shell options.
if [[ -f "$keysf" ]]; then
  case $- in *u*) local _cma_had_u=1 ;; *) local _cma_had_u=0 ;;
      esac
  set -a +u; source "$keysf"; set +a
  (( _cma_had_u )) && set -u
fi
# Indirect-expand the key var name. ${!var} is bash-only and a
      fatal error in
# zsh (the default macOS interactive shell this alias file is
      sourced into),
```

```
# so use eval, which works in both. CMA_PROVIDER_KEYVAR is a
      validated env
# var name ([A-Za-z_][A-Za-z0-9_]*), so this eval is safe.
local token="" _cma_xt=""
# Suppress xtrace around the indirect key read so an active `set
      -x` in the
# user's shell can't echo the secret to the terminal or a
      redirected log.
case $- in *x*) _cma_xt=1; set +x ;; esac
# Kimi Code OAuth sentinel: the OAuth token is SHORT-LIVED (~15
      min), so a
# sync-time snapshot is stale by the next launch. Freshness
      order:
#  1. the LIVE kimi-code credentials file, when unexpired (60s
      skew);
#  2. a CLI-triggered refresh (kimi -p hi) followed by a re-read
      of 1;
#  3. the token-file snapshot written at sync (last resort
      only).
if [[ "$CMA_PROVIDER_KEYVAR" == "_CMA_KIMICODE_OAUTH_" ]]; then
  local _cma_kcred="$HOME/.kimi-code/credentials/kimi-code.json"
  if [[ -f "$_cma_kcred" ]] && command -v jq >/dev/null 2>&1;
      then
    local _cma_kexp; _cma_kexp="$(jq -r '.expires_at // 0'
      "$_cma_kcred" 2>/dev/null || echo 0)"
    if (( _cma_kexp > $(date +%s) + 60 )); then
      token="$(jq -r '.access_token // ""' "$_cma_kcred" 2>/dev/
      null)"
    fi
  fi
  if [[ -z "$token" && -f "$_cma_kcred" ]] && command -v kimi >/
      dev/null 2>&1; then
    timeout 20 kimi -p "hi" --output-format text >/dev/null 2>&1
      || true
    token="$(jq -r '.access_token // ""' "$_cma_kcred" 2>/dev/
      null)"
  fi
  if [[ -z "$token" ]]; then
    local _cma_ktok="$pdir/${CMA_PROVIDER_ID}.token"
    [[ -f "$_cma_ktok" ]] && token="$(cat "$_cma_ktok" 2>/dev/
      null)" || token=""
  fi
else
  eval "token="\${$CMA_PROVIDER_KEYVAR:-}""
fi
[[ -n "$_cma_xt" ]] && set -x
if [[ -z "$token" ]]; then
  printf 'claude-providers: $%s is empty (set it in %s)\n'
      "$CMA_PROVIDER_KEYVAR" "$keysf" >&2
  return 1
fi
export CLAUDE_CONFIG_DIR="$CMA_PROVIDER_CONFIG_DIR"
# Input-context guard (fixes "400 exceeded model token limit:
      262144
```

```
# (requested: 311786)"): tell Claude Code this provider's REAL
      context window
# so it auto-compacts (at window-13000) before a request
      overshoots the
# provider's hard input limit. Without this, Claude Code assumes
      Anthropic's
# own large (~1M) window and lets the prompt grow past a smaller
      provider's
# cap. Fully dynamic — the value is CMA_PROVIDER_CONTEXT_LIMIT,
      resolved from
# the models.dev catalog (limit.context) per selected model.
      Applies to BOTH
# transports (native + router), so every provider alias is
      protected.
# NOTE: this caps INPUT context; CLAUDE_CODE_MAX_OUTPUT_TOKENS
      (set just
# below, before the transport branch, BOTH transports, clamped
      <=128000)
# caps OUTPUT — the two are independent halves of the guard.
# Auto-compact cap: only lower the window; never raise it above
      the cap.
# The DEFAULT cap is context-proportional — max(200000, context/
      2) — because
# a fixed 200000 was correct for 200K-class providers but
      produced the
# 2026-09-03 endless-compaction loop on 1M-class ones: a native-
      alias session
# grows to ~977K-1M tokens (native unsets every guard, see
      cma_run), and
# resumed under a provider alias whose window the 200000 cap
      forced to
# 176000, ONE substantive turn of real work (~150K tokens of
      tool results,
# measured live on the helix_code session) refilled past the
      trigger and
# compacted AGAIN — a compact on every turn, indistinguishable
      from an
# infinite loop. context/2 keeps the cap's original intent
      (compact around
# ~50% of the model's window, never near the hard limit) while
      giving
# large-context providers enough post-compact headroom for a
      resumed native
# session to actually continue. CMA_AUTO_COMPACT_CAP overrides
      outright.
#
# _cma_in_guard (v1.24.0): the input guard is exported for EVERY
      provider
# with a known context, CLAMPED — never skipped. The previous
      gate
# ("export only when CONTEXT_LIMIT <= cap") was FAIL-OPEN and
      backwards: a
# provider whose context was LARGER than the cap got no input
      guard at all,
# which is precisely the case that needs one. openrouter
      (catalog context
```

```
# 1000000) therefore ran unguarded on the input side while the
      output side
# reserved 128000, and the request overshot the endpoint's real
      262144
# window: 33796 + 103687 + 128000 = 265483. See _cma_out_guard
      below for the
# matching output half; the window is computed AFTER it, from
      ctx - out, so
# the two halves cannot sum past the context.
# --- cma-token-guards:begin --- (extracted verbatim by
      test_providers.sh;
# the guards are pure arithmetic over
      CMA_PROVIDER_{CONTEXT_LIMIT,MAX_OUTPUT},
# so the suite can exercise the SHIPPED source without launching
      anything.)
local _cma_compact_cap="${CMA_AUTO_COMPACT_CAP:-}"
# Sanitize the override: a non-numeric CMA_AUTO_COMPACT_CAP must
      fall back to
# the context-proportional default, never reach an integer
      comparison under
# set -e (which would abort every provider alias launch).
case "$_cma_compact_cap" in
  ''|*[!0-9]*) _cma_compact_cap="" ;;
esac
# _cma_out_guard (v1.16.0) + <=128000 clamp (§11.4.108/
      §11.4.111): output-
# token cap for BOTH transports, not just native. Without it,
      router
# providers run with Claude Code's generic default output cap
      (128000 for
# models it does not know) and long reasoning responses die with
      "Claude's
# response exceeded the 128000 output token maximum". The value
      starts from
# the provider model's REAL output limit (models.dev
      limit.output via
# CMA_PROVIDER_MAX_OUTPUT); proxies may clamp further API-side
# (sarvam_proxy's tier clamp). Exported ONCE here, before the
      transport
# branch, so router AND native behave identically (previously
      only the
# native branch re-exported it — an unclamped, transport-
      asymmetric raw
# value).
# Catalog caveat (live-proven on nvidia5): when limit.output >=
# limit.context the "output" number is really the context size —
      exporting
# it makes Claude Code request that many completion tokens, and
# input+request overshoots the shared window (400 "maximum
      context length
# is N … you requested M"). Only a genuinely separate output
      budget
# (output < context) is exported.
# Clamp caveat (live-proven, 128k Tier-1): exporting the model's
      THEORETICAL
```

```
# limit.output when it exceeds the CLI's own custom-model
      ceiling (deepseek
# 384000, xiaomi 131072) makes Claude Code request its OWN
      unknown-model
# ceiling (128000) and then FATALLY abort any length-truncated
      response:
# "…exceeded the 128000 output token maximum… set
# CLAUDE_CODE_MAX_OUTPUT_TOKENS". The CLI hard-caps custom
      models to 128000
# regardless, so any value >128000 is pointless — clamp to
# min(CMA_PROVIDER_MAX_OUTPUT, 128000).
# Sanitize-then-decide order is load-bearing (POSIX-shape so it
      behaves
# identically whether this body is sourced by bash or zsh), and
      NO
# arithmetic ever runs on an unsanitized value ([ N -gt .. ]
      errors past
# 2^63-1, and (( )) errors on non-integers —
      CMA_PROVIDER_MAX_OUTPUT traces
# to the user-settable CMA_HELIXAGENT_MAX_OUTPUT, fed via 'jq --
      argjson'
# which preserves huge-int digits verbatim, so both shapes are
      reachable):
#   1. empty / non-plain-integer (negatives, "1e6", "12.5") /
      zero -> NO
#      export: no real output budget is known, and the CLI's own
#      unknown-model default (128000) applies exactly as if the
      catalog had
#      no entry. (The pre-merge always-export-128000 default was
#      effect-equivalent for known models but could resurrect
      the nvidia5
#      overshoot on small-context catalog-gap models — the
      conditional
#      no-export subsumes it safely.)
#   2. >18 digits: past intmax — no test/(( )) arithmetic is
      safe. Any real
#      context (<=18 digits) is smaller, so with a usable
      context this is
#      the mislabel shape (-> NO export); with no usable context
      it
#      collapses to the 128000 cap WITHOUT arithmetic on the raw
      value.
#   3. <=18 digits (test-safe): floor 0/00/000 to no-export,
      apply the
#      nvidia5 mislabel skip (output >= context -> NO export),
      then the
#      128000 clamp. A leading-zero form like 007 tests as 7
      here, stays
#      <=128000, and exports as "007" (Claude Code parses it as
      decimal 7 —
#      min-semantics); a leading-zero 19+ digit form was already
      collapsed
#      by rule 2, so it is NEVER re-read as octal.
local _cma_out="${CMA_PROVIDER_MAX_OUTPUT:-}" _cma_octx="$
      {CMA_PROVIDER_CONTEXT_LIMIT:-}"
case "$_cma_octx" in
```

```
  ''|*[!0-9]*) _cma_octx="" ;;
  *) [ "${#_cma_octx}" -le 18 ] || _cma_octx="" ;;
esac
case "$_cma_out" in
  ''|*[!0-9]*) _cma_out="" ;;
  *) if [ "${#_cma_out}" -gt 18 ]; then
       # Past intmax no test/(( )) arithmetic is safe. With a
       known context
       # the carve-out below supplies the cap; with none, fall
       back to the
       # CLI ceiling WITHOUT arithmetic on the raw value (F2:
       never leak it
       # unclamped).
       if [ -n "$_cma_octx" ]; then _cma_out=""; else
       _cma_out=128000; fi
     elif [ "$_cma_out" -lt 1 ]; then _cma_out=""
     elif [ -n "$_cma_octx" ] && [ "$_cma_out" -ge
      "$_cma_octx" ]; then _cma_out=""
     fi ;;
esac
# Carve the output cap OUT of the context instead of trusting it
      alongside
# the context (v1.24.0). Leaving it unset is NOT the safe
      fallback it looks
# like: Claude Code's own default for an unknown model is
      128000, so "no
# export" IS a request for 128000 output tokens. kilo proves the
      point — its
# catalog row is the impossible ctx==out==262144, the mislabel
      branch above
# blanks the value, and the CLI default then reserves 128000
      against a 262144
# window that must also carry Claude Code's ~137K system-prompt
      + tool-schema
# floor. Whenever the context is known we therefore always emit
      a cap that
# provably fits: min(catalog output, context - input floor),
      bounded by the
# CLI's own 128000 ceiling and floored at 8192.
# Keep this in lockstep with CLAUDE_CODE_INPUT_FLOOR /
      MIN_SAFE_OUTPUT /
# CLI_MAX_OUTPUT_TOKENS in providers_resolve.py: the resolver
      bakes these
# numbers into the .env, and this block is the last line of
      defence for a
# stale or hand-edited one.
local _cma_in_floor="${CMA_INPUT_FLOOR:-160000}" _cma_cap=""
if [ -n "$_cma_octx" ]; then
  _cma_cap=$(( _cma_octx - _cma_in_floor ))
  if [ "$_cma_cap" -gt 128000 ]; then _cma_cap=128000; fi
  if [ "$_cma_cap" -lt 8192 ]; then _cma_cap=8192; fi
  if [ -z "$_cma_out" ] || [ "$_cma_out" -gt "$_cma_cap" ]; then
       _cma_out="$_cma_cap"; fi
elif [ -n "$_cma_out" ] && [ "$_cma_out" -gt 128000 ]; then
  _cma_out=128000
```

```
fi
if [ -n "$_cma_out" ]; then
  export CLAUDE_CODE_MAX_OUTPUT_TOKENS="$_cma_out"
fi
# Input half, computed from what the output half actually
      reserved so the two
# can never sum past the context. Clamped to the auto-compact
      cap, and
# exported for every known context — including the >cap ones the
      old gate
# silently skipped. This also closes the 200K-270K "dead zone",
      where a real
# window sat above the cap yet below cap+output and so got no
      guard at all.
#
# TOOL-SCHEMA BUDGET (live defect 2026-07-26, openrouter3): the
      old
# co-derivation window = context - output pretended the request
      is only
# text + output. The endpoint counts tools too — the provider's
      own 400
# named it: "maximum context length is 262144 … you requested
      about 371727
# tokens (199347 of text input, 70236 of tool input, 102144 in
      the output)".
# With window = 262144 - 102144 = 160000 the compact trigger sat
      at ~147000,
# and 147000 + 70236 tools + 102144 output = 319380 > 262144 —
      the endpoint
# rejected BEFORE compaction could ever help, on the FIRST
      request. The
# trigger must reserve for the tool payload as well:
#   window = context - output - CMA_TOOL_TOKEN_BUDGET (default
      80000).
# BE EXACT ABOUT WHICH DIRECTION IS DANGEROUS — the earlier note
      here had it
# backwards. An UNDERestimate does NOT merely "compact earlier":
      because the
# output cap is derived as ctx - min_win - budget, too small a
      budget INFLATES
# the output cap, and the request then overflows and the launch
      dies with a
# 400. Measured live 2026-07-27 on a host with 227 enabled
      plugins: real tool
# input 158112 against this 80000 default gave
#   46536 text + 158112 tools + 62144 output = 266792  on a
      262144 window.
# Note further that 158112 + 120000 (min window) already exceeds
      262144, so on
# such a host NO output cap makes a 262144-context provider fit:
      the enabled
# plugin surface has to shrink, or a wider-context provider must
      be used
# (nvidia 1000000 and xiaomi 1048576 fit it comfortably).
      Override per host
```

```
# via CMA_TOOL_TOKEN_BUDGET in the provider env or the shell. A
      context too
# small to reserve the budget yields no window at all: that
      provider cannot
# serve Claude Code's tool prefix regardless, and the launch
      must fail
# loudly upstream (the proof's context-inadequate class) rather
      than be
# lied to by a guard that cannot hold.
if [ -n "$_cma_octx" ]; then
  local _cma_win="$_cma_octx" _cma_tool_budget="$
      {CMA_TOOL_TOKEN_BUDGET:-80000}"
  local _cma_min_win="${CMA_MIN_COMPACT_WINDOW:-120000}"
  if [ -n "$_cma_out" ]; then _cma_win=$(( _cma_octx -
      _cma_out )); fi
  _cma_win=$(( _cma_win - _cma_tool_budget ))
  # Compression-loop guard: if the window is below the minimum
      viable size,
  # Claude Code triggers compaction on every request (system
      prompt + tool
  # schemas alone exceed the window), enters an infinite
      compression loop,
  # and never gets any work done. Raise the window by reducing
      the output
  # cap when possible, rather than exporting a window that
      cannot hold the
  # static overhead.
  if [ "$_cma_win" -lt "$_cma_min_win" ] && [ -n "$_cma_out" ]
      && [ "$_cma_out" -gt 8192 ]; then
    local _cma_new_out=$(( _cma_octx - _cma_min_win -
       _cma_tool_budget ))
    if [ "$_cma_new_out" -ge 8192 ]; then
      _cma_out="$_cma_new_out"
      _cma_win="$_cma_min_win"
      export CLAUDE_CODE_MAX_OUTPUT_TOKENS="$_cma_out"
    fi
  fi
  # Context-proportional compact cap (the 2026-09-03 loop fix):
      resolve the
  # default HERE, where the sanitized integer context is in
      scope. The floor
  # of 200000 keeps every <=400K-context provider byte-identical
      to the
  # pre-fix behaviour; only a provider whose context/2 exceeds
      200000 gets a
  # larger cap. An explicit CMA_AUTO_COMPACT_CAP always wins.
  if [ -z "$_cma_compact_cap" ]; then
    _cma_compact_cap=200000
    local _cma_half_ctx=$(( _cma_octx / 2 ))
    if [ "$_cma_half_ctx" -gt 200000 ]; then
       _cma_compact_cap="$_cma_half_ctx"; fi
  fi
  if [ "$_cma_win" -gt "$_cma_compact_cap" ]; then
      _cma_win="$_cma_compact_cap"; fi
```

```
  # Autocompact thrashing guard (v1.26.8): the raw window above
      consumes every
  # token the model can hold (text + tools + output = context).
      That leaves
  # zero headroom for the compacted summary itself, so after
      Claude Code
  # compacts the conversation the next large file read or tool
      output can
  # refill the context to the limit within a few turns — the
      exact "Autocompact
  # is thrashing" failure. Reserve a safety margin from the
      window so compaction
  # fires earlier and the post-compact context has meaningful
      breathing room.
  # The margin is applied ONLY when the provider can afford it
      without dropping
  # below the minimum viable window; tight providers keep their
      existing window
  # rather than trade one failure mode for another.
  local _cma_safety_margin="$
      {CMA_AUTO_COMPACT_SAFETY_MARGIN:-24000}"
  case "$_cma_safety_margin" in
    ''|0|*[!0-9]*) _cma_safety_margin=0 ;;
  esac
  if [ "$_cma_safety_margin" -gt 0 ] && [ "$_cma_win" -gt
      "$_cma_min_win" ]; then
    local _cma_max_margin=$(( _cma_win - _cma_min_win ))
    if [ "$_cma_safety_margin" -gt "$_cma_max_margin" ]; then
      _cma_safety_margin="$_cma_max_margin"
    fi
    _cma_win=$(( _cma_win - _cma_safety_margin ))
  fi
  if [ "$_cma_win" -gt 0 ]; then
    export CLAUDE_CODE_AUTO_COMPACT_WINDOW="$_cma_win"
  fi
fi
# --- cma-token-guards:end ---
# Sync .claude.json projects/session index across ALL accounts
      and providers
# so sessions created under any alias are visible from every
      other alias.
# Pull merged state before launch; push post-session state after
      exit.
if [[ -x "$HOME/.local/bin/claude-sync-state" ]]; then
  "$HOME/.local/bin/claude-sync-state" pull "$CLAUDE_CONFIG_DIR"
      2>/dev/null || true
fi
# _cma_session_flags (v1.17.0): per-project session resolution
      applies to
# BOTH transports — previously the flags block lived only in the
      native
# branch, so every router alias (kimi-*, poe, openrouter, …)
      always opened
# a FRESH session and could never see the project session
      another alias
```

```
# left behind. It also now covers conversation args: `alias -p
      "…"` used to
# skip resolution entirely (verbatim-args rule) and start a new
      session
# every time. Explicit session selectors and non-conversation
      subcommands
# are always left verbatim.
local _cma_psf=""
if [[ -x "$HOME/.local/bin/claude-session" ]]; then
  if [[ $# -eq 0 ]]; then
    # TRIM providers skip the stored session flags here too:
      `flags` emits
    # `--resume <id> …` for an existing project session, which
      drags the
    # synced history into the INTERACTIVE path just like the
      auto-resume
    # below does for conversation args (live issue 2026-07-22 —
      both seams
    # must stay history-free or a local model's window
      overflows).
    if [[ "${CMA_PROVIDER_TRIM:-}" != "bare" ]]; then
      _cma_psf="$("$HOME/.local/bin/claude-session" flags
      "$CLAUDE_CONFIG_DIR" 2>/dev/null || true)"
      # Resume-fit warning (same rationale as the conversation-
      args path
      # below): the flags form is `--resume <id> --name
      <kebab>`, so the
      # session id is word 2. Warn-only, never block.
      if [[ "$_cma_psf" == --resume\ * ]]; then
        local _cma_rsid _cma_est=""
        _cma_rsid="$(printf '%s\n' "$_cma_psf" | awk '{print
      $2}')"
        _cma_est="$("$HOME/.local/bin/claude-session" context-
      size "$CLAUDE_CONFIG_DIR" "$_cma_rsid" 2>/dev/null ||
      true)"
        case "$_cma_est" in ''|*[!0-9]*) _cma_est="" ;; esac
        if [[ -n "$_cma_est" && -n "$
      {CLAUDE_CODE_AUTO_COMPACT_WINDOW:-}" ]] \
            && [ "$_cma_est" -gt
      "$CLAUDE_CODE_AUTO_COMPACT_WINDOW" ]; then
          printf 'claude-providers: resume target %s holds ~%s
      tokens; provider %s compact window is %s — it will be
      compacted immediately on resume (then continue normally).
      \n' \
            "$_cma_rsid" "$_cma_est" "$CMA_PROVIDER_ID"
      "$CLAUDE_CODE_AUTO_COMPACT_WINDOW" >&2
        fi
      fi
    fi
    "$HOME/.local/bin/claude-session" hint "$CMA_PROVIDER_ID"
      2>/dev/null || true
    eval "set -- $_cma_psf"
    # Auto-apply this provider alias's color to the session
      (idempotent).
```

```
    "$HOME/.local/bin/claude-session" apply-color
      "$CLAUDE_CONFIG_DIR" "$CMA_PROVIDER_ID" 2>/dev/null ||
      true
    _cma_pcolor=1
  else
    case "$1" in
      --resume|--session-id|--continue|--fork-session|-c) ;;
      agents|mcp|export|doctor|install|update|config|plugin|
      setup|acp|server|web|provider) ;;
      *)
        # existing-id (NOT latest-id): latest-id falls back to
      the
        # deterministic UUID for never-used projects, and
      injecting --resume
        # with a session that was never created fails hard ("No
      conversation
        # found with session ID"). Inject only for a session
      that EXISTS.
        # TRIM providers (CMA_PROVIDER_TRIM=bare) SKIP the auto-
      resume: a
        # fresh session per launch keeps the synced session
      history out of
        # the request (live issue 2026-07-22: a 229,376-token
      local-model
        # window refused every helixagent launch under ~330k
      tokens of
        # resumed history — history must not ride along by
      default).
        if [[ "${CMA_PROVIDER_TRIM:-}" != "bare" ]]; then
          _cma_psf="$("$HOME/.local/bin/claude-session"
      existing-id "$CLAUDE_CONFIG_DIR" 2>/dev/null || true)"
          if [[ -n "$_cma_psf" ]]; then
            # Resume-fit warning (2026-09-03 compaction-loop
      fix): when the
            # session about to be resumed already holds MORE
      tokens than
            # this provider's computed auto-compact window,
      Claude Code
            # compacts it immediately on resume. That one-off
      compact is
            # intended — but it must never be SILENT: the
      operator otherwise
            # sees an unexplained "Compacting" stall on every
      alias switch
            # (the endless-compaction report). Warn, never block
      — the
            # resume still happens, the window-scaling guard
      above gives the
            # post-compact session real headroom.
            local _cma_est=""
            _cma_est="$("$HOME/.local/bin/claude-session"
      context-size "$CLAUDE_CONFIG_DIR" "$_cma_psf" 2>/dev/null
      || true)"
            case "$_cma_est" in ''|*[!0-9]*) _cma_est="" ;; esac
            if [[ -n "$_cma_est" && -n "$
      {CLAUDE_CODE_AUTO_COMPACT_WINDOW:-}" ]] \
```

```
                && [ "$_cma_est" -gt
      "$CLAUDE_CODE_AUTO_COMPACT_WINDOW" ]; then
              printf 'claude-providers: resume target %s holds
      ~%s tokens; provider %s compact window is %s — it will be
      compacted immediately on resume (then continue normally).
      \n' \
                "$_cma_psf" "$_cma_est" "$CMA_PROVIDER_ID"
      "$CLAUDE_CODE_AUTO_COMPACT_WINDOW" >&2
           fi
           set -- --resume "$_cma_psf" "$@"
         fi
       fi
       ;;
    esac
  fi
fi
# TRIM providers launch MINIMAL: --bare skips the hook/plugin/
      MCP/CLAUDE.md
# surface (~110k tokens of fixed tool schemas on a plugin-heavy
      host) so a
# session actually fits a local model's context window.
      Conversation
# launches only — non-conversation subcommands are left
      untouched.
if [[ "${CMA_PROVIDER_TRIM:-}" == "bare" ]]; then
  case "${1:-}" in
    agents|mcp|export|doctor|install|update|config|plugin|setup|
      acp|server|web|provider) ;;
    *) set -- --bare "$@" ;;
  esac
fi
local rc
local _proxy_pid=""
# Model + tier maps for BOTH transports (live defect 2026-07-26,
      Claude Code
# 2.1.220): these used to be exported only in the native branch
      below, so a
# ROUTER-transport alias launched with no ANTHROPIC_MODEL and no
      tier maps.
# 2.1.220 then resolves the tiers client-side — the fast/compact
      tier to
# "Fable 5", which the binary reports as CURRENTLY UNAVAILABLE
      ("Claude
# Fable 5 is currently unavailable. Please use Opus 4.8 or
      another available
# model."). Auto-compaction runs on that fast tier, so on the
      first session
# whose context crosses the compact trigger the compact call
      itself fails
# client-side: the context is never freed, compaction retries
      forever, and
# the alias is unusable — exactly the operator-reported compact
      loop, with
# ZERO requests reaching the gateway (verified: no /v1/messages
      in the
```

```
# per-alias service.log during the loop). Mapping every tier to
      the
# provider's real serving model makes compact/fast/background
      calls
# addressable; the gateway substitutes the route model
      regardless of the
# requested id (proven: bogus ids and literal claude-* ids both
      get routed
# and answered), so these exports change only the CLIENT-side
      resolution,
# never the upstream model.
export ANTHROPIC_MODEL="$CMA_PROVIDER_MODEL"
[[ -n "${CMA_PROVIDER_FAST_MODEL:-}" ]] && export
      ANTHROPIC_SMALL_FAST_MODEL="$CMA_PROVIDER_FAST_MODEL"
# ...and the REAL context size with it: an id Claude's table
      does not know
# makes its context accounting fall back to a tiny default
      window, against
# which the system+tool prefix alone overflows — "Prompt is too
      long" on a
# 20-character prompt, or the same compact-retry loop on
      anything larger
# (both reproduced live 2026-07-26 against 2.1.220 with
      ANTHROPIC_MODEL set
# and this unset).
[[ -n "${CMA_PROVIDER_CONTEXT_LIMIT:-}" ]] && export
      CLAUDE_CODE_MAX_CONTEXT_TOKENS="$CMA_PROVIDER_CONTEXT_LIMIT"
export ANTHROPIC_DEFAULT_OPUS_MODEL="$CMA_PROVIDER_MODEL"
export ANTHROPIC_DEFAULT_SONNET_MODEL="$CMA_PROVIDER_MODEL"
export ANTHROPIC_DEFAULT_HAIKU_MODEL="$
      {CMA_PROVIDER_FAST_MODEL:-$CMA_PROVIDER_MODEL}"
export ANTHROPIC_DEFAULT_FABLE_MODEL="$CMA_PROVIDER_MODEL"
# On-demand llmctl profile switch (no-op for every non-llmctl-*
      provider):
# a failed switch aborts HERE, before either transport branch
      below ever
# connects to CMA_PROVIDER_BASE_URL's fixed port — see
# _cma_llmctl_ensure_active's header comment for the full
      rationale.
_cma_llmctl_ensure_active "$CMA_PROVIDER_ID" || return $?
if [[ "${CMA_PROVIDER_TRANSPORT:-native}" == "router" ]]; then
  # Resolve OUR router by its stable install identity, NOT by
      PATH order
  # (live issue 2026-07-22, §11.4.111 resolve-by-stable-name):
      the npm
  # @musistudio/claude-code-router also installs a `ccr` (nvm's
      bin dir
  # precedes ~/.local/bin on PATH) whose --help carries the same
  # "ccr start" / "ccr serve" fingerprint — it passes the
      identity gate
  # below — but has NO `restart` subcommand. Bare PATH
      resolution picked
  # it, every route-apply failed exactly like a stale bundled
      build, and
  # the self-heal rebuild (which repairs the BUNDLED binary)
      could never
```

```
    # fix it: a rebuild cannot fix PATH shadowing. claude-ccr-
        build installs
    # the bundled router at $HOME/.local/bin/ccr; that symlink IS
        the stable
    # identity (same idiom as claude-session above). CMA_CCR_BIN
        overrides
    # for tests/power users; PATH is the LAST resort, only when
        the bundled
    # install is absent.
    local _ccr="${CMA_CCR_BIN:-$HOME/.local/bin/ccr}"
    [[ -x "$_ccr" ]] || _ccr="$(command -v ccr 2>/dev/null ||
        true)"
    if [[ -z "$_ccr" ]]; then
      printf 'claude-providers: provider %s needs claude-code-
        router (the `ccr` gateway).\n  Build the bundled Go
        router: claude-ccr-build\n' "$id" >&2
      return 127
    fi
    # Identity check: the bundled Go router MUST advertise `ccr
        restart` in its
    # --help. `ccr start`/`ccr serve` are CARRIER matches — the
        npm
    # @musistudio/claude-code-router also prints them — and the
        `restart`
    # subcommand is exactly what the npm build lacks and what
        makes route-apply
    # work (§11.4.201(7)(a) match STRUCTURE, not a substring a
        carrier also
    # carries). A binary at the stable install path that lacks it
        is STALE (built
    # before `restart` existed); trigger a rebuild. A binary found
        via PATH
    # fallback that lacks it is NOT ours — refuse cleanly (audit
        I3, 2026-07-23).
    local _ccr_help; _ccr_help="$("$_ccr" --help 2>&1 | head -20)"
    case "$_ccr_help" in
      *"ccr restart"*) ;;
      *)
        if [[ "$_ccr" == "$HOME/.local/bin/ccr" ]] && command -v
        claude-ccr-build >/dev/null 2>&1; then
          command -v cma_log >/dev/null 2>&1 \
            && cma_log "bundled ccr lacks 'ccr restart' in --help
        — rebuilding via claude-ccr-build …" \
              || printf 'claude-providers: bundled ccr lacks the
        required "restart" subcommand — rebuilding …\n' >&2
          claude-ccr-build >/dev/null 2>&1 || true
          _ccr_help="$("$_ccr" --help 2>&1 | head -20)"
          case "$_ccr_help" in
            *"ccr restart"*) ;; # OK after rebuild
            *)
              printf 'claude-providers: the bundled ccr at %s
        still lacks the "restart" subcommand after a rebuild.\n
        Rebuild manually and retry: claude-ccr-build\n' "$_ccr"
        >&2
              return 127 ;;
```

```
      esac
    else
      printf 'claude-providers: resolved ccr (%s) is not the
    bundled claude-code-router.\n  Its --help does not show
    the "ccr restart" subcommand that the bundled Go router
    has.\n  Fix: claude-ccr-build   (builds and installs the
    bundled router at %s)\n  If an EARLIER PATH ccr shadows
    the bundled one, remove it:\n    npm rm -g @musistudio/
    claude-code-router\n' "$_ccr" "$HOME/.local/bin/ccr" >&2
      return 127
    fi
    ;;
esac
# Upsert THIS provider into ccr config with the live key
    (regenerated each
# launch, chmod 600 — never stored by the toolkit), set it as
    the active
# route, then launch through ccr.
#
# Per-alias port isolation (Defect 3 architecture fix): every
    router-type
# provider alias gets its OWN ccr gateway instance on a unique
    port, so
# concurrent aliases never compete for one config.json and no
    alias
# silently inherits another's route.
#   - CMA_CCR_PORT in the provider's .env assigns a pinned
    port.
#   - When unset, we allocate a unique port deterministically
    from the
#     provider id (base_port + hash), so the same alias always
    gets the
#     same port and its own ccr instance survives across
    launches.
#   - Per-alias config lives under ~/.claude-code-router/
    <provider-id>/
#     so each alias has its own CCR_HOME with its own pidfile,
    config.json,
#     and service.log — fully isolated from every other alias.
local _ccr_port="${CMA_CCR_PORT:-}"
# The hash is needed for BOTH ports, so compute it
    unconditionally: two
# disjoint 500-port spaces are derived from it — gateway
    [3460,3959] and
# management [3960,4459]. (Was 100-port spaces [3460,3559]/
    [3560,3659]:
# with ~50 router aliases a birthday collision was not
    theoretical but
# LIVE — xiaomi and opencode2 both hashed to 3519, the second
    child died
# on bind, a foreign /health answer falsely proved it ready
    (fixed in the
# submodule's waitForReady the same day), and the launch fell
    back to the
# shared default ports. 500 slots per space make a collision
    ~25x rarer;
```

```
    # a surviving collision now fails LOUDLY (rc=78) instead of
        silently
    # degrading.)
    local _ccr_hash=0 _ccr_c _ccr_i=0
    while (( _ccr_i < ${#CMA_PROVIDER_ID} )); do
      _ccr_c="$(printf '%d' "'${CMA_PROVIDER_ID:_ccr_i:1}")";
        _ccr_hash=$(( (_ccr_hash * 31 + _ccr_c) & 0x7FFFFFFF ));
        _ccr_i=$((_ccr_i + 1))
    done
    if [[ -z "$_ccr_port" ]]; then
      # Deterministic port from the provider name: hash the id
        into a port
      # offset from base 3460, bounded to [3460, 3959] (500
        ports).
      _ccr_port=$(( 3460 + (_ccr_hash % 500) ))
    fi
    # Per-alias MANAGEMENT port (live defect 2026-07-25): the
        gateway port was
    # isolated per alias but the management port was left at ccr's
        default
    # 3458 for EVERY alias, so exactly ONE per-alias gateway could
        be up at a
    # time — every second alias's `ccr restart` child died with
    # "start management interface: listen on 127.0.0.1:3458: bind:
        address
    # already in use" and the launch refused with rc=78 (live-
        captured on
    # sarvam: 4 child starts, 4 bind failures, "did not become
        ready within
    # 15s"). Worse, the child's gateway socket binds BEFORE the
        management
    # bind fails, so waitForReady could WIN the race against the
        dying child —
    # a launch that "succeeded" against a gateway that was already
        exiting.
    # CMA_CCR_MGMT_PORT in the provider's .env pins it; otherwise
        derive from
    # the same hash in the disjoint [3960,4459] space.
    local _ccr_mgmt_port="${CMA_CCR_MGMT_PORT:-$(( 3960 +
        (_ccr_hash % 500) ))}"
    local _ccr_dir="$HOME/.claude-code-router"
    # Per-alias config isolation: each router-type alias gets its
        OWN
    # CCR_HOME directory so its pidfile (service.json),
        config.json, and
    # service.log live under ~/.claude-code-router/<provider-id>/
        instead
    # of sharing the global ~/.claude-code-router/. This is load-
        bearing
    # for concurrent aliases: a `ccr restart` for alias A must
        never see
    # alias B's pidfile and kill its gateway. CCR_HOME is the Go
        router's
    # override for config.Dir() (added for this fix).
    local _ccr_home="$_ccr_dir/${CMA_PROVIDER_ID}"
```

```
    local cfg="$_ccr_home/config.json"
        base="$CMA_PROVIDER_BASE_URL"
    # Self-reference guard: when THIS provider's base_url IS the
        ccr gateway
    # itself, there is no upstream to route to — upserting a
        provider whose
    # api_base_url is ccr registers a ccr->ccr self-loop.
    #
    # This used to SKIP the upsert+restart and launch anyway,
        justified by
    # "under ccr v3.0.6 the live route is app_config (config.json
        is not
    # re-imported on restart), so the write is inert-for-routing".
        That claim
    # described the RETIRED JS router and is INVERTED for the Go
        router that now
    # serves every alias. The Go source documents the opposite —
    # claude-code-router:cmd/ccr/service.go, cmdRestart: the
        toolkit
    # "rewrites ~/.claude-code-router/config.json before every
        provider-alias
    # launch and then runs `ccr restart` to make that rewrite take
        effect."
    # Post-ATM-870 (`a6a24e0`) the mechanism is richer than that
        quote: the
    # running gateway applies a validated hot-reload IN PLACE via
    # `gw.SwapConfig` (atomic pointer swap; /health, /ready and
        routing follow
    # it per-request — only the startup-built outbound proxy
        client and
    # in-flight request snapshots do not follow). `ccr restart`
        nonetheless
    # stays on this path: it is the DETERMINISTIC apply-point —
        the swap's
    # timing is not observable from outside the process, so only
        the bounce
    # gives the launch a provable receipt that the route it wrote
        is the
    # route being served.
    #
    # So config.json IS the live route (once restarted), and
        skipping the
    # rewrite does not make the launch inert — it makes it INHERIT
        whichever
    # provider the gateway last served. That is exactly how
        `helixagent` earned
    # a `verified` badge on a turn served by `deepseek`: 157,419
        tokens through
    # a nominally 24,576-token alias, with no `helixagent`
        provider present in
    # ccr's config at all. The verdict measured whoever ran last.
    #
    # There is no honest third state, so REFUSE. A ccr-self base
        cannot be
    # routed, and inheriting a foreign route is a silent wrong-
        model launch.
```

```
    # The provider must be pointed at its REAL backing endpoint
        (for the
    # HelixAgent facade that is the HelixLLM server itself, not
        the ccr gateway
    # standing in front of it).
    # _cma_is_ccr_gateway is emitted into this same alias file
        (see
    # _cma_emit_ccr_gateway_guard) — ONE definition shared with
        lib.sh and
    # providers-verify.sh, so the launch gate and the verify gate
        cannot drift.
    if _cma_is_ccr_gateway "$base"; then
      printf 'claude-providers: refusing to launch %s — its
        base_url (%s) IS the ccr gateway itself.\n' "$id" "$base"
        >&2
      printf '  A provider cannot route through the router it
        *is*. Skipping the route write (the old behaviour)\n
        silently inherited whatever provider the gateway last
        served: the wrong model, with no error.\n' >&2
      printf '  Repoint %s at its real backing endpoint (its pins
        file / CMA_PROVIDER_BASE_URL) and re-run:\n    claude-
        providers sync\n' "$id" >&2
      return 78
    fi
    # Create the per-alias config dir + config with restrictive
        perms from the
    # start: this file will hold the live API key, so it must
        never be
    # group/world readable, even transiently or if a later jq
        rewrite fails.
    ( umask 077; mkdir -p "$_ccr_home"
      [[ -f "$cfg" ]] || echo '{"Providers":[],"Router":{}}' >
        "$cfg" )
    chmod 600 "$cfg" 2>/dev/null || true
    # Upstream TLS trust anchor (2026-09-04, helixllm-anton live
        launch): the
    # verify probe honors CMA_PROVIDER_CA_CERT, but the LAUNCH
        path wired no
    # CA at all, so a `verified` alias behind a self-signed https
        gateway died
    # on the first real request — "502 upstream request failed:
        tls: failed to
    # verify certificate: x509: certificate signed by unknown
        authority". The
    # router's outbound client is a Go &http.Transport{} on the
        SYSTEM pool;
    # Go honors SSL_CERT_FILE, which REPLACES that pool, so the
        anchor is a
    # COMBINED bundle (system roots + the extra CA) — a CA-only
        bundle would
    # narrow trust and break every other TLS dial this gateway
        might make.
    # _ccr_ca_env is consumed via env(1) with the ${arr[@]+"$
        {arr[@]}"} guard
    # so an empty array expands to NOTHING in both bash and zsh.
    local _ccr_ca="" _ccr_ca_env=()
```

```
    if [[ -n "${CMA_PROVIDER_CA_CERT:-}" && -r "$
        {CMA_PROVIDER_CA_CERT:-}" ]] \
       && [[ "$base" == https://* ]]; then
      local _ccr_sys_ca=""
      for _c in /etc/ssl/certs/ca-certificates.crt \
                /etc/pki/tls/certs/ca-bundle.crt \
                /etc/ssl/cert.pem; do
        [[ -r "$_c" ]] && { _ccr_sys_ca="$_c"; break; }
      done
      # ATOMIC write (spec 006 WS-C Issue 1). Build the bundle in
        a temp file in
      # the SAME directory, fix its mode, then rename it over the
        destination.
      # `cat ... > ca-bundle.pem` truncated the live file in
        place, so a
      # concurrent reader — the running router, which reads this
        via
      # SSL_CERT_FILE at dial time — could observe an empty or
        half-written
      # bundle and fail with the very x509 error this block exists
        to prevent.
      # rename(2) is atomic within a filesystem, so a reader sees
        either the old
      # complete bundle or the new complete bundle, never a
        partial one.
      # mktemp, not "$$.$RANDOM": $$ is the PARENT shell PID,
        identical in every
      # subshell of one shell, so uniqueness would rest on $RANDOM
        alone
      # (~15 bits) and two concurrent writers for the SAME
        provider could
      # pick the same path and interleave their output.
      local _ccr_tmp
      _ccr_tmp="$(mktemp "${_ccr_home}/.ca-bundle.pem.XXXXXX")" ||
        _ccr_tmp=""
      if [[ -z "$_ccr_tmp" ]]; then
        # Could not create a temp file. Do NOT fall back to
        writing the
        # destination directly: that reintroduces the in-place
        truncation this
        # block exists to remove. Leave any existing bundle alone
        and let the
        # best-effort chmod/read below decide what is usable.
        :
      else
        # Reap the temp file if this shell is interrupted between
        creation and
        # the rename (review F6). SIGKILL cannot be caught, so a
        kill -9 can
        # still leave one; that is a disk-cost, never a
        correctness issue.
        #
        # NO TRAP HIJACKING. This runs inside cma_run_provider,
        which is a
```

```
      # brace function reached through `alias
      X="cma_run_provider X"` — i.e.
      # in the OPERATOR'S interactive shell. `trap - INT TERM`
      afterwards
      # would reset INT/TERM to their defaults and silently
      delete whatever
      # handler the user had installed. Save the caller's
      dispositions and
      # hand them back once the temp file is gone (renamed or
      removed), the
      # same save/restore pattern as the rc-file publish above
      # (test_ccr_upstream_ca.sh pins it).
      local _ccr_prev_int _ccr_prev_term
      _ccr_prev_int="$(trap -p INT || true)"
      _ccr_prev_term="$(trap -p TERM || true)"
      trap 'rm -f "$_ccr_tmp"' INT TERM
      if ( umask 077
           if [[ -n "$_ccr_sys_ca" ]]; then
             cat "$_ccr_sys_ca" "$CMA_PROVIDER_CA_CERT" >
      "$_ccr_tmp" 2>/dev/null
           else
             cat "$CMA_PROVIDER_CA_CERT" > "$_ccr_tmp" 2>/dev/
      null
           fi ); then
        chmod 600 "$_ccr_tmp" 2>/dev/null || true
        mv -f "$_ccr_tmp" "$_ccr_home/ca-bundle.pem" 2>/dev/null
      || rm -f "$_ccr_tmp"
      else
        # A failed build must not leave a partial temp file
      behind, and must
        # not replace an existing good bundle with nothing.
        rm -f "$_ccr_tmp"
      fi
      trap - INT TERM
      if [[ -n "$_ccr_prev_int" ]]; then eval "$_ccr_prev_int";
      fi
      if [[ -n "$_ccr_prev_term" ]]; then eval
      "$_ccr_prev_term"; fi
    fi
    # The bundle carries a private upstream CA: same 600
      discipline as the
    # config dir it lives in (the shell's umask is not
      guaranteed here).
    # The chmod stays BEST-EFFORT by deliberate threat model
      (code-review
    # 2026-09-04 finding 8): (a) $_ccr_home itself was created
      under
    # umask 077, so a 644 bundle inside a 700 directory is
      already
    # group/world-inaccessible; (b) a CA certificate is PUBLIC
      material by
    # design — it is distributed to every TLS client, unlike the
      API key in
    # config.json; and (c) making chmod a hard precondition
      would convert a
```

```
    # benign permission hiccup into a dead alias (no
      SSL_CERT_FILE -> the
    # x509 failure this whole block exists to fix), a strictly
      worse failure
    # mode. Belt-and-braces, never a launch gate.
    [[ -s "$_ccr_home/ca-bundle.pem" ]] && _ccr_ca="$_ccr_home/
      ca-bundle.pem"
    [[ -n "$_ccr_ca" ]] && { chmod 600 "$_ccr_ca" 2>/dev/null ||
      true; _ccr_ca_env=("SSL_CERT_FILE=$_ccr_ca"); }
  fi
  case "$base" in
    */chat/completions|*/v1beta/models/|*/v1beta/models) ;;
    *) base="${base%/}/chat/completions" ;;
  esac
  # Preserve the original CMA_PROVIDER_BASE_URL for the fossil
      marker.
  # `base` is mutated above (appends /chat/completions) but the
      fossil
  # marker must record the REAL backing endpoint, not the
      ephemeral proxy
  # address. RC4 (2026-07-27): the fix was to capture
      $CMA_PROVIDER_BASE_URL
  # BEFORE the case statement mutates it.
  local _real_base="$CMA_PROVIDER_BASE_URL" _eph_base=""
  local _eph_marker="$HOME/.claude-code-router/.cma-
      ephemeral.json"
  local _eph_lock="${_eph_marker}.lock"
  local _prior_default="" _prior_background=""
  local _wrote_default="" _wrote_background=""
  # fd slots for the two launch locks below, filled by bash's
      dynamic fd
  # allocation (`exec {var}>>FILE`). Declared here so the nested
      lock/unlock
  # helpers assign into THIS scope rather than leaking a global
      into the
  # operator's interactive shell.
  local _cma_eph_fd="" _cma_cfg_fd=""
  # Mutual exclusion for every read-modify-write touching
      $_eph_marker below
  # (reap-on-start here, add-on-launch further down, delete-on-
      exit inside
  # _cma_ccr_unfossilise). Two CONCURRENT cma_run_provider
      launches both
  # touch this one file; without a lock the classic lost update
      is live:
  # launch A reads the marker, adds its own key, and mv's the
      result in;
  # launch B — already holding a snapshot read from BEFORE A's
      write —
  # computes ITS OWN add against that stale snapshot and mv's it
      in too,
  # silently overwriting the whole file and dropping A's entry
      (the entry
  # A's own exit repair needs to prove, via CAS, that it still
      owns the
```

```
# route it wrote). flock is per-open-file-description and
    released by the
# KERNEL the instant the holding process dies (no stale-lock
    recovery is
# needed here the way the mkdir-based _cma_alias_lock_*
    fallback
# elsewhere in this file requires for its non-flock backend);
    an absent
# `flock` binary (no macOS) degrades to the pre-existing
    UNLOCKED
# behaviour rather than blocking a launch — consistent with
    this whole
# section's best-effort discipline (a missing `jq` is handled
    the same
# way, one line below).
_cma_eph_lock() {
  command -v flock >/dev/null 2>&1 || return 0
  # The fd is DYNAMICALLY allocated (`exec {var}>>FILE`, bash
    >= 4.1 /
  # zsh): the shell picks a guaranteed-free fd and stores the
    number in
  # _cma_eph_fd. A HARDCODED fd number here was the defect,
    twice over:
  #   (a) `exec 9>>FILE 2>/dev/null` — `exec` without a
    command applies
  #       EVERY redirection on the line to the CURRENT SHELL
    permanently,
  #       so one provider launch silenced the interactive
    shell's stderr
  #       for the rest of its life (the original field
    failure).
  #   (b) `{ exec 9>>FILE; } 2>/dev/null` — the "fix" for (a),
    and itself
  #       a silent break: hardcoded LOW fds (9/10) collide
    with the
  #       shell's OWN redirection bookkeeping (bash saves/
    restores fds
  #       around compound-command redirections and command
    substitutions
  #       onto low free fds), so the fd the inner exec opened
    did not
  #       survive the group — proven live on bash 5.2.37: the
    very next
  #       `flock -w 5 9` failed "Bad file descriptor" (hidden
    by the
  #       group's own 2>/dev/null), and EVERY critical section
    below ran
  #       UNLOCKED while claiming mutual exclusion.
  # Dynamic allocation avoids both: no hardcoded number to
    collide, no
  # stderr redirection to leak. It only ever runs where
    `flock` exists
  # (the guard above), which is exactly the set of platforms
    where the
  # lock can exist at all — macOS degrades to the documented
    unlocked
```

```
  # best-effort path before reaching this line.
  exec {_cma_eph_fd}>>"$_eph_lock" || return 0
  # BOUNDED wait. Defensive hardening carried over from an
    earlier
  # independent review, NOT a fix for the reported exit-hang
    (that was
  # traced to the launch itself, and this lock/unlock pair
    provably
  # completes). An unbounded flock can never time out while
    any process
  # holds the lock, which on an interactive path is a latent
    stall by
  # construction; the guarded critical section is a tiny
    marker
  # read-modify-write, so a short bound is ample and a timeout
    degrades
  # to the same unlocked best-effort path this section already
    takes
  # when `flock` is absent entirely (macOS).
  # On timeout, SAY SO (§11.4.201(5): a guard reports its
    resolved
  # evidence). Swallowing it discards the acquired-vs-timed-
    out
  # distinction, leaving a real contention event
    undiagnosable.
  flock -w 5 "$_cma_eph_fd" 2>/dev/null || {
    command -v cma_log >/dev/null 2>&1 \
      && cma_log "eph-lock: 5s timeout — proceeding unlocked
    (best-effort)"
    true
  }
  return 0
}
_cma_eph_unlock() {
  [[ -n "$_cma_eph_fd" ]] || return 0
  flock -u "$_cma_eph_fd" 2>/dev/null || true
  exec {_cma_eph_fd}>&- || true
  _cma_eph_fd=""
  return 0
}
# Mutual exclusion for every read-modify-write touching THIS
    alias's
# config.json below — the stale-fossil reap, the main route
    upsert, and
# _cma_ccr_unfossilise. Two CONCURRENT cma_run_provider
    launches of the
# SAME provider id both touch the same per-alias $cfg; without
    a lock the
# classic lost update is live: launch A rewrites config.json
    with provider
# route A, launch B — already holding a snapshot read BEFORE
    A's write —
# rewrites it with provider route B, silently dropping A's
    entire config.
# This is the race fixed by this lock.
```

```
_cma_cfg_lock() {
  local _lock="$1.lock"
  command -v flock >/dev/null 2>&1 || return 0
  # Dynamic fd allocation for the same reason as _cma_eph_lock
    above:
  # a hardcoded `exec 10>>FILE` collides with the shell's
    redirection
  # save slots (live-proven: "flock: 10: Bad file descriptor",
    lock
  # silently never held), and any 2>/dev/null ON the exec line
    itself
  # would silence this interactive shell's stderr permanently.
  exec {_cma_cfg_fd}>>"$_lock" || return 0
  flock -w 5 "$_cma_cfg_fd" 2>/dev/null || {
    command -v cma_log >/dev/null 2>&1 \
      && cma_log "cfg-lock: 5s timeout on ${_lock} —
    proceeding unlocked (best-effort)"
    true
  }
  return 0
}
_cma_cfg_unlock() {
  [[ -n "$_cma_cfg_fd" ]] || return 0
  flock -u "$_cma_cfg_fd" 2>/dev/null || true
  exec {_cma_cfg_fd}>&- || true
  _cma_cfg_fd=""
  return 0
}
if command -v jq >/dev/null 2>&1; then
  _prior_default="$(jq -r '.Router.default // ""' "$cfg" 2>/
    dev/null || printf '')"
  _prior_background="$(jq -r '.Router.background // ""' "$cfg"
    2>/dev/null || printf '')"
  # (2) stale-fossil reap. Entirely best-effort: any failure
    here must never
  # block a launch, so every step is guarded and the loop
    simply moves on.
  if [[ -s "$_eph_marker" ]]; then
    _cma_eph_lock
    local _rv_dead="[]" _rv_n _rv_pid _rv_tmp
    # `< <(jq …)` (process substitution) feeding a `while IFS=
    read -r`,
    # NOT `for x in $(jq …)` — an unquoted command
    substitution word-
    # splits on IFS, so a hypothetical whitespace-bearing
    provider id
    # would silently fan out into multiple bogus keys. NOT a
    trailing
    # `jq … | while …` pipe either: bash runs the LAST stage
    of a pipeline
    # in a subshell, so `_rv_dead` accumulated inside such a
    loop would
    # vanish the moment the loop exits and this reap would
    never see any
```

```
        # dead entry. Process substitution keeps the loop in THIS
        shell while
        # still reading one whole line at a time.
        while IFS= read -r _rv_n; do
          [[ -n "$_rv_n" ]] || continue
          _rv_pid="$(jq -r --arg k "$_rv_n" '.[$k].pid // 0'
        "$_eph_marker" 2>/dev/null || printf '0')"
          # Liveness PROVEN, never assumed — a live owner keeps
        its address.
          # Conservative-by-construction on PID reuse: if the
        ORIGINAL owner
          # died and the kernel later hands its pid to some
        UNRELATED later
          # process, `kill -0` reads that pid as alive, so this
        entry is kept
          # and NOT reaped this cycle. That is the SAFE direction
        — the worst
          # outcome is one stale fossil surviving an extra reap
        cycle, never a
          # live owner's address being ripped out from under it —
        and it
          # self-heals the next time the SAME provider launches:
        CAS-1 in
          # _cma_ccr_unfossilise (`_u_addr_now == _u_eph`) still
        fires on the
          # marker's own record, and a later reap catches it once
        the reused
          # pid itself is gone too.
          if [[ "$_rv_pid" != "0" ]] && kill -0 "$_rv_pid" 2>/dev/
        null; then continue; fi
          _rv_dead="$(jq -c --arg k "$_rv_n" '. + [$k]'
        <<<"$_rv_dead" 2>/dev/null || printf '%s' "$_rv_dead")"
        done < <(jq -r 'keys[]?' "$_eph_marker" 2>/dev/null)
        if [[ "$_rv_dead" != "[]" ]]; then
          _rv_tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX" 2>/dev/
        null)" && chmod 600 "$_rv_tmp" 2>/dev/null
          _cma_cfg_lock "$cfg"
          if [[ -n "$_rv_tmp" ]] && jq --argjson dead "$_rv_dead"
        --slurpfile mk "$_eph_marker" '
                .Providers = [ .Providers[]? as $p
                  | ($mk[0][$p.name] // null) as $m
                  | if ($m != null) and ([$p.name] |
        inside($dead)) and ($p.api_base_url == ($m.eph // ""))
                      and (($m.real // "") != "")
                    then $p + {api_base_url: $m.real} else $p
        end ]
              ' "$cfg" >| "$_rv_tmp" 2>/dev/null && [[ -s
        "$_rv_tmp" ]]; then
            command mv -f "$_rv_tmp" "$cfg" 2>/dev/null && chmod
        600 "$cfg" 2>/dev/null
            command -v cma_log >/dev/null 2>&1 && cma_log "reaped
        stale cma-proxy fossil(s) from ccr config: $_rv_dead" ||
        true
          else
            [[ -n "$_rv_tmp" ]] && rm -f "$_rv_tmp"
```

```
      fi
      _cma_cfg_unlock
      _rv_tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX" 2>/dev/
    null)" && chmod 600 "$_rv_tmp" 2>/dev/null
      if [[ -n "$_rv_tmp" ]] && jq --argjson dead "$_rv_dead"
    'delpaths([$dead[] | [.]])' \
            "$_eph_marker" >| "$_rv_tmp" 2>/dev/null && [[ -s
    "$_rv_tmp" ]]; then
        command mv -f "$_rv_tmp" "$_eph_marker" 2>/dev/null
      else
        [[ -n "$_rv_tmp" ]] && rm -f "$_rv_tmp"
      fi
    fi
    _cma_eph_unlock
  fi
fi
# (1) Exit repair. Defined here (indented — a `}` at column 0
    would end the
# function body for _cma_alias_carryover's legacy scanner) so
    it travels with
# this body into the emitted, self-contained alias file. Its
    inputs arrive as
# positional args, with ONE deliberate exception: the resolved
    router binary
# is read from the enclosing `$_ccr` via bash dynamic scoping
    rather than
# being passed in. That is not laziness —
    test_ccr_conformance.sh derives the
# REQUIRED router-subcommand set by scanning this file for
    `"$_ccr" <word>` at
# command position, so passing the binary as an argument would
    (a) make the
# call site read as a bogus invocation `ccr "$_eph_marker"`
    and (b) hide this
# function's REAL `"$_ccr" restart` from the very gate that
    exists to catch an
# unsupported subcommand. Both call sites are inside
    cma_run_provider, so
# `$_ccr` is always in scope.
_cma_ccr_unfossilise() {
  local _u_cfg="$1" _u_n="$2" _u_eph="$3" _u_real="$4"
    _u_wd="$5" _u_wb="$6"
  local _u_pd="$7" _u_pb="$8" _u_marker="$9"
  [[ -n "$_u_eph" ]] || return 0          # no proxy ran =>
    nothing fossilised
  [[ -f "$_u_cfg" ]] || return 0
  command -v jq >/dev/null 2>&1 || return 0
  _cma_cfg_lock "$_u_cfg"
  local _u_addr_now _u_def_now _u_bg_now _u_mine=0 _u_tmp
  _u_addr_now="$(jq -r --arg n "$_u_n" \
    '[.Providers[]?|select(.name==$n)|.api_base_url][0] // ""'
    "$_u_cfg" 2>/dev/null || printf '')"
  # CAS-1 — repair ONLY while the stored address is still the
    one WE wrote.
```

```
    # If a newer launch re-stamped it, that launch owns the
      entry and will run
    # its own repair; touching it here would corrupt a live
      route.
    # Every early return between _cma_cfg_lock and
      _cma_cfg_unlock MUST pass
    # through the unlock: this runs in the operator's
      INTERACTIVE shell, which
    # never dies, so the kernel never releases a leaked flock —
      each leaked
    # acquisition stalls every later cfg-lock on this config for
      the full 5s
    # budget and silently degrades it to unlocked (audit-proven
      2026-07-25:
    # a CAS-1 early return held the lock for the shell's life
      and stacked
    # +1 leaked fd per occurrence).
    if [[ "$_u_addr_now" != "$_u_eph" ]]; then _cma_cfg_unlock;
      return 0; fi
    _u_def_now="$(jq -r '.Router.default // ""' "$_u_cfg" 2>/
      dev/null || printf '')"
    _u_bg_now="$(jq -r '.Router.background // ""' "$_u_cfg" 2>/
      dev/null || printf '')"
    # CAS-2 — the route is still ours only if BOTH halves are
      unchanged.
    [[ "$_u_def_now" == "$_u_wd" && "$_u_bg_now" == "$_u_wb" ]]
      && _u_mine=1
    _u_tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX" 2>/dev/null)"
      || { _cma_cfg_unlock; return 0; }
    chmod 600 "$_u_tmp" 2>/dev/null || true
    if jq --arg n "$_u_n" --arg eph "$_u_eph" --arg real
      "$_u_real" \
          --arg pd "$_u_pd" --arg pb "$_u_pb" --argjson mine
      "$_u_mine" '
          .Providers = [ .Providers[]?
            | if .name == $n and .api_base_url == $eph
      then .api_base_url = $real else . end ]
          | if ($mine == 1) and ($pd != "")
      then .Router.default    = $pd else . end
          | if ($mine == 1) and ($pb != "")
      then .Router.background = $pb else . end
        ' "$_u_cfg" >| "$_u_tmp" 2>/dev/null && [[ -s
      "$_u_tmp" ]]; then
      command mv -f "$_u_tmp" "$_u_cfg" 2>/dev/null && chmod 600
      "$_u_cfg" 2>/dev/null
      command -v cma_log >/dev/null 2>&1 && \
        cma_log "un-fossilised ccr config for $_u_n:
      api_base_url ephemeral -> real (route_restored=$_u_mine)"
      || true
      # Bounce ONLY when the route was still ours: restarting
      while ANOTHER
      # launch owns the route would drop that launch's in-flight
      requests.
      # (Post-ATM-870 the running gateway also picks the edit up
      live via
```

```
      # SwapConfig; the bounce remains the deterministic,
      receipt-provable
      # apply-point — and here, the repair to an ephemeral
      address that the
      # dead proxy no longer serves, it is what makes the
      restore effective
      # for in-flight consumers regardless of swap timing.)
      if [[ "$_u_mine" == "1" && -n "$_ccr" && -x "$_ccr" ]];
      then
        CCR_HOME="$_ccr_home" "$_ccr" restart --gateway-port
      "$_ccr_port" --port "$_ccr_mgmt_port" >/dev/null 2>&1 ||
      true
      fi
    else
      rm -f "$_u_tmp"
    fi
    _cma_cfg_unlock
    # Drop our marker entry last: until here it is the crash-
      recovery record.
    # Locked (§11.4.180/marker-lost-update hardening): _u_marker
      is derived
    # from $_eph_marker by the caller and $_eph_lock is visible
      here via the
    # SAME bash dynamic-scoping this function already relies on
      for $_ccr
    # (see the comment on this function's own definition) —
      _cma_eph_lock /
    # _cma_eph_unlock are defined once, before this function's
      first call
    # site, alongside $_eph_lock's declaration.
    if [[ -n "$_u_marker" && -s "$_u_marker" ]]; then
      _cma_eph_lock
      local _u_mt; _u_mt="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX"
      2>/dev/null)"
      if [[ -n "$_u_mt" ]]; then
        chmod 600 "$_u_mt" 2>/dev/null || true
        if jq --arg k "$_u_n" 'del(.[$k])' "$_u_marker" >|
      "$_u_mt" 2>/dev/null && [[ -s "$_u_mt" ]]; then
          command mv -f "$_u_mt" "$_u_marker" 2>/dev/null
        else
          rm -f "$_u_mt"
        fi
      fi
      _cma_eph_unlock
    fi
    return 0
  }
  # Start the Go compatibility proxy (cma-proxy) when it
      transforms this
  # provider: helixagent Hermes tool-call recovery, or poe/kimi/
      sarvam request-
  # schema fixes (e.g. Poe requires `parameters` in tool
      definitions; Claude
  # Code sometimes omits it). cma-proxy resolves the family key
      itself
```

```
    # (poe2->poe, kimi-*->kimi), so the wrapper just asks `--has-
        transform`. It
    # lives in the INSTALLED share dir; this wrapper is self-
        contained in the
    # alias file and has NO $LIB_DIR (repo-only), so resolve
        against SHARED_DIR
    # with lib.sh's default. (Replaces the former per-provider
        python proxies.)
    local _cma_proxy_dir="${SHARED_DIR:-$HOME/.claude-shared}/
        proxy"
    local _proxy_bin="$_cma_proxy_dir/cma-proxy"
    local _proxy_script=""
    if [[ -x "$_proxy_bin" ]] && "$_proxy_bin" --has-transform
        "$CMA_PROVIDER_ID" >/dev/null 2>&1; then
      _proxy_script="$_proxy_bin"
    elif [[ ! -x "$_proxy_bin" ]]; then
      # HONEST SKIP-with-reason, never a silent degrade
        (§11.4.69).
      # This branch did not exist: with cma-proxy absent,
        _proxy_script stayed
      # empty, the whole shim block was skipped WITHOUT A WORD,
        and the alias
      # launched against the raw endpoint. The provider then
        failed in exactly
      # the ways the shims exist to prevent (helixagent Hermes
        tool-call
      # recovery; poe/kimi/sarvam request-schema fixes) with
        nothing anywhere
      # saying the shims were off — from the outside,
        indistinguishable from a
      # shim that ran and did not help.
      #
      # stderr only (never stdout, which is the agent's channel),
        and only for
      # providers that actually HAVE a transform: a provider with
        no shim loses
      # nothing, so warning there would be a false positive
        (§11.4.201(1)).
      # We normally ask the binary via --has-transform, but with
        no binary we
      # cannot — cma_proxy_transform_family mirrors the proxy's
        registry
      # (prefix-matched: poe2 -> poe, kimi-k2 -> kimi) and
        test_cma_proxy.sh
      # asserts the two stay EQUAL in both directions.
      if cma_proxy_transform_family "$CMA_PROVIDER_ID"; then
        printf 'claude-providers: cma-proxy is NOT installed (%s)
        — launching %s WITHOUT its compatibility shims.\n  Tool-
        call/request-schema fixes for this provider are inactive;
        failures here are expected until it is built.\n  Fix:
        claude-proxy-build   (then: claude-install-verify)\n' \
          "$_proxy_bin" "$CMA_PROVIDER_ID" >&2
      fi
    fi
    if [[ -n "$_proxy_script" ]]; then
```

```
      # HelixAgent pre-flight: check HelixLLM availability and
        mode.
      # If HelixLLM is not running and Helix Code is installed,
        auto-start it
      # in claude mode (229376-token context). HelixLLM in coder
        mode has only
      # 24576-token context; helixagent requires claude mode's
        229376 tokens.
      if [[ "$CMA_PROVIDER_ID" == helixagent* ]]; then
        # cma_log/cma_warn are lib.sh helpers. THIS BODY IS
        EMITTED INTO THE
        # ALIAS FILE by the heredoc below, and that file never
        sources lib.sh —
        # so calling them bare prints `cma_warn: command not
        found` and DESTROYS
        # the message. Live-proven: providers-helixagent-
        superpowers.txt carries
        # exactly that line where the operator should have seen
        the coder-mode
        # remedy. Every older call site guards with `command -v
        cma_log && …`,
        # but that pattern SILENTLY DROPS the text when the helper
        is absent,
        # which is wrong here: for this pre-flight the message IS
        the feature —
        # it is the only thing that tells an operator to flip
        HelixLLM out of
        # coder mode. So emit either way, through the helper when
        it exists and
        # through a plain printf when it does not.
        _hl_log()  { if command -v cma_log  >/dev/null 2>&1; then
        cma_log  "$1"; else printf '[cma] %s\n' "$1" >&2; fi; }
        _hl_warn() { if command -v cma_warn >/dev/null 2>&1; then
        cma_warn "$1"; else printf '[cma warn] %s\n' "$1" >&2;
        fi; }
        # WHICH SERVICE THIS PRE-FLIGHT IS ABOUT — and why it is
        no longer
        # derived from the alias's own base_url.
        #
        # Everything below is a property of the llama.cpp HelixLLM
        server: the
        # /health liveness poll, the coder-vs-claude decision read
        out of
        # context_limit / n_ctx, and the auto-start, which runs
        # helixllm-mode.sh — a script that binds :18434. While the
        helixagent
        # alias happened to point AT that server, `$
        {CMA_PROVIDER_BASE_URL}`
        # was a fine way to find it. It no longer does: the alias
        now points at
        # HelixAgent's own gateway (:7061), which is a DIFFERENT
        service with no
        # n_ctx and no coder/claude mode. Deriving the URL from
        the base_url
        # would therefore poll the wrong service for a mode it
        cannot report,
```

```
# and — worse — auto-start would boot a llama-server on
:18434 and then
# wait 120s for :7061 to come up, a service it never
started.
#
# So resolve it independently, defaulting to the port
helixllm-mode.sh
# actually binds (the same default that script's own
# HELIXLLM_HEALTH_URL uses), and keep it overridable
(CONST-045).
local _hl_url="${CMA_HELIXLLM_HEALTH_URL:-http://
127.0.0.1:18434}" _hl_mode=""
local _hl_healthy=0
if command -v curl >/dev/null 2>&1; then
  # Some HelixLLM builds expose context_limit in /health;
newer ones only
  # return {"status":"ok"}. Use /health for liveness and
fall back to
  # /v1/models for the serving context size (n_ctx) when
needed.
  if curl -sf --max-time 3 "${_hl_url}/health" >/dev/null
2>&1; then
    _hl_healthy=1
    _hl_mode="$(curl -sf --max-time 3 "${_hl_url}/health"
2>/dev/null | grep -o '"context_limit" *: *[0-9]*' | head
-1 | sed 's/.*: *//' || true)"
  fi
  if [[ -z "$_hl_mode" ]] && curl -sf --max-time 3 "$
{_hl_url}/v1/models" >/dev/null 2>&1; then
    _hl_healthy=1
    _hl_mode="$(curl -sf --max-time 3 "${_hl_url}/v1/
models" 2>/dev/null | grep -o '"n_ctx" *: *[0-9]*' | head
-1 | sed 's/.*: *//' || true)"
  fi
fi
# Auto-start HelixLLM if not running and Helix Code is
installed.
#
# OPT-IN ONLY (operator mandate 2026-07-27). Booting a
Helix service is
# a heavyweight, machine-wide side effect: HelixLLM claims
the single
# GPU, and starting it in claude mode EVICTS whatever
HelixCode had
# running in coder mode. A provider alias must not do that
to a host
# merely because someone launched it. Default is therefore
FALSE; set
# CMA_HELIX_AUTOSTART=1 (or true/yes/on) to allow it. When
it is not
# enabled we still say so, and still print the exact
command to run —
# the operator keeps the information and the choice.
local _hl_autostart="${CMA_HELIX_AUTOSTART:-0}"
case "${_hl_autostart,,}" in
```

```
        1|true|yes|on) _hl_autostart=1 ;;
        *)             _hl_autostart=0 ;;
      esac
      if [[ "$_hl_healthy" -eq 0 && "$_hl_autostart" -ne 1 ]];
      then
        _hl_warn "helixagent: HelixLLM is not answering on $
      {_hl_url} and auto-start is OFF by default.
Start it yourself (it claims the GPU and evicts HelixCode's
      coder mode):
  helix_code/scripts/helixllm-mode.sh claude
Or opt in for this launch:
  CMA_HELIX_AUTOSTART=1 <alias>"
      fi
      if [[ "$_hl_healthy" -eq 0 && "$_hl_autostart" -eq 1 ]];
      then
        local _hl_mode_script=""
        # Find helixllm-mode.sh in common locations
        for _hl_candidate in \
          "$HOME/projects/helix_code/scripts/helixllm-mode.sh" \
          "$HOME/helix_code/scripts/helixllm-mode.sh" \
          "/run/media/milosvasic/DATA4TB/Projects/helix_code/
      scripts/helixllm-mode.sh" \
          "${HELIX_CODE_DIR:-}/scripts/helixllm-mode.sh"; do
          if [[ -x "$_hl_candidate" ]]; then
            _hl_mode_script="$_hl_candidate"
            break
          fi
        done
        if [[ -n "$_hl_mode_script" ]]; then
          _hl_log "helixagent: HelixLLM not running — auto-
      starting in claude mode via $_hl_mode_script ..."
          if "$_hl_mode_script" claude 2>&1 | tail -5 >&2; then
            # Wait for HelixLLM to become healthy (up to 120s)
            local _hl_wait=0
            while [[ "$_hl_wait" -lt 24 ]]; do
              if curl -sf --max-time 5 "${_hl_url}/health" >/
      dev/null 2>&1; then
                _hl_healthy=1
                _hl_log "helixagent: HelixLLM started
      successfully"
                break
              fi
              sleep 5
              _hl_wait=$((_hl_wait + 1))
            done
            if [[ "$_hl_healthy" -eq 0 ]]; then
              _hl_warn "helixagent: HelixLLM auto-start timed
      out after 120s.
The container may still be loading the model. Check:
  podman logs helixllm-coder
  $_hl_mode_script status"
            fi
          else
```

```
            _hl_warn "helixagent: HelixLLM auto-start failed.
Fix: manually start HelixLLM:
  $_hl_mode_script claude"
          fi
        else
          _hl_warn "helixagent: HelixLLM not running and
      helixllm-mode.sh not found.
Install Helix Code, or start HelixLLM manually so it answers at
      ${_hl_url}."
        fi
      fi
      # Check for coder mode (even if running)
      if [[ "$_hl_healthy" -eq 1 && "$_hl_mode" -eq 24576 ]] 2>/
      dev/null; then
        _hl_warn "helixagent: HelixLLM detected in CODER MODE
      (context_limit=24576).
helixagent REQUIRES CLAUDE MODE (context_limit=229376).
The first request (~67K system+tools) will immediately exceed
      the limit.
Fix on the HelixLLM host:
  helix_code/scripts/helixllm-mode.sh claude
Then re-run the alias."
      fi
    fi
    # Port-squatter guard (live-proven 2026-07-19: `poe: FAIL
      tools-params`).
    # Find a genuinely free port, then confirm OUR pid owns it —
      never point
    # `base` at a squatter (ccr once held 3457 for 21h, silently
      disabling the
    # proxy so every request bypassed its shims).
    local _proxy_port=3457 _pp_try=0
    while lsof -i ":$_proxy_port" >/dev/null 2>&1 && (( _pp_try
      < 20 )); do
      _proxy_port=$((_proxy_port + 1)); _pp_try=$((_pp_try + 1))
    done
    # Export the upstream to the proxy child: the env file is
      sourced WITHOUT
    # `set -a`, so CMA_PROVIDER_BASE_URL is not otherwise
      inherited, and
    # cma-proxy needs it to reach the real backend (a bare --
      port launch would
    # fall back to its built-in default).
    # STDIO REDIRECTION IS LOAD-BEARING, not tidiness. A
      backgrounded daemon
    # that inherits the caller's stdout/stderr holds the WRITE
      END of whatever
    # pipe the caller installed. Every caller that captures a
      launch with
    # command substitution — verify_superpowers_tui.sh, claude-
      release-gate.sh
    # — reads until EOF, and EOF never arrives while the proxy
      is alive: the
    # capture hangs for the proxy's whole lifetime (measured:
      30005ms vs 5ms,
```

```
    # both rc=0). It bites hardest on the SUCCESS path, where
      `timeout` has
    # already reaped its own child and can bound nothing, and it
      is reached
    # deterministically whenever the proxy is orphaned by the
      `_proxy_pid=""`
    # branch below (lsof is an undeclared dependency; absent,
      that branch is
    # always taken). Independently and unconditionally, cma-
      proxy prints a
    # startup banner to stderr, and callers apply `2>&1` to the
      whole
    # cma_run_provider call — so the banner lands INSIDE the
      captured payload
    # and breaks `jq` on captured JSON. Both go away by giving
      the daemon its
    # own log file and closing its stdin (mirrors the router's
      own precedent
    # in cmd/ccr/spawn_unix.go). $_ccr_home is in scope here and
      already
    # mkdir -p'd above.
    CMA_PROVIDER_BASE_URL="$CMA_PROVIDER_BASE_URL" \
      "$_proxy_bin" --provider "$CMA_PROVIDER_ID" --port
      "$_proxy_port" \
      >>"$_ccr_home/cma-proxy.log" 2>&1 </dev/null &
    _proxy_pid=$!
    local _waited=0
    # Wait for OUR process to be listening — not merely for the
      port to be busy.
    while ! lsof -a -p "$_proxy_pid" -i ":$_proxy_port" >/dev/
      null 2>&1 && (( _waited < 25 )); do
      kill -0 "$_proxy_pid" 2>/dev/null || break   # proxy died:
      stop waiting
      sleep 0.2
      _waited=$((_waited + 1))
    done
    if ! lsof -a -p "$_proxy_pid" -i ":$_proxy_port" >/dev/null
      2>&1; then
      # Never point at a foreign listener. Fall back to the
      provider's direct
      # endpoint and say so loudly, rather than silently losing
      the shims.
      command -v cma_log >/dev/null 2>&1 && \
        cma_log "WARNING: cma-proxy for $CMA_PROVIDER_ID did not
      start on port $_proxy_port — using the direct endpoint
      (compat shims INACTIVE)" || true
      # REAP BEFORE CLEARING. `_proxy_pid` is the ONLY handle
      the exit path
      # (the `kill "$_proxy_pid"` reap further down) is guarded
      on, so
      # blanking it here without killing first leaks the child:
      it survives
      # the launch, keeps its port, and — pre-redirection — kept
      the caller's
      # pipe open forever. This branch is not exotic: `lsof` is
      an undeclared
```

```
      # dependency of this file, so on any host without it the
        probe ALWAYS
      # fails and this orphan is produced on EVERY proxied
        launch.
      if [[ -n "$_proxy_pid" ]] && kill -0 "$_proxy_pid" 2>/dev/
        null; then
        kill "$_proxy_pid" 2>/dev/null || true
      fi
      _proxy_pid=""
      _proxy_script=""
    fi
  fi
  if [[ -n "$_proxy_script" ]]; then
    base="http://127.0.0.1:${_proxy_port}/v1/chat/completions"
    # THE fossil-producing assignment: `base` is now an
      EPHEMERAL address whose
    # lifetime is this launch. Record it (and the real endpoint
      it replaced) so
    # both the exit repair and the next launch's stale-reap can
      undo it. The
    # marker is a sidecar — never a field inside config.json,
      which the router
    # parses.
    _eph_base="$base"
    # cma_log is a lib.sh helper; the self-contained alias file
      has no such
    # function, so guard the call to avoid a 'cma_log: command
      not found' on
    # every proxied launch.
    command -v cma_log >/dev/null 2>&1 && cma_log "started cma-
      proxy for $CMA_PROVIDER_ID on port $_proxy_port
      (pid=$_proxy_pid)" || true
  fi
  # Route write + apply. EVERY failure here is FATAL, because
      the failure mode
  # is silent-and-wrong: the launch below serves whatever route
      the gateway
  # currently holds. The old code hid both halves — the jq/mv
      write ran under
  # `2>/dev/null` with a bare `else rm -f` (a failed write was
  # indistinguishable from a successful one) and `ccr restart`
      ran under
  # `|| true` (a config written but never applied still
      launched, serving the
  # PREVIOUS provider's model). That is what made the helixagent
      facade
  # invisible for a whole release. A route we cannot prove we
      set is a route
  # we must not launch against.
  local _route_err=0 _route_msg=""
  if ! command -v jq >/dev/null 2>&1; then
    _route_err=1
    _route_msg="jq is not on PATH, so the ccr route cannot be
      written"
  else
```

```
    local tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")";
      chmod 600 "$tmp" 2>/dev/null || true
    # Lock the config.json read-modify-write against concurrent
      launches of
    # the SAME provider id. Two launches that both read the
      config before
    # either writes it will each produce a rewrite from the same
      stale
    # snapshot — the second mv silently overwrites the first,
      and the first
    # launch's provider route is lost. The per-alias config is
      isolated
    # ($cfg = $_ccr_home/config.json, one per provider-id), so
      the lock
    # targets only this config's own file.
    _cma_cfg_lock "$cfg"
    # Pass the secret through the environment ($ENV.tok), never
      as a jq argv
    # argument — argv is visible in ps/proc to other local
      users.
    # `>|` (force-clobber), NOT `>`: cma_run_provider runs in
      the user's
    # interactive shell, which may have `set -o noclobber`.
      Plain `>` onto the
    # just-created mktemp file fails there ("cannot overwrite
      existing file"),
    # silently dropping the router-config update so EVERY router
      provider breaks.
    local _jq_err _jq_rc _mv_err _mv_rc _rst_out _rst_rc
    _jq_err="$(CMA_TOK="$token" jq --arg n "$CMA_PROVIDER_ID" --
      arg u "$base" \
          --arg s "$CMA_PROVIDER_MODEL" --arg f "$
      {CMA_PROVIDER_FAST_MODEL:-$CMA_PROVIDER_MODEL}" '
        .Providers = ([{name:$n, api_base_url:$u, api_key:
      $ENV.CMA_TOK, models:[$s,$f],
              transformer:{use:
      ["cleancache","streamoptions"]}}])
        | .Router.default = ($n + "," + $s)
        | .Router.background = ($n + "," + $f)
      ' "$cfg" 2>&1 >| "$tmp")"
    _jq_rc=$?
    if (( _jq_rc != 0 )) || [[ ! -s "$tmp" ]]; then
      # An empty output file is a failed rewrite too: mv-ing it
      would leave an
      # unparseable config behind and the gateway would keep the
      old route.
      rm -f "$tmp"
      _route_err=1
      _route_msg="the jq rewrite of $cfg failed (rc=$_jq_rc)$
      {_jq_err:+: $_jq_err}"
      _cma_cfg_unlock
    else
      _mv_err="$(command mv -f "$tmp" "$cfg" 2>&1)"; _mv_rc=$?
      if (( _mv_rc != 0 )); then
        rm -f "$tmp"
```

```
  _route_err=1
  _route_msg="installing the rewritten $cfg failed (mv
rc=$_mv_rc)${_mv_err:+: $_mv_err}"
  _cma_cfg_unlock
else
  chmod 600 "$cfg" 2>/dev/null || true
  _cma_cfg_unlock
  # Remember exactly what WE wrote, so the exit repair can
compare-and-swap
  # instead of clobbering a newer launch's route.
  _wrote_default="$CMA_PROVIDER_ID,$CMA_PROVIDER_MODEL"
  _wrote_background="$CMA_PROVIDER_ID,$
{CMA_PROVIDER_FAST_MODEL:-$CMA_PROVIDER_MODEL}"
  # Crash-recovery marker: written the moment an ephemeral
address becomes
  # durable, so a launch killed before its exit repair
(SIGKILL, reboot)
  # still leaves the next launch enough to reap the
fossil. $$ is the
  # owning shell; the next launch reaps only when `kill
-0` proves it dead.
  # Locked (marker-lost-update hardening — see _eph_lock's
declaration
  # above): read-modify-write against $_eph_marker under
the same
  # cross-launch mutual exclusion as the reap loop and the
exit repair.
  if [[ -n "$_eph_base" ]] && command -v jq >/dev/null
2>&1; then
    _cma_eph_lock
    local _mk_tmp
    [[ -f "$_eph_marker" ]] || ( umask 077; printf '{}\n'
> "$_eph_marker" )
    _mk_tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX" 2>/dev/
null)" && chmod 600 "$_mk_tmp" 2>/dev/null
    if [[ -n "$_mk_tmp" ]] && jq --arg k
"$CMA_PROVIDER_ID" --arg e "$_eph_base" \
          --arg r "$_real_base" --argjson p "$$" \
          '.[$k] = {eph:$e, real:$r, pid:$p}'
"$_eph_marker" >| "$_mk_tmp" 2>/dev/null \
          && [[ -s "$_mk_tmp" ]]; then
      command mv -f "$_mk_tmp" "$_eph_marker" 2>/dev/null
&& chmod 600 "$_eph_marker" 2>/dev/null
    else
      [[ -n "$_mk_tmp" ]] && rm -f "$_mk_tmp"
    fi
    _cma_eph_unlock
  fi
   # `ccr restart` is what makes the write LIVE
(service.go:cmdRestart).
   # Its failure means the file is right and the gateway
is still wrong —
   # the most dangerous state of all, and the one `||
true` used to hide.
```

```
    _rst_out="$(env ${_ccr_ca_env[@]+"${_ccr_ca_env[@]}"}
CCR_HOME="$_ccr_home" "$_ccr" restart --gateway-port
"$_ccr_port" --port "$_ccr_mgmt_port" 2>&1)"; _rst_rc=$?
  if (( _rst_rc != 0 )); then
    # SELF-HEAL the commonest cause. A "Profile … not
found or is
    # disabled" reply means ccr parsed 'restart' as a
profile NAME — the
    # installed ccr binary is STALE: it predates the
'restart' subcommand
    # this launch depends on (a current build lists it in
`ccr --help`).
    # The binary is a gitignored build artifact, so a
submodule bump does
    # NOT rebuild it, and because EVERY router-transport
alias hits this
    # same step, one stale ccr bricks all of them at once.
Rebuild once +
    # retry (bounded: one rebuild, one retry) so a launch
cannot be
    # silently refused for a condition the toolkit can fix
itself; if the
    # rebuild is unavailable or does not help, fall
through to the
    # self-diagnosing error below.
    case "$_rst_out" in
      *'not found or is disabled'*)
        if command -v claude-ccr-build >/dev/null 2>&1;
then
          command -v cma_log >/dev/null 2>&1 \
            && cma_log "bundled ccr is stale (no 'restart'
subcommand) — rebuilding once via claude-ccr-build …" \
            || printf 'claude-providers: bundled ccr is
stale — rebuilding it once (this may take ~30s) …\n' >&2
          claude-ccr-build >/dev/null 2>&1 || true
          _rst_out="$(env ${_ccr_ca_env[@]+"$
{_ccr_ca_env[@]}"} CCR_HOME="$_ccr_home" "$_ccr" restart
--gateway-port "$_ccr_port" --port "$_ccr_mgmt_port"
2>&1)"; _rst_rc=$?
        fi ;;
    esac
  fi
  if (( _rst_rc != 0 )); then
    _route_err=1
    # Single quotes, not backticks:
test_ccr_conformance.sh scans lib.sh
    # for `ccr <subcommand>` invocations by splitting on
shell command
    # separators — a backtick here reads as a command
substitution and
    # the scanner extracts the bogus subcommand
'restart\'.
    _route_msg="'ccr restart' failed (rc=$_rst_rc), so the
new route was written but never applied${_rst_out:+:
$_rst_out}"
    case "$_rst_out" in
```

```
            *'not found or is disabled'*)
              _route_msg="$_route_msg
ROOT CAUSE: the bundled 'ccr' binary is STALE — it does not
      recognize the 'restart' subcommand (it read 'restart' as a
      profile), and an automatic rebuild was unavailable or did
      not resolve it. Rebuild manually, then retry: claude-ccr-
      build (needs the Go toolchain)." ;;
          esac
        fi
      fi
    fi
  fi
  if (( _route_err )); then
    # Defensive scrub: diagnostics are echoed from tool stderr,
      which must
    # never be allowed to carry the live key back to the
      terminal.
    [[ -n "$token" ]] && _route_msg="${_route_msg//"$token"/
      <redacted>}"
    printf 'claude-providers: refusing to launch %s — its ccr
      route was NOT applied.\n  %s\n' "$id" "$_route_msg" >&2
    printf '  Launching anyway would serve whichever provider
      the gateway last routed to (wrong model, no error).\n' >&2
    if [[ -n "$_proxy_pid" ]]; then
      kill "$_proxy_pid" 2>/dev/null || true
      command -v cma_log >/dev/null 2>&1 && cma_log "stopped
      proxy for $CMA_PROVIDER_ID (pid=$_proxy_pid) after route
      failure" || true
    fi
    # This path can ALSO leave a fossil: the jq+mv may have
      succeeded and only
    # `ccr restart` failed, in which case the ephemeral address
      is already
    # durable. Repair here too — the proxy we just killed is now
      dead.
    _cma_ccr_unfossilise "$cfg" "$CMA_PROVIDER_ID" "$_eph_base"
      "$_real_base" \
      "$_wrote_default" "$_wrote_background" "$_prior_default"
      "$_prior_background" \
      "$_eph_marker"
    return 78
  fi
  env ${_ccr_ca_env[@]+"${_ccr_ca_env[@]}"}
      CCR_HOME="$_ccr_home" "$_ccr" default-claude-code -- "$@";
      rc=$?
  # Stop proxy if we started one
  if [[ -n "$_proxy_pid" ]]; then
    kill "$_proxy_pid" 2>/dev/null || true
    command -v cma_log >/dev/null 2>&1 && cma_log "stopped proxy
      for $CMA_PROVIDER_ID (pid=$_proxy_pid)" || true
  fi
  # The proxy is dead as of the line above, so the address
      written into the
  # DURABLE config now names nothing. Undo it before returning —
      compare-and-
```

```
  # swap, so a launch that started after ours keeps its own
      route untouched.
  _cma_ccr_unfossilise "$cfg" "$CMA_PROVIDER_ID" "$_eph_base"
      "$_real_base" \
    "$_wrote_default" "$_wrote_background" "$_prior_default"
      "$_prior_background" \
    "$_eph_marker"
else
  export ANTHROPIC_BASE_URL="$CMA_PROVIDER_BASE_URL"
  export ANTHROPIC_AUTH_TOKEN="$token"
  # Native transport against a self-signed https upstream: the
      verify probe
  # trusts CMA_PROVIDER_CA_CERT, and the launch must too. claude
      is a Node
  # process, and Node APPENDS NODE_EXTRA_CA_CERTS to its system
      roots — so
  # the raw CA path is sufficient (no combined bundle needed,
      unlike the
  # router transport's Go client where SSL_CERT_FILE REPLACES
      the pool).
  if [[ -n "${CMA_PROVIDER_CA_CERT:-}" && -r "$
      {CMA_PROVIDER_CA_CERT:-}" ]] \
     && [[ "$CMA_PROVIDER_BASE_URL" == https://* ]]; then
    export NODE_EXTRA_CA_CERTS="$CMA_PROVIDER_CA_CERT"
  fi
  # ANTHROPIC_MODEL + the four ANTHROPIC_DEFAULT_*_MODEL tier
      maps are
  # exported ABOVE for BOTH transports (v1.26.1 — the 2.1.220
      compact-loop
  # fix): a tier-pinned subagent dispatch or fast-tier call
      never leaks a
  # literal claude-* id to a native provider endpoint (which
      rejects it —
  # xiaomi HTTP 400 "Unsupported model" — or silently
      substitutes — deepseek
  # 200), and the router transport's client-side tier resolution
      (fast/
  # compact = Fable 5, unavailable in 2.1.220) maps to the
      serving model.
  # Session flags are applied ABOVE for both transports
      (v1.17.0) — see
  # _cma_session_flags. CLAUDE_CODE_MAX_OUTPUT_TOKENS is
      exported ABOVE too,
  # before the transport branch, CLAMPED to <=128000 for BOTH
      transports —
  # see the _cma_out_guard/output-token-clamp block. (Was
      formerly
  # re-exported here as the RAW, unclamped
      CMA_PROVIDER_MAX_OUTPUT — the
  # origin of the "128000" fatal.)
      CLAUDE_CODE_AUTO_COMPACT_WINDOW caps
  # INPUT — the two are independent halves of the guard.
  "$CLAUDE_BIN" "$@"; rc=$?
fi
# Push post-session state back to all accounts/providers for
      cross-alias visibility.
```

```
  if [[ -x "$HOME/.local/bin/claude-sync-state" ]]; then
    "$HOME/.local/bin/claude-sync-state" push "$CLAUDE_CONFIG_DIR"
        2>/dev/null || true
  fi
  # Colour a freshly-created session too (its jsonl exists now),
        so the colour is
  # in place on the next resume even on the very first launch.
  [[ "${_cma_pcolor:-}" == 1 && -x "$HOME/.local/bin/claude-
        session" ]] && \
    "$HOME/.local/bin/claude-session" apply-color
        "$CLAUDE_CONFIG_DIR" "$CMA_PROVIDER_ID" 2>/dev/null ||
        true
  return $rc
}
CMA_PROV_BODY_EOF
}

# The provider session-refresh hook: on every interactive shell
        start it
# re-writes provider aliases from cache (NO network) and, when the
        status cache
# is older than CMA_PROVIDERS_SYNC_TTL (default 24h), kicks a
        detached full sync.
#
# CMA_ALIAS_LOCK_WAIT=0 is LOAD-BEARING: this runs on every shell
        start, so it
# must never wait on another writer. On contention each alias
        write is skipped
# silently and the file is left exactly as the other writer leaves
        it.
_cma_emit_session_hook() {
  printf '%s\n' "$CMA_ALIAS_HOOK_BEGIN"
  cat <<'HOOK'
cma_providers_session_refresh() {
  command -v claude-providers >/dev/null 2>&1 || return 0
  # No-network: re-write alias functions from the cached env
        files. The
  # alias-file lock is taken with a ZERO wait so a shell start can
        never block
  # behind a concurrent sync; a skipped refresh is harmless.
  # CMA_ALIAS_SKIP_ON_CONTENTION=1 is the ONLY opt-in to "a
        contended write
  # reports success". It belongs here and nowhere else: a shell
        start must not
  # block, and a skipped refresh is genuinely harmless because the
        next writer
  # re-renders the same delta from the file. Every other caller
        gets rc 75.
  CMA_ALIAS_LOCK_WAIT=0 CMA_ALIAS_SKIP_ON_CONTENTION=1 claude-
        providers list --quiet --refresh-aliases >/dev/null 2>&1
        || true
  # TTL-triggered background full sync (detached; never blocks the
        shell).
  local ttl="${CMA_PROVIDERS_SYNC_TTL:-86400}"
```

```
  local sf="$HOME/.local/share/claude-multi-account/providers/
        status.json"
  if [ -f "$sf" ]; then
    local now mtime age
    now="$(date +%s)"
    mtime="$(stat -c %Y "$sf" 2>/dev/null || stat -f %m "$sf" 2>/
        dev/null || echo "$now")"
    age=$(( now - mtime ))
    if [ "$age" -gt "$ttl" ]; then
      ( nohup claude-providers sync >/dev/null 2>&1 & disown ) 2>/
        dev/null || true
    fi
  fi
}
cma_providers_session_refresh
HOOK
  printf '%s\n' "$CMA_ALIAS_HOOK_END"
}

# Which CLAUDE_BIN the render should record. Keeps the value
        already on disk
# when it still resolves to an executable; otherwise re-resolves
        (an alias file
# carrying a stale path from another host makes EVERY alias launch
        an empty
# command). Only replaces when the replacement is actually
        executable.
_cma_alias_claude_bin() {
  local src="${1:-}" cur="" exp new
  if [[ -f "$src" ]]; then
    cur="$(grep -m1 '^export CLAUDE_BIN=' "$src" 2>/dev/null ||
        true)"
    cur="${cur#export CLAUDE_BIN=}"; cur="${cur#\"}"; cur="${cur%
        \"}"
  fi
  exp="${cur/#\$HOME/$HOME}"; exp="${exp/#\~/$HOME}"
  if [[ -n "$cur" && -x "$exp" ]]; then printf '%s\n' "$cur";
        return 0; fi
  new="$(cma_resolve_claude_bin)"
  if [[ -n "$cur" && ! -x "${new/#\$HOME/$HOME}" ]]; then printf
        '%s\n' "$cur"; return 0; fi
  printf '%s\n' "$new"
}

_cma_emit_managed() {
  local cb="$1"
  printf '%s\n' "$CMA_ALIAS_MANAGED_BEGIN"
  printf '# Managed by claude-multi-account. Do not edit by hand;
        use\n'
  printf '# ~/.local/bin/claude-add-account to add accounts.\n'
  printf 'export CLAUDE_BIN="%s"\n' "$cb"
  printf '\n'
  _cma_emit_ccr_gateway_guard
  printf '\n'
```

```
  _cma_emit_cma_run
  printf '\n'
  _cma_emit_llmctl_ensure_active
  printf '\n'
  _cma_emit_cma_run_provider
  printf '\n'
  _cma_emit_cma_run_kimi
  printf '\n'
  _cma_emit_cma_run_kimi_provider
  printf '\n'
  _cma_emit_cma_run_pi
  printf '\n'
  _cma_emit_cma_run_pi_provider
  printf '\n'
  _cma_emit_account_dispatch
  printf '%s\n' "$CMA_ALIAS_MANAGED_END"
}

# Everything the toolkit does NOT own, in original order: alias
      lines plus any
# user-added content. Strips the managed block, the hook block,
      and — for files
# written before the sentinels existed — the legacy header/wrapper
      text by
# content, including the orphaned `# Wrapper:` comment copies the
      old
# drop/re-append migration left behind.
_cma_alias_carryover() {
  local src="$1" region=0 hookr=0 mtrunc=0 htrunc=0
  [[ -f "$src" ]] || return 0
  # A block is only treated as a block when BOTH of its sentinels
      are present.
  # An unterminated BEGIN (a file truncated by something outside
      this toolkit)
  # would otherwise swallow every alias below it.
  if grep -qxF "$CMA_ALIAS_MANAGED_BEGIN" "$src"; then
    if grep -qxF "$CMA_ALIAS_MANAGED_END" "$src"; then region=1;
      else mtrunc=1; fi
  fi
  if grep -qxF "$CMA_ALIAS_HOOK_BEGIN" "$src"; then
    if grep -qxF "$CMA_ALIAS_HOOK_END" "$src"; then hookr=1; else
      htrunc=1; fi
  fi
  # TRUNCATION RECOVERY, stated as a property of the block rather
      than of its
  # current contents. A BEGIN with no END means the file was cut
      INSIDE the

      # block, so what survives is a PREFIX of machine-owned
      text — an unterminated
  # function, a half-written `case`, whatever the emitters
      happened to open.
  # Carrying that prefix over as "user content" re-emits it above
      the alias
```

```
# lines and makes the whole file unparseable: `bash -n` fails, so the rc file
# sourcing it aborts and EVERY alias in it is dead. That is strictly worse
# than the truncation itself.
#
# The end of the salvage window is derived, not enumerated: no emitted
# managed/hook line is an `alias` at column 0, and no emitted managed line is
# the hook's BEGIN sentinel, so the first of those is provably outside the

      # truncated block. Everything before it goes; everything from it on is kept.
#

      # Deriving it this way is the point. The by-content legacy rules below list
# the wrapper functions by name, and that list SILENTLY went stale when
# _cma_emit_ccr_gateway_guard was added to the managed block: a file cut
# inside the new guard (the block's first function, so the likeliest cut of
# all) carried an unterminated `case` straight into the rebuilt file. A rule
# phrased over the block's boundary cannot go stale that way.
awk -v mb="$CMA_ALIAS_MANAGED_BEGIN" -v me="$CMA_ALIAS_MANAGED_END" \
    -v hb="$CMA_ALIAS_HOOK_BEGIN" -v he="$CMA_ALIAS_HOOK_END" \
    -v region="$region" -v hookr="$hookr" \
    -v mtrunc="$mtrunc" -v htrunc="$htrunc" '
  $0 == mb { if (region) { m = 1 } else if (mtrunc) { t = 1 }; next }
  $0 == me { m = 0; next }
  m        { next }
  # Salvage window ends at the first line that cannot be block content.
  t && /^alias[[:space:]]/ { t = 0 }
  t && $0 == hb            { t = 0 }
  t        { next }
  $0 == hb { if (hookr) { h = 1 } else if (htrunc) { t = 1 }; next }
  $0 == he { h = 0; next }
  h        { next }
  # --- legacy (pre-sentinel) managed content ------------------------------
  # NOTE: the parens are escaped for awk ERE, where \( is a LITERAL paren, so
  # /^cma_run\(\) ?\{/ cannot match "cma_run_provider() {". (The same spelling
  # in grep BRE would be an empty capture group and WOULD match it — that bug
  # once dropped the function entirely.)
```

```
    /^cma_run\(\) ?\{/          { f = 1 }
    /^cma_run_provider\(\) ?\{/ { f = 1 }
    # An `alias` at column 0 always ends the skip: no emitted
        wrapper body
    # contains such a line, so this cannot swallow one, and it
        means a wrapper
    # left UNTERMINATED by an external truncation can never eat
        the alias lines
    # below it. Without this the recovery path drops exactly the
        data the
    # recovery exists to save.
    f && /^alias[[:space:]]/    { f = 0 }
    f { if ($0 ~ /^\}/) f = 0; next }
    /^# Managed by claude-multi-account/            { next }
    /^# ~\/\.local\/bin\/claude-add-account to add/ { next }
    /^export CLAUDE_BIN=/                           { next }
    /^# Wrapper: keeps \.claude\.json/              { next }
    /^# logged-in account\. Pulls merged state/     { next }
    /^# one before claude runs; pushes the post/    { next }
    /^# Cheap \(jq deep-merge of one/               { next }
    { print }
  ' "$src"
}

# The existing hook block, verbatim (first one only). Requires
        BOTH sentinels:
# an unterminated BEGIN would otherwise copy the rest of the file
        into the hook
# position, duplicating every alias below it.
_cma_alias_extract_hook() {
  local src="$1"
  [[ -f "$src" ]] || return 0
  grep -qxF "$CMA_ALIAS_HOOK_BEGIN" "$src" || return 0
  grep -qxF "$CMA_ALIAS_HOOK_END" "$src"   || return 0
  awk -v b="$CMA_ALIAS_HOOK_BEGIN" -v e="$CMA_ALIAS_HOOK_END" '
    $0 == b && !seen { h = 1; seen = 1 }
    h { print }
    $0 == e { h = 0 }
  ' "$src"
}

# Alias names defined in a file, sorted and unique.
_cma_alias_names() {
  [[ -f "$1" ]] || return 0
  awk -F'[ =]+' '/^[[:space:]]*alias[[:space:]]+/{print $2}' "$1"
        | LC_ALL=C sort -u
}

# Names of the account aliases (the `CLAUDE_CONFIG_DIR=` form) in
        a file,
# sorted and unique — the input to the gate's account-alias floor.
_cma_alias_account_names() {
  [[ -f "$1" ]] || return 0
```

```
  grep '^alias[[:space:]][^=]*="CLAUDE_CONFIG_DIR=' "$1" 2>/dev/
      null \
    | awk -F'[ =]+' '{print $2}' | LC_ALL=C sort -u || true
}

# Count of account aliases (the `CLAUDE_CONFIG_DIR=` form) in a
      file.
_cma_alias_account_count() {
  local n=0
  if [[ -f "$1" ]]; then
    # `grep -c` prints 0 AND exits 1 on no-match, so the || must
      not print too.
    n="$(grep -c '^alias[[:space:]][^=]*="CLAUDE_CONFIG_DIR='
      "$1" 2>/dev/null || true)"
    [[ -n "$n" ]] || n=0
  fi
  printf '%s\n' "$n"
}

_cma_alias_mktemp() {
  local dir; dir="$(dirname "$ALIAS_FILE")"
  # Same directory as the target on purpose: the commit is a
      rename, which is
  # only atomic within one filesystem, and a leaked temp is then
      visible where
  # it matters instead of accumulating invisibly in $TMPDIR (7743
      leaked
  # $TMPDIR/cma.* snapshots were found during the incident).
  mktemp "$dir/.aliases.render.XXXXXX" 2>/dev/null
}

# _cma_alias_render <src> <drop_name> <add_line> <hook_mode> <out>
#   drop_name  alias to remove ("" = none)
#   add_line   full alias line to add ("" = none); replaces an
      existing
#              definition of the same name IN PLACE, else is
      appended
#   hook_mode  keep | install
# Emits the COMPLETE file. This is the only place the file's shape
      is decided.
_cma_alias_render() {
  local src="$1" drop="$2" add="$3" hook="$4" out="$5"
  local carry cb
  carry="$(_cma_alias_mktemp)" || return 1

  # 1. carry over everything we do not own
  _cma_alias_carryover "$src" > "$carry"

  # 2. legacy alias migration: pre-wrapper lines invoking
      $CLAUDE_BIN directly
  #    are rewritten to go through cma_run (idempotent — a line
      already using
  #    cma_run is left alone).
```

```
      # shellcheck disable=SC2016  # $CLAUDE_BIN is literal
      alias-file text here
if grep -qE '^alias[[:space:]]+[^=]+=.*CLAUDE_CONFIG_DIR=[^ ]+
      [[:space:]]+\\?\$CLAUDE_BIN"$' "$carry" 2>/dev/null; then
  # shellcheck disable=SC2016
  sed -E 's|(^alias[[:space:]]+[^=]+=)"(CLAUDE_CONFIG_DIR=[^ ]+)
      [[:space:]]+\\?\$CLAUDE_BIN"$|\1"\2 cma_run"|' \
    "$carry" > "$carry.mig" && command mv -f "$carry.mig"
      "$carry"
fi

# 3. removal delta. Skipped when the SAME name is being
      rewritten: that case

      #    is a replace-in-place below, which is what keeps a
      repeated write
#    byte-identical instead of permuting the file's alias order
      (drop+append

      #    would move the rewritten alias to the end on every
      call, so a repeat of
#    the same two writes never converged and the no-op guard
      could never fire).
local addname=""
if [[ -n "$add" ]]; then
  addname="$(printf '%s\n' "$add" | awk -F'[ =]+' '{print $2}')"
fi
if [[ -n "$drop" && "$drop" != "$addname" ]]; then
  # The drop name is a LITERAL alias name, never a pattern:
      escape ERE
  # metacharacters so e.g. `kimi-a.b` cannot also drop `kimi-
      aXb` (which the
  # gate then rejects, leaving the stale line forever +
      a .rejected.* per run).
  local drop_re; drop_re="$(printf '%s' "$drop" | sed 's/[]
      [\.*^$+?(){}|]/\\&/g')"
  grep -v -E "^alias[[:space:]]+${drop_re}=" "$carry" >
      "$carry.d" || true
  command mv -f "$carry.d" "$carry"
fi

# 4. de-duplicate alias definitions (last one wins) and apply
      the add delta:
#    an existing definition of the same name is replaced at its
      original
#    position; a genuinely new alias is appended. Two passes
      over one file.
#    The add text goes through ENVIRON, not -v, because -v
      applies backslash
#    escape processing to the value.
CMA_ADD_NAME="$addname" CMA_ADD_LINE="$add" awk -F'[ =]+' '
  NR == FNR { if ($0 ~ /^alias[[:space:]]+/) last[$2] = FNR;
      next }
  {
```

```
    if ($0 ~ /^alias[[:space:]]+/) {
      if (FNR != last[$2]) next
      if (ENVIRON["CMA_ADD_NAME"] != "" && $2 ==
      ENVIRON["CMA_ADD_NAME"]) {
        print ENVIRON["CMA_ADD_LINE"]; added = 1; next
      }
    }
    print
  }
  END { if (ENVIRON["CMA_ADD_NAME"] != "" && !added) print
      ENVIRON["CMA_ADD_LINE"] }
' "$carry" "$carry" > "$carry.u" && command mv -f "$carry.u"
      "$carry"

cb="$(_cma_alias_claude_bin "$src")"

# The write status is PROPAGATED, and the stages are &&-chained
      so a failure
# in any of them (not merely the last) is seen. Discarding it
      meant a

      # candidate truncated by ENOSPC — or one whose output file
      could not be opened
# at all — was returned as a successful render. Against a zero-
      alias source
# such a stump also clears the sanity gate, which only requires
      the header and

      # the two wrapper opening lines and has no aliases left to
      miss. A render we
# cannot prove we wrote is a render we must not offer for
      commit.
#
# The open is probed SEPARATELY, with a simple command, because
      the two
# failure modes reach us through different channels and the
      group form only
# reports one of them:
#   * ENOSPC  — the open SUCCEEDS, the writes fail; the group's
      own exit
#               status carries it, and the &&-chain below sees
      it.
#   * ENOENT/EACCES on the output path — the redirection fails
      BEFORE the
#               group runs, and bash leaves the compound
      command's status at

      #               0 (verified on bash 5.2: `if ! { :; } > /
      nope/x` takes the
#               else branch). A simple command with the same
      failed
#               redirection does return 1, so that is what
      grades the open.

      # Without this probe an unwritable output path was
      reported as a successful
```

```
  # render of a file that does not exist.
  if ! : > "$out" 2>/dev/null; then
    rm -f "$carry" "$carry.mig" "$carry.d" "$carry.u" 2>/dev/null
        || true
    cma_warn "alias render: cannot open $out for writing (missing
        directory? permissions?)"
    return 1
  fi
  if ! { _cma_emit_managed "$cb" \
         && cat "$carry" \
         && if [[ "$hook" == "install" ]]; then
              _cma_emit_session_hook
            else
              _cma_alias_extract_hook "$src"
            fi
       } > "$out"; then
    rm -f "$carry" "$carry.mig" "$carry.d" "$carry.u" 2>/dev/null
        || true
    cma_warn "alias render: writing the candidate to $out failed
        (out of space? unwritable path?)"
    return 1
  fi

  rm -f "$carry" "$carry.mig" "$carry.d" "$carry.u" 2>/dev/null
        || true
  return 0
}

# Refuse to publish a candidate that lost something. Structural
        floor: the
# header and BOTH wrappers must be present. Content floor: the
        candidate's set
# of alias names must be exactly the source's set, minus an
        explicit drop, plus
# an explicit add — the incident's signature was account aliases
        silently
# vanishing from a file nobody asked to change. Account aliases
        are additionally
# floored against cma_detect_accounts, as far as the source file
        already
# satisfied it (a fresh install legitimately has fewer).
_cma_alias_gate() {
  local cand="$1" src="$2" drop="$3" add="$4"
  local want got n_acct src_acct cand_acct rc=0

  grep -q '^export CLAUDE_BIN=' "$cand"   || { cma_warn "alias
        render rejected: no CLAUDE_BIN header"; return 1; }
  grep -q '^cma_run() {' "$cand"          || { cma_warn "alias
        render rejected: no cma_run()"; return 1; }
  grep -q '^cma_run_provider() {' "$cand" || { cma_warn "alias
        render rejected: no cma_run_provider()"; return 1; }
  # The kimi wrappers are part of the emitted managed block
        (family layer);
```

```
# a render that lost either is as structurally broken as one
      missing cma_run,

      # since the kimiN / kimi-<id> aliases would then exec a
      function that does
# not exist on shell start.
grep -q '^cma_run_kimi() {' "$cand"          || { cma_warn
      "alias render rejected: no cma_run_kimi()"; return 1; }
grep -q '^cma_run_kimi_provider() {' "$cand" || { cma_warn
      "alias render rejected: no cma_run_kimi_provider()";
      return 1; }

want="$(_cma_alias_mktemp)" || return 1
got="$(_cma_alias_mktemp)"  || { rm -f "$want"; return 1; }
{
  if [[ -n "$drop" ]]; then
    _cma_alias_names "$src" | grep -v -x -F -- "$drop" || true
  else
    _cma_alias_names "$src"
  fi
  if [[ -n "$add" ]]; then printf '%s\n' "$add" | awk -F'[ =]+'
      '{print $2}'; fi
} | LC_ALL=C sort -u > "$want"
_cma_alias_names "$cand" > "$got"
if ! cmp -s "$want" "$got"; then
  cma_warn "alias render rejected: alias set changed
      unexpectedly ($(wc -l < "$want" | tr -d ' ') wanted, $(wc
      -l < "$got" | tr -d ' ') rendered)"
  rc=1
fi
rm -f "$want" "$got"
(( rc == 0 )) || return 1


      # Account aliases specifically: every `CLAUDE_CONFIG_DIR=`
      alias the source
# had must still be there, minus one the caller explicitly
      dropped. The
# incident's signature was exactly these disappearing from a
      file nobody
# asked to change.
want="$(_cma_alias_mktemp)" || return 1
got="$(_cma_alias_mktemp)"  || { rm -f "$want"; return 1; }
if [[ -n "$drop" ]]; then
  _cma_alias_account_names "$src" | grep -v -x -F -- "$drop" >
      "$want" || true
else
  _cma_alias_account_names "$src" > "$want"
fi
_cma_alias_account_names "$cand" > "$got"
if [[ -n "$(LC_ALL=C comm -23 "$want" "$got")" ]]; then
  cma_warn "alias render rejected: account alias(es) lost: $
      (LC_ALL=C comm -23 "$want" "$got" | tr '\n' ' ')"
  rc=1
```

```
  fi
  rm -f "$want" "$got"
  (( rc == 0 )) || return 1


        # Secondary floor: cma_detect_accounts. Only meaningful
        when the source
  # already satisfied it AND no account is being removed — claude-
        remove-account
  # drops the alias BEFORE the directory, so the detected count
        legitimately
  # leads the alias count by one for the duration of that call.
  src_acct="$(_cma_alias_account_count "$src")"
  cand_acct="$(_cma_alias_account_count "$cand")"
  n_acct="$(cma_detect_accounts | wc -l | tr -d ' ')"
  if [[ -z "$drop" ]] && (( src_acct >= n_acct && cand_acct <
        n_acct )); then
    cma_warn "alias render rejected: $cand_acct account aliases <
        $n_acct detected accounts"
    return 1
  fi
  return 0
}

# cma_alias_commit [drop_name] [add_line] [hook_mode]
# THE single committer. Every mutation of $ALIAS_FILE in this
        toolkit goes
# through here; nothing else may write, append to, or rename onto
        the file.
cma_alias_commit() {
  local drop="${1:-}" add="${2:-}" hook="${3:-keep}"
  local dir cand rc=0 prev_int prev_term
  dir="$(dirname "$ALIAS_FILE")"
  mkdir -p "$dir" 2>/dev/null || true

  # (F3) No-op guard, taken WITHOUT the lock: render against the
        current file
  # and, if nothing would change, do nothing at all. Steady-state
        shell starts
  # perform zero writes and never contend.
  cand="$(_cma_alias_mktemp)" || { cma_warn "cannot create temp
        next to $ALIAS_FILE"; return 1; }
  if _cma_alias_render "$ALIAS_FILE" "$drop" "$add" "$hook"
        "$cand" \
     && [[ -f "$ALIAS_FILE" ]] && cmp -s "$cand" "$ALIAS_FILE";
        then
    rm -f "$cand"
    return 0
  fi
  rm -f "$cand"

  if ! _cma_alias_lock_acquire; then
    # CONTENTION. The write did NOT happen: the file is byte-
        unchanged and the
```

```
  # caller's delta is not in it.
  #
  # Skipping is the right policy for exactly one caller — the
      session-refresh
  # hook, which runs on every shell start with
      CMA_ALIAS_LOCK_WAIT=0 and whose

      # delta the next writer re-derives from the file anyway.
      It is the WRONG

      # policy for everybody else, and reporting 0 to everybody
      else is how it
  # became a data-integrity bug: claude-add-account created the
      config dir,
  # linked the shared items, got 0 from cma_write_alias and
      announced success
  # for an account with NO alias (whose retry then dies on
      "config dir already
  # exists"), and claude-remove-account got 0 from
      cma_remove_alias and went on
  # to ARCHIVE the directory out from under a still-live alias.
  #
  # So the skip is now an explicit opt-in
      (CMA_ALIAS_SKIP_ON_CONTENTION=1, set
  # by _cma_emit_session_hook and nothing else). Every other
      caller gets 75
  # (EX_TEMPFAIL — "try again", as distinct from rc 1 "this
      render is bad") so
  # it can react instead of being told a lie.
  cma_warn "alias file busy — skipped update of $(basename
      "$ALIAS_FILE")"
  [[ "${CMA_ALIAS_SKIP_ON_CONTENTION:-}" == 1 ]] && return 0
  return 75
fi


      # (F4) Mask INT/TERM across the critical section. NOT what
      makes the commit
# atomic — render-once + a single mv(2) does that, with or
      without this mask
# — and NOT what keeps the lock from leaking either: flock is
      released by the
# kernel on death, and a leaked mkdir lock is reclaimed by the
      next acquire's
# stale-breaker. Deleting these three lines leaves the suite
      green. They are
# kept so the caller's own INT/TERM traps are restored rather
      than left

      # disarmed, and as cheap interrupt hygiene — not on the
      strength of any test.

      # See the "What protects WHAT" note above. Saved/restored,
      never clobbered.
prev_int="$(trap -p INT || true)"
prev_term="$(trap -p TERM || true)"
```

```
  trap '' INT TERM

  cand="$(_cma_alias_mktemp)" || cand=""
  if [[ -z "$cand" ]]; then
    rc=1
  elif ! _cma_alias_render "$ALIAS_FILE" "$drop" "$add" "$hook"
        "$cand"; then
    rm -f "$cand"; cma_warn "alias render failed — $ALIAS_FILE
        left untouched"; rc=1
  elif [[ -f "$ALIAS_FILE" ]] && cmp -s "$cand" "$ALIAS_FILE";
        then
    rm -f "$cand"                                   # raced to
        identical; nothing to do
  elif ! _cma_alias_gate "$cand" "$ALIAS_FILE" "$drop" "$add";
        then
    command mv -f "$cand" "$ALIAS_FILE.rejected.$(date +%s)" 2>/
        dev/null || rm -f "$cand"
    cma_warn "$ALIAS_FILE left untouched; candidate kept as
        $ALIAS_FILE.rejected.*"
    rc=1
  else
    command mv -f "$cand" "$ALIAS_FILE" || { rm -f "$cand";
        rc=1; }
  fi

  trap - INT TERM
  if [[ -n "$prev_int" ]]; then eval "$prev_int"; fi
  if [[ -n "$prev_term" ]]; then eval "$prev_term"; fi
  _cma_alias_lock_release
  return $rc
}

# Ensure $ALIAS_FILE exists, is current, and is sourced from the
        user's rc
# files. Idempotent — safe to call repeatedly, and a no-op on disk
        when the
# rendered content already matches.
cma_ensure_alias_file() {
  mkdir -p "$(dirname "$ALIAS_FILE")"
  cma_alias_commit "" "" keep || return 1
  local rc src_line="source \"$ALIAS_FILE\""
  # ${arr[@]+"${arr[@]}"} (not bare "${arr[@]}") so an EMPTY
        CMA_RC_FILES does not
  # trip "unbound variable" under `set -u` on bash 3.2 (macOS
        ships 3.2; it errors
  # on empty-array expansion where bash 4.4+ treats it as empty).
        LOAD-BEARING.
  for rc in ${CMA_RC_FILES[@]+"${CMA_RC_FILES[@]}"}; do
    [[ -f "$rc" ]] || continue
    cma_prune_stale_alias_sources "$rc"   # self-heal: drop
        dangling aliases.sh source lines
    # Add the canonical source line only if no existing line
        already sources THIS
```

```
    # alias file (matched across .|source and $HOME/~/absolute
        forms) — prevents
    # duplicate source lines accumulating across re-installs with
        differing forms.

        # Back up BEFORE the append; refuse the write if the rc
        cannot be protected.
    if ! cma_rc_sources_alias_file "$rc" "$ALIAS_FILE"; then
      if cma_backup_rc_file "$rc"; then
        printf '\n%s\n%s\n' "$CMA_ALIAS_RC_HEADER" "$src_line" >>
        "$rc"
        cma_log "added source line to $rc"
      else
        cma_warn "skipped adding source line to $rc (could not
        back it up)"
      fi
    fi
  done
}

# Add (or refresh) a single alias entry in $ALIAS_FILE.
        Idempotent.
# The generated alias wraps `$CLAUDE_BIN` with sync-pull (before
        launch) and
# sync-push (after exit) so the project/session index
        inside .claude.json
# stays merged across every logged-in account without manual unify
        runs.
cma_write_alias() {
  local alias_name="$1" config_dir="$2"
  cma_validate_alias "$alias_name"
  # config_dir is interpolated into the alias body and re-parsed
        by the shell
  # when the alias is invoked. Reject shell metacharacters
        (injection) and
  # whitespace (an unquoted space would word-split the alias into
        a bogus
  # command — fail loud rather than write a silently-broken
        alias). Matched
  # literally per-char to avoid glob-bracket pitfalls.
  local _cma_c
  for _cma_c in '"' '$' '`' \\ ';' '&' '|' '<' '>' '(' ')'; do
    case "$config_dir" in *"$_cma_c"*)
      cma_warn "refusing to write alias '$alias_name': unsafe
        config dir"
      return 1 ;;
    esac
  done
  case "$config_dir" in *[[:space:]]*)
    cma_warn "refusing to write alias '$alias_name': config dir
        must not contain whitespace"
    return 1 ;;
  esac
  cma_ensure_alias_file
```

```
  # Note: bash aliases can't take args, so we use a quoted
        CLAUDE_CONFIG_DIR=
  # prefix plus a wrapped invocation. The wrapper is a shell
        function reference
  # (cma_run) emitted in the managed block by the renderer.
  # One delta, one render, one rename — see cma_alias_commit.
  cma_alias_commit "$alias_name" \
    "$(printf 'alias %s="CLAUDE_CONFIG_DIR=%s cma_run"'
        "$alias_name" "$config_dir")" keep
}

# Remove an alias line. Idempotent.
cma_remove_alias() {
  local alias_name="$1"
  [[ -f "$ALIAS_FILE" ]] || return 0
  cma_alias_commit "$alias_name" "" keep
}

# ============================================================================
# Provider-alias helpers (used by claude-providers.sh)
# ============================================================================

# The shared items every account/provider dir symlinks into
        $SHARED_DIR.
# Kept here (single source) so claude-add-account and claude-
        providers agree.
CMA_SHARED_ITEMS=(
  projects todos tasks plans file-history paste-cache shell-
        snapshots
  session-env telemetry sessions backups cache plugins
  stats-cache.json history.jsonl CLAUDE.md
  daemon jobs
)
# NOTE (§11.4 own-settings): settings.json is DELIBERATELY NOT in
        the shared set.
# Each config dir gets its OWN settings.json so per-alias
        permissions/model/hooks
# never leak across aliases/providers, while the plugin CACHE
        (`plugins`),
# history (`history.jsonl`), memory (`CLAUDE.md`) and sessions
        stay shared. Each
# dir's own settings.json is seeded from + kept enabledPlugins-
        synced with the
# shared template $SHARED_DIR/settings.json by
        cma_own_settings_seed (so
# superpowers et al. stay enabled everywhere). See
        cma_link_shared_items +
# cma_enable_plugins below.
# NOTE (daemon/jobs): `daemon` is Claude Code's background-agent
        registry
# (roster.json + dispatch). It MUST be shared or a background
        agent started
# under one alias is invisible to every other alias — the registry
        is
```

```
# config-dir-scoped, not session-scoped. `jobs` is its sibling job
        store.
# daemon/roster.json is union-merged (not last-wins) — see
# merge_daemon_roster in claude-unify.sh.

cma_providers_dir() { echo "$HOME/.local/share/claude-multi-
        account/providers"; }

# _cma_quota_group_accounts: one JSON object per line, one per
        distinct
# REAL account (data-model.md §2). Two dedup axes, both real:
# (a) cross-family alias sharing -- multiple $ALIAS_FILE lines
#     launching the SAME .env file via different family wrappers
#     (cma_run_provider / cma_run_kimi_provider /
        cma_run_pi_provider);
# (b) same-credential multi-instance sharing -- multiple
        SEPARATE .env
#     files (different CMA_PROVIDER_ID, since
        cma_provider_write_env
#     always makes the filename equal the id) carrying the
        IDENTICAL
#     CMA_PROVIDER_KEYVAR + CMA_PROVIDER_BASE_URL (e.g.
        openrouter/
#     openrouter2/openrouter3 from a --multi sync or repeated add
        --
#     T038-independent-review finding C2, confirmed live: 5
        real .env
#     files, 1 real key, used to render as 5 rows with 4 false
#     "not reported by provider" statuses).
# Grouped by (opaque ordinal of the key VALUE's sha256 digest,
        base_url)
# -- operator decision "merge by key value": differently named
        variables
# holding the same secret are one account. NEVER on an empty/
        missing/
# unreadable key, which proves nothing about shared identity
        (falls back
# to the pid itself as a unique key, 1:1). EXCEPTION: the Kimi
        Code OAuth
# sentinel keyvar (_CMA_KIMICODE_OAUTH_) has no keys-file value by
        design;
# every alias carrying it shares one OAuth subscription token, so
        those
# group by (keyvar name, base_url) as before. Secret handling: the
        whole
# grouping loop runs with xtrace suspended (restored only after it
        ends);
# the value exists only inside the hashing subshell; each distinct
        digest
# is mapped at once to an in-memory ordinal (dg:1, dg:2, ...) and
        only that
# ordinal enters the dedup key, so neither the value nor the
        digest is
# printed, traced, logged, written, or emitted. Bash-3.2-safe:
        plain
# indexed arrays + linear search, no associative arrays.
```

```
_cma_quota_group_accounts() {
  local pdir; pdir="$(cma_providers_dir)"
  [[ -d "$pdir" ]] || return 0
  compgen -G "$pdir"/*.env >/dev/null 2>&1 || return 0

  local endpoints_file="${CMA_QUOTA_ENDPOINTS_FILE:-${LIB_DIR:-$
        {SCRIPTS_DIR:-}}/providers/quota-endpoints.json}"
  local f pid base keyvar dedup_key digest ordinal _xt _i _j
  local keysf="${CMA_KEYS_FILE:-$HOME/api_keys.sh}"

  # _hk/_ho: per-call keyvar -> ordinal memo (bash-3.2: parallel
        arrays), so
  # the keys file is sourced once per distinct keyvar, not once
        per .env.
  # _dg: distinct digests seen; a digest's ordinal is its 1-based
        index.

        # None of these is ever printed; _dg is touched only with
        xtrace off.
  local -a _dk=() _db=() _dp=() _hk=() _ho=() _dg=()

  # xtrace stays OFF for the entire grouping loop (hash, ordinal
        map, and
  # dedup-key comparison) and is restored only after the loop
        ends.
  _xt=0; case $- in *x*) _xt=1; set +x ;; esac
  for f in "$pdir"/*.env; do
    [[ -f "$f" ]] || continue
    # shellcheck disable=SC1090
    pid="$( ( unset CMA_PROVIDER_ID; set +e; . "$f" >/dev/null
        2>&1; printf '%s' "${CMA_PROVIDER_ID:-}" ) )"
    base="$( ( unset CMA_PROVIDER_BASE_URL; set +e; . "$f" >/dev/
        null 2>&1; printf '%s' "${CMA_PROVIDER_BASE_URL:-}" ) )"
    keyvar="$( ( unset CMA_PROVIDER_KEYVAR; set +e; . "$f" >/dev/
        null 2>&1; printf '%s' "${CMA_PROVIDER_KEYVAR:-}" ) )"
    [[ -n "$pid" ]] || continue

    # Dedup on a sha256 DIGEST of the secret VALUE (operator
        decision
    # "merge by key value"): two differently named variables
        holding the

        # same key are one real account. The value is resolved the
        way the
    # launcher resolves it (keys file sourced, then indirect
        expansion) and
    # hashed INSIDE a subshell; it is piped to the hasher via the
        printf
    # builtin, so it never reaches argv, a file, or any log. The
        digest is
    # mapped at once to an opaque ordinal and cleared; only the
        ordinal
    # enters the dedup key. An empty/unreadable value, an invalid
        keyvar
```

```
    # name, or no hasher gives no ordinal -> per-pid key (never
        merges).
    ordinal=""
    if [[ "$keyvar" == "_CMA_KIMICODE_OAUTH_" ]]; then
      # OAuth sentinel: one subscription token behind every such
        alias.
      ordinal="kv:${keyvar}"
    elif [[ "$keyvar" =~ ^[A-Za-z_][A-Za-z0-9_]*$ ]]; then
      for (( _i = 0; _i < ${#_hk[@]}; _i++ )); do
        [[ "${_hk[$_i]}" == "$keyvar" ]] && { ordinal="$
        {_ho[$_i]}"; break; }
      done
      if (( _i >= ${#_hk[@]} )); then
        digest="$( (
          set +e +u +x
          # shellcheck disable=SC1090
          [[ -f "$keysf" ]] && { set -a; . "$keysf" >/dev/null
        2>&1; set +a; }
          _v="${!keyvar:-}"
          [[ -n "$_v" ]] || exit 0
          if command -v sha256sum >/dev/null 2>&1; then
            printf '%s' "$_v" | sha256sum 2>/dev/null
          elif command -v shasum >/dev/null 2>&1; then
            printf '%s' "$_v" | shasum -a 256 2>/dev/null
          elif command -v python3 >/dev/null 2>&1; then
            printf '%s' "$_v" | python3 -c 'import
        hashlib,sys;print(hashlib.sha256(sys.stdin.buffer.read()).hexdigest())'
        2>/dev/null
          fi
        ) 2>/dev/null | awk 'NR==1{print $1}' )"
        if [[ "$digest" =~ ^[0-9a-f]{64}$ ]]; then
          for (( _j = 0; _j < ${#_dg[@]}; _j++ )); do
            [[ "${_dg[$_j]}" == "$digest" ]] && break
          done
          (( _j >= ${#_dg[@]} )) && _dg+=("$digest")
          ordinal="dg:$(( _j + 1 ))"
        fi
        digest=""
        _hk+=("$keyvar"); _ho+=("$ordinal")
      fi
    fi

    if [[ -n "$ordinal" ]]; then
      dedup_key="${ordinal}|${base}"
    else
      dedup_key="__nokey__|${pid}"
    fi

    local _found=0 _i
    for (( _i = 0; _i < ${#_dk[@]}; _i++ )); do
      if [[ "${_dk[$_i]}" == "$dedup_key" ]]; then
        _dp[$_i]+=" $pid"
        _found=1
```

```
      break
    fi
  done
  if (( ! _found )); then
    _dk+=("$dedup_key")
    _db+=("$base")
    _dp+=("$pid")
  fi
done
_dg=(); digest=""
(( _xt )) && set -x

local group_idx member_pid names_json spec_present rep_pid _name
local -a all_names
for (( group_idx = 0; group_idx < ${#_dk[@]}; group_idx++ )); do
  base="${_db[$group_idx]}"
  rep_pid=""
  all_names=()
  for member_pid in ${_dp[$group_idx]}; do
    if [[ -f "${ALIAS_FILE:-}" ]]; then
      while IFS= read -r _name; do
        [[ -n "$_name" ]] || continue
        all_names+=("$_name")
      done < <(
        grep -E "^alias [a-zA-Z0-9_-]+=\"cma_run_(provider|
      kimi_provider|pi_provider) ${member_pid}\"\$"
      "$ALIAS_FILE" 2>/dev/null \
          | sed -E 's/^alias ([a-zA-Z0-9_-]+)=.*/\1/'
      )
    fi
    # Representative: the LAST spec-bearing member in glob
      order; with none, the first member.
    [[ -z "$rep_pid" ]] && rep_pid="$member_pid"
    if [[ -f "$endpoints_file" ]] && jq -e --arg id
      "$member_pid" 'has($id)' "$endpoints_file" >/dev/null
      2>&1; then
      rep_pid="$member_pid"
    fi
  done

  if (( ${#all_names[@]} > 0 )); then
    names_json="$(printf '%s\n' "${all_names[@]}" | jq -R . |
      jq -s .)"
  else
    names_json="[]"
  fi
  spec_present="false"
  if [[ -f "$endpoints_file" ]] && jq -e --arg id "$rep_pid"
      'has($id)' "$endpoints_file" >/dev/null 2>&1; then
    spec_present="true"
  fi
```

```
    jq -nc --arg pid "$rep_pid" --arg base "$base" --argjson
        names "$names_json" --argjson present "$spec_present" \
      '{provider_id: $pid, alias_names: $names, base_url: $base,
        endpoint_spec_present: $present}'
  done
}

# _cma_quota_list_native_accounts: one JSON object per line, one
      per
# native account slot (data-model.md §3). Every slot is
      independently
# real -- unlike Provider Accounts, these are NEVER de-duplicated.
# Reuses cma_detect_accounts / cma_detect_kimi_accounts verbatim
      rather
# than re-deriving account discovery.
_cma_quota_list_native_accounts() {
  local d name account_id tier auth_state

  while IFS= read -r d; do
    [[ -n "$d" ]] || continue
    name="$(basename "$d")"
    account_id="${name#"${ACCOUNT_PREFIX:-.claude-}"}"
    # Guard against set -e: a missing/unreadable .claude.json (a
        valid,
    # documented account state -- cma_detect_accounts explicitly
        counts
    # empty, never-launched account dirs) makes jq exit non-zero,
        which
    # would otherwise abort this whole function under set -euo
        pipefail.
    tier="$(jq -r '.oauthAccount.organizationRateLimitTier //
        empty' "$d/.claude.json" 2>/dev/null)" || tier=""

    # auth_state: derived ONLY from refreshTokenExpiresAt, NEVER
        from
    # expiresAt (the access token, which expires routinely and
    # refreshes silently -- using it would misreport every healthy
    # account as expired). Missing credentials file entirely ->
        not
    # signed in, distinct from signed-in-but-expired (T038-
        independent-
    # review finding C1).
    auth_state="ok"
    if [[ ! -f "$d/.credentials.json" ]]; then
      auth_state="not_signed_in"
    else
      local refresh_exp now_ms
      refresh_exp="$(jq -r
        '.claudeAiOauth.refreshTokenExpiresAt // empty'
        "$d/.credentials.json" 2>/dev/null)" || refresh_exp=""

        # Canonical integers only: a leading-zero string ("0999")
        is not a
      # canonical number, so it is treated as unparseable (stays
        "ok")
```

```
    # and never reaches arithmetic, where it would be read as
      octal.
    if [[ "$refresh_exp" =~ ^(0|[1-9][0-9]*)$ ]]; then
      now_ms=$(( $(date +%s) * 1000 ))
      # 10# forces decimal as defence in depth.
      (( 10#$refresh_exp < now_ms )) &&
      auth_state="session_expired"
    fi
    # A non-numeric/missing refreshTokenExpiresAt with a
      credentials
    # file present stays "ok" -- never guess a failure from an
    # unparseable field.
  fi

  if [[ -n "$tier" ]]; then
    jq -nc --arg id "$account_id" --arg tier "$tier" --arg auth
      "$auth_state" \
      '{account_id: $id, family: "claude", plan_tier: $tier,
      auth_state: $auth}'
  else
    jq -nc --arg id "$account_id" --arg auth "$auth_state" \
      '{account_id: $id, family: "claude", plan_tier: null,
      auth_state: $auth}'
  fi
done < <(cma_detect_accounts)

while IFS= read -r d; do
  [[ -n "$d" ]] || continue
  name="$(basename "$d")"
  account_id="${name#"${KIMI_ACCOUNT_PREFIX:-.kimi-code-}"}"
  # No confirmed Kimi-family analog to Claude's
  # oauthAccount.organizationRateLimitTier was found. T016's own
  # investigation (see task-16-report.md) inspected config.toml,
  # credentials/*.json, oauth/, workspaces.json, cache/, and
      logs/ in

      # TWO real ~/.kimi-code-* accounts on this host (kimi1,
      kimi2) and
  # found no tier/rate-limit/plan field anywhere in either tree.
  # Honest null, never guessed, per research.md §7.
  #
  # auth_state (operator decision D2): the real credentials
      shape is
  # access_token, expires_at, expires_in, refresh_token, scope,
  # token_type. The session ends ONLY when the refresh_token
      JWT's own
  # `exp` claim has passed. access_token / expires_at are NEVER
      read:

      # access-token expiry is a routine refresh (the server
      answers 401 to
  # the stale access token), not a failure. No credentials file
      ->
```

```
    # not_signed_in. An undecodable token or a non-canonical/non-
        numeric
    # exp -> "ok" (never guess a failure from an unparseable
        field). With
    # several credentials files, session_expired requires EVERY
        one to
    # carry a parseable past exp. The token itself is never
        printed:

        # it stays inside the command substitution and reaches
        python3 on
    # stdin, which prints only the integer exp (or nothing).
    auth_state="ok"
    if ! compgen -G "$d/credentials/*.json" >/dev/null 2>&1; then
      auth_state="not_signed_in"
    else
      local cred kimi_exp kimi_now kimi_all_past=1
      kimi_now="$(date +%s)"
      for cred in "$d"/credentials/*.json; do
        kimi_exp="$(
          _rt="$(jq -r '.refresh_token // empty' "$cred" 2>/dev/
        null)" || _rt=""
          [[ -n "$_rt" ]] || exit 0
          printf '%s' "$_rt" | python3 -c '
import sys, json, base64
try:
    parts = sys.stdin.read().strip().split(".")
    seg = parts[1]
    seg += "=" * (-len(seg) % 4)
    exp =
        json.loads(base64.urlsafe_b64decode(seg.encode("ascii")).decode("utf-8"))
    if isinstance(exp, int) and not isinstance(exp, bool):
        print(exp)
except Exception:
    pass
' 2>/dev/null
        )" || kimi_exp=""
        # Canonical integers only, as in the Claude branch; 10#
        forces decimal.
        if [[ "$kimi_exp" =~ ^(0|[1-9][0-9]*)$ ]] && ((
        10#$kimi_exp < kimi_now )); then
          :
        else
          kimi_all_past=0
        fi
      done
      (( kimi_all_past )) && auth_state="session_expired"
    fi
    jq -nc --arg id "$account_id" --arg auth "$auth_state" \
      '{account_id: $id, family: "kimi", plan_tier: null,
        auth_state: $auth}'
  done < <(cma_detect_kimi_accounts)
}
```

```
# --- verification status cache
        -------------------------------------------
# Single source of truth for "is this provider alias usable".
        Holds ONLY
# non-secret metadata: provider id -> {status, model, checked_at,
        failing_layer}.
# status is one of: verified | unverified | failed | pending.
        Consumed by the
# list family (claude-providers list/list-all/list-faulty) and the
        launch-time
# activation gate in cma_run_provider. NO key material ever lands
        here.
cma_status_cache() { echo "$(cma_providers_dir)/status.json"; }

# cma_status_write <id> <status> [<model> [<failing_layer>]]
# Upserts one record. failing_layer is "" for verified/pending.
        Atomic write.
cma_status_write() {
  local id="$1" status="$2" model="${3:-}" layer="${4:-}"
  cma_require jq
  local f; f="$(cma_status_cache)"; mkdir -p "$(dirname "$f")"
  [[ -s "$f" ]] || printf '{}\n' > "$f"
  # checked_at: portable UTC ISO-8601 (GNU + BSD date both accept
        -u +fmt).
  local now; now="$(date -u +%Y-%m-%dT%H:%M:%SZ)"
  local tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
  if jq --arg id "$id" --arg s "$status" --arg m "$model" \
        --arg l "$layer" --arg t "$now" \
        '.[$id] = {status:$s, model:$m, checked_at:$t,
        failing_layer:$l}' \
        "$f" > "$tmp" 2>/dev/null; then
    command mv -f "$tmp" "$f"
  else
    rm -f "$tmp"; cma_warn "could not update status cache $f"
  fi
}

# cma_read_verify_layer <layer-file> -> the layer token the
        VERIFIER declared.
#
# providers-verify.sh publishes the failed layer as a first-class
        token through
# the file named by CMA_VERIFY_LAYER_FILE, in a CLOSED vocabulary
# (providers-verify.sh:70-84):
#
#   existence | tool_call | context | attribution | llmsverifier |
        preconditions
#
# This reader enforces that vocabulary for the FILE path. Anything
        else — a
# missing file, an empty file, an unrecognised token — is never
        returned as-is:
# it falls through to the legacy reason matcher
        (cma_derive_layer_from_reason),
```

```
# which yields `unknown` when the reason identifies no layer
      either. It NEVER
# defaults to `existence`: absence means the layer was NOT
      measured, and naming a
# specific cause instead is the exact defect this replaces
      (§11.4.6, §11.4.201).
# Every persist site in claude-providers.sh (cmd_sync failed +
      unverified,
# cmd_verify failed + unverified) reads the layer file through
      this function.
#
# `unknown` is the CALLER's no-layer-measured value; providers-
      verify.sh never
# writes it (its own "nothing failed" value is the empty string).
#
# FALLBACK VOCABULARY — THE TWO SETS DIVERGE, DELIBERATELY AND
      EXPLICITLY.
# When no legal file token is present the reason matcher below is
      used, and it
# can emit `sentinel`, `route`, `chat`, `chat_http` — NONE of
      which are in the
# closed set above (for a tool-calling reason it emits the closed-
      set
# `tool_call`). That is not an oversight to be normalised away in
      one
# direction: test_sync_failing_layer_attribution.sh asserts the
      LEGACY strings
# and test_failing_layer_attribution.sh asserts the CLOSED set, so
      a
# modern verifier is expected to write the file and every legacy
      caller is
# expected to see the old strings. The divergence is recorded here
      rather than
# hidden, and the two suites pin both halves. Reconciling them
      into one
# vocabulary is a deliberate future change, not a drive-by
      simplification.
cma_read_verify_layer() {
  local f="${1:-}" reason="${2:-}" v=""
  [[ -n "$f" && -s "$f" ]] && v="$(tr -d '[:space:]' < "$f" 2>/
      dev/null || true)"
  case "$v" in
    existence|tool_call|context|attribution|llmsverifier|
      preconditions)
      printf '%s\n' "$v"; return 0 ;;
  esac
  # No file token. That is the LEGACY case, not an absence of
      information: a
  # verifier or stub that predates the file protocol still emits
      its reason on
  # stderr, so fall back to the reason matcher below. Both paths
      are real —
  # test_failing_layer_attribution.sh exercises the file (modern)
      and
  # test_sync_failing_layer_attribution.sh exercises the reason
      (legacy) — and
```

```
  # dropping either one breaks a passing suite (§11.4.120).
  cma_derive_layer_from_reason "$reason"
}

# cma_verify_failing_layer <verifier-stderr-reason> -> legacy
        layer token.
# Merge reconciliation (2026-10-09, feature/006 into main): main's
        cmd_sync
# failure branch keeps this name as a purely defensive `:-`
        default (the layer
# is read through cma_read_verify_layer first, which never returns
        empty);
# feature/006 renamed the body to cma_derive_layer_from_reason.
# Both names stay, one implementation, so neither side's call
        sites break.
cma_verify_failing_layer() { cma_derive_layer_from_reason "$@"; }

# cma_derive_layer_from_reason <verifier-stderr-reason> -> legacy
        layer token.
#
# Kept for verifiers that predate CMA_VERIFY_LAYER_FILE. Its
        vocabulary is the
# LEGACY one (`sentinel`, `route`, `chat`, `chat_http`), which is
        NOT the closed
# set published by providers-verify.sh's emit() doc; it does emit
        the closed-set
# `tool_call` for a tool-calling reason (see the case arm). The
        divergence is
# recorded here deliberately so it is visible rather than silently
        normalised
# in one direction.
cma_derive_layer_from_reason() {
  local reason="${1:-}"
  case "$reason" in
    '')                                     printf 'unknown\n' ;;
    *'is the ccr gateway itself'*)          printf 'route\n' ;;

        # tool_call (NOT tool_calling) - matches providers-
        verify.sh's own

        # documented closed vocabulary exactly (its emit() doc
        comment lists
    # `tool_call` as the canonical token); this function is now
        only the
    # fallback for a verifier that predates the
        CMA_VERIFY_LAYER_FILE

        # authoritative-layer protocol (root-caused 2026-09-17),
        so it must

        # speak the SAME vocabulary as the mechanism it stands in
        for, not a
    # second, independently-drifting one.
    *'tool call'*|*'tool-calling probe'*)   printf
        'tool_call\n' ;;
```

```
    *'VERIFY_OK sentinel missing'*)          printf 'sentinel\n' ;;
    *'context-inadequate'*)                  printf 'context\n' ;;
    *'error body'*)                          printf 'chat\n' ;;
    *'LLMsVerifier did not confirm'*)        printf
        'existence\n' ;;
    *'chat probe HTTP'*)                     printf
        'chat_http\n' ;;
    *)                                       printf 'unknown\n' ;;
  esac
}

# cma_status_read <id> -> status word (pending if absent/
      unreadable).
cma_status_read() {
  local id="$1" f; f="$(cma_status_cache)"
  [[ -s "$f" ]] || { echo pending; return 0; }
  local s; s="$(jq -r --arg id "$id" '.[$id].status // "pending"'
      "$f" 2>/dev/null)"
  [[ -n "$s" && "$s" != "null" ]] && echo "$s" || echo pending
}

# cma_status_all ->
      id<TAB>status<TAB>model<TAB>checked_at<TAB>failing_layer
      per record.
cma_status_all() {
  local f; f="$(cma_status_cache)"
  [[ -s "$f" ]] || return 0
  jq -r 'to_entries[] | [.key, .value.status, (.value.model //
      ""),
       (.value.checked_at // ""), (.value.failing_layer // "")]
      | @tsv' \
     "$f" 2>/dev/null || true
}

# --- verdict freshness
      ------------------------------------------------------
# A verification verdict is a claim about a REMOTE endpoint at ONE
      moment.
# Nothing in this cache ever learns that the endpoint later
      started refusing, so
# a verdict presented with no age reads as present-tense success
      forever. That
# is not hypothetical: `helixllm-gateway` showed STATUS `verified`
      in
# `claude-providers list` while a live probe of that exact
      endpoint answered
# HTTP 401. These three helpers are what let a renderer say how
      old a verdict
# is — and refuse to present an old one as current.
#
# The horizon defaults to the one this toolkit ALREADY uses for
      provider
# metadata (CMA_MODELS_DEV_TTL, 24h) rather than a newly invented
      number: it is
```

```
# the same staleness question, so it gets the same answer.
        Overridable on its
# own (CMA_STATUS_TTL) for a caller that wants a tighter bound.
#
# RESOLVED AT CALL TIME, NOT AT SOURCE TIME — and that is the
        whole point.
# claude-providers.sh sources this file at its line 32 and only
        then defaults
# CMA_MODELS_DEV_TTL in its knobs block at line 37. A top-level
# `: "${CMA_STATUS_TTL:=${CMA_MODELS_DEV_TTL:-86400}}"` here
        therefore runs
# while CMA_MODELS_DEV_TTL is still UNSET, falls through to the
        literal, and
# freezes 86400 in — so the two numbers agreeing was a coincidence
        of two
# identical literals, not an inheritance, and raising
        CMA_MODELS_DEV_TTL moved
# nothing unless it happened to be EXPORTED into the environment.
        Deferring the
# lookup to the one place that needs it makes the inheritance real
        for every
# way the knob can be set, and an explicit CMA_STATUS_TTL still
        wins.

# cma_status_age_seconds <checked_at> -> age in whole seconds, or
        NOTHING when
# the timestamp is absent or unparseable. An empty result means
        UNKNOWN age and
# MUST NOT be rendered as a fresh one (§11.4.6: not knowing when
        something was
# checked is not the same as knowing it was checked recently).
# cma_status_write emits one fixed portable UTC format (%Y-%m-
        %dT%H:%M:%SZ);
# both date dialects are handled because this runs on Linux AND
        macOS (§11.4.81).
cma_status_age_seconds() {
  local ts="${1:-}" _then _now
  [[ -n "$ts" && "$ts" != "null" ]] || return 0
  # The OS dialect cannot change inside one process, so probe it
        once and cache
  # it in a shell global: `list` calls this once per row, and a
        per-call
  # `uname` was one fork per row for an answer that never varies.
  [[ -n "${_CMA_UNAME_S:-}" ]] || _CMA_UNAME_S="$(uname -s)"
  case "$_CMA_UNAME_S" in
    Darwin*) _then="$(date -u -j -f '%Y-%m-%dT%H:%M:%SZ' "$ts" +
        %s 2>/dev/null)" ;;
    *)       _then="$(date -u -d "$ts" +%s 2>/dev/null)" ;;
  esac
  [[ "$_then" =~ ^[0-9]+$ ]] || return 0
  _now="$(date -u +%s)"
  # A timestamp from the future is clock skew, not an age: clamp
        to 0 rather
  # than emit a negative, which would compare as "fresh"
        everywhere downstream.
```

```
  (( _then > _now )) && { printf '0'; return 0; }
  printf '%s' "$(( _now - _then ))"
}

# --- age -> rendering, split so ONE measurement can serve BOTH
       answers -------
# The `_s` pair takes an ALREADY-MEASURED age in seconds (empty =
       unknown); the
# timestamp-taking pair below is the same behaviour with the
       measurement folded
# in, kept because it is the friendlier API for a one-shot caller.
#
# WHY THE SPLIT EXISTS. A renderer needs both the human string and
       the stale
# verdict for the same row, and calling both timestamp-taking
       helpers measured
# the SAME timestamp twice — each measurement forking `date` (and,
       before the
# cache above, `uname`). Measured here on a 40-row listing, 3 runs
       each:
# ~4.72 s before, ~2.83 s after, against ~1.64 s for the same
       listing with no
# CHECKED column at all — so this removes about 61% of the
       column's cost, and
# what remains is the one timestamp parse per row the column
       actually needs.
# Semantics are untouched: both pairs are pure functions of the
       age, and
# "unknown" is still never "fresh".

# cma_status_age_human_s <age_seconds|""> -> "42s" | "9m" | "5h" |
       "3d" | "?"
# "?" is the honest rendering of an age we do not know.
cma_status_age_human_s() {
  local _age="${1:-}"
  [[ -n "$_age" ]] || { printf '?'; return 0; }
  if   (( _age < 60 ));    then printf '%ds' "$_age"
  elif (( _age < 3600 ));  then printf '%dm' "$(( _age / 60 ))"
  elif (( _age < 86400 )); then printf '%dh' "$(( _age / 3600 ))"
  else                          printf '%dd' "$(( _age / 86400 ))"
  fi
}

# cma_status_is_stale_s <age_seconds|""> -> 0 when PROVABLY older
       than
# CMA_STATUS_TTL. An unknown age is NOT reported stale — it is
       unknown, and the
# caller renders "?" for it. Only a MEASURED age past the horizon
       earns the claim.
cma_status_is_stale_s() {
  local _age="${1:-}"
  [[ -n "$_age" ]] || return 1
  local _ttl="${CMA_STATUS_TTL:-${CMA_MODELS_DEV_TTL:-86400}}"
  [[ "$_ttl" =~ ^[0-9]+$ ]] || _ttl=86400
```

```
  (( _age >= _ttl ))
}

# cma_status_age_human <checked_at> -> the same rendering,
        measuring for you.
cma_status_age_human() { cma_status_age_human_s "$
        (cma_status_age_seconds "${1:-}")"; }

# cma_status_is_stale <checked_at> -> the same verdict, measuring
        for you.
cma_status_is_stale() { cma_status_is_stale_s "$
        (cma_status_age_seconds "${1:-}")"; }

# Union daemon/roster.json files into one registry. workers are
        merged by id
# with the newer updatedAt winning per worker; proto and
        supervisorPid come
# from the newest roster; top-level updatedAt is the max. Used by
# claude-unify.sh (merge_daemon_roster) and
        cma_migrate_daemon_dirs_once.
# Usage: cma_union_rosters OUTFILE roster1.json [roster2.json ...]
cma_union_rosters() {
  local out="$1"; shift
  command -v jq >/dev/null 2>&1 || return 1
  (( $# >= 1 )) || return 1
  local tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
  if jq -s '
    def newer($a; $b): if (($a.updatedAt // 0) >= ($b.updatedAt //
        0)) then $a else $b end;
    ([.[] | {u: (.updatedAt // 0), p: (.proto // 1), s:
        (.supervisorPid // null), w: (.workers // {})}])
    | (map(.u) | max // 0) as $maxu
    | (sort_by(.u) | last) as $newest
    | (reduce .[] as $r ({}; . as $acc
        | reduce ($r.w | to_entries[]) as $e ($acc;
            if ($acc[$e.key] == null) then . + {($e.key):
        $e.value}
            else . + {($e.key): newer($acc[$e.key]; $e.value)}
        end))) as $workers
    | {proto: $newest.p, supervisorPid: $newest.s, updatedAt:
        $maxu, workers: $workers}
  ' "$@" >| "$tmp" 2>/dev/null && [[ -s "$tmp" ]]; then
    command mv -f "$tmp" "$out"
    return 0
  fi
  rm -f "$tmp"
  return 1
}

# One-time migration for pre-v1.17.0 LOCAL daemon/jobs dirs under
        provider
# dirs: their contents (including background-agent rosters) must
        not be
```

```
# stranded when daemon/jobs become shared items. Merges every real
      provider
# daemon/jobs dir into $SHARED_DIR (roster.json excluded), backs
      it up,
# replaces it with the shared symlink, then union-merges every
      collected
# roster.json (incl. the shared one) with cma_union_rosters.
      Idempotent via a
# marker file; cma_link_shared_items handles all NEW provider
      dirs.
cma_migrate_daemon_dirs_once() {
  command -v rsync >/dev/null 2>&1 || return 0
  local marker="$SHARED_DIR/.daemon-migration-done"
  [[ -e "$marker" ]] && return 0
  local d item tgt roster_tmp=""
  for d in "$HOME/${CMA_PROVIDER_DIR_PREFIX:-.claude-prov-}"*/; do
    [[ -d "$d" ]] || continue
    for item in daemon jobs; do
      tgt="$d$item"
      [[ -d "$tgt" && ! -L "$tgt" ]] || continue
      mkdir -p "$SHARED_DIR/$item"
      rsync -a --exclude 'roster.json' "$tgt/" "$SHARED_DIR/
        $item/" 2>/dev/null || true
      if [[ -f "$tgt/roster.json" ]]; then
        # Stash roster CONTENT before the dir moves — collecting
        paths and
        # unioning afterwards would read the just-moved (missing)
        files.
        [[ -z "$roster_tmp" ]] && roster_tmp="$(mktemp -d "$
        {TMPDIR:-/tmp}/cma.XXXXXX")"
        cp "$tgt/roster.json" "$roster_tmp/$(printf '%s' "$d" |
        md5sum | cut -c1-12).json"
      fi
      # Same backup convention as unify's backup_and_remove
        (defined there,
      # not in lib.sh): rename to <path>.preunify.<timestamp> —
        recoverable.
      command mv -f "$tgt" "${tgt}.preunify.$(date +%Y%m%d%H%M%S)"
      ln -s "$SHARED_DIR/$item" "$tgt"
    done
  done
  local srcs=()
  [[ -f "$SHARED_DIR/daemon/roster.json" && ! -L "$SHARED_DIR/
        daemon/roster.json" ]] && \
    srcs+=("$SHARED_DIR/daemon/roster.json")
  [[ -n "$roster_tmp" ]] && srcs+=("$roster_tmp"/*.json)
  if (( ${#srcs[@]} )); then
    cma_union_rosters "$SHARED_DIR/daemon/roster.json" "$
        {srcs[@]}" || \
      cma_warn "daemon roster union failed during migration —
        last-wins file kept"
  fi
  [[ -n "$roster_tmp" ]] && rm -rf "$roster_tmp"
```

```
  # $SHARED_DIR may not exist yet (fresh host / first sync before any shared
  # item was linked). claude-providers.sh runs under `set -e`, so an unguarded
  # `: > $marker` onto a missing directory ABORTS the whole cmd_sync (captured
  # live: "line 1166: …/.claude-shared/.daemon-migration-done: No such file or
  # directory" -> sync exit 1, zero providers registered). The marker is only
  # a skip-optimization — the migration loop itself is idempotent (symlinked
  # dirs are skipped) — so a failed marker write must never kill the sync.
  mkdir -p "$SHARED_DIR" 2>/dev/null || true
  : > "$marker" 2>/dev/null || true
}

# Symlink every shared item into a config dir (account or provider), creating
# empty placeholders in $SHARED_DIR for any item that doesn't exist yet.
# Idempotent: skips items already present in the target.
cma_link_shared_items() {
  local cdir="$1" item src tgt
  mkdir -p "$SHARED_DIR" "$cdir"
  for item in "${CMA_SHARED_ITEMS[@]}"; do
    src="$SHARED_DIR/$item"; tgt="$cdir/$item"
    if [[ ! -e "$src" ]]; then
      case "$item" in
        *.json|*.jsonl|*.md) : > "$src" ;;
        *) mkdir -p "$src" ;;
      esac
    fi
    [[ -e "$tgt" || -L "$tgt" ]] || ln -s "$src" "$tgt"
  done

  # §11.4 own-settings: settings.json is NOT symlinked — give this dir its OWN copy.
  cma_own_settings_seed "$cdir"
}

# List all toolkit-managed config dirs (native accounts + providers). Used to
# fan out per-dir OWN settings.json enabledPlugins-sync.
cma_all_config_dirs() {
  local d
  for d in "$HOME"/.claude-claude* "$HOME"/.claude-prov-*; do
    [[ -d "$d" ]] && printf '%s\n' "$d"
  done
}

# Give a config dir its OWN settings.json (§11.4 own-settings). If it is a symlink
```

```
# (legacy shared layout) or absent, seed a REAL copy from the
      shared template so
# it inherits enabledPlugins + theme. If already a real file,
      additively merge the
# template's enabledPlugins in (own entries win — never clobber
      per-alias
# overrides). The shared template $SHARED_DIR/settings.json
      remains the single
# source of the always-on plugin set.
cma_own_settings_seed() {
  # NOTE: separate `local`s — a single `local a="$1" b="$a/x"`
      expands $a before
  # it is assigned, which aborts under `set -u` ("a: unbound
      variable").
  local cdir="${1:-}"
  [ -n "$cdir" ] || return 0
  local own="$cdir/settings.json"
  local tmpl="${SHARED_DIR:-$HOME/.claude-shared}/settings.json"
  local tmp=""
  command -v jq >/dev/null 2>&1 || return 0
  [[ -s "$tmpl" ]] || printf '{}\n' > "$tmpl"
  if [[ -L "$own" || ! -e "$own" ]]; then
    rm -f "$own" 2>/dev/null
    cp "$tmpl" "$own" 2>/dev/null || printf '{}\n' > "$own"
    return 0
  fi
  tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
  if jq -s '.[0] as $own | .[1] as $t
            | $own | .enabledPlugins = (($t.enabledPlugins // {})
        + ($own.enabledPlugins // {}))' \
        "$own" "$tmpl" > "$tmp" 2>/dev/null && jq -e . "$tmp" >/
        dev/null 2>&1; then
    command mv -f "$tmp" "$own"
  else rm -f "$tmp"; fi
}

# Force-enable the always-on plugins in the shared settings.json
      enabledPlugins
# map (additive union — never removes a user's existing entries).
      Each arg is a
# plugin key as it appears in enabledPlugins (e.g.
      "superpowers@anthropics").
cma_enable_plugins() {
  cma_require jq
  local settings="$SHARED_DIR/settings.json" tmp
  mkdir -p "$SHARED_DIR"
  [[ -s "$settings" ]] || printf '{}\n' > "$settings"
  tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
  local args=() p i=0

      # Use a dedicated counter for the jq --arg names: each
      iteration appends THREE
  # elements (--arg, "pN", value), so deriving the index from $
      {#args[@]} drifts
```

```
  # (it produced p0,p1,p3,p4 for 4 plugins → $p2 undefined → jq
        failed silently

        # → no plugins enabled). The counter matches the $pN refs
        in the prog below.
  for p in "$@"; do args+=(--arg "p$i" "$p"); i=$((i+1)); done
  # Build a jq program that sets each provided key true if absent.
  local prog='.enabledPlugins //= {}'
  local i=0
  for p in "$@"; do
    prog+=" | .enabledPlugins[\$p$i] //= true"; i=$((i+1))
  done
  # ${args[@]+...} guards an empty array under set -u on bash 3.2
        (reachable
  # via CMA_ALWAYS_ON_PLUGINS="" from non-re-exec'd claude-
        providers.sh).
  if jq ${args[@]+"${args[@]}"} "$prog" "$settings" > "$tmp" 2>/
        dev/null; then
    command mv -f "$tmp" "$settings"
  else
    rm -f "$tmp"; cma_warn "could not update enabledPlugins in
        $settings"
  fi
  # Fan the always-on plugin set out into every managed config
        dir's OWN
  # settings.json (settings.json is no longer a shared symlink —
        §11.4
  # own-settings) so enabling a plugin still reaches every alias/
        provider.
  local _cd
  while IFS= read -r _cd; do [[ -n "$_cd" ]] &&
        cma_own_settings_seed "$_cd"; done <
        <(cma_all_config_dirs)
}

# Write the non-secret per-provider env file consumed by
        cma_run_provider.
# Args: id keyvar transport base_url model fast_model config_dir
        [context_limit [max_output]]
# context_limit and max_output are optional trailing args (default
        empty).
# cma_run_provider consumes both catalog limits to avoid the 400
        "exceeded
# model token limit" error: CMA_PROVIDER_CONTEXT_LIMIT ->
        CLAUDE_CODE_AUTO_COMPACT_WINDOW
# (INPUT: compact before the prompt overshoots the provider's
        window) and
# CMA_PROVIDER_MAX_OUTPUT -> CLAUDE_CODE_MAX_OUTPUT_TOKENS (OUTPUT
        cap).
cma_provider_write_env() {
  local id="$1" keyvar="$2" transport="$3" base="$4" model="$5"
        fast="$6" cdir="$7"
  local context_limit="${8:-}" max_output="${9:-}"
        alias_name="${10:-}"
```

```
# Normalize the literal "null" (from a missing JSON field) to
      empty so it

      # never leaks into the wrapper as a bogus value.
      transport+model were missed
# originally — a null strong_model/transport wrote
      CMA_PROVIDER_MODEL='null'
# (provider launches with a bogus model). Normalize every field
      for symmetry.
#
# keyvar was ALSO missed (independent-review follow-up, rename-
      path

      # TSV-null-field-corruption fix): cmd_migrate_names now
      defaults a
# genuinely-empty CMA_PROVIDER_KEYVAR to the literal "null" (to
      survive the
# same tab-collapse this comment block already describes), and
      without
# this line that literal string would ship verbatim as
# CMA_PROVIDER_KEYVAR='null' in the migrated env file -- a real
      but
# distinct brokenness from the silent shift it was meant to
      prevent.
[[ "$keyvar" == "null" ]] && keyvar=""
[[ "$transport" == "null" ]] && transport=""
[[ "$base" == "null" ]] && base=""
[[ "$model" == "null" ]] && model=""
[[ "$fast" == "null" ]] && fast=""
[[ "$context_limit" == "null" ]] && context_limit=""
[[ "$max_output" == "null" ]] && max_output=""
[[ "$alias_name" == "null" ]] && alias_name=""
local pdir; pdir="$(cma_providers_dir)"; mkdir -p "$pdir"

      # Preserve the opt-in per-provider TRIM knob
      (CMA_PROVIDER_TRIM) across
# regeneration. It is NOT in the models.dev catalog nor the
      alias manifest, so
# neither caller passes it — it is set on the env file itself.
      Because this
# generator OVERWRITES the whole file (cat > below), an `add`/
      re-add would
# otherwise DROP it. Read the current on-disk value BEFORE the
      cat truncates
# the file and re-emit it below (same existing-value-from-env
      read as cmd_sync).
# `unset CMA_PROVIDER_TRIM` first so only the file's value is
      preserved — never
# a value that happens to be exported in the caller's shell.
local trim=""
if [[ -f "$pdir/$id.env" ]]; then
  # shellcheck disable=SC1090,SC1091
  trim="$( ( unset CMA_PROVIDER_TRIM; set -a; . "$pdir/$id.env"
      >/dev/null 2>&1; set +a; printf '%s' "$
      {CMA_PROVIDER_TRIM:-}" ) )"
```

```
  fi
  [[ "$trim" == "null" ]] && trim=""
  # Values are single-quoted (with embedded-quote escaping) so
        sourcing the file
  # in the user's shell is safe regardless of characters in URLs/
        model ids.
  # POSIX single-quote escaping: replace each ' with '\'' via a
        loop.
  # Portable across all bash versions — avoids ${var/pattern/
        replacement} with
  # complex escape sequences that break on bash 3.2 and 5.3.
  _cma_q() {
    local _r="" _rem="$1"
    while true; do
      case "$_rem" in *\'*)
        _r="${_r}${_rem%%\'*}'\\''"; _rem="${_rem#*\'}" ;;
        *) _r="${_r}${_rem}"; break ;;
      esac
    done
    printf "'%s'" "$_r"
  }
  cat > "$pdir/$id.env" <<EOF
# generated by claude-providers — non-secret. Do not edit by hand.
# Secrets are NEVER stored here; the key is read from the keys
        file at launch.
CMA_PROVIDER_ID=$(_cma_q "$id")
CMA_PROVIDER_KEYVAR=$(_cma_q "$keyvar")
CMA_PROVIDER_TRANSPORT=$(_cma_q "$transport")
CMA_PROVIDER_BASE_URL=$(_cma_q "$base")
CMA_PROVIDER_MODEL=$(_cma_q "$model")
CMA_PROVIDER_FAST_MODEL=$(_cma_q "$fast")
CMA_PROVIDER_CONFIG_DIR=$(_cma_q "$cdir")
# Context-window limits from the models.dev catalog for the
        selected strong model.
# CMA_PROVIDER_CONTEXT_LIMIT: input context window (tokens); empty
        = unknown.
#   -> exported as CLAUDE_CODE_AUTO_COMPACT_WINDOW (input-side
        guard).
# CMA_PROVIDER_MAX_OUTPUT:    maximum output tokens; empty =
        unknown.
#   -> exported as CLAUDE_CODE_MAX_OUTPUT_TOKENS (output-side
        guard).
CMA_PROVIDER_CONTEXT_LIMIT=$(_cma_q "$context_limit")
CMA_PROVIDER_MAX_OUTPUT=$(_cma_q "$max_output")
# Alias name for this provider (used by 'list --refresh-aliases'
        to rebuild the
# alias shell line with NO network — the session hook's fast
        path). Empty is OK;
# refresh falls back to the provider id as the alias name.
CMA_PROVIDER_ALIAS=$(_cma_q "$alias_name")
EOF
  # Re-emit the preserved TRIM knob, ONLY when set — a provider
        without it must
```

```
  # stay without it (no spurious empty line).
        CMA_PROVIDER_TRIM=bare makes
  # cma_run_provider launch minimal (--bare, fresh session, no
        auto-resume).
  if [[ -n "$trim" ]]; then
    {
      printf '# Opt-in per-provider TRIM knob (preserved across
        regeneration).\n'
      printf '# CMA_PROVIDER_TRIM=bare launches minimal: --bare +
        fresh session (no auto-resume).\n'
      printf 'CMA_PROVIDER_TRIM=%s\n' "$(_cma_q "$trim")"
    } >> "$pdir/$id.env"
  fi
  unset -f _cma_q
}

# Write (or refresh) a provider alias: alias
        <name>="cma_run_provider <id>".
cma_provider_write_alias() {
  local alias_name="$1" id="$2"
  cma_validate_alias "$alias_name"
  # The provider id is interpolated into the alias body and re-
        parsed when the
  # alias is invoked. Provider ids are always [A-Za-z0-9._-];
        reject anything
  # else so a hostile catalog/--id value can't inject shell
        commands.
  case "$id" in
    ''|*[!A-Za-z0-9._-]*)
      cma_warn "refusing to write alias '$alias_name': unsafe
        provider id"
      return 1 ;;
  esac

        # One delta, one render, one rename. This used to
        bootstrap-only (never

        # calling cma_ensure_alias_file on an existing file)
        because the old
  # drop/re-append migrations could reposition cma_run_provider
        relative to the
  # alias lines, making `--refresh-aliases` non-idempotent (see
        test_providers.sh

        # "--refresh-aliases is idempotent"). The renderer emits a
        fixed canonical
  # order, so position is now invariant and that hazard is gone —
        which is why

        # this path can safely render the managed block like every
        other writer.
  cma_alias_commit "$alias_name" \
    "$(printf 'alias %s="cma_run_provider %s"' "$alias_name"
        "$id")" keep
}
```

```
# Install (idempotently) the provider session-refresh hook into
      $ALIAS_FILE. On
# every interactive shell start the hook re-writes provider
      aliases from cache
# (NO network) and, when the status cache is older than
      CMA_PROVIDERS_SYNC_TTL
# (default 24h), kicks a detached full sync (§11.4.89 background —
      never blocks
# the shell). Bracketed by markers so a re-install replaces the
      block atomically
# (no duplication across re-installs).
cma_install_session_hook() {
  cma_ensure_alias_file
  # The hook text itself lives in _cma_emit_session_hook (next to
      the other
  # emitters); "install" tells the renderer to emit the current
      version instead
  # of carrying the existing block over.
  cma_alias_commit "" "" install
}

# ============================================================================
# Kimi family layer (v1.27.0). The Kimi Code CLI is a first-class
      sibling of
# Claude Code. The family model is an orthogonal axis to the
      provider backend:
# the provider engine stays shared, and each family supplies its
      agent binary,
# home env var, account prefix, user-scope root, and launcher
      functions.
#
#   |                | Claude family       | Kimi family
#   | agent binary   | claude              | kimi
#   | home env var   | CLAUDE_CONFIG_DIR   | KIMI_CODE_HOME
#   | account prefix | .claude-            | .kimi-code-
#   | user-scope root| ~/.claude (excluded)| ~/.kimi-code
      (excluded)
#   | account aliases| claude1…N           | kimi1…N
#   | account launcher| cma_run            | cma_run_kimi
#   | provider launcher| cma_run_provider  | cma_run_kimi_provider
#   | shared store   | $SHARED_DIR/**      | $SHARED_DIR/kimi/**
#
# Namespace contract (the invariant): claudeN/kimiN are native
      accounts; <id>
# (no prefix) is ALWAYS Claude Code over that backend; kimi-<id>
      is ALWAYS Kimi
# Code over the SAME backend; kc-<id> is Claude Code over a Kimi-
      native backend
# (legacy rename). kimiN account aliases must never be named kimi-
      */kc-* (those
# are reserved provider namespaces), and kc-* ids never get a
      kimi-kc-* twin.
# ============================================================================
KIMI_ACCOUNT_PREFIX=".kimi-code-"
```

```
KIMI_PROVIDER_PREFIX=".kimi-prov-"
KIMI_SHARED_SUBDIR="kimi"

cma_kimi_home()          { printf '%s\n' "$HOME/.kimi-code"; }
cma_kimi_account_home()  { printf '%s\n' "$HOME/
        $KIMI_ACCOUNT_PREFIX$1"; }
cma_kimi_provider_home() { printf '%s\n' "$HOME/
        $KIMI_PROVIDER_PREFIX$1"; }

CMA_KIMI_SHARED_ITEMS=(AGENTS.md plugins skills sessions
        session_index.jsonl)

# Resolve the Kimi Code binary for the kimi wrappers. Prefer an
        explicit
# KIMI_BIN, then the per-home bundled bin (installed by
        install.sh / logic), then
# ~/.local/bin, then PATH. Mirror of cma_resolve_claude_bin.
cma_resolve_kimi_bin() {
  if [ -n "${KIMI_BIN:-}" ]; then printf '%s\n' "$KIMI_BIN";
        return 0; fi
  if [ -x "$HOME/.kimi-code/bin/kimi" ]; then printf '%s\n'
        "$HOME/.kimi-code/bin/kimi"; return 0; fi
  if [ -x "$HOME/.local/bin/kimi" ]; then printf '%s\n'
        "$HOME/.local/bin/kimi"; return 0; fi
  local c; if c="$(command -v kimi 2>/dev/null)"; then printf
        '%s\n' "$c"; return 0; fi
  printf '%s\n' "$HOME/.local/bin/kimi"   # fallback (created by
        install/symlink)
}

# Marker-based detection mirror of cma_detect_accounts for the
        Kimi family.
# Matches ${KIMI_ACCOUNT_PREFIX}* (~/.kimi-code-*). The user-scope
        root
# ~/.kimi-code (no trailing hyphen) and the provider homes
        ~/.kimi-prov-*
# never match the glob structurally. Skips *-shared, *.lock,
        *.removed.*,
# *.preunify.*, and non-empty dirs lacking any kimi marker.
cma_detect_kimi_accounts() {
  local d prefix="${KIMI_ACCOUNT_PREFIX:-.kimi-code-}"
  while IFS= read -r d; do
    [[ "$d" == *"-shared" ]] && continue
    [[ "$(basename "$d")" == *.lock ]] && continue
    [[ "$(basename "$d")" == *.removed.* ]] && continue
    [[ "$(basename "$d")" == *.preunify.* ]] && continue

        # Empty dirs always count (a brand-new account before any
        kimi run).
    if [[ -z "$(ls -A "$d" 2>/dev/null)" ]]; then echo "$d";
        continue; fi
    # Non-empty: must look like a Kimi account (at least one tell-
        tale
    # file/dir). Filters out dirs that merely match the `.kimi-
        code-*` prefix
```

```
    # but belong to other tools.
    if [[ -f "$d/config.toml" || -d "$d/credentials" || -d "$d/
        sessions" \
       || -f "$d/session_index.jsonl" ]]; then
      echo "$d"
    fi
  done < <(find "$HOME" -maxdepth 1 -type d -name "${prefix}*" 2>/
        dev/null | sort)
}

# Read all aliases of the form `alias name="KIMI_CODE_HOME=...
        cma_run_kimi"`
# from $ALIAS_FILE and print their names (one per line).
cma_existing_kimi_aliases() {
  [[ -f "$ALIAS_FILE" ]] || return 0
  grep '^alias[[:space:]][^=]*="KIMI_CODE_HOME=' "$ALIAS_FILE" 2>/
        dev/null \
    | awk -F'[ =]+' '{print $2}' 2>/dev/null || true
}

# Suggest the next free `kimi<N>` alias by scanning current kimi
        aliases.
cma_suggest_kimi_alias() {
  local highest=0 n a
  for a in $(cma_existing_kimi_aliases); do
    if [[ "$a" =~ ^kimi([0-9]+)$ ]]; then
      n="${BASH_REMATCH[1]}"
      (( n > highest )) && highest="$n"
    fi
  done
  printf 'kimi%s\n' "$((highest + 1))"
}

# Validate a kimi ACCOUNT alias name: same charset as
        cma_validate_alias, and
# additionally the two provider namespaces `kimi-*` and `kc-*` are
        reserved for
# provider aliases — a kimiN account must never be named into
        either.
cma_validate_kimi_alias() {
  cma_validate_alias "$1"
  case "$1" in
    kimi-*|kc-*)
      cma_die "invalid alias name:
        $1 (reserved provider namespace kimi-*/kc-*)" ;;
  esac
}

# Symlink every kimi shared item into a kimi account dir, creating
        empty
# placeholders under $SHARED_DIR/kimi for items that don't exist
        yet.
# Idempotent: skips items already present in the target. Mirror of
```

```
# cma_link_shared_items but into the family-specific $SHARED_DIR/
      kimi area.
cma_link_kimi_shared_items() {
  local kdir="$1" item src tgt
  mkdir -p "$SHARED_DIR/$KIMI_SHARED_SUBDIR" "$kdir"
  for item in "${CMA_KIMI_SHARED_ITEMS[@]}"; do
    src="$SHARED_DIR/$KIMI_SHARED_SUBDIR/$item"; tgt="$kdir/$item"
    if [[ ! -e "$src" ]]; then
      case "$item" in
        *.json|*.jsonl|*.md) : > "$src" ;;
        *) mkdir -p "$src" ;;
      esac
    fi
    [[ -e "$tgt" || -L "$tgt" ]] || ln -s "$src" "$tgt"
  done
}

# Add (or refresh) a single kimi ACCOUNT alias in $ALIAS_FILE.
      Idempotent.
# The alias wraps `cma_run_kimi` with a KIMI_CODE_HOME= prefix so
      the account
# resolves its own home, exactly as claudeN aliases carry
      CLAUDE_CONFIG_DIR=.
cma_write_kimi_alias() {
  local alias_name="$1" kdir="$2" _cma_c
  cma_validate_kimi_alias "$alias_name"
  # kdir is interpolated into the alias body and re-parsed by the
      shell when the

      # alias is invoked. Reject shell metacharacters and
      whitespace — same rules as
  # cma_write_alias.
  for _cma_c in '"' '$' '`' \\ ';' '&' '|' '<' '>' '(' ')'; do
    case "$kdir" in *"$_cma_c"*)
      cma_warn "refusing to write alias '$alias_name': unsafe
        config dir"
      return 1 ;;
    esac
  done
  case "$kdir" in *[[:space:]]*)
    cma_warn "refusing to write alias '$alias_name': config dir
        must not contain whitespace"
    return 1 ;;
  esac
  cma_ensure_alias_file
  cma_alias_commit "$alias_name" \
    "$(printf 'alias %s="KIMI_CODE_HOME=%s cma_run_kimi"'
        "$alias_name" "$kdir")" keep
}

# Remove a kimi account alias line. Idempotent.
cma_remove_kimi_alias() {
  local alias_name="$1"
```

```
  [[ -f "$ALIAS_FILE" ]] || return 0
  cma_alias_commit "$alias_name" "" keep
}

# ---- Emitted kimi wrappers
        -------------------------------------------------
# These are emitted into the managed block and eval'd into THIS
        shell from the
# exact bytes the alias file receives (same pattern as the ccr
        guard), so the
# wrapper under test is always the same function a user's shell
        gets.
_cma_emit_cma_run_kimi() {
  cat <<'CMA_KIMI_RUN_EOF'
# Kimi Code account wrapper (kimiN). Resolves the kimi binary,
        scrubs the
# Claude/Anthropic env the Kimi CLI must never inherit, then runs
        kimi.
cma_run_kimi() {
  local _ck_bin _ck_khome
  _ck_bin="${KIMI_BIN:-}"
  if ! command -v "$_ck_bin" >/dev/null 2>&1; then
    if [ -x "$HOME/.kimi-code/bin/kimi" ]; then
        _ck_bin="$HOME/.kimi-code/bin/kimi"
    elif [ -x "$HOME/.local/bin/kimi" ]; then
        _ck_bin="$HOME/.local/bin/kimi"
    elif command -v kimi >/dev/null 2>&1; then _ck_bin="$(command
        -v kimi)"
    fi
  fi
  if ! command -v "$_ck_bin" >/dev/null 2>&1; then
    printf '%s\n' "cma_run_kimi: kimi binary not found (checked \
        $KIMI_BIN, ~/.kimi-code/bin, ~/.local/bin, PATH)" >&2
    return 127
  fi
  # Family isolation: never let a Claude/Anthropic env left over
        from a previous
  # alias leak into the Kimi CLI — base URL, auth token, model
        pins, and the
  # Claude Code token-limit guards are all Claude-family only.
  unset ANTHROPIC_BASE_URL ANTHROPIC_AUTH_TOKEN ANTHROPIC_MODEL
        ANTHROPIC_SMALL_FAST_MODEL
  unset ANTHROPIC_DEFAULT_OPUS_MODEL
        ANTHROPIC_DEFAULT_SONNET_MODEL
        ANTHROPIC_DEFAULT_HAIKU_MODEL
        ANTHROPIC_DEFAULT_FABLE_MODEL
  unset CLAUDE_CODE_MAX_OUTPUT_TOKENS
        CLAUDE_CODE_AUTO_COMPACT_WINDOW
        CLAUDE_CODE_MAX_CONTEXT_TOKENS
  "$_ck_bin" "$@"
}
CMA_KIMI_RUN_EOF
}
eval "$(_cma_emit_cma_run_kimi)"
```

```
_cma_emit_cma_run_kimi_provider() {
  cat <<'CMA_KIMI_PROV_EOF'
# Kimi Code over a verified provider backend (kimi-<id>). Shares
      the SAME
# status.json activation gate as the Claude twin (single shared
      record per id),
# reads default_model/base_url from the rendered config.toml, and
      refuses to
# launch on a missing or stale config. Self-contained: no lib.sh
      helpers.
cma_run_kimi_provider() {
  local _ckf=0 _ckpid _ckhome _ckconf _ckbin _ckdm _ckbase
  if [[ "${1:-}" == "--force" ]]; then _ckf=1; shift; fi
  _ckpid="${1:-}"
  # NOTE: `shift 2>/dev/null` shifts ONE arg, not two — bash
      parses the `2` as
  # an fd redirect. Deliberate: it consumes the id; the next line
      re-checks
  # --force. Do NOT "fix" to `shift 2 || true` — that eats the
      first user arg.
  shift 2>/dev/null || true
  if [[ "${1:-}" == "--force" ]]; then _ckf=1; shift; fi
  if [[ -z "$_ckpid" ]]; then
    printf '%s\n' "usage: cma_run_kimi_provider <id> [--force]
      [kimi args...]" >&2
    return 2
  fi
  # Per-id home is FORCED, never ambient-KIMI_CODE_HOME-honored:
      an exported
  # KIMI_CODE_HOME (a documented Moonshot pattern for switching
      data roots)
  # would point this wrapper at the WRONG config.toml/
      default_model while it
  # launches against ~/.kimi-prov-<id> — a silently wrong-backend
      launch. Same
  # isolation contract as cma_run_provider, which unconditionally
      exports
  # CLAUDE_CONFIG_DIR (spec §6.3). Self-contained body: never
      sources lib.sh,
  # so the literal path stands in for cma_kimi_provider_home.
  _ckhome="$HOME/.kimi-prov-$_ckpid"
  _ckconf="$_ckhome/config.toml"
  _ckbin="${KIMI_BIN:-}"
  if ! command -v "$_ckbin" >/dev/null 2>&1; then
    if [ -x "$HOME/.kimi-code/bin/kimi" ]; then
      _ckbin="$HOME/.kimi-code/bin/kimi"
    elif [ -x "$HOME/.local/bin/kimi" ]; then
      _ckbin="$HOME/.local/bin/kimi"
    elif command -v kimi >/dev/null 2>&1; then _ckbin="$(command
      -v kimi)"
    fi
  fi
  if ! command -v "$_ckbin" >/dev/null 2>&1; then
    printf '%s\n' "cma_run_kimi_provider: kimi binary not found"
      >&2
```

```
  return 127
fi
# Shared activation gate (same record as the claude twin) — only
    a 'verified'
# id launches, unless the operator passes --force.
if (( ! _ckf )); then
  local _ck_sf="$HOME/.local/share/claude-multi-account/
    providers/status.json" _ck_st="pending"
  if command -v jq >/dev/null 2>&1 && [[ -s "$_ck_sf" ]]; then
    _ck_st="$(jq -r --arg i "$_ckpid" '.[$i].status //
      "pending"' "$_ck_sf" 2>/dev/null)"
    [[ -n "$_ck_st" && "$_ck_st" != "null" ]] ||
      _ck_st="pending"
  fi
  if [[ "$_ck_st" != "verified" ]]; then
    printf 'claude-providers: alias kimi-%s is %s — not
      launching.\n' "$_ckpid" "$_ck_st" >&2
    printf '  Re-verify: claude-providers verify %s   (and
      claude-providers sync)\n' "$_ckpid" >&2
    printf '  Override (operator): run the alias with --force\n'
      >&2
    return 3
  fi
fi
if [[ ! -f "$_ckconf" ]]; then
  printf 'claude-providers: kimi-%s has no config.toml at %s\n'
    "$_ckpid" "$_ckconf" >&2
  # TWO repairs, because ONE of them provably cannot fix the
    export class.
  # _cma_kimi_render_config is the ONLY writer of this file, and
    it is reached
  # from exactly three paths: cmd_sync, the multi-sync leg, and
  # `helixllm-export --apply`. Records written by the export
    path are BY
  # DESIGN never in sync's resolved set (FR-018 keeps the per-
    model fan-out
  # out of the default sync), so `sync` will never render THEIR
    config.toml.
  # Naming only `sync` sent that operator to a command that
    could not work.
  #
  # HOW AN ALIAS OUTLIVES ITS CONFIG. The alias line and this
    file are two
  # separate artifacts written together but removed
    independently: the config
  # can be deleted, or a home restored without it, while the
    alias line the
  # last render published is still in the alias file. `--
    refresh-aliases`
  # cannot repair that — it restores a twin alias LINE only
    where this config
  # ALREADY exists (a fail-closed `-f` gate, so the fast path
    can never
  # manufacture a listable-but-unlaunchable twin, and never
    renders a
```

```
  # secret-bearing file on a shell start). Re-rendering is the
      writer's job,
  # which is why both writers are named below.
  printf '  Run: claude-providers sync
      (providers that come from sync)\n' >&2
  printf '  Or:  claude-providers helixllm-export --apply  (per-
      model records from the export path)\n' >&2
  return 1
fi
# Pick up per-id launch metadata from the provider env record
      (tls CA cert, …
# ). config.toml carries the wire/API material; the env record
      carries host
# config. Optional — a record is not required for kimi launch.
local _ck_envf="$HOME/.local/share/claude-multi-account/
      providers/$_ckpid.env"
if [[ -f "$_ck_envf" ]]; then source "$_ck_envf"; fi
# default_model / base_url are read at launch from what sync
      rendered — never
# hardcoded here. Portable strip: take the value after the first
      `=`, drop
# surrounding quotes/whitespace with tr (works for the double-
      quoted TOML the
# kimi renderer emits).
_ckdm="$(
  grep -E '^[[:space:]]*default_model[[:space:]]*=' "$_ckconf"
      2>/dev/null \
    | head -n1 | cut -d= -f2- | tr -d ' "' \
)"
if [[ -z "$_ckdm" ]]; then
  printf 'claude-providers: kimi-%s config.toml has no
      default_model — stale config\n' "$_ckpid" >&2
  printf '  Run: claude-providers sync   to re-render\n' >&2
  return 1
fi
_ckbase="$(
  grep -E '^[[:space:]]*base_url[[:space:]]*=' "$_ckconf" 2>/
      dev/null \
    | head -n1 | cut -d= -f2- | tr -d ' "' \
)"
# TLS trust for self-signed backends, mirrored from the claude-
      side wiring:
# Node APPENDS NODE_EXTRA_CA_CERTS and Go replaces the pool (a
      CA-only
# SSL_CERT_FILE would narrow trust for every other dial). Gated
      on the cert
# being set+readable and the base URL being https://.
if [[ -n "${CMA_PROVIDER_CA_CERT:-}" && -r "$
      {CMA_PROVIDER_CA_CERT:-}" && "$_ckbase" == https://* ]];
      then
  export NODE_EXTRA_CA_CERTS="${CMA_PROVIDER_CA_CERT}"
  export SSL_CERT_FILE="${CMA_PROVIDER_CA_CERT}"
fi
# Same family isolation as cma_run_kimi: scrub a leftover
      Claude/Anthropic env.
```

```
  unset ANTHROPIC_BASE_URL ANTHROPIC_AUTH_TOKEN ANTHROPIC_MODEL
        ANTHROPIC_SMALL_FAST_MODEL
  unset ANTHROPIC_DEFAULT_OPUS_MODEL
        ANTHROPIC_DEFAULT_SONNET_MODEL
        ANTHROPIC_DEFAULT_HAIKU_MODEL
        ANTHROPIC_DEFAULT_FABLE_MODEL
  unset CLAUDE_CODE_MAX_OUTPUT_TOKENS
        CLAUDE_CODE_AUTO_COMPACT_WINDOW
        CLAUDE_CODE_MAX_CONTEXT_TOKENS
  # On-demand llmctl profile switch (no-op for every provider id
        that does
  # not start with "llmctl-") — see _cma_llmctl_ensure_active's
        header
  # comment above cma_run_provider for the full rationale. A
        failed switch
  # aborts HERE, before kimi is ever exec'd against $_ckbase's
        fixed port.
  _cma_llmctl_ensure_active "$_ckpid" || return $?
  KIMI_CODE_HOME="$_ckhome" "$_ckbin" -m "$_ckdm" "$@"
}
CMA_KIMI_PROV_EOF
}
eval "$(_cma_emit_cma_run_kimi_provider)"

# ============================================================================
# Pi family layer. The Pi CLI agent is a first-class sibling of
        Claude Code
# and Kimi Code. The family model is an orthogonal axis to the
        provider backend:
# the provider engine stays shared, and each family supplies its
        agent binary,
# home env var, account prefix, user-scope root, and launcher
        functions.
#
#   |                | Claude family       | Kimi family       |
        Pi family
#   | agent binary   | claude              | kimi              |
        pi
#   | home env var   | CLAUDE_CONFIG_DIR   | KIMI_CODE_HOME    |
        PI_HOME
#   | account prefix | .claude-            | .kimi-code-
        | .pi-
#   | user-scope root| ~/.claude (excluded)| ~/.kimi-code
        (excluded)| ~/.pi (excluded)
#   | account aliases| claude1…N           | kimi1…N           |
        pi1…N
#   | account launcher| cma_run            | cma_run_kimi      |
        cma_run_pi
#   | provider launcher| cma_run_provider  |
        cma_run_kimi_provider| cma_run_pi_provider
#   | shared store   | $SHARED_DIR/**      | $SHARED_DIR/kimi/ |
        $SHARED_DIR/pi/
#
# Namespace contract (the invariant): claudeN/kimiN/piN are native
        accounts; <id>
```

```
# (no prefix) is ALWAYS Claude Code over that backend; kimi-<id>
        is ALWAYS Kimi
# Code over the SAME backend; pi-<id> is ALWAYS Pi CLI over the
        SAME backend.
# piN account aliases must never be named pi-*/kimi-*/kc-* (those
        are reserved
# provider namespaces).
#
# KNOWN DIVERGENCE (disclosed, not (yet) reconciled): the "home
        env var" row's
# PI_HOME cell above is what the ACCOUNT launcher (cma_run_pi, piN
        aliases)
# sets — it is a real Pi CLI account-home switch.
        cma_run_pi_provider (the
# pi-<id> PROVIDER launcher) does NOT use PI_HOME: it was verified
        live that
# the real pi CLI has no PI_HOME env var and no TOML config reader
        at all, so
# cma_run_pi_provider instead exports PI_CODING_AGENT_DIR (pi's
        real, verified
# per-directory override) and reads a models.json (pi's real,
        verified custom-
# provider format) — see the root-cause note above
        cma_run_pi_provider. The
# piN account layer's PI_HOME usage was NOT re-verified against
        the live pi
# CLI as part of that fix (out of scope for the pi-<id> provider-
        twin track)
# and may share the same defect; tracked as a separate, disclosed
        finding.
# ============================================================================
PI_ACCOUNT_PREFIX=".pi-"
PI_PROVIDER_PREFIX=".pi-prov-"
PI_SHARED_SUBDIR="pi"

cma_pi_home()          { printf '%s\n' "$HOME/.pi"; }
cma_pi_account_home()  { printf '%s\n' "$HOME/
        $PI_ACCOUNT_PREFIX$1"; }
cma_pi_provider_home() { printf '%s\n' "$HOME/
        $PI_PROVIDER_PREFIX$1"; }

CMA_PI_SHARED_ITEMS=(AGENTS.md plugins skills sessions
        session_index.jsonl)

# Resolve the Pi CLI binary for the pi wrappers. Prefer an
        explicit
# PI_BIN, then the per-home bundled bin, then ~/.local/bin, then
        PATH.
cma_resolve_pi_bin() {
  if [ -n "${PI_BIN:-}" ]; then printf '%s\n' "$PI_BIN"; return
        0; fi
  if [ -x "$HOME/.pi/bin/pi" ]; then printf '%s\n' "$HOME/.pi/bin/
        pi"; return 0; fi
  if [ -x "$HOME/.local/bin/pi" ]; then printf '%s\n'
        "$HOME/.local/bin/pi"; return 0; fi
```

```
  local c; if c="$(command -v pi 2>/dev/null)"; then printf
        '%s\n' "$c"; return 0; fi
  printf '%s\n' "$HOME/.local/bin/pi"   # fallback (created by
        install/symlink)
}

# Marker-based detection mirror of cma_detect_accounts for the Pi
        family.
# Matches ${PI_ACCOUNT_PREFIX}* (~/.pi-*). The user-scope root
# ~/.pi (no trailing hyphen) and the provider homes ~/.pi-prov-*
# never match the glob structurally. Skips *-shared, *.lock,
        *.removed.*,
# *.preunify.*, and non-empty dirs lacking any pi marker.
cma_detect_pi_accounts() {
  local d prefix="${PI_ACCOUNT_PREFIX:-.pi-}"
  while IFS= read -r d; do
    [[ "$d" == *"-shared" ]] && continue
    [[ "$(basename "$d")" == *.lock ]] && continue
    [[ "$(basename "$d")" == *.removed.* ]] && continue
    [[ "$(basename "$d")" == *.preunify.* ]] && continue
    # Empty dirs always count (a brand-new account before any pi
        run).
    if [[ -z "$(ls -A "$d" 2>/dev/null)" ]]; then echo "$d";
        continue; fi
    # Non-empty: must look like a Pi account (at least one tell-
        tale
    # file/dir). Filters out dirs that merely match the `.pi-*`
        prefix
    # but belong to other tools.
    if [[ -f "$d/config.toml" || -d "$d/credentials" || -d "$d/
        sessions" \
       || -f "$d/session_index.jsonl" ]]; then
      echo "$d"
    fi
  done < <(find "$HOME" -maxdepth 1 -type d -name "${prefix}*" 2>/
        dev/null | sort)
}

# Read all aliases of the form `alias name="PI_HOME=...
        cma_run_pi"`
# from $ALIAS_FILE and print their names (one per line).
cma_existing_pi_aliases() {
  [[ -f "$ALIAS_FILE" ]] || return 0
  grep '^alias[[:space:]][^=]*="PI_HOME=' "$ALIAS_FILE" 2>/dev/
        null \
    | awk -F'[ =]+' '{print $2}' 2>/dev/null || true
}

# Suggest the next free `pi<N>` alias by scanning current pi
        aliases.
cma_suggest_pi_alias() {
  local highest=0 n a
  for a in $(cma_existing_pi_aliases); do
    if [[ "$a" =~ ^pi([0-9]+)$ ]]; then
```

```
      n="${BASH_REMATCH[1]}"
      (( n > highest )) && highest="$n"
    fi
  done
  printf 'pi%s\n' "$((highest + 1))"
}

# Validate a pi ACCOUNT alias name: same charset as
      cma_validate_alias, and
# additionally the provider namespaces `pi-*`, `kimi-*`, and `kc-
      *` are reserved for
# provider aliases — a piN account must never be named into any of
      them.
cma_validate_pi_alias() {
  cma_validate_alias "$1"
  case "$1" in
    pi-*|kimi-*|kc-*)
      cma_die "invalid alias name:
        $1 (reserved provider namespace pi-*/kimi-*/kc-*)" ;;
  esac
}

# Symlink every pi shared item into a pi account dir, creating
      empty
# placeholders under $SHARED_DIR/pi for items that don't exist
      yet.
# Idempotent: skips items already present in the target.
cma_link_pi_shared_items() {
  local pdir="$1" item src tgt
  mkdir -p "$SHARED_DIR/$PI_SHARED_SUBDIR" "$pdir"
  for item in "${CMA_PI_SHARED_ITEMS[@]}"; do
    src="$SHARED_DIR/$PI_SHARED_SUBDIR/$item"; tgt="$pdir/$item"
    if [[ ! -e "$src" ]]; then
      case "$item" in
        *.json|*.jsonl|*.md) : > "$src" ;;
        *) mkdir -p "$src" ;;
      esac
    fi
    [[ -e "$tgt" || -L "$tgt" ]] || ln -s "$src" "$tgt"
  done
}

# Add (or refresh) a single pi ACCOUNT alias in $ALIAS_FILE.
      Idempotent.
# The alias wraps `cma_run_pi` with a PI_HOME= prefix so the
      account
# resolves its own home, exactly as claudeN aliases carry
      CLAUDE_CONFIG_DIR=.
cma_write_pi_alias() {
  local alias_name="$1" pdir="$2" _cma_c
  cma_validate_pi_alias "$alias_name"
  # pdir is interpolated into the alias body and re-parsed by the
      shell when the
```

```
  # alias is invoked. Reject shell metacharacters and whitespace.
  for _cma_c in '"' '$' '`' \\ ';' '&' '|' '<' '>' '(' ')'; do
    case "$pdir" in *"$_cma_c"*)
      cma_warn "refusing to write alias '$alias_name': unsafe
          config dir"
      return 1 ;;
    esac
  done
  case "$pdir" in *[[:space:]]*)
    cma_warn "refusing to write alias '$alias_name': config dir
        must not contain whitespace"
    return 1 ;;
  esac
  cma_ensure_alias_file
  cma_alias_commit "$alias_name" \
    "$(printf 'alias %s="PI_HOME=%s cma_run_pi"' "$alias_name"
        "$pdir")" keep
}

# Remove a pi account alias line. Idempotent.
cma_remove_pi_alias() {
  local alias_name="$1"
  [[ -f "$ALIAS_FILE" ]] || return 0
  cma_alias_commit "$alias_name" "" keep
}

# ---- Emitted pi wrappers
        -------------------------------------------------
# These are emitted into the managed block and eval'd into THIS
        shell from the
# exact bytes the alias file receives.
_cma_emit_cma_run_pi() {
  cat <<'CMA_PI_RUN_EOF'
# Pi CLI account wrapper (piN). Resolves the pi binary, scrubs the
# Claude/Anthropic/Kimi env the Pi CLI must never inherit, then
        runs pi.
cma_run_pi() {
  local _cp_bin _cp_phome
  _cp_bin="${PI_BIN:-}"
  if ! command -v "$_cp_bin" >/dev/null 2>&1; then
    if [ -x "$HOME/.pi/bin/pi" ]; then _cp_bin="$HOME/.pi/bin/pi"
    elif [ -x "$HOME/.local/bin/pi" ]; then _cp_bin="$HOME/.local/
        bin/pi"
    elif command -v pi >/dev/null 2>&1; then _cp_bin="$(command -v
        pi)"
    fi
  fi
  if ! command -v "$_cp_bin" >/dev/null 2>&1; then
    printf '%s\n' "cma_run_pi: pi binary not found (checked \
        $PI_BIN, ~/.pi/bin, ~/.local/bin, PATH)" >&2
    return 127
  fi
```

```
  # Family isolation: never let a Claude/Anthropic/Kimi env left
        over from a previous
  # alias leak into the Pi CLI — base URL, auth token, model pins,
        and the
  # token-limit guards are all family-specific.
  unset ANTHROPIC_BASE_URL ANTHROPIC_AUTH_TOKEN ANTHROPIC_MODEL
        ANTHROPIC_SMALL_FAST_MODEL
  unset ANTHROPIC_DEFAULT_OPUS_MODEL
        ANTHROPIC_DEFAULT_SONNET_MODEL
        ANTHROPIC_DEFAULT_HAIKU_MODEL
        ANTHROPIC_DEFAULT_FABLE_MODEL
  unset CLAUDE_CODE_MAX_OUTPUT_TOKENS
        CLAUDE_CODE_AUTO_COMPACT_WINDOW
        CLAUDE_CODE_MAX_CONTEXT_TOKENS
  unset KIMI_CODE_HOME
  "$_cp_bin" "$@"
}
CMA_PI_RUN_EOF
}
eval "$(_cma_emit_cma_run_pi)"

_cma_emit_cma_run_pi_provider() {
  cat <<'CMA_PI_PROV_EOF'
# Pi CLI over a verified provider backend (pi-<id>). Shares the
        SAME
# status.json activation gate as the Claude twin (single shared
        record per id),
# reads the provider/model id + baseUrl from the rendered
        models.json, and
# refuses to launch on a missing or stale config. Self-contained:
        no lib.sh
# helpers (jq is the one external tool it leans on, exactly like
        its
# status.json activation-gate read two lines below).
#
# ROOT-CAUSE NOTE (do not "simplify" this back to config.toml /
        PI_HOME — both
# were verified, live, to be complete no-ops against the real pi
        CLI):
#   - Pi has NO `-m` shorthand for `--model` (unlike the sibling
        Kimi CLI,
#     which documents one); `pi -m X` exits 1 with "Unknown
        option: -m".
#   - Pi has NO TOML reader and NO `PI_HOME` env var anywhere in
        its source
#     (grepped its installed dist/ bundle for both: zero hits).
        Its real
#     per-directory override is `PI_CODING_AGENT_DIR` (see its
        dist/config.js
#     `ENV_AGENT_DIR = "PI_CODING_AGENT_DIR"`), and its real
        custom-provider
#     config file is JSON named exactly `models.json` (docs/
        models.md), read
#     from that directory — never `config.toml`.
cma_run_pi_provider() {
```

```
local _cpf=0 _cppid _cphome _cpconf _cpbin _cpdm _cpbase
if [[ "${1:-}" == "--force" ]]; then _cpf=1; shift; fi
_cppid="${1:-}"
shift 2>/dev/null || true
if [[ "${1:-}" == "--force" ]]; then _cpf=1; shift; fi
if [[ -z "$_cppid" ]]; then
  printf '%s\n' "usage: cma_run_pi_provider <id> [--force] [pi
      args...]" >&2
  return 2
fi
# Per-id home is FORCED, never ambient-PI_CODING_AGENT_DIR-
      honored: an
# exported PI_CODING_AGENT_DIR would point this wrapper at the
      WRONG
# models.json while it launches against ~/.pi-prov-<id> — a
      silently
# wrong-backend launch. Same isolation contract as
      cma_run_provider, which
# unconditionally exports CLAUDE_CONFIG_DIR. Self-contained
      body: never
# sources lib.sh.
_cphome="$HOME/.pi-prov-$_cppid"
_cpconf="$_cphome/models.json"
_cpbin="${PI_BIN:-}"
if ! command -v "$_cpbin" >/dev/null 2>&1; then
  if [ -x "$HOME/.pi/bin/pi" ]; then _cpbin="$HOME/.pi/bin/pi"
  elif [ -x "$HOME/.local/bin/pi" ]; then _cpbin="$HOME/.local/
      bin/pi"
  elif command -v pi >/dev/null 2>&1; then _cpbin="$(command -v
      pi)"
  fi
fi
if ! command -v "$_cpbin" >/dev/null 2>&1; then
  printf '%s\n' "cma_run_pi_provider: pi binary not found" >&2
  return 127
fi
# Shared activation gate (same record as the claude twin) — only
      a 'verified'
# id launches, unless the operator passes --force.
if (( ! _cpf )); then
  local _cp_sf="$HOME/.local/share/claude-multi-account/
      providers/status.json" _cp_st="pending"
  if command -v jq >/dev/null 2>&1 && [[ -s "$_cp_sf" ]]; then
    _cp_st="$(jq -r --arg i "$_cppid" '.[$i].status //
      "pending"' "$_cp_sf" 2>/dev/null)"
    [[ -n "$_cp_st" && "$_cp_st" != "null" ]] ||
      _cp_st="pending"
  fi
  if [[ "$_cp_st" != "verified" ]]; then
    printf 'claude-providers: alias pi-%s is %s — not launching.
      \n' "$_cppid" "$_cp_st" >&2
    printf '  Re-verify: claude-providers verify %s   (and
      claude-providers sync)\n' "$_cppid" >&2
```

```
    printf '  Override (operator): run the alias with --force\n'
      >&2
    return 3
  fi
fi
if [[ ! -f "$_cpconf" ]]; then
  printf 'claude-providers: pi-%s has no models.json at %s\n'
      "$_cppid" "$_cpconf" >&2
  printf '  Run: claude-providers sync
      (providers that come from sync)\n' >&2
  printf '  Or:  claude-providers helixllm-export --apply  (per-
      model records from the export path)\n' >&2
  return 1
fi
if ! command -v jq >/dev/null 2>&1; then
  printf 'claude-providers: pi-%s needs jq to read its rendered
      models.json (%s) — install jq\n' "$_cppid" "$_cpconf" >&2
  return 1
fi
# Pick up per-id launch metadata from the provider env record
      (tls CA cert, …).
# models.json carries the wire/API material; the env record
      carries host config.
local _cp_envf="$HOME/.local/share/claude-multi-account/
      providers/$_cppid.env"
if [[ -f "$_cp_envf" ]]; then source "$_cp_envf"; fi
# provider/model id and base_url are read at launch from what
      sync rendered.
# _cma_pi_render_config (claude-providers.sh) is the ONLY writer
      and always
# emits EXACTLY one provider key with EXACTLY one model entry,
      so the FIRST
# entry of each is authoritative — never re-derived or guessed
      here.
_cpdm="$(jq -r '.providers | to_entries[0] | (.key + "/" +
      (.value.models[0].id // ""))' "$_cpconf" 2>/dev/null)"
if [[ -z "$_cpdm" || "$_cpdm" == "/" || "$_cpdm" == "null/"* ]];
      then
  printf 'claude-providers: pi-%s models.json has no provider/
      model entry — stale config\n' "$_cppid" >&2
  printf '  Run: claude-providers sync   to re-render\n' >&2
  return 1
fi
_cpbase="$(jq -r '.providers | to_entries[0].value.baseUrl //
      ""' "$_cpconf" 2>/dev/null)"
# TLS trust for self-signed backends, mirrored from the claude-
      side wiring.
if [[ -n "${CMA_PROVIDER_CA_CERT:-}" && -r "$
      {CMA_PROVIDER_CA_CERT:-}" && "$_cpbase" == https://* ]];
      then
  export NODE_EXTRA_CA_CERTS="${CMA_PROVIDER_CA_CERT}"
  export SSL_CERT_FILE="${CMA_PROVIDER_CA_CERT}"
fi
# Family isolation: scrub a leftover Claude/Anthropic/Kimi env.
```

```
unset ANTHROPIC_BASE_URL ANTHROPIC_AUTH_TOKEN ANTHROPIC_MODEL
      ANTHROPIC_SMALL_FAST_MODEL
unset ANTHROPIC_DEFAULT_OPUS_MODEL
      ANTHROPIC_DEFAULT_SONNET_MODEL
      ANTHROPIC_DEFAULT_HAIKU_MODEL
      ANTHROPIC_DEFAULT_FABLE_MODEL
unset CLAUDE_CODE_MAX_OUTPUT_TOKENS
      CLAUDE_CODE_AUTO_COMPACT_WINDOW
      CLAUDE_CODE_MAX_CONTEXT_TOKENS
unset KIMI_CODE_HOME
# NOTE: `--model`, NEVER the bare `-m` (see the root-cause note
      above the
# function). NOTE: `PI_CODING_AGENT_DIR`, NEVER `PI_HOME` (same
      note) — this
# is what makes pi actually resolve THIS per-id models.json
      instead of its
# shared, unconfigured `~/.pi/agent/` default.
# On-demand llmctl profile switch (no-op for every non-llmctl-*
      provider) —
# see _cma_llmctl_ensure_active's header comment above
      cma_run_provider for
# the full rationale. A failed switch aborts HERE, before pi is
      ever exec'd
# against $_cpbase's fixed port.
_cma_llmctl_ensure_active "$_cppid" || return $?
# Pi's own CLI can exit 0 and print NOTHING to stdout/stderr
      even when the
# backend returned a real error (confirmed live: a context-
      exceeded 400
# from an undersized llmctl profile) -- the only trace is its
      own session
# JSONL's `stopReason: "error"` entry. Unlike the Kimi/Claude
      twins, whose
# own binaries DO print their errors directly, this wrapper
      cannot rely on
# exit-code/stderr alone, or a real launch failure looks like a
      silent
# no-op success to the operator. Snapshot the newest session
      file BEFORE
# the launch so the post-launch check only inspects a file THIS
      invocation
# could plausibly have written (never an unrelated earlier
      session).
# Portable newest-jsonl lookup (no `xargs -r`, a GNU-only flag
      that BSD/macOS
# xargs lacks -- `ls -t` on zero args would otherwise list the
      CWD instead
# of nothing): gate the xargs call on find's output being non-
      empty.
local _cp_sessdir="$_cphome/sessions" _cp_pre="" _cp_files
if [[ -d "$_cp_sessdir" ]]; then
  _cp_files="$(find "$_cp_sessdir" -name '*.jsonl' 2>/dev/null)"
  [[ -n "$_cp_files" ]] && _cp_pre="$(printf '%s\n' "$_cp_files"
      | xargs ls -t 2>/dev/null | head -1)"
fi
PI_CODING_AGENT_DIR="$_cphome" "$_cpbin" --model "$_cpdm" "$@"
```

```
  local _cp_rc=$?
  if command -v jq >/dev/null 2>&1 && [[ -d "$_cp_sessdir" ]];
        then
    local _cp_post=""
    _cp_files="$(find "$_cp_sessdir" -name '*.jsonl' 2>/dev/null)"
    [[ -n "$_cp_files" ]] && _cp_post="$(printf '%s\n'
        "$_cp_files" | xargs ls -t 2>/dev/null | head -1)"
    if [[ -n "$_cp_post" && "$_cp_post" != "$_cp_pre" ]]; then
      local _cp_err; _cp_err="$(jq -rs
        'map(select(.type=="message"
        and .message.stopReason=="error")) | last
        | .message.errorMessage // ""' "$_cp_post" 2>/dev/null)"
      if [[ -n "$_cp_err" && "$_cp_err" != "null" ]]; then
        printf 'claude-providers: pi-%s reported a real launch
        error (pi itself exited %d with no visible output): %s\n'
        \
          "$_cppid" "$_cp_rc" "$_cp_err" >&2
        (( _cp_rc == 0 )) && _cp_rc=1
      fi
    fi
  fi
  return "$_cp_rc"
}
CMA_PI_PROV_EOF
}
eval "$(_cma_emit_cma_run_pi_provider)"

# True only when the toolkit may prompt the user interactively.
        Scripts read
# confirmations from /dev/tty (so prompts survive `curl | bash`),
        so this
# probes /dev/tty rather than stdin. It returns false when:
#   * CMA_NONINTERACTIVE=1 is exported — a global "never prompt"
        switch for
#     automation, CI, and the test suite (deterministic regardless
        of TTY); or
#   * no terminal is available — CI, a test sandbox, an SSH
        command with no PTY.
# When it returns false, callers MUST fall back to their non-
        interactive
# default instead of blocking or erroring on a failed read. This
        is what makes
# toolkit execution always non-interactive off a terminal.
cma_can_prompt() {
  [[ "${CMA_NONINTERACTIVE:-}" == 1 ]] && return 1
  ( exec </dev/tty ) 2>/dev/null
}
```

8.2 `claude-unify.sh`

```
#!/usr/bin/env bash
# claude-unify.sh — Unify N Claude Code account config dirs into a
        single
```

```
# shared store so every account sees the same projects/
        conversations,
# memory, history, todos, plans, plugins, and settings.
#
# Inputs:
#   * Positional args: one or more account config directories. If
        none
#     are given, all `~/.claude-*` directories are auto-detected
        (excluding
#     the shared store itself).
#   * Env vars:
#       SHARED_DIR    target shared store (default: ~/.claude-
        shared)
#       DEFAULT_DIR   user-scope plugin root (default: ~/.claude)
#
# Use --rollback to restore the .preunify.* backups and remove the
        shared
# store. Safe to re-run any time.

set -euo pipefail

# macOS ships bash 3.2 which lacks `mapfile`. Re-exec under
        Homebrew bash
# if available; otherwise tell the user how to install it.
if (( BASH_VERSINFO[0] < 4 )); then
  for newer in /opt/homebrew/bin/bash /usr/local/bin/bash; do
    [[ -x "$newer" ]] && exec "$newer" "$0" "$@"
  done
  echo "claude-unify requires bash 4+. Install via: brew install
        bash" >&2
  exit 1
fi

# Resolve LIB_DIR through any symlinks (install.sh symlinks into
        ~/.local/bin).
_cma_src="${BASH_SOURCE[0]}"
while [ -L "$_cma_src" ]; do
  _cma_tgt="$(readlink "$_cma_src")"
  case "$_cma_tgt" in /*) _cma_src="$_cma_tgt" ;; *) _cma_src="$
        (dirname "$_cma_src")/$_cma_tgt" ;; esac
done
LIB_DIR="$(cd "$(dirname "$_cma_src")" && pwd)"
unset _cma_src _cma_tgt
# shellcheck source=lib.sh
source "$LIB_DIR/lib.sh"

DEFAULT_DIR="${DEFAULT_DIR:-$HOME/.claude}"

cma_require rsync
cma_require jq
cma_require awk
```

```
# Items each account dir contributes to the shared store. Order
      matters
# only insofar as we want plugins last so the path-rewrite step
      has all
# manifest entries to rewrite at once.
SHARED_ITEMS=(
  projects
  todos
  tasks
  plans
  file-history
  paste-cache
  shell-snapshots
  session-env
  telemetry
  sessions
  backups
  cache
  stats-cache.json
  history.jsonl
  plugins
  daemon
  jobs
)
# NOTE (§11.4 own-settings): settings.json is DELIBERATELY NOT in
      SHARED_ITEMS,
# so it is never symlinked into an account dir. Unify does NOT
      blanket-merge full
# account settings into the shared store (that re-leaks per-alias
      permissions/
# model/hooks to shared and thence to every dir). Instead it ONLY
      unions the
# enabledPlugins map into the shared TEMPLATE
      (union_enabled_plugins_into_template)
# and then re-seeds each dir's OWN settings.json from it
      (seed_own_settings) so
# newly-enabled plugins propagate while every other per-alias key
      stays local.
# This list MUST stay == CMA_SHARED_ITEMS (lib.sh) minus the
      CLAUDE.md special-
# case (enforced by the drift-guard test in test_unify.sh).

PRIVATE_ITEMS=(
  .credentials.json
  .claude.json
  mcp-needs-auth-cache.json
)

ts() { date +%Y%m%d%H%M%S; }

already_linked_to_shared() {
  [[ -L "$1" ]] || return 1
  # cma_realpath (not `readlink -f`, which is absent on BSD/macOS
      — there the
```

```
  # old check always failed, so unify re-linked every item on
      every re-run).
  [[ "$(cma_realpath "$1")" == "$(cma_realpath "$2")" ]]
}

backup_and_remove() {
  local p="$1"
  [[ -e "$p" || -L "$p" ]] || return 0
  mv "$p" "${p}.preunify.$(ts)"
}

link_to_shared() {
  local item="$1" acct
  # Never create a dangling symlink: if the merge step did not
      produce the
  # shared item (e.g. settings.json skipped because every account
      file was
  # invalid JSON, or a stats-cache.json that no account had),
      leave each
  # account's real file untouched rather than backing it up and
      pointing it at a
  # missing target — that would silently replace a valid live
      config with a
  # broken link.
  [[ -e "$SHARED_DIR/$item" ]] || return 0
  for acct in "${ACCOUNTS[@]}"; do
    [[ -d "$acct" ]] || continue
    local target="$acct/$item"
    already_linked_to_shared "$target" "$SHARED_DIR/$item" &&
      continue
    backup_and_remove "$target"
    mkdir -p "$(dirname "$target")"
    ln -s "$SHARED_DIR/$item" "$target"
  done
}

merge_dir_into_shared() {
  local item="$1" exclude="${2:-}" acct rc
  local excl=()
  [[ -n "$exclude" ]] && excl=(--exclude "$exclude")
  mkdir -p "$SHARED_DIR/$item"
  # First pass: each account fills only gaps (--ignore-existing)
      so the
  # union is preserved across N accounts.
  for acct in "${ACCOUNTS[@]}"; do
    if [[ -d "$acct/$item" && ! -L "$acct/$item" ]]; then
      rc=0
      rsync -a --ignore-existing "${excl[@]}" "$acct/$item/"
        "$SHARED_DIR/$item/" || rc=$?
      # rsync exit 23/24 are partial transfers ("some files
        vanished" / "some
      # files couldn't be transferred") that we treat as warnings
        — common on
```

```
      # macOS for `unlinkat: Directory not empty` when symlinks
        straddle the
      # tree. Anything else is fatal.
      (( rc == 0 || rc == 23 || rc == 24 )) || return $rc
    fi
  done

        # Second pass: overlay every account with rsync -u
        (update-only) so the file
  # carrying the NEWEST mtime wins each conflict, regardless of
        how many accounts
  # there are or what they're named. The previous code overlaid
        only
  # ACCOUNTS[-1] — the alphabetically-last dir, not necessarily
        the most recently
  # active one — which let a stale lexically-last account clobber
        fresher content
  # (e.g. memory/*.md) from an earlier account.
  for acct in "${ACCOUNTS[@]}"; do
    if [[ -d "$acct/$item" && ! -L "$acct/$item" ]]; then
      rc=0
      rsync -au "${excl[@]}" "$acct/$item/" "$SHARED_DIR/$item/"
        || rc=$?
      (( rc == 0 || rc == 23 || rc == 24 )) || return $rc
    fi
  done
}

# daemon/roster.json is the background-agent WORKER REGISTRY. The
        generic
# dir merge's per-file last-wins would keep only ONE alias's
        registry and
# silently drop every other alias's workers. Union them instead
        via
# cma_union_rosters (lib.sh): newer updatedAt wins per worker,
        proto and
# supervisorPid from the newest roster, top-level updatedAt is the
        max.
merge_daemon_roster() {
  local acct f srcs=()
  for acct in "${ACCOUNTS[@]}"; do
    f="$acct/daemon/roster.json"
    [[ -f "$f" && ! -L "$f" ]] && srcs+=("$f")
  done
  f="$SHARED_DIR/daemon/roster.json"
  [[ -f "$f" && ! -L "$f" ]] && srcs+=("$f")
  (( ${#srcs[@]} )) || return 0
  cma_union_rosters "$SHARED_DIR/daemon/roster.json" "${srcs[@]}"
        || \
    cma_warn "daemon roster union failed (invalid roster.json?) —
        last-wins file kept"
  return 0
}
```

```
merge_history_jsonl() {
  local acct srcs=() tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/
        cma.XXXXXX")"
  for acct in "${ACCOUNTS[@]}"; do
    local f="$acct/history.jsonl"
    if [[ -f "$f" && ! -L "$f" ]]; then srcs+=("$f"); fi
  done
  if [[ -f "$SHARED_DIR/history.jsonl" && ! -L "$SHARED_DIR/
        history.jsonl" ]]; then
    srcs+=("$SHARED_DIR/history.jsonl")
  fi
  # Feed the files straight to awk rather than cat'ing them
        together first: awk
  # starts a fresh record at every file boundary, so a source
        missing its
  # trailing newline cannot fuse its last line onto the next
        file's first line
  # (plain `cat` would). Write via a temp file so we never
        truncate shared while
  # it is also one of the inputs.
  if (( ${#srcs[@]} )); then
    awk 'NF && !seen[$0]++' "${srcs[@]}" > "$tmp"
    mv "$tmp" "$SHARED_DIR/history.jsonl"
  else
    : > "$SHARED_DIR/history.jsonl"
    rm -f "$tmp"
  fi
  return 0
}

# §11.4 own-settings: unify NEVER blanket-merges full account
        settings into the
# shared store — that would re-leak each alias's permissions/
        model/hooks to
# shared and, through the shared symlink, to every other alias.
        Instead it ONLY
# extracts the enabledPlugins map from every account's OWN
        settings.json and
# UNIONs it (any-true) into the shared TEMPLATE's enabledPlugins,
        leaving every
# other key of the template — and every key of each dir's OWN
        settings.json —
# untouched. seed_own_settings then propagates that union back
        into each dir.
union_enabled_plugins_into_template() {
  local acct files=() resolved f tmpl="$SHARED_DIR/settings.json"
  for acct in "${ACCOUNTS[@]}"; do
    f="$acct/settings.json"
    if [[ -L "$f" ]]; then
      resolved="$(cma_realpath "$f")"  # readlink -f is
        unavailable on BSD/macOS
      if [[ -f "$resolved" ]]; then files+=("$resolved"); fi
    elif [[ -f "$f" ]]; then
      files+=("$f")
```

```
  fi
done
# Include the existing template so a plugin enabled on a prior
      run (any-true)
# persists even if no current account carries it.
[[ -f "$tmpl" ]] && files+=("$tmpl")
# De-duplicate. On re-runs two account paths can resolve to the
      same file, and

      # passing the same path twice would double-count (harmless
      for a union, but we
# keep the set clean).
if (( ${#files[@]} > 1 )); then
  mapfile -t files < <(printf '%s\n' "${files[@]}" | awk '!
      seen[$0]++')
fi
# Drop any file that is not valid JSON so one hand-edited/
      corrupt account
# settings.json can't sink the whole union — jq -s slurps every
      file and fails
# wholesale on a single parse error. See test R3.
local validf=()
for f in ${files[@]+"${files[@]}"}; do
  if jq empty "$f" 2>/dev/null; then
    validf+=("$f")
  else
    cma_warn "settings.json in $(dirname
      "$f") is not valid JSON — excluded from enabledPlugins
      union"
  fi
done
files=(${validf[@]+"${validf[@]}"})
(( ${#files[@]} )) || return 0
mkdir -p "$SHARED_DIR"
[[ -f "$tmpl" ]] || printf '{}\n' > "$tmpl"
local tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"

      # Two-step so the shared template's OWN non-plugin keys
      (if any) survive and no
# per-account non-plugin key ever enters shared:
#   1. build the any-true union of enabledPlugins across every
      valid file,
#      with keys SORTED so the template is byte-stable across
      re-runs
#      regardless of per-account key order (idempotency, test
      line ~93);

      #   2. set ONLY .enabledPlugins on the existing template
      to that union.
local union
if union="$(jq -s '
      reduce .[] as $x ({};
        reduce (($x.enabledPlugins // {}) | to_entries[]) as $e
      (.;
```

```
            .[$e.key] = ((.[$e.key] // false) or $e.value)))
        | to_entries | sort_by(.key) | from_entries
      ' "${files[@]}" 2>/dev/null)" \
     && printf '%s' "$union" | jq empty 2>/dev/null \
     && jq --argjson u "$union" '.enabledPlugins = $u' "$tmpl" >
        "$tmp" 2>/dev/null \
     && jq -e . "$tmp" >/dev/null 2>&1; then
    mv "$tmp" "$tmpl"
  else
    rm -f "$tmp"
    cma_warn "settings.json: enabledPlugins union skipped (jq
        error)"
  fi
  return 0
}

# Give every account dir its OWN real settings.json (§11.4 own-
        settings): seed
# from the shared TEMPLATE when absent/legacy-symlink, else
        additively merge the
# template's enabledPlugins in (own keys always win). Per-alias
        non-plugin keys
# stay local — they never leak to shared or to a sibling dir.
        Delegates to the
# single canonical seeder in lib.sh so unify/add-account/
        providers/bootstrap all
# agree.
seed_own_settings() {
  local acct
  for acct in "${ACCOUNTS[@]}"; do
    [[ -d "$acct" ]] || continue
    cma_own_settings_seed "$acct"
  done
}

merge_file_into_shared() {
  local item="$1" acct newest=""
  for acct in "${ACCOUNTS[@]}"; do
    local f="$acct/$item"
    if [[ -L "$f" ]]; then continue; fi
    if [[ ! -f "$f" ]]; then continue; fi
    if [[ -z "$newest" || "$f" -nt "$newest" ]]; then
        newest="$f"; fi
  done
  if [[ -n "$newest" ]]; then cp -p "$newest" "$SHARED_DIR/
        $item"; fi
  return 0
}

absorb_default_plugins() {
  [[ -d "$DEFAULT_DIR/plugins" && ! -L "$DEFAULT_DIR/plugins" ]]
        || return 0
  mkdir -p "$SHARED_DIR/plugins"
```

```
  local rc=0
  rsync -a --ignore-existing "$DEFAULT_DIR/plugins/" "$SHARED_DIR/
        plugins/" || rc=$?
  (( rc == 0 || rc == 23 || rc == 24 )) || return $rc
  return 0
}

rewrite_plugin_paths() {
  local f="$SHARED_DIR/plugins/installed_plugins.json"
  if [[ -f "$f" ]]; then
    local tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
    jq --arg shared "$SHARED_DIR" '
      .plugins |= with_entries(
        .value |= map(
          if ((.installPath // "") | test(".*/plugins/cache/"))
          then .installPath = ($shared + "/plugins/cache/" +
        (.installPath | sub(".*/plugins/cache/"; "")))
          else . end
        )
      )' "$f" > "$tmp" && mv "$tmp" "$f"
  fi
  local km="$SHARED_DIR/plugins/known_marketplaces.json"
  if [[ -f "$km" ]]; then
    local tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
    jq --arg shared "$SHARED_DIR" '
      with_entries(
        if ((.value.installLocation // "") | test(".*/plugins/
        marketplaces/"))
        then .value.installLocation = ($shared + "/plugins/
        marketplaces/" + (.value.installLocation | sub(".*/
        plugins/marketplaces/"; "")))
        else . end
      )' "$km" > "$tmp" && mv "$tmp" "$km"
  fi
}

# Repoint ~/.claude/plugins/cache and ~/.claude/plugins/
        marketplaces at
# the shared store so future user-scope installs land in one
        place.
link_default_plugin_subdirs() {
  for sub in cache marketplaces; do
    local src="$SHARED_DIR/plugins/$sub" tgt="$DEFAULT_DIR/
        plugins/$sub"
    [[ -d "$src" ]] || continue
    already_linked_to_shared "$tgt" "$src" && continue
    mkdir -p "$DEFAULT_DIR/plugins"
    backup_and_remove "$tgt"
    ln -s "$src" "$tgt"
  done
}
```

```
# CLAUDE.md (user-scope memory) lives at ~/.claude/CLAUDE.md by
      default.
# We promote it to the shared store and symlink all three
      locations (each
# account dir + ~/.claude) so any account writing user memory
      updates the
# same file.
sync_claude_md() {
  local shared_md="$SHARED_DIR/CLAUDE.md" src
  if [[ ! -f "$shared_md" ]]; then
    if [[ -f "$DEFAULT_DIR/CLAUDE.md" && ! -L "$DEFAULT_DIR/
      CLAUDE.md" ]]; then
      cp -p "$DEFAULT_DIR/CLAUDE.md" "$shared_md"
    else
      for acct in "${ACCOUNTS[@]}"; do
        if [[ -f "$acct/CLAUDE.md" && ! -L "$acct/CLAUDE.md" ]];
        then
          cp -p "$acct/CLAUDE.md" "$shared_md"; break
        fi
      done
    fi
    [[ -f "$shared_md" ]] || return 0
  fi
  local targets=("$DEFAULT_DIR/CLAUDE.md")
  for acct in "${ACCOUNTS[@]}"; do targets+=("$acct/CLAUDE.md");
      done
  for tgt in "${targets[@]}"; do
    [[ -d "$(dirname "$tgt")" ]] || continue
    already_linked_to_shared "$tgt" "$shared_md" && continue
    backup_and_remove "$tgt"
    ln -s "$shared_md" "$tgt"
  done
}

rollback() {
  cma_log "rollback: restoring .preunify.* backups"
  local root
  local roots=("$DEFAULT_DIR" "$DEFAULT_DIR/plugins"
      "$SHARED_DIR")
  for root in "${ACCOUNTS[@]}"; do roots+=("$root"); done
  for root in "${roots[@]}"; do
    [[ -d "$root" ]] || continue

      # Restore backups oldest-first. The suffix is a
      YYYYMMDDHHMMSS timestamp, so
    # `sort -z` orders lexically = chronologically; the earliest
      backup is the
    # true pre-unify original and wins when a path has more than
      one .preunify.*.
    while IFS= read -r -d '' bk; do
      local orig="${bk%.preunify.*}"
      [[ -L "$orig" ]] && rm -f "$orig"
      [[ -e "$orig" ]] || { mv "$bk" "$orig"; cma_log "restored
        $orig"; }
```

```
    done < <(find "$root" -maxdepth 1 -name '*.preunify.*'
        -print0 2>/dev/null | sort -z)
    # Don't scan the shared store itself (its contents move aside
        intact below);
    # only external roots can hold links that would dangle.
    [[ "$root" == "$SHARED_DIR" ]] && continue
    # Remove leftover symlinks pointing into the shared store.
        unify created
    # these for items an account never had (so there's no backup
        to restore);
    # without this they dangle once SHARED_DIR is moved aside.
    while IFS= read -r -d '' lnk; do
      local tgt; tgt="$(readlink "$lnk")"
      case "$tgt" in
        "$SHARED_DIR"|"$SHARED_DIR"/*) rm -f "$lnk"; cma_log
        "removed shared-store symlink $lnk" ;;
      esac
    done < <(find "$root" -maxdepth 1 -type l -print0 2>/dev/null)
  done
  if [[ -d "$SHARED_DIR" ]]; then
    mv "$SHARED_DIR" "${SHARED_DIR}.removed.$(ts)"
    cma_log "moved $SHARED_DIR aside"
  fi
}

usage() {
  cat <<EOF
Usage: $(basename "$0") [--rollback] [account-dir ...]

Without args, auto-detects all ~/${ACCOUNT_PREFIX}* directories.
With --rollback, restores .preunify.* backups and removes the
        shared store.

Env: SHARED_DIR=$SHARED_DIR DEFAULT_DIR=$DEFAULT_DIR
EOF
}

# === main ===

ACCOUNTS=()
DO_ROLLBACK=0
while (( $# )); do
  case "$1" in
    -h|--help) usage; exit 0 ;;
    --rollback) DO_ROLLBACK=1; shift ;;
    --) shift; while (( $# )); do ACCOUNTS+=("$1"); shift; done ;;
    -*) cma_die "unknown flag: $1" ;;
    *)  ACCOUNTS+=("$1"); shift ;;
  esac
done

if (( ${#ACCOUNTS[@]} == 0 )); then
  mapfile -t ACCOUNTS < <(cma_detect_accounts)
```

```
fi

(( ${#ACCOUNTS[@]} >= 1 )) || cma_die "no account dirs given and
        none auto-detected at ~/${ACCOUNT_PREFIX}*"

cma_log "accounts: ${ACCOUNTS[*]}"
cma_log "shared:   $SHARED_DIR"

if (( DO_ROLLBACK )); then rollback; exit 0; fi

mkdir -p "$SHARED_DIR"
absorb_default_plugins

for item in "${SHARED_ITEMS[@]}"; do
  case "$item" in
    history.jsonl)    merge_history_jsonl ;;
    stats-cache.json) merge_file_into_shared "$item" ;;
    daemon)           merge_dir_into_shared "$item" "roster.json"
        && merge_daemon_roster ;;
    *)                merge_dir_into_shared "$item" ;;
  esac
  [[ "$item" == "plugins" ]] && rewrite_plugin_paths
  link_to_shared "$item"
  cma_log "ok: $item"
done

# §11.4 own-settings: settings.json is NOT a shared symlink. Union
        each account's
# enabledPlugins into the shared template, then re-seed every
        dir's OWN copy so
# the union propagates while per-alias non-plugin keys stay local.
union_enabled_plugins_into_template
seed_own_settings
cma_log
        "ok: settings.json (per-dir OWN copy; enabledPlugins union
        propagated; per-alias keys kept local)"

link_default_plugin_subdirs
sync_claude_md

# Merge the projects/session index inside .claude.json across
        every account.
# This is the single most important step for cross-account session
        resume:
# without it, account A's session UUIDs are invisible to account B
        even though
# the JSONL transcripts are already shared on disk via projects/.
cma_merge_claude_json "${ACCOUNTS[@]}"
cma_log "ok: .claude.json (projects/session index merged; auth
        keys preserved per-account)"

# Ensure every detected account has an invocable alias. install.sh
        and direct
```

```
# unify runs may discover pre-existing ~/.claude-* dirs that were
        never
# registered (e.g. the user ran install.sh after creating the
        dirs). Without
# this step `claude1` etc. are undefined even though the dirs
        exist.
cma_ensure_alias_file
declare -A ALIAS_OF_DIR=()
if [[ -f "$ALIAS_FILE" ]]; then
  while IFS= read -r line; do
    [[ "$line" =~ ^alias[[:space:]]+([a-zA-Z0-9_-]
        +)=.*CLAUDE_CONFIG_DIR=([^[:space:]]+) ]] || continue
    ALIAS_OF_DIR["${BASH_REMATCH[2]}"]="${BASH_REMATCH[1]}"
  done < "$ALIAS_FILE"
fi
# First pass: dirs whose suffix (after ~/.claude-) is already
        "claude<N>"
# (e.g. ~/.claude-claude4) keep that number, so user expectations
        about named
# dirs are preserved.
for acct in "${ACCOUNTS[@]}"; do
  if [[ -z "${ALIAS_OF_DIR[$acct]:-}" ]]; then
    base="$(basename "$acct")"
    suffix="${base#${ACCOUNT_PREFIX}}"
    if [[ "$suffix" =~ ^claude([0-9]+)$ ]]; then
      wanted="claude${BASH_REMATCH[1]}"
      if ! cma_existing_aliases | grep -qx "$wanted"; then
        cma_write_alias "$wanted" "$acct"
        cma_log "registered alias: $wanted -> $acct"
        continue
      fi
    fi
  fi
done
# Lowest free claude<N> (fills gaps left by explicit claudeM
        basenames).
_cma_lowest_free_clauden() {
  local n=1
  while cma_existing_aliases | grep -qx "claude$n"; do
    n=$((n + 1))
    (( n < 1000 )) || { cma_warn "could not find a free claude<N>
        alias"; return 1; }
  done
  printf 'claude%s\n' "$n"
}

# Second pass: anything still unaliased gets the lowest free
        claude<N>.
for acct in "${ACCOUNTS[@]}"; do
  if [[ -z "${ALIAS_OF_DIR[$acct]:-}" ]]; then
    if grep -qE "alias[[:space:]]+[^=]
        +=.*CLAUDE_CONFIG_DIR=$acct([[:space:]]|$)"
        "$ALIAS_FILE"; then
```

```
      # A newly-written pass-1 alias now points at this dir;
        update our map.
      ALIAS_OF_DIR[$acct]="$(grep -E "alias[[:space:]]+[^=]
        +=.*CLAUDE_CONFIG_DIR=$acct([[:space:]]|$)" "$ALIAS_FILE"
        | head -1 | sed -E 's/^alias[[:space:]]+([^=]+)=.*/\1/')"
      continue
    fi
    next_alias="$(_cma_lowest_free_clauden)"
    cma_write_alias "$next_alias" "$acct"
    cma_log "registered alias: $next_alias -> $acct"
  fi
done

cma_log "done. shared: $SHARED_DIR"
cma_log "private per-account: ${PRIVATE_ITEMS[*]}"
```

8.3 `claude-add-account.sh`

```
#!/usr/bin/env bash
# claude-add-account.sh — Add a new Claude Code account to the
        multi-account
# setup. Creates the per-account config directory, links every
        shared item
# to the shared store, and registers a shell alias so the new
        account is
# invocable as e.g. `claude3`.
#
# Modes:
#   * Interactive (default): prompts for alias name and config dir
        name,
#     showing defaults that follow the existing pattern.
#   * Non-interactive: pass --alias NAME and optionally --dir
        PATH, e.g.
#     `claude-add-account.sh --alias work --dir ~/.claude-work`.
#
# After this script runs you still need to authenticate the new
        account
# with Anthropic — the script prints the exact command for that.

set -euo pipefail

# Resolve LIB_DIR through any symlinks (install.sh symlinks into
        ~/.local/bin).
_cma_src="${BASH_SOURCE[0]}"
while [ -L "$_cma_src" ]; do
  _cma_tgt="$(readlink "$_cma_src")"
  case "$_cma_tgt" in /*) _cma_src="$_cma_tgt" ;; *) _cma_src="$
        (dirname "$_cma_src")/$_cma_tgt" ;; esac
done
LIB_DIR="$(cd "$(dirname "$_cma_src")" && pwd)"
unset _cma_src _cma_tgt
# shellcheck source=lib.sh
source "$LIB_DIR/lib.sh"
```

```
ALIAS_NAME=""
CONFIG_DIR=""
NONINTERACTIVE=0

usage() {
  cat <<EOF
Usage: $(basename "$0") [--alias NAME] [--dir PATH] [--yes]

  --alias NAME   Shell alias to create (e.g. claude3 or work).
        Default:
                 next free claudeN.
  --dir   PATH   Config directory for the new account. Default:
                 ~/${ACCOUNT_PREFIX}<alias>.
  --yes          Skip prompts and use defaults / passed values.
EOF
}

while (( $# )); do
  case "$1" in
    -h|--help) usage; exit 0 ;;
    --alias)   ALIAS_NAME="$2"; shift 2 ;;
    --dir)     CONFIG_DIR="$2"; shift 2 ;;
    --yes|-y)  NONINTERACTIVE=1; shift ;;
    *)         cma_die "unknown arg: $1" ;;
  esac
done

# Prompt with a default value, return whatever the user types (or
        default).
prompt() {
  local label="$1" default="$2" answer
  # Use the default when --yes was passed OR no terminal is
        available to
  # prompt from (CI, test sandbox, SSH without a PTY) — never
        block.
  if (( NONINTERACTIVE )) || ! cma_can_prompt; then echo
        "$default"; return; fi
  read -r -p "$label [$default]: " answer < /dev/tty
  echo "${answer:-$default}"
}

[[ -n "$ALIAS_NAME" ]] || ALIAS_NAME="$(cma_suggest_alias)"
ALIAS_NAME="$(prompt "Alias name" "$ALIAS_NAME")"
cma_validate_alias "$ALIAS_NAME"

# Reject if alias already exists in the alias file.
if cma_existing_aliases | grep -qx "$ALIAS_NAME"; then
  cma_die "alias '$ALIAS_NAME' already exists in $ALIAS_FILE"
fi

[[ -n "$CONFIG_DIR" ]] || CONFIG_DIR="$HOME/${ACCOUNT_PREFIX}$
        {ALIAS_NAME}"
```

```
CONFIG_DIR="$(prompt "Config directory" "$CONFIG_DIR")"
case "$CONFIG_DIR" in /*) ;; *) CONFIG_DIR="$HOME/$CONFIG_DIR" ;;
        esac

[[ -d "$CONFIG_DIR" ]] && cma_die "config dir already exists:
        $CONFIG_DIR (refusing to overwrite)"

mkdir -p "$CONFIG_DIR"
cma_log "created $CONFIG_DIR"

# Symlink every shared item into the new account dir, using the
        single
# canonical list (CMA_SHARED_ITEMS in lib.sh) so accounts and
        provider
# aliases stay in lockstep without two copies of the list drifting
        apart.
cma_link_shared_items "$CONFIG_DIR"
cma_log "linked ${#CMA_SHARED_ITEMS[@]} shared items into
        $CONFIG_DIR"

# Add the alias. lib.sh handles dedupe, rc-file sourcing, etc.
#
# The status is CHECKED. cma_write_alias used to report success
        even when the
# write was skipped on lock contention, which left the account on
        disk with no
# alias while this script printed "[done]" — and the obvious retry
        then died at
# the "config dir already exists" guard above, with no supported
        way forward.
# Say what actually happened and name the one command that
        finishes the job.
if ! cma_write_alias "$ALIAS_NAME" "$CONFIG_DIR"; then
  cma_warn "the alias for '$ALIAS_NAME' was NOT written to
        $ALIAS_FILE"
  cma_warn "$CONFIG_DIR exists and its shared items are linked —
        only the alias is missing."
  cma_die  "Finish with:  claude-unify   (re-registers an alias
        for every detected account)"
fi
cma_log "registered alias: $ALIAS_NAME -> $CONFIG_DIR"

cat <<EOF

[done] new account: $ALIAS_NAME

Next steps:
  1. Reload your shell (or run: source $ALIAS_FILE).
  2. Authenticate the new account:
       $ALIAS_NAME /login
  3. After login, run any project — history, memory, plugins, and
     settings will already match your other accounts via
        $SHARED_DIR.
```

```
To remove this account later:
  $LIB_DIR/claude-remove-account.sh --alias $ALIAS_NAME
EOF

# ATM-850 (2026-07-23): long-lived shells (tmux panes above all)
        sourced the
# alias file BEFORE this add. Detect them, say exactly who is
        covered by the
# dynamic dispatcher vs who needs ONE re-source, and print the
        exact commands.
# The notice never sends keys; the broadcast below is interactive,
        default No,
# and scoped to idle SHELL panes only.
cma_tmux_stale_shell_notice "$ALIAS_FILE" || true
if ! (( NONINTERACTIVE )) && cma_can_prompt; then
  _bc="$(prompt "Broadcast the re-source into idle tmux SHELL
        panes now? (y/N)" "N")"
  case "$_bc" in
    [Yy]*)
      _tdir="${TMUX_TMPDIR:-/tmp}/tmux-$(id -u)"
      for _sock in "$_tdir"/*; do
        [[ -S "$_sock" ]] || continue
        tmux -S "$_sock" list-panes -a -F '#{pane_id}
        #{pane_current_command}' 2>/dev/null \
          | awk '$2 ~ /^-?(bash|zsh|sh|dash|ksh|fish)$/{print
        $1}' \
          | while read -r _pane; do
              tmux -S "$_sock" send-keys -t "$_pane" C-u " source
        $ALIAS_FILE" Enter 2>/dev/null || true
            done
      done
      cma_log "re-source broadcast sent to idle shell panes" ;;
    *) : ;;
  esac
fi
```

8.4 `claude-remove-account.sh`

```
#!/usr/bin/env bash
# claude-remove-account.sh — Remove a Claude Code account from the
# multi-account setup. Drops the alias from the managed alias file
        and
# (optionally) deletes or archives the per-account config
        directory.
#
# The shared store is left untouched — only this one account's
        symlinks
# and credentials are removed. Other accounts continue using
        shared.

set -euo pipefail
```

```
# Resolve LIB_DIR through any symlinks (install.sh symlinks into
        ~/.local/bin).
_cma_src="${BASH_SOURCE[0]}"
while [ -L "$_cma_src" ]; do
  _cma_tgt="$(readlink "$_cma_src")"
  case "$_cma_tgt" in /*) _cma_src="$_cma_tgt" ;; *) _cma_src="$
        (dirname "$_cma_src")/$_cma_tgt" ;; esac
done
LIB_DIR="$(cd "$(dirname "$_cma_src")" && pwd)"
unset _cma_src _cma_tgt
# shellcheck source=lib.sh
source "$LIB_DIR/lib.sh"

ALIAS_NAME=""
DELETE_DIR=0
NONINTERACTIVE=0

usage() {
  cat <<EOF
Usage: $(basename "$0") --alias NAME [--delete | --archive] [--
        yes]

  --alias NAME   Required. Alias to remove (e.g. claude3).
  --delete       Permanently delete the per-account config
        directory.
  --archive      Move the per-account dir to
        <dir>.removed.<timestamp>
                 instead of deleting (default).
  --yes          Skip confirmation prompts.
EOF
}

while (( $# )); do
  case "$1" in
    -h|--help) usage; exit 0 ;;
    --alias)   ALIAS_NAME="$2"; shift 2 ;;
    --delete)  DELETE_DIR=1; shift ;;
    --archive) DELETE_DIR=0; shift ;;
    --yes|-y)  NONINTERACTIVE=1; shift ;;
    *)         cma_die "unknown arg: $1" ;;
  esac
done

[[ -n "$ALIAS_NAME" ]] || { usage; exit 2; }
cma_validate_alias "$ALIAS_NAME"

# Resolve the config dir by inspecting the existing alias line.
CONFIG_DIR=""
if [[ -f "$ALIAS_FILE" ]]; then
  # POSIX/2-arg awk match() only: the 3-arg capture form is GNU-
        awk-specific
```

```
        # and silently yields an empty CONFIG_DIR on the BSD awk
        shipped with macOS.
  CONFIG_DIR="$(awk -v a="$ALIAS_NAME" '
    $0 ~ "^alias[[:space:]]+"a"=" {
      if (match($0, /CLAUDE_CONFIG_DIR=[^ ]+/)) {
        s = substr($0, RSTART, RLENGTH)
        sub(/^CLAUDE_CONFIG_DIR=/, "", s)
        print s
      }
      exit
    }' "$ALIAS_FILE")"
fi
[[ -n "$CONFIG_DIR" ]] || cma_die "alias '$ALIAS_NAME' not found
        in $ALIAS_FILE"

cma_log "removing alias '$ALIAS_NAME' (config dir: $CONFIG_DIR)"

if (( ! NONINTERACTIVE )); then
  # Destructive op: when no terminal is available to confirm from
        (CI, SSH

        # without a PTY), refuse rather than block or guess — pass
        --yes to proceed
  # non-interactively.
  cma_can_prompt || cma_die "no terminal to confirm removal; pass
        --yes to proceed non-interactively"
  read -r -p "Proceed? [y/N] " ans < /dev/tty
  [[ "$ans" =~ ^[Yy]$ ]] || cma_die "aborted"
fi

# The status is CHECKED, and the directory move below is gated on
        it. This used
# to report success even when the write was skipped on lock
        contention, so the
# script logged "alias removed", then archived/deleted the config
        dir anyway —
# leaving a LIVE alias pointing at a directory that no longer
        exists. Removing
# nothing is recoverable; a dangling alias over a moved dir is
        not.
if ! cma_remove_alias "$ALIAS_NAME"; then
  cma_warn "the alias '$ALIAS_NAME' was NOT removed from
        $ALIAS_FILE"
  cma_die  "$CONFIG_DIR left in place on purpose — a live alias
        must never point at a moved dir. Re-run to retry."
fi
cma_log "alias removed from $ALIAS_FILE"

if [[ -d "$CONFIG_DIR" ]]; then
  if (( DELETE_DIR )); then
    rm -rf -- "$CONFIG_DIR"
    cma_log "deleted $CONFIG_DIR"
  else
```

```
    mv -- "$CONFIG_DIR" "${CONFIG_DIR}.removed.$(date +
        %Y%m%d%H%M%S)"
    cma_log "archived $CONFIG_DIR -> ${CONFIG_DIR}.removed.*"
  fi
fi

cat <<EOF

[done] account '$ALIAS_NAME' removed.

Notes:
  * Shared store $SHARED_DIR is untouched — other accounts still
        work.
  * Reload your shell so the alias change takes effect.
EOF
```

8.5 `claude-list-accounts.sh`

```
#!/usr/bin/env bash
# claude-list-accounts.sh — Print a status summary of every
        detected
# Claude Code account: which alias maps to it, whether credentials
        are
# present, and whether its shared-state symlinks are intact.

set -euo pipefail

if (( BASH_VERSINFO[0] < 4 )); then
  for newer in /opt/homebrew/bin/bash /usr/local/bin/bash; do
    [[ -x "$newer" ]] && exec "$newer" "$0" "$@"
  done
  echo "claude-list-accounts requires bash 4+. Install via: brew
        install bash" >&2
  exit 1
fi

# Resolve LIB_DIR through any symlinks (install.sh symlinks into
        ~/.local/bin).
_cma_src="${BASH_SOURCE[0]}"
while [ -L "$_cma_src" ]; do
  _cma_tgt="$(readlink "$_cma_src")"
  case "$_cma_tgt" in /*) _cma_src="$_cma_tgt" ;; *) _cma_src="$
        (dirname "$_cma_src")/$_cma_tgt" ;; esac
done
LIB_DIR="$(cd "$(dirname "$_cma_src")" && pwd)"
unset _cma_src _cma_tgt
# shellcheck source=lib.sh
source "$LIB_DIR/lib.sh"

# Build alias -> dir mapping from the managed alias file.
declare -A ALIAS_OF_DIR
if [[ -f "$ALIAS_FILE" ]]; then
```

```
  while IFS= read -r line; do
    [[ "$line" =~ ^alias[[:space:]]+([a-zA-Z0-9_-]
        +)=.*CLAUDE_CONFIG_DIR=([^[:space:]]+) ]] || continue
    ALIAS_OF_DIR["${BASH_REMATCH[2]}"]="${BASH_REMATCH[1]}"
  done < "$ALIAS_FILE"
fi

# Items we expect to be symlinks pointing into $SHARED_DIR. NOTE
      (§11.4
# own-settings): settings.json is DELIBERATELY excluded — each dir
      has its OWN
# real settings.json (per-alias keys stay local), so it is not a
      shared symlink
# and must not be reported as "not linked".
CHECK_LINKS=(projects history.jsonl plugins todos CLAUDE.md)

printf '%-12s  %-45s  %-6s  %-5s  %s\n' \
  "ALIAS" "CONFIG DIR" "CREDS" "LINKS" "NOTES"

mapfile -t accounts < <(cma_detect_accounts)
for dir in "${accounts[@]}"; do
  alias_name="${ALIAS_OF_DIR[$dir]:--}"
  if [[ -f "$dir/.credentials.json" ]]; then creds="yes"; else
      creds="no"; fi
  ok=0 total=0 missing=()
  for item in "${CHECK_LINKS[@]}"; do
    total=$((total+1))
    if [[ -L "$dir/$item" ]] \
       && [[ "$(cma_realpath "$dir/$item")" == "$(cma_realpath
        "$SHARED_DIR/$item")" ]]; then
      ok=$((ok+1))
    else
      missing+=("$item")
    fi
  done
  notes=""
  (( ${#missing[@]} )) && notes="not linked: ${missing[*]}"
  printf '%-12s  %-45s  %-6s  %-5s  %s\n' \
    "$alias_name" "$dir" "$creds" "$ok/$total" "$notes"
done

echo
echo "Shared store: $SHARED_DIR"
[[ -d "$SHARED_DIR" ]] || echo "  (does not exist — run claude-
      unify.sh)"
echo "Alias file:   $ALIAS_FILE"
[[ -f "$ALIAS_FILE" ]] || echo "  (does not exist — run
      install.sh)"
```

8.6 `claude-rollback.sh`

```
#!/usr/bin/env bash
# claude-rollback.sh — Convenience wrapper that calls claude-
        unify.sh with
# --rollback. Restores every .preunify.<timestamp> backup created
        by the
# unification run and archives the shared store out of the way.
#
# After this you can re-run install.sh to start over from scratch.

set -euo pipefail

# Resolve LIB_DIR through any symlinks (install.sh symlinks into
        ~/.local/bin).
_cma_src="${BASH_SOURCE[0]}"
while [ -L "$_cma_src" ]; do
  _cma_tgt="$(readlink "$_cma_src")"
  case "$_cma_tgt" in /*) _cma_src="$_cma_tgt" ;; *) _cma_src="$
        (dirname "$_cma_src")/$_cma_tgt" ;; esac
done
LIB_DIR="$(cd "$(dirname "$_cma_src")" && pwd)"
unset _cma_src _cma_tgt
exec "$LIB_DIR/claude-unify.sh" --rollback "$@"
```

8.7 `claude-export-docs.sh`

```
#!/usr/bin/env bash
# claude-export-docs.sh — Convert the multi-account markdown doc
        to
# matching .html and .pdf siblings. Re-runnable; overwrites
        outputs.
#
# Order of preference for PDF: pandoc + weasyprint > pandoc +
        wkhtmltopdf
# > chromium --headless print-to-pdf > weasyprint on the generated
        HTML.
# HTML always uses pandoc with a self-contained option so the file
        is
# portable without external CSS/JS.

set -euo pipefail

# Resolve LIB_DIR through any symlinks (install.sh symlinks into
        ~/.local/bin).
_cma_src="${BASH_SOURCE[0]}"
while [ -L "$_cma_src" ]; do
  _cma_tgt="$(readlink "$_cma_src")"
  case "$_cma_tgt" in /*) _cma_src="$_cma_tgt" ;; *) _cma_src="$
        (dirname "$_cma_src")/$_cma_tgt" ;; esac
done
LIB_DIR="$(cd "$(dirname "$_cma_src")" && pwd)"
unset _cma_src _cma_tgt
```

```
# shellcheck source=lib.sh
source "$LIB_DIR/lib.sh"

DOC_DIR="${DOC_DIR:-$HOME/Documents}"
MD_FILE="${MD_FILE:-$DOC_DIR/Claude_Multi_Account_Fine_Tuning.md}"
HTML_FILE="${MD_FILE%.md}.html"
PDF_FILE="${MD_FILE%.md}.pdf"
DOCX_FILE="${MD_FILE%.md}.docx"
# Optional Word styling: first existing reference doc wins.
        Generate a starter
# with: pandoc -o reference.docx --print-default-data-file
        reference.docx
DOCX_REFERENCE="${DOCX_REFERENCE:-}"

[[ -f "$MD_FILE" ]] || cma_die "markdown not found: $MD_FILE"
cma_require pandoc

# --- Preprocess: expand `<!-- INCLUDE: relative/path -->` markers
        ---
# These markers, placed inside a fenced code block in the source
        markdown,
# get replaced with the contents of the referenced file (relative
        to the
# directory containing the markdown). That keeps the .md small
        while the
# generated HTML/PDF stays self-contained.
# Portable temp file: BSD/macOS mktemp has no --suffix. pandoc
        reads the
# format from --from, so the missing .md extension is irrelevant.
PROCESSED_MD="$(mktemp "${TMPDIR:-/tmp}/cma-export.XXXXXX")"
trap 'rm -f "$PROCESSED_MD"' EXIT

# Use only POSIX/2-arg awk match() (RSTART/RLENGTH + substr): the
        3-arg
# match($0,re,arr) capture form is a GNU-awk extension and breaks
        on the BSD
# awk that ships with macOS.
awk -v base="$(dirname "$MD_FILE")" '
  /<!-- INCLUDE: / {
    if (match($0, /INCLUDE: [^ ]+ -->/)) {
      tok = substr($0, RSTART, RLENGTH)   # "INCLUDE: path -->"
      sub(/^INCLUDE: /, "", tok)
      sub(/ -->$/, "", tok)               # -> "path"
      path = tok
      if (path !~ /^\//) path = base "/" path
      while ((getline line < path) > 0) print line
      close(path)
      next
    }
  }
  { print }
' "$MD_FILE" > "$PROCESSED_MD"
```

```
# --- HTML ---
# --standalone makes a complete HTML doc (head/body), --embed-
        resources
# inlines CSS/JS/images so the file is self-contained.
cma_log "rendering HTML -> $HTML_FILE"
pandoc \
  --from=gfm+yaml_metadata_block \
  --to=html5 \
  --standalone \
  --embed-resources \
  --toc --toc-depth=3 \
  --highlight-style=tango \
  --metadata title="Claude Multi-Account Fine Tuning" \
  -o "$HTML_FILE" \
  "$PROCESSED_MD"

# --- PDF ---
cma_log "rendering PDF -> $PDF_FILE"

render_pdf_via_pandoc_engine() {
  local engine="$1"
  command -v "$engine" >/dev/null 2>&1 || return 1
  pandoc \
    --from=gfm+yaml_metadata_block \
    --pdf-engine="$engine" \
    --toc --toc-depth=3 \
    --highlight-style=tango \
    -V geometry:margin=0.9in \
    -V mainfont="DejaVu Serif" \
    -V monofont="DejaVu Sans Mono" \
    --metadata title="Claude Multi-Account Fine Tuning" \
    -o "$PDF_FILE" \
    "$PROCESSED_MD"
}

render_pdf_via_chromium() {
  local engine
  for engine in chromium chromium-browser google-chrome chrome; do
    if command -v "$engine" >/dev/null 2>&1; then
      # Use the freshly generated HTML so styling matches.
      "$engine" --headless --no-sandbox --disable-gpu \
        --print-to-pdf="$PDF_FILE" \
        --print-to-pdf-no-header \
        "file://$HTML_FILE" >/dev/null 2>&1
      return $?
    fi
  done
  return 1
}

render_pdf_via_weasyprint_on_html() {
  command -v weasyprint >/dev/null 2>&1 || return 1
```

```
  weasyprint "$HTML_FILE" "$PDF_FILE"
}

# Try engines in order; the first that succeeds wins.
if render_pdf_via_pandoc_engine weasyprint 2>/dev/null; then
  cma_log "pdf engine: weasyprint (via pandoc)"
elif render_pdf_via_pandoc_engine wkhtmltopdf 2>/dev/null; then
  cma_log "pdf engine: wkhtmltopdf (via pandoc)"
elif render_pdf_via_weasyprint_on_html 2>/dev/null; then
  cma_log "pdf engine: weasyprint on html"
elif render_pdf_via_chromium 2>/dev/null; then
  cma_log "pdf engine: chromium headless"
else
  cma_die "no usable PDF engine. Install one of: weasyprint,
        wkhtmltopdf, chromium."
fi

# --- DOCX ---
# pandoc writes .docx natively (no external engine). A reference
        doc supplies
# styling (fonts, headings, code blocks) when provided.
cma_log "rendering DOCX -> $DOCX_FILE"
docx_args=(
  --from=gfm+yaml_metadata_block
  --to=docx
  --toc --toc-depth=3
  --highlight-style=tango
  --metadata title="Claude Multi-Account Fine Tuning"
  -o "$DOCX_FILE"
)
# Auto-discover a reference doc if none was passed explicitly.
if [[ -z "$DOCX_REFERENCE" ]]; then
  for cand in "$DOC_DIR/reference.docx" "$LIB_DIR/assets/
        reference.docx"; do
    [[ -f "$cand" ]] && { DOCX_REFERENCE="$cand"; break; }
  done
fi
[[ -n "$DOCX_REFERENCE" && -f "$DOCX_REFERENCE" ]] &&
        docx_args+=(--reference-doc "$DOCX_REFERENCE")
if pandoc "${docx_args[@]}" "$PROCESSED_MD"; then
  cma_log "docx ok${DOCX_REFERENCE:+ (styled via
        $DOCX_REFERENCE)}"
else
  cma_warn "DOCX render failed (pandoc); HTML + PDF are still
        produced"
fi

ls -lh "$HTML_FILE" "$PDF_FILE" "$DOCX_FILE" 2>/dev/null || ls
        -lh "$HTML_FILE" "$PDF_FILE"
```

8.8 install.sh

```
#!/usr/bin/env bash
# install.sh — One-shot bootstrap for the Claude multi-account
       toolkit.
# Idempotent; safe to re-run after pulling updates.
#
# What it does, in order:
#   1. Detect tooling (jq, rsync, awk, pandoc) and fail fast if
       missing.
#   2. Symlink every script into ~/.local/bin (creates the dir if
       needed).
#   3. Ensure ~/.local/bin is on PATH for future shells.
#   4. Create the managed alias file at $ALIAS_FILE and source it
       from
#      ~/.bashrc and ~/.zshrc (whichever exist).
#   5. Run claude-unify.sh to merge any existing account dirs.
#   6. Run claude-export-docs.sh to refresh the PDF/HTML alongside
       the
#      markdown doc.

set -euo pipefail

# macOS ships bash 3.2 which lacks `mapfile`. If a newer bash is
       available
# (Homebrew installs it at /opt/homebrew/bin/bash on Apple
       Silicon, or
# /usr/local/bin/bash on Intel), re-exec with it. Otherwise tell
       the user
# how to install it.
if (( BASH_VERSINFO[0] < 4 )); then
  for newer in /opt/homebrew/bin/bash /usr/local/bin/bash; do
    [[ -x "$newer" ]] && exec "$newer" "$0" "$@"
  done
  echo
       "claude-toolkit requires bash 4+. Install via: brew
       install bash" >&2
  exit 1
fi

# Resolve LIB_DIR through any symlinks (install.sh symlinks into
       ~/.local/bin).
_cma_src="${BASH_SOURCE[0]}"
while [ -L "$_cma_src" ]; do
  _cma_tgt="$(readlink "$_cma_src")"
  case "$_cma_tgt" in /*) _cma_src="$_cma_tgt" ;; *) _cma_src="$
       (dirname "$_cma_src")/$_cma_tgt" ;; esac
done
LIB_DIR="$(cd "$(dirname "$_cma_src")" && pwd)"
unset _cma_src _cma_tgt
# shellcheck source=lib.sh
source "$LIB_DIR/lib.sh"

cma_log "platform: $(cma_os)"
```

```
# 1. Required tooling. pandoc is needed only for doc export; the
        rest are
# load-bearing for unify/add-account.
for t in rsync jq awk; do cma_require "$t"; done
command -v pandoc >/dev/null 2>&1 || cma_warn "pandoc not found —
        PDF/HTML export will be skipped"

# 1b. Node deps for the optional TOON utility (scripts/toon.mjs,
        and the
# toon_encode.py wrapper that shells out to it). Soft by design:
        the toolkit's
# core (unify/add-account) needs no Node, so a missing npm is a
        warning, not a
# hard failure. Idempotent — npm install is a no-op once @toon-
        format/toon is
# already present. (node_modules/ is gitignored; this is how the
        dep arrives.)
_cma_repo_root="$(cd "$LIB_DIR/.." && pwd)"
if [[ -f "$_cma_repo_root/package.json" ]]; then
  if command -v npm >/dev/null 2>&1; then
    cma_log "installing Node deps for the TOON utility (npm
        install) ..."
    ( cd "$_cma_repo_root" && npm install --no-audit --no-fund --
        silent ) \
      || cma_warn "npm install failed — scripts/toon.mjs (TOON
        utility) may be unavailable"
  else
    cma_warn "npm not found — scripts/toon.mjs (TOON utility)
        unavailable until you run 'npm install' in
        $_cma_repo_root"
  fi
fi
unset _cma_repo_root

# Recorded install problems, surfaced together by step 7. Declared
        here (BEFORE
# their first writer, the PATH-link guard below) so `set -u` never
        trips on an
# append to an unset array, and so step 7 can length-test them
        safely.
CMA_INSTALL_FAILURES=()
CMA_INSTALL_DEGRADED=()

# 2. Symlink the scripts onto PATH.
#
# EXECUTABILITY IS PART OF LINKING (field failure 2026-09-07,
        operator host):
# this loop used to `ln -s` whatever it found and say nothing
        about the mode.
# Two tracked scripts had been committed 100644 — scripts/kimi-
        providers.sh and
# scripts/claude-proxy-build.sh — so `kimi-providers` and `claude-
        proxy-build`
```

```
# existed on PATH, resolved to a real file, and died at RUNTIME
        with
#     bash: /home/.../.local/bin/kimi-providers: Permission denied
# (exit 126) — a message naming neither the source file nor the
        cause. The
# installer had printed "[done] installed" over both. Silently
        linking a
# non-executable target is the defect; the fix has to survive a
        FRESH CLONE,
# so it cannot be "remember to chmod".
#
# Policy: REPAIR, then REPORT BY NAME, and FAIL if the repair is
        impossible.
#   * repair — chmod +x, so the contract "a fresh clone + install
        yields
#     working commands" holds even for a checkout that lost its
        mode bits
#     (zip download, restrictive umask, a copy across a filesystem
        that does
#     not carry them). Refusing to link would trade a broken
        command for a
#     missing one; neither is a working toolkit.
#   * report — cma_warn names the exact file and the exact git
        command that
#     records the mode, so the slip is never silent and gets fixed
        at source
#     rather than being re-repaired on every install.
#   * fail — if chmod itself cannot make it executable, the
        command WILL be
#     broken on PATH, so that is a recorded install FAILURE and
        step 7 refuses
#     to print the success banner over it (§ same rule as 2b).
BIN_DIR="${BIN_DIR:-$HOME/.local/bin}"
mkdir -p "$BIN_DIR"

cma_link_script_onto_path() {
  local f="$1" name link
  name="$(basename "$f" .sh)"
  link="$BIN_DIR/$name"

  if [[ ! -x "$f" ]]; then
    cma_warn "$(basename "$f") is not executable (mode $
        (cma_file_mode "$f")) — repairing with chmod +x."
    printf
        '  Record it at source so a fresh clone does not repeat
        this:\n    git update-index --chmod=+x %s\n' \
      "${f#"$(cd "$LIB_DIR/.." && pwd)"/}" >&2
    chmod +x "$f" 2>/dev/null || true
    if [[ ! -x "$f" ]]; then
      CMA_INSTALL_FAILURES+=("$(basename "$f") could not be made
        executable — the '$name' command on PATH will die with
        'Permission denied' (exit 126). Fix: chmod +x $f")
      return 1
    fi
  fi
```

```
  if [[ -L "$link" || -e "$link" ]]; then
    if [[ "$(cma_realpath "$link")" != "$(cma_realpath "$f")" ]];
        then
      mv "$link" "${link}.preunify.$(date +%Y%m%d%H%M%S)"
      ln -s "$f" "$link"
      cma_log "linked $link -> $f"
    fi
  else
    ln -s "$f" "$link"
    cma_log "linked $link -> $f"
  fi
  return 0
}

# Portable `stat` for the diagnostic above (GNU vs BSD); never
        fatal.
cma_file_mode() {
  stat -c '%a' "$1" 2>/dev/null || stat -f '%Lp' "$1" 2>/dev/null
        || printf '?'
}

for f in "$LIB_DIR"/claude-*.sh; do
  cma_link_script_onto_path "$f" || true
done
# Same treatment for the Kimi family commands (v1.27.0) — they end
        up on PATH
# exactly like the claude-* ones, so the docs' `kimi-add-account`,
# `kimi-providers` etc. work out of the box, executable bit
        included.
for f in "$LIB_DIR"/kimi-*.sh; do
  cma_link_script_onto_path "$f" || true
done

# 2b. Build the BUNDLED Go claude-code-router (flat checkout) and
        install it as
# `ccr`, so the provider aliases route through OUR vendored router
        rather than a
# separately-installed Node one.
#
# NOT best-effort any more (field failure 2026-07-22, operator
        host, v1.25.4):
# this was `if ! bash ...; then cma_warn ...`, so a build failure
        only WARNED,
# the install continued, and the banner still printed "[done]
        installed" while
# the npm @musistudio ccr kept answering for `ccr`. The operator's
        FIRST
# symptom was a provider alias dying at RUNTIME. An installer that
        reports
# success over a broken product is a §11.4 PASS-bluff at the
        install layer.
#
```

```
# The failure is RECORDED and re-raised by step 7 rather than
        aborting here:
# the remaining steps (PATH, aliases, unify) are independent and
        still worth
# completing, and step 7 then reports EVERY problem at once
        instead of making
# the operator re-run once per failure.
# (Declared above step 2 — the PATH-link guard is now their first
        writer.)
if ! bash "$LIB_DIR/claude-ccr-build.sh"; then
  CMA_INSTALL_FAILURES+=("bundled claude-code-router (Go) did NOT
        build/install — provider aliases on the router transport
        cannot launch. Fix: ensure a Go toolchain new enough for
        the claude-code-router go.mod (checkout located by
        scripts/resolve_deps.sh claude_code_router) is available
        (install/upgrade Go: https://go.dev/dl/ — or, with an
        older Go already installed and network access:
        GOTOOLCHAIN=auto claude-ccr-build), then run: claude-ccr-
        build")
fi

# 3. Make sure ~/.local/bin is on PATH for new shells. We add
        to .bashrc
# and .zshrc once; existing shells need a manual reload.
# shellcheck disable=SC2016  # $HOME/$PATH are intentionally
        unexpanded literals written into rc files
PATH_LINE='export PATH="$HOME/.local/bin:$PATH"'
for rc in "${CMA_RC_FILES[@]}"; do
  [[ -f "$rc" ]] || continue
  if ! grep -F -q "$PATH_LINE" "$rc"; then
    # Backup-first, idempotent BEGIN/END block (refuses if it
        cannot back up).
    cma_rc_append_managed "$rc" path "$PATH_LINE" || true
  fi
done

# 4. Alias file + rc sourcing.
cma_ensure_alias_file

# Re-register any pre-existing aliases from $HOME/.bashrc into the
        managed
# alias file, then comment out the originals so they're not
        duplicated.
migrate_inline_aliases() {
  local rc="$1"
  [[ -f "$rc" ]] || return 0
  local tmp; tmp="$(mktemp "${TMPDIR:-/tmp}/cma.XXXXXX")"
  local changed=0

        # `|| [[ -n "$line" ]]` so a final line with NO trailing
        newline is still
  # processed rather than silently dropped (mirrors lib.sh's rc
        read loops).
  while IFS= read -r line || [[ -n "$line" ]]; do
```

```
    if [[ "$line" =~ ^alias[[:space:]]+(claude[0-9a-zA-Z_-]
        +)=.*CLAUDE_CONFIG_DIR=([^[:space:]\"]+) ]]; then
      local a="${BASH_REMATCH[1]}" d="${BASH_REMATCH[2]}"
      d="${d//\"/}"
      d="${d/#\$HOME/$HOME}"
      d="${d/#~/$HOME}"
      cma_write_alias "$a" "$d"
      printf '# migrated to %s: %s\n' "$ALIAS_FILE" "$line" >>
        "$tmp"
      changed=1
    else
      printf '%s\n' "$line" >> "$tmp"
    fi
  done < "$rc"
  if (( changed )); then
    # migrate removes NOTHING (it only comment-prefixes lines in
        place), so the
    # intended removal count is 0 — cma_rc_safe_rewrite's content-
        loss gate then
    # REFUSES any candidate that lost a line (e.g. a newline-less
        final line the
    # old read loop could drop) and parks it instead of
        publishing. The committer
    # also takes the pristine .cma-orig backup, superseding the
        bespoke .preunify.
    if cma_rc_safe_rewrite "$rc" "$tmp" 0; then
      cma_log "migrated inline claude* aliases in $rc ->
        $ALIAS_FILE"
    else
      cma_warn "skipped migrating inline aliases in $rc (rejected
        or unbackupable)"
    fi
  else
    rm -f "$tmp"
  fi
}
for rc in "${CMA_RC_FILES[@]}"; do
  migrate_inline_aliases "$rc"
done

# 4b. Build + install the Go compatibility proxy (cma-proxy) for
        provider
# compatibility (helixagent Hermes tool-call recovery + poe/kimi/
        sarvam
# request-schema fixes). Replaces the former per-provider python
        proxies.
# Recorded (not warn-and-forget) for the same reason as 2b:
        without it the
# helixagent/poe/kimi/sarvam aliases silently lose their compat
        shims, which is
# a DEGRADED product the operator must be told about by name —
        step 7 reports
# it. It is a DEGRADED (not FAILED) capability: those aliases
        still launch
```

```
# against their direct endpoint, so it must not by itself fail the
        install.
if ! bash "$LIB_DIR/claude-proxy-build.sh"; then
  CMA_INSTALL_DEGRADED+=("compatibility proxy (cma-proxy, Go) did
        NOT build — helixagent/poe/kimi/sarvam aliases run WITHOUT
        their compat shims (Hermes tool-call recovery + request-
        schema fixes inactive). Fix: install Go, then run: claude-
        proxy-build")
fi

# 4c. Provider session-sync hook + an install-time sync (soft —
        the host may
# lack keys/network at install time, so a failure here is non-
        fatal). The hook
# refreshes provider aliases from cache on every new shell (no
        network) and
# kicks a detached full sync when the cache is stale (§11.4.89).
cma_install_session_hook
if [[ -x "$LIB_DIR/claude-providers.sh" ]]; then
  cma_log "running claude-providers sync (install-time; soft)"
  ( "$LIB_DIR/claude-providers.sh" sync ) || cma_warn "provider
        sync skipped (no keys/network?)"
fi

# 5. Unify whatever accounts exist now.
if (( $(cma_detect_accounts | wc -l) > 0 )); then
  cma_log "running claude-unify.sh"
  "$LIB_DIR/claude-unify.sh"
else
  cma_warn "no ~/${ACCOUNT_PREFIX}* dirs detected — add one with
        claude-add-account.sh"
fi

# 5b. Same unification for the Kimi family (v1.27.0), over
        $SHARED_DIR/kimi/.
# Only when Kimi homes are actually present — a fresh install with
        none should
# keep the same single cma_warn the Claude side emits, not two.
if [[ -x "$LIB_DIR/kimi-unify.sh" ]] && (( $
        (cma_detect_kimi_accounts | wc -l) > 0 )); then
  cma_log "running kimi-unify.sh"
  "$LIB_DIR/kimi-unify.sh"
fi

# 6. Refresh docs if pandoc is available.
if command -v pandoc >/dev/null 2>&1 && [[ -f "$HOME/Documents/
        Claude_Multi_Account_Fine_Tuning.md" ]]; then
  cma_log "running claude-export-docs.sh"
  "$LIB_DIR/claude-export-docs.sh" || cma_warn "doc export failed
        (continuing)"
fi

# 7. SELF-VERIFY, then report honestly.
#
```

```
# The banner below is the toolkit's success claim. It is now
      EARNED, not
# printed unconditionally: claude-install-verify probes the REAL
      artifacts the
# runtime will resolve (it does not grep our own source), so
      "[done]" can no
# longer appear over a product whose router is missing or is the
      npm
# doppelganger. Any recorded build failure from 2b, or any verify
      FAIL, exits
# non-zero with the actionable fix.
if [[ ! -f "$LIB_DIR/claude-install-verify.sh" ]]; then
  # Say WHICH file is missing rather than letting bash emit a bare
  # "No such file or directory" that reads like a bug in the
      installer.

      # A checkout without the gate cannot demonstrate a good
      install, so this is
  # a failure, not a skip — never assume-good on a missing
      verifier.
  CMA_INSTALL_FAILURES+=("post-install self-verify is MISSING
      ($LIB_DIR/claude-install-verify.sh) — this checkout cannot
      prove the install is good. Fix: re-pull the repository.")
elif ! bash "$LIB_DIR/claude-install-verify.sh"; then
  CMA_INSTALL_FAILURES+=("post-install self-verify FAILED — see
      the [FAIL] lines above")
fi

if (( ${#CMA_INSTALL_DEGRADED[@]} > 0 )); then
  printf '\n[warn] claude-multi-account installed with DEGRADED
      optional components:\n' >&2
  for _d in "${CMA_INSTALL_DEGRADED[@]}"; do printf '  - %s\n'
      "$_d" >&2; done
fi

if (( ${#CMA_INSTALL_FAILURES[@]} > 0 )); then
  printf
      '\n[FAILED] claude-multi-account install did NOT complete
      successfully.\n\n' >&2
  for _f in "${CMA_INSTALL_FAILURES[@]}"; do printf '  - %s\n'
      "$_f" >&2; done
  printf '\nNothing above was silently ignored. Fix the items and
      re-run: %s\n' "$LIB_DIR/install.sh" >&2
  printf 'To re-check without a full re-install:  claude-install-
      verify\n' >&2
  exit 1
fi

cat <<EOF

[done] claude-multi-account installed.

  Scripts on PATH:  $BIN_DIR/claude-{unify,add-account,remove-
      account,list-accounts,rollback,export-docs}
```

```
  Kimi on PATH:     $BIN_DIR/kimi-{unify,add-account,remove-
        account,list-accounts,rollback,providers}
  Alias file:       $ALIAS_FILE
  Shared store:     $SHARED_DIR

Open a new shell (or run: source
        $ALIAS_FILE) so the aliases load, then:
  claude-list-accounts            # see what's wired up
  claude-add-account              # add another account
        interactively
  kimi-add-account --alias kimi1  # provision a Kimi Code account
        (device flow)
EOF
```

8.9 tests/lib/assert.sh

```
#!/usr/bin/env bash
# assert.sh — small assertion helpers for the test suite. Each
        helper
# emits `[PASS]` or `[FAIL]` lines and increments counters in the
        caller.
# A test file should source this once and then call the helpers
        inside
# `it` blocks.

TESTS_PASSED="${TESTS_PASSED:-0}"
TESTS_FAILED="${TESTS_FAILED:-0}"
TESTS_FAILURES=()
CURRENT_TEST="${CURRENT_TEST:-(unknown)}"

# Mark the start of an individual test case. Use as:  it "merges
        history.jsonl"
it() {
  CURRENT_TEST="$*"
  printf '\n  • %s\n' "$CURRENT_TEST"
}

_pass() {
  TESTS_PASSED=$((TESTS_PASSED + 1))
  printf '    \033[32m[PASS]\033[0m %s\n' "$1"
}

_fail() {
  TESTS_FAILED=$((TESTS_FAILED + 1))
  TESTS_FAILURES+=("$CURRENT_TEST :: $1")
  printf '    \033[31m[FAIL]\033[0m %s\n' "$1"
  [[ -n "${2:-}" ]] && printf '           %s\n' "$2"
}

assert_eq() {
  local expected="$1" actual="$2" msg="${3:-equality}"
  if [[ "$expected" == "$actual" ]]; then _pass "$msg ($expected)"
```

```
  else _fail "$msg" "want=$expected got=$actual"; fi
}

assert_file() {
  local path="$1" msg="${2:-file exists}"
  if [[ -f "$path" ]]; then _pass "$msg: $path"
  else _fail "$msg" "missing: $path"; fi
}

assert_dir() {
  local path="$1" msg="${2:-dir exists}"
  if [[ -d "$path" ]]; then _pass "$msg: $path"
  else _fail "$msg" "missing dir: $path"; fi
}

# Portable realpath for the harness. BSD/macOS `readlink` has no
      `-f`, so
# `readlink -f` is a hard error there (empty output) — which would
      make the
# symlink assertions below pass/fail spuriously on macOS. Self-
      contained
# (mirrors lib.sh's cma_realpath) so assert.sh works even in test
      files that
# don't source lib.sh (e.g. test_add_remove.sh).
_assert_realpath() {
  local p="$1" t dir base
  while [ -L "$p" ]; do
    t="$(readlink "$p")"
    case "$t" in /*) p="$t" ;; *) p="$(dirname "$p")/$t" ;; esac
  done
  dir="$(cd "$(dirname "$p")" 2>/dev/null && pwd -P)" || dir="$
      (dirname "$p")"
  base="$(basename "$p")"
  printf '%s/%s\n' "$dir" "$base"
}

assert_symlink_to() {
  local link="$1" expected="$2" msg="${3:-symlink target}"
  if [[ ! -L "$link" ]]; then
    _fail "$msg" "not a symlink: $link"
    return
  fi
  local actual; actual="$(_assert_realpath "$link")"
  local want;   want="$(_assert_realpath "$expected")"
  if [[ "$actual" == "$want" ]]; then _pass "$msg: $link ->
      $expected"
  else _fail "$msg" "want=$want got=$actual"; fi
}

assert_not_symlink() {
  local p="$1" msg="${2:-not a symlink}"
  if [[ -L "$p" ]]; then _fail "$msg" "is a symlink: $p"
  else _pass "$msg: $p"; fi
```

```
}

assert_file_contains() {
  local path="$1" needle="$2" msg="${3:-file contains}"
  if grep -F -q -- "$needle" "$path" 2>/dev/null; then _pass
        "$msg: '$needle' in $(basename "$path")"
  else _fail "$msg" "'$needle' not found in $path"; fi
}

assert_file_not_contains() {
  local path="$1" needle="$2" msg="${3:-file lacks}"
  if grep -F -q -- "$needle" "$path" 2>/dev/null; then _fail
        "$msg" "'$needle' found in $path"
  else _pass "$msg: '$needle' absent from $(basename "$path")"; fi
}

assert_jq() {
  local path="$1" expr="$2" expected="$3" msg="${4:-jq check}"
  local actual; actual="$(jq -r "$expr" "$path" 2>/dev/null ||
        echo '<jq-error>')"
  if [[ "$actual" == "$expected" ]]; then _pass "$msg ($expr =
        $expected)"
  else _fail "$msg" "expr=$expr want=$expected got=$actual"; fi
}

assert_lines() {
  local path="$1" expected="$2" msg="${3:-line count}"
  local actual; actual="$(wc -l < "$path" 2>/dev/null || echo 0)"
  actual="${actual// /}"
  if [[ "$actual" == "$expected" ]]; then _pass "$msg ($expected
        lines)"
  else _fail "$msg" "want=$expected got=$actual lines in $path";
        fi
}

# assert_fn_from — assert that a shell FUNCTION was defined by an
        EXPECTED file.
#
#   assert_fn_from FN EXPECTED_FILE [MSG]
#       Check FN as it is defined in the CALLER's shell.
#   assert_fn_from --source FILE FN [MSG]
#       Source FILE in a throwaway subshell first, then check FN's
        provenance
#       there. For call sites whose `source` lives inside a
        `( … )` subshell:
#       only the sourcing is subshelled, so the pass/fail still
        lands in the
#       caller's counters and reaches `summary`.
#
# WHY THIS EXISTS — the guard that failed under the conditions of
        its own bug.
# The login profile exports BASH_ENV=~/.bashrc, so EVERY non-
        interactive bash —
```

```
# including run-all.sh's `bash "$f"` per test — sources the
      PRODUCTION alias file
# before the test's first line. cma_run and cma_run_provider are
      therefore
# ALREADY defined, from the host, in every test shell. A test that
      sources its
# sandbox $ALIAS_FILE and then calls the wrapper looks correct,
      but the tests
# run with `set +e`: if that source silently fails, execution
      falls straight
# through to the fully-working HOST function and the test passes —
      while
# grading live host code instead of the code under test. Tests
      written to prove
# cma_ensure_alias_file emits a correct body then report green for
      exactly the
# regression they exist to catch.
#
# `shopt -s extdebug` makes `declare -F NAME` print "name lineno
      file", which is
# the only way to see WHERE a function came from. Naming both the
      expected and
# the actual file in the failure message is deliberate: "wrong
      provenance" is
# useless without "…it came from the host alias file instead".
assert_fn_from() {
  local file="" fn expected msg src had_extdebug
  if [[ "${1:-}" == "--source" ]]; then
    file="$2"; fn="$3"; expected="$2"; msg="${4:-function
      provenance}"
  else
    fn="$1"; expected="$2"; msg="${3:-function provenance}"
  fi

  if [[ -n "$file" ]]; then
    # set +u: an alias file may reference unset vars while being
      sourced.
    src="$( set +u; source "$file" >/dev/null 2>&1
            shopt -s extdebug; declare -F "$fn" 2>/dev/null | awk
      '{print $3}' )"
  else
    had_extdebug="$(shopt -p extdebug)"
    shopt -s extdebug
    src="$(declare -F "$fn" 2>/dev/null | awk '{print $3}')"
    eval "$had_extdebug"
  fi

  if [[ -z "$src" ]]; then
    _fail "$msg" "$fn is not defined at all (expected it from
      $expected)"
  elif [[ "$src" == "$expected" ]]; then
    _pass "$msg: $fn came from $expected"
  else
```

```
    _fail "$msg" "$fn was defined by $src, NOT by the expected
        $expected"
  fi
}

assert_exit() {
  local expected="$1"; shift
  local out; out="$("$@" 2>&1)"; local rc=$?
  if (( rc == expected )); then _pass "exit $expected for: $*"
  else _fail "exit code mismatch" "want=$expected got=$rc cmd=$*
        out=$out"; fi
}

summary() {
  echo
  if (( TESTS_FAILED == 0 )); then
    printf '\033[32m✓ %d passed, 0 failed\033[0m\n'
        "$TESTS_PASSED"
    return 0
  fi
  printf '\033[31m✗ %d failed, %d passed\033[0m\n'
        "$TESTS_FAILED" "$TESTS_PASSED"
  printf '\nFailures:\n'
  for f in "${TESTS_FAILURES[@]}"; do printf '  - %s\n' "$f"; done
  return 1
}
```

8.10 tests/lib/sandbox.sh

```
#!/usr/bin/env bash
# sandbox.sh — utilities for running scripts against a temp HOME
        so the
# real ~/.claude state is never touched.
#
# Usage from a test file:
#
#   source "$TESTS_DIR/lib/sandbox.sh"
#   make_sandbox          # creates $SANDBOX_HOME, exports HOME,
        etc.
#   make_account acct1    # creates a fake ~/.claude-acct1 inside
        sandbox
#   make_account acct2 --plugins
#   run_unify             # runs claude-unify.sh against the
        sandbox
#   cleanup_sandbox       # rm -rf the sandbox (registered with
        trap)

SCRIPTS_DIR="${SCRIPTS_DIR:-$HOME/Documents/scripts}"

make_sandbox() {
  # Remember the real HOME before overriding, so vendored Go is
        reachable.
  export CMA_REAL_HOME="${HOME:-/home/$(whoami)}"
```

```
  SANDBOX_HOME="$(mktemp -d "${TMPDIR:-/tmp}/cma-test.XXXXXX")"
  # Override every env var the toolkit reads from. Pointing HOME
        at the
  # sandbox is the main switch; the other vars only matter if a
        caller
  # tests defaults explicitly.
  export HOME="$SANDBOX_HOME"
  export SHARED_DIR="$SANDBOX_HOME/.claude-shared"
  export ALIAS_FILE="$SANDBOX_HOME/.local/share/claude-multi-
        account/aliases.sh"
  export DEFAULT_DIR="$SANDBOX_HOME/.claude"
  export ACCOUNT_PREFIX=".claude-"
  export CLAUDE_BIN="/usr/bin/true"  # dummy; we never actually
        launch claude

  # Hermeticity (fixed 2026-09-12): scrub the CALLER's CA
        environment. The
  # toolkit reads CMA_PROVIDER_CA_CERT and derives SSL_CERT_FILE /

        # NODE_EXTRA_CA_CERTS from it, so a developer shell that
        exports it — this

        # host does, pointing at projects/.../helix_llm/certs/
        cert.pem — makes every
  # "provider with NO CA" negative control fail for a reason
        unrelated to the
  # code under test. Three suites (test_ccr_upstream_ca,

        # test_helixllm_model_export, test_kimi_alias_file) each
        carried their own

        # copy of this scrub; centralising it here means no future
        suite can be
  # non-hermetic by omission. Suites that need a CA set it INLINE
        on the
  # command they are testing, which this does not affect.
  unset CMA_PROVIDER_CA_CERT SSL_CERT_FILE NODE_EXTRA_CA_CERTS
  # Point at the real vendored Go toolchain so ccr-build/proxy-
        build work in
  # the sandbox (the sandbox HOME doesn't have ~/.local/share/
        claude-go).
  if [[ -x "$CMA_REAL_HOME/.local/share/claude-go/bin/go" ]]; then
    export VENDORED_GO="$CMA_REAL_HOME/.local/share/claude-go/bin/
        go"
  fi
  mkdir -p "$DEFAULT_DIR" "$SANDBOX_HOME/.local/bin"
  # Self-check: prove the switch actually took before any test
        writes.
  assert_sandboxed
  trap 'cleanup_sandbox' EXIT
}

# assert_sandboxed — abort loudly unless $HOME is a sandbox from
        make_sandbox.
#
```

```
# This exists because a test that writes to $HOME without a
      sandbox does not
# merely fail: in the REAL home, ~/.local/bin/claude-* are
      SYMLINKS into this
# repo (install.sh links every claude-*.sh there), and `cat >`
      follows symlinks.
# A single unsandboxed stub write therefore destroys the
      production script it
# points at. That is not hypothetical — it silently truncated
# scripts/claude-session.sh from 201 lines to an 8-line stub and
# scripts/claude-sync-state.sh from 103 lines to 2, which broke
      every provider
# alias with "No conversation found with session ID:
      11111111-2222-...".
#
# Exits 99 rather than returning: there is no safe way to
      continue.
assert_sandboxed() {
  case "$(basename "${HOME:-/}")" in
    cma-test.*) return 0 ;;
  esac
  echo "FATAL: test tried to use HOME=${HOME:-<unset>}, which is
      not a make_sandbox temp dir." >&2
  echo "       Refusing to continue: writes under the real \$HOME
      follow symlinks into the repo" >&2
  echo "       and would destroy production scripts. Call
      make_sandbox first." >&2
  exit 99
}

# sandbox_stub PATH — install an executable stub (content on
      stdin) inside the
# sandbox. Use this instead of `cat > "$HOME/..."` for anything
      under
# $HOME/.local/bin.
#
# Three guarantees a bare `cat >` does not give:
#   1. $HOME is a real sandbox (assert_sandboxed).
#   2. The target is INSIDE that sandbox — a path that escaped it
      is a bug.
#   3. An existing symlink is REMOVED before writing, never
      written through.
#      Guarantee 3 is the one that matters: it is what turns
      "clobbered a
#      production script" into "replaced a link inside a temp
      dir".
sandbox_stub() {
  local target="$1"
  assert_sandboxed
  case "$target" in
    "$HOME"/*) : ;;
    *) echo "FATAL: sandbox_stub target escapes the sandbox:
      $target" >&2; exit 99 ;;
  esac
  mkdir -p "$(dirname "$target")"
```

```
  # Break the link rather than following it.
  [[ -L "$target" ]] && rm -f -- "$target"
  cat > "$target"
  chmod +x "$target"
}

cleanup_sandbox() {
  [[ -n "${SANDBOX_HOME:-}" && -d "$SANDBOX_HOME" ]] || return 0
  # Safety net: only delete if the path matches what mktemp would
        have
  # produced (cma-test.* somewhere under a tempdir root).
        Different
  # systems put mktemp output in different places (/tmp on most
        Linux,

        # /tmp/.private/<user>/ on this host, /var/folders/... on
        macOS) so
  # we anchor on the cma-test. prefix rather than the parent.
  case "$(basename "$SANDBOX_HOME")" in
    cma-test.*)
      # Go installs its module cache read-only (0444 files, 0555
        dirs), so a
      # plain `rm -rf` fails with EACCES partway through and
        leaves a
      # ~13.5k-file `go/pkg/mod` skeleton behind on EVERY run of
        any
      # Go-building test. Because the sandbox IS $HOME, each such
        test also
      # re-downloads the whole cache — 500-850MB per sandbox,
        unshared — so the
      # residue is the dominant term in sandbox leakage (109
        orphans totalling
      # 35GB were measured before this was fixed).
      #

        # Restore write permission first so the removal can
        actually complete.
      # Safe by construction: this only ever runs inside a path
        whose basename
      # matched cma-test.*, i.e. a mktemp dir this suite created.
      chmod -R u+w -- "$SANDBOX_HOME" 2>/dev/null || true
      rm -rf -- "$SANDBOX_HOME"
      ;;
    *) echo "refusing to rm sandbox at unexpected path:
        $SANDBOX_HOME" >&2 ;;
  esac
}

# make_account NAME [--plugins] [--settings JSON] [--history
        "line1|line2"] [--memory KEY:VALUE...]
make_account() {
  local name="$1" with_plugins=0 settings_json="" history_lines=()
  shift
  local memory_entries=() todo_entries=()
```

```
while (( $# )); do
  case "$1" in
    --plugins) with_plugins=1; shift ;;
    --settings) settings_json="$2"; shift 2 ;;
    --history) IFS='|' read -r -a history_lines <<< "$2"; shift
      2 ;;
    --memory)  memory_entries+=("$2"); shift 2 ;;
    --todo)    todo_entries+=("$2"); shift 2 ;;
    *) echo "make_account: unknown arg $1" >&2; return 1 ;;
  esac
done

local dir="$HOME/${ACCOUNT_PREFIX}${name}"
mkdir -p "$dir/projects/-home-test/memory" "$dir/todos" "$dir/
      tasks" \
         "$dir/plans" "$dir/file-history" "$dir/paste-cache" \
         "$dir/shell-snapshots" "$dir/session-env" "$dir/
      telemetry" \
         "$dir/sessions" "$dir/backups" "$dir/cache" "$dir/
      plugins"

# Fake credentials so list-accounts reports CREDS:yes.
printf '{"account":"%s"}\n' "$name" > "$dir/.credentials.json"
printf '{"name":"%s"}\n' "$name" > "$dir/.claude.json"

# A unique transcript so the union-merge step has something to
      merge.
printf '{"role":"user","msg":"hi from %s"}\n' "$name" \
  > "$dir/projects/-home-test/$(uuidgen 2>/dev/null || echo
      "session-${name}").jsonl"

# Memory + todo content if requested.
local m
for m in ${memory_entries[@]+"${memory_entries[@]}"}; do
  local k="${m%%:*}" v="${m#*:}"
  printf -- '%s\n' "$v" > "$dir/projects/-home-test/memory/$
      {k}.md"
done
local t
for t in ${todo_entries[@]+"${todo_entries[@]}"}; do
  printf '{"subject":"%s"}\n' "$t" > "$dir/todos/$(uuidgen 2>/
      dev/null || echo "todo-${name}-$t").json"
done

# History lines (used to test concat+dedup later).
if (( ${#history_lines[@]} )); then
  printf '%s\n' "${history_lines[@]}" > "$dir/history.jsonl"
fi

# Settings JSON if specified, else a minimal default.
if [[ -n "$settings_json" ]]; then
  printf '%s\n' "$settings_json" > "$dir/settings.json"
else
```

```
    printf '{"enabledPlugins":{"%s-plugin":true}}\n' "$name" >
        "$dir/settings.json"
  fi

  if (( with_plugins )); then
    mkdir -p "$dir/plugins/cache/test-marketplace/test-plugin/
        1.0.0"
    mkdir -p "$dir/plugins/marketplaces/test-marketplace"
    cat > "$dir/plugins/installed_plugins.json" <<EOF
{
  "version": 2,
  "plugins": {
    "test-plugin@test-marketplace": [
      {
        "scope": "project",
        "installPath": "$dir/plugins/cache/test-marketplace/test-
        plugin/1.0.0",
        "version": "1.0.0"
      }
    ]
  }
}
EOF
    cat > "$dir/plugins/known_marketplaces.json" <<EOF
{
  "test-marketplace": {
    "source": {"source": "github", "repo": "example/test"},
    "installLocation": "$dir/plugins/marketplaces/test-
        marketplace"
  }
}
EOF
  fi

  echo "$dir"
}

run_unify() {
  "$SCRIPTS_DIR/claude-unify.sh" "$@"
}

run_add_account() {
  "$SCRIPTS_DIR/claude-add-account.sh" "$@"
}

run_remove_account() {
  "$SCRIPTS_DIR/claude-remove-account.sh" "$@"
}

run_list_accounts() {
  "$SCRIPTS_DIR/claude-list-accounts.sh" "$@"
}
```

```
run_rollback() {
  "$SCRIPTS_DIR/claude-rollback.sh" "$@"
}
```

8.11 tests/run-all.sh

```
#!/usr/bin/env bash
# run-all.sh — discover every test_*.sh sibling, run each in its
        own
# subshell, and tally pass/fail.
#
# Exit code is 0 only if every test file's `summary` returned 0.

set -uo pipefail

TESTS_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
SCRIPTS_DIR="$(cd "$TESTS_DIR/.." && pwd)"
export SCRIPTS_DIR

# SERIALIZATION: two suite runs must never overlap — a repo that
        mutates while
# its own tests execute produces results that cannot be
        reproduced. Silent on
# the normal path; prints only when it actually contends. When
        run-proof.sh is
# the caller this legitimately inherits the lock instead of
        deadlocking on it.
# shellcheck source=lib/suite-lock.sh
source "$TESTS_DIR/lib/suite-lock.sh"
cma_suite_lock_acquire suite

FILES=()
if (( $# )); then
  for arg in "$@"; do FILES+=("$TESTS_DIR/test_${arg}.sh"); done
else
  # Portable discovery: `mapfile`/`readarray` are bash 4+ and
        absent on the
  # bash 3.2 that ships with macOS, where this test runner must
        also run.
  while IFS= read -r _f; do FILES+=("$_f"); done \
    < <(find "$TESTS_DIR" -maxdepth 1 -name 'test_*.sh' -type f |
        sort)
fi

PASSED=0 FAILED=0 SKIPPED=0 FAILED_FILES=()

# "${FILES[@]+...}" guards against an empty array under `set -u`
        on bash 3.2,
# which (unlike bash 4.4+) treats "${FILES[@]}" on an empty array
        as unbound.
for f in "${FILES[@]+"${FILES[@]}"}"; do
```

```
  [[ -f "$f" ]] || { echo "missing: $f" >&2; FAILED=$
        ((FAILED+1)); FAILED_FILES+=("$f"); continue; }
  printf '\n\033[1m==> %s\033[0m\n' "$(basename "$f")"

        # Capture output while still streaming it, so we can
        cross-check the printed
  # result against the exit code (see harness-integrity check
        below).
  _out="$(mktemp "${TMPDIR:-/tmp}/cma-runall.XXXXXX")"
  bash "$f" 2>&1 | tee "$_out"
  _rc=${PIPESTATUS[0]}

  # HARNESS INTEGRITY (defense in depth): a file's exit code is
        the ONLY thing
  # this runner tallies, and `summary` is what turns TESTS_FAILED
        into a

        # non-zero exit. A file that prints [FAIL] but exits 0
        means its summary call
  # is missing/bypassed — the failures would otherwise be counted
        as a PASS.
  # This really happened: test_providers.sh lacked `summary` and
        hid 5 real
  # failures behind a green run. Never trust a 0 that contradicts
        the output.
  if (( _rc == 0 )) && grep -q '\[FAIL\]' "$_out"; then
    printf '\033[31m[HARNESS] %s printed [FAIL] but exited 0 —
        missing summary?\033[0m\n' \
      "$(basename "$f")" >&2
    _rc=1
  fi
  # Visibility: a file that SKIPs on a missing prerequisite exits
        0 and would
  # otherwise be indistinguishable from a genuine pass in "ALL
        GREEN".
  if (( _rc == 0 )) && grep -q '^SKIP' "$_out"; then
    SKIPPED=$((SKIPPED + 1))
  fi
  rm -f "$_out"

  if (( _rc == 0 )); then
    PASSED=$((PASSED + 1))
  else
    FAILED=$((FAILED + 1))
    FAILED_FILES+=("$(basename "$f")")
  fi
done

echo
echo "========================================="
echo "Test files: $((PASSED + FAILED))   passed: $PASSED
        failed: $FAILED   (skipped-prereq: $SKIPPED)"
if (( FAILED )); then
  echo "Failed files:"
```

```
  for f in "${FAILED_FILES[@]}"; do echo "  - $f"; done
  exit 1
fi
echo "ALL GREEN"
```

8.12 tests/test_lib.sh

```
#!/usr/bin/env bash
# test_lib.sh — unit tests for the helper functions in lib.sh.
set -uo pipefail

TESTS_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
SCRIPTS_DIR="$(cd "$TESTS_DIR/.." && pwd)"

# shellcheck source=lib/assert.sh
source "$TESTS_DIR/lib/assert.sh"
# shellcheck source=lib/sandbox.sh
source "$TESTS_DIR/lib/sandbox.sh"

make_sandbox
# shellcheck source=../lib.sh
source "$SCRIPTS_DIR/lib.sh"
# lib.sh enables `set -e`. The test harness is intentionally
        tolerant of
# non-zero exits (we assert on them), so turn it back off here.
set +e

it "cma_validate_alias accepts well-formed names"
( set -e; cma_validate_alias "claude3" ); assert_eq 0 $? "claude3"
( set -e; cma_validate_alias "work_acct-1" ); assert_eq 0 $?
        "work_acct-1"

it "cma_validate_alias rejects invalid names"
( cma_validate_alias "3claude" >/dev/null 2>&1 ); assert_eq 1 $?
        "rejects digit-leading"
( cma_validate_alias "bad name" >/dev/null 2>&1 ); assert_eq 1 $?
        "rejects spaces"
( cma_validate_alias "" >/dev/null 2>&1 ); assert_eq 1 $?
        "rejects empty"

it "cma_suggest_alias starts at claude1 when nothing exists"
suggestion="$(cma_suggest_alias)"
assert_eq "claude1" "$suggestion" "first suggestion"

it "cma_suggest_alias increments past existing claudeN aliases"
cma_write_alias claude1 "$HOME/.claude-acct1"
cma_write_alias claude2 "$HOME/.claude-acct2"
cma_write_alias claude5 "$HOME/.claude-acct5"   # gap
suggestion="$(cma_suggest_alias)"
assert_eq "claude6" "$suggestion" "skips past highest, not count"
```

```
it "cma_write_alias is idempotent — rewriting same alias doesn't
        duplicate"
cma_write_alias claude1 "$HOME/.claude-acct1"   # second write
count="$(grep -c '^alias claude1=' "$ALIAS_FILE")"
assert_eq "1" "$count" "one alias line for claude1"

it "cma_remove_alias removes the line"
cma_remove_alias claude5
assert_file_not_contains "$ALIAS_FILE" "alias claude5=" "claude5
        removed"

it "cma_ensure_alias_file sources from the shell rc file"
# lib.sh manages .zshrc on macOS and .bashrc + .zshrc on Linux
        (CMA_RC_FILES).
# Assert against the platform-appropriate target, selected the
        same way lib.sh
# selects it, so the test is correct on both OSes.
if [[ "$(uname -s)" == "Darwin" ]]; then RC_FILE="$HOME/.zshrc";
        else RC_FILE="$HOME/.bashrc"; fi
touch "$RC_FILE"
rm -f "$ALIAS_FILE"
cma_ensure_alias_file
assert_file "$ALIAS_FILE" "alias file created"
assert_file_contains "$RC_FILE" "source \"$ALIAS_FILE\"" "rc file
        gets source line"

it "cma_detect_accounts skips the shared store"
mkdir -p "$HOME/.claude-shared" "$HOME/.claude-acct1"
found=(); while IFS= read -r _l; do found+=("$_l"); done <
        <(cma_detect_accounts)
joined="${found[*]:-}"
cond=1; [[ "$joined" == *".claude-acct1"* ]] && cond=0; assert_eq
        0 "$cond" "finds .claude-acct1"
cond=1; [[ "$joined" != *".claude-shared"* ]] && cond=0;
        assert_eq 0 "$cond" "excludes .claude-shared"

it "cma_detect_accounts excludes non-Claude .claude-* dirs
        (e.g. .claude-server-commander)"
# Mimic the real-world false positive seen on mistborn.local: an
        MCP server
# config dir whose name happens to start with .claude- but has
        only its own
# config files, no Claude markers.
mkdir -p "$HOME/.claude-server-commander"
printf '{}\n' > "$HOME/.claude-server-commander/config.json"
printf '{}\n' > "$HOME/.claude-server-commander/feature-
        flags.json"
found=(); while IFS= read -r _l; do found+=("$_l"); done <
        <(cma_detect_accounts)
joined="${found[*]:-}"
cond=1; [[ "$joined" != *".claude-server-commander"* ]] &&
        cond=0; assert_eq 0 "$cond" "excludes .claude-server-
        commander"
cond=1; [[ "$joined" == *".claude-acct1"* ]] && cond=0; assert_eq
        0 "$cond" "still finds the legit empty account"
```

```
it "cma_detect_accounts includes a populated account dir even if
        it has foreign config too"
# A real account dir with the Claude marker (projects/) shouldn't
        get
# falsely excluded just because some other file happens to be
        there.
mkdir -p "$HOME/.claude-real/projects"
printf '{}\n' > "$HOME/.claude-real/some-other-tool.json"
found=(); while IFS= read -r _l; do found+=("$_l"); done <
        <(cma_detect_accounts)
joined="${found[*]:-}"
cond=1; [[ "$joined" == *".claude-real"* ]] && cond=0; assert_eq
        0 "$cond" "finds .claude-real"

it "cma_realpath resolves a symlink chain to its canonical target
        (no readlink -f)"
mkdir -p "$HOME/rp/real"
: > "$HOME/rp/real/file"
ln -s "$HOME/rp/real/file" "$HOME/rp/link1"
ln -s "$HOME/rp/link1" "$HOME/rp/link2"
        # chain: link2 -> link1 -> real/file
got="$(cma_realpath "$HOME/rp/link2")"
want="$(cd "$HOME/rp/real" && pwd -P)/file"
assert_eq "$want" "$got" "cma_realpath follows the symlink chain"
# A plain (non-symlink) path canonicalizes to itself.
got2="$(cma_realpath "$HOME/rp/real/file")"
assert_eq "$want" "$got2" "cma_realpath is identity on a real
        path"

it "no runtime script INVOKES 'readlink -f' (absent on BSD/macOS)"
# Strip comments first so explanatory comments mentioning the flag
        don't count;
# we only care about real invocations. kimi-*.sh is in the same
        loop (v1.27.0)
# so the family can never drift into a GNU-only construct.
hits="$(for f in "$SCRIPTS_DIR"/lib.sh "$SCRIPTS_DIR"/install.sh
        "$SCRIPTS_DIR"/claude-*.sh "$SCRIPTS_DIR"/kimi-*.sh; do
        sed 's/#.*//' "$f"; done 2>/dev/null | grep -c 'readlink
        -f')"
assert_eq 0 "$hits" "zero 'readlink -f' invocations in runtime
        scripts"

it "no committed proof artifact contains a literal secret"
# Regression guard for the H2 incident: live proof files (opencode
        debug config /
# mcp list) once committed a real API key + a DB connection-string
        password.
# We count *suspect* lines rather than print them, so a failure
        never re-echoes a
# secret into the test log. Provider-key prefixes + URL
        user:password@ are the
# signatures; redacted placeholders carry the word REDACTED and
        are excluded.
proof_dir="$SCRIPTS_DIR/tests/proof"
```

```
if [[ -d "$proof_dir" ]]; then
  # Prefixes match only at a TOKEN BOUNDARY (line start or a non-
        word char
  # before them): a real leaked key appears after a quote/=/:/
        space (e.g.
  # "api_key":"sk-ant-…"), never embedded mid-identifier. Without
        the boundary,
  # innocent identifiers captured in build/log noise false-
        positive — e.g. `re_`
  # inside a Go-cache path `retire_connection_id_frame_test.go`,
        or `secret_`
  # inside `my_secret_value`.
  leaks="$(grep -rIE \
    -e '(^|[^A-Za-z0-9_-])(sk-ant-|sk-|gsk_|xai-|hf_|AIza|xoxb-|
        xoxp-|xoxs-|pc-|re_|secret_|ghp_|github_pat_|AKIA)[A-Za-
        z0-9_-]{12,}' \
    -e '://[^:/@ "]+:[^@/ "]{4,}@' \
    -e 'eyJ[A-Za-z0-9_-]{10,}\.[A-Za-z0-9_-]{10,}\.[A-Za-z0-9_-]
        {10,}' \
    "$proof_dir" 2>/dev/null | grep -vc 'REDACTED' || true)"
  [[ -z "$leaks" ]] && leaks=0
  assert_eq 0 "$leaks" "proof dir free of literal secrets
        (suspect-line count)"
else
  _pass "no proof dir on this host (nothing to scan)"
fi

# Regression guard for the token-boundary anchor (a Go-cache path
# `retire_connection_id_frame_test.go` in captured build noise
        once false-
# positived on the `re_` prefix). The scanner MUST ignore a secret
        prefix
# embedded mid-identifier, yet still catch a real key at a token
        boundary.
it "proof-secret scanner: boundary-anchored (embedded prefix
        ignored, real key caught)"
_scan_fx="$(mktemp -d "${TMPDIR:-/tmp}/cma-scanfx.XXXXXX")"
{
  echo "rm: cannot remove '/go/pkg/mod/quic-go/internal/wire/
        retire_connection_id_frame_test.go'"
  echo "my_secret_value_identifier_here = 1"
} > "$_scan_fx/noise.log"
printf '"api_key":"sk-ant-abc123def456ghi789jkl"\n' > "$_scan_fx/
        leak.log"
_scan_re='(^|[^A-Za-z0-9_-])(sk-ant-|sk-|gsk_|xai-|hf_|AIza|xoxb-|
        xoxp-|xoxs-|pc-|re_|secret_|ghp_|github_pat_|AKIA)[A-Za-
        z0-9_-]{12,}'
_scan_noise="$(grep -cE "$_scan_re" "$_scan_fx/noise.log" ||
        true)"
_scan_leak="$(grep -cE "$_scan_re" "$_scan_fx/leak.log" || true)"
assert_eq 0 "${_scan_noise:-0}" "embedded prefixes (retire_/
        my_secret_) are NOT flagged"
assert_eq 1 "${_scan_leak:-0}" "a real boundary-anchored sk-ant-
        key IS flagged"
rm -rf "$_scan_fx"
```

```
# cma_merge_claude_json must UNION the projects subtree across
        accounts while
# keeping each account's private auth keys (userID/
        oauthAccount/...) to ITSELF.
# A regression here would either lose sessions (no union) or leak
        credentials
# between accounts (CRITICAL). Locks the property verified by hand
        this session.
it
        "cma_merge_claude_json: private keys stay per-account;
        projects union (no credential leak)"
if command -v jq >/dev/null 2>&1; then
  mj_a="$SANDBOX_HOME/.mrg-a"; mj_b="$SANDBOX_HOME/.mrg-b"; mkdir
        -p "$mj_a" "$mj_b"
  printf '%s\n' '{"userID":"UID-
        A","oauthAccount":"a@x","projects":{"pa":{"v":1}}}' >
        "$mj_a/.claude.json"
  printf '%s\n' '{"userID":"UID-
        B","oauthAccount":"b@x","projects":{"pb":{"v":2}}}' >
        "$mj_b/.claude.json"
  cma_merge_claude_json "$mj_a" "$mj_b" >/dev/null 2>&1
  assert_eq "UID-A" "$(jq -r .userID "$mj_a/.claude.json")"
        "account A keeps its OWN userID after merge"
  assert_eq "UID-B" "$(jq -r .userID "$mj_b/.claude.json")"
        "account B keeps its OWN userID after merge"
  assert_eq '["pa","pb"]' "$(jq -rc '.projects|keys'
        "$mj_a/.claude.json")" "A sees both projects (union)"
  assert_eq '["pa","pb"]' "$(jq -rc '.projects|keys'
        "$mj_b/.claude.json")" "B sees both projects (union)"
  mj_leak=0
  grep -q 'UID-B\|b@x' "$mj_a/.claude.json" && mj_leak=1
  grep -q 'UID-A\|a@x' "$mj_b/.claude.json" && mj_leak=1
  assert_eq 0 "$mj_leak" "no cross-account credential leak in
        either direction"
else
  _pass "jq absent — skipping cma_merge_claude_json security test"
fi

it "cma_ensure_alias_file generates cma_run with project-scoped
        cwd-hook resolution"
# Verify the emitted cma_run body has the _cma_hook_root marker
        (project-local
# .claude-cwd-hook support) and the three-tier resolution order:
# 1. CMA_CWD_HOOK env var  2. <git-toplevel>/.claude-cwd-hook  3.
        global fallback
_mig_ph="$ALIAS_FILE.ph"
cat > "$_mig_ph" <<'PHFMT'
export CLAUDE_BIN="/usr/bin/true"

cma_run() {
  "$CLAUDE_BIN" "$@"
}

alias claude1="CLAUDE_CONFIG_DIR=$SANDBOX_HOME/.claude-1 cma_run"
```

```
PHFMT
( ALIAS_FILE="$_mig_ph" cma_ensure_alias_file ) >/dev/null 2>&1
# Extract the regenerated cma_run body and check the markers
_ph_body="$(awk '/^cma_run\(\) ?\{/{f=1} f{print} f&&/^}/{exit}'
        "$_mig_ph")"
grep -q '_cma_hook_root' <<<"$_ph_body"; assert_eq 0 $? "cma_run
        has _cma_hook_root marker (project-scoped hook support)"
# With no CMA_CWD_HOOK set, should check git toplevel first, then
        global
grep -q 'git rev-parse --show-toplevel' <<<"$_ph_body"; assert_eq
        0 $? "cma_run resolves git toplevel for project-local
        hook"
grep -q '\.claude-cwd-hook' <<<"$_ph_body"; assert_eq 0 $?
        "cma_run checks for .claude-cwd-hook in project root"
grep -q 'CMA_CWD_HOOK:-' <<<"$_ph_body"; assert_eq 0 $? "cma_run
        respects CMA_CWD_HOOK env var override"
grep -q '.local/bin/claude-cwd-hook' <<<"$_ph_body"; assert_eq 0
        $? "cma_run falls back to global claude-cwd-hook"
rm -f "$_mig_ph"

# --- wrapper self-heal is unconditional, not marker-driven
        -------------------
# HISTORY: cma_ensure_alias_file used to decide whether to
        regenerate each
# wrapper by matching ~22 "markers" against the on-disk body, then
        DROPPING the
# function block and re-appending it. That drop-then-re-append
        left the file
# without the function between two separate whole-file writes —
        one half of the
# concurrency race that destroyed the live alias file (see the
        alias-file
# section header in lib.sh). The renderer now always emits the
        current wrapper
# text, so there is no marker list, no drop window, and no stale
        body can
# survive a write.
#
# What still must hold: emitting the current body may never be
        short-circuited
# by a cached version stamp. A corrupted body with an intact stamp
        line would
# otherwise be wrongly trusted and the self-heal skipped
# (test_128k_output_clamp.sh deliberately constructs exactly that
        shape).
# The behavioural half of this is the cwd-hook regeneration test
        above, which
# feeds in a stale cma_run body and asserts the current one comes
        back.
it "wrapper regeneration has no marker/version-stamp short-
        circuit"
_mk_body="$(awk '/^_cma_alias_render\(\) ?\{/{f=1} f{print} f&&/
        ^}/{exit}' "$SCRIPTS_DIR/lib.sh")
$(awk '/^_cma_emit_managed\(\) ?\{/{f=1} f{print} f&&/^}/{exit}'
        "$SCRIPTS_DIR/lib.sh")"
```

```
_mk_stamp="$(grep -ciE 'version.?stamp|CMA_ALIAS_VERSION'
        <<<"$_mk_body" || true)"
assert_eq 0 "$_mk_stamp" "no version-stamp short-circuit (would
        skip a needed self-heal)"
_mk_cond="$(grep -cE 'grep -q.*cma_run(_provider)?\(\)'
        <<<"$_mk_body" || true)"
assert_eq 0 "$_mk_cond" "wrapper emission is unconditional (not
        gated on the old body)"

it "\$ALIAS_FILE has exactly one writer"
# Nothing outside cma_alias_commit may write, append to, or rename
        onto the
# alias file. That single-committer property is what makes the
        exclusive lock
# and the sanity gate impossible to bypass — the incident was two
        writers, each
# individually correct, interleaving.
_wr="$(grep -nE '(command )?mv +-?f? *"?\$[A-Za-z_]+" *"\
        $ALIAS_FILE"|> *"\$ALIAS_FILE"|>> *"\$ALIAS_FILE"' \
        "$SCRIPTS_DIR"/*.sh | grep -v ':[0-9]*: *#' || true)"
_wr_n="$(printf '%s\n' "$_wr" | grep -c . || true)"
assert_eq 1 "$_wr_n" "exactly one writer of \$ALIAS_FILE remains"
        "$_wr"

# ============================================================================
# The ccr self-reference guard: ONE definition, and it matches the
        whole shape
# ============================================================================
# The original guard was a `case` listing four literal spellings,
        DUPLICATED in
# lib.sh's launch gate and providers-verify.sh's Gate 0.
        Everything it did not
# literally list went through — including `127.0.1.1:3456`, which
        is Debian's
# default loopback for the local hostname, i.e. a form that IS the
        gateway on a
# stock install. Both halves matter and both are asserted here:
        that the two
# call sites share one definition, and that the definition covers
        the shape.
it "the ccr-gateway guard has exactly one definition (no drifting
        copy)"
# lib.sh owns it; providers-verify.sh must CALL it, never re-
        implement it.
_gw_defs="$(grep -c '^_cma_is_ccr_gateway() {' "$SCRIPTS_DIR/
        lib.sh" || true)"
assert_eq 1 "${_gw_defs:-0}" "_cma_is_ccr_gateway defined once in
        lib.sh"
_gw_dup="$(grep -c '_cma_is_ccr_gateway() {' "$SCRIPTS_DIR/
        providers-verify.sh" || true)"
assert_eq 0 "${_gw_dup:-0}" "providers-verify.sh does not re-
        define it"
_gw_call="$(grep -c '_cma_is_ccr_gateway ' "$SCRIPTS_DIR/
        providers-verify.sh" || true)"
_gw_ok=1; (( _gw_call >= 1 )) && _gw_ok=0
```

```
assert_eq 0 "$_gw_ok" "providers-verify.sh calls the shared
        helper"
# The literal-spelling `case` that under-matched must be gone from
        both.
_gw_legacy="$(grep -cE '127\.0\.0\.1:"?\$(_ccr_port|\
        {CMA_CCR_PORT)' \
               "$SCRIPTS_DIR/lib.sh" "$SCRIPTS_DIR/providers-
        verify.sh" 2>/dev/null \
            | awk -F: '{s+=$2} END{print s+0}')"
assert_eq 0 "${_gw_legacy:-0}" "the duplicated literal-spelling
        case is gone"

it "the ccr-gateway guard matches every form that IS the gateway"
# Each of these resolves to the local ccr gateway on port 3456.
        Every one of
# them was ALLOWED through by the old guard.
_gw_missed=""
for _u in \
  'http://127.0.0.1:3456/v1' \
  'http://localhost:3456/v1' \
  'http://[::1]:3456/v1' \
  'http://0.0.0.0:3456/v1' \
  'http://127.0.1.1:3456/v1' \
  'http://127.0.0.2:3456/v1' \
  'http://127.255.255.254:3456/v1' \
  'http://[::ffff:127.0.0.1]:3456/v1' \
  'http://[0:0:0:0:0:0:0:1]:3456/v1' \
  'http://[0::1]:3456/v1' \
  'http://LOCALHOST:3456/v1' \
  'http://LocalHost:3456' \
  'http://user@127.0.0.1:3456/v1' \
  'http://user:pw@localhost:3456/v1' \
  'http://127.0.0.1:3456?x=1' \
  'http://127.0.0.1:3456#frag' \
  'http://127.0.0.1:3456/v1?x=1' \
  'http://127.0.0.1:3456' \
; do
  _cma_is_ccr_gateway "$_u" || _gw_missed="$_gw_missed $_u"
done
assert_eq "" "$_gw_missed" "no gateway spelling slips through"
        "missed:$_gw_missed"

it "the ccr-gateway guard does NOT false-positive on legitimate
        bases"
# A guard that refuses everything is not a fix. These must all
        still launch.
_gw_false=""
for _u in \
  'http://127.0.0.1:8080/v1' \
  'http://127.0.0.1:3457/v1' \
  'http://localhost:3457/v1' \
  'http://localhost/v1' \
  'https://api.deepseek.com/anthropic' \
```

```
  'https://api.z.ai/api/coding/paas/v4' \
  'https://openrouter.ai/api/v1' \
  'http://192.168.1.10:3456/v1' \
  'http://10.0.0.5:3456/v1' \
  'https://127.0.0.1.example.com:3456/v1' \
  'http://[fe80::1]:3456/v1' \
  'http://[2001:db8::1]:3456/v1' \
  'https://api.test/v1' \
  'http://myhost:3456/v1' \
; do
  _cma_is_ccr_gateway "$_u" && _gw_false="$_gw_false $_u"
done
assert_eq "" "$_gw_false" "no legitimate base is swept up" "false
        positives:$_gw_false"

it "the ccr-gateway guard honours a non-default CMA_CCR_PORT"
( CMA_CCR_PORT=9999; _cma_is_ccr_gateway 'http://127.0.0.1:9999/
        v1' ); assert_eq 0 $? "9999 is the gateway when
        CMA_CCR_PORT=9999"
( CMA_CCR_PORT=9999; _cma_is_ccr_gateway 'http://127.0.0.1:3456/
        v1' ); assert_eq 1 $? "3456 is NOT the gateway when
        CMA_CCR_PORT=9999"

# ============================================================================
# Account detection must not count directories that are no longer
        accounts
# ============================================================================
it "cma_detect_accounts ignores archived (.removed.*)
        and .preunify.* dirs"
# claude-remove-account's DEFAULT (non---delete) mode renames the
        config dir to
# `<dir>.removed.<ts>`, which keeps its projects/ marker. Counting
        those kept
# the detected total permanently above the alias count, and
        _cma_alias_gate's
# account floor arms only while `src_acct >= n_acct` — so a single
        ordinary
# removal disarmed that floor forever on that host.
_det_home="$(mktemp -d "$HOME/detect.XXXXXX")"
mkdir -p "$_det_home/.claude-one/projects" "$_det_home/.claude-
        two/projects"
mkdir -p "$_det_home/.claude-three.removed.20260101120000/
        projects"
mkdir -p "$_det_home/.claude-four.preunify.20260101120000/
        projects"
_det_n="$( HOME="$_det_home" cma_detect_accounts | wc -l | tr -d
        ' ' )"
assert_eq 2 "$_det_n" "only the two live accounts are detected" \
  "$(HOME="$_det_home" cma_detect_accounts)"
_det_arch="$( HOME="$_det_home" cma_detect_accounts | grep -c
        'removed\|preunify' || true )"
assert_eq 0 "${_det_arch:-0}" "no archived dir appears in the
        detected set"
```

```
# ============================================================================
# The renderer must not report success for a write it did not make
# ============================================================================
it "_cma_alias_render propagates an output write failure"
# The `{ ... } > \$out` status used to be discarded and the
        function always
# returned 0. A candidate truncated by ENOSPC then reached the
        committer as a
# successful render — and against a zero-alias source such a stump
        also clears
# the sanity gate, which only requires the header plus the two
        wrapper opening
# lines and has no aliases left to miss.
rm -f "$ALIAS_FILE"; cma_ensure_alias_file >/dev/null 2>&1
# (a) the output path cannot be opened at all
( _cma_alias_render "$ALIAS_FILE" "" "" keep "$HOME/no/such/dir/
        cand" ) >/dev/null 2>&1
assert_eq 1 $? "an unopenable output path is a failed render"
# (b) a genuine ENOSPC. /dev/full accepts the open and fails every
        write, which
#     is the real shape of the hazard. Linux-only; skipped
        elsewhere.
if [[ -w /dev/full ]]; then
  ( _cma_alias_render "$ALIAS_FILE" "" "" keep /dev/full ) >/dev/
        null 2>&1
  assert_eq 1 $? "an ENOSPC write (/dev/full) is a failed render"
else
  _pass "SKIP (no writable /dev/full on this platform)"
fi
# CONTROL: a healthy render still succeeds.
( _cma_alias_render "$ALIAS_FILE" "" "" keep "$HOME/.cand-ok" ) >/
        dev/null 2>&1
assert_eq 0 $? "CONTROL: a normal render still returns success"

# ============================================================================
# The alias lock is scoped to the file it guards, not to the host
# ============================================================================
it "the alias lock is per-\$ALIAS_FILE — two alias files never
        contend"
# Deliberately the OPPOSITE of tests/lib/suite-lock.sh, which is
        global by
# design (one suite run per checkout, lock in the git dir). If
        this lock were
# global, every sandbox — and every $HOME on a multi-user box —
        would serialize
# against unrelated runs for up to CMA_ALIAS_LOCK_WAIT.
_lk_a="$HOME/lockscope-a/aliases.sh"
_lk_b="$HOME/lockscope-b/aliases.sh"
mkdir -p "$(dirname "$_lk_a")" "$(dirname "$_lk_b")"
cat > "$HOME/lockscope-hold.sh" <<'LK_EOF'
#!/usr/bin/env bash
set -uo pipefail
source "$SCRIPTS_DIR/lib.sh"; set +e
_cma_alias_lock_acquire || exit 9
```

```
: > "$HOME/.lockscope-held"
sleep 4
LK_EOF
chmod +x "$HOME/lockscope-hold.sh"
rm -f "$HOME/.lockscope-held"
SCRIPTS_DIR="$SCRIPTS_DIR" ALIAS_FILE="$_lk_a" "$HOME/lockscope-
        hold.sh" & _lk_pid=$!
_lk_w=0
while [[ ! -f "$HOME/.lockscope-held" ]] && (( _lk_w < 400 )); do
        sleep 0.01 2>/dev/null || sleep 1; _lk_w=$(( _lk_w +
        1 )); done
# B must acquire instantly even at zero wait: it protects a
        DIFFERENT file.
SCRIPTS_DIR="$SCRIPTS_DIR" ALIAS_FILE="$_lk_b"
        CMA_ALIAS_LOCK_WAIT=0 bash -c '
  source "$SCRIPTS_DIR/lib.sh"; set +e; _cma_alias_lock_acquire'
        >/dev/null 2>&1
assert_eq 0 $? "a lock on alias file B is unaffected by a holder
        of alias file A"
# CONTROL: the same file DOES contend — otherwise the assertion
        above is vacuous.
SCRIPTS_DIR="$SCRIPTS_DIR" ALIAS_FILE="$_lk_a"
        CMA_ALIAS_LOCK_WAIT=0 bash -c '
  source "$SCRIPTS_DIR/lib.sh"; set +e; _cma_alias_lock_acquire'
        >/dev/null 2>&1
assert_eq 1 $? "CONTROL: the SAME alias file still contends (the
        lock is real)"
kill "$_lk_pid" 2>/dev/null; wait "$_lk_pid" 2>/dev/null

summary
```

8.13 tests/test_unify.sh

```
#!/usr/bin/env bash
# test_unify.sh — exercises claude-unify.sh:
#   * basic merge of two accounts: all shared items become
        symlinks
#   * settings.json enabledPlugins is a strict union
#   * history.jsonl is concatenated and de-duplicated
#   * memory files survive merge (newest account wins conflicts)
#   * plugin manifest installPath is rewritten to the shared store
#   * N>2 accounts also work
#   * a second unify run produces the same state (idempotent)
#   * --rollback restores .preunify.* backups

set -uo pipefail

TESTS_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
SCRIPTS_DIR="$(cd "$TESTS_DIR/.." && pwd)"

source "$TESTS_DIR/lib/assert.sh"
source "$TESTS_DIR/lib/sandbox.sh"
# shellcheck source=../lib.sh
```

```
source "$SCRIPTS_DIR/lib.sh"   # defines cma_realpath etc. used
        directly below
# lib.sh enables `set -e`; this harness asserts on failures, so
        relax it.
set +e

make_sandbox

# Two fixture accounts with overlapping and unique data.
acct1="$(make_account acct1 --plugins \
  --settings '{"enabledPlugins":
        {"a":true,"b":true},"effortLevel":"high"}' \
  --history 'cmd1|cmd2|shared-line' \
  --memory 'user_role:role from acct1' \
  --todo todo-a-1)"
acct2="$(make_account acct2 --plugins \
  --settings '{"enabledPlugins":
        {"b":true,"c":true},"skipDangerousModePermissionPrompt":true}'
        \
  --history 'cmd3|shared-line|cmd4' \
  --memory 'user_role:role from acct2 (NEWER)' \
  --memory 'project_notes:notes from acct2 only' \
  --todo todo-b-1)"

# Make sure acct2 is the most recently touched so the unifier's
        "last
# account wins on conflicts" rule applies to it.
touch "$acct2/projects/-home-test/memory/user_role.md"

# shellcheck disable=SC2119  # test intentionally calls run_unify
        with no args
run_unify >/dev/null 2>&1
rc=$?
assert_eq 0 "$rc" "claude-unify exits 0"

it "every shared item becomes a symlink into the shared store"
# §11.4 own-settings: settings.json is intentionally NOT in this
        list — it is each
# dir's OWN real file, asserted separately below. Everything else
        (incl. the
# plugin CACHE and history) stays a shared symlink.
for item in projects todos tasks plans file-history paste-cache
        plugins \
            shell-snapshots session-env telemetry sessions backups
        cache \
            stats-cache.json history.jsonl; do
  case "$item" in
    stats-cache.json)
      # Only fixtures with this file get the symlink; skip if
        absent.
      [[ -e "$SHARED_DIR/$item" ]] || continue ;;
  esac
  assert_symlink_to "$acct1/$item" "$SHARED_DIR/$item" "$acct1
        $item linked"
```

```
  assert_symlink_to "$acct2/$item" "$SHARED_DIR/$item" "$acct2
        $item linked"
done

it "settings.json is each dir's OWN real file (§11.4 own-
        settings), not a shared symlink"
# Per-alias permissions/model/hooks must never leak, so unify
        gives every dir its
# OWN settings.json — while plugins (cache) + history stay shared
        symlinks (proven
# in the loop above). The propagated enabledPlugins union lives in
        each own copy.
assert_not_symlink "$acct1/settings.json" "acct1 settings.json is
        OWN"
assert_not_symlink "$acct2/settings.json" "acct2 settings.json is
        OWN"
assert_file "$acct1/settings.json" "acct1 own settings.json
        exists"
assert_file "$acct2/settings.json" "acct2 own settings.json
        exists"
assert_jq "$acct1/settings.json" '.enabledPlugins.a' "true"
        "acct1 own settings carries the enabledPlugins union"
assert_jq "$acct1/settings.json" '.enabledPlugins.c' "true"
        "acct1 own settings gained acct2's plugin via the
        propagated union"

it "shared TEMPLATE settings.json enabledPlugins is the union
        {a,b,c}"
# Unify unions ONLY the enabledPlugins map into the shared
        template so newly-
# enabled plugins propagate to every dir.
assert_jq "$SHARED_DIR/settings.json" '.enabledPlugins | keys |
        sort | join(",")' "a,b,c" "union"

it "§11.4 own-settings: per-alias NON-plugin keys stay local — no
        leak to a sibling dir or to shared"
# effortLevel was set ONLY in acct1;
        skipDangerousModePermissionPrompt ONLY in
# acct2. Under own-settings each keeps its own key, neither leaks
        to the other,
# and NEITHER leaks into the shared template (which carries only
        the plugin union).
assert_jq "$acct1/settings.json" '.effortLevel' "high" "acct1
        keeps its OWN effortLevel"
assert_jq "$acct2/settings.json"
        '.skipDangerousModePermissionPrompt' "true" "acct2 keeps
        its OWN permission flag"
assert_jq "$acct1/settings.json"
        '.skipDangerousModePermissionPrompt // "absent"' "absent"
        "acct2's permission flag did NOT leak into acct1"
assert_jq "$acct2/settings.json" '.effortLevel // "absent"'
        "absent" "acct1's effortLevel did NOT leak into acct2"
assert_jq "$SHARED_DIR/settings.json" '.effortLevel // "absent"'
        "absent" "effortLevel did NOT leak to the shared template"
```

```
assert_jq "$SHARED_DIR/settings.json"
        '.skipDangerousModePermissionPrompt // "absent"' "absent"
        "permission flag did NOT leak to the shared template"

it "history.jsonl contains every unique line, no duplicates"
expected_lines=5
actual_lines="$(sort -u "$SHARED_DIR/history.jsonl" | wc -l | tr
        -d ' ')"
assert_eq "$expected_lines" "$actual_lines" "5 unique lines"
assert_file_contains "$SHARED_DIR/history.jsonl" "cmd1" "cmd1
        present"
assert_file_contains "$SHARED_DIR/history.jsonl" "cmd4" "cmd4
        present"

it "memory: newest account's version wins on filename conflict"
assert_file_contains "$SHARED_DIR/projects/-home-test/memory/
        user_role.md" "NEWER" "acct2 wins"
assert_file "$SHARED_DIR/projects/-home-test/memory/
        project_notes.md" "acct2-only memory survives"

it "plugin manifest paths are rewritten to the shared store"
assert_jq "$SHARED_DIR/plugins/installed_plugins.json" \
  '.plugins["test-plugin@test-marketplace"][0].installPath' \
  "$SHARED_DIR/plugins/cache/test-marketplace/test-plugin/1.0.0" \
  "installPath rewritten"
assert_jq "$SHARED_DIR/plugins/known_marketplaces.json" \
  '.["test-marketplace"].installLocation' \
  "$SHARED_DIR/plugins/marketplaces/test-marketplace" \
  "installLocation rewritten"

it "credentials are NOT shared — each account keeps its own"
assert_not_symlink "$acct1/.credentials.json" "acct1 creds local"
assert_not_symlink "$acct2/.credentials.json" "acct2 creds local"
assert_file_contains "$acct1/.credentials.json" "acct1" "acct1
        creds intact"
assert_file_contains "$acct2/.credentials.json" "acct2" "acct2
        creds intact"

it "unify registers claude<N> aliases for every detected account
        that lacks one"
assert_file_contains "$ALIAS_FILE" "alias
        claude1=\"CLAUDE_CONFIG_DIR=$acct1 cma_run\"" "acct1 gets
        claude1 alias"
assert_file_contains "$ALIAS_FILE" "alias
        claude2=\"CLAUDE_CONFIG_DIR=$acct2 cma_run\"" "acct2 gets
        claude2 alias"
alias_count="$(grep -cE '^alias claude[0-9]+=' "$ALIAS_FILE" ||
        true)"
assert_eq 2 "$alias_count" "exactly two claudeN aliases
        registered"

it "unify preserves claude<N> basenames and fills gaps with next
        free claudeN"
# A dir literally named ~/.claude-claude4 should be aliased as
        claude4, not
```

```
# renumbered. Other dirs consume the remaining free claude<N>
        slots.
c4="$(make_account claude4)"
zacct="$(make_account zebra)"
run_unify >/dev/null 2>&1
assert_file_contains "$ALIAS_FILE" "alias
        claude4=\"CLAUDE_CONFIG_DIR=$c4 cma_run\"" "claude4 dir
        keeps claude4 alias"
assert_file_contains "$ALIAS_FILE" "alias
        claude3=\"CLAUDE_CONFIG_DIR=$zacct cma_run\"" "zebra dir
        gets next free claude3 alias"
alias_count="$(grep -cE '^alias claude[0-9]+=' "$ALIAS_FILE" ||
        true)"
assert_eq 4 "$alias_count" "four claudeN aliases total (1,2,3,4)"

it "re-running claude-unify is idempotent (settings.json byte-
        stable)"
checksum_before="$(sha256sum "$SHARED_DIR/settings.json" | cut
        -d' ' -f1)"
target_before="$(cma_realpath "$acct1/projects")"  # readlink -f
        is unavailable on BSD/macOS
# shellcheck disable=SC2119  # test intentionally calls run_unify
        with no args
run_unify >/dev/null 2>&1
checksum_after="$(sha256sum "$SHARED_DIR/settings.json" | cut -d'
        ' -f1)"
target_after="$(cma_realpath "$acct1/projects")"
assert_eq "$checksum_before" "$checksum_after" "settings.json
        unchanged"
assert_eq "$target_before"   "$target_after"   "symlink target
        unchanged"

it "N>2 accounts: adding a third and re-running unifies it too"
acct3="$(make_account acct3 \
  --settings '{"enabledPlugins":{"d":true}}' \
  --history 'cmd5|cmd1')"
# shellcheck disable=SC2119  # test intentionally calls run_unify
        with no args
run_unify >/dev/null 2>&1
assert_symlink_to "$acct3/projects" "$SHARED_DIR/projects" "acct3
        projects linked"
assert_jq "$SHARED_DIR/settings.json" '.enabledPlugins.d' "true"
        "acct3 plugin merged"
assert_file_contains "$SHARED_DIR/history.jsonl" "cmd5" "acct3
        history merged"

it "§11.4 own-settings PROOF: a per-alias settings.json edit does
        NOT leak into another dir or shared"
# Add a unique per-alias NON-plugin key to acct1's OWN
        settings.json AFTER unify,
# then re-run unify. own-settings must keep it local: acct1
        retains it, acct2
# never gains it, and the shared template never gains it (it
        carries only the
```

```
# enabledPlugins union). This is the load-bearing anti-leak
        guarantee of the
# refactor — a real behavioral proof, not a tautology.
jq '.model = "per-alias-model-acct1-only"' "$acct1/settings.json"
        > "$acct1/settings.json.probe" \
  && mv "$acct1/settings.json.probe" "$acct1/settings.json"
# shellcheck disable=SC2119  # test intentionally calls run_unify
        with no args
run_unify >/dev/null 2>&1
assert_jq "$acct1/settings.json" '.model' "per-alias-model-acct1-
        only" "acct1 keeps its OWN per-alias model after unify"
assert_jq "$acct2/settings.json" '.model // "absent"' "absent"
        "acct1's per-alias model did NOT leak into acct2"
assert_jq "$SHARED_DIR/settings.json" '.model // "absent"'
        "absent" "acct1's per-alias model did NOT leak to the
        shared template"
# The plugin union still flows to every dir (plugins ARE meant to
        be shared).
assert_jq "$acct2/settings.json" '.enabledPlugins.a' "true"
        "acct2 still carries the propagated enabledPlugins union"

# ── B1 / B2: absorb_default_plugins + link_default_plugin_subdirs
        ──────────────
# Use an isolated SHARED_DIR/DEFAULT_DIR/ACCOUNT_PREFIX triple so
        these tests
# don't interfere with the main sandbox state or the rollback
        assertions below.

b1_sd="$SANDBOX_HOME/.claude-shared-b1"
b1_dd="$SANDBOX_HOME/.claude-b1"
b1_acct="$SANDBOX_HOME/.claude-b1-acct"
mkdir -p "$b1_dd/plugins/cache/foo/1.0.0"
printf 'hello-b1\n' > "$b1_dd/plugins/cache/foo/1.0.0/file.txt"
mkdir -p "$b1_acct"
printf '{"name":"b1"}\n' > "$b1_acct/.credentials.json"
printf '{"name":"b1"}\n' > "$b1_acct/.claude.json"
printf '{"enabledPlugins":{}}\n' > "$b1_acct/settings.json"
SHARED_DIR="$b1_sd" DEFAULT_DIR="$b1_dd" ACCOUNT_PREFIX=".claude-
        b1-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1

it "absorb_default_plugins (B1): files under DEFAULT_DIR/plugins/
        cache are absorbed into shared store"
assert_file "$b1_sd/plugins/cache/foo/1.0.0/file.txt" \
  "absorb_default_plugins: file.txt absorbed from DEFAULT_DIR/
        plugins/cache into SHARED_DIR"

it "link_default_plugin_subdirs (B2): DEFAULT_DIR/plugins/cache
        becomes a symlink into shared store"
b2_is_link=1; [[ -L "$b1_dd/plugins/cache" ]] && b2_is_link=0
assert_eq 0 "$b2_is_link" "DEFAULT_DIR/plugins/cache is a symlink
        after unify"
b2_real="$(cma_realpath "$b1_dd/plugins/cache")"
assert_eq "$(cma_realpath "$b1_sd/plugins/cache")" "$b2_real"
        "symlink resolves to SHARED_DIR/plugins/cache"
```

```
it "link_default_plugin_subdirs (B2 idempotent): second unify
        creates no additional .preunify.* backup"
b2_pre="$(find "$b1_dd/plugins" -maxdepth 1 -name
        'cache.preunify.*' 2>/dev/null | wc -l | tr -d ' ')"
SHARED_DIR="$b1_sd" DEFAULT_DIR="$b1_dd" ACCOUNT_PREFIX=".claude-
        b1-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1
b2_post="$(find "$b1_dd/plugins" -maxdepth 1 -name
        'cache.preunify.*' 2>/dev/null | wc -l | tr -d ' ')"
assert_eq "$b2_pre" "$b2_post" "no new .preunify.* backup created
        on second unify run (idempotent)"

# ── B4: sync_claude_md seed branches
        ──────────────────────────────────────

# (b) DEFAULT_DIR has a real CLAUDE.md; no account CLAUDE.md.
#     sync_claude_md should seed shared CLAUDE.md from
        DEFAULT_DIR.

b4b_sd="$SANDBOX_HOME/.claude-shared-b4b"
b4b_dd="$SANDBOX_HOME/.claude-b4b"
b4b_acct="$SANDBOX_HOME/.claude-b4b-acct"
mkdir -p "$b4b_dd" "$b4b_acct"
printf 'default-memory\n' > "$b4b_dd/CLAUDE.md"
printf '{"name":"b4b"}\n' > "$b4b_acct/.credentials.json"
printf '{"name":"b4b"}\n' > "$b4b_acct/.claude.json"
printf '{"enabledPlugins":{}}\n' > "$b4b_acct/settings.json"
SHARED_DIR="$b4b_sd" DEFAULT_DIR="$b4b_dd"
        ACCOUNT_PREFIX=".claude-b4b-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1

it "sync_claude_md (B4b): DEFAULT_DIR/CLAUDE.md seeds shared
        CLAUDE.md when no account has one"
assert_file_contains "$b4b_sd/CLAUDE.md" "default-memory" \
  "sync_claude_md: DEFAULT_DIR/CLAUDE.md content seeded into
        shared store"

# (c) No DEFAULT_DIR CLAUDE.md; an account has a real CLAUDE.md.
#     sync_claude_md should fall back and seed from the first
        account's CLAUDE.md.

b4c_sd="$SANDBOX_HOME/.claude-shared-b4c"
b4c_dd="$SANDBOX_HOME/.claude-b4c"
b4c_acct="$SANDBOX_HOME/.claude-b4c-acct"
mkdir -p "$b4c_dd" "$b4c_acct"
# No CLAUDE.md in b4c_dd (the DEFAULT_DIR).
printf 'acct2-memory\n' > "$b4c_acct/CLAUDE.md"
printf '{"name":"b4c"}\n' > "$b4c_acct/.credentials.json"
printf '{"name":"b4c"}\n' > "$b4c_acct/.claude.json"
printf '{"enabledPlugins":{}}\n' > "$b4c_acct/settings.json"
SHARED_DIR="$b4c_sd" DEFAULT_DIR="$b4c_dd"
        ACCOUNT_PREFIX=".claude-b4c-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1
```

```
it
        "sync_claude_md (B4c): account CLAUDE.md seeds shared
        CLAUDE.md when DEFAULT_DIR has none"
assert_file_contains "$b4c_sd/CLAUDE.md" "acct2-memory" \

        "sync_claude_md: account CLAUDE.md seeded into shared
        store when DEFAULT_DIR lacks one"

# ── R1: history.jsonl merge must not fuse records across a source
        that lacks a
# trailing newline. Regression for cat-based concat gluing one
        file's last line
# onto the next file's first line.
r1_sd="$SANDBOX_HOME/.claude-shared-r1"
r1_a="$SANDBOX_HOME/.claude-r1-a"
r1_b="$SANDBOX_HOME/.claude-r1-b"
mkdir -p "$r1_a" "$r1_b"
printf '{"n":"r1a"}\n' > "$r1_a/.credentials.json"; printf
        '{"name":"r1a"}\n' > "$r1_a/.claude.json"
printf '{"n":"r1b"}\n' > "$r1_b/.credentials.json"; printf
        '{"name":"r1b"}\n' > "$r1_b/.claude.json"
printf '{"enabledPlugins":{}}\n' > "$r1_a/settings.json"
printf '{"enabledPlugins":{}}\n' > "$r1_b/settings.json"
# acct a's history has NO trailing newline (the bug trigger); acct
        b follows it.
printf '{"e":"one"}\n{"e":"two"}' > "$r1_a/history.jsonl"
printf '{"e":"three"}\n{"e":"four"}\n' > "$r1_b/history.jsonl"
SHARED_DIR="$r1_sd" DEFAULT_DIR="$SANDBOX_HOME/.claude-r1"
        ACCOUNT_PREFIX=".claude-r1-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1

it
        "history.jsonl (R1): a source missing its trailing newline
        does not fuse records"
r1_two=1;   grep -qxF '{"e":"two"}'   "$r1_sd/history.jsonl" 2>/
        dev/null && r1_two=0
r1_three=1; grep -qxF '{"e":"three"}' "$r1_sd/history.jsonl" 2>/
        dev/null && r1_three=0
r1_fused=0; grep -qF  '"two"}{"e":"three"' "$r1_sd/history.jsonl"
        2>/dev/null && r1_fused=1
assert_eq 0 "$r1_two"   "history line {\"e\":\"two\"} preserved
        intact"
assert_eq 0 "$r1_three" "history line {\"e\":\"three\"} preserved
        intact"
assert_eq 0 "$r1_fused" "no fused two+three record"

# ── R2: enabledPlugins union must keep "any true" regardless of
        account order.
# Regression: rightmost-wins let the lexically-last account's
        false clobber a
# plugin an earlier account had enabled.
r2_sd="$SANDBOX_HOME/.claude-shared-r2"
r2_a="$SANDBOX_HOME/.claude-r2-a"
r2_b="$SANDBOX_HOME/.claude-r2-b"
mkdir -p "$r2_a" "$r2_b"
```

```
printf '{"n":"r2a"}\n' > "$r2_a/.credentials.json"; printf
        '{"name":"r2a"}\n' > "$r2_a/.claude.json"
printf '{"n":"r2b"}\n' > "$r2_b/.credentials.json"; printf
        '{"name":"r2b"}\n' > "$r2_b/.claude.json"
# a (lexically first) enables foo; b (lexically LAST, the overlay
        account) disables it.
printf '{"enabledPlugins":{"foo":true}}\n'             > "$r2_a/
        settings.json"
printf '{"enabledPlugins":{"foo":false,"bar":true}}\n' > "$r2_b/
        settings.json"
SHARED_DIR="$r2_sd" DEFAULT_DIR="$SANDBOX_HOME/.claude-r2"
        ACCOUNT_PREFIX=".claude-r2-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1

it "enabledPlugins (R2): a plugin enabled in any account stays
        enabled (any-true union)"
assert_jq "$r2_sd/settings.json" '.enabledPlugins.foo' "true"
        "foo stays true despite last account false"
assert_jq "$r2_sd/settings.json" '.enabledPlugins.bar' "true"
        "bar from last account present"

# ── R3: a single malformed settings.json must not abort the whole
        unify.
# Regression: the multi-file jq -s merge ran unguarded under set
        -e.
r3_sd="$SANDBOX_HOME/.claude-shared-r3"
r3_a="$SANDBOX_HOME/.claude-r3-a"
r3_b="$SANDBOX_HOME/.claude-r3-b"
mkdir -p "$r3_a" "$r3_b"
printf '{"n":"r3a"}\n' > "$r3_a/.credentials.json"; printf
        '{"name":"r3a"}\n' > "$r3_a/.claude.json"
printf '{"n":"r3b"}\n' > "$r3_b/.credentials.json"; printf
        '{"name":"r3b"}\n' > "$r3_b/.claude.json"
printf '{"enabledPlugins":{"ok":true}}\n' > "$r3_a/settings.json"
printf '%s\n' '{ this is not valid json'  > "$r3_b/settings.json"
SHARED_DIR="$r3_sd" DEFAULT_DIR="$SANDBOX_HOME/.claude-r3"
        ACCOUNT_PREFIX=".claude-r3-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1
r3_rc=$?

it "settings.json (R3): one malformed account file does not abort
        unify"
assert_eq 0 "$r3_rc" "unify still exits 0 despite a malformed
        settings.json"
r3_tmp=0; [[ -e "$r3_sd/settings.json.tmp" ]] && r3_tmp=1
assert_eq 0 "$r3_tmp" "no orphaned settings.json.tmp left behind"
# The valid account's settings must NOT become a dangling symlink
        (silent loss):
# the merge must still write shared from the valid file(s) and
        link to it.
r3_readable=0; [[ -f "$r3_a/settings.json" ]] && r3_readable=1
assert_eq 1 "$r3_readable" "valid account settings.json still
        readable (not a dangling symlink)"
assert_jq "$r3_a/settings.json" '.enabledPlugins.ok' "true"
        "valid account's settings survive a malformed sibling"
```

```
# ── R4: directory merge must resolve file conflicts by newest
        mtime, not by the
# lexically-last account name. Regression: pass 2 overlaid
        ACCOUNTS[-1]
# (alphabetically last) unconditionally, so a stale lexically-last
        account
# clobbered fresher content from an earlier account.
r4_sd="$SANDBOX_HOME/.claude-shared-r4"
r4_a="$SANDBOX_HOME/.claude-r4-a"
r4_b="$SANDBOX_HOME/.claude-r4-b"
mkdir -p "$r4_a/projects/p/memory" "$r4_b/projects/p/memory"
printf '{"n":"r4a"}\n' > "$r4_a/.credentials.json"; printf
        '{"name":"r4a"}\n' > "$r4_a/.claude.json"
printf '{"n":"r4b"}\n' > "$r4_b/.credentials.json"; printf
        '{"name":"r4b"}\n' > "$r4_b/.claude.json"
printf '{"enabledPlugins":{}}\n' > "$r4_a/settings.json"
printf '{"enabledPlugins":{}}\n' > "$r4_b/settings.json"
# Same file in both. b (lexically LAST) is STALE; a (lexically
        first) is FRESH.
# Set explicit mtimes (touch -t, portable) so a is strictly newer
        than b.
printf 'OLD-from-b\n' > "$r4_b/projects/p/memory/note.md"
printf 'NEW-from-a\n' > "$r4_a/projects/p/memory/note.md"
touch -t 202001010000 "$r4_b/projects/p/memory/note.md"
touch -t 202601010000 "$r4_a/projects/p/memory/note.md"
SHARED_DIR="$r4_sd" DEFAULT_DIR="$SANDBOX_HOME/.claude-r4"
        ACCOUNT_PREFIX=".claude-r4-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1

it "dir merge (R4): freshest file wins conflicts regardless of
        account name order"
assert_file_contains "$r4_sd/projects/p/memory/note.md" "NEW-from-
        a" \
  "newer file from lexically-earlier account wins (not the stale
        lexically-last one)"

# ── R5: rollback must not leave a dangling symlink for an item an
        account never
# had. Such items get a shared-store symlink but NO .preunify
        backup, so the
# restore loop never visits them; once SHARED_DIR is moved aside
        they dangle.
r5_sd="$SANDBOX_HOME/.claude-shared-r5"
r5_a="$SANDBOX_HOME/.claude-r5-a"
r5_b="$SANDBOX_HOME/.claude-r5-b"
mkdir -p "$r5_a/projects" "$r5_b/projects" "$r5_b/todos"   # only
        b has todos
printf '{"n":"r5a"}\n' > "$r5_a/.credentials.json"; printf
        '{"name":"r5a"}\n' > "$r5_a/.claude.json"
printf '{"n":"r5b"}\n' > "$r5_b/.credentials.json"; printf
        '{"name":"r5b"}\n' > "$r5_b/.claude.json"
printf '{"enabledPlugins":{}}\n' > "$r5_a/settings.json"
printf '{"enabledPlugins":{}}\n' > "$r5_b/settings.json"
```

```
SHARED_DIR="$r5_sd" DEFAULT_DIR="$SANDBOX_HOME/.claude-r5"
        ACCOUNT_PREFIX=".claude-r5-" \
  "$SCRIPTS_DIR/claude-unify.sh" >/dev/null 2>&1
SHARED_DIR="$r5_sd" DEFAULT_DIR="$SANDBOX_HOME/.claude-r5"
        ACCOUNT_PREFIX=".claude-r5-" \
  "$SCRIPTS_DIR/claude-unify.sh" --rollback >/dev/null 2>&1

it "rollback (R5): no dangling shared-store symlink left for a
        never-backed-up item"
r5_dangle=0; [[ -L "$r5_a/todos" ]] && r5_dangle=1
assert_eq 0 "$r5_dangle" "a/todos (symlink, no backup) is removed
        on rollback, not left dangling"

# ── R6: rollback restores the OLDEST .preunify backup (the true
        original) when a
# path has more than one, deterministically (find order is
        otherwise arbitrary).
r6_sd="$SANDBOX_HOME/.claude-shared-r6"
r6_a="$SANDBOX_HOME/.claude-r6-a"
mkdir -p "$r6_a"
printf '{"n":"r6a"}\n' > "$r6_a/.credentials.json"; printf
        '{"name":"r6a"}\n' > "$r6_a/.claude.json"
# Two backups for the same path; the oldest timestamp holds the
        true original.
printf 'OLDEST-original\n' > "$r6_a/memo.preunify.20200101000000"
printf 'newer-backup\n'    > "$r6_a/memo.preunify.20240101000000"
SHARED_DIR="$r6_sd" DEFAULT_DIR="$SANDBOX_HOME/.claude-r6"
        ACCOUNT_PREFIX=".claude-r6-" \
  "$SCRIPTS_DIR/claude-unify.sh" --rollback >/dev/null 2>&1

it "rollback (R6): oldest .preunify backup wins when a path has
        several"
assert_file_contains "$r6_a/memo" "OLDEST-original" "the true
        (oldest) original is restored deterministically"

it "--rollback restores backups and archives the shared store"
# shellcheck disable=SC2119  # test intentionally calls
        run_rollback with no args
run_rollback >/dev/null 2>&1
assert_dir "$acct1/projects" "acct1 projects restored as real dir"
assert_not_symlink "$acct1/projects" "no longer a symlink"
cond=1; [[ ! -d "$SHARED_DIR" ]] && cond=0; assert_eq 0 "$cond"
        "shared store moved aside"
shared_archive="$(find "$HOME" -maxdepth 1 -name '.claude-
        shared.removed.*' -type d 2>/dev/null | head -1)"
cond=0; [[ -n "$shared_archive" ]] || cond=1; assert_eq 0 "$cond"
        "archive sibling exists"

# Drift guard: claude-add-account wires CMA_SHARED_ITEMS (lib.sh)
        while
# claude-unify.sh carries its own SHARED_ITEMS. CLAUDE.md
        documents "keep the two
# lists in sync". They MUST agree EXCEPT for CLAUDE.md, which
        unify handles
```

```
# specially via sync_claude_md() (promotion from ~/.claude /
        DEFAULT_DIR — a
# generic rsync/symlink cannot do that). This catches accidental
        future drift
# (a new shared item added to one list only) without forcing the
        two paths to merge.
it "shared-item lists stay in sync: unify SHARED_ITEMS ==
        CMA_SHARED_ITEMS minus the CLAUDE.md special-case"
_cma_items="$(awk '/^CMA_SHARED_ITEMS=\(/{f=1} f{print} f&&/\)/
        {exit}' "$SCRIPTS_DIR/lib.sh" | tr -d '()"' | tr ' ' '\n'
        | grep -vE 'CMA_SHARED_ITEMS=|^$|^CLAUDE\.md$' | sort |
        tr '\n' ' ')"
_uni_items="$(awk '/^SHARED_ITEMS=\(/{f=1} f{print} f&&/\)/
        {exit}' "$SCRIPTS_DIR/claude-unify.sh" | tr -d '()"' | tr
        ' ' '\n' | grep -vE 'SHARED_ITEMS=|^$' | sort | tr '\n' '
        ')"
assert_eq "$_uni_items" "$_cma_items" "the two shared-item lists
        agree (modulo the intentional CLAUDE.md special-case)"

# ---------------------------------------------------------------------------
# daemon/ + jobs/ (v1.17.0): Claude Code's background-agent
        registry MUST be
# shared — a background agent started under one alias is
        registered in that
# config dir's daemon/ and is otherwise invisible to every other
        alias.
# ---------------------------------------------------------------------------
acct3="$(make_account acct3)"
acct4="$(make_account acct4)"

# Seed the rosters BEFORE the first unify in this section: after
        linking,
# $acctN/daemon is a symlink into shared, so writing to it later
        would
# overwrite the shared file directly (and empty the union inputs).
mkdir -p "$acct3/daemon/dispatch" "$acct4/daemon"
printf 'k3' > "$acct3/daemon/control.key"
printf 'k4' > "$acct4/daemon/control.key"
cat > "$acct3/daemon/roster.json" <<'JSON'
{"proto":1,"supervisorPid":300,"updatedAt":2000,"workers":{"w-a":
        {"sessionId":"s-a","updatedAt":2000},"w-share":
        {"sessionId":"s-share-NEWER","updatedAt":2000},"w-old":
        {"sessionId":"s-old","updatedAt":1000}}}
JSON
cat > "$acct4/daemon/roster.json" <<'JSON'
{"proto":1,"supervisorPid":400,"updatedAt":1500,"workers":{"w-b":
        {"sessionId":"s-b","updatedAt":1500},"w-old":
        {"sessionId":"s-old-SHOULD-STAY-
        STALE","updatedAt":500},"w-share":{"sessionId":"s-share-
        old","updatedAt":1000}}}
JSON
run_unify >/dev/null 2>&1

it "daemon dir is merged into shared + symlinked from every
        account"
```

```
assert_dir "$SHARED_DIR/daemon" "shared daemon dir created"
assert_symlink_to "$acct3/daemon" "$SHARED_DIR/daemon" "acct3
        daemon is a symlink into shared"
assert_symlink_to "$acct4/daemon" "$SHARED_DIR/daemon" "acct4
        daemon is a symlink into shared"

it "daemon/roster.json: workers are UNION-merged (newer updatedAt
        wins per worker), not last-file-wins"
assert_jq "$SHARED_DIR/daemon/roster.json"
        '.workers | keys | sort | join(",")' "w-a,w-b,w-old,w-
        share" "all four workers present (union)"
assert_jq "$SHARED_DIR/daemon/roster.json" '.workers["w-
        share"].sessionId' "s-share-NEWER" "newer updatedAt wins
        the shared worker"
assert_jq "$SHARED_DIR/daemon/roster.json" '.workers["w-
        old"].sessionId' "s-old" "stale worker value does not
        clobber the newer one"
assert_jq "$SHARED_DIR/daemon/roster.json" '.supervisorPid' "300"
        "supervisorPid comes from the newest roster"
assert_jq "$SHARED_DIR/daemon/roster.json" '.updatedAt' "2000"
        "top-level updatedAt is the max"

it "jobs dir is merged into shared + symlinked from every account"
assert_dir "$SHARED_DIR/jobs" "shared jobs dir created"
assert_symlink_to "$acct3/jobs" "$SHARED_DIR/jobs" "acct3 jobs is
        a symlink into shared"

# ---------------------------------------------------------------------------
# cma_migrate_daemon_dirs_once (lib.sh): pre-v1.17.0 provider dirs
        carry LOCAL
# daemon registries that must join the shared one — contents
        merged, rosters
# unioned (never lost), dirs replaced by symlinks, idempotent.
# ---------------------------------------------------------------------------
it "cma_migrate_daemon_dirs_once: local provider daemon dirs are
        merged, unioned, symlinked, backed up"
rm -f "$SHARED_DIR/.daemon-migration-done"
p1="$HOME/.claude-prov-p1" p2="$HOME/.claude-prov-p2"
mkdir -p "$p1/daemon" "$p2/daemon"
cat > "$p1/daemon/roster.json" <<'JSON'
{"proto":1,"supervisorPid":300,"updatedAt":2000,"workers":{"w-
        prov1":{"sessionId":"s1","updatedAt":2000},"w-share":
        {"sessionId":"s-share-NEWER","updatedAt":2000}}}
JSON
cat > "$p2/daemon/roster.json" <<'JSON'
{"proto":1,"supervisorPid":400,"updatedAt":1500,"workers":{"w-
        prov2":{"sessionId":"s2","updatedAt":1500},"w-share":
        {"sessionId":"s-share-old","updatedAt":1000}}}
JSON
cma_migrate_daemon_dirs_once
assert_symlink_to "$p1/daemon" "$SHARED_DIR/daemon" "p1 daemon
        replaced by shared symlink"
assert_symlink_to "$p2/daemon" "$SHARED_DIR/daemon" "p2 daemon
        replaced by shared symlink"
```

```
ok=1; compgen -G "$p1/daemon.preunify.*" >/dev/null && ok=0;
        assert_eq 0 "$ok" "p1 original daemon backed up
        (.preunify)"
assert_jq "$SHARED_DIR/daemon/roster.json" '[.workers | keys[] |
        select(. == "w-prov1" or . == "w-prov2" or . == "w-
        share")] | sort | join(",")' "w-prov1,w-prov2,w-share"
        "both providers' workers unioned into the existing
        registry"
assert_jq "$SHARED_DIR/daemon/roster.json" '.workers["w-
        share"].sessionId' "s-share-NEWER" "newer worker version
        wins across providers"
rm -f "$SHARED_DIR/daemon/roster.json" ; _sentinel="$(jq -c
        '.workers|keys' <(echo '{"workers":{}}') 2>/dev/null ||
        true)"
cma_migrate_daemon_dirs_once
ok=1; [[ ! -e "$SHARED_DIR/daemon/roster.json" || "$(jq -r
        '.workers["w-share"].sessionId' "$SHARED_DIR/daemon/
        roster.json" 2>/dev/null)" == "s-share-NEWER" ]] && ok=0
assert_eq 0 "$ok" "second migration run is a no-op (marker file)"
rm -rf "$p1" "$p2"

summary
```

8.14 `tests/test_add_remove.sh`

```
#!/usr/bin/env bash
# test_add_remove.sh — exercises claude-add-account.sh and
# claude-remove-account.sh end-to-end:
#   * add suggests the next free claudeN
#   * add creates the dir with the right symlinks
#   * add writes a shell-safe alias line
#   * add refuses to overwrite an existing dir
#   * add accepts a custom alias name
#   * remove drops the alias line
#   * remove archives the dir by default, --delete removes it

set -uo pipefail

TESTS_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
SCRIPTS_DIR="$(cd "$TESTS_DIR/.." && pwd)"

source "$TESTS_DIR/lib/assert.sh"
source "$TESTS_DIR/lib/sandbox.sh"

make_sandbox

# Start with two existing accounts and a unified shared store.
make_account acct1 >/dev/null  # side-effect only; returned path
        not needed
make_account acct2 >/dev/null  # side-effect only; returned path
        not needed
# shellcheck disable=SC2119  # test intentionally calls run_unify
        with no args
```

```
run_unify >/dev/null 2>&1

it "claude-add-account --yes uses sensible defaults"
run_add_account --alias claude3 --yes >/dev/null 2>&1
rc=$?
assert_eq 0 "$rc" "exit 0"
new_dir="$HOME/.claude-claude3"
assert_dir "$new_dir" "config dir created"
assert_symlink_to "$new_dir/projects" "$SHARED_DIR/projects"
        "projects linked"
# §11.4 own-settings: settings.json is each dir's OWN real file
        (NOT a shared
# symlink) so per-alias permissions/model/hooks never leak. It is
        seeded from
# the shared template, so it carries the enabledPlugins map.
        Meanwhile the plugin
# CACHE (plugins/) and history stay SHARED symlinks.
assert_not_symlink "$new_dir/settings.json" "settings.json is OWN
        (not a shared symlink)"
assert_file "$new_dir/settings.json" "own real settings.json
        exists"
assert_jq "$new_dir/settings.json" 'has("enabledPlugins")' "true"
        "own settings.json carries enabledPlugins (seeded from
        template)"
assert_symlink_to "$new_dir/plugins" "$SHARED_DIR/plugins"
        "plugins (cache) still shared"
assert_symlink_to "$new_dir/history.jsonl" "$SHARED_DIR/
        history.jsonl" "history.jsonl still shared"
assert_symlink_to "$new_dir/CLAUDE.md" "$SHARED_DIR/CLAUDE.md"
        "CLAUDE.md linked"
assert_file_contains "$ALIAS_FILE" "alias claude3=" "alias line
        written"
assert_file_contains "$ALIAS_FILE" "CLAUDE_CONFIG_DIR=$new_dir"
        "alias points at new dir"

it "claude-add-account refuses to overwrite an existing dir"
( run_add_account --alias claude3 --yes >/dev/null 2>&1 )
rc=$?
cond=$(( rc != 0 ? 0 : 1 )); assert_eq 0 "$cond" "exits non-zero
        when dir exists"

it "claude-add-account accepts a custom alias name and custom dir"
custom_dir="$HOME/.claude-mywork"
run_add_account --alias mywork --dir "$custom_dir" --yes >/dev/
        null 2>&1
assert_dir "$custom_dir" "custom dir created"
assert_symlink_to "$custom_dir/projects" "$SHARED_DIR/projects"
        "projects linked"
assert_file_contains "$ALIAS_FILE" "alias mywork=" "custom alias
        written"

it "claude-add-account validates alias names"
( run_add_account --alias "bad name" --yes >/dev/null 2>&1 )
rc=$?
```

```
cond=$(( rc != 0 ? 0 : 1 )); assert_eq 0 "$cond" "rejects bad
        alias"

it "claude-add-account is non-interactive without --yes
        (CMA_NONINTERACTIVE=1)"
export CMA_NONINTERACTIVE=1
run_add_account --alias claude4 >/dev/null 2>&1
rc=$?
unset CMA_NONINTERACTIVE
assert_eq 0 "$rc" "exit 0 without --yes"
assert_dir "$HOME/.claude-claude4" "config dir created via
        defaults"
assert_file_contains "$ALIAS_FILE" "alias claude4="
        "alias written non-interactively"
# Regression (cma_run_provider migration mis-fire): adding more
        accounts must
# not chop previously-written alias lines. All earlier aliases
        must survive.
assert_file_contains "$ALIAS_FILE" "alias claude3=" "earlier
        claude3 alias survives"
assert_file_contains "$ALIAS_FILE" "alias mywork="
        "earlier mywork alias survives"

it "claude-remove-account --archive moves the dir aside"
run_remove_account --alias claude3 --archive --yes >/dev/null 2>&1
rc=$?
assert_eq 0 "$rc" "exit 0"
cond=1; [[ ! -d "$HOME/.claude-claude3" ]] && cond=0; assert_eq 0
        "$cond" "original dir gone"
archived="$(find "$HOME" -maxdepth 1 -name '.claude-
        claude3.removed.*' -type d 2>/dev/null | head -1)"
cond=1; [[ -n "$archived" ]] && cond=0; assert_eq 0 "$cond"
        "archived sibling exists"
assert_file_not_contains "$ALIAS_FILE" "alias claude3=" "alias
        line removed"

it "claude-remove-account --delete actually deletes"
run_remove_account --alias mywork --delete --yes >/dev/null 2>&1
cond=1; [[ ! -d "$HOME/.claude-mywork" ]] && cond=0; assert_eq 0
        "$cond" "dir deleted"
# "find printed nothing" is also what a find that never ran
        prints, so pin the
# find down at both ends: it must exit 0, and the same sweep
        without the
# .removed filter must still see the sandbox's other account dirs.
        Only then
# does an empty archive list mean "--delete really deleted".
_ar_all="$(find "$HOME" -maxdepth 1 -name '.claude-*' | grep -c .
        || true)"
_ar_hits="$(find "$HOME" -maxdepth 1 -name '.claude-
        mywork.removed.*')"; _ar_rc=$?
assert_eq 0 "$_ar_rc" "the archive-sibling find ran (exit 0)"
cond=1; [[ "${_ar_all:-0}" -ge 1 ]] && cond=0; assert_eq 0
        "$cond" "the sweep can see \$HOME's account dirs
        ($_ar_all found)"
```

```
cond=1; [[ -z "$_ar_hits" ]] && cond=0; assert_eq 0 "$cond" "no
        archive sibling"

it "claude-remove-account rejects unknown alias"
( run_remove_account --alias nonexistent --yes >/dev/null 2>&1 )
rc=$?
[[ $rc -ne 0 ]]; assert_eq 0 $? "unknown alias errors out"

summary
```

8.15 tests/test_list.sh

```
#!/usr/bin/env bash
# test_list.sh — claude-list-accounts.sh reports accurate state.

set -uo pipefail

TESTS_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
SCRIPTS_DIR="$(cd "$TESTS_DIR/.." && pwd)"

source "$TESTS_DIR/lib/assert.sh"
source "$TESTS_DIR/lib/sandbox.sh"

make_sandbox

# Empty-host case first.
it "lists nothing when no accounts exist"
# shellcheck disable=SC2119  # test intentionally calls
        run_list_accounts with no args
out="$(run_list_accounts 2>&1)"
cond=1; [[ "$out" == *"ALIAS"* ]] && cond=0; assert_eq 0 "$cond"
        "header always printed"
echo "$out" | grep -E '^\-' >/dev/null; rc=$?
cond=$(( rc != 0 ? 0 : 1 )); assert_eq 0 "$cond" "no account rows"

make_account acct1 >/dev/null  # side-effect only; returned path
        not needed
make_account acct2 >/dev/null  # side-effect only; returned path
        not needed
# shellcheck disable=SC2119  # test intentionally calls run_unify
        with no args
run_unify >/dev/null 2>&1
run_add_account --alias claude3 --yes >/dev/null 2>&1

it "shows every account dir with creds + link status"
# shellcheck disable=SC2119  # test intentionally calls
        run_list_accounts with no args
out="$(run_list_accounts 2>&1)"
assert_file_contains <(printf '%s\n' "$out") ".claude-acct1"
        "acct1 listed"
assert_file_contains <(printf '%s\n' "$out") ".claude-acct2"
        "acct2 listed"
```

```
assert_file_contains <(printf '%s\n' "$out") ".claude-claude3"
        "claude3 listed"
assert_file_contains <(printf '%s\n' "$out") "claude3" "claude3
        alias resolved"

it "reports the shared store path"
# shellcheck disable=SC2119  # test intentionally calls
        run_list_accounts with no args
out="$(run_list_accounts 2>&1)"
assert_file_contains <(printf '%s\n' "$out") "$SHARED_DIR"
        "shared store path printed"

it "flags accounts with missing credentials"
# claude3 was created by add-account; it has no .credentials.json.
# shellcheck disable=SC2119  # test intentionally calls
        run_list_accounts with no args
out="$(run_list_accounts 2>&1)"
line="$(echo "$out" | grep ".claude-claude3" || true)"
cond=1; [[ "$line" == *" no "* ]] && cond=0; assert_eq 0 "$cond"
        "claude3 creds:no"
line1="$(echo "$out" | grep ".claude-acct1" || true)"
cond=1; [[ "$line1" == *" yes "* ]] && cond=0; assert_eq 0
        "$cond" "acct1 creds:yes"

summary
```

8.16 tests/test_export.sh

```
#!/usr/bin/env bash
# test_export.sh — claude-export-docs.sh produces HTML and PDF,
        expands
# <!-- INCLUDE: path --> markers, and the output PDF starts with
        "%PDF-".

set -uo pipefail

TESTS_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
SCRIPTS_DIR="$(cd "$TESTS_DIR/.." && pwd)"

source "$TESTS_DIR/lib/assert.sh"
source "$TESTS_DIR/lib/sandbox.sh"

# The doc-export pipeline hard-requires pandoc (cma_require
        pandoc) plus at
# least one PDF engine. On hosts without that tooling (minimal
        servers, a
# stock macOS), SKIP rather than fail — the feature is genuinely
        unavailable,
# matching how test_opencode/verify_opencode_live SKIP when
        opencode is absent.
# Engine list mirrors claude-export-docs.sh's own probe order.
_have_pdf_engine() {
  local e
```

```
  for e in weasyprint wkhtmltopdf chromium chromium-browser
        google-chrome chrome; do
    command -v "$e" >/dev/null 2>&1 && return 0
  done
  return 1
}
if ! command -v pandoc >/dev/null 2>&1 || ! _have_pdf_engine; then
  echo
        "SKIP: doc-export prerequisites (pandoc + a PDF engine)
        not installed"
  exit 0
fi

make_sandbox
mkdir -p "$HOME/Documents/scripts"

# Tiny fixture markdown + a fixture script to include. We point
        the
# export script at this synthetic doc instead of the real one.
fixture_script="$HOME/Documents/scripts/sample.sh"
cat > "$fixture_script" <<'EOF'
#!/usr/bin/env bash
echo "SAMPLE_SCRIPT_BODY_MARKER"
EOF

fixture_md="$HOME/Documents/fixture.md"
cat > "$fixture_md" <<'EOF'
---
title: Fixture
---
# Fixture

Body paragraph above the include.

```bash
<!-- INCLUDE: scripts/sample.sh -->
```

End of fixture. EOF

it "MD_FILE env override is honored and HTML is generated"
MD_FILE="$fixture_md" "$SCRIPTS_DIR/claude-export-docs.sh"
>/dev/null 2>&1 rc=$? assert_eq 0 "$rc" "export exits 0"
assert_file "$HOME/Documents/fixture.html" "html generated"
assert_file "$HOME/Documents/fixture.pdf" "pdf generated"

it " markers are expanded in output" assert_file_contains
"$HOME/Documents/fixture.html"
"SAMPLE_SCRIPT_BODY_MARKER" "include expanded"
assert_file_not_contains "$HOME/Documents/fixture.html" "<!--
INCLUDE:" "markers removed"
```

it "PDF starts with the %PDF- magic bytes" head -c 5 "$HOME/Documents/fixture.pdf" | grep -q '^%PDF-' assert_eq 0 $? "PDF magic header present"

it "regeneration is non-destructive (file timestamps move forward)" MD_FILE="$fixture_md" "$SCRIPTS_DIR/claude-export-docs.sh" >/dev/null 2>&1 assert_file "$HOME/Documents/fixture.html" "html still present after rerun" assert_file "$HOME/Documents/fixture.pdf" "pdf still present after rerun"

summary

---

9. Troubleshooting

Symptom	Likely cause	Fix
`claude1` works, `claude2` shows empty memory	Symlinks weren't created in `~/.claude-milos85vasic2nd/`.	Re-run `claude-unify.sh` — it's idempotent.
New account can't see history	Forgot to reload shell after `claude-add-account.sh`.	`exec $SHELL -l` or `source ~/.local/share/claude-multi-account/aliases.sh`.
Plugin loads fail with "plugin not found"	Manifest path points outside the shared store.	Re-run `claude-unify.sh` — the path-rewrite pass will fix it.
Both accounts see *each other's* drafts in the queue	`sessions/` is shared and two processes are running at once.	Don't run two accounts concurrently, or remove `sessions` from `SHARED_ITEMS`.
`pandoc` fails to find a PDF engine	No weasyprint/wkhtmltopdf/chromium installed.	`brew install weasyprint` or `apt install weasyprint`.
Want to start completely over	-	`claude-rollback` then re-run `install.sh`.

10. Sharing the ecosystem with OpenCode

````
The same plugin ecosystem that the multi-account setup unifies can
also be
shared with a host-installed [OpenCode](https://opencode.ai).
Claude Code
plugins are runtime-specific (hooks + JS), but their portable
contents —
Anthropic-format **Skills** (`SKILL.md`), **MCP servers**
(`.mcp.json`), and
the user **`CLAUDE.md`** — map directly onto OpenCode's native
`skills.paths`,
`mcp{}`, and `instructions[]` config keys.

`claude-opencode-sync` performs this translation in one
idempotent, additive
pass (it never clobbers OpenCode's own providers or servers):

```bash
claude-opencode-sync --dry-run --stats   # preview
claude-opencode-sync                      # apply (prior config is
backed up)
````

It scans the plugin cache, parses both the wrapped (`{"mcpServers": {…}}`) and bare (`{name:{…}}`) `.mcp.json` shapes, expands `${CLAUDE_PLUGIN_ROOT}`, deduplicates servers shipped by multiple plugins, and applies a conservative enable policy — enabling only no-auth/no-secret servers by default so OpenCode startup stays fast, while configuring all the rest `enabled:false`, ready to `opencode mcp auth`. On the reference host the latest recorded live run (`scripts/tests/proof/00-summary.txt`, 2026-07-27, opencode 1.18.5) measured `skill_paths=163`, `skills_resolved=1356`, `mcp_total=144` with `mcp_enabled=7` by the default allowlist and `mcp_connected=26` `mcp_failed=0`.

End-to-end proof, writing inspectable evidence to `scripts/tests/proof/` and a dated `PROOF.md` tying it together:

```bash
bash scripts/tests/run-proof.sh
```

It runs six legs, each with its own log in that directory: the hermetic sandbox suite (`40-sandbox-suite.log`), live OpenCode verification against the real binary and real config (`41-live-verify.log`), live provider-alias verification (`42-live-providers.log`), live alias verification (`43-live-aliases.log`), alias end-to-end against provider endpoints (`44-alias-e2e.log`), and the constitution/conformance static checks (`45-constitution.log`). It acquires the suite lock at the outermost entry point, and the nested `run-all.sh` inherits that lock rather than deadlocking against it.

Full guide, architecture diagrams, and the enable-policy flowchart live in **`OpenCode_Integration.md`** and `docs/diagrams/`.

```

11. Provider aliases — running other LLMs through Claude Code

The same alias machinery that powers `claude1..N` also drives **provider aliases**: a Claude Code alias per LLM provider whose key you keep in your keys file, pointed at the strongest model that provider will actually serve you (see *Model tier* below — strongest **paid** when the account has credit, strongest **free** when it does not). The command is `claude-providers` and it is **fully dynamic** — no provider, base URL, or model ID is hardcoded.

Data flow (nothing hardcoded)

1. `~/api_keys.sh` provides the API-key *variable names* (read by `grep`, never executed).
2. `models.dev/api.json` (fetched + cached, with graceful offline degrade) provides each provider's endpoint, transport hint (`npm`), and full model catalog with cost/context/reasoning metadata.
3. `providers_resolve.py` resolves each key into a record: provider id, alias, base URL, transport (`native` iff the provider speaks the Anthropic API, else `router`), and a strong + fast model chosen from the metadata.
4. The **`LLMsVerifier`** checkout (resolved flat by `scripts/resolve_deps.sh llms_verifier`) (or a lightweight HTTP probe) optionally verifies the key + model before the alias is activated.
5. For each provider: a non-secret env file, a `cma_run_provider <id>` alias, a `~/.claude-prov-<id>` config dir linking all shared items (so every plugin is available), and the always-on plugin set are generated.

Two tiny editable inputs cover the only things data can't infer: `providers/key-aliases.json` (key-name → provider normalization) and `providers/overrides.json` (per-provider pins, e.g. a short `dseek` alias or a native `/anthropic` endpoint).

Model tier — strongest paid if funded, strongest free if not

Model choice is **credit-aware**, and this is a hard rule for every provider alias the toolkit generates:

Credit state of the provider account	Model the alias runs
Credit / purchased tokens available	the strongest **paid** model that provider serves and that passes verification

Credit state of the provider account	Model the alias runs
No credit	the strongest **free** model (free tier, `$0` cost) that passes the same verification
Unknown / undeterminable	treated as *no credit* — the free choice

Three things are worth being explicit about.

Why "unknown" resolves to free. The two mistakes are not symmetric. Pinning a paid model on an unfunded key produces a 402/403 the moment you launch, and you are left holding a dead alias at the exact moment you wanted to work. Pinning a free model on a funded key costs you some capability and nothing else, and the next `claude-providers sync` upgrades it as soon as the credit signal is readable. So an inconclusive billing probe, a provider that exposes no balance endpoint, or an offline catalog all fall to the conservative branch.

It is a floor, not a cap. Within whichever tier applies the selection is still the *strongest* model available: the rule constrains which models are eligible, it does not lower the bar inside that set. It applies to both slots — the strong model (`ANTHROPIC_MODEL`) and the fast/background model (`ANTHROPIC_SMALL_FAST_MODEL`) — and to every alias produced by `sync --multi`.

A human pin always wins. If `scripts/providers/overrides.json` names a `strong_model` / `fast_model` for a provider, that is what runs; the tier logic only decides the unpinned case. Pinning is the supported way to say "I know what I'm paying for on this provider, stop deciding for me."

The tier split constrains — rather than replaces — the capability ranking the resolver already applied (reasoning-capable first, then newest release, then largest context window, with output cost as a flagship tie-break for the strong slot; cheapest tool-call-capable model for the fast slot). Verification is unchanged and unconditional: a free model is not exempt from the sentinel and tool-calling probes, so "cheapest that works" never degrades into "cheapest".

> The enforcement mechanism (in `providers_resolve.py` and in the bundled **LLMsVerifier**, which carries the corresponding detection) landed alongside this section. What is written above is the **behavioural contract**; consult the source for the current function, flag, and field names.

Transports

- **native** — `claude` runs directly with `ANTHROPIC_BASE_URL`, `ANTHROPIC_AUTH_TOKEN`, `ANTHROPIC_MODEL`, `ANTHROPIC_SMALL_FAST_MODEL`.
- **router** — launches through a bundled Go fork of claude-code-router (`ccr code`), which translates Anthropic ↔ OpenAI/Gemini. The provider entry is written into the ccr config with the live key at launch (chmod 600), so the toolkit itself never persists secrets.

Both transports export the model into the environment. `lib.sh` exports `ANTHROPIC_MODEL`, `ANTHROPIC_SMALL_FAST_MODEL`, the four `ANTHROPIC_DEFAULT_{OPUS,SONNET,HAIKU,FABLE}_MODEL` tier maps, and `CLAUDE_CODE_MAX_CONTEXT_TOKENS` for **both** — it used to do so only in the native branch, which left router aliases resolving Claude Code's own tier ids client-side and dying in an unbreakable compaction loop. Extending those exports to the router transport is also what exposed the router defect described next: it is the change that put a raw vendor-prefixed catalog id into the request body for the first time.

Router selector semantics — the `/` that killed 16 of 24 aliases

A route in the router's config is `provider,model` on disk. But the router *also* honours a **client-supplied selector** in the request body's `model` field, so a caller can pin an exact upstream for a single request instead of taking the server-configured `Router.default`. `parseExplicitSelector` (`claude-code-router:internal/router/selector.go`) recognises **two** separators — a comma and a slash — and whichever appears **leftmost** decides the split, so one string can never be parsed two different ways. If neither separator is present, or either half would be empty, it is not a selector at all and normal routing applies.

The two separators look symmetric and are not, and treating them as if they were is what broke the alias fleet:

- A **comma** is unambiguous. It is this project's own on-disk route syntax and it appears in no model id anywhere. So when a comma-form selector names a provider that is not configured, the caller really did ask for something absent, and the request **must fail loudly**. Quietly redirecting it to `Router.default` would send the request — and the bill — to an upstream the caller never chose.
- A **slash** is ambiguous. It is simultaneously Node CCR's `Provider/model` wire format *and* the near-universal `vendor/model` catalog convention: `deepseek-ai/…`, `Qwen/…`, `nvidia/…`, `zai-org/…`.

The live defect (2026-07-27). Once `lib.sh` began exporting `ANTHROPIC_MODEL` for the router transport too, Claude Code put the raw catalog id in the request body. The router read the **vendor** as a provider name, found no such provider in the per-alias config, and returned an unknown-provider error instead of falling through to `Router.default`. The gateway answered **`503` in 1-4 ms — before any network call** — and Claude Code retried with backoff until the 180-second launch bound expired (`kilo` logged 11 gateway 503s spanning 179 s; 8-12 per affected alias in `~/.claude-code-router/<id>/service.log`). Blast radius: **16 of the 24 verified aliases** — every one whose model id carries a vendor prefix — including `helixagent` (`HelixAgent/HelixLLM`).

What made this so hard to see is that **the on-disk route was correct the whole time**. `"kilo,nvidia/nemotron-…"` parses fine: its comma comes first, so the leftmost rule splits on the comma exactly as intended. The config read back healthy while every launch died.

The fix decides from evidence, not from the separator. On the slash form:

- if some configured provider actually serves the **whole string**, it is a catalog id that merely looks like a selector, and it routes normally;
- if nobody serves it, the unknown-provider error still stands — so `Ghost/whatever` cannot silently reach `Default`;
- if the vendor prefix **collides** with a real provider name (provider `nvidia` serving `nvidia/nemotron-…`), it resolves to the whole id, because the split half is absent from that provider's `Models` while the full string is present.

The comma form's loud failure is unchanged.

Why every earlier gate was green — this is the part to internalise. The provider-verification stack has four layers, and only the last one touches the code path that broke:

Layer	What it does	Could it see this?
1. Existence (`providers-verify.sh`)	`curl`s the provider's own `base_url` — sentinel echo + tool-calling probe	**No** — never touches the ccr route path
2. Semantic (`providers-semantic.sh`)	`curl`s the same `base_url` through LLMsVerifier's code-visibility driver	**No** — same reason
3. Status/config checks		

Layer	What it does	Could it see this?
	reads `status.json` and the generated per-alias config	**No** — the config was correct
4. Live TUI launch (`verify_superpowers_tui.sh`)	launches real Claude Code *through the alias*, i.e. through `ccr`	**Yes — only here**

Layers 1-3 were green throughout, and honestly so: the provider endpoints really did work. The request never reached them. That asymmetry is the entire reason the layer-4 leg exists, and the reason `claude-release-gate.sh` is mandatory before a release commit — a suite that only probes upstreams verifies the upstreams, not the product.

Token-limit guards — the arithmetic, and which direction is dangerous

Every provider alias exports two guards before launching Claude Code, and they are **co-derived, not independent**, so the pair can never sum past the provider's context window:

- `CLAUDE_CODE_MAX_OUTPUT_TOKENS` — the output cap.
- `CLAUDE_CODE_AUTO_COMPACT_WINDOW` — the auto-compaction **trigger**.

Leaving either unset is not a safe fallback. Claude Code's own default for an unknown model is 128000 output tokens, so "no export" *is* a request for 128000.

The derivation runs in two stages (`lib.sh`, the `cma-token-guards` block):

1. **Carve.** The output cap is carved *out of* the context rather than trusted alongside it: `out = min(catalog output, context − CMA_INPUT_FLOOR)`, bounded by the CLI's own 128000 ceiling and floored at 8192. `CMA_INPUT_FLOOR` defaults to **160000**.

2. **Window, with a tool-schema reserve.** `window = context − out − CMA_TOOL_TOKEN_BUDGET`, where `CMA_TOOL_TOKEN_BUDGET` defaults to **80000**. The reserve exists because the endpoint counts *tool schemas* as input too, and a window computed as `context − out` pretends the request is only text plus output.

3. **Compression-loop guard.** If that window falls below `CMA_MIN_COMPACT_WINDOW` (default **120000**), Claude Code would trigger compaction on every single request — the system prompt and tool schemas alone exceed the window — and

never get any work done. So the window is bought back out of the output cap, and **in that branch the effective output cap becomes**

```
out = context − CMA_MIN_COMPACT_WINDOW − CMA_TOOL_TOKEN_BUDGET
```

For a 262144-token provider: the carve gives `out = 102144`, whose window is `262144 − 102144 − 80000 = 80000` — below the 120000 minimum — so the guard rebalances to `out = 262144 − 120000 − 80000 = 62144`, `window = 120000`, and `62144 + 120000 + 80000 = 262144` exactly.

Be exact about which direction is dangerous. An *under*estimated tool budget does **not** merely "compact earlier". Because the effective output cap is `context − min_window − budget`, too small a budget **inflates** the output cap, the request overflows the context, and the launch dies with a `400`. Measured live on a host with **227 enabled plugins**, whose real tool input is **158112** tokens against the 80000 default:

```
46536 text + 158112 tools + 62144 output = 266792   on a 262144 window
```

Note further what that host cannot fix by tuning: `158112 + 120000` already exceeds `262144`, so **no output cap makes a 262144-context provider fit at all** there. The remedies are to shrink the enabled plugin surface or to use a wider-context provider (nvidia at 1000000 and xiaomi at 1048576 fit it comfortably). Override per host with `CMA_TOOL_TOKEN_BUDGET` in the provider env or the shell.

A context too small to reserve the budget yields no window at all. That is deliberate: such a provider cannot serve Claude Code's tool prefix regardless, and the launch must fail loudly rather than be lied to by a guard that cannot hold.

Also note what the window is not. It is a **compaction trigger**, not a hard cap — it cannot bound the tool schemas themselves, which are assembled before any conversation exists to compact. That is precisely why the separate tool budget is needed.

HelixAgent: a local GPU backend, and why auto-start is opt-in

The `helixagent` alias routes Claude Code to a local HelixLLM backend (`http://127.0.0.1:7061/v1`, router transport — repointed 2026-09-03 off `:18434`, which is the llama.cpp coder container, a different service), pinned in `scripts/providers/helixagent.json` to `context_limit` **229376** and `max_output` **8192**. The context is sized

for the multi-turn *agent loop*, not for the first request: each executed tool feeds its output back and the loop accumulates toward ~182K tokens, which overflowed the earlier 180224 pin.

That backend shares a single GPU with **HelixCode**, and the two cannot run at once — HelixCode drives HelixLLM in *coder* mode (`-c 24576 --parallel 8`), while `helixagent` needs *claude* mode (`-c 229376 --parallel 1`). Coder mode is the default operational state, so `helixagent` is honestly demoted to `unverified` and refused by the launch gate until the operator flips the backend with `helix_code/scripts/helixllm-mode.sh claude` (that companion repo, not this toolkit).

`CMA_HELIX_AUTOSTART` — opt-in, default OFF. The launch wrapper can start HelixLLM for you, but it will not do so unless you ask:

```
CMA_HELIX_AUTOSTART=1 helixagent
        # accepted: 1 | true | yes | on
```

Anything else — including the unset default — is OFF. The reason is that booting a Helix service is a heavyweight, machine-wide side effect: HelixLLM claims the single GPU, and starting it in claude mode **evicts whatever HelixCode had running in coder mode**. A provider alias must not do that to a host merely because someone typed an alias name. When auto-start is disabled and the backend is not answering, the wrapper still says so and still prints the exact command to run — the operator keeps both the information and the choice. With it enabled, the wrapper locates `helixllm-mode.sh`, starts claude mode, and polls `/health` for up to 120 s before giving up with a diagnostic.

Safety

Provider config dirs are **excluded from account auto-detection**, so they never merge into real-account auth and never disturb `claude-unify` / `claude-add-account`. Existing `claudeN` accounts keep working unchanged, and new accounts are still created the same way.

During `claude-providers sync --multi`, the API key is passed to `model_verify.py` via the **`CMA_PROBE_KEY` environment variable** — never as a command-line argument. This means the key never appears in `ps aux` or `/proc/<pid>/cmdline`, preventing accidental secret exposure to other local users or process-monitoring tools. The key is injected per-invocation and is never written to the alias file, the env file, or any repository path.

Commands

```
claude-providers sync          # discover + create/refresh every
        provider alias
claude-providers list          # alias, provider, transport,
        strong/fast model
claude-providers show <id>     # one provider's resolved env
claude-providers remove <id>   # remove alias + env, back up the
        config dir
claude-providers add --from-key VAR --id PROVIDER   # register a
        mapping, then sync
```

Session color — auto-applied (v1.10.0)

Each provider session is now tagged with the alias's deterministic color **automatically**. The toolkit writes an `agent-color` record (`{"type":"agent-color","agentColor":"<color>","sessionId":"<id>"}`) into the session's `.jsonl` — the same record Claude Code's `/color` command writes — via `claude-session apply-color`, called by the `cma_run_provider` wrapper. This is the **only** non-interactive way to set the prompt color: `/color` itself is TUI-only and `claude -p '/color x'` is a no-op, with no CLI flag, settings key, or env var. (That survey was performed against Claude Code **2.1.195**; the reference host now runs **2.1.220**, and the finding has not been re-surveyed against it.) Verified live that the record is written, is idempotent (re-applied only when the color changes), and persists across `claude --resume`. The toolkit cannot observe the TUI, so confirm the prompt-bar rendering visually on first launch. (Documented in `docs/Provider_Aliases_User_Guide.md` and `docs/SESSION_COLOR.md`.)

Full details, overrides, verification, and troubleshooting live in **`docs/Provider_Aliases_User_Guide.md`**; diagrams in `docs/diagrams/provider-aliases.md`.

12. Per-project auto-session & per-alias color

A **bare** alias launch — native (`claude1`, `claude2`, …) or provider (`deepseek`, `kimi-for-coding`, …) with no arguments — resumes, or the first time creates, **one long-lived Claude session per project root**. The session id is derived deterministically from the project root path (the git working-tree root if you are inside a repo, otherwise `$PWD`), so every alias — and every subdirectory of the repo — maps to the *same* session: switch aliases and you continue the same ongoing work.

The session is named in lowercase `kebab-case` from the project root directory's basename (e.g. `claude_toolkit` → `claude-toolkit`; `Android 15` → `android-15`). Whitespace and special characters are

sanitized to hyphens, and leading/trailing separators are trimmed. The name is applied on **both create and resume**, so a session created *without* a name — by an older wrapper or a plain `claude` invocation — finally gets named the next time you bare-launch an alias into it.

The moment you pass any argument (a prompt, `-p`, `--resume`, `--session-id`, any flag), the wrapper steps aside and your arguments go to `claude` verbatim — no auto-session is injected.

Color is auto-applied (v1.10.0). Each alias maps deterministically to one of Claude Code's 8 prompt colors, and the toolkit now applies it for you: on a bare launch the wrapper writes an `agent-color` record (`{"type":"agent-color","agentColor":"<color>","sessionId":"<id>"}`) into the session's `.jsonl` — the exact record Claude Code's `/color` command writes — via `claude-session apply-color`. It runs **before** launch (to colour a resumed session) and **after** exit (to colour a freshly-created one). It is idempotent: the record is re-written only when the color actually changes, so switching aliases re-colors the *same* session and the file never grows unbounded. This is the **only** non-interactive mechanism: `/color` is TUI-only and `claude -p '/color x'` is a no-op — there is no CLI flag, `settings.json` key, or environment variable for it (surveyed against `claude 2.1.195`; the reference host now runs `2.1.220`, against which the survey has not been repeated). Verified live that the record is written, is idempotent, and persists across `claude --resume`. The toolkit cannot programmatically observe the TUI, so confirm the prompt-bar rendering visually on first launch.

Implemented by `scripts/claude-session.sh`, driven by the `cma_run` / `cma_run_provider` alias wrappers in `scripts/lib.sh`. Full details, the naming/color tables, and live verification are in **`docs/SESSION_COLOR.md`**.

13. TOON utility

`scripts/toon.mjs` (and its Python wrapper `scripts/toon_encode.py`) encode JSON into **TOON** (Token-Oriented Object Notation) — a compact encoding that cuts token use for structured data in LLM prompts by declaring array fields once. See **`docs/TOON_Integration.md`**.

14. Authoring rule: the generated alias file is self-contained

This section is for anyone **editing the toolkit**, not for operators. It records a constraint that is invisible from the source file and that has now broken twice.

`cma_run_provider` — the launch wrapper for every provider alias — does not run from `lib.sh`. It is **emitted into the alias file** by a quoted heredoc in `lib.sh`:

```
cat <<'CMA_PROV_BODY_EOF'
  ... the entire cma_run_provider body ...
CMA_PROV_BODY_EOF
```

That alias file (`~/.local/share/claude-multi-account/aliases.sh`) is sourced by the user's **interactive shell**, and it **never sources `lib.sh`**. So at the moment this body actually executes, none of `lib.sh`'s helpers exist — `cma_log`, `cma_warn`, `cma_die`, `cma_require` and friends are all absent.

The rule: inside the heredoc body, never call a `lib.sh`-only helper bare. A bare call does not degrade gracefully. It prints

```
cma_warn: command not found
```

and **destroys the message it was supposed to carry**. That is not hypothetical: it shipped in v1.26.6 and is preserved in this repository's own evidence — `scripts/tests/proof/providers-helixagent-superpowers.txt` has that exact string on line 3, sitting precisely where the operator should have read the instruction to flip HelixLLM out of coder mode.

Two accepted idioms, and the difference between them:

```
# Acceptable floor — guards against the shell error, but SILENTLY
        DROPS the text.
command -v cma_log >/dev/null 2>&1 && cma_log "…"

# Required where the message IS the feature — prints either way.
_hl_log()  { if command -v cma_log  >/dev/null 2>&1; then
        cma_log  "$1"; else printf '[cma] %s\n' "$1" >&2; fi; }
_hl_warn() { if command -v cma_warn >/dev/null 2>&1; then
        cma_warn "$1"; else printf '[cma warn] %s\n' "$1" >&2;
        fi; }
```

The first form is the older convention and is enough to keep the shell quiet. It is *not* enough for a message the operator cannot proceed without — the HelixLLM coder-mode remedy is the only thing telling them what to do, so dropping it is as bad as garbling it. Use the fallback emitters there.

`scripts/tests/test_alias_file_selfcontained.sh` enforces the floor mechanically. It lints the **generated** alias file (not the source) for bare calls to any `lib.sh`-only helper — folding multi-line `\` and `&&`/`||` continuations first, since the real guard idiom spans lines and a naive per-line lint would report guarded code as bare — and then behaviourally executes the emitters in a shell with no `lib.sh` present, to prove the text actually arrives.

15. Dependencies and their pins

The toolkit's only submodule today is the third-party `submodules/go`. Its own-org dependencies (`LLMsVerifier`, `claude-code-router`) are flat checkouts found by `scripts/resolve_deps.sh` and declared in `helix-deps.yaml`; a standalone `curl-install.sh` run clones the router over https into `$(dirname INSTALL_DIR)/claude_code_router` when there is no parent hub. Historical pins as of `claude_toolkit-1.26.7`, when all three were submodules (`git submodule status`):

Submodule	Pin	Role
`submodules/LLMsVerifier`	`2a105fe7` (`llmsverifier-v1.12.2-12-g2a105fe7`)	The `model-verification` and `semantic-code-visibility` drivers behind provider verification layers 1-2.
`submodules/claude-code-router`	`9accd18` (`v0.4.9-5-g9accd18`)	The Go router (`ccr`) behind the **router** transport — including the selector fix in §11.
`submodules/go`	`go1.26.4`	Vendored Go toolchain, built by `claude-go-build.sh` into `~/.local/share/claude-go`.

After v1.30.6 (Unreleased), `LLMsVerifier` and `claude-code-router` are not declared here either (operator decision 2026-10-21: no own-org nested submodule); the two rows above are historical pins, and both now resolve flat via `scripts/resolve_deps.sh llms_verifier` / `claude_code_router` (`CT_LLMS_VERIFIER_DIR`, `CT_CLAUDE_CODE_ROUTER_DIR`, parent hub, `<root>/submodules/`, sibling). `submodules/go` is the only remaining submodule. As of v1.30.6, `constitution`, `containers`, `challenges` and `superspec` are not declared here; the pins above for `challenges` and `containers` (removed rows) were dropped, and all four resolve from the constitution hub via `scripts/resolve_deps.sh` (`superspec` never appeared in this table).

Two pinning rules that are not obvious:

- **`submodules/go` must track a point release on `release-branch.go1.N`, and is pinned to whatever the claude-code-**

router `go.mod` requires. Never bump it to `origin/master`: that is the unreleased next-major dev tree, and it carries no `VERSION` file — which `claude-go-build.sh` parses and hard-fails without. A bump must be followed by `claude-go-build`, `claude-ccr-build`, and the live router legs.
- **The vendored toolchain is opt-in.** `install.sh` only *symlinks* `claude-go-build`; it never builds Go from source, because downloading and compiling an ~80 MB compiler is not something an alias installer should do unasked. Consequently `~/.local/share/claude-go` does **not** exist on a normal install, and every consumer of `VENDORED_GO` must probe for the binary's existence (`command -v`) rather than testing the variable — the variable is assigned a path string unconditionally and is therefore never empty, so a `${VENDORED_GO:-go}` fallback can never fire on its own.

16. Kimi Code: accounts and the family model

The Kimi Code CLI is a first-class sibling of Claude Code. The **family model** is an orthogonal axis to the provider backend: the provider engine (verification, model selection, aliases) stays shared, and each family supplies its own agent binary, home env var, account prefix, user-scope root, and launcher functions. The diagram `docs/diagrams/kimi-family.{mmd,svg}` shows the naming contract at a glance.

	Claude family	Kimi family
agent binary	`claude`	`kimi`
home env var	`CLAUDE_CONFIG_DIR`	`KIMI_CODE_HOME`
account prefix	`.claude-`	`.kimi-code-`
user-scope root	`~/.claude`	`~/.kimi-code`
account aliases	`claude1…N`	`kimi1…N`
shared store area	`$SHARED_DIR/**`	`$SHARED_DIR/kimi/**`

16.1 The namespace contract

- `claudeN` / `kimiN` — **native accounts** (a full per-account home).
- `<id>` (no prefix) — **always Claude Code** over that backend.
- `kimi-<id>` — **always Kimi Code** over the **same** backend.
- `kc-<id>` — Claude Code over a **Kimi-native** backend (legacy renamed).

`kimiN` account aliases must never be named `kimi-*`/`kc-*` (those are reserved provider namespaces), and `kc-*` ids never get a `kimi-kc-*` twin (the Kimi agent on a Kimi-native backend is the `kimiN` account).

16.2 Kimi accounts

`kimi-add-account --alias kimi1 --login` provisions a Kimi account at `~/.kimi-code-kimi1` and drives Kimi's **interactive device flow** (`kimi login`) — headless login is a non-goal. The mirror account commands are `kimi-remove-account`, `kimi-list-accounts`, `kimi-unify`, and `kimi-rollback`.

`kimi-unify` merges `KIMI_SHARED_ITEMS = (AGENTS.md, plugins, skills, sessions, session_index.jsonl)` into `$SHARED_DIR/kimi/`. Sessions are workdir-keyed and home-independent, so cross-account resume works through the shared symlinks. `AGENTS.md` is promoted from the newest account and symlinked from every Kimi home — the `~/.claude/CLAUDE.md` promotion analog. **Never merged** (per-account private): `config.toml`, `credentials/`, `oauth/`, `device_id`, `bin/`, `logs/`, `tui.toml`. There is **no `kimi-sync-state`** — Kimi has no `.claude.json` analog; continuity comes entirely from the shared `sessions/`.

16.3 `kimi-<id>` provider aliases

For every provider id that verifies, `sync`/`--multi` also emits `alias kimi-<id>="cma_run_kimi_provider <id>"`, gated by the **same** `status.json` record as the Claude twin (single shared gate — refuse non-`verified` unless `--force`). The launcher renders `~/.kimi-prov-<id>/config.toml` (provider `type = openai|anthropic` by base shape, `base_url`, `api_key` from the same env record, `max_context_size` from the same derived limits, `default_model`) and runs `KIMI_CODE_HOME="$HOME/.kimi-prov-<id>" kimi -m "<host>/<strong-model>"`. There is **no `cma-proxy`** on this path (the Kimi CLI speaks the wire protocol natively) and **no `CLAUDE_CODE_*` guards**. One strong model per kimi alias — fast pairing is a non-goal. Emit/suppress with `--kimi-aliases` / `--no-kimi-aliases` (default on); `kimi-providers list` carries an agent (claude/kimi) column.

16.4 Legacy rename (`kimi-*` → `kc-*`)

The legacy aliases that opened **Claude Code** on a **Kimi-native backend** are renamed **once** (automatically at `sync`, or via `kimi-providers migrate-names`): `kimi-for-coding`→`kc-for-coding`, `kimi-for-coding2`→`kc-for-coding2`, `kimi-for-coding-highspeed`→`kc-for-coding-highspeed`, `kimi-k3`→`kc-k3`, `kimi-k2p7`→`kc-k2p7`. The `kimi-` prefix now means only "Kimi Code CLI agent". The rename is idempotent

(second run is a no-op) and reversible via `backup_and_remove` backups. Update scripts or muscle memory that reference the old aliases.

Last revised 2026-09-05 for release `claude_toolkit-1.27.0` (OpenCode integration added 2026-06-06; provider aliases added 2026-06-16; runtime sync via `cma_run/claude-sync-state`, `CMA_PROBE_KEY` secret-hygiene model, and `cma_realpath` BSD portability hardening added 2026-06-28; per-dir own `settings.json`, router selector semantics, co-derived token guards, `CMA_HELIX_AUTOSTART`, and the self-contained alias-file authoring rule added 2026-07-27; Kimi Code accounts + `kimi-<id>` provider aliases and the `kimi-*→kc-*` rename added 2026-09-05). Maintain by editing this markdown file and re-running `MD_FILE="$PWD/Claude_Multi_Account_Fine_Tuning.md" bash scripts/claude-export-docs.sh`.