CHANGELOG

Changelog

[Unreleased]

(Nothing yet.)

[1.2.3] - 2026-10-27 (test hygiene; no production-code change)

Tag `containers-1.2.3`. Production (non-`_test.go`) code delta versus `containers-1.2.2` (4f507ca): NONE. Public API unchanged (`MIGRATION.md` gains only a note).

- test: `make anti-bluff-scan` reported 17 pre-existing `BLUFF-G-001` (`t.Skip` without exempt marker) hits. Each was classified by reading the surrounding code. 16 were genuine conditional skips with a concrete environmental reason (no POSIX shell / Windows, no `/dev/kvm`, no `systemd --user`, running as root, `-short`, QEMU absent, or an inert subprocess worker) and now carry the exact `// SKIP-OK: <reason>` marker the scanner accepts. They still run on every capable host.
- test: the 17th was a genuine violation: `TestRTRace1_DirectAccessRacesWithSetRuntimePriority` (`pkg/runtime`) was an unconditional `t.Skip` since its introduction in b325a83, so the RT-RACE-1 evidence never executed. It is now a real test: under `go test -race` it re-executes the test binary as a worker that performs the racy direct read of the exported `RuntimePriority` against `SetRuntimePriority` and asserts the child really reported `WARNING: DATA RACE` involving `SetRuntimePriority`. Without `-race` it skips for that concrete reason. Mutation check: making the worker use `GetRuntimePriority()` (race-free) makes the test fail. The underlying race is still flagged, not fixed (the clean fix removes an

exported symbol and needs an operator API decision). New helper files: `pkg/runtime/race_on_test.go`, `race_off_test.go`.
- `make anti-bluff-scan`: 17 hits -> 0.

[1.2.2] - 2026-10-27 (docs-only)

Tag `containers-1.2.2`. Code delta versus `containers-1.2.1` (06a0b52): NONE.

- docs: `MIGRATION.md` no longer says llmctl must be updated. Verified 2026-10-27: llmctl `v3.3.0` (7cc9e83) and llmctl local `main` (81645ab) both build (`go build ./...` rc=0) and pass their `internal/registry`, `internal/vantage`, `internal/gateway` tests against `containers-1.2.1` (06a0b52); llmctl already handles the `error` returns of `Unregister` / `UpdateHealth`. No code change in this repository.

[1.2.1] - 2026-10-27

Tag `containers-1.2.1`. Code delta versus `containers-1.2.0` (cb5c727): NONE; `origin/main` == `containers-1.2.0` at preparation time. This release adds `MIGRATION.md` (every breaking signature change since `helixcode-v1.1.0`, verified with `apidiff` + consumer scan) and corrects the release metadata.

SemVer deviation (operator decision): the breaking Go API changes listed in `MIGRATION.md` were first shipped in `containers-1.2.0` (a minor bump). Strict SemVer requires a major bump (2.0.0). The operator chose a patch release `1.2.1` to attach the migration guide without renumbering the already-published 1.2.0 line; consumers MUST NOT assume 1.2.x patch releases are source-compatible with 1.1.x. See `MIGRATION.md` and `RELEASE_NOTES_1.2.1.md`.

[1.2.0] - 2026-10-27

Tag `containers-1.2.0` (project-prefixed per section 11.4.151). Range: `helixcode-v1.1.0..919ad1e` + release-docs commit = 159 commits (21 first-parent), 399 files changed, +45683 / -2371 lines (`git diff --stat`). Commit-type counts by conventional-commit prefix: fix 82, hardening 54, feat 8, docs 4, govern 2, chore 2, test 1, style 1, remainder merges/ WIP.

Verification run for this release (host-run, NOT containerised; see Known limitations): `go vet ./...` rc=0; `go test -count=1 -race -p 1 ./...` over 56 packages = 43 ok, 12 with no test files, 1 FAIL (`pkg/remote`, root-caused to the test environment, see Fixed) and, after the test-only fix, `pkg/remote` passes (`ok ... 15.4s`) under the default umask 0002.

Versioning decision (pending owner confirmation): strict SemVer would call this release 2.0.0 because exported signatures changed (see BREAKING). The owner picked 1.2.0 by default; that decision is recorded as PENDING, not final.

BREAKING (Go API, source-level) - verified against `git diff` of non-test code

Earlier drafts stated “no breaking changes”; that is NOT correct. The following exported signatures changed since `helixcode-v1.1.0`:

- `serviceregistry.(*ServiceRegistry).Unregister(name)` and `UpdateHealth(name, healthy)` now return `error` (a551ffd, persistence errors are surfaced).
- `emulator.Cleanup(ctx)` is now `Cleanup(ctx, avdName string)` and `cuttlefish.Cleanup(ctx)` is now `Cleanup(ctx, ownerToken string)` (552be2c, process kill is scoped to OUR device; the host-wide reap fallbacks were removed). `cmd/emulator-cleanup` was updated accordingly.
- Behaviour change: `cuttlefish` default `NetworkHost=true` and image refs are passed after `--` (fbff142). `health.CheckHTTP` treats 4xx as UNHEALTHY and accepts only 2xx-3xx (d21f0d8). `envconfig` now surfaces SET-but-invalid env values as errors instead of silently defaulting (90cb2f9).

Callers of the changed signatures must be updated; this is why the proposed version is a minor bump on a 1.x line only if the maintainers accept the signature changes (decision pending).

Added

- `emulator-matrix`: `--build-type` and `--gradle-property` flags to close the release-variant device-testing gap (4a8f04e).
- `emulator`: install extra APKs alongside the primary matrix APK (0788dd7); containerised-runner support in `RunCanary` / `emulator-canary` (7fa49f7); LVA-014 durable device-gate fixes: baked-AVD

resolution, `WaitForBoot` container liveness, per-API image template (746efe3).
- `network`: race-free `ListenEphemeral` port helper (0053986).
- `orchestrator`: dependency-ordered startup in topological waves (c8178cd).
- `egress` + `remoteexec`: SOCKS egress verification, durable remote execution and durable-run shell (`scripts/lib/durable-run.sh`) (cde354f).
- QEMU end-to-end integration test: QMP capability negotiation, `query-version`, clean exit (feeba3f).
- Docs: `docs/PRE_INTEGRATION_MATERIALS.md`.

Changed

- `lifecycle`: idle-shutdown, lease and lazy-boot reworked for race/leak safety (see Fixed); `lazyservice` detects dependency cycles instead of overflowing the stack (406e7b9).
- `scheduler`: gpu-affinity fitting-zero-score false negative fixed and deterministic tie-breaks across all 5 strategies (f0349a8).
- `runtime`: `AutoDetect` now honours `SetRuntimePriority` (9e92e51); docker / nerdctl `List` populate `Created` and `Ports` (c7cd749).
- `health` / `endpoint`: IPv6 literals are bracketed correctly (11280cc, f810e6d, 6158d9b).
- Governance: universal covenant anchors carried (9da662f), four-carrier lockstep restored (4dab992), GEMINI.md mirror backfilled, upstream scripts lowercased per section 11.4.29, shebangs made portable (d940b51).

Fixed / hardened (82 fix + 54 hardening commits; selected, by area)

- Security (argument / shell injection class): shell-quoting of caller- and registry-controlled values spliced into remote commands (7f7649a, 4b89cda, 3c1dc01, 70a9084, e97636e, 2862ec0, cf52b5f); leading-dash ssh/scp/simctl/ device-name refusal and `--` end-of-options before image refs (14e73b5, 5627348, 3a52825, 26a1009, c76d4f5, ddc4b45, a028b4c); VM guest-shell/argv injection (b745208); crossbuild artifact path-traversal, symlink exfiltration and FIFO copy-hang (cc4281a, 69df446, 4884191); dotenv inline-comment credential corruption (d293baa).

- Concurrency / lifecycle: ReleaseFunc double-release, idle-vs-lease reclaim, TOCTOU double-boot, Stop-during-Start resurrection, event bus Close hang and self-unsubscribe deadlock, panicking subscriber/`onIdle` containment (9470007, a9c660d, c6d401c, 031d305, da4c3b8, 2f3c0b1, 6800059).

- Durability / honesty: atomic registry persistence, fsync-before-rename cache durability and corrupt-blob quarantine, remoteexec honest transport and sentinel reporting, boot rollback tears down distributed endpoints (06e9872, 686db32, ca83bd7, 9b8d6f5, fc25fc8).

- Resource leaks / teardown: tunnel port leaks and dead-tunnel reaping, `Undistribute` of `StateMigrating` containers, deadline-bounded waits across emulator / cuttlefish / genymotion / brokertest / applesim / vm (bfd8fd3, 7c228f8, 8e16441, 1ec51e7, 5e38856, 793d402, a900f3a, 822a6d1).

- Challenges / scanners: a challenge no longer certifies a panicking binary as PASSED (7f59225); the CONST-033 host-power scanner gains a paired `--prove-failure` proof and stops reporting false greens (919ad1e, VSC-368); scripts no longer report success for work never done (b3758dd).

- Per-package fix/hardening commit counts (measured from subject prefixes; a commit naming several packages counts for each): remote 8, lifecycle 8, vm 7, serviceregistry 7, network 7, emulator 7, distribution 7, volume 6, scheduler 5, runtime 5, health 5, event 5, and further packages (`git log`).

- Tests: `pkg/remote` now pins umask 0022 in `TestMain` (`main_umask_unix_test.go`). Under umask 0002 `t.TempDir()` is 0775 and the pool's hardening (refuse a pre-existing group/other-writable control-socket dir) rejected it; `TestNewConnectionPool` then dereferenced a nil pool and the panic aborted the whole package. Test-only change, no product code touched.

Known limitations / imperfections

- `internal/buildpkg/executor.go` `LaunchLocalBuild` is a stub that returns an error ("local builds are handled by the shell pipeline, not the Go executor"); the design question is open in `docs/LOCAL_HOST_BUILD_TARGET_PROPOSAL.md`.

- Test run was on the local host, not inside a build container (the repository ships no containerised test target); section 11.4.173 compliance for this release is therefore NOT claimed.
- The test-only umask fix has not had an independent review (section 11.4.142 / 11.4.209); it is owed.
- Tag naming in this repository is inconsistent: `helixcode-v1.1.0`, `helix_translate-2.3.x`, `1.0.2-dev-0.0.2`, `1.1.0-dev`, `1.1.1-dev-0.0.x`, `yole-1.0.0-0.0.0.0.6-dev`. `containers-1.2.0` follows section 11.4.151 (`<prefix>-<version>`); no `v1.2.0` alias was created because no existing tag uses a bare `vX.Y.Z` form.
- HTML/PDF twins of README/CHANGELOG/docs are stale (no exporter in the repo).

Notes

- The former `[Unreleased]` entries (Apple `container` crossbuild backend, GPU-aware scheduling, `CONTAINERS_REMOTE_HOST_N_GPU_AUTOPROBE`) were already contained in tag `helixcode-v1.1.0` (verified: commits 61e01dc and a3ee5ce are ancestors of that tag); they are kept below under that tag, not re-announced.
- HTML/PDF twins of this file are NOT regenerated (no documented exporter in the repository); they are stale until regenerated.

[helixcode-v1.1.0] - 2026-06-23 (retroactive heading; content previously under [Unreleased])

Added

- Apple `container` crossbuild backend (`pkg/crossbuild/apple_container.go`
  - `apple_container_run.go`): boots a real Linux micro-VM via Apple's `container` CLI on macOS / Apple-Silicon hosts and bind-mounts host directories into it, providing the same Linux-target capability the podman/docker `LinuxContainerBackend` provides on Linux. Selected on darwin/arm64 ahead of the podman/docker fallback. Anti-bluff evidence (host darwin/arm64, container CLI v1.0.0): `go test -tags=integration -run AppleContainer` PASS — `container uname -s -m` => `Linux aarch64` while the host is Darwin (unforgeable real-Linux-kernel-on-macOS proof); host-dir mount round-trips both ways;

`challenges/scripts/apple_container_linux_challenge.sh` PASS, `--mutate` => exit 99 (stripping `--mount` breaks the round-trip). Project-decoupled (§11.4.28): no consumer-project references.

- GPU-aware scheduling: `HostResources.GPU`, `GPURequirement`, `StrategyGPUAffinity`, `GPUHealthCheck`, `ProbeGPU`. See `docs/gpu-scheduling.md`.
- `CONTAINERS_REMOTE_HOST_N_GPU_AUTOPROBE` env var.