

USE_CASE_CATALOGUE

Docs Chain — Use-Case Catalogue

Revision: 2 **Last modified:** 2026-05-29T12:00:00Z **Status:** Living registry. Every recipe below is a DESIGNED context. Engine support is PLANNED (Phases 1–4); ATMOSphere wiring is PLANNED (Phase 7). See per-recipe status tags. **Authority:** Operator mandate 2026-05-29 (Docs Chain initiative) **Design provenance:** authoritative Phase-0 DESIGN / RESEARCH / PLAN live in the consuming project research tree (docs/research/docs_chain/); this document is the self-contained specification.

Status legend

Per §11.4.6 (no-guessing):

- **PLANNED (Phase N)** — the recipe is designed; engine/wiring lands in Phase N of PLAN.md.
- A recipe is marked **IMPLEMENTED** only once its context is registered and green in a future revision of this file.

At the time of writing every recipe is PLANNED. These are ready-to-use chain definitions a consuming project can stage now; they are not claims that the engine processes them today.

This file is a **living registry** — new projects extend it by appending a recipe section in the same shape (purpose · members · edge directions · transform · mandate satisfied · script superseded · YAML).

Catalogue index

#	Recipe	Mandate(s) satisfied	Supersedes (ad-hoc script)
(a)	<u>Issues chain</u>	§11.4.93 · §11.4.12 · §11.4.95	sync_issues_docs.sh, generate_issues_summary.sh
(b)	<u>Fixed chain</u>	§11.4.53 · §11.4.19	

#	Recipe	Mandate(s) satisfied	Supersedes (ad-hoc script)
			generate_fixed_summary.sh, sync_issues_docs.sh (Fixed stage)
(c)	<u>Status-doc chain</u>	§11.4.45 · §11.4.56	sync_integration_status.sh, generate_status_summary.sh
(d)	<u>Roster / corpus chain</u>	§11.4.86	sync_asset_player_status.sh
(e)	<u>Changelog chain</u>	§11.4.65	export_changelog.sh
(f)	<u>README doc-link chain</u>	§11.4.57 · §11.4.59	update_readme_doc_links.sh, sync_readme_export.sh
(g)	<u>Universal markdown-export chain</u>	§11.4.65	sync_all_markdown_exports.sh
(h)	<u>CONTINUATION chain</u>	§12.10 · §11.4.44	(manual) sync_issues_docs.sh CONTINUATION stage

Catalogued scenario count: 8.

(a) Issues chain

Status: PLANNED (Phase 7).

- **Purpose:** keep the workable-items tracker mutually consistent — Issues.md and workable_items.db are bidirectional views of the same data; Issues_Summary.md is generated from the Markdown; HTML + PDF exports are derived.
- **Members:** workable_items.db (sqlite), Issues.md (markdown), Issues_Summary.md (summary), Issues.html / Issues.pdf (exports), and the summary's own .html / .pdf.
- **Edge directions:** Issues.md $\leftrightarrow$ workable_items.db (sync, authority = db); Issues.md $\rightarrow$ Issues_Summary.md (derive); Issues.md $\rightarrow$.html $\rightarrow$.pdf (derive); Issues_Summary.md $\rightarrow$.html $\rightarrow$.pdf (derive).
- **Transform:** md-to-db / db-to-md (the §11.4.93 workable-items binary), gen-issues-summary, pandoc-html, weasyprint-pdf.
- **Mandate:** §11.4.93 (DB single source of truth) · §11.4.12 (Issues_Summary sync) · §11.4.95 (DB tracked + WAL-checkpoint commit).
- **Supersedes:** sync_issues_docs.sh (Issues stage), generate_issues_summary.sh.

context: issues

description: Workable-items tracker chain (DB single source of truth)

nodes:

```

items_db:      { kind: sqlite,  path: docs/workable_items.db }
issues_md:     { kind: markdown, path: docs/Issues.md }
issues_summary: { kind: summary, path: docs/Issues_Summary.md }
issues_html:   { kind: html,    path: docs/Issues.html }

```

```

issues_pdf:      { kind: pdf,      path: docs/Issues.pdf }
summary_html:    { kind: html,     path: docs/
  Issues_Summary.html }
summary_pdf:     { kind: pdf,      path: docs/
  Issues_Summary.pdf }
edges:
- { type: sync, a: issues_md, b: items_db, authority: items_db,
  transform_a_to_b: md-to-db, transform_b_to_a: db-to-md }
- { type: derive-from, from: issues_md, to:
  issues_summary, transform: gen-issues-summary }
- { type: derive-from, from: issues_md, to:
  issues_html, transform: md-to-html }
- { type: derive-from, from: issues_html, to:
  issues_pdf, transform: html-to-pdf }
- { type: derive-from, from: issues_summary, to:
  summary_html, transform: md-to-html }
- { type: derive-from, from: summary_html, to:
  summary_pdf, transform: html-to-pdf }
transforms:
md-to-db:        { exec: "scripts/testing/workable_items",
  args: ["sync", "md-to-db"] }
db-to-md:        { exec: "scripts/testing/workable_items",
  args: ["sync", "db-to-md"] }
gen-issues-summary: { exec: "scripts/testing/
  generate_issues_summary.sh" }
md-to-html:      { builtin: pandoc-html }
html-to-pdf:     { builtin: weasyprint-pdf }

```

(b) Fixed chain

Status: PLANNED (Phase 7).

- **Purpose:** mirror of the issues chain for the closed-archive tracker — Fixed_Summary.md regenerated from Fixed.md, with synchronized exports.
- **Members:** Fixed.md (markdown), Fixed_Summary.md (summary), the .html / .pdf of each.
- **Edge directions:** Fixed.md → Fixed_Summary.md (derive); Fixed.md → .html → .pdf (derive); Fixed_Summary.md → .html → .pdf (derive).
- **Transform:** gen-fixed-summary, pandoc-html, weasyprint-pdf.
- **Mandate:** §11.4.53 (Fixed_Summary parity) · §11.4.19 (column alignment).
- **Supersedes:** generate_fixed_summary.sh, sync_issues_docs.sh (Fixed stage).

context: fixed

description: Closed-archive tracker chain (Fixed_Summary parity)

nodes:

```

fixed_md:      { kind: markdown, path: docs/Fixed.md }
fixed_summary: { kind: summary,  path: docs/Fixed_Summary.md }
fixed_html:    { kind: html,     path: docs/Fixed.html }
fixed_pdf:     { kind: pdf,      path: docs/Fixed.pdf }
fsum_html:     { kind: html,     path: docs/Fixed_Summary.html }
fsum_pdf:      { kind: pdf,      path: docs/Fixed_Summary.pdf }

```

```

edges:
- { type: derive-from, from: fixed_md,      to: fixed_summary,
    transform: gen-fixed-summary }
- { type: derive-from, from: fixed_md,      to: fixed_html,
    transform: md-to-html }
- { type: derive-from, from: fixed_html,    to: fixed_pdf,
    transform: html-to-pdf }
- { type: derive-from, from: fixed_summary, to: fsum_html,
    transform: md-to-html }
- { type: derive-from, from: fsum_html,     to: fsum_pdf,
    transform: html-to-pdf }
transforms:
  gen-fixed-summary: { exec: "scripts/testing/
                        generate_fixed_summary.sh" }
  md-to-html:        { builtin: pandoc-html }
  html-to-pdf:       { builtin: weasyprint-pdf }

```

(c) Status-doc chain

Status: PLANNED (Phase 7).

- **Purpose:** every per-domain integration `Status.md` keeps its `Status_Summary.md` (two-audience digest) and exports in sync.
- **Members:** `docs/<domain>/<integration>/Status.md`, `Status_Summary.md`, and the `.html` / `.pdf` of each.
- **Edge directions:** `Status.md` → `Status_Summary.md` (derive); `Status.md` → `.html` → `.pdf` (derive); `Status_Summary.md` → `.html` → `.pdf` (derive).
- **Transform:** `gen-status-summary` (two-page page-1 non-developer + page-2 engineer output, §11.4.56), `pandoc-html`, `weasyprint-pdf`.
- **Mandate:** §11.4.45 (`Status.md` maintenance) · §11.4.56 (`Status_Summary` two-audience parity).
- **Supersedes:** `sync_integration_status.sh`, `generate_status_summary.sh`.

```

context: status_dolby
description: Dolby integration status chain (per-domain instance)
nodes:
  status_md: { kind: status,      path: docs/dolby/
              test_assets/Status.md }
  status_sum: { kind: status_summary, path: docs/dolby/
              test_assets/Status_Summary.md }
  status_html: { kind: html,      path: docs/dolby/
              test_assets/Status.html }
  status_pdf: { kind: pdf,        path: docs/dolby/
              test_assets/Status.pdf }
  sum_html: { kind: html,        path: docs/dolby/
              test_assets/Status_Summary.html }
  sum_pdf: { kind: pdf,          path: docs/dolby/
              test_assets/Status_Summary.pdf }
edges:
- { type: derive-from, from: status_md, to: status_sum,
    transform: gen-status-summary }

```

```

- { type: derive-from, from: status_md, to: status_html,
  transform: md-to-html }
- { type: derive-from, from: status_html, to: status_pdf,
  transform: html-to-pdf }
- { type: derive-from, from: status_sum, to: sum_html,
  transform: md-to-html }
- { type: derive-from, from: sum_html, to: sum_pdf,
  transform: html-to-pdf }
transforms:
  gen-status-summary: { exec: "scripts/testing/
    generate_status_summary.sh",
    args: ["docs/dolby/test_assets/
      Status.md"] }
  md-to-html: { builtin: pandoc-html }
  html-to-pdf: { builtin: weasyprint-pdf }

```

Register one such context per integration domain (status_dolby, status_players, ...).

(d) Roster / corpus chain

Status: PLANNED (Phase 7).

- **Purpose:** when a tracked roster (installed apps) or asset corpus changes membership, the backing Status.md re-syncs out of the box (drift-proof content fingerprint, NOT mtime).
- **Members:** a fingerprint node over the roster/corpus glob, the backing Status.md, its Status_Summary.md, and exports.
- **Edge directions:** fingerprint → Status.md (derive — a membership change re-derives the Status doc); Status.md → Status_Summary.md → exports (derive, as in recipe c).
- **Transform:** members-fingerprint (builtin, sha256 of sorted member list), gen-roster-status, gen-status-summary, exports.
- **Mandate:** §11.4.86 (roster/corpus-backed Status auto-sync, fingerprint not mtime).
- **Supersedes:** sync_asset_player_status.sh.

```

context: asset_player
description: Pre-installed player roster -> players Status chain
nodes:
  roster_fp: { kind: fingerprint, path: docs/
    players/.roster_fingerprint,
    members: "device/rockchip/rk3588/prebuilt_apps/
      *.apk" }
  players_md: { kind: status, path: docs/players/
    Status.md }
  players_sum: { kind: status_summary, path: docs/players/
    Status_Summary.md }
  players_html: { kind: html, path: docs/players/
    Status.html }
  players_pdf: { kind: pdf, path: docs/players/
    Status.pdf }
edges:

```

```

- { type: derive-from, from: roster_fp, to: players_md,
  transform: gen-roster-status }
- { type: derive-from, from: players_md, to: players_sum,
  transform: gen-status-summary }
- { type: derive-from, from: players_md, to: players_html,
  transform: md-to-html }
- { type: derive-from, from: players_html, to: players_pdf,
  transform: html-to-pdf }
transforms:
  gen-roster-status: { exec: "scripts/testing/
    sync_asset_player_status.sh" }
  gen-status-summary: { exec: "scripts/testing/
    generate_status_summary.sh",
    args: ["docs/players/Status.md"] }
  md-to-html: { builtin: pandoc-html }
  html-to-pdf: { builtin: weasyprint-pdf }

```

The fingerprint node hashes the sorted APK list — adding / removing / renaming a player APK changes the hash and re-derives the Status doc, even though git checkout would reset mtime (§11.4.86 forensic lesson). A second corpus context (asset_corpus) registers the same shape over a test-asset directory glob with an exclude: for gitignored downloaded/.

(e) Changelog chain

Status: PLANNED (Phase 7).

- **Purpose:** per-version changelogs/<tag>.md always carries synchronized .html / .pdf exports.
- **Members:** docs/changelogs/<tag>.md (markdown), its .html / .pdf.
- **Edge directions:** <tag>.md → .html → .pdf (derive).
- **Transform:** pandoc-html, weasyprint-pdf (and optionally an export-changelog exec wrapping the existing multi-format exporter).
- **Mandate:** §11.4.65 (universal markdown export).
- **Supersedes:** export_changelog.sh.

```

context: changelog
description: Per-version changelog markdown -> html + pdf
nodes:
  cl_md: { kind: markdown, path: docs/changelogs/1.1.5-dev.md }
  cl_html: { kind: html, path: docs/changelogs/1.1.5-dev.html }
  cl_pdf: { kind: pdf, path: docs/changelogs/1.1.5-dev.pdf }
edges:
- { type: derive-from, from: cl_md, to: cl_html, transform:
  md-to-html }
- { type: derive-from, from: cl_html, to: cl_pdf, transform:
  html-to-pdf }
transforms:
  md-to-html: { builtin: pandoc-html }
  html-to-pdf: { builtin: weasyprint-pdf }

```

For a directory of changelogs, register one context per active version or use a glob-expanding wrapper context (see recipe g).

(f) README doc-link chain

Status: PLANNED (Phase 7).

- **Purpose:** the README's Tracked-Items + Status Documents section (per-doc revision + last-modified) re-renders whenever any linked doc changes; README's own HTML + PDF stay in sync.
- **Members:** every tracked-doc node feeding the link table, README.md (summary-like — regenerated section), README.html / README.pdf.
- **Edge directions:** each linked doc → README.md (derive — the doc-link generator reads each source's revision header); README.md → .html → .pdf (derive).
- **Transform:** gen-readme-doc-links (reads each source's §11.4.44 revision header), pandoc-html, weasyprint-pdf.
- **Mandate:** §11.4.57 (README doc-link section) · §11.4.59 (README always-sync export).
- **Supersedes:** update_readme_doc_links.sh, sync_readme_export.sh.

```
context: readme_doclinks
description: README Tracked-Items section + README exports
nodes:
  issues_md: { kind: markdown, path: docs/Issues.md }
  fixed_md:  { kind: markdown, path: docs/Fixed.md }
  contin_md: { kind: markdown, path: docs/CONTINUATION.md }
  readme_md: { kind: summary,  path: README.md }
  readme_html: { kind: html,    path: README.html }
  readme_pdf: { kind: pdf,      path: README.pdf }
edges:
  - { type: derive-from, from: [issues_md, fixed_md, contin_md],
      to: readme_md,
      transform: gen-readme-doc-links }
  - { type: derive-from, from: readme_md, to: readme_html,
      transform: md-to-html }
  - { type: derive-from, from: readme_html, to: readme_pdf,
      transform: html-to-pdf }
transforms:
  gen-readme-doc-links: { exec: "scripts/testing/
                             update_readme_doc_links.sh" }
  md-to-html:           { builtin: pandoc-html }
  html-to-pdf:          { builtin: weasyprint-pdf }
```

The from: list (multi-input derive) means a change in ANY linked doc re-renders the README section. Status docs auto-discovered by the generator are added to the from: list as the project grows.

(g) Universal markdown-export chain

Status: PLANNED (Phase 7).

- **Purpose:** the catch-all — any project Markdown that is not part of an application/service source tree gets synchronized .html + .pdf siblings.
- **Members:** for each in-scope .md: the markdown node + its .html + .pdf.
- **Edge directions:** <doc>.md → .html → .pdf (derive), repeated per doc.
- **Transform:** pandoc-html, weasyprint-pdf (the same builtins sync_all_markdown_exports.sh shells to).
- **Mandate:** §11.4.65 (universal markdown export — md → html + pdf for all governed docs).
- **Supersedes:** sync_all_markdown_exports.sh.

context: markdown_exports

description: Universal md → html + pdf for governed docs (one block per doc)

nodes:

```
guide_arch_md: { kind: markdown, path: docs/guides/
                SYSTEM_ARCHITECTURE.md }
guide_arch_html: { kind: html, path: docs/guides/
                  SYSTEM_ARCHITECTURE.html }
guide_arch_pdf: { kind: pdf, path: docs/guides/
                  SYSTEM_ARCHITECTURE.pdf }
# ... one node-triple + edge-pair per governed .md ...
```

edges:

```
- { type: derive-from, from: guide_arch_md, to:
  guide_arch_html, transform: md-to-html }
- { type: derive-from, from: guide_arch_html, to:
  guide_arch_pdf, transform: html-to-pdf }
```

transforms:

```
md-to-html: { builtin: pandoc-html }
html-to-pdf: { builtin: weasyprint-pdf }
```

This context is the broadest; the §11.4.65 in-scope set (project-root *.md, docs/**, scripts/** companion docs, owned-submodule top-level docs, constitution/**) is enumerated by the same discovery rules the legacy script uses. Excludes external/, prebuilts/, packages/modules/, kernel-5.10/, out/, build/, and application/service source trees.

(h) CONTINUATION chain

Status: PLANNED (Phase 7).

- **Purpose:** the §12.10 resumption document keeps its Last updated: revision header current and its .html / .pdf exports in sync, so any agent resuming work reads a non-divergent view across formats.
- **Members:** docs/CONTINUATION.md (markdown), its .html / .pdf.
- **Edge directions:** CONTINUATION.md → .html → .pdf (derive).
- **Transform:** pandoc-html, weasyprint-pdf. (Revision-header freshness is the source-edit author's responsibility per §11.4.44 / §12.10; Docs Chain keeps the exports from drifting behind the source.)

- **Mandate:** §12.10 (CONTINUATION maintenance) · §11.4.44 (revision header — the Last updated: line IS the §11.4.44 Last modified: line).
- **Supersedes:** the CONTINUATION stage of sync_issues_docs.sh.

```
context: continuation
description: Resumption document + synchronized exports
nodes:
  cont_md: { kind: markdown, path: docs/CONTINUATION.md }
  cont_html: { kind: html, path: docs/CONTINUATION.html }
  cont_pdf: { kind: pdf, path: docs/CONTINUATION.pdf }
edges:
  - { type: derive-from, from: cont_md, to: cont_html,
      transform: md-to-html }
  - { type: derive-from, from: cont_html, to: cont_pdf,
      transform: html-to-pdf }
transforms:
  md-to-html: { builtin: pandoc-html }
  html-to-pdf: { builtin: weasyprint-pdf }
```

Extending this registry

A new project (or a new domain in this project) adds a scenario by appending a section in the exact shape above:

1. **Purpose** — one sentence.
2. **Members** — the node list with kinds.
3. **Edge directions** — derive-from (one-way) and/or sync (bidirectional, with authority).
4. **Transform** — builtins and/or exec: adapters.
5. **Mandate satisfied** — the §11.4.x / §12.x anchor it enforces.
6. **Supersedes** — the ad-hoc script it retires.
7. **The YAML** — copy-paste ready.

Keep the [catalogue index](#) table and the **catalogued scenario count** in sync when adding a recipe.