llmctl docs/diagrams/README

llmctl diagrams

Sources are `*.mmd` (Mermaid); the rendered `*.svg` files are committed so they display without a renderer. Each diagram is also embedded as a Mermaid block at the point of use (Constitution 11.4.258); `tests/test_docs_diagrams_governance.sh` checks that the embedded block is byte-identical to its `.mmd` source.

Diagram	Source	Rendered	Embedded in
Validation gate state machine (exit codes 0, 1, 2, 75, 77, 98)	validation-gate.mmd	validation-gate.svg	validation
Decide gateway request flow (HTTPS + bearer key)	decide-gateway-flow.mmd	decide-gateway-flow.svg	decide gateway
Hub-engine placement and dependency resolution	hub-engine-placement.mmd	hub-engine-placement.svg	dependency layout
Vision tiers and model identity	vision-tiers.mmd	vision-tiers.svg	validation

Regenerate after editing a source (same renderer and flags as `claude_toolkit/docs/diagrams`; `mmdc` needs a Chromium and, in a container or as root, `--no-sandbox`):

```
echo '{"args":["--no-sandbox"]}' > "${TMPDIR:-/tmp}/pptr.json"
for d in validation-gate decide-gateway-flow hub-engine-placement
        vision-tiers; do
```

```
  mmdc -i docs/diagrams/$d.mmd -o docs/diagrams/$d.svg -p "${TMPDIR:-/
       tmp}/pptr.json"
done
```

Where `mmdc` is absent the `.svg` cannot be produced; the index then records `<name> not rendered (SKIP: no mmdc)` instead of shipping a placeholder. All four were rendered on 2026-10-22 with `mmdc` from node v26.8.1.