

Defaults work out of the box: SFTP_PORT=7721, API_PORT=7722, DB_DRIVER=sqlite. Edit only if a port is busy (ss -tlnp | grep -E ': (7721|7722) ').

3. Bootstrap

```
# PLANNED — STREAM-1 compose (ATM-001) + STREAM-6 setup script (ATM-006)
bash scripts/setup.sh
```

setup.sh validates .env, brings the stack up with podman-compose, prompts for the super-admin credentials (never echoed), and runs a smoke probe. Expect a final line like SETUP OK – sftp:7721 api:7722 admin console ready.

Manual equivalent if you want to see the pieces:

```
podman-compose -f deploy/docker-compose.yml up -d
# PLANNED — ATM-001
podman ps --format '{{.Names}} {{.Status}}' # all Up
```

4. Sign in to the web admin

PLANNED — STREAM-4 (ATM-004): open http://<server>:7722/ (loopback or behind TLS per [security guide §8](#)), sign in with the super-admin from §3. Dashboard loads with light/dark theme toggle (OpenDesign).

5. Create the first user

Web console (PLANNED — ATM-004): Accounts → **New account** → username alice, password per policy, permission read_write, leave **Public** off → Save.

Or via API (PLANNED — ATM-002): see [api_quickstart.md](#) for the exact curl sequence (login → token → POST /api/v1/accounts).

Behind the scenes the API writes the DB row, re-renders users.conf atomically, provisions data/alice/ (root-owned top + writable subdirectory), reloads the container, and audit-logs the action.

6. Upload + download test

```
cd /tmp && echo "hello-sftp" > quickstart_probe.txt
sftp -P 7721 alice@127.0.0.1 <<'EOF'
cd upload
```

```
put quickstart_probe.txt
get quickstart_probe.txt downloaded.txt
ls -la
bye
EOF
```

PASS criteria (all required — positive evidence, §11.4): 1. put reports 100% with non-zero bytes. 2. `ls -la` lists `quickstart_probe.txt`. 3. `downloaded.txt` exists locally and `cmp quickstart_probe.txt downloaded.txt` exits 0.

Then clean up the probe files. If anything fails, run the matching playbook in [troubleshooting_guide.md](#).

7. What next

- [user_management_guide.md](#) — permissions, keys, public-guard
 - [security_guide.md](#) — production hardening checklist
 - [deployment_guide.md](#) — systemd install, upgrades, rollback
 - [api_quickstart.md](#) — automate everything with curl
-

Sources verified (2026-07-11)

- Internal: `docs/Issues.md` ATM-001/002/004/006 · `docs/research/mvp/MVP.md` (sftp client round-trip pattern) · `docs/guides/deployment_guide.md`.
- External: none fetched for this file specifically — stack facts verified via the guides' fetches (`atmoz/sftp`, `podman-compose`, `docs.podman.io`) on 2026-07-11.