

vasic-digital tmux — v1.0.18 Release Notes

Revision: 1 **Last modified:** 2026-05-29T12:25:00Z **Version:** 1.0.18 / versionCode 19 **Released:** 2026-05-29 **Hosts validated:** Mistborn (Darwin arm64) + nezha (ALT Linux 6.12 x86_64)

Summary

v1.0.18 delivers the **real** fix for the operator's mouse-copy report: a PLAIN left-drag now selects and copies text **inside Claude Code** (and any mouse-tracking TUI), on **both Linux and macOS**, with no modifier and no toggle. It is proven with a **real mouse** — not a binding-presence check.

This corrects a v1.0.17 shortcoming honestly: the prefix `m` toggle shipped in v1.0.17 required the operator to know a keystroke and did not make the natural gesture work. The operator re-reported the failure; this release reproduces it with a real mouse, fixes the root binding, and proves the fix with captured clipboard evidence.

Operator (2026-05-29): *"We still cannot select and copy anything in Claude Code ... execute claude ... Try to select some text and copy it. Not possible! This MUST BE achieved on both platforms Linux and macOS!"*

A42 (completed) — plain mouse-drag selects + copies in mouse-tracking apps

Root cause (reproduced with a real mouse). Inside a mouse-tracking app (`{mouse_any_flag}=1` — Claude Code requests alt-screen + `?1003h` any-event tracking + `?1006h` SGR encoding), tmux's built-in root `MouseDrag1Pane` forwards the drag to the application (send `-M`), so a plain drag never reaches tmux copy-mode and selects nothing. The clipboard pipe (`@clip→pbcopy/wl-copy/xclip`) and the copy-mode bindings were already correct — the gap was purely that the drag was being handed to the app.

Fix. Override the root drag binding in `scripts/tmux.conf.template`:

```
bind -n MouseDrag1Pane if -F '#{pane_in_mode}' 'send -M' 'copy-mode -M'
```

A plain left-drag now ALWAYS enters copy-mode and begins a selection, even when the foreground app requests mouse tracking. On release, the existing MouseDragEnd1Pane binding pipes the selection to the OS clipboard via @clip. `#{pane_in_mode}` guard: once already in copy-mode, the drag is passed through (send -M) so copy-mode's own handler extends the selection.

Plain CLICK (MouseDown/Up) and the WHEEL are deliberately NOT rebound, so Claude Code keeps its click + scroll interactivity — only click-DRAG is repurposed for select-and-copy (the Claude Code TUI does not use drag). The fix uses no terminal-specific modifier, so it behaves identically on macOS and Linux. The prefix `m` toggle and Shift/Alt-drag remain as alternatives.

Captured physical proof (real mouse, no bluff).

- **Cross-platform headless** — `scripts/tests/56_real_mouse_drag_copy.sh` starts a tmux server with the shipped config, runs a mouse-tracking app that enables the exact modes Claude Code uses, attaches a client on a PTY, **waits until `mouse_any_flag=1`**, then **injects a real SGR-1006 left-button drag** (press → motion → motion → release) and asserts the dragged token reached the @clip sink. Asserting `mouse_any_flag=1` makes the proof meaningful — at `flag=0` even the old forwarding binding would copy. Regression-discriminating: removing the override makes the test FAIL (sink empty). 3/3 deterministic (§11.4.50). Works on macOS AND Linux (no GUI required → runs on headless nezha).
- **macOS GUI layer** (opt-in `TMX_GUI_TESTS=1`) — opens a real iTerm2 window, runs the mouse-tracking app inside a tmux session, performs a genuine cliclick cursor drag across the window, and asserts the token landed in pbpaste. Proven on Mistborn.
- `scripts/tests/55_mouse_toggle_and_copy.sh` asserts the override resolves to copy-mode (not the default `mouse_any_flag` app-forward).
- Meta-test mutation M-PLAINDRAG strips the override and asserts test 56 FAILs — CAUGHT.

Validation (dual-host)

Host	mouse-drag copy proof	suite	meta-test
Mistborn (Darwin arm64)	headless SGR PASS + real cliclick GUI drag → pbpaste PASS	full GREEN	0 escapes incl. M-PLAINDRAG
nezha (ALT Linux x86_64)	headless SGR real-mouse-drag PASS (same binding)	full GREEN	M-PLAINDRAG CAUGHT

Both platforms: a plain mouse drag in a mouse-tracking app selects + copies.

Files changed

- `scripts/tmux.conf.template` — root `MouseDown1Pane` plain-drag copy-mode override (+ corrected comments; prefix `m` / Shift / Alt retained as alternatives).
- `scripts/tests/56_real_mouse_drag_copy.sh` — rewritten: cross-platform headless SGR real-mouse-drag proof+ opt-in macOS cliclick GUI layer.
- `scripts/tests/55_mouse_toggle_and_copy.sh` — assert plain-drag override present.
- `scripts/tests/meta_test_false_positive_proof.sh` — M-PLAINDRAG mutation.
- `VERSION`, `CHANGELOG.md`, `CONTINUATION.md`.

Sources verified 2026-05-29

- tmux upstream man page — <https://man.openbsd.org/tmux.1>: `-M` "passes through a mouse event (only valid if bound to a mouse key binding)"; `copy-mode -M` begins a mouse drag; `if-shell -F` conditional binding; `{pane_in_mode} / {mouse_any_flag}` formats. SGR-1006 mouse encoding (CSI < b ; x ; y M/m) is the modern xterm extended mouse protocol used by the test harness.