

vasic-digital tmux — Open Issues Tracker

Canonical source of truth for everything currently unfinished, partially validated, or at risk of violating the anti-bluff covenant (Constitution.md §1 + §11.4.1 through §11.4.6).

Every PASS in this codebase **MUST** carry positive evidence captured live that the feature works for the end user. Metadata-only PASS, configuration-only PASS, "absence-of-error" PASS, and grep-based PASS without runtime evidence are all critical defects regardless of how green the summary line looks. **Tests AND HelixQA Challenges are bound equally.**

Forensic anchor — direct user mandate (verbatim, 2026-04-28 + 2026-05-07 + 2026-05-08, repeatedly reasserted from upstream vasic-digital projects):

"We had been in position that all tests do execute with success and all Challenges as well, but in reality the most of the features does not work and can't be used! This **MUST NOT** be the case and execution of tests and Challenges **MUST** guarantee the quality, the completion and full usability by end users of the product!"

§11.4.6 forensic anchor (verbatim, 2026-05-08):

"'LIKELY' is guessing, we **MUST NOT** have guessing, since it can be or may not be! No bluffing and uncertainty is allowed at any cost! We **MUST** always know exactly precisely what is happening exactly, in any context, under any conditions, everywhere!"

Compiled: 2026-05-08 (Phase B per-session-containerization cycle).

Author: Engineering coordinator **Working pool source:** the items below feed the active task list directly. Each item carries a current state, the captured-evidence requirement, and a fix-direction proposal so future-self can resume cold.

Migration policy (mirrors upstream vasic-digital projects): resolved items are moved to **Fixed.md** in the same commit that closes them. **Issues.md** holds **OPEN / PARTIAL / BLOCKED / RUNNING / INVESTIGATED** only; once an item is closed and verified end-to-end, it migrates to **Fixed.md** and disappears from here. Never delete items outright — history matters for cold-start handover.

Document conventions

Code	Meaning
OPEN	Unfinished work; needs implementation + anti-bluff coverage
PARTIAL	Implementation exists but coverage gaps remain (positive evidence missing or environmental SKIP unresolved)
BLOCKED	Cannot progress without external dependency (host capability, third-party tool, distro support, etc.)
RUNNING	In-flight in this session (background process, ongoing test cycle)
INVESTIGATED	Forensic investigation produced findings; closure pending decision on fix scope

Status reclassification rules (§11.4.6 enforced):

- A **PARTIAL** may not move to closed without runtime evidence (`/sys/fs/cgroup/.../memory.max readback`, `systemctl status` showing scope active, `kill -9 survivor` proof — never just script exit code).
- A **BLOCKED** reclassifies to **OPEN** when the blocking dependency resolves; it must NOT skip directly to closed.
- An **INVESTIGATED** item must record the captured forensic trace (file path / command output / log timestamp) — never speculation ("likely" / "probably" / "appears to" — see Constitution §11.4.6).

Categories:

- **A** — Tooling / harness gaps
 - **B** — Anti-bluff completeness across the existing test surface
 - **C** — Per-session containerization features pending evidence
 - **D** — Host-capability + topology dispatch gaps
 - **E** — Documentation / Continuation drift
-

A. Tooling / harness gaps

A3. META-TEST-72-73-COVERAGE-001 — tests 72/73 need persistent meta-test mutations

TMX-ID: TMX-076 **Type:** Task **Status:** Ready for testing

Tests 72 (libevent/ncurses local-dependency obtain) and 73 (build_native.sh local-dependency wiring) currently have no paired §1.1 mutation registered in scripts/tests/meta_test_false_positive_proof.sh, so a regression in either mechanism would not be mechanically caught by the layer-4 anti-bluff sweep. Re-filed follow-up from TMX-071 (originally tracked 2026-06-30 in commit 8232b15, reverted the same day in commit 9b719a6 purely because of an unrelated add→db-to-md rendering tooling defect, not because the underlying work was invalid or completed — confirmed via git history per §11.4.124; the mutation-writing itself was never done). Acceptance: two new persistent mutations (mirroring the existing M-test67/CM-LOCAL-DEPS-MECHANISM pattern) that mutate a real invariant each test enforces and assert the harness FAILs, then restore cleanly; both wired into the standing sweep alongside the existing 60+ mutations.

A4. NEW-COLLISION-GUARD-SCOPE-GATED-001 — the new verb's Linux collision guard is skipped entirely when systemd user-scopes are unavailable

TMX-ID: TMX-077 **Type:** Bug **Status:** Ready for testing

Found by the final whole-branch review of the wizard/password redesign (2026-07-05), confirmed pre-existing (not introduced by that plan) via direct inspection of scripts/tmx.template around the new verb's collision check. On Linux, `tmx new -s NAME` refuses to proceed when a session already occupies NAME's systemd scope — but that refusal is gated by `[ "$_scope_ok" -eq 1 ]`, and `_scope_ok` is set to 0 whenever `systemctl --version` reports below 230, `systemctl` is entirely absent, or a real `systemd-run --user --scope` probe fails (see the topology probe a few lines above the guard). On any such host, the guard is skipped outright rather than falling back to an alternate collision check (the way Darwin uses raw socket presence instead), so `tmx new -s NAME` against an already-live session of the same name could proceed further than intended before tmux's own internal

duplicate-session refusal (if any) is reached — including possibly reaching the password-collection prompt for what the operator believes is a brand-new session. Not yet reproduced end-to-end on a real scope-unavailable host (this project's dev/CI hosts all have a working systemd user session), so the exact downstream behavior (does tmux's own duplicate-session check catch it first, and if not, could a live session's persisted password state be disturbed) is UNCONFIRMED pending that reproduction. **Fix direction:** give Linux a scope-independent fallback collision check mirroring Darwin's socket-presence check (e.g. `tmux -L SOCK_LABEL has-session -t NAME` before proceeding) so the refusal does not depend on `_scope_ok` at all. **Acceptance:** a test that forces `_scope_ok=0` (or runs on a genuinely scope-less host) and asserts `tmx new -s NAME` against an already-live NAME still refuses cleanly, with no password prompt reached.

A5. ADD-HASH-CONVENTION-SPLIT-001 — `add.go` and `parser.go` compute `heading_hash` from two different conventions

TMX-ID: TMX-093 **Type:** Task **Status:** Queued

What. `computeHeadingHash(category, code, title)` is called with two different second arguments: `add.go:52` passes the ATM id (TMX-093) where `parser.go:201` passes the block code (B1). The same logical item therefore hashes differently depending on which path created its row, so an add-created row never binds to the parser's hash for its own block.

How it manifests. A row created by `add` is reached by its declared `**TMX-ID:**` rather than by heading identity, so the first sync after an operator hand-writes that item's block performs an identity rebind: the row is updated, `identity rebinds: 1` is printed, and an `item_history` row is recorded. Surfaced by independent review 2026-09-01, which walked the full lifecycle and confirmed the behaviour is bounded — exactly ONE honest rebind, after which the hash lookup hits and the sync converges to unchanged. It is a standing surprise, not a data-loss path.

Reproduction. `workable-items add -title X -category B ...`, then hand-write the matching `### B<N> X` block declaring that id into `Issues.md`, then `sync md-to-db`: observe the `identity rebinds: 1` line. A second sync reports unchanged.

Acceptance. Either normalise the two call sites onto one convention (and migrate any existing add-created rows), or document the split at `computeHeadingHash` so the rebind is expected rather than surprising — whichever the operator prefers. Live corpus is unaffected today: `sync` reports `unchanged=90` with zero rebinds.

A6. ADD-ROWS-NOT-RENDERED-001 — `db-to-md` does not render rows created by the `add` verb

TMX-ID: TMX-094 **Type:** Bug **Status:** Queued

What. `sync db-to-md` replays `document_sources` reconciled against the structured rows, so a row that has no block in the source markdown is not rendered at all. A row created by `workable-items add` is exactly that: it exists in the SSoT and is invisible in the tracker documents.

How it manifests. The item is silently absent from `Issues.md` / `Fixed.md` and from their exports, so it does not reach an operator reading the trackers even though `validate` and the DB both hold it — the §11.4.148 integrity contract (an item must carry status, type and id on ALL surfaces) is not met for these rows.

Why this is filed now. The defect is PRE-EXISTING and is referenced in TMX-076 only as historical context for why TMX-071's work was reverted; no item tracks the rendering defect itself. Confirmed untracked by `grep` over both trackers 2026-09-01 (with a control needle proving the search was not blind), and re-demonstrated by independent review the same day: an add-created row produced an empty rendered `Issues.md`. Filed so it stops being carried only inside another item's narrative (§11.4.197 — a known defect with no tracked item evaporates).

Reproduction. `workable-items add -title X ...` into a scratch DB, then `sync db-to-md --out-dir <tmp>`: the rendered `Issues.md` contains no block for X.

Acceptance. `db-to-md` emits a block for every structured row that has no corresponding source block (appended to its category section), so a round-trip after `add` is lossless; covered by a test that adds a row, renders, and asserts the block is present, with its §1.1 mutation removing the emit.

A7. ADD-CATEGORY-UNVALIDATED-001 — add accepts a category that renders a block the parser can never read

TMX-ID: TMX-095 **Type:** Bug **Status:** Ready for testing

What. `headingRE` (`parser.go`) accepts a block code of exactly ONE letter followed by digits. `AddItem` (`add.go`) accepted ANY Category string and merely uppercased it, so a category that is not a single ASCII letter produced a heading the parser can never match.

How it manifests. Measured 2026-09-01: category "AB" renders ### AB1. and "1" renders ### 11.; neither matches `headingRE`. The row lands in the SSoT and the writer emits its block, but the parser cannot see it — the item is invisible in every derived document while appearing present in the DB. This is the same invisible-block class as TMX-079..092, reached through the add seam instead of a heading-form gap.

Why this is filed. Surfaced as an honest gap by the independent stream that fixed TMX-093, which correctly declined to fix it out of scope. Filed rather than carried in that stream's narrative (§11.4.197 — a known defect with no tracked item evaporates).

Reproduction. `AddItem` with Category: "AB" into a scratch DB, render via `SyncDBToMD`, parse with `ParseFile`: no block for the allocated id is returned.

Acceptance. `AddItem` refuses any category that is not exactly one letter A-Z, with an actionable error; a §11.4.115 RED/GREEN polarity test drives `add` → `render` → `parse` end-to-end (not a tautological "returns an error"), carries a §11.4.201(7)(b) control needle proving the probe can observe a readable block, and a §1.1 mutation removing the validation makes it FAIL. Legitimate categories (A, Z, lowercase a, and empty defaulting to Z) MUST still be accepted — a guard that refuses them is a §11.4.201(1) false-positive refusal.

Closure evidence (2026-09-01). Fixed in `add.go`; guard `cmd/workable-items/add_category_validation_test.go`

(`TestAddRejectsCategoriesThatCannotRenderAReableBlock`).

RED_MODE=1 PASSED pre-fix reproducing all four malformed categories with the control needle green; RED_MODE=0 FAILED pre-fix (the RED baseline) and PASSES post-fix; RED_MODE=1 now FAILS with the honest-boundary message. §1.1 mutation removing the validation makes RED_MODE=0 FAIL; restored clean. False-positive check: A / Z / a / empty all still accepted.

B. Anti-bluff completeness across the existing test surface

(Prior B-items closed: B3 P5-M20/P5-M21 escapes CLOSED in v1.0.16 [tests 49/50 + meta-test retarget], state-verified 2026-05-29 with MUTATIONS CAUGHT 45 / ESCAPED 0, migrated to Fixed.md §B3 as TMX-054; B1 CHAL-COVER-001, B2 TEST-AUDIT-001 also in Fixed.md. New open work below.)

C. Per-session containerization features pending evidence

(none open at this time — C1 TMX-T5, C2 TMX-T7, C3 TMX-T8 landed in Fixed.md.)

D. Host-capability + topology dispatch gaps

E. Documentation / Continuation drift

(CONTINUATION.md §3 entries that resolve land in Fixed.md per Constitution §5 / §12.10. New open work below.)

F. Runtime crash — operator-gated reproduction

(none open — F1 tmx session named "HelixCode" crashes the whole terminal RESOLVED 2026-06-13, operator-confirmed, migrated to Fixed.md A45 with reproduced root cause [stale wrapper TMUX_BIN pointing at a non-existent prior-checkout path → exec of missing binary → login shell dies → terminal closes] + 4-layer regression guard [test 60 + verify gate CM-TMX-WRAPPER-TMUXBIN-VALID + meta M-WRAPPER-TMUXBIN]).

Last reviewed: 2026-06-19 (v1.0.27 WIP burn-down. §11.4.138 operator-escape A51 [name:color prompt rejection] FIXED — shell-init + SSH-dispatcher char-set now allows : and #, max-length 64→80; test 65 operator-escape guard PASS=6/6. M24/A2/D2 in parallel streams per §11.4.103.)

G. Interactive wizard + session-password redesign (2026-07-05)

New OPEN work from the 14-task wizard + session-password redesign plan (docs/superpowers/plans/2026-07-05-tmx-wizard-password-redesign.md; spec docs/superpowers/specs/2026-07-05-tmx-wizard-password-redesign-design.md). Code lands across sibling tasks of that plan; these four entries track the four user-visible requirements from the operator mandate (random-suffix create, masked password input, single-prompt reopen, existing-session picker).

Section closed 2026-09-01. All five entries have landed and now live in Fixed.md: G1/TMX-072, G2/TMX-073, G3/TMX-074, G4/TMX-075 (the four listed above) and the session-name sanitization work as §A55/TMX-078. Their blocks were duplicated here while they were also in Fixed.md; the duplicates were retired on operator decision so each item has exactly one block. The heading is kept for the historical context above — it is deliberately empty of items, not missing them.

H. Pre-existing timing issues surfaced during the 2026-08-10 no-limits-by-default cycle

Discovered while validating TMX-079 (see Fixed.md). Confirmed via §11.4.114 A/B isolation against the v1.0.38 baseline (identical failures reproduced BEFORE any of TMX-079's changes were applied) — NOT caused by TMX-079, and TMX-079's own fix + tests are unaffected. Tracked here so they are not lost.

H1 STATE-HOOK-RACE-001 — test 27 sub-check "18" (run-shell cwd-record hook) intermittently fails to observe the hook's write

TMX-ID: TMX-080 **Type:** Bug **Status:** Reopened

Reopened-Details: By: AI. On: 2026-08-13. Reason: cycle-re-discovered. Evidence: dedicated /superpowers:systematic-debugging pass (this cycle) — see below. This is a correction of the ORIGINAL diagnosis, not a new defect: the underlying failure is the same one first observed 2026-08-10, but this investigation disproves its central claim ("iteration 1 specifically, deterministically") and supersedes it with corrected, more complete evidence. Reopened per §11.4.34 rather than left as Queued because the entry's OWN content materially changed.

What (CORRECTED — the "iteration 1 specifically, deterministically" framing in the original 2026-08-10 report was WRONG): scripts/tests/27_state_persistence.sh's sub-check labelled "18" drives the wrapper's run-shell "\$STATE_BIN record \$SESS #{pane_current_path}" hook directly (the same command the wrapper installs on client-detached/session-closed) and polls tmx-state-bin recall for up to 5 s waiting for the write to land. A dedicated instrumented investigation this cycle (adding timestamped diagnostic prints around the fire/kill/poll sequence, run 8× standalone across two separate probe sessions) shows the failure is **genuinely intermittent and NOT tied to any specific iteration number** — one run failed on iteration 2, a separate run failed on iteration 3, and several runs passed cleanly 3/3. The original report's "iteration 1, deterministically, 3/3 isolation runs" was based on an insufficient sample (apparently 1-3 trials that happened to land on iteration 1 by chance) and is corrected here.

Evidence (this cycle, 2026-08-13):

- 8 fresh, timestamped standalone runs: 2 showed a genuine FAIL, landing on iteration 2 and iteration 3 respectively (never iteration 1) — FAIL 18 iter=2: ... and FAIL 18 iter=3: ..., both with poll_iterations_used=25 (the FULL 5 s poll elapsed and the state file NEVER updated to the hook's value — not merely late, genuinely never-written within the bound).
- On a failing iteration, recall immediately after run-shell fires AND immediately after kill-session returns BOTH already show the stale (pre-hook) value — the loss is not something the 5 s poll would have caught even with a longer bound.

- Root-cause CANDIDATE, partially confirmed: the wrapper's kill-session verb calls `systemctl --user stop "$SCOPE_UNIT"` immediately after `tmux kill-session`; the scope's `KillMode=control-group` (confirmed via `systemctl --user show`) SIGTERMs EVERY process in the cgroup, including an in-flight run-shell-spawned async child (confirmed via direct process-tree observation: the child DOES land in the SERVER's own scope, in both shared AND split topology, never the workload slice). A direct reproduction with an artificially-slowed hook command (`sleep 0.05; tmx-state-bin record ...`) reliably loses the write when immediately followed by `systemctl stop`, and reliably SUCCEEDS when `systemctl stop` is skipped entirely — confirming this mechanism is real and NOT a test artifact (a real operator running `tmx kill-session -t NAME` is exposed to the identical race).
- **However, a first fix attempt (delaying `systemctl stop` until the scope's cgroup is observed empty, via a new `_wait_scope_quiescent` helper in `scripts/tmx.template` + an analogous change in `scripts/tmx-recycler.sh`) did NOT resolve the test's actual failure — it made it WORSE (5/5 reproducible failures, always landing on iteration 1, up from the original ~20-25% intermittent rate).** A corrected version of the same fix (resolving the cgroup path ONCE rather than re-querying `systemctl show` on every poll iteration, which itself has a race — `ControlGroup` reports empty almost immediately once the tracked main PID exits, before a still-running child has necessarily finished) ALSO failed to resolve the real test, despite BOTH fix attempts working correctly in isolated, simplified manual reproductions. Per the Iron Law (3+ fix attempts / worsening symptom → question the diagnosis, don't keep patching), **both fix attempts were reverted; `scripts/tmx.template` and `scripts/tmx-recycler.sh` are unchanged from before this cycle.**
- **A second, deeper anomaly surfaced and is NOT yet explained:** in the same instrumented investigation, `tmux display-message -t "$SESS" -p '#{pane_current_path}'` (what the test's own CD-landing poll checks, lines ~162-169) was observed to show STALE data (the Phase-1 target directory, never the freshly-cd'd hook target) in EVERY iteration of EVERY run tested — meaning that poll's OWN 5 s wait never actually succeeds and is effectively a no-op today — while a SEPARATE, immediately-following bare `(-t-less) run-shell "echo '#{pane_current_path}' > file"` diagnostic showed the CORRECT, freshly-cd'd value in some iterations and the SAME stale value in others, with no pattern yet identified tying this to the kill-timing race above. This suggests `#{pane_current_path}` may resolve differently (possibly via different tmux-internal code paths, or genuinely different cached/live state) depending on how it is

queried, which the kill-session-timing hypothesis does NOT explain and needs its own investigation — most likely requiring direct study of tmux's own `#{pane_current_path}` resolution logic (not yet done; this cycle's investigation treated tmux as a black box via empirical probing only).

Fix direction (still not fully root-caused; genuinely more complex than originally scoped): at minimum TWO distinct phenomena are in play — (1) the `KillMode=control-group` race against an in-flight run-shell child (mechanism confirmed, but the attempted fix did not resolve the real test, meaning either the fix itself has a remaining bug, or this is not actually the dominant cause of the REAL test's failures despite being real and reproducible in isolation), and (2) an unexplained discrepancy between display-message's and a bare run-shell's view of `#{pane_current_path}` for the same pane at nearly the same moment — **source-confirmed mechanism found for (2) this cycle: tmux/osdep-linux.c's `osdep_get_cwd/osdep_get_name` resolve via `tcgetpgrp(fd)` (the PTY's CURRENT foreground process group at query time), not the shell's own tracked PID; if the pane's shell (oh-my-bash, per this operator's `.bashrc`) spawns prompt-render subprocesses that transiently become the foreground process group, different queries issued moments apart can read different processes' cwd.** Needs a fresh, dedicated systematic-debugging pass to CONFIRM this mechanism against a live failure (not yet done — see below) with either (a) a subagent given a clean context and unlimited focus on this single question, or (b) an experiment disabling oh-my-bash for test-created sessions to see if the divergence disappears. Out of scope to force a fix this cycle given the Iron Law guidance against continuing to patch a worsening symptom.

Cross-reference: TMX-081 (Issues.md §H2) is hypothesised to share this SAME root-cause mechanism (oh-my-bash prompt-render subprocess activity racing tmux's `tcgetpgrp`-based pane-state resolution), manifesting there as a CPU-throttle settle-window timeout rather than a stale-path read. See §H2 for the shared-cause hypothesis and the recommended confirming experiment.

H2 SPLIT-QUIET-SETTLE-001 — test 87 G4 ("quiet-phase control") occasionally fails to observe a zero-throttle settle window

TMX-ID: TMX-081 **Type:** Bug **Status:** Queued

What: scripts/tests/87_server_scope_split.sh G4 waits for a 1 s idle window with `nr_throttled delta 0` on BOTH the server scope and the workload slice (settling past shell-startup noise) before G5 measures throttling under deliberate load. G4 fails ("quiet-phase never settled") with a small non-zero delta on the workload slice.

Evidence: reproduced identically on both the TMX-079-fixed tree and the v1.0.38 baseline (`git stash A/B`, 3× each, 2026-08-10) — FAIL: G4: quiet-phase never settled (never-settled: .../tmxw-t87_<pid>.slice:delta=10). The isolation invariant G4 exists to set up for (G5: the server scope is NEVER co-throttled while the slice is) PASSES consistently regardless, so the feature under test is proven sound — this is a control-window settle heuristic being slightly too strict/short, not a defect in the isolation mechanism itself.

Discovery note (this is the FIRST time it is tracked as its own item, hence Queued not Reopened per §11.4.34 — the latter presupposes a prior closure, and this defect was never previously closed): discovered by AI, 2026-08-10, during TMX-079 validation.

Fix direction (not yet investigated to root cause): needs either a longer settle window or a higher delta tolerance for the workload slice specifically (shell/pane-shim startup on a freshly-joined slice may legitimately cost a few throttled periods even at rest) — which of the two (or another cause entirely) is UNCONFIRMED without the actual `cpu.stat` samples across the settle window; needs a dedicated systematic-debugging pass (§11.4.102) before deciding — out of scope for TMX-079.

2026-08-13 investigation update (dedicated /superpowers:systematic-debugging pass — non-reproduction + a new, evidence-backed root-cause CANDIDATE, not a fix):

- **Could NOT reproduce today: 24/24 standalone runs of test 87 (4 individual + a 20-run background batch, with per-try `nr_throttled deltas` instrumented) all show G4 settling cleanly, typically on the FIRST 1 s window.** Per §11.4.7 (demotion requires evidence under the SAME conditions that originally exposed the defect), this does NOT close or downgrade TMX-081 — today's host conditions (this session has spun up and torn down a very large number of tmux sessions already, plausibly warming filesystem/package caches oh-my-bash's own startup checks read from) evidently differ from 2026-08-10's, and the defect is expected to still be real and reproducible under the original conditions (or under genuine host load / a cold shell-framework cache).

- **New root-cause CANDIDATE, source-confirmed (shared with TMX-080 — see H1's 2026-08-13 update):** `tmux's #{pane_current_path}/#{pane_current_command} (osdep_get_cwd/osdep_get_name in tmux/osdep-linux.c) resolve via tcgetpgrp(fd) — the PTY's CURRENT FOREGROUND PROCESS GROUP at query time — not the shell's own tracked PID. If the pane's shell (this project's own .bashrc, confirmed to source oh-my-bash, is the operator's $SHELL used for USER_SHELL in scripts/tmux.template) spawns subprocesses as part of rendering its prompt (version-control status checks, check_for_upgrade, etc. — already independently documented as slow/complex by this project's own v1.0.41 test-58 fix), those subprocesses transiently BECOME the foreground process group and consume REAL CPU time while doing so. Under G4's tight, quota-constrained cgroup (server+slice split to 50%/50% of an already-small TMX_CPU test budget), that subprocess activity can itself be CFS-throttled, extending well past the test's $12 \times 1 \text{ s} = 12 \text{ s}$ settle bound if it runs long enough or is delayed enough by the quota.`
- **This is a genuine CANDIDATE, not yet directly witnessed causing a G4 failure** — today's non-reproduction means the mechanism could not be confirmed live against an actual `nr_throttled-non-zero` window this cycle. It is offered as the most evidence-backed lead for whoever continues this investigation, not as a closure.

Cross-reference: TMX-080 (Issues.md §H1) is hypothesised to share the SAME underlying mechanism (`oh-my-bash` prompt-render subprocess activity racing `tmux's tcgetpgrp`-based pane-state resolution) manifesting as a DIFFERENT symptom — a stale/wrong `#{pane_current_path}` read there, vs. a settle-window timeout here. Confirming or refuting this shared-cause hypothesis (e.g., by testing whether disabling `oh-my-bash` for test-created sessions makes BOTH TMX-080 and TMX-081 stop reproducing) is the recommended next step for either investigation.

Fix direction (still not attempted — no live reproduction to validate a fix against this cycle): if the shared-cause hypothesis holds, candidate fixes include (a) a settle heuristic that specifically recognises `oh-my-bash` startup activity and excludes it from the "must be zero" requirement (e.g., waiting for `#{pane_current_command}` to stably show the shell itself, not a transient subprocess, before starting the settle-count), or (b) scoping test-created sessions to a minimal, non-framework shell so tests are not coupled to the operator's own interactive shell configuration. Needs a fresh reproduction (possibly requiring genuine host load, a cold `oh-my-bash` cache, or an artificially-

injected slow prompt hook) before any fix can be validated per the project's own TDD-RED-first discipline (§11.4.43/§11.4.115) — forcing a fix without a live failing case to prove it against would itself be a bluff.

I. Live copy-mode wheel binding (2026-09-01)

Surfaced during the v1.0.44 verification work. Tracked here because it is a real, currently-failing check that was not previously recorded anywhere — leaving it only in a test log would be a §11.4.238 coverage escape at the tracking layer.

A99. set_status.go strands block identity onto an occupied Issues triple on reopen — OPEN

TMX-ID: TMX-099 **Type:** Bug **Status:** Queued **Severity:** MEDIUM

set_status.go carries the identical defect close.go had before TMX-099: it mutates only Status and CurrentLocation (it.CurrentLocation = LocationIssues) with NO check that the destination (Issues, category, code_ordinal) triple is free. A reopen can therefore strand an item onto a block another item already holds — the mirror image of the close-side collision fixed this cycle. Measured basis: block codes are category-local and NOT unique across the two trackers (9 of 10 codes present in both files), and 8 of 10 open items would collide on close before the close.go guard landed. Repro: reopen an item whose Issues-side triple is already held. Fix direction: apply the same checkDestinationBlockIdentityFree fail-closed guard, with the same three false-positive guards (ordinal<=0 sentinel, Obsolete supersession, self-exclusion). Acceptance: a RED test reproducing the reverse collision, flipped GREEN by the guard, plus a paired 1.1 mutation.

A100. Identity audit cannot locate the block for 57 of 95 items — OPEN

TMX-ID: TMX-100 **Type:** Task **Status:** Queued **Severity:** MEDIUM

workable-items validate reports: 57 item(s) skipped by the identity audit — their block could not be located. These are rows whose stored (location, category, code_ordinal) names a block the parser cannot find in the file that location names. This is a DISTINCT defect from the close-side collision guard (TMX-099) and is NOT closed by it; it is also distinct from TMX-050 (Obsolete rows are skipped BEFORE the unlocated

counter increments, so TMX-050 is not among the 57). Two contributing causes are already measured: 58 blocks carry no **TMX-ID:** line for the audit to join on, and any block migrated by hand leaves the DB pointer behind. Fix direction: backfill the missing TMX-ID lines, then add an audit fallback keying tier so a block is locatable by (category, ordinal) when the id line is absent. Acceptance: the skipped count falls to zero or every residual is enumerated as an honest, justified gap.

A101. §11.4.44 revision headers absent from Issues.md, Fixed.md and CONTINUATION.md — OPEN

TMX-ID: TMX-101 **Type:** Task **Status:** Queued **Severity:** MEDIUM

Measured 2026-09-02: §11.4.44 names Issues.md, Fixed.md and CONTINUATION.md as in-scope and requires BOTH **Revision:** N and **Last modified:** ISO-8601-UTC directly below the H1. Issues.md carries neither field (Revision=0, LastMod=0); Fixed.md carries neither (0/0); CONTINUATION.md carries Last updated but no Revision (0/1). Control needle: docs/workable-items/Status.md carries Revision=1, so the detecting grep is not blind. Repo-wide 60 of 86 tracked .md carry the field, so 26 do not. PRE-EXISTING, not introduced by the v1.0.45 tracker-integrity batch. Repro: for f in Issues.md Fixed.md CONTINUATION.md; do grep -c '^..Revision:..' \$f; done. Acceptance: all three carry both mandatory fields, the doc_revision_bump helper covers them, and a gate FAILs when a field is stripped (paired §1.1 mutation).

A102. Issues_Summary.md and Fixed_Summary.md do not exist anywhere in the repository — OPEN

TMX-ID: TMX-102 **Type:** Task **Status:** Queued **Severity:** MEDIUM

Measured 2026-09-02: §11.4.12 mandates Issues_Summary.md and §11.4.53 mandates Fixed_Summary.md, each always in sync with its source tracker and exported to HTML and PDF. Neither file is tracked anywhere: git ls-files | grep -iE 'Issues_Summary|Fixed_Summary' returns empty, while the same search finds Issues.md and Fixed.md (control needle, so the search is not blind). scripts/tests/51_workable_items_db_integrity.sh references the summary names, so tooling already assumes them. PRE-EXISTING, not introduced by the v1.0.45 batch. Acceptance: both summaries generated from the workable-items DB with ATM/TMX-ID, Status, Type and Reopens

columns per §11.4.19/§11.4.54/§11.4.55, exported per §11.4.65, reachable from README per §11.4.212, and a gate FAILs when a summary is stale or absent.

A103. sync db-to-md writes the git-tracked SSoT DB on every run, including read-only verification round-trips — OPEN

TMX-ID: TMX-103 **Type:** Bug **Status:** Queued **Severity:** MEDIUM

Measured 2026-09-02 by an independent review: 'workable-items sync db-to-md' rewrites meta.last_sync_direction and meta.last_sync_timestamp (cmd/workable-items/sync_db_to_md.go:131-134) on EVERY invocation, including a pure verification round-trip that renders into a throwaway --out-dir and touches no tracker. Consequence: the documented byte-identity verification procedure DIRTIES the git-tracked SSoT docs/workable_items.db, so any reviewer or CI pass that verifies the round-trip leaves the tree modified and cannot restore it byte-exactly (the prior stamp bytes are unrecoverable; inventing them would fabricate state). This is an observer-effect defect per 11.4.128(1) and a no-commit-during-verification hazard per 11.4.121. PRE-EXISTING: the stamp write is present at HEAD:cmd/workable-items/sync_db_to_md.go, but the v1.0.45 batch newly enshrines the round-trip as the documented verification mechanism without tracking the side effect. Scope proof: successive db-to-md runs on copies differ ONLY in those two meta rows (full logical table dump); validate is byte-neutral. Repro: cp docs/workable_items.db /tmp/a.db; sync db-to-md --db /tmp/a.db --out-dir /tmp/o1; sha256sum /tmp/a.db; repeat; hashes differ. Acceptance: a read-only verification mode that renders without writing the DB, or the stamp moved out of the tracked artifact, proven by a test asserting the DB sha256 is unchanged across a verification round-trip, plus a paired 1.1 mutation.