

# Issues

## vasic-digital tmux — Open Issues Tracker

**Canonical source of truth for everything currently unfinished, partially validated, or at risk of violating the anti-bluff covenant (Constitution.md §1 + §11.4.1 through §11.4.6).**

Every PASS in this codebase MUST carry positive evidence captured live that the feature works for the end user. Metadata-only PASS, configuration-only PASS, "absence-of-error" PASS, and grep-based PASS without runtime evidence are all critical defects regardless of how green the summary line looks. **Tests AND HelixQA Challenges are bound equally.**

Forensic anchor — direct user mandate (verbatim, 2026-04-28 + 2026-05-07 + 2026-05-08, repeatedly reasserted from upstream vasic-digital projects):

"We had been in position that all tests do execute with success and all Challenges as well, but in reality the most of the features does not work and can't be used! This MUST NOT be the case and execution of tests and Challenges MUST guarantee the quality, the completion and full usability by end users of the product!"

§11.4.6 forensic anchor (verbatim, 2026-05-08):

"'LIKELY' is guessing, we MUST NOT have guessing, since it can be or may not be! No bluffing and uncertainty is allowed at any cost! We MUST always know exactly precisely what is happening exactly, in any context, under any conditions, everywhere!"

**Compiled:** 2026-05-08 (Phase B per-session-containerization cycle). **Author:** Engineering coordinator **Working pool source:** the items below feed the active task list directly. Each item carries a current state, the captured-evidence requirement, and a fix-direction proposal so future-self can resume cold.

**Migration policy** (mirrors upstream vasic-digital projects): resolved items are moved to **Fixed.md** in the same commit that closes them. **Issues.md holds OPEN / PARTIAL / BLOCKED / RUNNING / INVESTIGATED only**; once an item is closed and verified end-to-end, it migrates to Fixed.md and disappears from here. Never delete items outright — history matters for cold-start handover.

## Document conventions

| Code         | Meaning                                                                                                     |
|--------------|-------------------------------------------------------------------------------------------------------------|
| OPEN         | Unfinished work; needs implementation + anti-bluff coverage                                                 |
| PARTIAL      | Implementation exists but coverage gaps remain (positive evidence missing or environmental SKIP unresolved) |
| BLOCKED      | Cannot progress without external dependency (host capability, third-party tool, distro support, etc.)       |
| RUNNING      | In-flight in this session (background process, ongoing test cycle)                                          |
| INVESTIGATED | Forensic investigation produced findings; closure pending decision on fix scope                             |

### Status reclassification rules (§11.4.6 enforced):

- A PARTIAL may not move to closed without runtime evidence (/ sys/fs/cgroup/.../memory.max readback, systemctl status showing scope active, kill -9 survivor proof — never just script exit code).
- A BLOCKED reclassifies to OPEN when the blocking dependency resolves; it must NOT skip directly to closed.
- An INVESTIGATED item must record the captured forensic trace (file path / command output / log timestamp) — never speculation ("likely" / "probably" / "appears to" — see Constitution §11.4.6).

### Categories:

- **A** — Tooling / harness gaps
- **B** — Anti-bluff completeness across the existing test surface
- **C** — Per-session containerization features pending evidence

- **D** — Host-capability + topology dispatch gaps
  - **E** — Documentation / Continuation drift
- 

## A. Tooling / harness gaps

### A2 RUNALL-NATIVE-RESOLVE-001 — standalone run\_all.sh mis-resolves the binary on native macOS

**Status:** Fixed (→ Fixed.md) **Type:** Task

CLOSED v1.0.27. scripts/tests/run\_all.sh hardcodes TMUX\_BIN=tmux/build/bin/tmux (the build\_containerized.sh output path) and is the containerized-build validator. On native macOS the authoritative validator is setup.sh (builds + verifies against tmux/build-darwin/). Invoked standalone on macOS with a stale tmux/build/ present (a prior Linux containerized build), run\_all.sh resolved the wrong-arch binary → Exec format error mass-FAIL (observed 2026-06-16; NOT a product defect — setup.sh run\_all 55/0/6 + installed-binary smoke GREEN the same session; removing the stale tmux/build/ then gave not executable because run\_all expects that path). **Fix direction:** make run\_all.sh OS-aware (prefer tmux/build-darwin/ on Darwin) OR document that native-macOS validation is setup.sh-only and run\_all.sh is the containerized path. Captured-evidence requirement: a clean native-macOS run\_all GREEN after the fix.

---

## B. Anti-bluff completeness across the existing test surface

(Prior B-items closed: B3 P5-M20/P5-M21 escapes CLOSED in v1.0.16 [tests 49/50 + meta-test retarget], state-verified 2026-05-29 with MUTATIONS CAUGHT 45 / ESCAPED 0, migrated to Fixed.md §B3 as TMX-054; B1 CHAL-COVER-001, B2 TEST-AUDIT-001 also in Fixed.md. New open work below.)

---

## C. Per-session containerization features pending evidence

(none open at this time — C1 TMX-T5, C2 TMX-T7, C3 TMX-T8 landed in Fixed.md.)

---

## D. Host-capability + topology dispatch gaps

### D2 TMPDIR-HARDCODE-001 — tests hardcoding / tmp false-FAIL under host disk-pressure

**Status:** Fixed (→ Fixed.md) **Type:** Task

CLOSED v1.0.27. Several tests create scratch under a hardcoded /tmp (e.g. 27\_state\_persistence.sh target tmx-test-18-target-\*). When the host root volume is full (observed 2026-06-16 on macOS, / at <200 MiB during the operator's away-window), the cd/mkdir into /tmp fails → pane\_current\_path='' false-FAIL instead of an honest §11.4.3 SKIP-with-reason. The tests pass normally + standalone (27 3/3, 38 3/3, 43 15/0 re-run the same session) — the failure is purely the abnormal host-disk condition (a §11.4.1 FAIL-bluff class: environment, not product). **Fix direction:** route test scratch through \$TMPDIR (operator now sets /Volumes/T7/tmp via ~/.zshrc + ~/.bashrc) OR guard each test on /tmp writability and SKIP-with-reason (§11.4.3/§11.4.50). Captured-evidence requirement: an induced-disk-full run shows SKIP-with-reason, not FAIL.

---

## E. Documentation / Continuation drift

(CONTINUATION.md §3 entries that resolve land in Fixed.md per Constitution §5 / §12.10. New open work below.)

---

## F. Runtime crash — operator-gated reproduction

(none open — F1 tmx session named "HelixCode" crashes the whole terminal RESOLVED 2026-06-13, operator-confirmed, migrated to Fixed.md A45 with reproduced root cause [stale wrapper TMUX\_BIN pointing at a non-existent prior-checkout path → exec of missing binary → login shell dies → terminal closes] + 4-layer regression guard [test 60 + verify gate CM-TMX-WRAPPER-TMUXBIN-VALID + meta M-WRAPPER-TMUXBIN]).

---

**Last reviewed:** 2026-06-19 (v1.0.27 WIP burn-down. §11.4.138 operator-escape A51 [name:color prompt rejection] FIXED — shell-init + SSH-dispatcher char-set now allows : and #, max-length 64→80; test 65 operator-escape guard PASS=6/6. M24/A2/D2 in parallel streams per §11.4.103.)

---

## **M24-ESCAPE-001 — meta-test M24 (hostname 4-surface color) escapes: test 26 misses a 3-set-line removal**

**Status:** Fixed (→ Fixed.md) **Type:** Bug **Severity:** Minor (test-coverage gap, no user-facing break — closed v1.0.27: count=1 removed from M24 regex → strips from BOTH `_apply_color` and `_apply_host_color`, test 26 now FAILs on the mutation → CAUGHT) **Closure:** meta-test 37 CAUGHT / 0 ESCAPED (was 34 CAUGHT / 3 ESCAPED pre-fix)

**What:** The §1.1 paired-mutation M24 in `scripts/tests/meta_test_false_positive_proof.sh` removes three of the four `tmux set -g ...` lines in `_apply_host_color()` and expects test 26 to FAIL. The harness reports `MUTATION ESCAPED` — test 26 does not FAIL, because it asserts only a subset of the four surfaces, so removing the un-asserted set-lines leaves the test green.

**Evidence:** `bash scripts/tests/meta_test_false_positive_proof.sh 2>&1 | grep M24` → FAIL: M24: MUTATION ESCAPED — test 26 did not FAIL with the three set-lines removed. Confirmed pre-existing (M24 added in commit f151d13, v1.0.9 — before the per-session-color feature). Surfaced 2026-06-19 during the per-session-color M25/M26 verification run.

**Fix direction:** strengthen test 26 to assert ALL FOUR surfaces (`status-style`, `pane-active-border-style`, `clock-mode-colour`, `window-status-current-style`) so the M24 mutation (removing any 3) reliably FAILs it — mirroring the all-4-surfaces assertion already proven in test 63 T3 for the per-session path. (This also closes the symmetry gap: the per-session path has a 4-surface guard; the `hostname` path should too.)

**Out of scope:** the per-session-color feature (TMX-051). Tracked separately so the color release is not blocked by an unrelated pre-existing test-gap.

---

## **G. Interactive wizard + session-password redesign (2026-07-05)**

New OPEN work from the 14-task wizard + session-password redesign plan (docs/superpowers/plans/2026-07-05-tmx-wizard-password-redesign.md; spec docs/superpowers/specs/2026-07-05-tmx-wizard-password-redesign-design.md). Code lands across sibling tasks of that plan; these four entries track the four user-visible requirements from the operator mandate (random-suffix create, masked password input, single-prompt reopen, existing-session picker).

### **G1 WIZARD-SUFFIX-001 — wizard-created sessions get a random 4-digit name suffix**

**TMX-ID:** TMX-072 **Type:** Feature **Status:** Queued

Typing a session name at the interactive tmx wizard now always creates a brand-new session whose real name is the typed name plus a random 4-digit suffix (e.g. my-session-2507), so retyping the same base name later can never collide with or be confused for an earlier session. This makes every session created through the wizard genuinely unique by construction, while scripts and tests that need a deterministic exact name can set `TMX_EXACT_NAME=1` to opt out. Implemented in scripts/tmx-shell-init.sh.template. Acceptance: test 78 passes, showing the created session name matches base-NNNN and that `TMX_EXACT_NAME=1` suppresses it.

### **G2 PASSWORD-MASK-001 — password input is masked with asterisks while typing**

**TMX-ID:** TMX-073 **Type:** Feature **Status:** Queued

Session passwords are no longer echoed in plaintext to the terminal while being typed. Every password prompt in the tmx wrapper now shows a single asterisk character for each keystroke, with backspace erasing one asterisk, so a password can never be read off the screen by someone glancing at it. Implemented via the shared `_read_password_masked` helper in scripts/tmx.template. Acceptance: test 77 passes, proving the pane buffer never contains the typed plaintext.

### **G3 DOUBLE-PROMPT-001 — reopening a password-protected session no longer asks for the password twice**

**TMX-ID:** TMX-074 **Type:** Bug **Status:** Queued

Reopening a session that had been idle-recycled (its tmux process torn down for inactivity, but its password remembered) used to show a confusing second prompt that looked like it might be resetting the password, even though typing the same password both times always worked. The root cause was the attach command checking the remembered password before checking whether the session was actually still running, so a doomed attach attempt fell through to the create flow, which unconditionally asked to set a password again. Opening an already-protected session (live or recycled) now verifies the password exactly once; only a genuinely brand-new session name asks for a password and a confirmation. Fixed in scripts/tmx.template's attach and new command handling. Acceptance: test 81 reproduces the exact reported scenario end-to-end and proves exactly one prompt appears, with the stored password unchanged afterward.

## **G4 WIZARD-PICKER-001 — wizard offers a picker of existing sessions when no new name is typed**

**TMX-ID:** TMX-075 **Type:** Feature **Status:** Queued

Previously, pressing Enter without typing a session name at the interactive tmx wizard always dropped the operator into a plain shell with no other option. Now, if any sessions already exist, the operator sees a numbered list of them plus a 'None' option, and can pick a number to join that session directly (still prompted for its password exactly once if it is protected) instead of having to remember and retype its exact name. Choosing None, or pressing Enter again, behaves exactly as before (a plain shell). Implemented in scripts/tmx-shell-init.sh.template. Acceptance: test 79 passes, covering picking a plain session, picking a password-protected one, and choosing None.