

vasic-digital tmux — v1.0.19 Release Notes

Revision: 1 **Last modified:** 2026-05-29T13:40:00Z **Version:** 1.0.19 / versionCode 20 **Released:** 2026-05-29 **Hosts validated:** Mistborn (Darwin arm64) + nezha (ALT Linux 6.12 x86_64)

Summary

A test-harness + verification robustness fix surfaced while bringing both supported hosts to the latest codebase and running a full test/verify: the CodeGraph CLI now resolves for `run_all.sh` and the meta-test even in **non-interactive** shells, so the dual-host full suite is deterministically green on Linux as well as macOS.

No product/runtime behaviour changes in this release — the v1.0.18 mouse select+copy and double-prompt fixes are unchanged and remain GREEN on both hosts.

Fixed — CodeGraph PATH in non-interactive shells (run_all + meta-test)

Symptom. The standalone full suite on nezha failed `20_codegraph_installed.sh` and `22_codegraph_mcp_wired.sh` with "codegraph CLI not on PATH" / "bare 'codegraph' does not resolve on PATH", even though:

- `@colbymchenry/codegraph@0.9.7` is installed via npm global (`~/ .npm-global/bin/codegraph`);
- every MCP config (`.mcp.json`, OpenCode, Kimi, Crush, Qwen) is correctly wired (those sub-assertions all PASS);
- in an **interactive** login shell (the real agent context) codegraph resolves and the tests PASS.

Root cause. nezha's `~/ .bashrc` begins with the standard interactive-guard `case $- in *i*) ;; *) return ;; esac` and only adds `~/ .npm-global/bin` to PATH on line 32 — *after* the guard. A non-interactive shell (ssh-batch / CI) returns before reaching it, so codegraph is invisible. `setup.sh` already worked around this with a top-of-script npm-prefix PATH probe (the A31 nezha fix, 2026-05-21) — which is why the setup verify gate was green — but the standalone `run_all.sh` and the meta-test lacked the same probe.

Fix. Generalised the A31 probe to `scripts/tests/run_all.sh` and `scripts/tests/meta_test_false_positive_proof.sh`:

```
if ! command -v codegraph >/dev/null 2>&1 && command -v npm >/dev/null 2>&1; then
  NPM_PREFIX="$(npm config get prefix 2>/dev/null | tr -d '\r\n' || true)"
  if [ -n "$NPM_PREFIX" ] && [ -x "${NPM_PREFIX}/bin/codegraph" ]; then
    export PATH="${NPM_PREFIX}/bin:$PATH"
  fi
fi
```

Idempotent (no-op when codegraph is already on PATH, e.g. on macOS via Homebrew or in interactive shells). After the fix the codegraph tests pass and the M22 CodeGraph mutation runs **CAUGHT** rather than honest-SKIP on nezha — the nezha meta-test rose from 46 → 48 mutations caught.

Dual-host validation (latest HEAD)

Host	run_all	meta-test	M22	setup gate
Mistborn (Darwin arm64)	PASS=51 FAIL=0 SKIP=4	48 CAUGHT / 0 ESCAPED	CAUGHT + intact	GREEN
nezha (ALT Linux x86_64)	PASS=43 FAIL=0 SKIP=12	48 CAUGHT / 0 ESCAPED	CAUGHT + intact	GREEN

Both hosts on the identical latest commit; remote main parity on GitHub + GitLab. CodeGraph 0.9.7 codegraph_validate PASS on both.

Files changed

- scripts/tests/run_all.sh — A31 npm-prefix PATH probe.
- scripts/tests/meta_test_false_positive_proof.sh — A31 npm-prefix PATH probe.
- VERSION, CHANGELOG.md, CONTINUATION.md (§3.19).

Sources verified 2026-05-29

- npm CLI — npm config get prefix / global bin layout (<prefix>/bin/<cmd> symlink to the package). Behaviour confirmed live on nezha (/home/milosvasic/.npm-global/bin/codegraph → package npm-shim).
- bash manual — non-interactive shells skip the interactive-guarded body of .bashrc; consistent with the observed case \$- in *i*) ;; *) return pattern on nezha.