

tmux documentation

uninstall.sh

Revision: 1 **Last modified:** 2026-05-22T15:15:00Z **Authority:** vasic-digital tmux project
Maintainer: milosvasic **Scope:** v1.0.11 operator-facing uninstall entry point per §11.4.18

Purpose

Operator-facing thin wrapper that delegates to `scripts/setup.sh --uninstall`. Single source of truth for what "uninstall" means lives in `setup.sh`'s `_do_uninstall` function; `uninstall.sh` only exists so operators have a discoverable verb (`bash scripts/uninstall.sh`) that mirrors `bash scripts/setup.sh`.

Usage

```
# Standard uninstall — preserves operator data under ~/.tmx/  
bash scripts/uninstall.sh  
  
# Also remove per-session last-pwd state in ~/.tmx/  
bash scripts/uninstall.sh --purge-state
```

Inputs

Source	Meaning
<code>--purge-state</code> flag	When set, also remove <code>~/.tmx/</code> (per-session last-pwd state). Default: preserve.
<code>--help</code> / <code>-h</code>	Show this guide's header.
<code>PURGE_STATE=1</code> env var	Same effect as <code>--purge-state</code> (used by tests).

Outputs

Side-effecting only. No stdout JSON / structured output. Per-step progress lines printed to stderr by the underlying `_do_uninstall` function.

What is removed

Artefact	Removed?	Why
— vasic-digital optimized tmux — fenced block in <code>~/.bashrc</code> + <code>~/.zshrc</code>	YES	Generated by <code>setup.sh</code> ; nothing else should reference it.
	YES	Pre-v1.0.9 hand-pasted snippets that would otherwise double-trigger.

Artefact	Removed?	Why
Legacy pre-v1.0.9 unfenced if command -v tmx ...; then ...; fi snippet ~/.tmux.conf (only if it contains vasic-digital optimized tmux configuration)	YES	Setup.sh generated; operator's pre-existing file preserved via backup ~/.tmux.conf.pre-vasic-digital.
scripts/tmx (wrapper)	YES	Generated from scripts/tmx.template at install time.
scripts/tmx-shell-init.sh (shell init — v1.0.9+)	YES	Generated from scripts/tmx-shell-init.sh.template at install time.
scripts/tmx-state-bin (Go binary — v1.0.9+)	YES	Built from scripts/tmx-state/ Go source at install time.
~/.tmx/state.json (per-session last-pwd)	NO (unless --purge-state)	§9 zero-risk-data-safety — operator data.
tmux/build*/ (compiled tmux binary)	NO	Rebuild costs minutes; manual rm -rf tmux/build* if desired.

Side-effects

- Touches the operator's ~/.bashrc, ~/.zshrc, ~/.tmux.conf (only to remove our content).
- Removes generated files inside the project's scripts/ directory.

Dependencies

- scripts/setup.sh (the underlying implementation).
- perl and python3 (used by _strip_bashrc_snippet).

Cross-references

- [docs/guides/tmx-shell-integration.md](#) §uninstall
- [docs/scripts/tmx-shell-init.md](#)
- [docs/scripts/tmx-state.md](#)
- Tests: scripts/tests/42_setup_install_uninstall_e2e.sh

§11.4 anti-bluff

Uninstall is verified by test 42's Phase B (3 iterations, identical hash). Removing the rc snippet, the init.sh file, the wrapper, AND asserting they are all gone is captured-evidence per §11.4.5.

Last verified

2026-05-22 (test 42 PASSes on macOS + nezha-Linux).