CUSTOMER JOURNEY MAP

Script-Controlled ACL – Restrict Record Access Based on Custom Script

Team ID: SWTID-2026-5170 | **Date:** 02 October 2026

Scenario: A user works with confidential records in ServiceNow. Script-controlled ACLs decide at each step whether the user may read, create, edit or delete the record.

	1. Log in	2. Open record list	3. View a record (READ)	4. Create record (CREATE)	5. Edit record (WRITE)	6. Delete record (DELETE)
Steps	User signs in to the instance.	User opens the Confidential Record list.	User opens a record from the list.	User clicks New and submits the form.	User changes field values and saves.	User deletes a record.
Interactions	ServiceNow login, session	List view, ACL (read)	Form view, ACL (read)	New form, ACL (create)	Form, ACL (write)	Delete UI action, ACL (delete)
Goals and motivations	"Get in securely."	"Show me only what I may see."	"Let me open my records."	"Let me add new records."	"Let me update my own data."	"Keep data safe from accidental deletion."
Positive moments	Roles load with the session.	List shows only permitted records.	Owner sees own confidential record.	Authorised users create quickly.	Owner edits freely until closed.	Only admin can remove records.
Negative moments	Missing role means no access.	Records may be unexpectedly hidden.	Access denied message for others.	No-role users cannot create.	Closed records are read-only.	Owners cannot delete.
Areas of opportunity	Show assigned roles to users.	Explain why a record is hidden.	Add audit logging of denials.	Add field guidance.	Add approval for closed records.	Add soft-delete / archive.